

# MC10H607, MC100H607

## Registered Hex PECL to TTL Translator

The MC10H/100H607 is a 6-bit, registered PECL to TTL translator. The device features differential PECL inputs for both data and clock. The TTL outputs feature 48mA sink, 24mA source drive capability for driving high fanout loads or transmission lines. The asynchronous master reset control is an ECL level input.

With its differential PECL inputs and TTL outputs the H607 device is ideally suited for the receive function of a HPPI bus type board-to-board interface application. The on chip registers simplify the task of synchronizing the data between the two boards.


The device is available in either ECL standard: the 10H device is compatible with MECL 10H™ logic levels, with a  $V_{CC}$  of +5.0 volts, while the 100H device is compatible with 100K logic levels, with a  $V_{CC}$  of +5.0 volts.

- Differential ECL Data and Clock Inputs
- 48mA Sink, 24mA Source TTL Outputs
- Single Power Supply
- Multiple Power and Ground Pins to Minimize Noise




**ON Semiconductor**

<http://onsemi.com>



**PLCC-28  
FN SUFFIX  
CASE 776**

### MARKING DIAGRAM




A = Assembly Location  
WL = Wafer Lot  
YY = Year  
WW = Work Week

### ORDERING INFORMATION


Device	Package	Shipping
MC10H607FN	PLCC-28	37 Units/Rail
MC100H607FN	PLCC-28	37 Units/Rail

# MC10H607, MC100H607

## LOGIC DIAGRAM



## Pinout: 28-Lead PLCC (Top View)



## PIN NAMES

Pin	Function
$D_0 - D_5$	True PECL Data Inputs
$\overline{D}_0 - \overline{D}_5$	Inverted PECL Data Inputs
$CLK, \overline{CLK}$	Differential PECL Clock Input
$MR$	PECL Master Reset Input
$Q_0 - Q_5$	TTL Outputs
$V_{CCE}$	PECL $V_{CC}$
$V_{CCT}$	TTL $V_{CC}$
$TGND$	TTL Ground
$EGND$	PECL Ground

## TRUTH TABLE

$D_n$	$MR$	$TCLK/CLK$	$Q_n + 1$
L	L	Z	L
H	L	Z	H
X	H	X	L
Open Input	X	X	L

Z = LOW to HIGH Transition

## DC CHARACTERISTICS ( $V_{CCT} = V_{CCE} = 5.0V \pm 5\%$ )

Symbol	Characteristic	$T_A = 0^\circ C$			$T_A = +25^\circ C$			$T_A = +85^\circ C$			Unit	Condition
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max		
$I_{EE}$	ECL Power Supply Current		70	85		70	85		70	85	mA	
	10H		65	80		70	85		75	95		
	100H											
$I_{CCL}$	TTL Supply Current		100	120		100	120		100	120	mA	
$I_{CCH}$	TTL Supply Current		100	120		100	120		100	120	mA	

# MC10H607, MC100H607

## 10H PECL DC CHARACTERISTICS ( $V_{CCT} = V_{CCE} = 5.0V \pm 5\%$ )

Symbol	Characteristic	$T_A = 0^\circ C$		$T_A = 25^\circ C$		$T_A = 85^\circ C$		Unit	Condition
		Min	Max	Min	Max	Min	Max		
$I_{INH}$	Input HIGH Current		255		145		145	$\mu A$	
$I_{INL}$	Input LOW Current		0.5		0.5		0.5	$\mu A$	
$V_{IH}$	Input HIGH Voltage	3830	4160	3870	4190	3930	4280	mV	$V_{CCT} = 5.0V$
$V_{IL}$	Input LOW Voltage	3050	3520	3050	3520	3050	3555	mV	$V_{CCT} = 5.0V$
$V_{BB}$	Output Bias Voltage	3600	3710	3630	3730	3670	3790	mV	$V_{CCT} = 5.0V$

NOTE: PECL  $V_{IL}$ ,  $V_{IH}$ ,  $V_{OL}$ ,  $V_{OH}$ ,  $V_{BB}$  are given for  $V_{CCT} = V_{CCE} = 5.0V$  and will vary 1:1 with power supply.

## 100H PECL DC CHARACTERISTICS ( $V_{CCT} = V_{CCE} = 5.0V \pm 5\%$ )

Symbol	Characteristic	$T_A = 0^\circ C$		$T_A = 25^\circ C$		$T_A = 85^\circ C$		Unit	Condition
		Min	Max	Min	Max	Min	Max		
$I_{IH}$	Input HIGH Current		255		145		145	$\mu A$	
$I_{IL}$	Input LOW Current		0.5		0.5		0.5	$\mu A$	
$V_{IH}$	Input HIGH Voltage	3835	4120	3835	4120	3835	4120	mV	$V_{CCT} = 5.0V$
$V_{IL}$	Input LOW Voltage	3190	3525	3190	3525	3190	3525	mV	$V_{CCT} = 5.0V$
$V_{BB}$	Output Bias Voltage	3600	3720	3600	3720	3600	3720	mV	$V_{CCT} = 5.0V$

NOTE: PECL  $V_{IL}$ ,  $V_{IH}$ ,  $V_{OL}$ ,  $V_{OH}$ ,  $V_{BB}$  are given for  $V_{CCT} = V_{CCE} = 5.0V$  and will vary 1:1 with power supply.

## 10H/100H TTL DC CHARACTERISTICS ( $V_{CCT} = V_{CCE} = 5.0V \pm 5\%$ )

Symbol	Characteristic	$T_A = 0^\circ C$		$T_A = 25^\circ C$		$T_A = 85^\circ C$		Unit	Condition
		Min	Max	Min	Max	Min	Max		
$V_{OH}$	Output HIGH Voltage	2.5 2.0		2.5 2.0		2.5 2.0		V	$I_{OH} = -15mA$ $I_{OH} = -24mA$
$V_{OL}$	Output LOW Voltage		0.55		0.55		0.55	V	$I_{OL} = 48mA$

NOTE: DC levels such as  $V_{OH}$ ,  $V_{OL}$ , etc., are standard for PECL and FAST devices, with the exceptions of:  $I_{OL} = 48mA$  at  $0.5V_{OL}$ ; and  $I_{OH} = -24mA$  at  $2.0V_{OH}$ .

## AC CHARACTERISTICS ( $V_{CCT} = V_{CCE} = 5.0V \pm 5\%$ )



Symbol	Characteristic	$T_A = 0^\circ C$		$T_A = + 25^\circ C$		$T_A = + 85^\circ C$		Unit	Condition
		Min	Max	Min	Max	Min	Max		
$t_{PLH}$ $t_{PHH}$	Propagation Delay to Output CLK to Q	5.5 4.6	7.7 7.7	6.0 4.9	8.2 8.3	6.7 5.9	10.0 10.0	ns	CL = 50pF
$t_{PHL}$	Propagation Delay to Output MR to Q	4.4	7.5	4.7	8.1	5.8	10.5	ns	CL = 50pF
$t_{PW}$	Minimum Pulse Width CLK, MR	1.0		1.0		1.0		ns	
$t_r$	Rise Time	0.5	2.0	0.5	2.0	0.5	2.0	ns	1.0V to 2.0V
$t_f$	Fall Time	0.5	2.0	0.5	2.0	0.5	2.0	ns	1.0V to 2.0V
$t_S$	Setup Time	1.5		1.5		1.5		ns	
$t_H$	Hold Time	1.5		1.5		1.5		ns	
$V_{PP}$	Minimum Input Swing	200		200		200		mV	

1. Numbers are for both ++ and -- delay MR to Q.


# MC10H607, MC100H607

## PACKAGE DIMENSIONS


PLCC-28  
FN SUFFIX  
PLASTIC PLCC PACKAGE  
CASE 776-02  
ISSUE D



VIEW D-D



VIEW S



VIEW S

### NOTES:

- DATUMS -L-, -M-, AND -N- DETERMINED WHERE TOP OF LEAD SHOULDER EXITS PLASTIC BODY AT MOLD PARTING LINE.
- DIMENSION G1, TRUE POSITION TO BE MEASURED AT DATUM -T-, SEATING PLANE.
- DIMENSIONS R AND U DO NOT INCLUDE MOLD FLASH. ALLOWABLE MOLD FLASH IS 0.010 (0.250) PER SIDE.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.
- THE PACKAGE TOP MAY BE SMALLER THAN THE PACKAGE BOTTOM BY UP TO 0.012 (0.300). DIMENSIONS R AND U ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
- DIMENSION H DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION. THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE GREATER THAN 0.037 (0.940). THE DAMBAR INTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE SMALLER THAN 0.025 (0.635).

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.485	0.495	12.32	12.57
B	0.485	0.495	12.32	12.57
C	0.165	0.180	4.20	4.57
E	0.090	0.110	2.29	2.79
F	0.013	0.019	0.33	0.48
G	0.050 BSC		1.27 BSC	
H	0.026	0.032	0.66	0.81
J	0.020	---	0.51	---
K	0.025	---	0.64	---
R	0.450	0.456	11.43	11.58
U	0.450	0.456	11.43	11.58
V	0.042	0.048	1.07	1.21
W	0.042	0.048	1.07	1.21
X	0.042	0.056	1.07	1.42
Y	---	0.020	---	0.50
Z	2°	10°	2°	10°
G1	0.410	0.430	10.42	10.92
K1	0.040	---	1.02	---

## **Notes**

## **Notes**

## **Notes**

**ON Semiconductor** and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### North America Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** ONlit@hibbertco.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

### EUROPE: LDC for ON Semiconductor – European Support

**German Phone:** (+1) 303-308-7140 (M–F 2:30pm to 5:00pm Munich Time)  
**Email:** ONlit-german@hibbertco.com  
**French Phone:** (+1) 303-308-7141 (M–F 2:30pm to 5:00pm Toulouse Time)  
**Email:** ONlit-french@hibbertco.com  
**English Phone:** (+1) 303-308-7142 (M–F 1:30pm to 5:00pm UK Time)  
**Email:** ONlit@hibbertco.com

### ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

**Phone:** 303-675-2121 (Tue–Fri 9:00am to 1:00pm, Hong Kong Time)  
Toll Free from Hong Kong 800-4422-3781  
**Email:** ONlit-asia@hibbertco.com

### JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-8549  
**Phone:** 81-3-5740-2745  
**Email:** r14525@onsemi.com

**Fax Response Line:** 303-675-2167  
800-344-3810 Toll Free USA/Canada

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local Sales Representative.