

UF300G THRU UF308G

GLASS PASSIVATED JUNCTION ULTRAFAST SWITCHING RECTIFIER

VOLTAGE - 50 to 800 Volts CURRENT - 3.0 Amperes

DO-201AD

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O Utilizing Flame Retardant Epoxy Molding Compound
- Glass passivated junction in DO-201AD package
- 3.0 ampere operation at $T_A=55^{\circ}\text{C}$ with no thermal runaway
- Exceeds environmental standards of MIL-S-19500/228
- Ultra Fast switching for high efficiency

MECHANICAL DATA


Case: Molded plastic, DO-201AD

Terminals: axial leads, solderable per MIL-STD-202, Method 208

Polarity: Band denotes cathode

Mounting Position: Any

Weight: 0.04 ounce, 1.1 gram



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Resistive or inductive load 60Hz.

	UF300G	UF301G	UF302G	UF304G	UF306G	UF308G	UNITS
Peak Reverse Voltage, Repetitive; V _{RM} :	50	100	200	400	600	800	V
Maximum RMS Voltage	35	70	140	280	420	560	V
DC Reverse Voltage; V _R	50	100	200	400	600	800	V
Average Forward Current, I _o @ T _A =55 °C 3/8" lead length, 60 Hz, resistive or inductive load	3.0						A
Peak Forward Surge Current, I _{FM} (surge) 8.3msec. single half sine wave superimposed on rated load(JEDEC method)	150						A
Maximum Forward Voltage VF @ 3.0A, 25 °C	1.00			1.30	1.70		V
Maximum Reverse Current, @ Rated T _J =25 °C	10.0						µg A
Reverse Voltage T _J =100 °C	300						µg A
Typical Junction capacitance (Note 1) C _J	75.0			50.0			pF
Typical Junction Resistance (Note 2) R θJA	60.0						°C/W
Reverse Recovery Time I _F = .5A, I _R =1A, I _{rr} = .25A	50	50	50	50	100	100	ns
Operating and Storage Temperature Range	-55 to +150						°C

NOTES:

1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC
2. Thermal resistance from junction to ambient and from junction to lead length 0.375" (9.5mm) P.C.B. mounted

RATING AND CHARACTERISTIC CURVES

UF300G THRU UF308G




Fig. 1-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




Fig. 2-FORWARD CHARACTERISTICS




Fig. 3-FORWARD CURRENT DERATING CURVE




Fig. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS




Fig. 5-PEAK FORWARD SURGE CURRENT