

M3 SERIES

P10LU-XXXXE 3KV ISOLATED 2W UNREGULATED SINGLE OUTPUT SIP7

Available Inputs:

5, 12, 24 and 48 VDC

Available Outputs:

5, 7.2, 12 and 15 VDC

Other specifications please enquire

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

Voltage range

+/- 10 %

Filter

Capacitors

Isolation Specifications

Rated voltage

3000 VDC

Leakage current

1 mA

Resistance

10⁹ Ohm

Capacitance

60 pF typ.

Output Specifications

Voltage accuracy

+/- 5 %, max.

Ripple and noise (at 20 MHz BW)

75 mV p-p, max.

Short circuit protection

Momentary

Line voltage regulation

+/- 1,2 % / 1,0 % of Vin

Load voltage regulation

+/- 8 %, load = 20 ~ 100 %

Temperature coefficient

+/- 0,02 % / °C

General Specifications

Efficiency

70 % to 85 %

Switching frequency

85 KHz, typ.

Environmental Specifications

Operating temperature (ambient)

- 40° C to + 85° C

Storage temperature

- 55 °C to + 125 °C

Derating

See graph

Humidity

Up to 90 %, non condensing

Cooling

Free air convection

Physical Characteristics

Dimensions SIP

19,50 x 6,00 x 9,50 mm

0,76 x 0,24 x 0,37 inches

Weight

2,5 g 3,5 g for 48 VDC


Case material

Non conductive black plastic


Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC)	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P10LU-0505E	5	28	555	5	400	72
P10LU-0512E	5	28	500	12	167	80
P10LU-0518E	5	30	500	18	110	80
P10LU-1205E	12	22	228	5	400	73
P10LU-1212E	12	20	208	12	167	80
P10LU-2405E	24	10	113	5	400	74
P10LU-2412E	24	9	101	12	167	82

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH