

## MQ SERIES P18TG-XXXXE4:1H35 3.5 KV ISOLATED 4 W REGULATED SINGLE OUTPUT DIP24

### Available Inputs:

24 and 48 VDC Wide Input 4:1

### Available Outputs:

3.3, 5, 12, 15 and 18 VDC

Other specifications please enquire.

### Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

#### Input Specifications

Voltage range

9 - 36 VDC (24 VDC), 18 - 72 VDC (48 VDC)

Filter

Pi Network

#### Isolation Specifications

Rated voltage

3500 Vdc

Leakage current

1 mA

Resistance

10<sup>9</sup> Ohm

Capacitance

80 pF typ.

#### Output Specifications

Voltage accuracy

+/- 1 % typ. +/-2% max.

Ripple and noise (at 20 MHz BW)

60 mV p-p, max.

Short circuit protection

Continuous , restart automatic

Line voltage regulation

+/- 0,5 % max.

Load voltage regulation

+/- 0,5 % max.

Temperature coefficient

+/- 0,02 % / °C

#### General Specifications

Efficiency

70 % to 85 %

Switching frequency

250 KHz, typ.

#### Environmental Specifications

Operating temperature (ambient)

-40°C to +85°C

Storage temperature

- 55 °C to + 125 °C

Derating

See graph

Humidity

Up to 90 %, non condensing

Cooling

Free air convection

#### Physical Characteristics

Dimensions

31,75 x 20,32 x 10,16 mm

1,25 x 0,80 x 0,40 inches

Weight

21,5 g


Case material

Non conductive black plastic

### Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC) Nominal	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P18TG-2405E4:1H35	9-36	12	219	5	800	76
P18TG-2412E4:1H35	9-36	11	214	12	333	76
P18TG-4805E4:1H35	18-72	12	111	5	800	75
P18TG-4812E4:1H35	18-72	12	107	12	333	78
P18TG-4815E4:1H35	18-72	12	104	15	267	80
P18TG-4818E4:1H35	18-72	12	104	18	222	80

Dimensions



Derating Graph and Pinning

