



STS8201



Dual N-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY

| V _{DS} | I _D | R _{DS(ON)} (m Ω) Max |
|-----------------|----------------|--|
| 20V | 5A | 27 @ V _{GS} = 4.0V 40 @ V _{GS} = 2.5V |

FEATURES

- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- Surface Mount Package.
- ESD Protected.



ABSOLUTE MAXIMUM RATINGS (T_A=25 °C unless otherwise noted)

| Parameter | Symbol | Limit | Unit |
|--|-----------------------------------|------------|------|
| Drain-Source Voltage | V _{DS} | ±20 | V |
| Gate-Source Voltage | V _{GS} | ±12 | V |
| Drain Current-Continuous @ T _J =25 °C -Pulsed ^b | I _D | 5 | A |
| | I _{DM} | 20 | A |
| Drain-Source Diode Forward Current ^a | I _S | 1.25 | A |
| Maximum Power Dissipation ^a | P _D | 1.25 | W |
| Operating Junction and Storage Temperature Range | T _J , T _{STG} | -55 to 150 | °C |

THERMAL CHARACTERISTICS

| | | | |
|--|---------------|-----|------|
| Thermal Resistance, Junction-to-Ambient ^a | R θ JA | 100 | °C/W |
|--|---------------|-----|------|

STS 8201

ELECTRICAL CHARACTERISTICS (TA=25 °C unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ ^c | Max | Unit |
|--|---------------------|---|-----|------------------|-----|-------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV _{DSS} | V _{GS} =0V, I _D =250uA | 20 | | | V |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} =16V, V _{GS} =0V | | | 1 | uA |
| Gate-Body Leakage | I _{GSS} | V _{GS} = ±12V, V _{DS} =0V | | | ±10 | uA |
| ON CHARACTERISTICS ^b | | | | | | |
| Gate Threshold Voltage | V _{GS(th)} | V _{DS} =V _{GS} , I _D = 250uA | 0.5 | 0.8 | 1.5 | V |
| Drain-Source On-State Resistance | R _{DS(ON)} | V _{GS} =4.0V, I _D = 5A | | 22 | 27 | m ohm |
| | | V _{GS} =2.5V, I _D = 3A | | 30 | 40 | m ohm |
| Forward Transconductance | g _{FS} | V _{DS} = 5V, I _D =5A | | 19 | | S |
| DYNAMIC CHARACTERISTICS ^c | | | | | | |
| Input Capacitance | C _{ISS} | V _{DS} =8V, V _{GS} = 0V f =1.0MHz | | 720 | | pF |
| Output Capacitance | C _{OSS} | | | 195 | | pF |
| Reverse Transfer Capacitance | C _{RSS} | | | 147 | | pF |
| SWITCHING CHARACTERISTICS ^c | | | | | | |
| Turn-On Delay Time | t _{D(ON)} | V _{DD} = 10V, I _D = 1A, V _{GEN} = 4.0V, R _{GEN} = 10 ohm | | 34 | | ns |
| Rise Time | t _r | | | 68 | | ns |
| Turn-Off Delay Time | t _{D(OFF)} | | | 104 | | ns |
| Fall Time | t _f | | | 43 | | ns |
| Total Gate Charge | Q _g | V _{DS} =10V, I _D = 5A, V _{GS} =4.0V | | 12 | | nC |
| Gate-Source Charge | Q _{gs} | | | 2.3 | | nC |
| Gate-Drain Charge | Q _{gd} | | | 5.5 | | nC |

STS8201

ELECTRICAL CHARACTERISTICS (T_A=25 °C unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---|-----------------|---|-----|-----|-----|------|
| DRAIN-SOURCE DIODE CHARACTERISTICS ^b | | | | | | |
| Diode Forward Voltage | V _{SD} | V _{GS} = 0 V, I _S = 1.25A | | 0.8 | 1.2 | V |

Notes

- a.Surface Mounted on FR4 Board, t ≤ 10sec.
- b.Pulse Test:Pulse Width ≤ 300us, Duty Cycle ≤ 2%.
- c.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STS 8201




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STS 8201




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11. switching characteristics




Figure 12. Maximum Safe Operating Area

STS8201




Figure 11. Switching Test Circuit






Figure 12. Switching Waveforms



STS 8201

PACKAGE OUTLINE DIMENSIONS

SOT26




| SYMBOL | MIN. | NOM. | MAX. |
|--------|-----------|------|------|
| A | — | — | 1.45 |
| A1 | — | — | 0.15 |
| A2 | 0.90 | 1.15 | 1.30 |
| b | 0.30 | — | 0.50 |
| c | 0.08 | — | 0.22 |
| D | 2.90 BSC. | | |
| E | 2.80 BSC. | | |
| E1 | 1.60 BSC. | | |
| e | 0.95 BSC. | | |
| e1 | 1.90 BSC. | | |
| L | 0.30 | 0.45 | 0.60 |
| L1 | 0.60 REF. | | |
| L2 | 0.25 BSC. | | |
| R | 0.10 | — | — |
| R1 | 0.10 | — | 0.25 |
| Ø | 0° | 4° | 8° |
| Ø1 | 5° | 10° | 15° |


STS 8201

SOT26 Tape and Reel Data

SOT26 Carrier Tape



SOT26 Reel



SOT-28