

Revision History

Revision 6 (May 1998)

- Input leakage current (Inputs) I_{IL} is updated.
- Input Capacitances are updated.

Revision 7 (May 1998)

- Revised PLL Input cap. 20pF to 5pF.
- CLK Input Cap. is added by PLL Input Cap. (5pF)

Revision 8 (June 1998)

- "REGE" description is changed.

SDRAM MODULE

Preliminary KMM375S400CT

KMM375S400CT SDRAM DIMM

4Mx72 SDRAM DIMM with PLL & Register based on 4Mx4, 4K Ref., 3.3V Synchronous DRAMs with SPD

GENERAL DESCRIPTION

The Samsung KMM375S400CT is a 4M bit x 72 Synchronous Dynamic RAM high density memory module. The Samsung KMM375S400CT consists of eighteen CMOS 4Mx4 bit Synchronous DRAMs in TSOP-II 400mil packages, two 20-bits Drive ICs for input control signal, one PLL in 24-pin TSSOP package for clock and one 2K EEPROM in 8-pin TSSOP package for Serial Presence Detect on a 168-pin glass-epoxy substrate. Two 0.1uF decoupling capacitors are mounted on the printed circuit board in parallel for each SDRAM. The KMM375S400CT is a Dual In-line Memory Module and is intended for mounting into 168-pin edge connector sockets.

Synchronous design allows precise cycle control with the use of system clock. I/O transactions are possible on every clock cycle. Range of operating frequencies, programmable latencies allows the same device to be useful for a variety of high bandwidth, high performance memory system applications.

FEATURE

- Performance Range

Part No.	Max Freq. (Speed)
KMM375S400CT-G8	125MHz (8ns @ CL=3)
KMM375S400CT-GH	100MHz (10ns @ CL=2)
KMM375S400CT-GL	100MHz (10ns @ CL=3)
KMM375S400CT-G0	100MHz (10ns @ CL=3)

- Burst Mode Operation
- Auto & Self Refresh Capability (4096 Cycles/64ms)
- LVTTL Compatible Inputs and Outputs
- Single 3.3V \pm 0.3V Power Supply
- MRS Cycle with Address Key Programs
 - Latency (Access from Column Address)
 - Burst Length (1, 2, 4, 8 & Full Page)
 - Data Scramble (Sequential & Interleave)
- All inputs are sampled at the positive going edge of the system clock
- Serial Presence Detect with EEPROM
- PCB : **Height(1,500mil)**, Double Sided Component

PIN CONFIGURATIONS (Front Side/Back Side)

Pin	Front	Pin	Front	Pin	Front	Pin	Back	Pin	Back	Pin	Back
1	Vss	29	DQM1	57	DQ18	85	Vss	113	DQM5	141	DQ50
2	DQ0	30	$\overline{\text{CS0}}$	58	DQ19	86	DQ32	114	$\overline{\text{CS1}}$	142	DQ51
3	DQ1	31	DU	59	VDD	87	DQ33	115	$\overline{\text{RAS}}$	143	VDD
4	DQ2	32	Vss	60	DQ20	88	DQ34	116	Vss	144	DQ52
5	DQ3	33	A0	61	NC	89	DQ35	117	A1	145	NC
6	VDD	34	A2	62	*VREF	90	VDD	118	A3	146	*VREF
7	DQ4	35	A4	63	CKE1	91	DQ36	119	A5	147	REGE
8	DQ5	36	A6	64	Vss	92	DQ37	120	A7	148	Vss
9	DQ6	37	A8	65	DQ21	93	DQ38	121	A9	149	DQ53
10	DQ7	38	A10/AP	66	DQ22	94	DQ39	122	BA0	150	DQ54
11	DQ8	39	*BA1	67	DQ23	95	DQ40	123	*A11	151	DQ55
12	Vss	40	VDD	68	Vss	96	Vss	124	VDD	152	Vss
13	DQ9	41	VDD	69	DQ24	97	DQ41	125	*CLK1	153	DQ56
14	DQ10	42	CLK0	70	DQ25	98	DQ42	126	*A12	154	DQ57
15	DQ11	43	Vss	71	DQ26	99	DQ43	127	Vss	155	DQ58
16	DQ12	44	DU	72	DQ27	100	DQ44	128	CKE0	156	DQ59
17	DQ13	45	$\overline{\text{CS2}}$	73	VDD	101	DQ45	129	* $\overline{\text{CS3}}$	157	VDD
18	VDD	46	DQM2	74	DQ28	102	VDD	130	DQM6	158	DQ60
19	DQ14	47	DQM3	75	DQ29	103	DQ46	131	DQM7	159	DQ61
20	DQ15	48	DU	76	DQ30	104	DQ47	132	*A13	160	DQ62
21	CB0	49	VDD	77	DQ31	105	CB4	133	VDD	161	DQ63
22	CB1	50	NC	78	Vss	106	CB5	134	NC	162	Vss
23	Vss	51	NC	79	*CLK2	107	Vss	135	NC	163	*CLK3
24	NC	52	CB2	80	NC	108	NC	136	CB6	164	NC
25	NC	53	CB3	81	NC/WP	109	NC	137	CB7	165	**SA0
26	VDD	54	Vss	82	**SDA	110	VDD	138	Vss	166	**SA1
27	$\overline{\text{WE}}$	55	DQ16	83	**SCL	111	$\overline{\text{CAS}}$	139	DQ48	167	**SA2
28	DQM0	56	DQ17	84	VDD	112	DQM4	140	DQ49	168	VDD

PIN NAMES

Pin Name	Function
A0 ~ A10/AP	Address Input (Multiplexed)
BA0	Select Bank
DQ0 ~ DQ63	Data Input/Output
CB0 ~ CB7	Check Bit (Data-in/Data-out)
CLK0	Clock Input
CKE0 ~ CKE1	Clock Enable Input
$\overline{\text{CS0}}, \overline{\text{CS2}}$	Chip Select Input
$\overline{\text{RAS}}$	Row Address Strobe
$\overline{\text{CAS}}$	Column Address Strobe
$\overline{\text{WE}}$	Write Enable
DQM0 ~ 7	DQM
VDD	Power Supply (3.3V)
Vss	Ground
*VREF	Power Supply for Reference
REGE	Register Enable
SDA	Serial Data I/O
SCL	Serial Clock
SA0 ~ 2	Address in EEPROM
DU	Don't use
NC	No Connection
WP	Write protection

* These pins are not used in this module.

** These pins should be NC in the system which does not support SPD.

SAMSUNG ELECTRONICS CO., Ltd. reserves the right to change products and specifications without notice.

SDRAM MODULE

Preliminary
KMM375S400CT


PIN CONFIGURATION DESCRIPTION

Pin	Name	Input Function
CLK	<i>System Clock</i>	Active on the positive going edge to sample all inputs.
$\overline{\text{CS}}$	<i>Chip Select</i>	Disables or enables device operation by masking or enabling all inputs except CLK, CKE and DQM
CKE	<i>Clock Enable</i>	Masks system clock to freeze operation from the next clock cycle. CKE should be enabled at least one cycle prior to new command. Disable input buffers for power down in standby. CKE should be enabled 1CLK+tss prior to valid command.
A0 ~ A10/AP	<i>Address</i>	Row/Column Addresses are multiplexed on the same pins. Row Address : RA0 ~ RA10, Column Address : CA0 ~ CA9
BA0	<i>Bank Select Address</i>	Selects bank to be activated during row address latch time. Selects bank for read/write during column address latch time.
$\overline{\text{RAS}}$	<i>Row Address Strobe</i>	Latches row addresses on the positive going edge of the CLK with $\overline{\text{RAS}}$ low. Enables row access & precharge.
$\overline{\text{CAS}}$	<i>Column Address Strobe</i>	Latches column addresses on the positive going edge of the CLK with $\overline{\text{CAS}}$ low. Enables column access.
$\overline{\text{WE}}$	<i>Write Enable</i>	Enables write operation and row precharge. Latches data in starting from $\overline{\text{CAS}}$, $\overline{\text{WE}}$ active.
DQM0 ~ 7	<i>Data Input/Output Mask</i>	Makes data output Hi-Z, t SHZ after the clock and masks the output. Blocks data input when DQM active. (Byte masking)
REGE	<i>Register Enable</i>	The device operates in the transparent mode when REGE is low. When REGE is high, the device operates in the registered mode. In registered mode, the Address and control inputs are latched. If CLK is held at a high or low logic level ; the inputs are stored in the latch/flip-flop on the rising edge of CLK. REGE is tied to V _{cc} through 10K ohm Register on PCB. So if REGE of module is floating, this module will be operated as registered mode.
DQ0 ~ 63	<i>Data Input/Output</i>	Data inputs/outputs are multiplexed on the same pins.
CB0 ~ 7	<i>Check bit</i>	Check bits for ECC.
V _{DD} /V _{SS}	<i>Power Supply/Ground</i>	Power and ground for the input buffers and the core logic.

SDRAM MODULE

Preliminary
KMM375S400CT


FUNCTIONAL BLOCK DIAGRAM




SDRAM MODULE

Preliminary
KMM375S400CT


STANDARD TIMING DIAGRAM WITH PLL & REGISTER (CL=2, BL=4)




*1. Register Input



*2. Register Output



*3. SDRAM



t_d , t_r = Delay of Register (SN74ALVCH162836 of TI)

Note : 1. In case of module timing, command cycles delayed 1CLK with respect to external input timing at the address and input signal because of the buffering in register (SN74ALVCH162836). Therefore, Input/Output signals of read/write function should be issued 1CLK earlier as compared to Unbuffered DIMMs.

2. D_{IN} is to be issued 1clock after write command in external timing because D_{IN} is issued directly to module.

□ : Don't Care

SDRAM MODULE

Preliminary
KMM375S400CT

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Voltage on Any Pin Relative to V _{SS}	V _{IN} , V _{OUT}	-1.0 ~ 4.6	V
Voltage on V _{DD} Supply Relative to V _{SS}	V _{DD} , V _{DDQ}	-1.0 ~ 4.6	V
Storage Temperature	T _{STG}	-55 ~ +150	°C
Power Dissipation	P _D	18	W
Short Circuit Current	I _{OS}	50	mA

Note : Permanent device damage may occur if "ABSOLUTE MAXIMUM RATINGS" are exceeded.
Functional operation should be restricted to recommended operating condition.
Exposure to higher than recommended voltage for extended periods of time could affect device reliability.

DC OPERATING CONDITIONS AND CHARACTERISTICS

Recommended Operating Conditions (Voltage Referenced to V_{SS} = 0V, T_A = 0 to 70 °C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply Voltage	V _{DD}	3.0	3.3	3.6	V	
Input High Voltage	V _{IH}	2.0	3.0	V _{DDQ} +0.3	V	1
Input Low Voltage	V _{IL}	-0.3	0	0.8	V	2
Output High Voltage	V _{OH}	2.4	-	-	V	I _{OH} = -2mA
Output Low Voltage	V _{OL}	-	-	0.4	V	I _{OL} = 2mA
Input Leakage Current (Inputs)	I _{IL}	-2	-	2	uA	3
Input Leakage Current (I/O Pins)	I _{IL}	-1.5	-	1.5	uA	3,4

Note : 1. V_{IH} (max) = 5.6V AC. The overshoot voltage duration is ≤ 3ns.
2. V_{IL} (min) = -2.0V AC. The undershoot voltage duration is ≤ 3ns.
3. Any input 0V ≤ V_{IN} ≤ V_{DDQ}.
Input leakage currents include Hi-Z output leakage for all bi-directional buffers with Tri-State outputs.
4. Dout is disabled, 0V ≤ V_{OUT} ≤ V_{DDQ}.

CAPACITANCE (V_{DD} = 3.3V, T_A = 23°C, f = 1MHz, V_{REF} = 1.4V ± 200 mV)

Parameter	Symbol	Min	Max	Unit
Input Capacitance (A ₀ ~ A _{10/AP})	C _{IN1}	-	15	pF
Input Capacitance ($\overline{\text{RAS}}$, $\overline{\text{CAS}}$, $\overline{\text{WE}}$)	C _{IN2}	-	15	pF
Input Capacitance (CKE ₀ ~ CKE ₁)	C _{IN3}	-	15	pF
Input Capacitance (CLK ₀)	C _{IN4}	-	19	pF
Input Capacitance ($\overline{\text{CS0}}$, $\overline{\text{CS2}}$)	C _{IN5}	-	15	pF
Input Capacitance (DQM ₀ ~ DQM ₇)	C _{IN6}	-	15	pF
Input Capacitance (BA ₀)	C _{IN7}	-	15	pF
Data Input/Output Capacitance (DQ ₀ ~ DQ ₆₃)	C _{OUT1}	-	17	pF

SDRAM MODULE

Preliminary
KMM375S400CT

DC CHARACTERISTICS

(Recommended Operating Condition Unless Otherwise Noted, T_A = 0 to 70 °C)

Parameter	Symbol	Test Condition	CAS Latency	Version				Unit	Note
				-8	-H	-L	-0		
Operating Current (One Bank Active)	I _{CC1}	Burst Length = 1 t _{RC} ≥ t _{RC} (min) I _{OL} = 0 mA		1,680	1,590	1,590	1,410	mA	1
Precharge Standby Current in Power-down Mode	I _{CC2P}	CKE ≤ V _{IL} (max), t _{CC} = 15ns		20				mA	
	I _{CC2PS}	CKE & CLK ≤ V _{IL} (max), t _{CC} = ∞		20					
Precharge Standby Current in Non Power-down Mode	I _{CC2N}	CKE ≥ V _{IH} (min), \overline{CS} ≥ V _{IH} (min), t _{CC} = 15ns Input signals are changed one time during 30ns		272				mA	
	I _{CC2NS}	CKE ≥ V _{IH} (min), CLK ≤ V _{IL} (max), t _{CC} = ∞ Input signals are stable		74					
Active Standby Current in Power-down Mode	I _{CC3P}	CKE ≤ V _{IL} (max), t _{CC} = 15ns		38				mA	
	I _{CC3PS}	CKE & CLK ≤ V _{IL} (max), t _{CC} = ∞		20					
Active Standby Current in Non Power-down Mode (One Bank Active)	I _{CC3N}	CKE ≥ V _{IH} (min), \overline{CS} ≥ V _{IH} (min), t _{CC} = 15ns Input signals are changed one time during 30ns		452				mA	
	I _{CC3NS}	CKE ≥ V _{IH} (min), CLK ≤ V _{IL} (max), t _{CC} = ∞ Input signals are stable		272				mA	
Operating Current (Burst Mode)	I _{CC4}	I _{OL} = 0 mA Page Burst t _{CCD} = 2CLKs	3	2,130	1,770	1,770	1,770	mA	1
			2	1,590	1,770	1,590	1,590		
Refresh Current	I _{CC5}	t _{RC} ≥ t _{RC} (min)		990			900	mA	2
Self Refresh Current	I _{CC6}	CKE ≤ 0.2V		20				mA	3


Note : 1. Measured with outputs open.
2. Refresh period is 64ms.
3. Measured with 1 PLL & 2 Drive ICs.

SDRAM MODULE


Preliminary
KMM375S400CT

AC OPERATING TEST CONDITIONS ($V_{DD} = 3.3V \pm 0.3V$, $T_A = 0$ to $70^\circ C$)

Parameter	Value	Unit
AC Input Levels (V_{ih}/V_{il})	2.4/0.4	V
Input Timing Measurement Reference Level	1.4	V
Input Rise and Fall Time	$t_r/t_f = 1/1$	ns
Output Timing Measurement Reference Level	1.4	V
Output Load Condition	See Fig. 2	



(Fig. 1) DC Output Load Circuit



(Fig. 2) AC Output Load Circuit

OPERATING AC PARAMETER

(AC Operating Conditions Unless Otherwise Noted)

Parameter		Symbol	Version				Unit	Note
			-8	-H	-L	-0		
Row Active to Row Active Delay		tRRD(min)	16	20	20	20	ns	1
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ Delay		tRCD(min)	20	20	20	26	ns	1
Row Precharge Time		tRP(min)	20	20	20	26	ns	1
Row Active Time		tRAS(min)	48	50	50	50	ns	1
		tRAS(max)	100				us	
Row Cycle Time		tRC(min)	68	70	70	80	ns	1
Last Data in to Row Precharge		tRDL(min)	8	10	10	12	ns	2
Last Data in to New Col. Address Delay		tCDL(min)	1				CLK	2
Last Data in to Burst Stop		tBDL(min)	1				CLK	2
Col. Address to Col. Address Delay		tCCD(min)	1				CLK	3
Number of Valid Output Data	CAS Latency=3	2					ea	4
	CAS Latency=2	1						

- Note :**
1. The minimum number of clock cycles is determined by dividing the minimum time required with clock cycle time and then rounding off to the next higher integer.
 2. Minimum delay is required to complete write.
 3. All parts allow every cycle column address change.
 4. In case of row precharge interrupt, auto precharge and read burst stop.

SDRAM MODULE

Preliminary
KMM375S400CT

AC CHARACTERISTICS (AC Operating Conditions Unless Otherwise Noted)

Parameter		Symbol	-8		-H		-L		-0		Unit	Note
			Min	Max	Min	Max	Min	Max	Min	Max		
CLK Cycle Time	CAS Latency=3	tCC	8	1000	10	1000	10	1000	10	1000	ns	1
	CAS Latency=2		12		10		12		13			
CLK to Valid Output Delay	CAS Latency=3	tSAC		6		6		6		7	ns	1,2
	CAS Latency=2			6		6		7		8		
Output Data Hold Time	CAS Latency=3	tOH	3		3		3		3		ns	1,2
	CAS Latency=2		3		3		3		3			
CLK High Pulse Width		tCH	3		3		3		3.5		ns	3
CLK Low Pulse Width		tCL	3		3		3		3.5		ns	3
Input Setup Time		tSS	2		2		2		2.5		ns	3
Input Hold Time		tSH	1		1		1		1		ns	3
CLK to Output in Low-Z		tSLZ	1		1		1		1		ns	2
CLK to Output in Hi-Z	CAS Latency=3	tSHZ		6		6		6		7	ns	1
	CAS Latency=2			6		6		7		8		

- Note :** 1. Parameters depend on programmed CAS latency.
 2. If clock rising time is longer than 1ns, (tr/2-0.5)ns should be added to the parameter.
 3. Assumed input rise and fall time (tr & tf) = 1ns.
 If tr & tf is longer than 1ns, transient time compensation should be considered,
 i.e., [(tr + tf)/2-1]ns should be added to the parameter.

SDRAM MODULE

Preliminary
KMM375S400CT

FREQUENCY vs. AC PARAMETER RELATIONSHIP TABLE

KMM375S400CT-8

(Unit : Number of Clock)

Frequency	CAS Latency	tRC	tRAS	tRP	tRRD	tRCD	tCCD	tCDL	tRDL
		68ns	48ns	20ns	16ns	20ns	8ns	8ns	8ns
125MHz (8.0ns)	3	9	6	3	2	3	1	1	1
100MHz (10.0ns)	3	7	5	2	2	2	1	1	1
83MHz (12.0ns)	2	6	4	2	2	2	1	1	1
75MHz (13.0ns)	2	6	4	2	2	2	1	1	1
66MHz (15.0ns)	2	6	4	2	2	2	1	1	1

KMM375S400CT-H

(Unit : Number of Clock)

Frequency	CAS Latency	tRC	tRAS	tRP	tRRD	tRCD	tCCD	tCDL	tRDL
		70ns	50ns	20ns	20ns	20ns	10ns	10ns	10ns
100MHz (10.0ns)	2	7	5	2	2	2	1	1	1
83MHz (12.0ns)	2	6	5	2	2	2	1	1	1
75MHz (13.0ns)	2	6	4	2	2	2	1	1	1
66MHz (15.0ns)	2	5	4	2	2	2	1	1	1
60MHz (16.7ns)	2	5	3	2	2	2	1	1	1

KMM375S400CT-L

(Unit : Number of Clock)

Frequency	CAS Latency	tRC	tRAS	tRP	tRRD	tRCD	tCCD	tCDL	tRDL
		70ns	50ns	20ns	20ns	20ns	10ns	10ns	10ns
100MHz (10.0ns)	3	7	5	2	2	2	1	1	1
83MHz (12.0ns)	2	6	5	2	2	2	1	1	1
75MHz (13.0ns)	2	6	4	2	2	2	1	1	1
66MHz (15.0ns)	2	5	4	2	2	2	1	1	1
60MHz (16.7ns)	2	5	3	2	2	2	1	1	1

KMM375S400CT-0

(Unit : Number of Clock)

Frequency	CAS Latency	tRC	tRAS	tRP	tRRD	tRCD	tCCD	tCDL	tRDL
		80ns	50ns	26ns	20ns	26ns	10ns	10ns	12ns
100MHz (10.0ns)	3	8	5	3	2	3	1	1	2
83MHz (12.0ns)	3	7	5	3	2	3	1	1	1
75MHz (13.0ns)	2	7	4	2	2	2	1	1	1
66MHz (15.0ns)	2	6	4	2	2	2	1	1	1
60MHz (16.7ns)	2	5	3	2	2	2	1	1	1

SDRAM MODULE

Preliminary
KMM375S400CT

SIMPLIFIED TRUTH TABLE

Command			CKEn-1	CKEn	\overline{CS}	\overline{RAS}	\overline{CAS}	\overline{WE}	DQM	BA ₀	A ₁₀ /AP	A ₉ ~ A ₀	Note								
Register	Mode Register Set		H	X	L	L	L	L	X	OP Code			1,2								
Refresh	Auto Refresh		H	H	L	L	L	H	X	X			3								
	Self Refresh	Entry		L									H	L	H	H	X	X			3
		Exit	L		H	L	H	H	X	X											3
Bank Active & Row Addr.			H	X	L	L	H	H	X	V	Row Address										
Read & Column Address	Auto Precharge Disable		H	X	L	H	L	H	X	V	L	Column Address (A ₀ ~ A ₉)	4								
	Auto Precharge Enable										H		4,5								
Write & Column Address	Auto Precharge Disable		H	X	L	H	L	L	X	V	L	Column Address (A ₀ ~ A ₉)	4								
	Auto Precharge Enable										H		4,5								
Burst Stop			H	X	L	H	H	L	X	X			6								
Precharge	Bank Selection		H	X	L	L	H	L	X	V	L	X									
	Both Banks									X	H										
Clock Suspend or Active Power Down		Entry	H	L	H	X	X	X	X	X											
					L	V	V	V													
		Exit	L	H	X	X	X	X	X												
Precharge Power Down Mode		Entry	H	L	H	X	X	X	X	X											
					L	H	H	H													
		Exit	L	H	H	X	X	X	X												
					L	V	V	V													
DQM			H	X					V	X			7								
No Operation Command			H	X	H	X	X	X	X	X											
					L	H	H	H													

(V=Valid, X=Don't Care, H=Logic High, L=Logic Low)

Note : 1. OP Code : Operand Code

A₀ ~ A₁₀/AP, BA₀ : Program Keys. (@ MRS)

2. MRS can be issued only at both banks precharge state.

A new command can be issued after 2 CLK cycles of MRS.

3. Auto refresh functions are as same as CBR refresh of DRAM.

The automatical precharge without row precharge command is meant by "Auto".

Auto/Self refresh can be issued only at both banks precharge state.

4. BA₀ : Bank Select Address.

If "Low" at read, write, row active and precharge, bank A is selected.

If "High" at read, write, row active and precharge, bank B is selected.

If A₁₀/AP is "High" at row precharge, BA₀ is ignored and both banks are selected.

5. During burst read or write with auto precharge, new read/write command can not be issued.

Another bank read/write command can be issued after the end of burst.

New row active of the associated bank can be issued at t_{RP} after the end of burst.

6. Burst stop command is valid at every burst length.

7. DQM sampled at positive going edge of a CLK masks the data-in at the very CLK (Write DQM latency is 0),

but makes Hi-Z state the data-out of 2 CLK cycles after. (Read DQM latency is 2)

Preliminary
KMM375S400CT

Units : Inches (Millimeters)

