


Revision History

- First Edition: March 1999

- Second Edition: February 2000

- Library name change STD111
- All characteristic values are updated with mass product line characteristics.
- Add high density compiled memories to second edition. (chapter 5)
- The name of previous compiled memories are changed for example: spsram into spsram_lp
- power equations are changed. (chapter 1)
- Updated PLL information
- Updated wire-load model



STD111

**0.25 μ m 2.5V CMOS Standard Cell Library
for Pure Logic Products**

STD111
0.25 μ m 2.5V CMOS Standard Cell Library
for Pure Logic Products
Data Book

© 1999-2000 Samsung Electronics Co., Ltd.

All rights reserved. No part of this document may be reproduced, in any form or by any means, without the prior written consent of the publisher. Samsung assumes no responsibility for any errors resulting from the use of the information contained herein, nor does it convey any license under the patent rights of Samsung or others. Samsung reserves the right to make changes in its products or product specification to improve function or design at any time, without notice.

SEC and STD111 are trademarks of Samsung Electronics Co., Ltd. Verilog is a registered trademark of Cadence Design Systems, Inc. Viewlogic is a registered trademark of Viewlogic Systems, Inc. Mentor is a registered trademark of Mentor Graphics Co. Synopsys is a registered trademark of Synopsys, Inc.

Head Office

Samsung Electronics Co., Ltd
System LSI Business,
ASIC Division, SOC Design Technology
San #24, Nongseo-Ri,
Kiheung-Eup, Yongin-City,
Kyunggi-Do, Korea

TEL 82-2-760-6500, 6501 (Hot Line)
FAX 82-331-209-4920
<http://www.intl.samsungsemi.com>

Marketing Team

Samsung Electronics Co., Ltd
System LSI Business,
ASIC Division,
ASIC Marketing Team
San #24, Nongseo-Ri,
Kiheung-Eup, Yongin-City,
Kyunggi-Do, Korea

TEL 82-2-331-209-1930
FAX 82-2-331-209-1919

Introduction

This databook contains information about STD111 0.25 μ m 2.5V standard cell library for pure Logic products developed by SEC (Samsung Electronics Corporation).

The “library” basically contains various kinds of internal and I/O cells and soft-macros which are used for developing ASIC (Application Specific Integrated Circuit). It also includes a design kit helping designers to work in a workstation platform, and all sorts of design environments needed for an automatic chip design.

There are six chapters in this databook:

Chapter 1	Introduction
Chapter 2	Electrical Characteristics
Chapter 3	Internal Macrocells
Chapter 4	Input/Output Cells
Chapter 5	Compiled Macrocells
Chapter 6	PLL

In this databook each cell is followed by its AC electrical characteristics, and these characteristic values are almost equal when the corresponding cell is operated in a real chip.

The purpose of this databook is to prevent any misuse or misapplication of STD111 cell library by providing precise information about the cell list, electrical data, directions for use, and matters demanding special attention.

If you want to get more information about Digital cores and Analog cores that are not included in this databook, access the Samsung ASIC web site(<http://www.intl.samsungsemi.com>) or contact Head Office.

Contents

1 Introduction

1.1 Library Description	1-1
1.2 Features	1-2
1.3 EDA Support	1-4
1.4 Product Family	1-4
1.4.1 Analog Core Cell	1-4
1.4.2 Internal Macrocells	1-12
1.4.3 Compiled Macrocells	1-12
1.4.4 Input/Output Cells	1-14
1.5 Timings	1-16
1.6 Delay Model	1-22
1.7 Testability Design Methodology	1-24
1.8 Maximum Fanouts	1-27
1.9 Packages Capability by Lead Count	1-34
1.10 Power Dissipation	1-36
1.11 V_{DD}/V_{SS} Rules and Guidelines	1-39
1.12 Crystal Oscillator Considerations	1-45

2 Electrical Characteristics

DC Electrical Characteristics	2-1
-------------------------------------	-----

3 Internal Macrocells

Overview	3-1
Summary Tables	3-2
Logic Cells	
AD2DH/AD2/AD2D2/AD2D4	3-17
AD3DH/AD3/AD3D2/AD3D4	3-19
AD4DH/AD4/AD4D2/AD4D4	3-21
AD5/AD5D2/AD5D4	3-24
ND2DH/ND2/ND2D2/ND2D4	3-27
ND3DH/ND3/ND3D2/ND3D4	3-29
ND4DH/ND4/ND4D2/ND4D2B/ND4D4	3-32
ND5/ND5D2/ND5D4	3-35
ND6/ND6D2/ND6D4	3-38

Contents

ND8/ND8D2/ND8D4	3-42
NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A	3-46
NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A	3-49
NR4DH/NR4/NR4D2/NR4D2B/NR4D4	3-53
NR5/NR5D2/NR5D4	3-56
NR6/NR6D2/NR6D4	3-60
NR8/NR8D2/NR8D4	3-64
OR2DH/OR2/OR2D2/OR2D4	3-68
OR3DH/OR3/OR3D3/OR3D4	3-70
OR4DH/OR4/OR4D2/OR4D4	3-73
OR5/OR5D2/OR5D4	3-76
XN2/XN2D2/XN2D4	3-80
XN3/XN3D2/XN3D4	3-82
XO2/XO2D2/XO2D4	3-84
XO3/XO3D2/XO3D4	3-86
AO21DH/AO21/AO21D2/AO21D2B/AO21D4	3-88
AO211DH/AO211/AO211D2/AO211D2B/AO211D4	3-91
AO2111/AO2111D2	3-94
AO22DH/AO22/AO22D2/AO22D2B/AO22D4	3-97
AO22DHA/AO22A/AO22D2A/AO22D4A	3-100
AO221/AO221D2/AO221D4	3-103
AO222/AO222D2/AO222D2B/AO222D4	3-107
AO222A/AO222D2A/AO222D4A	3-112
AO2222/AO2222D2/AO2222D4	3-114
AO31DH/AO31/AO31D2/AO31D4	3-118
AO311/AO311D2/AO311D4	3-121
AO3111/AO3111D2	3-125
AO32/AO32D2/AO32D4	3-128
AO321/AO321D2/AO321D4	3-132
AO322/AO322D2/AO322D4	3-136
AO33/AO33D2/AO33D4	3-140
AO331/AO331D2/AO331D4	3-144
AO332/AO332D2/AO332D4	3-148
AO4111/AO4111D2	3-152
OA21DH/OA21/OA21D2/OA21D2B/OA21D4	3-155
OA211DH/OA211/OA211D2/OA211D2B/OA211D4	3-158
OA2111/OA2111D2	3-161
OA22DH/OA22/OA22D2/OA22D2B/OA22D4	3-164
OA22DHA/OA22A/OA22D2A/OA22D4A	3-167
OA221/OA221D2/OA221D4	3-170
OA222/OA222D2/OA222D2B/OA222D4	3-174
OA2222/OA2222D2/OA2222D4	3-179
OA31/OA31D2/OA31D4	3-183

OA311/OA311D2/OA311D4.....	3-186
OA3111/OA3111D2	3-190
OA32/OA32D2/OA32D4.....	3-193
OA321/OA321D2/OA321D.....	3-197
OA322/OA322D2/OA322D4.....	3-201
OA33/OA33D2/OA33D4.....	3-205
OA331/OA331D2/OA331D4.....	3-209
OA332/OA332D2/OA332D4.....	3-213
OA4111/OA4111D2	3-217
SCG1/SCG1D2	3-220
SCG2//SCG2D2	3-223
SCG3/SCG3D2	3-225
SCG4/SCG4D2	3-228
SCG5/SCG5D2	3-231
SCG6/SCG6D2	3-234
SCG7/SCG7D2	3-236
SCG8/SCG8D2	3-239
SCG9/SCG9D2	3-241
SCG10/SCG10D2	3-243
SCG11/SCG11D2	3-246
SCG12/SCG12D2	3-248
SCG13/SCG13D2	3-250
SCG14/SCG14D2	3-252
SCG15/SCG15D2	3-254
SCG16/SCG16D2	3-256
SCG17/SCG17D2	3-258
SCG18/SCG18D2	3-260
SCG19/SCG19D2	3-263
SCG20/SCG20D2	3-265
SCG21/SCG21D2	3-267
SCG22/SCG22D2	3-269
DL1D2/DL1D4.....	3-271
DL2D2/DL2D4.....	3-272
DL3D2/DL3D4.....	3-273
DL4D2/DL4D4.....	3-274
DL5D2/DL5D4.....	3-275
DL10D2/DL10D4.....	3-276
IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16	3-277
IVCD(11/13)/IVCD(22/26)/IVCD44.....	3-280
IVT/IVTD2/IVTD4/IVTD8/IVTD16	3-282
IVTN/IVTND2/IVTND4/IVTND8/IVTND16	3-284
NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16	3-286
OAK_NID10P/OAK_NID20P	3-289

NIT/NITD2/NITD4/NITD8/NITD16	3-290
NITN/NITND2/NITND4/NITND8/NITND16	3-293
OAK_DUCLK10/OAK_DUCLK16	3-296
CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/CTSBD8/CTSBD16.....	3-298
Flip-Flops	
FD1/FD1D2	3-303
FD1CS/FD1CSD2	3-305
FD1S/FD1SD2	3-307
FD1SQ/FD1SQD2.....	3-309
FD1Q/FD1QD2	3-311
FD2/FD2D2	3-313
FD2CS/FD2CSD2	3-315
FD2S/FD2SD2	3-319
FD2SQ/FD2SQD2.....	3-321
FD2Q/FD2QD2	3-323
FD3/FD3D2	3-325
FD3CS/FD3CSD2	3-327
FD3S/FD3SD2	3-331
FD3SQ/FD3SQD2.....	3-333
FD3Q/FD3QD2	3-335
FD4/FD4D2	3-337
FD4CS/FD4CSD2	3-340
FD4S/FD4SD2	3-344
FD4SQ/FD4SQD2.....	3-348
FD4Q/FD4QD2	3-351
FD5/FD5D2	3-353
FD5S/FD5SD2	3-355
FD6/FD6D2	3-357
FD6S/FD6SD2	3-359
FD7/FD7D2	3-361
FD7S/FD7SD2	3-363
FD8/FD8D2	3-365
FD8S/FD8SD2	3-368
FDS2/FDS2D2	3-372
FDS2CS/FDS2CSD2	3-374
FDS2S/FDS2SD2	3-376
FDS3/FDS3D2	3-378
FDS3CS/FDS3CSD2	3-380
FDS3S/FDS3SD2	3-382
FJ1/FJ1D2.....	3-384
FJ1S/FJ1SD2.....	3-386
FJ2/FJ2D2.....	3-388

FJ2S/FJ2SD2	3-390
FJ4/FJ4D2	3-392
FJ4S/FJ4SD2	3-395
FT2/FT2D2	3-398

Latches

LD1/LD1D2	3-402
LD1A/LD1D2A	3-404
LD1Q/LD1QD2	3-406
LD2/LD2D2	3-408
LD2Q/LD2QD2	3-411
LD3/LD3D2	3-413
LD4/LD4D2	3-416
LD5/LD5D2	3-419
LD5Q/LD5QD2	3-421
LD6/LD6D2	3-423
LD6Q/LD6QD2	3-426
LD7/LD7D2	3-428
LD8/LD8D2	3-431
OAK_LDI2/OAK_LDI2D2	3-434
OAK_LDI3/OAK_LDI3D2	3-437
LS0/LS0D2	3-442
LS1/LS1D2	3-444

Bus Holder

BUSHOLDER	3-448
-----------------	-------

Internal Clock Drivers

CK(2/4/6/8)	3-449
-------------------	-------

Decoders

DC4	3-452
DC4I	3-454
DC8I	3-456

Adders

FADH/FA/FAD2	3-461
HADH/HA/HAD2	3-464
SCG23/SCG23D2	3-467

Multiplexers

MX2DH/MX2/MX2D2/MX2D4	3-471
MX2X4	3-474
MX2IDH/MX2I/MX2ID2/MX2ID4	3-477
MX2IDHA/MX2IA/MX2ID2A/MX2ID4A	3-480

MX2IX4	3-483
MX3I/MX3ID2/MX3ID4	3-486
MX4/MX4D2/MX4D4	3-490
MX8/MX8D2/MX8D4	3-494

4 Input/Output Cells

Overview	4-1
Summary Tables	4-2

Input Buffers

PvIC/PvICD/PvICU	4-8
PvIS/PvISD/PvISU	4-12
PvIT/PvITD/PvITU	4-16

Output Buffers

PvOByz	4-20
PvODyz	4-29
PvOTyz	4-39

Bi-Directional Buffers

PvBaDyz/PvBaUDyz	4-59
PvBaTyz/PvBaDTyz/PvBaUTyz	4-59

Input Clock Drivers

PSCKDCaby	4-61
PSCKDSaby	4-65

Oscillators

PHSOSC(K1/K2/M1/M2/M3)	4-70
PHSOSC(K17/K27/M16/M26/M36)	4-76
PSOSC(K1/K2/M1/M2)	4-82

PCI Buffers

PTIPCI	4-89
PTOPCI	4-90
PTBPCI	4-91

USB I/O Buffers

PBUSB/PBUSB1	4-94
PBUSB_LS	4-95
PBUSB_FS	4-96

Power Pads

VDD2(I/P/O/IP/OP/T/R)/VDD3(P/O/OP)	4-103
VSS2(I/P/O/IP/OP/T/R)/VSS3(P/O/OP)	4-103

Analog Interface

PIC_ABB	4-105
PICC_ABB	4-106
PICEN_ABB	4-107
POT1/2/3/4_ABB	4-108

ESD Slot Cells

EV2I/EV2P/EV2O/EV2IP/EV2OP/EV2T/EV2P/EV2O/EV2OP	4-111
EV2I_ABB/EV2OP_ABB/EV2T_ABB	4-111

Common Slot Cells

EC0C0/EC0C0D/EC0CA0/EC0CA0D/EC0C0_BB/EC0C0D_BB/EC0C0_VBB/EC0C0D_VBB	4-112
---	-------

5 Compiled Macrocells

Overview to Compiled Memory	5-1
Compiled Memory Naming Convention	5-1
Characteristics for Timing and Power	5-2
Built-In Self Test for Compiled Memory	5-3
Selection Guide for Compiled Memory	5-4

High-Density Compiled Memory

SPSRAM_HD	5-7
SPSRAMBW_HD	5-17
DPSRAM_HD	5-27
SPARAM_HD	5-37
DROM_HD	5-48
MROM_HD	5-56
ARFRAM_HD	5-64
FIFO_HD	5-83

Low-Power Compiled Memory

SPSRAM_LP	5-95
DPSRAM_LP	5-105
SPARAM_LP	5-115
DROM_LP	5-125
MROM_LP	5-133

Contents

Overview to Compiled Datapath

Overview to Compiled Datapath5-141

Compiled Macrocell Selection Guide5-142

ADDER.....5-143

BS5-148

MPY5-153

6 PLL

PLL2013X6-1

NOTE

Introduction

1

Table of Contents

1.1	Library Description	1-1
1.2	Features	1-2
1.3	EDA Support.....	1-4
1.4	Product Family.....	1-4
	1.4.1 Analog Core Cells.....	1-4
	1.4.2 Internal Macrocells	1-12
	1.4.3 Compiled Macrocells	1-12
	1.4.4 Input/Output Cells.....	1-14
1.5	Timings	1-16
1.6	Delay Model.....	1-22
1.7	Testability Design Methodology	1-24
1.8	Maximum Fanouts	1-27
1.9	Packages Capability by Lead Count.....	1-34
1.10	Power Dissipation	1-37
1.11	V_{DD}/V_{SS} Rules and Guidelines	1-41
1.12	Crystal Oscillator Considerations	1-47

1.1 Library Description

Samsung ASIC offers STD111 as 0.25um CMOS standard cell library. Samsung's 0.25um cell-based logic process providing up to 5 layers of interconnect metal with various I/O pad-pitch options such as 70um pitch pad and 80um pitch pad.

STD111 which reduced power dissipation and system cost by merging the logic and IPs as a whole and connecting internally from logic to memory data bus is ideal for high-performance products such as graphics controller, projector, portable CD and so on.

STD111 can support up to six million gate counts of logic providing 75% of usable gate. STD111 is 25% faster than 0.35um library STD90. Logic density is 1.7 times greater than that of STD90. The power consumption of compiled memory is 90% smaller than STD90.

STD111 also supports fully user-configurable compiled memory and datapath elements. Each element is provided as a compiler. Two different types of compiled memories in STD111 are available to support memories suitable to high-density and low-power applications.

To support mixed voltage environments, 2.5V, 3.3V drive and 5V-tolerant IO cells are available. LVTTTL, LVCMOS, PCI, OSC, AGP, PECL, HSTL, LVDS and USB buffers are supported. To better support a system-on-chip design style, various core cells are available including processor cores like ARM7TDMI/ARM9TDMI/ARM920T/ARM940T from ARM, Teaklite from DSPG.

The STD111 supports data transmission and communication core such as USB, IEEE1284 and UART.

The list of analog core cells includes ADC, DAC, CODEC, LVDS, RAMDAC and PLL with various bits and frequency ranges.

Samsung design methodology offers an comprehensive timing driven design flow including automated time budgeting, tight floorplan synthesis intergration, powerful timing analysis and timing driven layout. Its advanced characterization flow provides accurate timing data and robust delay models for a 0.25um very deep-submicron technology. Advanced verification methods like static timing analysis and formal verification provide an effective verification methodology with a variety of simulators and cycle based simulation. Samsung DFT methodology supports scan design, BIST and JTAG boundary scan. Samsung provides a full set of test-ready IPs with an efficient core test integration methodology.

1.2 Features

- 2.5V standard cell library including processor and analog cores
- 0.25um five layer metal(from four layer metal option) CMOS technology
 - Logic, processor and analog
- High basic cell usages
 - Up to 6 million gates
 - Maximum usage: 75% for five layer metal
- High speed
 - Typical 2-input NAND gate delay (ND2D4): 68ps (F/O=2 + WL (0.02pF))
- Operation temperature (T_A)
 - Commercial range: 0°C to +70°C
 - Industrial range: -40°C to +85°C
- Digital cores usages
 - Hard-macro: ARM7TDMI, ARM9TDMI, ARM920T, ARM940T, Teaklite
 - Soft-macro: AMBA, DMA Controller, SDRAM Controller, Interrupt Controller, IIC, WDT, RTC, USB, IrDA, UART (16C450, 16C550), Fast Ethernet MAC, P1394a LINK, RS Decoder, Viterbi Decoder
- Analog cores usages
 - Ultra low voltage analog core (2.5V and 1.8V) available
 - Analog core supply voltage:
 - 2.5V analog core: $2.5V \pm 5\%$
 - 1.8V analog core: $1.8V \pm 5\%$
 - ADC: 8bit (30M, 2.5V), 10bit ((30M, 100M, 2.5V), (250K, 20M, 1.8V)), 12bit (200K, 20M, 2.5V)
 - DAC: 8bit (2M, 2.5V), 10bit ((300M, 2.5V), (2M, 1.8V)), 12bit ((2M, 2.5V), (80M, 1.8V))
 - CODEC: 8bit (8K~11K), 16bit (44.1K)
 - PLL: 25M ~ 300M (FSPLL, 2.5V), 1G (PLL, 2.5V), 20M ~ 170M (FSPLL, 1.8V)
 - Others: 300M (RAMDAC+PLL)
- Fully user-configurable Static RAMs and ROMs
 - High-density and low-power memory available
 - Duty-free cycle in synchronous memory available
 - 2-bank architecture available
 - Flexible aspect ratio available
 - Up to 256K-bit single-port SRAM available.
 - Up to 128K-bit dual-port SRAM available.
 - Up to 512K-bit diffusion and metal-2 ROM available.
 - Up to 16K-bit multi-port register file available.
 - Up to 32K-bit FIFO available.
- Fully configurable datapath macrocells
 - 4 ~ 64 bit adder available
 - 4 ~ 64 bit barrel shifter available
 - 6 ~ 64 bit multiplier with 1-stage pipeline available
 - Various output driver strength available
 - A tightly integrate apollo, Avant!, design environment
- I/O cells
 - 2.5V/3.3V and 5V tolerant IO
 - 3-level (high, medium, no) slew rate control
 - 1/2/4/6/8/10/12mA available for 3.3V and 2.5V output buffers
 - 1/2/3mA available for 5V-tolerant output buffers

- IO IP available
 - PCI ((33MHz, 66MHz, 3.3V), (33MHz, 3.3/5V tolerant))
 - USB (full speed/low speed)
 - SSTL2 (DDR SDRAM interface, up to 200MHz)
 - AGP (AGP2.0 Compliant, 66MHz@1X, 133MHz@2X, 266MHz@4X)
 - PECL (2.5V interface, up to 400MHz)
 - HSTL (class1, class2, 30MHz)
 - LVDS (3.3V(2.5V optional) interface, 300MHz)
- Various package options
 - QFP, thin QFP, power QFP, plastic BGA, super BGA, plastic leaded chip carrier, etc.
- Fully integrated CAD software and EDA support
 - Logic synthesis: Synopsys Design Compiler
 - Logic simulation: Cadence Verilog-XL, Cadence NC-Verilog, Viewlogic ViewSim, Mentor ModelSim-VHDL, Mentor ModelSim-Verilog, Synopsys VSS, Synopsys VCS
 - Scan insertion and ATPG: Synopsys TestGen, Synopsys Test Compiler, Mentor Fastscan
 - Static timing analysis: Synopsys PrimeTime, Synopsys MOTIVE
 - RC analysis: Avant! Star-RC
 - Power analysis: Synopsys DesignPower, CubicPower (In-House Tool)
 - Formal verification: Synopsys Formality, Chrysalis Design VERIFYer, Verplex Tuxedo-LEC
 - Fault simulation: Cadence Verifault, SuperTest (In-House Tool)
 - Delay calculator: CubicDelay (In-House Tool)
- STD111 contains 12 user selectable clock tree cells(CTC). At the pre-layout design stage, these will be used as the cells which represent actual clock tree informatin of P&R. The key features of new Samsung ASIC CTS flow are as follows:
 - 12 user selectable clock tree cells (CTC) for STD111
 - Good pre-layout and post-layout correlation
 - No customer netlist modification
 - Accurate post-layout back-annotation mechanism
 - Insertion delay, skew, transition time management
 - Clock tree information file generation
 - Cover 100 to 30,000 fanouts and up to 1M gate count for CTS spanning block (GCCSB)
 - Tightly coupled with Samsung in-house delay calculator, CubicDelay Gated CTS support
 - Hierarchical/Flatten verilog, edif interface for P&R

For more detail information for CTC flow, refer to "CTC flow guideline for CubicDelay" included in Samsung ASIC design kit.

1.3 EDA Support

Samsung ASIC provides an efficient solution for multi-million gate ASICs in very deep submicron (VDSM) technology. For large system-on-chip (SOC) type designs, static verification methodology (static timing analysis and formal verification) will shorten your design cycle time, which in turn will lessen today's ever-increasing time-to-market pressure. Our Design-for-Test (DFT) methodology and service take you through all phases of test insertion, test pattern generation and fault grading to get high test coverage.

STD111 supports a rich collection of industry-standard EDA tools from Cadence, Synopsys, Mentor graphics, and Avant! on multiple design platforms such as Solaris and HP. Customers are allowed to choose among the industry-leading EDA tools from design capture, synthesis, simulation, and DFT to layout. Several powerful proprietary software tools are seamlessly integrated in our design kits to improve your product quality.

For high simulation accuracy, STD111 uses a proprietary delay calculator. Cell delay is calculated based on a matrix of delay parameters for each macrocell, and signal interconnect delay is calculated based on the RC tree analysis.

1.4 Product Family

STD111 library include the following design elements:

- Analog core cells
- Digital core cells
- Internal macrocells
- Compiled macrocells
- Input/Output cells.

1.4.1 ANALOG CORE CELLS

Introduction to Analog Cores

Samsung ASIC is one of the leading suppliers of cell based mixed analog and digital designs. As a leading supplier of mixed analog and digital designs, Samsung ASIC has more analog design experience than any other vendors. Analog has been and will continue to be a part of the strategic focus at Samsung ASIC. Analog design is a part of the total Samsung ASIC integrated design system. Workstation symbols are supplied for analog cells and are entered as part of the design by the customer or design center. Samsung ASIC uses basically the same automatic layout and verification tools for analog cells as for digital cells. Analog designs are processed on the same production line as digital designs.

Samsung's analog core family comprises ADC, DAC, PLL and sigma-delta ADC/DAC, and their brief functional descriptions are introduced below.
[data sheets for all analog cores available]

Analog-to-Digital Converters

Analog-to-digital converters provide the link between the analog world and digital systems. Due to their extensive use of analog and mixed analog-digital operations, A/D converters often appear as the bottleneck in data processing applications, limiting the overall speed or precision.

An A/D converter produces a digital output, D, as a function of the analog input, A:

$$D = f(A)$$

While the input can assume an infinite number of values, the output can be selected from only a finite set of codes given by the converter's output word length(i.e, resolution). Thus, the ADC must approximate each input level with one of these codes, this process is so called 'quantization'.

In a digital system the amplitude is quantized into discrete steps, and at the same time the signal is sampled at discrete time intervals. This time interval is called sampling time or sampling frequency. After sampling and quantization process, the analog signal(A) becomes digital output (D).

Digital-to-Analog Converters

The D/A converters are the digital-to-analog conversion circuits, which are also called DACs. They can be considered as decoding devices that accept digitally coded signals and provide analog output in the form of currents or voltages. In this manner, they provide an interface between the digital signal of the computer systems and continuous signals of analog world. They are employed in a variety of applications, from CRT display systems and voice synthesizers to automatic test systems, digital controlled attenuators, and process control actuators. In addition, they are key components inside most A/D converters.

Figure 1 shows the functional block diagram of a basic D/A converter system. The input to the D/A converter is a digital word, made up a stream of binary bits comprised of 1's and 0's. The output analog quantity A, which can be a voltage or current, is related to the input as

$$A = KV_{REF} \left[\frac{b1}{2^1} + \frac{b2}{2^2} + \dots + \frac{bn}{2^n} \right]$$


where K is a scale factor, V_{REF} is a reference voltage, n is the total number of bits, and $b1, b2, \dots, bn$ are the bit coefficients, which are quantized to be a 1 or a 0.

As a function of the input binary word which determines the bit coefficients, the output exhibits 2^n discrete voltage level ranging from zero to a maximum value of

$$V_o(\max) = V_{REF} \frac{2^n - 1}{2^n}$$

with a minimum step change ΔV_o given as $\Delta V_o = \frac{V_{REF}}{2^n}$

Figure 1-1. Functional Block Diagram of Basic D/A Converter



Sigma-Delta ADC/DAC

VLSI offers high speed and high density, but reduced accuracy for analog components and reduced signal range (reduced dynamic range). Hence, an exchange of digital complexity and of resolution in time for resolution in signal amplitude is needed. So good solution is over-sampling data converter. Oversampling sigma-delta converter is used in slow speed (audio band) application because of process limit. It's noise shaping (sigma-delta) feature make high resolution about max. $SND=90\sim100dB$

In ADC path, analog single input is converted to differential signal with anti-aliasing filtering through anti-aliasing filter block. And sigma-delta modulator converts the signal into oversampled noise-shaping 1bit PDM (Pulse Density Modulation). Following digital decimation filter reject the out of band noise and outputs 16bits high resolution digital data with down sampled to F_s rate. In DAC path, digital input data is oversampled by interpolation filter and it is converted to noise-shaped 1bit PDM through digital sigma-delta modulator. Analog SC-post-filter rejects the out of band noise. And anti-image filter rejects sampling images and outputs single analog signal with high resolution.

Phase Locked Loop

Samsung's PLL cores implemented as an analog function provide frequency multiplication capabilities and enable system designers to synchronize ASIC chip-level clock networks with a common reference signal.

In the past, designers wishing to incorporate a PLL into a digital design environment had only two options:

- (1) A special mixed-signal process to incorporate analog functions onto the chip
- (2) An all digital PLL that can be incorporated into a standard digital process.

However, a mixed-signal process is too expensive to be a feasible solution. On the other hand digital PLLs typically require huge silicon area and exhibits poor locking time despite their high accuracy.

Differing from the previous solutions, Samsung's PLL cores can be implemented on standard digital CMOS process while functioning as an analog PLL.

Samsung's PLL cores:


- * Require only a few off-chip passive components for the whole function
- * Remove the need for an expensive mixed-signal process
- * Provide faster locking time than all digital PLLs
- * Present low jitter characteristics

Glossary by Core Families

1. Digital-to-Analog Converter

1. Resolution - An n-bit binary converter should be able to provide 2^n distinct and different analog output values corresponding to the set of n-bit binary words. A converter that satisfies this criterion is said to have resolution of n bits. The smallest output change that can be resolved by a linear DAC is 2^{-n} of the full-scale span.

2. Accuracy - Error of a D/A converter is the difference between the actual analog output and the output that is expected when a given digital code is applied to the converter. Source of error include gain error, offset error, linearity errors and noise. Error is usually commensurate with resolution, less than $2^{-(n+1)}$, or 1/2 LSB of full scale.

Figure 1-2. Error of D/A Converter

3. LSB (Least-Significant Bit) - In a system in which a numerical magnitude is represented by a series of binary digits, the LSB is that bit that carries the smallest value or weight. It represents the smallest analog change that can be resolved by an n-bit converter.

$$\text{LSB (Analog Value)} = \text{FSR}/2^n$$

FSR = Full-Scale Range, n = number of bits

4. MSB (Most-Significant Bit) - The binary digit with the largest numerical weighting. Normally, the MSB of a digital word has a weighting of 1/2 the full range.

5. Compliance-Voltage Range - For a current output DAC, the maximum range of (output) terminal voltage for which the device will provide the specified current-output characteristics.

6. Glitch - A glitch is a switching transient appearing in the output during a code transition. Its value is expressed as a product of voltage (V*ns) or current (mA*ns) and time duration or charge transferred.

7. Harmonic Distortion (and Total Harmonic Distortion) - The DAC is driven by the digitized representation of sine wave. The ratio of the RMS sum of the harmonics of the DAC output to the fundamental value is the THD. Usually only the lower order harmonics are included, such as second through fifth.

$$\text{THD} = 20 \log \frac{(V_2^2 + V_3^2 + V_4^2 + V_5^2)^{1/2}}{V_1}$$

V1: RMS amplitude of the fundamental


8. Signal-to-Noise Ratio (SNR) - This signal to noise ratio depends on the resolution of the converter and automatically includes specifications of linearity, distortion, sampling time uncertainty, glitches, noise, and settling time. Over half the sampling frequency, this signal to noise ratio must be specified and should ideally follow the theoretical formula;

$$\text{S/N}_{\text{max}} = 6.02N + 1.76\text{dB}$$

9. Slew Rate - Slew rate of a device or circuit is a limitation in the rate of change of output voltage, usually imposed by some basic circuit consideration such as limited current to charge of capacitor. Amplifiers with slew rate of a few V/μs are common and moderate in cost. Slew rates greater than about 75 V/μs are usually seen only in more sophisticated (and expensive) devices. The output slewing speed of a voltage-output D/A converter is usually limited by the slew rate of the amplifier used at its output (if one is used).

10. Settling Time - The time required, following a prescribed data change from the 50% point of the login input change, for the output of a DAC to reach and to remain within a given fraction (usually $\pm 1/2\text{lsb}$) of the final value. Typical prescribed changes are full scale, 1MSB and 1LSB at a major carry. Settling time of current-output DACs is quite fast. The major share of settling time of a voltage-output DAC is usually contributed by the settling time of the output op-amp circuit.

Figure 1-3. Setting Time



11. Power-Supply Sensitivity - The sensitivity of a converter to changes in the power-supply voltages is normally expressed in terms of percent-of-full-scale change in analog output value (of fractions of 1LSB) for a 1% dc change in the power supply. Power supply sensitivity may also be expressed in relation to a specified dc shift of supply voltage. A converter may be considered "good" if the change in reading at full scale does not exceed $1/2\text{LSB}$ for 3% change in power supply. Even better specs are necessary for converters designed for battery operation.

12. ILE (integral Linearity Error) - Linearity error of a converter, expressed in %, ppm of full-scale range or multiples of 1LSB, is a deviation of the analog values in a plot of the measured conversion relationship from a straight line. The straight line can be either a "best straight line" determined empirically by manipulation of the gain and/or offset to equalize maximum positive and negative deviation of the actual transfer characteristics from this straight line; or it can be a straight line passing through the endpoints of the transfer characteristic endpoints of the transfer characteristic after they have been calibrated (sometimes referred to as "endpoint" linearity). Endpoint linearity error is similar to relative accuracy error. For multiplying D/A converters, the analog linearity error, at a specified digital code, is defined in the same way as for multipliers, by deviation from a "best straight line" through the plot of the analog output-input response.

13. DLE (Differential Linearity Error) - Any two adjacent digital codes should result in measured output values that are exactly 1LSB apart (2^{-n} of full scale for an n -bit converter). Any deviation of the measured "step" from the ideal difference is called differential linearity error expressed in multiples of 1LSB. It is an important specification because a differential linearity error greater than 1LSB can lead to non-monotonic response in a D/A converter and missed codes in an A/D converter.

14. Monotonic - A DAC is said to be monotonic if the output either increases or remains constant as the digital input increases with the result that the output will always be a single-valued function of the input. The specification "monotonic"

(over a given temperature range) is sometimes substituted for a differential nonlinearity specification since differential nonlinearity less than 1LSB is a sufficient condition for monotonic behaviour.

2. Analog-to-Digital Converter

1. ILE (Integral Linearity Error: INL) - Integral nonlinearity refers to the deviation of each individual code from a line drawn from "zero" through "full scale". The point used as "zero" occurs 1/2LSB before the first code transition. "Full scale" is defined as a level 1 1/2LSB beyond the last code transition. The deviation is measured from the center of each particular code to the true straight line.

2. DLE (Differential Linearity Error: DNL) - An ideal ADC exhibits code transitions that are exactly 1LSB apart. DNL is the deviation from this ideal value. It is often specified in terms of the resolution for which no missing codes are guaranteed.

3. Offset Error - The first transition should occur at a level 1/2LSB above "zero". Offset is defined as the deviation of the actual first code transition from that point.

4. Gain Error - The first code transition should occur for an analog value 1/2LSB above nominal negative full scale. The last transition should occur for an analog value 1 1/2LSB below the nominal positive full scale. Gain error is the deviation of the actual difference between first and last code transitions and the ideal difference between the first and last code transitions.

5. Pipeline Delay (Latency) - The number of clock cycles between conversion initiation and the associated output data being made available. New output data is provided every clock cycle.

6. Effective Number of Bits (ENOB) - This is a measure of a device's dynamic performance and may be obtained from the SNDR or from a sine wave curve test fit according to the following expression:

$$\text{ENOB} = \text{SNDR} - 1.76/6.02$$

$$\text{ENOB} = N - \log_2[\text{RMS error (actual)} / \text{RMS error (ideal)}]$$

7. Analog Bandwidth - The analog input frequency at which the spectral power of the fundamental frequency, as determined by FFT analysis is reduced by 3dB.

8. Aperture Delay - The delay between the sampling clock and the instant the analog input signal is sampled.

9. Aperture Jitter - The sample to sample variation in aperture delay.

10. Bit Error Rate (BER) - The number of spurious code errors produced for any given input sine wave frequency at a given clock frequency. In this case it is the number of codes occurring outside the histogram cusp for a 1/2 FS sine wave.

11. Signal to Noise Ratio - This signal to noise ratio depends on the resolution of the converter and automatically includes specifications of linearity, distortion, sampling time uncertainty, glitches, noise, and settling time. Over half the sampling frequency, this signal to noise ratio must be specified and should ideally follow the theoretical formula;

$$\text{S/N}_{\text{max}} = 6.02N + 1.76\text{dB}$$

3. Phase Locked Loop


1. Lock Time - The time it takes the PLL to lock onto the system clock. Fast or slow lock time may be controlled by the loop filter characteristics. The loop filter characteristics are controlled by varying the R and C components. (Remember that R and C define the damping-factor as well)

2. Phase Error - The phase difference between the feedback clock signal and the system signal clock.

3. Clock Jitter - The deviations in a clock's output transitions from their ideal positions define the clock jitter. Jitter is sometimes specified as an absolute value in nanoseconds. All jitter measurement are made at a specified voltage.

1) Cycle-to-Cycle Jitter: The change in a clock's output transition from its corresponding position in the previous cycle. This kind of jitter is the most difficult to measure and usually requires a time-interval analyzer


Figure 1-4. Cycle-to-Cycle Jitter



: The maximum of such values over multiple cycles (J_1, J_2, \dots) is the max. cycle-to-cycle jitter.

2) Period Jitter: Period jitter measures the maximum change in a clock's output transition from its ideal position. You can use period-jitter measurements to calculate timing margins in systems.

Figure 1-5. Period Jitter



3) Long-term Jitter: Long-term jitter measures the maximum change in a clock's output transition from its ideal position over many cycles. How many cycles depends on the application and the frequency. A classic example of system affected by long-term jitter is a graphics card driving a CRT

4) Power Down Mode: PLL state in which the quiescent current is lowered to a very low level to conserve power.

5) Synthesize clock: a system clock may run at a relatively low rate compared to system components. A CPU, for example, may require an internal clock that is several times faster than the system I/O bus clock. Designers can use PLL technology to synthesize a higher frequency on-chip clock using the system clock as a reference.

6) Deskeiw clock: Multiple chips on a printed circuit board or cores of different sizes within a single system on a chip experience clock skew. By using PLL or DLL technology to shift the phase of the reference clock within each chip or core, designers can minimize skew tune a system to perform up its potential.

7) Duty Ratio: the percentage of the period that the output is in a high state.

8) Output frequency range: The maximum output frequency range minus the minimum output frequency that is produced with an input signal for which the cell specifications still apply.

Customer Service

Samsung provides a full custom support for our customers need of analog cores. Samsung's worldwide sales offices and representatives give our customers a first-hand support for analog cores. And if needed, Samsung engineers are prepared to provide a fully customized total solution to satisfy our customers.

Technical Support

If our customers want to develop mixed-signal products, Samsung provides all technical support to meet customers needs. Mixed-signal design is quite different from pure logic design in terms of circuit design, techniques, layout and test methodology. Thus Samsung provides a successful technical guide and firmly support for all development steps.

Definition of Analog Core Data Sheet Types

Each product developed by Samsung will be supported by technical literature where the data sheets progress through the following levels of refinement

1. Core Preview

Describes the main features and specifications for core that is under development. Some specifications such as exact pin-outs may not be finalized at time of publication. The purpose of this document is to provide customers with advance product planning information.

2. Preliminary Datasheet

This is the first document completely describing a new core. It contains an features, application, timing diagram, theory of operation, core pin information, test guide, layout guide and AC/DC electrical information. This data sheet are based on prototype silicon performance and on worst case simulation models. The purpose of this data sheet is to provide ASIC customer with technical information sufficiently detailed to guarantee that they can safely begin active development.

3. Final Data sheet

This is an updated version of preliminary data sheet reflecting actual performance of the final silicon. Updates include tighter specifications, more min. and max. values. The purpose of this data sheet is to communicate the confirmed performance of cores which have passed qualification, been fully characterized.

1.4.2 INTERNAL MACROCELLS

Internal Macrocells are the lowest level of logic functions such as NAND, NOR and flip-flop used for logic designs. There are about 471 different types of internal macrocells. They usually come in four levels of drive strength (0.5X, 1X, 2X and 4X).

These macrocells have many levels of representations—logic symbol, logic model, timing model, transistor schematic, HSPICE netlist, physical layout, and placement and routing model.

1.4.3 COMPILED MACROCELLS

Compiled macrocells of STD111 consist of compiled memory and compiled datapath macrocells.

1.4.3.1 Compiled Memory Macrocells

Memories in STD111 are fully user-configurable and are provided as a compiler. Two different types of memories are available in STD111. One is suitable for high-density application with high-performance, called STD111-HD compiled memory. The other is suitable for low-power application, called STD111-LP compiled memory.

In STD111-HD compiled memory, eight types of memories are available such as single-port synchronous/asynchronous static RAM, dual-port synchronous static RAM, synchronous diffusion/metal-programmable ROM, multi-port asynchronous register file and synchronous first-in first-out memory. Synchronous memories have a fully synchronous operation at the rising-edge of clock and the duty-free cycle is available. Also, the bit-write capability is available. Asynchronous memories have a synchronous operation for a write enable signal during write mode and have an asynchronous operation for address signal during read mode. Multi-port asynchronous register file supports four kinds of configurations such as 2 port(1-read/1-write), 3 port(1-read/2-write and 2-read/1-write) and 4 port (2-read/2-write). The first-in first-out memory which is widely used in communication buffering types of applications has also fully synchronous operation at the rising- edge of clock.

On the other hand, in STD111-LP compiled memory, five types of memories are available such as single-port synchronous/asynchronous static RAM, dual-port synchronous static RAM and synchronous diffusion/metal-programmable ROM. Synchronous memories are almost same as that of STD111-HD except that the duty-free cycle is not available. Asynchronous memory is same as that of STD111-HD.

To dramatically reduce the power consumption in STD111-LP, some of low-power techniques such as a partial activation architecture in cell array and a divided word-line structure was adopted, rather than STD111-HD.

Basically in STD111-HD and STD111-LP, the power-down mode which significantly reduces the power dissipated during a read or write mode is provided. Also compiled memories have a standby mode except multi-port asynchronous register file and first-in first-out memory. While in standby mode, the data stored in the memory is retained, data outputs remain stable and the power is greatly reduced because memory operation is internally blocked while the memory contents and the data outputs are unaffected.

To improve the memory performance and to reduce the power consumption, 2-bank architecture is provided except some memories such as dual-port synchronous static RAM, multi-port asynchronous register file and first-in first-out memory. In 2-bank architecture, only one bank is activated and the other bank is in standby mode.

To support various memory shapes which are determined by the floorplan of a chip design, flexible memory aspect ratios are provided. For certain specific memory configuration, all types of timing, power and area values are provided by an automatic datasheet generator.

To easily do interface to layout, the physical abstract data for Silicon Ensemble and Apollo, called phantom cell or black box, is provided. BIST(Built-In Self-Test) circuitry is currently available for most of STD111 compiled memories. BIST circuits are designed to detect a set of fault types that impact the functionality of memory and is generated by a softmacro-based BIST generator.

The softmacro-based BIST generator generates both an individual BIST netlist for each memory and a shared BIST netlist for all memories used in a design. However, when several memories of the same or the different type area used in the design, if you generate the individual BIST netlist for each memory, there are some redundant blocks because the individual BIST netlist has same function. In this case, it would better use the shared BIST netlist to eliminate such redundancy and reduce area.

1.4.3.2 Compiled Datapath Macrocells

Compiled datapath macro cells include Adder, Barrel Shifter and Multiplier. Adder performs the adding or adding/subtracting operation on the control of a mode selection signal. Barrel Shifter makes input data shift or rotate in the left/right direction. In the shift operation, the vacant bit can be padded with zero, MSB value, or external data. Multiplier performs the 2's compliment multiplication. One pipeline stage insertion is available to get a high operating frequency.

They have two output drive strengths, which are equal to the 1X and 2X-Drive in the primitive cell library. The hard macro cells are built through the Apollo, placement and routing tool from Avant!. All the leaf cells have the same physical configuration compatible with the primitive cell library. It allows that any primitive cell can be used as a bit slice cell in the datapath module design.

We provide two kinds of engineering design services. One is to support additional compiled datapath macrocells such as ALUs, Comparators, Priority encoders, Incrementers and Decrementers, and so on. Another is to make hardwired datapath module design which provides a regular structured layout.

1.4.4 INPUT/OUTPUT CELLS

There are about seven hundreds different I/O buffers. Each I/O cell is implemented solely on the basic I/O cell architecture which forms the periphery of a chip.

A test logic is provided to enable the efficient parametric (threshold voltage) testing on input buffers including LVCMOS and TTL level converters, Schmitt trigger input buffers, clock drivers and oscillator buffers. Pull-up and pull-down resistors are optional features.

Three basic types of output buffers (non-inverting, tri-state and open drain) are available in a range of driving capabilities from 1mA to 12mA for 2.5V, 3.3V drive and from 1mA to 3mA for 5.0V tolerant drive. One or two levels of slew rate controls are provided for each buffer type (except 1mA, 2mA and 3mA buffers) to reduce output power/ground noise and signal ringing, especially in simultaneous switching outputs.


Bi-directional buffers are combinations of input buffers and output buffers (tri-state and open drain) in a single unit. The I/O structure has been fully characterized for ESD protection and latch-up resistance.

For user's convenience, STD111 library provides 100K Ω pull-down and pull-up resistance respectively.

1.4.4.1 I/O Applications

To support mixed voltage environments, LVTTTL, LVCMOS and Schmitt trigger I/O cells are available at 2.5V, 3.3V interface and 5V tolerant interface. The I/O application diagram is as follows.

Figure 1-6. I/O Applications



1.4.4.2 I/O Cell Drives Options

To provide designers with the greater flexibility, each I/O buffer can be selected among various current levels (e.g., 1mA, 2mA,..., 12mA). The choice of current-level for I/O buffers affects their propagation delay and current noise.

The slew rate control helps decrease the system noise and output signal overshoot/undershoot caused by the switching of output buffers. The output edge rate can be slowed down by selecting the high slew rate control cells.

STD111 provides three different sets of output slew rate controls. Only one I/O slot is required for any slew rate control options.


1.4.4.3 5V Tolerant I/O Buffers

STD111 I/O library is based on a process which has the most optimum performance in 2.5V.

In this process, voltage more than 3.6V are not allowed at the gate oxide because of a reliability problem. And a special circuit is adopted in order to make pin voltage tolerable up to 5.25V and to offer TTL interface driving up to 3mA. Obviously, this circuit is constructed not to permit more than 3.6V at the gate oxide. The external circuit diagram is as follows.

The maximum external tolerance of this buffer is 5.25V. It can be used as a 3.3V normal buffer.

Figure 1-7. 5V Tolerant I/O Buffers



1.4.4.4 PCI Buffers

PCI buffers are designed for PCI local bus application which is an industry-standard, high-performance 32bit or 64bit bus architecture. Samsung ASIC offers input, output, bi-directional PCI buffers for 33MHz and 66MHz operation. These buffers are compliant with PCI local bus specification 2.1.

1.4.4.5 USB (Universal Serial Bus) Buffers

Various kinds of peripheral equipment such as mouse, joy stick, keyboard, modem, scanner and printer improve the power of a computer. However, it is not easy to connect and use them properly in the computer.

USB specification established late in 1995 is a good solution for this problem, providing facile method of an expansion. Samsung ASIC offers full speed and low speed USB buffers that complies with Universal Serial Bus specification 1.0, 1.1.

1.4.4.6 Other Buffers

Samsung ASIC can support various kinds of buffers such as HSTL, SSTL, AGP, PECL, LVDS, and so on. For more information please contact us.

1.5 Timings

1.5.1 WIRE LENGTH LOAD

Table 1-1. shows the equivalent standard load matrix for 4-layer and 5-layer metal interconnect. The equivalent standard load values are function of gate count and fanout. These values are based on capacitive loading and are used in wire length estimates which affect propagation delay.

Table 1-1. Equivalent Standard loads for 4-layer and 5-layer Metal Interconnect

Gates Count	Fanouts										
	1	2	3	4	5	6	7	8	16	32	64
4LM											
5000	0.701	1.357	2.312	3.093	3.609	4.247	4.755	6.622	17.348	27.615	48.295
10000	0.926	1.774	3.365	4.660	5.423	6.353	7.327	9.203	18.092	28.876	50.533
50000	2.536	4.990	7.526	9.980	10.165	10.879	12.722	13.798	21.501	29.252	51.190
100000	2.780	5.643	8.425	11.207	11.429	12.247	14.168	16.355	24.808	32.825	57.446
150000	7.770	10.361	12.952	13.724	14.279	14.700	15.732	17.988	24.098	38.524	77.049
200000	8.180	10.907	13.633	14.451	15.035	15.478	16.561	18.937	25.330	40.496	80.963
300000	8.998	11.998	14.997	16.087	16.697	17.161	18.343	20.955	27.994	44.696	89.297
400000	9.816	13.088	16.247	17.360	18.057	18.586	19.887	22.677	30.262	48.227	96.358
500000	10.951	14.601	18.252	19.468	20.229	20.807	22.252	25.431	32.210	51.345	102.531
600000	11.723	15.632	19.650	20.930	21.730	22.338	23.880	27.339	33.134	52.828	105.472
800000	13.507	18.010	22.834	24.270	25.165	25.847	27.615	31.704	35.807	57.110	113.982
1000000	15.174	20.232	25.809	27.392	28.376	29.127	31.104	35.779	38.289	61.088	121.885
1500000	19.743	26.325	33.911	35.904	37.138	38.085	40.643	46.899	45.765	73.055	145.688
2000000	24.024	32.032	41.504	43.880	45.352	46.480	49.581	57.320	52.758	84.249	167.954
2500000	28.030	37.374	48.611	51.347	53.036	54.338	57.946	67.072	59.291	94.706	188.751
3000000	31.775	42.367	55.254	58.326	60.221	61.682	65.764	76.187	65.385	104.459	208.150
4000000	36.455	48.606	63.391	66.915	69.090	70.765	75.450	87.407	75.013	119.844	238.804
4500000	38.642	51.522	67.194	70.930	73.235	75.011	79.978	92.651	79.513	127.034	253.132
5LM											
5000	0.666	1.289	2.197	2.938	3.429	4.035	4.517	6.291	16.480	26.235	45.880
10000	0.880	1.686	3.196	4.427	5.152	6.036	6.961	8.743	17.188	27.432	48.007
50000	2.409	4.740	7.150	9.481	9.657	10.335	12.086	13.109	20.426	27.789	48.630
100000	2.642	5.361	8.004	10.647	10.857	11.634	13.555	15.537	23.568	31.184	54.574
150000	7.382	9.843	12.304	13.038	13.565	13.965	14.945	17.089	22.893	36.598	73.197
200000	7.770	10.361	12.952	13.729	14.283	14.705	15.733	17.990	24.064	38.471	76.915
300000	8.548	11.398	14.247	15.283	15.862	16.302	17.426	19.908	26.595	42.461	84.832
400000	9.326	12.433	15.434	16.492	17.155	17.656	18.892	21.543	28.749	45.816	91.512
500000	10.403	13.871	17.339	18.495	19.218	19.767	21.139	24.160	30.599	48.778	97.404
600000	11.137	14.850	18.667	19.883	20.643	21.220	22.686	25.972	31.477	50.187	100.199
800000	12.832	17.110	21.692	23.056	23.908	24.555	26.235	30.119	34.016	54.255	108.284
1000000	14.415	19.220	24.519	26.022	26.957	27.670	29.549	33.990	36.375	58.034	115.790
1500000	18.756	25.009	32.216	34.109	35.282	36.181	38.611	44.554	43.477	69.403	138.404
2000000	22.823	30.431	39.429	41.687	43.084	44.156	47.102	54.454	50.120	80.036	159.556
2500000	26.629	35.505	46.180	48.779	50.385	51.621	55.049	63.718	56.326	89.971	179.313
3000000	30.186	40.249	52.491	55.410	57.211	58.598	62.476	72.377	62.115	99.237	197.743
4000000	34.633	46.176	60.221	63.569	65.635	67.227	71.678	83.036	71.262	113.852	226.863
5000000	38.832	51.777	67.527	71.279	73.597	75.382	80.372	93.108	79.907	127.662	254.382
6000000	43.542	58.057	75.716	79.926	82.525	84.525	90.121	104.403	89.598	143.146	285.238


1.5.2 TIMING PARAMETERS

This section discusses issues involving timing parameters.

1.5.2.1 Transition Time

Figure 1-8. shows the definition of rise transition time (t_R) and fall transition time (t_F). Transition time is defined as the delay between the time when the input (output) signal voltage level is 10% of supply voltage (V_{DD}) and the time of the input (output) signal voltage level is 90% of V_{DD} .


Figure 1-8. Rise and Fall Transition Times



1.5.2.2 Propagation Delays

Figure 1-9. shows the definition of propagation delays. Propagation delay is defined as the delay between the time when the input signal voltage level is 50% of supply voltage (V_{DD}) and the time when the output signal voltage level is 50% of V_{DD} .

Figure 1-9. Propagation Delay




1.5.2.3 Setup / Hold Time

Figure 1-10. shows the definition of setup time and hold time. The setup timing check is defined as the minimum interval which a data signal must remain stable before active transition of a clock. Any change to the data signal within this interval results in a timing violation.

The hold timing check is defined as the minimum interval which a data signal must remain stable after active transition of a clock. Any change to the data signal within this interval results in a timing violation.

Figure 1-10. Setup and Hold Times




1.5.2.4 Recovery Times

Figure 1-11. shows the definition of recovery time. A recovery timing check measures the time between the release of an asynchronous control signal from the active state to the next active clock edge.

For example, the time between RN and the CK of FD2 cell. If the active edge of the CK occurs too soon after the release of the RN, the state of the FD2 becomes uncertain. The state can be the value set by the RN or the value clocked into the FD2 from the data input.

Figure 1-11. Recovery Time




1.5.2.5 Removal Times

Figure 1-12. shows the definition of removal time. A removal timing check measures the time between the active clock edge and the release of an asynchronous control signal from the active state.

For example, the time between RN and the CK of FD2 cell. If the release of the RN occurs too soon after the active edge of the clock, the state of the FD2 becomes uncertain. The uncertainty can be caused by the value set by the RN or the value clocked into the FD2 from the data input.


Figure 1-12. Removal Time



1.5.2.6 Minimum Pulse Widths

Figure 1-13. shows the definition of minimum pulse width. The minimum pulse width timing check is the minimum allowable time for the positive (high) or negative (low) phase of each cycle.


Figure 1-13. Minimum Pulse Width



1.5.2.7 Minimum Period

Figure 1-14. shows the definition of minimum period. The minimum period timing check is the minimum allowable time for one complete cycle of the signal.

Figure 1-14. Minimum Period




1.5.3 TEMPERATURE AND SUPPLY VOLTAGE

The next figure describes propagation delay derating factors (K_T , K_V) as a function of on-chip junction temperature (T_J) and supply voltage (V_{DD}). As a result of power dissipation, the junction temperature is generally higher than the ambient temperature.

The temperature of the die inside the package (junction temperature, T_J) is calculated using chip power dissipation and the thermal resistance to the ambient temperature (θ_{JA}) of the package. Information on package thermal performance can be obtained from Samsung application engineers.

Figure 1-15. Effect of Temperature and Supply Voltage on Propagation Delay



1.5.4 BEST AND WORST CASE CONDITIONS

A circuit should be designed to operate properly within a given specification level, either commercial or industrial. It is recommended that circuits be simulated for best case, normal case, and worst case conditions at each specification level.

The following expressions also allow for the effect of process variation on circuit performance.

Best case (Worst case):

$$T_{BC} (T_{WC}) = K_P \times K_T \times K_V \times T_{NOM}$$

where

T_{BC} = Best case propagation delay

T_{WC} = Worst case propagation delay

T_{NOM} = Normal propagation delay

($T_J = 25^\circ\text{C}$, $V_{DD} = 2.5\text{V}$ and typical process)

K_P , K_T , K_V = Refer to Table 1-2., Table 1-3., and Table 1-4.

1.5.5 DERATING FACTORS OF STD111

The multipliers can be applied to nominal delay data in order to estimate the effects of supply voltage, temperature and process. Nominal data are provided for conditions of $V_{DD} = 2.5\text{V}$, $T_J = 25^\circ\text{C}$ and typical process.

The derating factors of STD111 is as follows.

Table 1-2. STD111 cell process derating factor (K_P)

Process Factor (K_P)	Slow	Typ	Fast
	1.200	1.0	0.849

Table 1-3. STD111 cell temperature derating factor (K_T)

Temp. ($^\circ\text{C}$)	125	85	70	25	0	-40
K_T	1.144	1.087	1.065	1.000	0.964	0.906

Table 1-4. STD111 cell voltage derating factor (K_V)

Voltage (V)	2.3	2.5	2.7
K_V	1.074	1.000	0.941


1.6 Delay Model

The ASIC timing characteristics consist of the following components:

- Cell propagation delay from input to output transitions based on input waveform slope, fanout loads and distributed interconnection wire resistance and capacitance.
- Interconnection wire delay across the metal lines.
- Timing requirement parameters such as setup time, hold time, recovery time, skew time, minimum pulse width, etc.
- Derating factors for junction temperature, power supply voltage, and process variations.

Timing model for STD111 focuses on how to characterize cell propagation delay time accurately. To accomplish this goal, 2-dimensional table look-up delay model has been adopted. The index variables of this table are input waveform slope and output load capacitance. See the figure below. Samsung ASIC design automation system supports an n-dimensional table model even though we adopted 2-dimensional model for our 0.25 μ m cell-based products.

Figure 1-16. 2-Dimensional Table Delay Model



The Table 1-5. shows an example of this model for 2-input NAND cell. The data in this table are high-to-low transition delay times from one of the two input pins to output pin. The number of points and values of the index variables can differ for each cell.

Table 1-5. Table Delay Model Example


SLOPE \ CAP	0.010	0.042	0.106	0.233	0.424	0.678
0.020	0.04146	0.08814	0.18023	0.36303	0.63784	1.00330
0.198	0.06338	0.11782	0.20862	0.39030	0.66461	1.02980
0.415	0.07617	0.14488	0.24869	0.42763	0.70005	1.06410
0.849	0.08747	0.17724	0.30697	0.50902	0.77668	1.13720
1.500	0.09268	0.20337	0.36332	0.60379	0.90022	1.25490

Notice that 5-by-6 table is used. Delay values between grid points and beyond this table are determined by linear interpolation and extrapolation methods. This general table delay model provides great flexibility as well as high accuracy since extensive software revisions are not required when a cell library is updated. The other timing components such as interconnection wire delay, timing requirement parameters and derating factors are characterized in a commonly-accepted way in industry.

The figure below summarizes the features of Samsung ASIC's delay model.

- ① 2-dimensional table delay model for output loading and input waveform slope effects is used. The slopes (t_R , t_F) and delay times (t_{PLH} , t_{PHL}) of all cell instances are calculated recursively.
- ② The input waveform slope of each primary input pad and the loading capacitance of each primary output pad can be assigned individually or by default.
- ③ Pin to pin delays of cells and interconnection wires are supported.
- ④ The effect of distributed interconnection wire resistance and capacitance on cell delay is analysed using the effective capacitance concept.

Figure 1-17. Features of Delay Model



1.7 Testability Design Methodology

1.7.1 SCAN DESIGN

- Multiplexed scan flip-flop that minimizes the area or delay overhead needed to implement scan design.
- Automated design rules checking, scan insertion, and test pattern generation
- High fault coverage on synchronous designs


1.7.2 BOUNDARY-SCAN

- IEEE Std 1149.1
- JTAG boundary-scan registers with primitive cells
- Boundary-Scan Description Language (BSDL) description for board testing
- Combination with internal scan design and core testing

Boundary Scan Architecture

A boundary scan architecture contains TAP (Test Access Port), TAP controller, instruction register and a group of test data registers. The instruction and test data registers are separate shift-register-based paths connected in parallel with a common serial data input and a common serial data output which are connected to TAP, TDI and TDO signals. TAP controller selects the alternative instruction and test data register paths between TDI and TDO. The schematic view of the top level design of the test logic architecture is shown in the Figure 1-18.

Figure 1-18. JTAG Test Access Port (TAP) Block Diagram



Boundary Scan Functional Block Descriptions

TAP (Test Access Port)

TAP is a general-purpose port that can provide with an access to many test support functions built into a component, including the test logic. It includes three inputs (TCK; Test Clock Signal, TMS; Test Mode Signal and TDI; Test Data Input) and one output (TDO; Test Data Output) required by the test logic. An optional fourth input (TRSTN; Test Reset) is provided for the asynchronous initialization of the test logic. The values applied at TMS and TDI pins are sampled on the rising edge of TCK, and the value placed on TDO pin changes on the falling edge of TCK.

TAP Controller

TAP controller receives TCK, interprets the signals on TMS, and generates clock and control signals for both instruction and test data registers and for other parts of the test circuitries as required.

Instruction Register/Instruction Decoder

Test instructions are shifted into and held by the instruction register. Test instructions include a selection of tests to be performed or the test data register to be accessed. A basic 3-bit instruction register and its instruction decoder are provided as macrofunctions in the library.

Test Data Registers

Data registers include a bypass register, a boundary scan register, a device identification register and other design specific registers. Only the bypass- and boundary scan registers are mandatory; the rest are optional.

Bypass register: The bypass register provides a single-bit serial connection through the circuit when none of the other test data registers is selected. It can be used to allow test data to flow through a given device to the other components in a product without affecting a normal operation.

Boundary scan register: The boundary scan register detects typical production defects in board interconnects, such as opens, shorts, etc. It also allows an access to component inputs and outputs when you test their logic or sample flow-through signals. Special boundary scan register macrocells are provided for this purpose. These special registers is discussed in the next section of next pages.

Design-specific test data register: These optional registers may be provided to allow an access to design-specific test support features in the integrated circuit, such as self-test, scan test.

Device identification register: This is an optional test data register that allows the manufacturer part number and variant of a components to be identified. The 32-bit identification register is partitioned into four fields:

Device version identifier	1st field	The first four bits beginning from MSB
Device part number	2nd field	16 bits
Manufacturer's JEDEC number	3rd field	11 bits
LSB	4th field	1 bit —tied in High

The ASIC designer is free to fill the version and part number in any manner as long as the total twenty bits are used.


Samsung's JEDEC code: 78 decimal = 1001110

Continuation field (4 bits) = 0000

Contents of device identification register:

XXXX XXXXXXXXXXXXXXXX 0000 1001110 1

Users can define these two fields.



1.7.3 BIST (BUILT-IN SELF-TEST)

- Efficient test solution for compiled memory macrocells
- At speed and parallel testing of multiple memories
- Less routing overhead and test pin requirements

1.8 Maximum Fanouts

1.8.1 INTERNAL MACROCELLS

The maximum fanouts for STD111 primitive cells are as follows. Note that these fanout limitation values are calculated when the rise and fall times of the input signal is 0.198ns. Depending on the rise and fall times, the maximum fanout limitations can be varied case by case.

In the following table the maximum fanout values for all pins of STD111 internal macrocells are listed.

Table 1-6. Maximum Fanouts of Internal Macrocells

(When input $t_R/t_F = 0.198\text{ns}$, one fanout (SL) = 0.01109pF)

Cell Name	Output Pin	Maximum Fanouts
ad2	Y	51
ad2d2	Y	104
ad2d4	Y	206
ad2dh	Y	24
ad3	Y	52
ad3d2	Y	103
ad3d4	Y	207
ad3dh	Y	24
ad4	Y	51
ad4d2	Y	103
ad4d4	Y	201
ad4dh	Y	24
ad5	Y	25
ad5d2	Y	51
ad5d4	Y	207
ao21	Y	24
ao211	Y	15
ao2111	Y	10
ao2111d2	Y	103
ao211d2	Y	30
ao211d2b	Y	103
ao211d4	Y	207
ao211dh	Y	7
ao21d2	Y	48
ao21d2b	Y	102
ao21d4	Y	206
ao21dh	Y	11
ao22	Y	23
ao221	Y	14
ao221d2	Y	103
ao221d4	Y	207
ao222	Y	13
ao2222	Y	8
ao2222d2	Y	103
ao2222d4	Y	208
ao222a	Y	22
ao222d2	Y	28
ao222d2a	Y	102
ao222d2b	Y	102
ao222d4	Y	206
ao222d4a	Y	206
ao22a	Y	23

Cell Name	Output Pin	Maximum Fanouts
ao22d2	Y	47
ao22d2a	Y	47
ao22d2b	Y	102
ao22d4	Y	206
ao22d4a	Y	206
ao22dh	Y	11
ao22dha	Y	11
ao31	Y	22
ao311	Y	14
ao3111	Y	9
ao3111d2	Y	103
ao311d2	Y	103
ao311d4	Y	207
ao31d2	Y	46
ao31d4	Y	206
ao31dh	Y	10
ao32	Y	17
ao321	Y	13
ao321d2	Y	103
ao321d4	Y	207
ao322	Y	12
ao322d2	Y	103
ao322d4	Y	207
ao32d2	Y	102
ao32d4	Y	206
ao33	Y	16
ao331	Y	12
ao331d2	Y	103
ao331d4	Y	207
ao332	Y	11
ao332d2	Y	102
ao332d4	Y	207
ao33d2	Y	102
ao33d4	Y	206
ao4111	Y	8
ao4111d2	Y	103
busholder	Y	10000
dc4	Y0	51
	Y1	51
	Y2	51
	Y3	51
dc4i	YN0	41
	YN1	41
	YN2	41
	YN3	41
dc8i	YN0	29
	YN1	29
	YN2	29
	YN3	29
	YN4	29
	YN5	29
	YN6	29
	YN7	29
dl1d2	Y	104
dl1d4	Y	210
dl2d2	Y	104
dl2d4	Y	211
dl3d2	Y	104
dl3d4	Y	211
dl4d2	Y	104
dl4d4	Y	211
dl5d2	Y	103
dl5d4	Y	209
dl10d2	Y	103
dl10d4	Y	209

Cell Name	Output Pin	Maximum Fanouts
oak_ducclk 10	CK	222
	CKB	222
oak_ducclk 16	CK	223
	CKB	223
fa	S	52
	CO	51
fad2	S	103
	CO	103
fadh	S	24
	CO	23
fd1	Q	51
	QN	51
fd1d2	Q	102
	QN	102
fd1cs	Q	51
	QN	51
fd1csd2	Q	102
	QN	102
fd1q	Q	51
fd1qd2	Q	102
fd1s	Q	51
	QN	51
fd1sd2	Q	102
	QN	102
fd1sq	Q	51
fd1sqd2	Q	103
fd2	Q	51
	QN	51
fd2d2	Q	104
	QN	103
fd2cs	Q	51
	QN	49
fd2csd2	Q	103
	QN	100
fd2q	Q	51
fd2qd2	Q	103
fd2s	Q	51
	QN	51
fd2sd2	Q	104
	QN	103
fd2sq	Q	51
fd2sqd2	Q	103
fd3	Q	51
	QN	51
fd3d2	Q	103
	QN	103
fd3cs	Q	51
	QN	51
fd3csd2	Q	102
	QN	102
fd3q	Q	51
fd3qd2	Q	102
fd3s	Q	51
	QN	51
fd3sd2	Q	103
	QN	102
fd3sq	Q	51
fd3sqd2	Q	103
fd4	Q	51
	QN	50
fd4d2	Q	103
	QN	102
fd4cs	Q	51
	QN	49

Cell Name	Output Pin	Maximum Fanouts
fd4csd2	Q	103
	QN	99
fd4q	Q	51
fd4qd2	Q	103
fd4s	Q	51
	QN	50
fd4sd2	Q	103
	QN	102
fd4sq	Q	51
fd4sqd2	Q	103
fd5	Q	51
	QN	51
fd5d2	Q	102
	QN	102
fd5s	Q	51
	QN	51
fd5sd2	Q	102
	QN	102
fd6	Q	51
	QN	51
fd6d2	Q	104
	QN	103
fd6s	Q	51
	QN	51
fd6sd2	Q	104
	QN	103
fd7	Q	51
	QN	51
fd7d2	Q	103
	QN	103
fd7s	Q	51
	QN	51
fd7sd2	Q	103
	QN	102
fd8	Q	51
	QN	50
fd8d2	Q	103
	QN	102
fd8s	Q	51
	QN	50
fd8sd2	Q	103
	QN	102
fds2	Q	51
	QN	51
fds2d2	Q	102
	QN	102
fds2cs	Q	51
	QN	51
fds2csd2	Q	103
	QN	102
fds2s	Q	51
	QN	51
fds2sd2	Q	102
	QN	102
fds3	Q	51
	QN	51
fds3d2	Q	102
	QN	102
fds3cs	Q	51
	QN	51
fds3csd2	Q	102
	QN	102
fds3s	Q	51
	QN	51

Cell Name	Output Pin	Maximum Fanouts
fds3sd2	Q	102
	QN	102
fj1	Q	51
	QN	51
fj1d2	Q	103
	QN	103
fj1s	Q	51
	QN	51
fj1sd2	Q	103
	QN	102
fj2	Q	51
	QN	51
fj2d2	Q	103
	QN	103
fj2s	Q	51
	QN	51
fj2sd2	Q	103
	QN	102
fj4	Q	51
	QN	51
fj4d2	Q	102
	QN	103
fj4s	Q	51
	QN	50
fj4sd2	Q	103
	QN	102
ft2	Q	51
	QN	51
ft2d2	Q	103
	QN	103
ha	S	51
	CO	51
had2	S	104
	CO	103
hadh	S	24
	CO	23
iv	Y	52
ivcd11	Y	48
	YN	49
ivcd13	Y	45
	YN	147
ivcd22	Y	97
	YN	99
ivcd26	Y	90
	YN	295
ivcd44	Y	194
	YN	199
ivd2	Y	105
ivd3	Y	156
ivd4	Y	211
ivd6	Y	308
ivd8	Y	414
ivd16	Y	853
ivdh	Y	23
ivt	Y	48
ivtd2	Y	101
ivtd4	Y	203
ivtd8	Y	407
ivtd16	Y	824
ivtn	Y	48
ivtnd2	Y	101
ivtnd4	Y	203
ivtnd8	Y	407
ivtnd16	Y	824

Cell Name	Output Pin	Maximum Fanouts
ld1	Q	51
	QN	51
ld1d2	Q	102
	QN	102
ld1a	Q	40
ld1d2a	Q	84
ld1q	Q	51
ld1qd2	Q	102
ld2	Q	51
	QN	51
ld2d2	Q	103
	QN	103
ld2q	Q	51
ld2qd2	Q	102
ld3	Q	51
	QN	51
ld3d2	Q	103
	QN	103
ld4	Q	51
	QN	51
ld4d2	Q	104
	QN	103
ld5	Q	51
	QN	51
ld5d2	Q	102
	QN	102
ld5q	Q	51
ld5qd2	Q	102
ld6	Q	51
	QN	51
ld6d2	Q	103
	QN	103
ld6q	Q	51
ld6qd2	Q	102
ld7	Q	51
	QN	51
ld7d2	Q	103
	QN	103
ld8	Q	51
	QN	51
ld8d2	Q	104
	QN	103
oak_ldi2	Q	51
	QN	51
oak_ldi2d2	Q	102
	QN	102
oak_ldi3	Q	51
	QN	51
oak_ldi3d2	Q	104
	QN	103
ls0	Q	42
	QN	42
ls0d2	Q	83
	QN	83
ls1	Q	26
	QN	26
ls1d2	Q	102
	QN	103
mx2	Y	51
mx2d2	Y	103
mx2d4	Y	204
mx2dh	Y	24
mx2i	YN	24
mx2ia	YN	23
mx2id2	YN	103

Cell Name	Output Pin	Maximum Fanouts
mx2id2a	YN	103
mx2id4	YN	206
mx2id4a	YN	207
mx2idh	YN	11
mx2idha	YN	11
mx2ix4	YN0	24
	YN1	24
	YN2	24
	YN3	24
mx2x4	Y0	51
	Y1	51
	Y2	51
	Y3	51
mx3i	YN	51
mx3id2	YN	103
mx3id4	YN	207
mx4	Y	51
mx4d2	Y	102
mx4d4	Y	197
mx8	Y	50
mx8d2	Y	99
mx8d4	Y	186
nd2	Y	41
nd2d2	Y	83
nd2d4	Y	168
nd2dh	Y	19
nd3	Y	29
nd3d2	Y	60
nd3d4	Y	120
nd3dh	Y	13
nd4	Y	22
nd4d2	Y	45
nd4d2b	Y	103
nd4d4	Y	206
nd4dh	Y	10
nd5	Y	51
nd5d2	Y	102
nd5d4	Y	206
nd6	Y	51
nd6d2	Y	102
nd6d4	Y	206
nd8	Y	51
nd8d2	Y	102
nd8d4	Y	206
nid	Y	50
oak_nid10p	Y	1451
nid16	Y	790
nid2	Y	97
oak_nid20p	Y	2883
nid3	Y	146
nid4	Y	196
nid6	Y	290
nid8	Y	387
nidh	Y	24
nit	Y	48
nitd16	Y	825
nitd2	Y	101
nitd4	Y	202
nitd8	Y	407
nitn	Y	48
nitnd16	Y	825
nitnd2	Y	101
nitnd4	Y	202
nitnd8	Y	407
nr2	Y	25

Cell Name	Output Pin	Maximum Fanouts
nr2a	Y	52
nr2d2	Y	51
nr2d2b	Y	102
nr2d4	Y	206
nr2dh	Y	12
nr3	Y	16
nr3a	Y	33
nr3d2	Y	33
nr3d2b	Y	102
nr3d4	Y	206
nr3dh	Y	7
nr4	Y	51
nr4d2	Y	103
nr4d4	Y	206
nr4dh	Y	23
nr5	Y	51
nr5d2	Y	103
nr5d4	Y	208
nr6	Y	51
nr6d2	Y	103
nr6d4	Y	208
nr8	Y	51
nr8d2	Y	102
nr8d4	Y	204
oa21	Y	25
oa211	Y	24
oa2111	Y	20
oa2111d2	Y	102
oa211d2	Y	49
oa211d2b	Y	103
oa211d4	Y	206
oa211dh	Y	11
oa21d2	Y	51
oa21d2b	Y	102
oa21d4	Y	206
oa21dh	Y	11
oa22	Y	23
oa221	Y	22
oa221d2	Y	103
oa221d4	Y	206
oa222	Y	17
oa2222	Y	13
oa2222d2	Y	102
oa2222d4	Y	207
oa222d2	Y	34
oa222d2b	Y	103
oa222d4	Y	207
oa22a	Y	25
oa22d2	Y	47
oa22d2a	Y	50
oa22d2b	Y	103
oa22d4	Y	206
oa22d4a	Y	207
oa22dh	Y	11
oa22dha	Y	11
oa31	Y	16
oa311	Y	15
oa3111	Y	15
oa3111d2	Y	102
oa311d2	Y	102
oa311d4	Y	206
oa31d2	Y	32
oa31d4	Y	206
oa31dh	Y	7
oa32	Y	15

Cell Name	Output Pin	Maximum Fanouts
oa321	Y	14
oa321d2	Y	103
oa321d4	Y	206
oa322	Y	12
oa322d2	Y	103
oa322d4	Y	207
oa32d2	Y	103
oa32d4	Y	206
oa33	Y	13
oa331	Y	13
oa331d2	Y	102
oa331d4	Y	206
oa332	Y	9
oa332d2	Y	102
oa332d4	Y	207
oa33d2	Y	103
oa33d4	Y	207
oa4111	Y	10
oa4111d2	Y	102
or2	Y	51
or2d2	Y	103
or2d4	Y	208
or2dh	Y	23
or3	Y	51
or3d2	Y	103
or3d4	Y	206
or3dh	Y	23
or4	Y	41
or4d2	Y	83
or4d4	Y	206
or4dh	Y	19
or5	Y	41
or5d2	Y	83
or5d4	Y	206
scg1	Y	29
scg1d2	Y	59
scg2	Y	51
scg2d2	Y	104
scg3	Y	29
scg3d2	Y	59
scg4	Y	41
scg4d2	Y	83
scg5	Y	51
scg5d2	Y	102
scg6	Y	51
scg6d2	Y	102
scg7	Y	41
scg7d2	Y	83
scg8	Y	51
scg8d2	Y	103
scg9	Y	51
scg9d2	Y	102
scg10	Y	51
scg10d2	Y	102
scg11	Y	16
scg11d2	Y	32
scg12	Y	25
scg12d2	Y	51
scg13	Y	42
scg13d2	Y	84
scg14	Y	41
scg14d2	Y	83
scg15	Y	29
scg15d2	Y	59
scg16	Y	24

Cell Name	Output Pin	Maximum Fanouts
scg16d2	Y	49
scg17	Y	41
scg17d2	Y	83
scg18	Y	29
scg18d2	Y	59
scg19	Y	24
scg19d2	Y	48
scg20	Y	25
scg20d2	Y	51
scg21	Y	16
scg21d2	Y	33
scg22	Y	24
scg22d2	Y	49
scg23	S	51
	CO	51
scg23d2	S	103
	CO	103
xn2	Y	52
xn2d2	Y	103
xn2d4	Y	205
xn3	Y	50
xn3d2	Y	100
xn3d4	Y	194
xo2	Y	52
xo2d2	Y	103
xo2d4	Y	205
xo3	Y	50
xo3d2	Y	100
xo3d4	Y	194

1.8.2 I/O Cells

The maximum fanouts for I/O cells are as follows.

Table 1-7. Maximum Fanouts of I/O Cells

($t_R/t_F = 0.198\text{ns}$, one fanout (SL) = 0.01109pF)

Cell Name	Output Pin	Maximum Fanouts
phic	Y	163
phicd	Y	163
phicu	Y	163
phis	Y	163
phisd	Y	163
phisu	Y	163
phit	Y	163
phitd	Y	163
phitu	Y	163
phsosc1	YN	115
phsosc17	YN	116
phsosc2	YN	117
phsosc27	YN	117
phsosc1	YN	117
phsosc16	YN	117
phsosc2	YN	124
phsosc26	YN	124
phsosc3	YN	243
phsosc36	YN	243
pic	Y	79
pic_abb	Y	79
picc_abb	Y	81
picd	Y	79
picen_abb	Y	78
picu	Y	79
pis	Y	78
pisd	Y	78
pisu	Y	78
psosc1	YN	117
psosc2	YN	117
psosc1	YN	43
psosc2	YN	152
ptic	Y	163
pticd	Y	163
pticu	Y	163
ptis	Y	163
ptisd	Y	163
ptisu	Y	163
ptit	Y	163
ptitd	Y	163
ptitu	Y	163

1.8.3 CK Cell Max Fanout

STD111 maximum fanout for CK cells

<Condition>

- VDD = 2.5V
- Fanout = 0.00813pF (= input cap for CK pin of FD1)
- Standard Load (SL) = 0.01109pF
- Input slope = 0.198ns
- Max output transition time (mott) = 1.5ns
- Maximum frequency $\leq 200\text{MHz}$
- Net length ($\mu\text{m}/\text{fanout}$): branch net length for each fanout except trunk

Table 1-8. Maximum Fanout for CK Cells

Trunk width (μm)	8				In case that interconnection is not considered
Net length (μm/fanout)	20		200		
Trunk length (μm)	5000	10000	5000	10000	
ck2	87	1	27		237
ck4	251	151	79	48	472
ck6	408	286	128	90	709
ck8	555	403	175	127	944

Table 1-9. Maximum Fanout for NID Cells

Trunk width (μm)	0.44		8		In case that interconnection is not considered
Net length (μm/fanout)	20		200		
Trunk length (μm)	5000	10000	5000	10000	
nid					50
nid2	15				97
nid3	34		6		146
nid4	48		17		196
nid6	67		38	10	290
nid8	79		59	29	387
nid16	102		137	97	790
oak_nid10p	114		246	172	1451
oak_nid20p	123		420	267	2883

For high fanout nets including clock net, Samsung strongly recommends using clock tree synthesis.

1.9 Package Capability By Lead Count

■ In-house □ Sub-contractor

PQFP (PQ2 Thermally Enhanced)									
Package	Pitch	Lead Count							
		100	120	128	144	160	208	240	304
1420 mm	0.65	□							
	0.5			□					
2828 mm	0.8		□	□					
	0.65				□	□			
	0.5						□		
3232 mm	0.5							□	
4040 mm	0.5								□
QFP (with Heat Spreader)									
1420 mm	0.65	■							
	0.5								
2828 mm	0.8		□	■					
	0.65				□	□			
	0.5						□		
3232 mm	0.5							□	
4040 mm	0.5								□

PQFP (PQ2 Thermally Enhanced)									
Package	Pitch	Lead Count							
		100	120	128	144	160	208	240	304
1420 mm	0.65	□							
	0.5			□					
2828 mm	0.8		□	□					
	0.65				□	□			
	0.5						□		
3232 mm	0.5							□	
4040 mm	0.5								□
QFP (with Heat Spreader)									
1420 mm	0.65	■							
	0.5								
2828 mm	0.8		□	■					
	0.65				□	□			
	0.5						□		
3232 mm	0.5							□	
4040 mm	0.5								□

■ In-house □ Sub-contractor

PLCC									
Package	Pitch	Lead Inductance	Lead Count						
			18	28	32	44	52	68	84
7.37 x 12.35 mm	1.27		■						
11.53 x 11.53 mm				■					
11.44 x 13.98 mm					■				
16.61 x 16.61 mm		< 5nH				■			
19.10 x 19.10 mm							■		
24.23 x 24.23 mm								■	
29.31 x 29.31 mm		< 13nH							■

SOP								
Package	Pitch	Lead Count						
		32	48	64(56)	68	69	100	256
8.34 x 20.30 mm	1.27	■						
TSOP1								
1014 mm	0.4		■					
PLCC								
24.33 x 24.23mm	1.27				■			
QFP								
1420 mm	0.65						■	
FBGA								
0909 mm	0.75			■				
0911 mm	0.8					■		
1717 mm	1.00							■

SBGA									
Package	Pitch	Lead Inductance		Lead Count					
		Lp/g	Lsig	256	304	352	540	648	696
2727 mm	1.27	< 3nH	< 7nH	□					
3131 mm		< 3nH	< 8nH		□				
3535 mm		< 3nH	< 8nH			□			
42.5 x 47.5 mm		< 3nH	< 9nH				□		
4545 mm		< 3nH	< 9nH					□	
47.5 x 47.5 mm									□

Package Parameter Guide for PBGAs and FBGAs

Lead Inductance							
Package Type	Stack-Up (layer)	PCB Size (mm x mm)	L _{p/g} (nH)	L _{wire} (nH)	L _{total} (nH)	T (mm)	L _{sig} (nH)
PBGA	2L	23 x 23	< 3.5	1.5	< 4.5	5	< 7
	2L	27 x 27	< 4	1.5	< 5.5	6	< 7.5
	2L	31 x 31	< 4.1	1.5	< 5.6	7	< 8.5
	2L	35 x 35	< 4.5	1.5	< 6	8	< 10
	4L	23 x 23	< 1.3	1.5	< 2.8	5	< 3.5
	4L	27 x 27	< 1.5	1.5	< 3	6	< 4
	4L	31 x 31	< 1.6	1.5	< 3.1	7	< 4.5
	4L	35 x 35	< 1.7	1.5	< 3.2	8	< 5.5
FBGA	2L	06 x 06	< 2	1.5	< 3.5	2	< 2.5
	2L	08 x 08	< 2	1.5	< 3.5	2	< 3.5
	2L	09 x 09	< 2	1.5	< 3.5	2	< 4.5
	2L	10 x 10	< 2	1.5	< 3.5	2	< 4.5
	2L	12 x 12	< 2	1.5	< 3.5	2	< 5
	2L	13 x 13	< 2	1.5	< 3.5	2	< 6
	2L	14 x 14	< 2	1.5	< 3.5	2	< 6
	2L	16 x 16	< 2	1.5	< 3.5	2	< 7
	2L	17 x 17	< 2	1.5	< 3.5	2	< 8
	2L	18 x 18	< 2	1.5	< 3.5	2	< 8

NOTES: Condition to use above package parameter guide;

1. Above data are estimated calculations with below assumptions.
2. Center balls are all ground balls for PBGA ball map design.
3. For a ball map design, the power/ground ball pair should be arranged next to each other and located on the center closed inside row and column.
4. Distance between power/ground bonding pad and ball must be less than listed above T[mm] column distance.
5. The bonding wire length between power/ground ball and PCB bonding pad should be less than 2mm.
6. $L_{total} = L_{p/g} + L_{wire}$; L_{p/g}: Total inductance of power/ground pad L_{sig}: Signal line inductance.
7. Contact IPT development P/T for ball map design request form in special case, other than above 1) ~ 6) notes. Special guide will be provided.

1.10 Power Dissipation

1.10.1 ESTIMATION OF POWER DISSIPATION IN CMOS CIRCUIT

CMOS circuits have been traditionally considered to consume low power since they draw very small amount of current in a steady state. However, the recent revolution in a CMOS technology that allows very high gate density has changed the way the power dissipation should be understood. The power dissipation in a CMOS circuit is affected by various factors such as the number of gates, the switching frequency, the loading on the output of a gate, and so on.

Power dissipation is important when designers decide the amount of necessary power supply current for the device to operate in safety. Propagation delays and reliability of the device also depend on power dissipation that determines the temperature at which the die operates. To obtain high speed and reliability, designers must estimate power dissipation of the device accurately and determine the appropriate environments including the package and system cooling methods.

This section describes the concepts of two types of power dissipation (static and dynamic) in a CMOS circuit, the method of calculating those in the Samsung STD111 library.

1.10.2 STATIC (DC) POWER DISSIPATION

There are two types of static or DC current contributing to the total static power dissipation in CMOS circuits.

One is the leakage current of the gates resulted by a reverse bias between a well and a substrate region. There is no DC current path from power to ground in a CMOS because one of the transistor pair is always off, therefore, no static current except the leakage current flows through the internal gates of the device. The amount of this leakage current is, however, in the range of tens of nano amperes, which is negligible.

The other is DC current that flows through the input and output buffers when the circuit is interfaced with other devices, especially TTL. The current of pull-up/pull-down transistor in the input buffers is about 33μA (at 3.3V) and 25μA (at 2.5V) typically, which is also negligible. Therefore, only DC current that the output buffers source or sink has to be counted to estimate the total static power dissipation.

DC power dissipation of output and bi-directional buffers is determined by the following formula:

$$P_{DC_OUTPUT} [mW] = \left(\sum_{k=1}^n (V_{OL(k)} \times I_{OL(k)} \times t_{L(k)}) + \sum_{k=1}^n ((V_{DD} - V_{OH(k)}) \times I_{OH(k)} \times t_{H(k)}) \right) T$$

$$P_{DC_BI} [mW] = \left(\sum_{k=1}^n (V_{OL(k)} \times I_{OL(k)} \times t_{L(k)}) + \sum_{k=1}^n ((V_{DD} - V_{OH(k)}) \times I_{OH(k)} \times t_{H(k)}) \right) \times S_{out} T$$

where,

n = Number of output and bidirectional buffers

T = Total operation time in output mode

t_H = The sum of logic high state time

t_L = The sum of logic low state time

t_L + t_H = T (Supposed that all output and bidirectional buffers have just logic high or low state)

S_{out} is the output mode ratio of bidirectional buffers (typically 0.5)

1.10.3 DYNAMIC (AC) POWER DISSIPATION

When a CMOS gate changes its state, it draws switching current as a result of charging or discharging a load capacitance, C_L . The energy associated with the switching current for a node capacitance, C_L , is

$$C_L \times V_{DD}^2$$

where V_{DD} is the power supply voltage.

In addition to the power dissipated by the load capacitance, CMOS circuits consume power due to the short-circuit current flowing through a temporary V_{DD} -to-ground path during switching.

The dynamic power dissipation for an entire chip is much more complicated to estimate since it depends on the degree of switching activity of the circuit. Samsung has found that the degree of switching activity is 10% on the average and recommends this number to be used in estimating the total dynamic power dissipation.

1.10.4 POWER DISSIPATION IN STD111

This section describes the equations on how to estimate the power dissipation in STD111. As explained in the previous section, the total power dissipation (P_{TOTAL}) consists of static power dissipation (P_{DC}) and dynamic power dissipation (P_{AC}).

$$P_{TOTAL} = P_{AC} + P_{DC}$$

P_{DC} is negligible in case of CMOS logic.

The dynamic power dissipation is caused by three components: input buffers (P_{AC_INPUT}), output buffers (P_{AC_OUTPUT}), bidirectional buffers (P_{AC_BI}), and internal cells ($P_{AC_INTERNAL}$).

$$P_{AC} = P_{AC_INPUT} + P_{AC_OUTPUT} + P_{AC_BI} + P_{AC_INTERNAL}$$

Each term mentioned above is characterized by the following equations:

$$\begin{aligned}
P_{AC_INPUT} [\text{mW}] &= 2.5 \times \sum_j^{N_2.5V_input} \left(I_{j_eq_p} \times \frac{F_j}{100} \times S_j \right) + 3.3 \times \sum_k^{N_3.3V_input} \left(I_{k_eq_p} \times \frac{F_k}{100} \times S_k \right) + 6.25 \times \sum_i^{N_total_input} (0.001 \times S_i \times F_i \times C_{i_inload}) \\
P_{AC_OUTPUT} [\text{mW}] &= 2.5 \times \sum_i^{N_2.5V_output} \left(I_{i_eq_p} \times \frac{F_i}{100} \times S_i \right) + 3.3 \times \sum_j^{N_3.3V_output} \left(I_{j_eq_p} \times \frac{F_j}{100} \times S_j \right) + \\
&\quad 6.25 \times \sum_i^{N_2.5V_output} (0.001 \times S_i \times F_i \times C_{i_outload}) + 10.89 \times \sum_j^{N_3.3V_output} (0.001 \times S_j \times F_j \times C_{j_outload}) \\
P_{AC_BI} [\text{mW}] &= P_{AC_BI_INPUT} \times (1 - S_{out}) + P_{AC_BI_OUTPUT} \times S_{out} \\
P_{AC_BI_INPUT} [\text{mW}] &= 2.5 \times \sum_j^{N_2.5V_bi} \left(I_{j_eq_p} \times \frac{F_j}{100} \times S_j \right) + 3.3 \times \sum_k^{N_3.3V_bi} \left(I_{k_eq_p} \times \frac{F_k}{100} \times S_k \right) + 6.25 \times \sum_i^{N_total_bi} (0.001 \times S_i \times F_i \times C_{i_inload}) \\
P_{AC_BI_OUTPUT} [\text{mW}] &= 2.5 \times \sum_i^{N_2.5V_bi} \left(I_{i_eq_p} \times \frac{F_i}{100} \times S_i \right) + 3.3 \times \sum_j^{N_3.3V_bi} \left(I_{j_eq_p} \times \frac{F_j}{100} \times S_j \right) + \\
&\quad 6.25 \times \sum_i^{N_2.5V_bi} (0.001 \times S_i \times F_i \times C_{i_outload}) + 10.89 \times \sum_j^{N_3.3V_bi} (0.001 \times S_j \times F_j \times C_{j_outload}) \\
P_{AC_INTERNAL} [\text{mW}] &= 0.001 \times (0.3018 \times S + 0.0331) \times G \times F + \sum_j^{N_macro} (0.001 \times P_i \times F_i)
\end{aligned}$$

where,

N_2.5V_input is the number of 2.5V interface input buffers used

N_3.3V_input is the number of 3.3V interface input buffers used,

N_total_input = N_2.5V_input + N_3.3V_input

N_2.5V_output is the number of 2.5V interface output buffers used,

N_3.3V_output is the number of 3.3V interface output buffers used,

N_2.5V_bi is the number of 2.5V interface bidirectional buffers used,

N_3.3V_bi is the number of 3.3V interface bidirectional buffer used,

N_macro is the number of macro cells used,

G is the size of the design in gate count,

F is the operating frequency in MHz,

S is the estimated degree of switching activity (typically 0.1 for internal and 0.5 for I/O),

Sout is the output mode ratio of bidirectional buffers (typically 0.5),

C is the load capacitance in pF.

P is the characterized power for the i-th hard macro block (μW/MHz)

1.10.5 TEMPERATURE AND POWER DISSIPATION

The total power dissipation, P_{TOTAL} can be used to find out the device temperature by the following equation:

$$\theta_{JA} = (T_J - T_A) / P_{TOTAL}$$

where

θ_{JA} is the thermal impedance,

T_J is the junction temperature of the device,

T_A is the ambient temperature.

Thermal impedances of the Samsung packages are given in the following table. The junction temperature, obtained by multiplying P_{TOTAL} by the appropriate θ_{JA} and adding T_A , determines the derating factor for the propagation delays and also indicates the reliability measures. Hence, designers can achieve the desired derating factor and reliability targets by choosing appropriate packages and system cooling methods.

Table 1-10. Thermal Impedances of Samsung Plastic Packages

	SOP/TSOP									
Pin Number	20	24	28	32	44	50	54	62	66	
$\theta_{\text{JA}}[^{\circ}\text{C/W}]$	63	58	41-44	46-56	44-71	39-59	34-56	27-33	34-46	
	QFP									
Pin Number	44	48	80	100	120	128	160	208	240	256
$\theta_{\text{JA}}[^{\circ}\text{C/W}]$	51-62	43-56	43-74	27-61	33-47	43-51	29-51	22-43	28-47	29-42
	TQFP/LQFP									
Pin Number	32	64	100	144	160	176	208	256		
$\theta_{\text{JA}}[^{\circ}\text{C/W}]$	68-70	47	37-70	38	35-62	31-34	37-56	30-42		
	PBGA									
Pin Number	272		388		356 (TEPBGA)		452 (TEPBGA)			
$\theta_{\text{JA}}[^{\circ}\text{C/W}]$	19-22		16-19		16		14			
	SBGA									
Pin Number	256		304		352		432		600	
$\theta_{\text{JA}}[^{\circ}\text{C/W}]$	14.1		13.1		11.7		10.2		8.3	

1.11 V_{DD}/V_{SS} Rules And Guidelines

There are three kinds of VDD and VSS in STD111, providing power to internal and I/O area.

- Core logic
 - VDD2I, VSS2I
- Pre-driver (I/O area)
 - VDD2P, VDD3P, VSS2P, VSS3P
- Output-drive (I/O area)
 - VDD2O, VDD3O, VSS2O, VSS3O

The number of VDD and VSS pads required for a specific design depends on the following factors:

- Number of input and output buffers
- Number of simultaneous switching outputs
- Number of used gates and simultaneous switching gates
- Operating frequency

1.11.1 BASIC PLACEMENT GUIDELINES

The purpose of these guidelines is to minimize IR drop and noise for reliable device operations.

- Core logic and pre-driver V_{DD}/V_{SS} pads should be evenly distributed on all sides of the chip.
- If you have core block demanding high power (compiled memory, analog), extra power pads should be placed on that side.
- Power pads for SSO group should be evenly distributed in the SSO group.
- Do not place the quiet signal (analog, reference) or analog power (VDDA/VSSA) or bi-directional buffer next to a SSO group.
- The opposite types of power pads (V_{DD}/V_{SS}) should be placed as close as possible.
- If it is possible, do not place power pads (V_{DD}/V_{SS}) at the corner of the chip.

1.11.2 VDD2I/VSS2I ALLOCATION GUIDELINES

The purpose of these guidelines is to ensure that the minimum number of core logic power pad pairs meeting the electromigration current limit are used. The number of VDD2I/VSS2I pads required for a specific design is determined by the function of the operating frequency of a chip.

- VDD2I bus width and the number of pads are equal to those of VSS2I
- VDD2I/VSS2I buses and pads should be distributed evenly in the core and on each side of the chip.
- The total number of core logic VDD2I pads is equal to that of VSS2I pads.

The number of VDD2I/VSS2I pad pairs required for a design can be calculated from the following expression:

The number of VDD2I/VSS2I pad pairs =

$$\left\lceil \left[0.001 \times (0.1207 \times S + 0.0133) \times G \times F + \sum_i^{N_{\text{macro}}} (P_i \times F_i) \right] / I_{\text{em}} \right\rceil \text{round-up}$$

where,

G = The core (excluding hard macro blocks) size in the gate counts

S = The switching ratio (typically = 0.1)

F = Operating frequency (MHz)

P_i = Characterized current for the i-th hard macro block (mA/MHz)

F_i = Operating frequency for the i-th hard macro block (MHz)

I_{em} = Current limit per VDD/VSS pad pairs based on ElectroMigration rule (80mA)

For reliable device operation and minimize IR voltage drop, minimum number of VDD2I/VSS2I power pad pairs is 4.

Extra power may be needed for the demanding high power macro blocks (SRAM, analog block...).

1.11.3 VDD2P/VSS2P (VDD3P/VSS3P) ALLOCATION GUIDELINES.

These guidelines ensure that an adequate input threshold voltage margin is maintained during a switching.

The number of VDD2P/VSS2P (VDD3P/VSS3P) pads required for a design can be calculated from the following expression:

$$\text{Number_of_VDD2P/VSS2P(VDD3P/VSS3P) pairs} = \left\lceil \frac{I_{\text{eq_p}}}{I_{\text{em}}} \right\rceil \text{round-up}$$

In above expression,

I_{eq_p} = \sum (Average current of input/output buffers and bi-direction pre-drivers at maximum operational I/O frequency) [mA] (Refer Table 1-11)

$$I_{\text{eq_p}} = \sum_i^{N_{\text{input}}} \left(I_{\text{eq_p_in}} \times \frac{F_i}{100} \right) + \sum_j^{N_{\text{output}}} \left(I_{\text{j_eq_p_out}} \times \frac{F_j}{100} \right) + \sum_k^{N_{\text{bi}}} \left[\left(I_{\text{k_eq_p_in}} \times \frac{F_k}{100} \right) (1 - S_{\text{out}}) + \left(I_{\text{k_eq_p_out}} \times \frac{F_k}{100} \right) \times S_{\text{out}} \right]$$

where

N_{input} is the number of input buffers used,

N_{output} is the number of output buffers used,

N_{bi} is the number of bi-directional buffers used,

F is the operating frequency in MHz,

S_{out} is the output mode ratio of bi-directional buffers (typically 0.5),

I_{em} = Current limit per VDD/VSS pad pairs based on electromigration rule. (80mA)

Table 1-11. 2.5V Interface

Input Buffer Type		CMOS			CMOS Schmitt		
I _{eq_p} (mA)		0.35			0.36		
Output Pre-Driver Type		Driver			Tristate		
		B1-4	B6-8	B10-12	T1-4	T6-8	T10-12
I _{eq_p} (mA)	Normal	0.14	0.27	0.41	0.24	0.36	0.53
	Slew rate	0.14	0.25	0.35	0.25	0.35	0.45

Table 1-12. 3.3V Interface

Input Buffer Type			CMOS		TTL	Schmitt Trigger		
Ieq_p (mA)	Normal		0.52		0.54	0.54		
	Tolerant		0.60		0.60	0.51		
Output Pre-driver Type			CMOS Driver			Tristate		
			B1–4	B6–8	B10–12	T1–4	T6–8	T10–12
Ieq_p (mA)	Normal	Normal	0.25	0.46	0.55	0.34	0.51	0.60
		Slew rate	0.28	0.37	0.46	0.36	0.45	0.55
	Tolerant		-	-	-	(T1,2,3) 0.50	-	-

For reliable device operation and minimum IR voltage drop, at least 4 pairs of VDD2P/VSS2P (VDD3P/VSS3P) power pads are needed.

1.11.4 VDD2O/VSS2O (VDD3O/VSS3O) ALLOCATION GUIDE

SSO (Simultaneous Switching Output) current induced in power and ground inductance can cause system failure because of voltage fluctuations. For the calculation of output drive power pad numbers, we consider the SSO noise as well as the current limit based on electromigration. We may define the SSO as outputs switching simultaneously in 1ns windows, such as bus type buffers.

NOTE: In case of heavy load, high frequency and low package inductance, the number of power pads for SSO block could be determined by electromigration rule rather than limit of SSO noise. So the number of power pads for SSO block should be determined as the worse one of the power pad number under the limit of SSO noise and that under the limit of electromigration rule.

1) Number of power pads for SSO block

- Number of power pads for SSO block under the limit of SSO noise

- Calculating the number of power pad for each SSO group from the following expressions:

$$NVDDO_{\text{each_SSO}} = \frac{\text{number_of_SSO}}{NBvdd} \times L_{pg} \times \frac{1}{D_{SSO_mode}}$$

$$NVSSO_{\text{each_SSO}} = \frac{\text{number_of_SSO}}{NBvss} \times L_{pg} \times \frac{1}{D_{SSO_mode}}$$

In above formula,

$NVDDO_{\text{each_SSO}}$ = Number of VDD2O (VDD3O) pad required for each SSO group

$NVSSO_{\text{each_SSO}}$ = Number of VSS2O (VSS3O) pad required for each SSO group

$NBvdd$ = Number of buffers per VDD2O (VDD3O) power pad with 1nH lead inductance
(Refer Table 1-15.)

$NBvss$ = Number of buffers per VSS2O (VSS3O) ground pas with 1nH lead inductance

L_{pg} = Package lead frame inductance

(refer to 1.9 package capability by lead count)

$D_{SSO_mode} = D_{L_mode} \times D_{P_mode} \times D_{V_mode} \times D_{T_mode} \times D_{C_mode}$ (Refer to Table 1-13. and Table 1-14.)

D_{L_mode} = Lead inductance derating factor

D_{P_mode} = Process derating factor

D_{V_mode} = Voltage derating factor

D_{T_mode} = Temperature derating factor

D_{C_mode} = Cloud derating factor (*mode is either vdd or vss.)

Table 1-13. Derating Equation (external 2.5V interface)

Item	Mode	Equation	Range
Package Lead	D _{L_vdd}	0.0417 x Lpg + 0.9375 0.0417 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH ≤ Lpg ≤ 15nH
	D _{L_vss}	0.0417 x Lpg + 0.9375 0.0417 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH < Lpg ≤ 15nH
Process	D _{P_vdd}	1.0000 1.2549 1.7255	best typical worst
	D _{P_vss}	1.0000 1.2549 1.7451	best typical worst
Voltage	D _{V_vdd}	- 0.8824 x voltage + 3.3235 - 0.5882 x voltage + 2.5882	2.3 ≤ voltage ≤ 2.5 2.5 < voltage ≤ 2.7
	D _{V_vss}	- 0.8824 x voltage + 3.3235 - 0.5882 x voltage + 2.5882	2.3 ≤ voltage ≤ 2.5 2.5 < voltage ≤ 2.7
Temperature	D _{T_vdd}	0.0024 x temperature + 1.0000 0.0032 x temperature + 0.9786	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
	D _{T_vss}	0.0031 x temperature + 1.0000 0.0029 x temperature + 1.0071	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
Cload	D _{C_vdd}	0.0347 x Cload + 0.6525 0.0286 x Cload + 0.8369	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF
	D _{C_vss}	0.0354 x Cload + 0.6456 0.0285 x Cload + 0.8544	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF

Table 1-14. Derating Equation (external 3.3V interface)

Item	Mode	Equation	Range
Package Lead	D _{L_vdd}	0.0462 x Lpg + 1.1538 0.0231 x Lpg + 1.3846	3nH ≤ Lpg ≤ 10nH 10nH ≤ Lpg ≤ 15nH
	D _{L_vss}	0.0469 x Lpg + 0.7813 0.0313 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH < Lpg ≤ 15nH
Process	D _{P_vdd}	1.0000 1.2537 2.2985	best typical worst
	D _{P_vss}	1.0000 1.1563 1.4063	best typical worst
Voltage	D _{V_vdd}	- 1.2936 x voltage + 5.4328 - 0.4478 x voltage + 2.6119	3.0 ≤ voltage ≤ 3.3 3.3 < voltage ≤ 3.6
	D _{V_vss}	- 0.4166 x voltage + 2.5000 - 0.4166 x voltage + 2.5000	3.0 ≤ voltage ≤ 3.3 3.3 < voltage ≤ 3.6
Temperature	D _{T_vdd}	0.0036 x temperature + 1.0000 0.0041 x temperature + 0.9878	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
	D _{T_vss}	0.0038 x temperature + 1.0000 0.0028 x temperature + 1.0227	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
Cload	D _{C_vdd}	0.0338 x Cload + 0.6618 0.0554 x Cload + 0.0146	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF
	D _{C_vss}	0.0444 x Cload + 0.5556 0.0370 x Cload + 0.7778	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF

Table 1-15. NBvdd/NBvss Parameter (Process = best, Volt = 2.7V/3.6V Temp. = 0°C, Llead = 1nH)

Buffer Type	Voltage Type	Normal		Slew-Rate Medium (sm)		Slew-Rate High (sh)	
		NBvdd	NBvss	NBvdd	NBvss	NBvdd	NBvss
pob1 (pot1)	2.5V Interface	176	178	—	—	—	—
pob2 (pot2)		140	142	—	—	—	—
pob4 (pot4)		102	102	160	160	—	—
pob6 (pot6)		84	84	142	142	—	—
pob8 (pot8)		72	72	116	116	—	—
pob12 (pot12)		60	60	96	96	236	236
phob1 (phot1)	3.3V Interface	382	166	—	—	—	—
phob2 (phot2)		276	104	—	—	—	—
phob4 (phot4)		134	64	168	104	—	—
phob6 (phot6)		108	44	132	90	—	—
phob8 (phot8)		98	38	118	86	—	—
phob12 (phot12)		86	32	92	62	130	124
ptot1	5V Tolerant	434	376	—			
ptot2		272	180				
ptot3		203	116				

NOTE: pob1 means 1mA output driver cell, and pob12 means 12mA output driver cell.

- Calculating the number of required power pad for total SSO from the following expression:

$$NVDDO1sso = \sum NVDDO_{each_sso}$$

$$NVSSO1sso = \sum NVSSO_{each_sso}$$

When there are SSO blocks which are not switching simultaneously with the others, only maximum value of NVDDO_each_sso/NVSSO_each_sso among those SSO block should be accounted.

In the above formula,

NVDDO_{ss} = Number of VDD2O (VDD3O) pad per total SSO buffers

NVSSO_{ss} = Number of VSS2O (VSS3O) pad per total SSO buffers

- Number of power pads for SSO block under the limit of electromigration rule

- Calculating the following expression:

$$NVDDO_{SSO}/NVSSO_{SSO} = \frac{I_{eq_o}}{I_{em}}$$

$$I_{eq_o} = \sum_i^{N_SSO_output} (0.001 \times C_{i_outload} \times V_i \times F_i \times S_i) + \sum_j^{N_SSO_bi} (0.001 \times C_{j_outload} \times V_j \times F_j \times S_j \times S_{j_out})$$

where

N_SSO_output is the number of simultaneous switching output buffers used,

N_SSO_bi is the number of simultaneous switching bi-directional buffers used,

C_outload = Output load capacitance [pF]

V = Operating voltage [V]

F = Maximum I/O operating frequency [MHz]

S = Switching ratio (typically 0.5)

S_out = Output mode ratio of bidirectional buffers (typically 0.5)

I_em = Current limit per VDD/VSS pad paris based on electromigration rule. (80mA)

2) Number of power pads for non-SSO block

- Calculating the following expression:

$$NVDDO_{non_SSO}/NVSSO_{non_SSO} = \frac{I_{eq_o}}{I_{em}}$$

$$I_{eq_o} = \sum_i^{N_non_SSO_output} (0.001 \times C_{i_outload} \times V_i \times F_i \times S_i) + \sum_j^{N_non_SSO_bi} (0.001 \times C_{j_outload} \times V_j \times F_j \times S_j \times S_{j_out})$$

where

N_non_SSO_output is the number of non-simultaneous switching output buffers used,

N_non_SSO_bi is the number of non-simultaneous switching bi-directional buffers used,

C_outload = Output load capacitance [pF]

V = Operating voltage [V]

F = Maximum I/O operating frequency [MHz]

S = Switching ratio (typically 0.5)

S_out = Output mode ratio of bidirectional buffers (typically 0.5)

I_em = Current limit per VDD/VSS pad paris based on electromigration rule. (80mA)

3) Total number of power pads for VDD20/VSS20 (VDD30/VSS30)

- Calculating the following expressions:

$$\text{Number of VDD20 (VDD30)} = \lceil \max(NVDDO1_{SSO}, NVDDO2_{SSO}) + NVDDO_{non_SSO} \rceil \text{ round-up}$$

$$\text{Number of VSS20 (VSS30)} = \lceil \max(NVSSO1_{SSO}, NVSSO2_{SSO}) + NVSSO_{non_SSO} \rceil \text{ round-up}$$

When open drain type buffers are used, you can consider using VSS20 (VSS30) pads since they have current sink only.

1.12 Crystal Oscillator Consideration

1.12.1 OVERVIEW

STD111 contains a circuit commonly referred to as an “on-chip oscillator.” The on-chip circuit itself is not an oscillator but an amplifier which is suitable for being used as the amplifier part of a feedback oscillator. With proper selection of off-chip components, this oscillator circuit performs better than any other types of clock oscillators.

It is very important to select suitable off-chip components to work with the on-chip oscillator circuitry. It should be noted, however, that Samsung cannot assume the responsibility of writing specifications for the off-chip components of the complete oscillator circuit, nor of guaranteeing the performance of the finished design in production, any more than a transistor manufacturer, whose data sheets show a number of suggested amplifier circuits, can assume responsibility for the operation, in production, of any of them.

We are often asked why we don’t publish a list of required crystal or ceramic resonator specifications, and recommend values for the other off-chip components. This has been done in the past, but sometimes with consequences that were not intended.

Suppose we suggest a maximum crystal resistance of 30ohms for some given frequency. Then your crystal supplier tells you the 30ohm crystals are going to cost twice as much as 50ohm crystals. Fearing that Samsung will not “guarantee operation” with 50ohm crystals, you order the expensive ones.

In fact, Samsung guarantees only what is embodied within an Samsung product. Besides, there is no reason why 50ohm crystals couldn’t be used, if the other off-chip components are suitably adjusted.

Should we recommend values for the other off-chip components? Should we do for 50ohm crystals or 30ohm crystals? With respect to what should we optimize their selection? Should we minimize start-up time or maximize frequency stability?

In many applications, neither start-up time nor frequency stability is particularly critical, and our “recommendations” are only restricting your system to unnecessary tolerances. It all depends on the application.

1.12.2 OSCILLATOR DESIGN CONSIDERATIONS

ASIC designers have a number of options for clocking the system. The main decision is whether to use the “on-chip” oscillator or an external oscillator. If the choice is to use the on-chip oscillator, what kinds of external components are to use an external oscillator, what type of oscillator would it be?


The decisions have to be based on both economic and technical requirements. In this section we will discuss some of the factors that should be considered.

1.12.2.1 On-Chip Oscillator

In most cases, the on-chip amplifier with the appropriate external components provides the most economical solution to the clocking problem. Exceptions may arise in server environments when frequency tolerances are tighter than about 0.01%.

The external components that commonly used for CMOS gate oscillator are a positive reactance (normal crystal oscillator), two capacitors, C1 and C2, and two resistor Rf and Rx as shown in the figure below.

Figure 1-19. CMOS Oscillator



1.12.2.2 Crystal Specifications

Specifications for an appropriate crystal are not very critical, unless the frequency is. Any fundamental-mode crystal of medium or better quality can be used.

We are often asked what maximum crystal resistance should be specified. The best answer to that question is the lower the better, but use what is available.

The crystal resistance will have some effect on start-up time and steady-state amplitude, but not so much that it can't be compensated for by appropriate selection of the capacitance, C1 and C2.

Similar questions are asked about specifications of load capacitance and shunt capacitance. The best advice we can give is to understand what these parameters mean and how they affect the operation of the circuit (that being the purpose of this application note), and then to decide for yourself if such specifications are meaningful in your frequency tolerances are tighter than about 0.1%.

Part of the problem is that crystal manufacturers are accustomed to talking "ppm" tolerances with radio engineers and simply won't take your order until you've filled out their list of frequency tolerance requirements, both for yourself and to the crystal manufacturer. Don't pay for 0.003% crystals if your actual frequency tolerance is 1%.

1.12.2.3 Oscillation Frequency

The oscillation frequency is determined 99.5% by the crystal and up to about 0.5% by the circuit external to the crystal.

The on-chip amplifier has little effect on the frequency, which is as it should be, since the amplifier parameterizes temperature and process dependent.

The influence of the on-chip amplifier on the frequency is by means of its input and output (pin-to-ground) capacitances, which parallel C1 and C2, and the PADA-to-PADY (pin-to-pin) capacitance, which parallels the crystal. The input and pin-to-pin capacitances are about 7pF each.

Internal phase deviations capacitance of 25 to 30pF. These deviations from the ideal have less effect in the positive reactance oscillator (with the inverting amplifier) than in a comparable series resonant oscillator (with the non-inverting amplifier) for two reasons: first, the effect of the output capacitor; second, the positive reactance oscillator is less sensitive, frequency-wise, to such phase errors.

1.12.2.4 C1 / C2 Selection

Optimal values for the capacitors C1 and C2 depend on whether a quartz crystal or ceramic resonator is being used, and also on application-specific requirements on start-up time and frequency tolerance.

Start-up time is sometimes more critical in microcontroller systems than frequency stability, because of various reset and initialization requirements.

Less commonly, accuracy of the oscillator frequency is also critical, for example, when the oscillator is being used as a time base. As a general rule, fast start-up and stable frequency tend to pull the oscillator design in opposite directions.

Considerations of both start-up time and frequency stability over temperature suggest that C1 and C2 should be about equal and at least 15pF. (But they don't have to be either.)

Increasing the value of these capacitances above some 40 or 50pF improves frequency stability. It also tends to increase the start-up time. There is a maximum value (several hundred pF, depending on the value of R1 of the quartz or ceramic resonator) above which the oscillator won't start up at all.

If the on-chip amplifier is a simple inverter, the user can select values for C1 and C2 between some 15 and 50pF, depending on whether start-up time or frequency stability is the more critical parameter in a specific application.

1.12.2.5 Rf / Rx Selection

A CMOS inverter might work better in this application since a large Rf (1mega-ohm) can be used to hold the inverter in its linear region.

Logic gates tend to have a fairly low output resistance, which destabilizes the oscillator. For that reason a resistor Rx (several k-ohm) is often added to the feedback network, as shown in Figure 1-19.

At higher frequencies a 20 or 30pF capacitor is sometimes used in the Rx position, to compensate for some of the internal propagation delay.

1.12.2.6 Pin Capacitance Rf / Rx Selection

Internal pin-to-ground and pin-to-pin capacitances, and PADA and PADY have some effect on the oscillator. These capacitances are normally taken to be in the range of 5 to 10pF, but they are extremely difficult to evaluate. Any measurement of one such capacitance necessarily include effects from the others.

One advantage of the positive reactance oscillator is that the pin-to ground cap. is paralleled by an external bulk capacitance, so a precise determination of their value is unnecessary.

We would suggest that there is little justification for more precision than to assign them a value of 7pF (PADA-to-ground and PADA-to-PADY). This value is probably not in error by more than 3 or 4pF.

The PADY-to-ground cap. is not entirely a “pin capacitance”, but more like an “equivalent output capacitance” of some 25 to 30pF, having to include the effect of internal phase delays. This value varies to some extent with temperature, process, and frequency.

1.12.2.7 Placement of Components

Noise glitches arising at PADA or PADY pins at the wrong time can cause a miscount in the internal clock-generating circuitry. These kinds of glitches can be produced through capacitive coupling between the oscillator components and PCB traces carrying digital signals with fast rise and fall times.

For this reason, the oscillator components should be mounted close to the chip and have short, direct traces to the PADA, PADY, and V_{SS} pins.

If possible, use dedicated V_{SS} and V_{DD} pin for only crystal feedback amplifier.

1.12.3 TROUBLESHOOTING OSCILLATOR PROBLEMS

The first thing to consider in case of difficulty is that there may be significant differences in stray caps between the test jig and the actual application, particularly if the actual application is on a multi-layer board.

Noise glitches, that are not present in the test jig but are in the application board, are another possibility. Capacitive coupling between the oscillator circuitry and other signal has already been mentioned as a source of miscounts in the internal clocking circuitry. Inductive coupling is also doubtful, if there is strong current nearby. These problems are a function of the PCB layout.

Surrounding oscillator components with “quiet” traces (for example, VCC and ground) will alleviate capacitive coupling to signals having fast transition time. To minimize inductive coupling, the PCB layout should minimize the areas of the loops formed by oscillator components.

The loops demanding to be checked are as follows:

- PADA through the resonator to PADY;
- PADA through C1 to the V_{SS} pin;
- PADY through C2 to the V_{SS} pin.

It is not unusual to find that the ground ends of C1 and C2 eventually connect up to the V_{SS} pin only after looping around the farthest ends of the board. Not good.

Finally, it should not be overlooked that software problems sometimes imitate the symptoms of a slow-starting oscillator or incorrect frequency. Never underestimate the perversity of a software problem.

Electrical Characteristics

2

Contents

DC Electrical Characteristics 2-1

DC ELECTRICAL CHARACTERISTICS

$V_{DD} = 3.3 \pm 0.3V$, $T_A = -40$ to $85^\circ C$, $V_{EXT} = 5 \pm 0.25V$ (In case of 5V tolerant)

Symbol	Parameter	Condition	Min	Type	Max	Unit
V _{IH}	High level input voltage					V
	LVC MOS interface		0.7V _{DD}			
	LVTTL interface		2.0			
V _{IL}	Low level input voltage					V
	LVC MOS interface				0.3V _{DD}	
	LVTTL interface				0.8	
VT	Switching threshold	LVC MOS		0.5V _{DD}		V
		LVTTL		1.4		
VT ⁺	Schmitt trigger, positive-going threshold	LVC MOS/LVTTL			2.0	
VT ⁻	Schmitt trigger, negative-going threshold	LVC MOS/LVTTL	0.8			
V _H	VT ⁺ - VT ⁻	Schmitt-trigger	0.5	0.575	0.65	
I _{IH}	High level input current					μA
	Input buffer	V _{IN} = V _{DD}	-10		10	
	Input buffer with pull-down		10	33	60	
I _{IL}	Low level input current					μA
	Input buffer	V _{IN} = V _{SS}	-10		10	
	Input buffer with pull-up		-60	-33	-10	
V _{OH}	High level output voltage					V
	Type B1 to B12 ^{Note1}	I _{OH} = -1μA	V _{DD} - 0.05			
	Type B1	I _{OH} = -1mA				
	Type B2	I _{OH} = -2mA				
	Type B3	I _{OH} = -3mA				
	Type B4	I _{OH} = -4mA				
	Type B6	I _{OH} = -6mA				
	Type B8	I _{OH} = -8mA				
	Type B10	I _{OH} = -10mA				
	Type B12	I _{OH} = -12mA				
V _{OL}	Low level output voltage					V
	Type B1 to B12 ^{Note1}	I _{OL} = 1μA			0.05	
	Type B1	I _{OL} = 1mA			0.4	
	Type B2	I _{OL} = 2mA				
	Type B3	I _{OL} = 3mA				
	Type B4	I _{OL} = 4mA				
	Type B6	I _{OL} = 6mA				
	Type B8	I _{OL} = 8mA				
	Type B10	I _{OL} = 10mA				
	Type B12	I _{OL} = 12mA				
I _{OZ}	Tri-state output leakage current	V _{OUT} = V _{SS} or V _{EXT}	-10		10	μA
I _{OS}	Output short circuit current	V _{DD} = 3.6V, V _O = V _{DD}			55	mA
		V _{DD} = 3.6V, V _O = V _{SS}	-55			
I _{DD}	Quiescent supply current	V _{IN} = V _{SS} or V _{DD}			100 ^{Note2}	μA
C _{IN}	Input capacitance ^{Note3}	Any Input and Bidirectional Buffers			4	pF
C _{OUT}	Output capacitance ^{Note3}	Any Output Buffer			4	pF

$V_{DD} = 2.5 \pm 0.2V$, $T_A = -40$ to $85^\circ C$ (In case of general I/O)

Symbol	Parameter	Condition	Min	Type	Max	Unit
V _{IH}	High level input voltage					V
	LVC MOS interface		1.7			
V _{IL}	Low level input voltage					V
	LVC MOS interface				0.7	
VT	Switching threshold	LVC MOS		0.5V _{DD}		V
VT ⁺	Schmitt trigger, positive-going threshold	LVC MOS			1.9	
VT ⁻	Schmitt trigger, negative-going threshold	LVC MOS	0.6			
V _H	VT ⁺ - VT ⁻	Schmitt-trigger	0.5	0.65	0.8	
I _{IH}	High level input current					μA
	Input buffer	V _{IN} = V _{DD}	-10		10	
	Input buffer with pull-down		10	25	50	
I _{IL}	Low level input current					μA
	Input buffer	V _{IN} = V _{SS}	-10		10	
	Input buffer with pull-up		-50	-25	-10	
V _{OH}	High level output voltage					V
	Type B1 to B12 ^{Note1}	I _{OH} = -1μA	V _{DD} - 0.05			
	Type B1	I _{OH} = -1mA				
	Type B2	I _{OH} = -2mA				
	Type B4	I _{OH} = -4mA				
	Type B6	I _{OH} = -6mA				
	Type B8	I _{OH} = -8mA				
	Type B10	I _{OH} = -10mA				
	Type B12	I _{OH} = -12mA				
V _{OL}	Low level output voltage					V
	Type B1 to B12 ^{Note1}	I _{OL} = 1μA			0.05	
	Type B1	I _{OL} = 1mA				
	Type B2	I _{OL} = 2mA				
	Type B4	I _{OL} = 4mA				
	Type B6	I _{OH} = 6mA				
	Type B8	I _{OH} = 8mA				
	Type B10	I _{OH} = 10mA				
	Type B12	I _{OH} = 12mA				
I _{OZ}	Tri-state output leakage current	V _{OUT} = V _{SS} or V _{EXT}	-10		10	μA
I _{OS}	Output short circuit current	V _{DD} = 3.6V, V _O = V _{DD}			55	mA
		V _{DD} = 3.6V, V _O = V _{SS}	-55			
I _{DD}	Quiescent supply current	V _{IN} = V _{SS} or V _{DD}			100 ^{Note2}	μA
C _{IN}	Input capacitance ^{Note3}	Any Input and Bidirectional Buffers			4	pF
C _{OUT}	Output capacitance ^{Note3}	Any Output Buffer			4	pF

NOTES:

1. Type B1 means 1mA output driver cells, and type B6/B12 means 6mA/12mA output driver cells.
2. This value depends on the customer design.
3. This value exclude package parasitics.

Absolute Maximum Ratings

Symbol	Parameter	Rating		Unit
V_{DD}	DC supply voltage	2.5V V_{DD}	3.6	V
		3.3V V_{DD}	4.6	
V_{IN}	DC input voltage	2.5V input buffer	3.6	
		3.3V input buffer	4.6	
		3.3V interface/5V tolerant input buffer	6.5	
V_{OUT}	DC output voltage	2.5V output buffer	3.6	
		3.3V output buffer	4.6	
		3.3V interface/5V tolerant output buffer	6.5	
I_{latch}	Latch-up current	± 200		mA
T_{STG}	Storage temperature	- 65 to 150		°C

Recommended Operating Conditions

Symbol	Parameter	Rating			Unit
			Min	Max	
V_{DD}	DC Supply Voltage for Internal ($=V_{DDIN}$)	2.5V V_{DD}	2.3	2.7	V
		3.3V V_{DD}	3.0	3.6	
	DC Supply Voltage for I/O Block ($=V_{DDIO}$)	2.5V V_{DD}	2.3	2.7	
		3.3V V_{DD}	3.0	3.6	
V_{IN}	DC Input Voltage	2.5V V_{DD}	2.5 - 5%	2.5 + 5%	
		3.3V V_{DD}	3.3 - 5%	3.3 + 5%	
		2.5V input buffer	-0.2	$V_{DDIO}+0.2$	
		3.3V input buffer	-0.3	$V_{DDIO}+0.3$	
V_{OUT}	DC Output Voltage	3.3V interface / 5V tolerant input buffer	-0.3	5.5	
		2.5V output buffer	-0.2	$V_{DDIO}+0.2$	
		3.3V output buffer	-0.3	$V_{DDIO}+0.3$	
		3.3V interface / 5V tolerant output buffer	-0.3	5.5	
T_A	Commercial temperature range			0 to 70	°C
	Industrial temperature range			-40 to 85	

Internal Macrocells

3

Contents

Overview 3-1

Summary Tables..... 3-2

Logic Cells..... 3-7

Flip-Flops..... 3-300

Latches..... 3-400

Bus Holder..... 3-448

Internal Clock Drivers 3-449

Decoders 3-451

Adders 3-460

Multiplexers 3-470

OVERVIEW

The third chapter contains data sheets of logic cells, flip-flops, latches, bus holder, internal clock drivers, decoders, adders and multiplexers.

The electrical characteristics of each cell follow its basic cell data.

Summary tables in the following pages list the whole STD111 internal macrocells by the type and show their reference page numbers for your convenience. Moreover, you can find the more detailed description tables on the leading pages of each category.

SUMMARY TABLES

Logic Cells

Cell Type	Cell Name	Page
AND Cells	AD2DH/AD2/AD2D2/AD2D4	3-17
	AD3DH/AD3/AD3D2/AD3D4	3-19
	AD4DH/AD4/AD4D2/AD4D4	3-21
	AD5/AD5D2/AD5D4	3-24
NAND Cells	ND2DH/ND2/ND2D2/ND2D4	3-27
	ND3DH/ND3/ND3D2/ND3D4	3-29
	ND4DH/ND4/ND4D2/ND4D2B/ND4D4	3-32
	ND5/ND5D2/ND5D4	3-35
	ND6/ND6D2/ND6D4	3-38
	ND8/ND8D2/ND8D4	3-42
NOR Cells	NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A	3-46
	NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A	3-49
	NR4DH/NR4/NR4D2/NR4D4	3-53
	NR5/NR5D2/NR5D4	3-56
	NR6/NR6D2/NR6D4	3-60
	NR8/NR8D2/NR8D4	3-64
OR Cells	OR2DH/OR2/OR2D2/OR2D4	3-68
	OR3DH/OR3/OR3D3/OR3D4	3-70
	OR4DH/OR4/OR4D2/OR4D4	3-73
	OR5/OR5D2/OR5D4	3-76
Exclusive-NOR Cells	XN2/XN2D2/XN2D4	3-80
	XN3/XN3D2/XN3D4	3-82
Exclusive-OR Cells	XO2/XO2D2/XO2D4	3-84
	XO3/XO3D2/XO3D4	3-86
Combinational Cells of AND and NOR	AO21DH/AO21/AO21D2/AO21D2B/AO21D4	3-88
	AO211DH//AO211D2/AO211D2B/AO211D4	3-91
	AO2111/AO2111D2	3-94
	AO22DH/AO22/AO22D2/AO22D2B/AO22D4	3-97
	AO22DHA/AO22A/AO22D2A/AO22D4A	3-100
	AO221/AO221D2/AO221D4	3-103
	AO222/AO222D2/AO222D2B/AO222D4	3-107
	AO222A/AO222D2A/AO222D4A	3-112
	AO2222/AO2222D2/AO2222D4	3-114
	AO31DH/AO31/AO31D2/AO31D4	3-118
	AO311/AO311D2/AO311D4	3-121
	AO3111/AO3111D2	3-125
	AO32/AO32D2/AO32D4	3-128

Cell Type	Cell Name	Page
	AO321/AO321D2/AO321D4	3-132
	AO322/AO322D2/AO322D4	3-136
	AO33/AO33D2/AO33D4	3-140
	AO331/AO331D2/AO331D4	3-144
	AO332/AO332D2/AO332D4	3-148
	AO4111/AO4111D2	3-152
Combinational Cells of OR and NAND	OA21DH/OA21/OA21D2/OA21D2B/OA21D4	3-155
	OA211DH/OA211/OA211D2/OA211D2B/OA211D4	3-158
	OA2111/OA2111D2	3-161
	OA22DH/OA22/OA22D2/OA22D2B/OA22D4	3-164
	OA22DHA/OA22A/OA22D2A/OA22D4A	3-167
	OA221/OA221D2/OA221D4	3-170
	OA222/OA222D2/OA222D2B/OA222D4	3-174
	OA2222/OA2222D2/OA2222D4	3-179
	OA31DH/OA31/OA31D2/OA31D4	3-183
	OA311/OA311D2/OA311D4	3-186
	OA3111/OA3111D2	3-190
	OA32/OA32D2/OA32D4	3-193
	OA321/OA321D2/OA321D4	3-197
	OA322/OA322D2/OA322D4	3-201
	OA33/OA33D2/OA33D4	3-205
	OA331/OA331D2/OA331D4	3-209
	OA332/OA332D2/OA332D4	3-213
	OA4111/OA4111D2	3-217
Complex Cells	SCG1/SCG1D2	3-220
	SCG2/SCG2D2	3-223
	SCG3/SCGD2	3-225
	SCG4/SCG4D2	3-228
	SCG5/SCG5D2	3-231
	SCG6/SCG6D2	3-234
	SCG7/SCG7D2	3-236
	SCG8/SCG8D2	3-239
	SCG9/SCG9D2	3-241
	SCG10/SCG10D2	3-243
	SCG11/SCG11D2	3-246
	SCG12/SCG12D2	3-248
	SCG13/SCG13D2	3-250
	SCG14/SCG14D2	3-252
	SCG15/SCG15D2	3-254
	SCG16/SCG16D2	3-256
	SCG17/SCG17D2	3-258

Cell Type	Cell Name	Page
Complex Cells	SCG18/SCG18D2	3-260
	SCG19/SCG19D2	3-263
	SCG20/SCG20D2	3-265
	SCG21/SCG21D2	3-267
	SCG22/SCG22D2	3-269
Delay Cells	DL1D2/DL1D4	3-271
	DL2D2/DL2D4	3-272
	DL3D2/DL3D4	3-273
	DL4D2/DL4D4	3-274
	DL5D2/DL5D4	3-275
	DL10D2/DL10D4	3-276
Inverters	IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16	3-277
	IVCD(11/13)/IVCD(22/26)/IVCD44	3-280
Inverting Tri-State Buffers	IVT/IVTD2/IVTD4/IVTD8/IVTD16	3-282
	IVTN/IVTND2/IVTND4/IVTND8/IVTND16	3-284
Non-Inverting Buffers	NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16	3-286
Clock Buffers for OAK core only	OAK_NID10P/OAK_NID 20P	3-289
Non-Inverting Tri-State Buffers	NIT/NITD2/NITD4/NITD8/NITD16	3-290
	NITN/NITND2/NITND4/NITND8/NITND16	3-293
2 Phase Clock Generator Buffers for OAK core only	OAK_DUCLK10/OAK_DUCLK16	3-296
Clock Tree Synthesis Buffers	CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/CTSBD8/CTSBD16	3-298

Flip-Flops

Cell Type	Cell Name	Page
D Flip-Flop	FD1/FD1D2	3-303
	FD1CS/FD1CSD2	3-305
	FD1S/FD1SD2	3-307
	FD1SQ/FD1SQD2	3-309
	FD1Q/FD1QD2	3-311
D Flip-Flop with Reset	FD2/FD2D2	3-313
	FD2CS/FD2CSD2	3-315
	FD2S/FD2SD2	3-319
	FD2SQ/FD2SQD2	3-321
	FD2Q/FD2QD2	3-323
D Flip-Flop with Set	FD3/FD3D2	3-325
	FD3CS/FD3CSD2	3-327
	FD3S/FD3SD2	3-331
	FD3SQ/FD3SQD2	3-333
	FD3Q/FD3QD2	3-335

Cell Type	Cell Name	Page
D Flip-Flop with Reset, Set	FD4/FD4D2	3-337
	FD4CS/FD4CSD2	3-340
	FD4S/FD4SD2	3-344
	FD4SQ/FD4SQD2	3-348
	FD4Q/FD4QD2	3-351
D Flip-Flop with Negative Edge Trigger	FD5/FD5D2	3-353
	FD5S/FD5SD2	3-355
	FD6/FD6D2	3-357
	FD6S/FD6SD2	3-359
	FD7/FD7D2	3-361
	FD7S/FD7SD2	3-363
	FD8/FD8D2	3-365
	FD8S/FD8SD2	3-368
D Flip-Flop with Synchronous Clear	FDS2/FDS2D2	3-372
	FDS2CS/FDS2CSD2	3-374
	FDS2S/FDS2SD2	3-376
	FDS3/FDS3D2	3-378
	FDS3CS/FDS3CSD2	3-380
	FDS3S/FDS3SD2	3-382
JK Flip-Flop	FJ1/FJ1D2	3-384
	FJ1S/FJ1SD2	3-386
	FJ2/FJ2D2	3-388
	FJ2S/FJ2SD2	3-390
	FJ4/FJ4D2	3-392
	FJ4S/FJ4SD2	3-395
Toggle Flip-Flop	FT2/FT2D2	3-398

Latches

Cell Type	Cell Name	Page
D Latch with Active High	LD1/LD1D2	3-402
	LD1A/LD1D2A	3-404
	LD1Q/LD1QD2	3-406
	LD2/LD2D2	3-408
	LD2Q/LD2QD2	3-411
	LD3/LD3D2	3-413
	LD4/LD4D2	3-416
D Latch with Active Low	LD5/LD5D2	3-419
	LD5Q/LD5QD2	3-421
	LD6/LD6D2	3-423
	LD6Q/LD6QD2	3-426

Cell Type	Cell Name	Page
	LD7/LD7D2	3-428
	LD8/LD8D2	3-431
D Latch with Active Low for OAK core only	OAK_LDI2/OAK_LDI2D2	3-434
	OAK_LDI3/OAK_LDI3D2	3-437
SR Latch	LS0/LS0D2	3-442
	LS1/LS1D2	3-444

Bus Holder

Cell Type	Cell Name	Page
Bus Holder	BUSHOLDER	3-448

Internal Clock Drivers

Cell Type	Cell Name	Page
Internal Clock Drivers	CK2/CK4/CK6/CK8	3-449

Decoders

Cell Type	Cell Name	Page
Non-Inverting Decoder	DC4	3-452
Inverting Decoders	DC4I	3-454
	DC8I	3-456

Adders

Cell Type	Cell Name	Page
Full Adders	FADH/FA/FAD2	3-461
Half Adders	HADH/HA/HAD2	3-464
Complex Cells	SCG23/SCG23D2	3-467

Multiplexers

Cell Type	Cell Name	Page
2 > 1 Non-Inverting Mux	MX2DH/MX2/MX2D2/MX2D4	3-471
	MX2X4	3-474
2 > 1 Inverting Mux	MX2IDH/MX2I/MX2ID2/MX2ID4	3-477
	MX2IDHA/MX2IA/MX2ID2A/MX2ID4A	3-480
	MX2IX4	3-483
3 > 1 Inverting Mux	MX3I/MX3ID2/MX3ID4	3-486
4 > 1 Non-Inverting Mux	MX4/MX4D2/MX4D4	3-490
8 > 1 Non-Inverting Mux	MX8/MX8D2/MX8D4	3-494

Cell Names & Function Descriptions

Cell Name	Function Description
AD2DH	2-Input AND with 0.5X Drive
AD2	2-Input AND with 1X Drive
AD2D2	2-Input AND with 2X Drive
AD2D4	2-Input AND with 4X Drive
AD3DH	3-Input AND with 0.5X Drive
AD3	3-Input AND with 1X Drive
AD3D2	3-Input AND with 2X Drive
AD3D4	3-Input AND with 4X Drive
AD4DH	4-Input AND with 0.5X Drive
AD4	4-Input AND with 1X Drive
AD4D2	4-Input AND with 2X Drive
AD4D4	4-Input AND with 4X Drive
AD5	5-Input AND with 1X Drive
AD5D2	5-Input AND with 2X Drive
AD5D4	5-Input AND with 4X Drive
ND2DH	2-Input NAND with 0.5X Drive
ND2	2-Input NAND with 1X Drive
ND2D2	2-Input NAND with 2X Drive
ND2D4	2-Input NAND with 4X Drive
ND3DH	3-Input NAND with 0.5X Drive
ND3	3-Input NAND with 1X Drive
ND3D2	3-Input NAND with 2X Drive
ND3D4	3-Input NAND with 4X Drive
ND4DH	4-Input NAND with 0.5X Drive
ND4	4-Input NAND with 1X Drive
ND4D2	4-Input NAND with 2X Drive
ND4D2B	4-Input NAND with 2X (Buffered) Drive
ND4D4	4-Input NAND with 4X Drive
ND5	5-Input NAND with 1X Drive
ND5D2	5-Input NAND with 2X Drive
ND5D4	5-Input NAND with 4X Drive
ND6	6-Input NAND with 1X Drive
ND6D2	6-Input NAND with 2X Drive
ND6D4	6-Input NAND with 4X Drive
ND8	8-Input NAND with 1X Drive
ND8D2	8-Input NAND with 2X Drive
ND8D4	8-Input NAND with 4X Drive

LOGIC CELLS

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
NR2DH	2-Input NOR with 0.5X Drive
NR2	2-Input NOR with 1X Drive
NR2D2	2-Input NOR with 2X Drive
NR2D2B	2-Input NOR with 2X (Buffered) Drive
NR2D4	2-Input NOR with 4X Drive
NR2A	NR2 with 2X P-Transistor, 1X N-Transistor
NR3DH	3-Input NOR with 0.5X Drive
NR3	3-Input NOR with 1X Drive
NR3D2	3-Input NOR with 2X Drive
NR3D2B	3-Input NOR with 2X (Buffered) Drive
NR3D4	3-Input NOR with 4X Drive
NR3A	NR3 with 2X P-Transistor, 1X N-Transistor
NR4DH	4-Input NOR with 0.5X Drive
NR4	4-Input NOR with 1X Drive
NR4D2	4-Input NOR with 2X Drive
NR4D4	4-Input NOR with 4X Drive
NR5	5-Input NOR with 1X Drive
NR5D2	5-Input NOR with 2X Drive
NR5D4	5-Input NOR with 4X Drive
NR6	6-Input NOR with 1X Drive
NR6D2	6-Input NOR with 2X Drive
NR6D4	6-Input NOR with 4X Drive
NR8	8-Input NOR with 1X Drive
NR8D2	8-Input NOR with 2X Drive
NR8D4	8-Input NOR with 4X Drive
OR2DH	2-Input OR with 0.5X Drive
OR2	2-Input OR with 1X Drive
OR2D2	2-Input OR with 2X Drive
OR2D4	2-Input OR with 4X Drive
OR3DH	3-Input OR with 0.5X Drive
OR3	3-Input OR with 1X Drive
OR3D2	3-Input OR with 2X Drive
OR3D4	3-Input OR with 4X Drive
OR4DH	4-Input OR with 0.5X Drive
OR4	4-Input OR with 1X Drive
OR4D2	4-Input OR with 2X Drive
OR4D4	4-Input OR with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
OR5	5-Input OR with 1X Drive
OR5D2	5-Input OR with 2X Drive
OR5D4	5-Input OR with 4X Drive
XN2	2-Input Exclusive-NOR with 1X Drive
XN2D2	2-Input Exclusive-NOR with 2X Drive
XN2D4	2-Input Exclusive-NOR with 4X Drive
XN3	3-Input Exclusive-NOR with 1X Drive
XN3D2	3-Input Exclusive-NOR with 2X Drive
XN3D4	3-Input Exclusive-NOR with 4X Drive
XO2	2-Input Exclusive-OR with 1X Drive
XO2D2	2-Input Exclusive-OR with 2X Drive
XO2D4	2-Input Exclusive-OR with 4X Drive
XO3	3-Input Exclusive-OR with 1X Drive
XO3D2	3-Input Exclusive-OR with 2X Drive
XO3D4	3-Input Exclusive-OR with 4X Drive
AO21DH	2-AND into 2-NOR with 0.5X Drive
AO21	2-AND into 2-NOR with 1X Drive
AO21D2	2-AND into 2-NOR with 2X Drive
AO21D2B	2-AND into 2-NOR with 2X(Buffered) Drive
AO21D4	2-AND into 2-NOR with 4X Drive
AO211DH	2-AND into 3-NOR with 0.5X Drive
AO211	2-AND into 3-NOR with 1X Drive
AO211D2	2-AND into 3-NOR with 2X Drive
AO211D2B	2-AND into 3-NOR with 2X(Buffered) Drive
AO211D4	2-AND into 3-NOR with 4X Drive
AO2111	2-AND into 4-NOR with 1X Drive
AO2111D2	2-AND into 4-NOR with 2X Drive
AO22DH	Two 2-ANDs into 2-NOR with 0.5X Drive
AO22	Two 2-ANDs into 2-NOR with 1X Drive
AO22D2	Two 2-ANDs into 2-NOR with 2X Drive
AO22D2B	Two 2-ANDs into 2-NOR with 2X(Buffered) Drive
AO22D4	Two 2-ANDs into 2-NOR with 4X Drive
AO22DHA	2-AND and 2-NOR into 2-NOR with 0.5X Drive
AO22A	2-AND and 2-NOR into 2-NOR with 1X Drive
AO22D2A	2-AND and 2-NOR into 2-NOR with 2X Drive
AO22D4A	2-AND and 2-NOR into 2-NOR with 4X Drive

LOGIC CELLS

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
AO221	Two 2-ANDs into 3-NOR with 1X Drive
AO221D2	Two 2-ANDs into 3-NOR with 2X Drive
AO221D4	Two 2-ANDs into 3-NOR with 4X Drive
AO222	Three 2-ANDs into 3-NOR with 1X Drive
AO222D2	Three 2-ANDs into 3-NOR with 2X Drive
AO222D2B	Three 2-ANDs into 3-NOR with 2X(Buffered) Drive
AO222D4	Three 2-ANDs into 3-NOR with 4X Drive
AO222A	Inverting 2-of-3 Majority with 1X Drive
AO222D2A	Inverting 2-of-3 Majority with 2X Drive
AO222D4A	Inverting 2-of-3 Majority with 4X Drive
AO2222	Four 2-ANDs into 4-NOR with 1X Drive
AO2222D2	Four 2-ANDs into 4-NOR with 2X Drive
AO2222D4	Four 2-ANDs into 4-NOR with 4X Drive
AO31DH	3-AND into 2-NOR with 0.5X Drive
AO31	3-AND into 2-NOR with 1X Drive
AO31D2	3-AND into 2-NOR with 2X Drive
AO31D4	3-AND into 2-NOR with 4X Drive
AO311	3-AND into 3-NOR with 1X Drive
AO311D2	3-AND into 3-NOR with 2X Drive
AO311D4	3-AND into 3-NOR with 4X Drive
AO3111	3-AND into 4-NOR with 1X Drive
AO3111D2	3-AND into 4-NOR with 2X Drive
AO32	3-AND and 2-AND into 2-NOR with 1X Drive
AO32D2	3-AND and 2-AND into 2-NOR with 2X Drive
AO32D4	3-AND and 2-AND into 2-NOR with 4X Drive
AO321	3-AND and 2-AND into 3-NOR with 1X Drive
AO321D2	3-AND and 2-AND into 3-NOR with 2X Drive
AO321D4	3-AND and 2-AND into 3-NOR with 4X Drive
AO322	3-AND and Two 2-ANDs into 3-NOR with 1X Drive
AO322D2	3-AND and Two 2-ANDs into 3-NOR with 2X Drive
AO322D4	3-AND and Two 2-ANDs into 3-NOR with 4X Drive
AO33	Two 3-ANDs into 2-NOR with 1X Drive
AO33D2	Two 3-ANDs into 2-NOR with 2X Drive
AO33D4	Two 3-ANDs into 2-NOR with 4X Drive
AO331	Two 3-ANDs into 3-NOR with 1X Drive
AO331D2	Two 3-ANDs into 3-NOR with 2X Drive
AO331D4	Two 3-ANDs into 3-NOR with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
AO332	Two 3-ANDs and 2-AND into 3-NOR
AO332D2	Two 3-ANDs and 2-AND into 3-NOR with 2X Drive
AO332D4	Two 3-ANDs and 2-AND into 3-NOR with 4X Drive
AO4111	4-AND into 4-NOR with 1X Drive
AO4111D2	4-AND into 4-NOR with 2X Drive
OA21DH	2-OR into 2-NAND with 0.5X Drive
OA21	2-OR into 2-NAND with 1X Drive
OA21D2	2-OR into 2-NAND with 2X Drive
OA21D2B	2-OR into 2-NAND with 2X(Buffered) Drive
OA21D4	2-OR into 2-NAND with 4X Drive
OA211DH	2-OR into 3-NAND with 0.5X Drive
OA211	2-OR into 3-NAND with 1X Drive
OA211D2	2-OR into 3-NAND with 2X Drive
OA211D2B	2-OR into 3-NAND with 2X(Buffered) Drive
OA211D4	2-OR into 3-NAND with 4X Drive
OA2111	2-OR into 4-NAND with 1X Drive
OA2111D2	2-OR into 4-NAND with 2X Drive
OA22DH	Two 2-ORs into 2-NAND with 0.5X Drive
OA22	Two 2-ORs into 2-NAND with 1X Drive
OA22D2	Two 2-ORs into 2-NAND with 2X Drive
OA22D2B	Two 2-ORs into 2-NAND with 2X(Buffered) Drive
OA22D4	Two 2-ORs into 2-NAND with 4X Drive
OA22DHA	2-OR and 2-NAND into 2-NAND with 0.5X Drive
OA22A	2-OR and 2-NAND into 2-NAND with 1X Drive
OA22D2A	2-OR and 2-NAND into 2-NAND with 2X Drive
OA22D4A	2-OR and 2-NAND into 2-NAND with 4X Drive
OA221	Two 2-ORs into 3-NAND with 1X Drive
OA221D2	Two 2-ORs into 3-NAND with 2X Drive
OA221D4	Two 2-ORs into 3-NAND with 4X Drive
OA222	Three 2-ORs into 3-NAND with 1X Drive
OA222D2	Three 2-ORs into 3-NAND with 2X Drive
OA222D2B	Three 2-ORs into 3-NAND with 2X(Buffered) Drive
OA222D4	Three 2-ORs into 3-NAND with 4X Drive
OA2222	Four 2-ORs into 4-NAND with 1X Drive
OA2222D2	Four 2-ORs into 4-NAND with 2X Drive
OA2222D4	Four 2-ORs into 4-NAND with 4X Drive

LOGIC CELLS

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
OA31DH	3-OR into 2-NAND with 0.5X Drive
OA31	3-OR into 2-NAND with 1X Drive
OA31D2	3-OR into 2-NAND with 2X Drive
OA31D4	3-OR into 2-NAND with 4X Drive
OA311	3-OR into 3-NAND with 1X Drive
OA311D2	3-OR into 3-NAND with 2X Drive
OA311D4	3-OR into 3-NAND with 4X Drive
OA3111	3-OR into 4-NAND with 1X Drive
OA3111D2	3-OR into 4-NAND with 2X Drive
OA32	3-OR and 2-OR into 2-NAND with 1X Drive
OA32D2	3-OR and 2-OR into 2-NAND with 2X Drive
OA32D4	3-OR and 2-OR into 2-NAND with 4X Drive
OA321	3-OR and 2-OR into 3-NAND with 1X Drive
OA321D2	3-OR and 2-OR into 3-NAND with 2X Drive
OA321D4	3-OR and 2-OR into 3-NAND with 4X Drive
OA322	3-OR and Two 2-ORs into 3-NAND with 1X Drive
OA322D2	3-OR and Two 2-ORs into 3-NAND with 2X Drive
OA322D4	3-OR and Two 2-ORs into 3-NAND with 4X Drive
OA33	Two 3-ORs into 2-NAND with 1X Drive
OA33D2	Two 3-ORs into 2-NAND with 2X Drive
OA33D4	Two 3-ORs into 2-NAND with 4X Drive
OA331	Two 3-ORs into 3-NAND with 1X Drive
OA331D2	Two 3-ORs into 3-NAND with 2X Drive
OA331D4	Two 3-ORs into 3-NAND with 4X Drive
OA332	Two 3-ORs and 2-OR into 3-NAND with 1X Drive
OA332D2	Two 3-ORs and 2-OR into 3-NAND with 2X Drive
OA332D4	Two 3-ORs and 2-OR into 3-NAND with 4X Drive
OA4111	4-OR into 4-NAND with 1X Drive
OA4111D2	4-OR into 4-NAND with 2X Drive
SCG1	2-NAND and two (2-AND into 2-NOR)s into 3-NAND
SCG1D2	2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 2X Drive
SCG2	Two 2-ANDs into 2-OR
SCG2D2	Two 2-ANDs into 2-OR with 2X Drive
SCG3	Two 2-NANDs into 3-NAND
SCG3D2	Two 2-NANDs into 3-NAND with 2X Drive
SCG4	Two (two 2-ANDs into 2-NOR)s into 2-NAND
SCG4D2	Two (two 2-ANDs into 2-NOR)s into 2-NAND with 2X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
SCG5	Three 2-ANDs into 3-OR
SCG5D2	Three 2-ANDs into 3-OR with 2X Drive
SCG6	2-AND into 2-OR
SCG6D2	2-AND into 2-OR with 2X Drive
SCG7	2-NAND and (2-AND into 2-NOR) into 2-NAND
SCG7D2	2-NAND and (2-AND into 2-NOR) into 2-NAND with 2X Drive
SCG8	2-AND into 3-OR
SCG8D2	2-AND into 3-OR with 2X Drive
SCG9	2-OR into 2-AND
SCG9D2	2-OR into 2-AND with 2X Drive
SCG10	Two 2-ORs into 2-AND
SCG10D2	Two 2-ORs into 2-AND with 2X Drive
SCG11	Two 2-NORs into 3-NOR
SCG11D2	Two 2-NORs into 3-NOR with 2X Drive
SCG12	2-NAND into 2-NOR
SCG12D2	2-NAND into 2-NOR with 2X Drive
SCG13	2-NOR into 2-NAND
SCG13D2	2-NOR into 2-NAND with 2X Drive
SCG14	2-NAND into 2-NAND
SCG14D2	2-NAND into 2-NAND with 2X Drive
SCG15	2-NAND into 3-NAND
SCG15D2	2-NAND into 3-NAND with 2X Drive
SCG16	2-OR with one inverted input into 2-NAND
SCG16D2	2-OR with one inverted input into 2-NAND with 2X Drive
SCG17	2-AND into 2-NOR into 2-NAND
SCG17D2	2-AND into 2-NOR into 2-NAND with 2X Drive
SCG18	2-AND into 2-NOR into 3-NAND
SCG18D2	2-AND into 2-NOR into 3-NAND with 2X Drive
SCG19	2-AND into 2-AND into 2-NOR
SCG19D2	2-AND into 2-AND into 2-NOR with 2X Drive
SCG20	2-NOR into 2-NOR
SCG20D2	2-NOR into 2-NOR with 2X Drive
SCG21	2-NOR into 3-NOR
SCG21D2	2-NOR into 3-NOR with 2X Drive
SCG22	2-NAND into 2-OR into 2-NAND
SCG22D2	2-NAND into 2-OR into 2-NAND with 2X Drive
SCG23	Full Adder with one inverted input with 1X Drive
SCG23D2	Full Adder with one inverted input with 2X Drive

LOGIC CELLS

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
DL1D2	1ns Delay Cell with 2X Drive
DL1D4	1ns Delay Cell with 4X Drive
DL2D2	2ns Delay Cell with 2X Drive
DL2D4	2ns Delay Cell with 4X Drive
DL3D2	3ns Delay Cell with 2X Drive
DL3D4	3ns Delay Cell with 4X Drive
DL4D2	4ns Delay Cell with 2X Drive
DL4D4	4ns Delay Cell with 4X Drive
DL5D2	5ns Delay Cell with 2X Drive
DL5D4	5ns Delay Cell with 4X Drive
DL10D2	10ns Delay Cell with 2X Drive
DL10D4	10ns Delay Cell with 4X Drive
IVDH	Inverter with 0.5X Drive
IV	Inverter with 1X Drive
IVD2	Inverter with 2X Drive
IVD3	Inverter with 3X Drive
IVD4	Inverter with 4X Drive
IVD6	Inverter with 6X Drive
IVD8	Inverter with 8X Drive
IVD16	Inverter with 16X Drive
IVCD11	1X Inverter into 1X Inverter
IVCD13	1X Inverter into 3X Inverter
IVCD22	2X Inverter into 2X Inverter
IVCD26	2X Inverter into 6X Inverter
IVCD44	4X Inverter into 4X Inverter
IVT	Inverting Tri-State Buffer with Enable High, 1X Drive
IVTD2	Inverting Tri-State Buffer with Enable High, 2X Drive
IVTD4	Inverting Tri-State Buffer with Enable High, 4X Drive
IVTD8	Inverting Tri-State Buffer with Enable High, 8X Drive
IVTD16	Inverting Tri-State Buffer with Enable High, 16X Drive
IVTN	Inverting Tri-State Buffer with Enable Low, 1X Drive
IVTND2	Inverting Tri-State Buffer with Enable Low, 2X Drive
IVTND4	Inverting Tri-State Buffer with Enable Low, 4X Drive
IVTND8	Inverting Tri-State Buffer with Enable Low, 8X Drive
IVTND16	Inverting Tri-State Buffer with Enable Low, 16X Drive
NIDH	Non-Inverting Buffer with 0.5X Drive
NID	Non-Inverting Buffer with 1X Drive
NID2	Non-Inverting Buffer with 2X Drive

Cell Names & Function Descriptions (Continued)


Cell Name	Function Description
NID3	Non-Inverting Buffer with 3X Drive
NID4	Non-Inverting Buffer with 4X Drive
NID6	Non-Inverting Buffer with 6X Drive
NID8	Non-Inverting Buffer with 8X Drive
NID16	Non-Inverting Buffer with 16X Drive
OAK_NID10P	Clock Buffer for 10pF Drive (for OAK core only)
OAK_NID20P	Clock Buffer for 20pF Drive (for OAK core only)
NIT	Non-Inverting Tri-State Buffer with Enable High, 1X Drive
NITD2	Non-Inverting Tri-State Buffer with Enable High, 2X Drive
NITD4	Non-Inverting Tri-State Buffer with Enable High, 4X Drive
NITD8	Non-Inverting Tri-State Buffer with Enable High, 8X Drive
NITD16	Non-Inverting Tri-State Buffer with Enable High, 16X Drive
NITN	Non-Inverting Tri-State Buffer with Enable Low, 1X Drive
NITND2	Non-Inverting Tri-State Buffer with Enable Low, 2X Drive
NITND4	Non-Inverting Tri-State Buffer with Enable Low, 4X Drive
NITND8	Non-Inverting Tri-State Buffer with Enable Low, 8X Drive
NITND16	Non-Inverting Tri-State Buffer with Enable Low, 16X Drive
OAK_DUCLK10	2 Phase Clock Generator (1ns Non-overlapped, for OAK core only)
OAK_DUCLK16	2 Phase Clock Generator (1.6ns Non-overlapped, for OAK core only)
CTSB	Clock Tree Synthesis Buffer with 1X Drive
CTSBD2	Clock Tree Synthesis Buffer with 2X Drive
CTSBD3	Clock Tree Synthesis Buffer with 3X Drive
CTSBD4	Clock Tree Synthesis Buffer with 4X Drive
CTSBD6	Clock Tree Synthesis Buffer with 6X Drive
CTSBD8	Clock Tree Synthesis Buffer with 8X Drive
CTSBD16	Clock Tree Synthesis Buffer with 16X Drive

NOTE

AD2DH/AD2/AD2D2/AD2D4

2-Input AND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	0
1	0	0
1	1	1

Cell Data

Input Load (SL)								Gate Count			
AD2DH		AD2		AD2D2		AD2D4		AD2DH	AD2	AD2D2	AD2D4
A	B	A	B	A	B	A	B				
0.4	0.4	0.7	0.7	0.8	0.9	1.0	1.0	1.33	1.33	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.175	$0.062 + 0.057 \cdot \text{SL}$	$0.054 + 0.059 \cdot \text{SL}$	$0.046 + 0.060 \cdot \text{SL}$
	t_F	0.149	$0.056 + 0.047 \cdot \text{SL}$	$0.050 + 0.048 \cdot \text{SL}$	$0.040 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.181	$0.126 + 0.028 \cdot \text{SL}$	$0.133 + 0.026 \cdot \text{SL}$	$0.134 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.194	$0.138 + 0.028 \cdot \text{SL}$	$0.147 + 0.026 \cdot \text{SL}$	$0.149 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.176	$0.062 + 0.057 \cdot \text{SL}$	$0.055 + 0.059 \cdot \text{SL}$	$0.046 + 0.060 \cdot \text{SL}$
	t_F	0.152	$0.059 + 0.046 \cdot \text{SL}$	$0.053 + 0.048 \cdot \text{SL}$	$0.042 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.177	$0.122 + 0.028 \cdot \text{SL}$	$0.129 + 0.026 \cdot \text{SL}$	$0.130 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.210	$0.153 + 0.028 \cdot \text{SL}$	$0.162 + 0.026 \cdot \text{SL}$	$0.165 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.109	$0.057 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.059 + 0.020 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.139	$0.110 + 0.014 \cdot \text{SL}$	$0.117 + 0.013 \cdot \text{SL}$	$0.120 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.152	$0.123 + 0.015 \cdot \text{SL}$	$0.130 + 0.013 \cdot \text{SL}$	$0.134 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.108	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.053 + 0.022 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.134	$0.105 + 0.014 \cdot \text{SL}$	$0.112 + 0.013 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.167	$0.136 + 0.015 \cdot \text{SL}$	$0.145 + 0.013 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD2DH/AD2/AD2D2/AD2D4

2-Input AND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.051 + 0.011 \cdot \text{SL}$	$0.049 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.142	$0.125 + 0.008 \cdot \text{SL}$	$0.131 + 0.007 \cdot \text{SL}$	$0.140 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.148	$0.131 + 0.009 \cdot \text{SL}$	$0.138 + 0.007 \cdot \text{SL}$	$0.148 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.083	$0.056 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.135	$0.119 + 0.008 \cdot \text{SL}$	$0.125 + 0.007 \cdot \text{SL}$	$0.134 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.161	$0.143 + 0.009 \cdot \text{SL}$	$0.150 + 0.007 \cdot \text{SL}$	$0.161 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AD2D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.066 + 0.007 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.057 + 0.007 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.161	$0.150 + 0.005 \cdot \text{SL}$	$0.156 + 0.004 \cdot \text{SL}$	$0.172 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.167	$0.157 + 0.005 \cdot \text{SL}$	$0.162 + 0.004 \cdot \text{SL}$	$0.180 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.083	$0.073 + 0.005 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.063 + 0.007 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.154	$0.143 + 0.005 \cdot \text{SL}$	$0.149 + 0.004 \cdot \text{SL}$	$0.166 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.179	$0.167 + 0.006 \cdot \text{SL}$	$0.174 + 0.004 \cdot \text{SL}$	$0.192 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AD3DH/AD3/AD3D2/AD3D4

3-Input AND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	x	0
x	0	x	0
x	x	0	0
1	1	1	1

Cell Data

Input Load (SL)												Gate Count			
AD3DH			AD3			AD3D2			AD3D4			AD3DH	AD3	AD3D2	AD3D4
A	B	C	A	B	C	A	B	C	A	B	C				
0.3	0.3	0.3	0.6	0.6	0.7	0.7	0.8	0.8	0.8	0.9	0.9	1.67	1.67	2.00	2.33

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.192	$0.078 + 0.057 \cdot \text{SL}$	$0.076 + 0.058 \cdot \text{SL}$	$0.064 + 0.059 \cdot \text{SL}$
	t_F	0.162	$0.069 + 0.047 \cdot \text{SL}$	$0.066 + 0.048 \cdot \text{SL}$	$0.053 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.221	$0.161 + 0.030 \cdot \text{SL}$	$0.175 + 0.026 \cdot \text{SL}$	$0.181 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.231	$0.172 + 0.030 \cdot \text{SL}$	$0.186 + 0.026 \cdot \text{SL}$	$0.191 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.194	$0.080 + 0.057 \cdot \text{SL}$	$0.076 + 0.058 \cdot \text{SL}$	$0.064 + 0.059 \cdot \text{SL}$
	t_F	0.167	$0.075 + 0.046 \cdot \text{SL}$	$0.070 + 0.047 \cdot \text{SL}$	$0.056 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.223	$0.163 + 0.030 \cdot \text{SL}$	$0.177 + 0.026 \cdot \text{SL}$	$0.183 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.249	$0.189 + 0.030 \cdot \text{SL}$	$0.203 + 0.026 \cdot \text{SL}$	$0.210 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.193	$0.080 + 0.057 \cdot \text{SL}$	$0.076 + 0.058 \cdot \text{SL}$	$0.063 + 0.059 \cdot \text{SL}$
	t_F	0.173	$0.081 + 0.046 \cdot \text{SL}$	$0.076 + 0.047 \cdot \text{SL}$	$0.062 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.224	$0.164 + 0.030 \cdot \text{SL}$	$0.178 + 0.026 \cdot \text{SL}$	$0.183 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.266	$0.205 + 0.031 \cdot \text{SL}$	$0.221 + 0.026 \cdot \text{SL}$	$0.228 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	$0.069 + 0.027 \cdot \text{SL}$	$0.068 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.056 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.171	$0.139 + 0.016 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.158 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.180	$0.149 + 0.016 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.166 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.126	$0.075 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.061 + 0.023 \cdot \text{SL}$	$0.063 + 0.022 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.173	$0.140 + 0.016 \cdot \text{SL}$	$0.151 + 0.013 \cdot \text{SL}$	$0.160 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.194	$0.162 + 0.016 \cdot \text{SL}$	$0.172 + 0.013 \cdot \text{SL}$	$0.180 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.123	$0.070 + 0.027 \cdot \text{SL}$	$0.068 + 0.027 \cdot \text{SL}$	$0.063 + 0.028 \cdot \text{SL}$
	t_F	0.112	$0.066 + 0.023 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.172	$0.140 + 0.016 \cdot \text{SL}$	$0.150 + 0.013 \cdot \text{SL}$	$0.159 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.176 + 0.016 \cdot \text{SL}$	$0.186 + 0.014 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD3DH/AD3/AD3D2/AD3D4

3-Input AND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	$0.070 + 0.014 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.175	$0.156 + 0.010 \cdot \text{SL}$	$0.164 + 0.007 \cdot \text{SL}$	$0.180 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.178	$0.159 + 0.010 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$	$0.183 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.100	$0.072 + 0.014 \cdot \text{SL}$	$0.074 + 0.013 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.177	$0.158 + 0.010 \cdot \text{SL}$	$0.166 + 0.007 \cdot \text{SL}$	$0.182 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.191	$0.171 + 0.010 \cdot \text{SL}$	$0.180 + 0.007 \cdot \text{SL}$	$0.196 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.100	$0.072 + 0.014 \cdot \text{SL}$	$0.073 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.094	$0.069 + 0.012 \cdot \text{SL}$	$0.073 + 0.011 \cdot \text{SL}$	$0.068 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.175	$0.156 + 0.010 \cdot \text{SL}$	$0.164 + 0.007 \cdot \text{SL}$	$0.180 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.204	$0.183 + 0.010 \cdot \text{SL}$	$0.193 + 0.007 \cdot \text{SL}$	$0.210 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AD3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.105	$0.092 + 0.006 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.204	$0.192 + 0.006 \cdot \text{SL}$	$0.199 + 0.004 \cdot \text{SL}$	$0.222 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.204	$0.192 + 0.006 \cdot \text{SL}$	$0.199 + 0.004 \cdot \text{SL}$	$0.222 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.104	$0.091 + 0.007 \cdot \text{SL}$	$0.091 + 0.007 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$
	t_F	0.094	$0.080 + 0.007 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.206	$0.194 + 0.006 \cdot \text{SL}$	$0.201 + 0.004 \cdot \text{SL}$	$0.224 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.218	$0.205 + 0.006 \cdot \text{SL}$	$0.213 + 0.004 \cdot \text{SL}$	$0.238 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.105	$0.092 + 0.006 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$
	t_F	0.099	$0.087 + 0.006 \cdot \text{SL}$	$0.089 + 0.006 \cdot \text{SL}$	$0.090 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.205	$0.193 + 0.006 \cdot \text{SL}$	$0.200 + 0.004 \cdot \text{SL}$	$0.223 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.228	$0.215 + 0.006 \cdot \text{SL}$	$0.223 + 0.004 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AD4DH/AD4/AD4D2/AD4D4

4-Input AND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	x	x	0
x	0	x	x	0
x	x	0	x	0
x	x	x	0	0
1	1	1	1	1

Cell Data

Input Load (SL)															
AD4DH				AD4				AD4D2				AD4D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.3	0.3	0.3	0.3	0.6	0.6	0.6	0.6	0.7	0.7	0.7	0.7	0.8	0.8	0.8	0.8
Gate Counts															
AD4DH				AD4				AD4D2				AD4D4			
2.00				2.00				2.00				2.67			

AD4DH/AD4/AD4D2/AD4D4

4-Input AND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.210	$0.095 + 0.058 \cdot \text{SL}$	$0.095 + 0.057 \cdot \text{SL}$	$0.084 + 0.059 \cdot \text{SL}$
	t_F	0.169	$0.075 + 0.047 \cdot \text{SL}$	$0.072 + 0.047 \cdot \text{SL}$	$0.060 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.252	$0.187 + 0.032 \cdot \text{SL}$	$0.205 + 0.027 \cdot \text{SL}$	$0.219 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.248	$0.187 + 0.031 \cdot \text{SL}$	$0.202 + 0.026 \cdot \text{SL}$	$0.210 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.210	$0.095 + 0.058 \cdot \text{SL}$	$0.096 + 0.057 \cdot \text{SL}$	$0.084 + 0.059 \cdot \text{SL}$
	t_F	0.174	$0.081 + 0.047 \cdot \text{SL}$	$0.079 + 0.047 \cdot \text{SL}$	$0.064 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.262	$0.198 + 0.032 \cdot \text{SL}$	$0.216 + 0.027 \cdot \text{SL}$	$0.229 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.268	$0.206 + 0.031 \cdot \text{SL}$	$0.223 + 0.027 \cdot \text{SL}$	$0.231 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.211	$0.096 + 0.057 \cdot \text{SL}$	$0.096 + 0.057 \cdot \text{SL}$	$0.084 + 0.059 \cdot \text{SL}$
	t_F	0.181	$0.089 + 0.046 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$	$0.070 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.268	$0.204 + 0.032 \cdot \text{SL}$	$0.222 + 0.027 \cdot \text{SL}$	$0.236 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.285	$0.222 + 0.031 \cdot \text{SL}$	$0.240 + 0.027 \cdot \text{SL}$	$0.250 + 0.026 \cdot \text{SL}$
D to Y	t_R	0.210	$0.095 + 0.058 \cdot \text{SL}$	$0.095 + 0.057 \cdot \text{SL}$	$0.084 + 0.059 \cdot \text{SL}$
	t_F	0.187	$0.095 + 0.046 \cdot \text{SL}$	$0.093 + 0.047 \cdot \text{SL}$	$0.077 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.273	$0.209 + 0.032 \cdot \text{SL}$	$0.227 + 0.027 \cdot \text{SL}$	$0.241 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.302	$0.237 + 0.032 \cdot \text{SL}$	$0.257 + 0.027 \cdot \text{SL}$	$0.269 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.135	$0.079 + 0.028 \cdot \text{SL}$	$0.082 + 0.027 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$
	t_F	0.108	$0.061 + 0.024 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.190	$0.156 + 0.017 \cdot \text{SL}$	$0.167 + 0.014 \cdot \text{SL}$	$0.181 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.193	$0.161 + 0.016 \cdot \text{SL}$	$0.171 + 0.014 \cdot \text{SL}$	$0.180 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.136	$0.081 + 0.028 \cdot \text{SL}$	$0.083 + 0.027 \cdot \text{SL}$	$0.080 + 0.027 \cdot \text{SL}$
	t_F	0.113	$0.067 + 0.023 \cdot \text{SL}$	$0.071 + 0.022 \cdot \text{SL}$	$0.063 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.199	$0.166 + 0.017 \cdot \text{SL}$	$0.177 + 0.014 \cdot \text{SL}$	$0.190 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.212	$0.179 + 0.016 \cdot \text{SL}$	$0.190 + 0.014 \cdot \text{SL}$	$0.200 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.136	$0.081 + 0.027 \cdot \text{SL}$	$0.082 + 0.027 \cdot \text{SL}$	$0.080 + 0.027 \cdot \text{SL}$
	t_F	0.120	$0.074 + 0.023 \cdot \text{SL}$	$0.076 + 0.022 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.205	$0.171 + 0.017 \cdot \text{SL}$	$0.182 + 0.014 \cdot \text{SL}$	$0.195 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.228	$0.195 + 0.017 \cdot \text{SL}$	$0.206 + 0.014 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.136	$0.080 + 0.028 \cdot \text{SL}$	$0.084 + 0.027 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$
	t_F	0.127	$0.082 + 0.023 \cdot \text{SL}$	$0.084 + 0.022 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.208	$0.174 + 0.017 \cdot \text{SL}$	$0.185 + 0.014 \cdot \text{SL}$	$0.199 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.243	$0.208 + 0.017 \cdot \text{SL}$	$0.220 + 0.014 \cdot \text{SL}$	$0.234 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AD4DH/AD4/AD4D2/AD4D4

4-Input AND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	$0.084 + 0.014 \cdot \text{SL}$	$0.084 + 0.014 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$
	t_F	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.069 + 0.011 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.194	$0.173 + 0.011 \cdot \text{SL}$	$0.184 + 0.008 \cdot \text{SL}$	$0.204 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.195	$0.174 + 0.010 \cdot \text{SL}$	$0.184 + 0.008 \cdot \text{SL}$	$0.202 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.113	$0.086 + 0.014 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$
	t_F	0.097	$0.072 + 0.012 \cdot \text{SL}$	$0.076 + 0.011 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.204	$0.183 + 0.011 \cdot \text{SL}$	$0.193 + 0.008 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.213	$0.192 + 0.011 \cdot \text{SL}$	$0.202 + 0.008 \cdot \text{SL}$	$0.221 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.113	$0.086 + 0.014 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$
	t_F	0.101	$0.077 + 0.012 \cdot \text{SL}$	$0.080 + 0.011 \cdot \text{SL}$	$0.077 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.209	$0.188 + 0.011 \cdot \text{SL}$	$0.198 + 0.008 \cdot \text{SL}$	$0.219 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.224	$0.202 + 0.011 \cdot \text{SL}$	$0.214 + 0.008 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.113	$0.086 + 0.014 \cdot \text{SL}$	$0.085 + 0.014 \cdot \text{SL}$	$0.087 + 0.014 \cdot \text{SL}$
	t_F	0.108	$0.084 + 0.012 \cdot \text{SL}$	$0.087 + 0.011 \cdot \text{SL}$	$0.085 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.212	$0.191 + 0.011 \cdot \text{SL}$	$0.201 + 0.008 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.237	$0.215 + 0.011 \cdot \text{SL}$	$0.227 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AD4D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	$0.114 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$	$0.113 + 0.007 \cdot \text{SL}$
	t_F	0.099	$0.088 + 0.006 \cdot \text{SL}$	$0.087 + 0.006 \cdot \text{SL}$	$0.091 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.233	$0.220 + 0.007 \cdot \text{SL}$	$0.228 + 0.004 \cdot \text{SL}$	$0.255 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.226	$0.213 + 0.006 \cdot \text{SL}$	$0.221 + 0.004 \cdot \text{SL}$	$0.246 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.127	$0.114 + 0.007 \cdot \text{SL}$	$0.113 + 0.007 \cdot \text{SL}$	$0.114 + 0.007 \cdot \text{SL}$
	t_F	0.106	$0.092 + 0.007 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$	$0.099 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.243	$0.230 + 0.007 \cdot \text{SL}$	$0.238 + 0.004 \cdot \text{SL}$	$0.265 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.242	$0.229 + 0.007 \cdot \text{SL}$	$0.237 + 0.004 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.127	$0.115 + 0.006 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$
	t_F	0.114	$0.100 + 0.007 \cdot \text{SL}$	$0.104 + 0.006 \cdot \text{SL}$	$0.106 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.248	$0.235 + 0.007 \cdot \text{SL}$	$0.243 + 0.004 \cdot \text{SL}$	$0.271 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.243 + 0.007 \cdot \text{SL}$	$0.252 + 0.005 \cdot \text{SL}$	$0.281 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.127	$0.114 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$	$0.113 + 0.007 \cdot \text{SL}$
	t_F	0.121	$0.107 + 0.007 \cdot \text{SL}$	$0.111 + 0.006 \cdot \text{SL}$	$0.113 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.251	$0.238 + 0.007 \cdot \text{SL}$	$0.246 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.271	$0.257 + 0.007 \cdot \text{SL}$	$0.266 + 0.005 \cdot \text{SL}$	$0.296 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AD5/AD5D2/AD5D4

5-Input AND with 1X/2X/4XDrive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	x	x	x	0
x	0	x	x	x	0
x	x	0	x	x	0
x	x	x	0	x	0
x	x	x	x	0	0
1	1	1	1	1	1

Cell Data

Input Load (SL)														
AD5					AD5D2					AD5D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.6	0.6	0.6	0.6	0.7	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.7
Gate Count														
AD5					AD5D2					AD5D4				
2.67					3.00					4.33				

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.211	$0.104 + 0.054 \cdot \text{SL}$	$0.101 + 0.054 \cdot \text{SL}$	$0.094 + 0.055 \cdot \text{SL}$
	t_F	0.110	$0.065 + 0.022 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.062 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.193	$0.142 + 0.025 \cdot \text{SL}$	$0.147 + 0.024 \cdot \text{SL}$	$0.149 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.200	$0.168 + 0.016 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$	$0.189 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.212	$0.106 + 0.053 \cdot \text{SL}$	$0.101 + 0.054 \cdot \text{SL}$	$0.094 + 0.055 \cdot \text{SL}$
	t_F	0.117	$0.073 + 0.022 \cdot \text{SL}$	$0.074 + 0.021 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.196	$0.145 + 0.025 \cdot \text{SL}$	$0.151 + 0.024 \cdot \text{SL}$	$0.153 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.222	$0.189 + 0.016 \cdot \text{SL}$	$0.201 + 0.013 \cdot \text{SL}$	$0.213 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.211	$0.104 + 0.053 \cdot \text{SL}$	$0.101 + 0.054 \cdot \text{SL}$	$0.094 + 0.055 \cdot \text{SL}$
	t_F	0.125	$0.082 + 0.022 \cdot \text{SL}$	$0.084 + 0.021 \cdot \text{SL}$	$0.077 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.195	$0.144 + 0.026 \cdot \text{SL}$	$0.150 + 0.024 \cdot \text{SL}$	$0.152 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.242	$0.207 + 0.017 \cdot \text{SL}$	$0.221 + 0.014 \cdot \text{SL}$	$0.234 + 0.012 \cdot \text{SL}$
D to Y	t_R	0.203	$0.095 + 0.054 \cdot \text{SL}$	$0.092 + 0.055 \cdot \text{SL}$	$0.089 + 0.055 \cdot \text{SL}$
	t_F	0.123	$0.082 + 0.021 \cdot \text{SL}$	$0.079 + 0.022 \cdot \text{SL}$	$0.072 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.175	$0.125 + 0.025 \cdot \text{SL}$	$0.130 + 0.024 \cdot \text{SL}$	$0.132 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.191	$0.162 + 0.014 \cdot \text{SL}$	$0.169 + 0.013 \cdot \text{SL}$	$0.175 + 0.012 \cdot \text{SL}$
E to Y	t_R	0.203	$0.095 + 0.054 \cdot \text{SL}$	$0.093 + 0.055 \cdot \text{SL}$	$0.088 + 0.055 \cdot \text{SL}$
	t_F	0.128	$0.086 + 0.021 \cdot \text{SL}$	$0.083 + 0.021 \cdot \text{SL}$	$0.076 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.173	$0.123 + 0.025 \cdot \text{SL}$	$0.127 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.209	$0.180 + 0.015 \cdot \text{SL}$	$0.187 + 0.013 \cdot \text{SL}$	$0.194 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**AD5D2**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	$0.099 + 0.027 \cdot \text{SL}$	$0.101 + 0.027 \cdot \text{SL}$	$0.091 + 0.027 \cdot \text{SL}$
	t_F	0.099	$0.075 + 0.012 \cdot \text{SL}$	$0.079 + 0.011 \cdot \text{SL}$	$0.078 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.192	$0.165 + 0.014 \cdot \text{SL}$	$0.170 + 0.012 \cdot \text{SL}$	$0.177 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.213	$0.192 + 0.010 \cdot \text{SL}$	$0.202 + 0.008 \cdot \text{SL}$	$0.222 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.153	$0.099 + 0.027 \cdot \text{SL}$	$0.100 + 0.027 \cdot \text{SL}$	$0.091 + 0.027 \cdot \text{SL}$
	t_F	0.106	$0.082 + 0.012 \cdot \text{SL}$	$0.086 + 0.011 \cdot \text{SL}$	$0.083 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.195	$0.168 + 0.014 \cdot \text{SL}$	$0.173 + 0.012 \cdot \text{SL}$	$0.180 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.228	$0.207 + 0.011 \cdot \text{SL}$	$0.218 + 0.008 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.154	$0.100 + 0.027 \cdot \text{SL}$	$0.101 + 0.027 \cdot \text{SL}$	$0.090 + 0.027 \cdot \text{SL}$
	t_F	0.113	$0.088 + 0.012 \cdot \text{SL}$	$0.093 + 0.011 \cdot \text{SL}$	$0.091 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.193	$0.165 + 0.014 \cdot \text{SL}$	$0.171 + 0.012 \cdot \text{SL}$	$0.178 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.245	$0.222 + 0.011 \cdot \text{SL}$	$0.235 + 0.008 \cdot \text{SL}$	$0.258 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.143	$0.089 + 0.027 \cdot \text{SL}$	$0.088 + 0.027 \cdot \text{SL}$	$0.083 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.093 + 0.011 \cdot \text{SL}$	$0.095 + 0.011 \cdot \text{SL}$	$0.090 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.171	$0.144 + 0.014 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$	$0.155 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.190 + 0.009 \cdot \text{SL}$	$0.197 + 0.007 \cdot \text{SL}$	$0.212 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.142	$0.089 + 0.027 \cdot \text{SL}$	$0.087 + 0.027 \cdot \text{SL}$	$0.082 + 0.028 \cdot \text{SL}$
	t_F	0.124	$0.100 + 0.012 \cdot \text{SL}$	$0.104 + 0.011 \cdot \text{SL}$	$0.097 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.166	$0.139 + 0.014 \cdot \text{SL}$	$0.144 + 0.012 \cdot \text{SL}$	$0.151 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.227	$0.209 + 0.009 \cdot \text{SL}$	$0.217 + 0.007 \cdot \text{SL}$	$0.233 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AD5/AD5D2/AD5D4

5-Input AND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AD5D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.051 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.313	$0.304 + 0.005 \cdot \text{SL}$	$0.308 + 0.003 \cdot \text{SL}$	$0.319 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.309	$0.298 + 0.005 \cdot \text{SL}$	$0.304 + 0.004 \cdot \text{SL}$	$0.319 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.072	$0.059 + 0.007 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.051 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.317	$0.307 + 0.005 \cdot \text{SL}$	$0.312 + 0.003 \cdot \text{SL}$	$0.322 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.332	$0.321 + 0.005 \cdot \text{SL}$	$0.327 + 0.004 \cdot \text{SL}$	$0.342 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.053 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.306 + 0.005 \cdot \text{SL}$	$0.311 + 0.003 \cdot \text{SL}$	$0.321 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.351	$0.341 + 0.005 \cdot \text{SL}$	$0.346 + 0.004 \cdot \text{SL}$	$0.361 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.072	$0.058 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.063	$0.049 + 0.007 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.298	$0.288 + 0.005 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$	$0.303 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.303	$0.292 + 0.005 \cdot \text{SL}$	$0.298 + 0.004 \cdot \text{SL}$	$0.313 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.072	$0.059 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.063	$0.049 + 0.007 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.295	$0.285 + 0.005 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$	$0.301 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.313 + 0.005 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.334 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND2DH/ND2/ND2D2/ND2D4

2-Input NAND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	1
1	0	1
1	1	0

Cell Data

Input Load (SL)								Gate Count			
ND2DH		ND2		ND2D2		ND2D4		ND2DH	ND2	ND2D2	ND2D4
A	B	A	B	A	B	A	B				
0.5	0.5	1.0	1.0	2.0	2.0	4.1	4.0	1.00	1.00	1.67	2.67

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.221	$0.083 + 0.069 \cdot \text{SL}$	$0.065 + 0.074 \cdot \text{SL}$	$0.047 + 0.076 \cdot \text{SL}$
	t_F	0.212	$0.087 + 0.062 \cdot \text{SL}$	$0.068 + 0.067 \cdot \text{SL}$	$0.047 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.132	$0.066 + 0.033 \cdot \text{SL}$	$0.068 + 0.032 \cdot \text{SL}$	$0.067 + 0.033 \cdot \text{SL}$
	t_{PHL}	0.123	$0.055 + 0.034 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$
B to Y	t_R	0.239	$0.101 + 0.069 \cdot \text{SL}$	$0.083 + 0.074 \cdot \text{SL}$	$0.064 + 0.076 \cdot \text{SL}$
	t_F	0.205	$0.078 + 0.063 \cdot \text{SL}$	$0.060 + 0.068 \cdot \text{SL}$	$0.048 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.143	$0.078 + 0.032 \cdot \text{SL}$	$0.078 + 0.032 \cdot \text{SL}$	$0.077 + 0.032 \cdot \text{SL}$
	t_{PHL}	0.117	$0.049 + 0.034 \cdot \text{SL}$	$0.053 + 0.033 \cdot \text{SL}$	$0.052 + 0.033 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.145	$0.086 + 0.029 \cdot \text{SL}$	$0.075 + 0.032 \cdot \text{SL}$	$0.058 + 0.034 \cdot \text{SL}$
	t_F	0.144	$0.087 + 0.028 \cdot \text{SL}$	$0.078 + 0.031 \cdot \text{SL}$	$0.060 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.090	$0.055 + 0.018 \cdot \text{SL}$	$0.065 + 0.015 \cdot \text{SL}$	$0.065 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.084	$0.046 + 0.019 \cdot \text{SL}$	$0.058 + 0.016 \cdot \text{SL}$	$0.057 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.162	$0.104 + 0.029 \cdot \text{SL}$	$0.091 + 0.032 \cdot \text{SL}$	$0.074 + 0.034 \cdot \text{SL}$
	t_F	0.136	$0.078 + 0.029 \cdot \text{SL}$	$0.067 + 0.032 \cdot \text{SL}$	$0.055 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.102	$0.069 + 0.016 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.078	$0.042 + 0.018 \cdot \text{SL}$	$0.050 + 0.016 \cdot \text{SL}$	$0.051 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND2DH/ND2/ND2D2/ND2D4

2-Input NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.115	$0.087 + 0.014 \cdot \text{SL}$	$0.081 + 0.016 \cdot \text{SL}$	$0.063 + 0.017 \cdot \text{SL}$
	t_F	0.115	$0.085 + 0.015 \cdot \text{SL}$	$0.084 + 0.015 \cdot \text{SL}$	$0.064 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.072	$0.052 + 0.010 \cdot \text{SL}$	$0.061 + 0.008 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.065	$0.044 + 0.011 \cdot \text{SL}$	$0.054 + 0.008 \cdot \text{SL}$	$0.058 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.132	$0.105 + 0.014 \cdot \text{SL}$	$0.097 + 0.016 \cdot \text{SL}$	$0.079 + 0.017 \cdot \text{SL}$
	t_F	0.107	$0.078 + 0.014 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.057 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.086	$0.068 + 0.009 \cdot \text{SL}$	$0.073 + 0.008 \cdot \text{SL}$	$0.074 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.060	$0.041 + 0.010 \cdot \text{SL}$	$0.047 + 0.008 \cdot \text{SL}$	$0.051 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

ND2D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	$0.084 + 0.008 \cdot \text{SL}$	$0.085 + 0.008 \cdot \text{SL}$	$0.063 + 0.008 \cdot \text{SL}$
	t_F	0.099	$0.083 + 0.008 \cdot \text{SL}$	$0.086 + 0.007 \cdot \text{SL}$	$0.065 + 0.008 \cdot \text{SL}$
	t_{PLH}	0.060	$0.049 + 0.006 \cdot \text{SL}$	$0.055 + 0.004 \cdot \text{SL}$	$0.065 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.054	$0.042 + 0.006 \cdot \text{SL}$	$0.048 + 0.004 \cdot \text{SL}$	$0.058 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.117	$0.102 + 0.007 \cdot \text{SL}$	$0.102 + 0.008 \cdot \text{SL}$	$0.080 + 0.008 \cdot \text{SL}$
	t_F	0.093	$0.079 + 0.007 \cdot \text{SL}$	$0.077 + 0.008 \cdot \text{SL}$	$0.057 + 0.008 \cdot \text{SL}$
	t_{PLH}	0.075	$0.065 + 0.005 \cdot \text{SL}$	$0.069 + 0.004 \cdot \text{SL}$	$0.074 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.050	$0.039 + 0.005 \cdot \text{SL}$	$0.044 + 0.004 \cdot \text{SL}$	$0.051 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND3DH/ND3/ND3D2/ND3D4

3-Input NAND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	x	1
x	0	x	1
x	x	0	1
1	1	1	0

Cell Data

Input Load (SL)											
ND3DH			ND3			ND3D2			ND3D4		
A	B	C	A	B	C	A	B	C	A	B	C
0.4	0.4	0.5	0.8	0.9	0.9	1.7	1.8	1.7	3.6	3.6	3.6
Gate Count											
ND3DH			ND3			ND3D2			ND3D4		
1.33			1.33			2.33			4.00		

ND3DH/ND3/ND3D2/ND3D4

3-Input NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.297	$0.107 + 0.095 \cdot \text{SL}$	$0.088 + 0.100 \cdot \text{SL}$	$0.079 + 0.101 \cdot \text{SL}$
	t_F	0.306	$0.120 + 0.093 \cdot \text{SL}$	$0.102 + 0.098 \cdot \text{SL}$	$0.089 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.171	$0.084 + 0.043 \cdot \text{SL}$	$0.084 + 0.044 \cdot \text{SL}$	$0.083 + 0.044 \cdot \text{SL}$
	t_{PHL}	0.162	$0.071 + 0.045 \cdot \text{SL}$	$0.070 + 0.045 \cdot \text{SL}$	$0.069 + 0.046 \cdot \text{SL}$
B to Y	t_R	0.319	$0.128 + 0.096 \cdot \text{SL}$	$0.110 + 0.100 \cdot \text{SL}$	$0.101 + 0.101 \cdot \text{SL}$
	t_F	0.302	$0.113 + 0.095 \cdot \text{SL}$	$0.100 + 0.098 \cdot \text{SL}$	$0.089 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.185	$0.099 + 0.043 \cdot \text{SL}$	$0.098 + 0.043 \cdot \text{SL}$	$0.097 + 0.044 \cdot \text{SL}$
	t_{PHL}	0.164	$0.073 + 0.046 \cdot \text{SL}$	$0.074 + 0.046 \cdot \text{SL}$	$0.073 + 0.046 \cdot \text{SL}$
C to Y	t_R	0.344	$0.153 + 0.095 \cdot \text{SL}$	$0.134 + 0.100 \cdot \text{SL}$	$0.124 + 0.101 \cdot \text{SL}$
	t_F	0.298	$0.106 + 0.096 \cdot \text{SL}$	$0.097 + 0.098 \cdot \text{SL}$	$0.089 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.198	$0.111 + 0.043 \cdot \text{SL}$	$0.110 + 0.044 \cdot \text{SL}$	$0.110 + 0.044 \cdot \text{SL}$
	t_{PHL}	0.163	$0.072 + 0.046 \cdot \text{SL}$	$0.072 + 0.046 \cdot \text{SL}$	$0.072 + 0.046 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.183	$0.101 + 0.041 \cdot \text{SL}$	$0.091 + 0.044 \cdot \text{SL}$	$0.074 + 0.046 \cdot \text{SL}$
	t_F	0.202	$0.118 + 0.042 \cdot \text{SL}$	$0.105 + 0.045 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.115	$0.073 + 0.021 \cdot \text{SL}$	$0.078 + 0.020 \cdot \text{SL}$	$0.077 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.063 + 0.023 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.204	$0.122 + 0.041 \cdot \text{SL}$	$0.110 + 0.044 \cdot \text{SL}$	$0.094 + 0.046 \cdot \text{SL}$
	t_F	0.197	$0.110 + 0.043 \cdot \text{SL}$	$0.099 + 0.046 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.129	$0.089 + 0.020 \cdot \text{SL}$	$0.091 + 0.020 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.110	$0.064 + 0.023 \cdot \text{SL}$	$0.069 + 0.022 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.227	$0.145 + 0.041 \cdot \text{SL}$	$0.134 + 0.044 \cdot \text{SL}$	$0.116 + 0.046 \cdot \text{SL}$
	t_F	0.190	$0.102 + 0.044 \cdot \text{SL}$	$0.093 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.140	$0.100 + 0.020 \cdot \text{SL}$	$0.101 + 0.020 \cdot \text{SL}$	$0.101 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.109	$0.063 + 0.023 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND3DH/ND3/ND3D2/ND3D4

3-Input NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.135	$0.095 + 0.020 \cdot \text{SL}$	$0.089 + 0.021 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_F	0.153	$0.113 + 0.020 \cdot \text{SL}$	$0.105 + 0.022 \cdot \text{SL}$	$0.084 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.091	$0.067 + 0.012 \cdot \text{SL}$	$0.075 + 0.010 \cdot \text{SL}$	$0.075 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.155	$0.116 + 0.020 \cdot \text{SL}$	$0.109 + 0.022 \cdot \text{SL}$	$0.090 + 0.023 \cdot \text{SL}$
	t_F	0.148	$0.108 + 0.020 \cdot \text{SL}$	$0.098 + 0.023 \cdot \text{SL}$	$0.083 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.105	$0.083 + 0.011 \cdot \text{SL}$	$0.087 + 0.010 \cdot \text{SL}$	$0.087 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.064 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.179	$0.141 + 0.019 \cdot \text{SL}$	$0.133 + 0.022 \cdot \text{SL}$	$0.113 + 0.023 \cdot \text{SL}$
	t_F	0.139	$0.098 + 0.021 \cdot \text{SL}$	$0.090 + 0.023 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.117	$0.096 + 0.010 \cdot \text{SL}$	$0.098 + 0.010 \cdot \text{SL}$	$0.097 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.081	$0.056 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

ND3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.116	$0.098 + 0.009 \cdot \text{SL}$	$0.093 + 0.011 \cdot \text{SL}$	$0.072 + 0.011 \cdot \text{SL}$
	t_F	0.133	$0.113 + 0.010 \cdot \text{SL}$	$0.110 + 0.011 \cdot \text{SL}$	$0.087 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.077	$0.064 + 0.007 \cdot \text{SL}$	$0.070 + 0.005 \cdot \text{SL}$	$0.074 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.067	$0.053 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.062 + 0.005 \cdot \text{SL}$
B to Y	t_R	0.136	$0.118 + 0.009 \cdot \text{SL}$	$0.113 + 0.011 \cdot \text{SL}$	$0.092 + 0.011 \cdot \text{SL}$
	t_F	0.127	$0.106 + 0.010 \cdot \text{SL}$	$0.102 + 0.011 \cdot \text{SL}$	$0.084 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.087 + 0.005 \cdot \text{SL}$	$0.087 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.070	$0.057 + 0.007 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.065 + 0.005 \cdot \text{SL}$
C to Y	t_R	0.160	$0.141 + 0.010 \cdot \text{SL}$	$0.138 + 0.011 \cdot \text{SL}$	$0.115 + 0.011 \cdot \text{SL}$
	t_F	0.118	$0.097 + 0.010 \cdot \text{SL}$	$0.093 + 0.011 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.106	$0.095 + 0.006 \cdot \text{SL}$	$0.097 + 0.005 \cdot \text{SL}$	$0.097 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.062 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND4DH/ND4/ND4D2/ND4D2B/ND4D4

4-Input NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	x	x	1
x	0	x	x	1
x	x	0	x	1
x	x	x	0	1
1	1	1	1	0

Cell Data

Input Load (SL)																			
ND4DH				ND4				ND4D2				ND4D2B				ND4D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.4	0.4	0.4	0.4	0.9	0.8	0.8	0.8	1.5	1.6	1.7	1.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8
Gate Count																			
ND4DH				ND4				ND4D2				ND4D2B				ND4D4			
1.67				1.67				2.67				2.67				3.00			

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.331	$0.114 + 0.108 \cdot \text{SL}$	$0.096 + 0.113 \cdot \text{SL}$	$0.089 + 0.114 \cdot \text{SL}$
	t_F	0.397	$0.151 + 0.123 \cdot \text{SL}$	$0.132 + 0.128 \cdot \text{SL}$	$0.127 + 0.129 \cdot \text{SL}$
	t_{PLH}	0.188	$0.091 + 0.049 \cdot \text{SL}$	$0.090 + 0.049 \cdot \text{SL}$	$0.090 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.192	$0.077 + 0.058 \cdot \text{SL}$	$0.075 + 0.058 \cdot \text{SL}$	$0.074 + 0.058 \cdot \text{SL}$
B to Y	t_R	0.356	$0.138 + 0.109 \cdot \text{SL}$	$0.122 + 0.113 \cdot \text{SL}$	$0.115 + 0.114 \cdot \text{SL}$
	t_F	0.397	$0.149 + 0.124 \cdot \text{SL}$	$0.136 + 0.128 \cdot \text{SL}$	$0.128 + 0.129 \cdot \text{SL}$
	t_{PLH}	0.205	$0.107 + 0.049 \cdot \text{SL}$	$0.106 + 0.049 \cdot \text{SL}$	$0.106 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.203	$0.087 + 0.058 \cdot \text{SL}$	$0.087 + 0.058 \cdot \text{SL}$	$0.087 + 0.058 \cdot \text{SL}$
C to Y	t_R	0.383	$0.167 + 0.108 \cdot \text{SL}$	$0.148 + 0.113 \cdot \text{SL}$	$0.142 + 0.114 \cdot \text{SL}$
	t_F	0.394	$0.143 + 0.126 \cdot \text{SL}$	$0.134 + 0.128 \cdot \text{SL}$	$0.128 + 0.129 \cdot \text{SL}$
	t_{PLH}	0.219	$0.120 + 0.049 \cdot \text{SL}$	$0.121 + 0.049 \cdot \text{SL}$	$0.121 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.210	$0.093 + 0.059 \cdot \text{SL}$	$0.093 + 0.058 \cdot \text{SL}$	$0.094 + 0.058 \cdot \text{SL}$
D to Y	t_R	0.411	$0.195 + 0.108 \cdot \text{SL}$	$0.176 + 0.113 \cdot \text{SL}$	$0.169 + 0.114 \cdot \text{SL}$
	t_F	0.391	$0.139 + 0.126 \cdot \text{SL}$	$0.132 + 0.128 \cdot \text{SL}$	$0.128 + 0.129 \cdot \text{SL}$
	t_{PLH}	0.230	$0.129 + 0.050 \cdot \text{SL}$	$0.132 + 0.049 \cdot \text{SL}$	$0.134 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.211	$0.094 + 0.059 \cdot \text{SL}$	$0.095 + 0.058 \cdot \text{SL}$	$0.096 + 0.058 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND4DH/ND4/ND4D2/ND4D2B/ND4D4

4-Input NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.201	$0.104 + 0.049 \cdot \text{SL}$	$0.091 + 0.052 \cdot \text{SL}$	$0.076 + 0.054 \cdot \text{SL}$
	t_F	0.253	$0.140 + 0.057 \cdot \text{SL}$	$0.127 + 0.060 \cdot \text{SL}$	$0.110 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.127	$0.079 + 0.024 \cdot \text{SL}$	$0.082 + 0.023 \cdot \text{SL}$	$0.081 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.122	$0.066 + 0.028 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$	$0.065 + 0.028 \cdot \text{SL}$
B to Y	t_R	0.225	$0.127 + 0.049 \cdot \text{SL}$	$0.115 + 0.052 \cdot \text{SL}$	$0.100 + 0.054 \cdot \text{SL}$
	t_F	0.251	$0.137 + 0.057 \cdot \text{SL}$	$0.125 + 0.060 \cdot \text{SL}$	$0.114 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.143	$0.097 + 0.023 \cdot \text{SL}$	$0.097 + 0.023 \cdot \text{SL}$	$0.097 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.131	$0.073 + 0.029 \cdot \text{SL}$	$0.077 + 0.028 \cdot \text{SL}$	$0.076 + 0.028 \cdot \text{SL}$
C to Y	t_R	0.251	$0.154 + 0.049 \cdot \text{SL}$	$0.141 + 0.052 \cdot \text{SL}$	$0.126 + 0.054 \cdot \text{SL}$
	t_F	0.247	$0.130 + 0.058 \cdot \text{SL}$	$0.121 + 0.061 \cdot \text{SL}$	$0.113 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.156	$0.109 + 0.023 \cdot \text{SL}$	$0.110 + 0.023 \cdot \text{SL}$	$0.110 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.137	$0.080 + 0.029 \cdot \text{SL}$	$0.082 + 0.028 \cdot \text{SL}$	$0.083 + 0.028 \cdot \text{SL}$
D to Y	t_R	0.278	$0.181 + 0.049 \cdot \text{SL}$	$0.169 + 0.052 \cdot \text{SL}$	$0.152 + 0.054 \cdot \text{SL}$
	t_F	0.243	$0.125 + 0.059 \cdot \text{SL}$	$0.118 + 0.061 \cdot \text{SL}$	$0.111 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.166	$0.118 + 0.024 \cdot \text{SL}$	$0.120 + 0.023 \cdot \text{SL}$	$0.122 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.139	$0.082 + 0.029 \cdot \text{SL}$	$0.084 + 0.028 \cdot \text{SL}$	$0.084 + 0.028 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.148	$0.102 + 0.023 \cdot \text{SL}$	$0.092 + 0.026 \cdot \text{SL}$	$0.074 + 0.027 \cdot \text{SL}$
	t_F	0.191	$0.137 + 0.027 \cdot \text{SL}$	$0.128 + 0.030 \cdot \text{SL}$	$0.108 + 0.031 \cdot \text{SL}$
	t_{PLH}	0.099	$0.072 + 0.013 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.091	$0.060 + 0.015 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
B to Y	t_R	0.172	$0.126 + 0.023 \cdot \text{SL}$	$0.117 + 0.026 \cdot \text{SL}$	$0.099 + 0.027 \cdot \text{SL}$
	t_F	0.190	$0.134 + 0.028 \cdot \text{SL}$	$0.126 + 0.030 \cdot \text{SL}$	$0.111 + 0.031 \cdot \text{SL}$
	t_{PLH}	0.118	$0.094 + 0.012 \cdot \text{SL}$	$0.096 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.100	$0.070 + 0.015 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
C to Y	t_R	0.199	$0.153 + 0.023 \cdot \text{SL}$	$0.145 + 0.025 \cdot \text{SL}$	$0.125 + 0.027 \cdot \text{SL}$
	t_F	0.184	$0.127 + 0.028 \cdot \text{SL}$	$0.120 + 0.030 \cdot \text{SL}$	$0.109 + 0.031 \cdot \text{SL}$
	t_{PLH}	0.132	$0.108 + 0.012 \cdot \text{SL}$	$0.109 + 0.012 \cdot \text{SL}$	$0.110 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.107	$0.076 + 0.015 \cdot \text{SL}$	$0.081 + 0.014 \cdot \text{SL}$	$0.082 + 0.014 \cdot \text{SL}$
D to Y	t_R	0.226	$0.179 + 0.023 \cdot \text{SL}$	$0.171 + 0.025 \cdot \text{SL}$	$0.151 + 0.027 \cdot \text{SL}$
	t_F	0.179	$0.122 + 0.029 \cdot \text{SL}$	$0.116 + 0.030 \cdot \text{SL}$	$0.107 + 0.031 \cdot \text{SL}$
	t_{PLH}	0.140	$0.116 + 0.012 \cdot \text{SL}$	$0.117 + 0.012 \cdot \text{SL}$	$0.120 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.109	$0.079 + 0.015 \cdot \text{SL}$	$0.082 + 0.014 \cdot \text{SL}$	$0.083 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

ND4DH/ND4/ND4D2/ND4D2B/ND4D4

4-Input NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND4D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$	$0.035 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.042 + 0.013 \cdot \text{SL}$	$0.046 + 0.011 \cdot \text{SL}$	$0.038 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.215	$0.200 + 0.008 \cdot \text{SL}$	$0.204 + 0.006 \cdot \text{SL}$	$0.208 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.218	$0.201 + 0.008 \cdot \text{SL}$	$0.208 + 0.007 \cdot \text{SL}$	$0.215 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$	$0.035 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.045 + 0.011 \cdot \text{SL}$	$0.044 + 0.011 \cdot \text{SL}$	$0.038 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.234	$0.219 + 0.008 \cdot \text{SL}$	$0.224 + 0.006 \cdot \text{SL}$	$0.227 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.227	$0.210 + 0.008 \cdot \text{SL}$	$0.217 + 0.007 \cdot \text{SL}$	$0.224 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$	$0.035 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.043 + 0.012 \cdot \text{SL}$	$0.046 + 0.011 \cdot \text{SL}$	$0.038 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.251	$0.235 + 0.008 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.216 + 0.008 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$	$0.229 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$	$0.036 + 0.014 \cdot \text{SL}$
	t_F	0.066	$0.041 + 0.013 \cdot \text{SL}$	$0.047 + 0.011 \cdot \text{SL}$	$0.038 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.264	$0.249 + 0.008 \cdot \text{SL}$	$0.254 + 0.006 \cdot \text{SL}$	$0.257 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.235	$0.218 + 0.008 \cdot \text{SL}$	$0.224 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

ND4D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.071	$0.058 + 0.007 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.245	$0.235 + 0.005 \cdot \text{SL}$	$0.240 + 0.003 \cdot \text{SL}$	$0.250 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.247	$0.237 + 0.005 \cdot \text{SL}$	$0.242 + 0.004 \cdot \text{SL}$	$0.258 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.072	$0.059 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.264	$0.255 + 0.005 \cdot \text{SL}$	$0.260 + 0.003 \cdot \text{SL}$	$0.270 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.246 + 0.005 \cdot \text{SL}$	$0.252 + 0.004 \cdot \text{SL}$	$0.268 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.073	$0.060 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.282	$0.272 + 0.005 \cdot \text{SL}$	$0.277 + 0.003 \cdot \text{SL}$	$0.288 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.262	$0.251 + 0.005 \cdot \text{SL}$	$0.257 + 0.004 \cdot \text{SL}$	$0.273 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.074	$0.061 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.296	$0.287 + 0.005 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$	$0.302 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.264	$0.254 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.275 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND5/ND5D2/ND5D4

5-Input NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	x	x	x	1
x	0	x	x	x	1
x	x	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
1	1	1	1	1	0

Cell Data

Input Load (SL)															Gate Count		
ND5					ND5D2					ND5D4					ND5	ND5D2	ND5D4
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.7	0.8	0.8	0.9	0.9	0.7	0.8	0.8	0.9	0.9	0.7	0.8	0.8	0.9	0.9	3.00	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.101	$0.047 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.104	$0.056 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.235	$0.208 + 0.013 \cdot \text{SL}$	$0.211 + 0.012 \cdot \text{SL}$	$0.212 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.224	$0.191 + 0.016 \cdot \text{SL}$	$0.201 + 0.014 \cdot \text{SL}$	$0.209 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.105	$0.057 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.258	$0.231 + 0.013 \cdot \text{SL}$	$0.235 + 0.012 \cdot \text{SL}$	$0.236 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.228	$0.195 + 0.016 \cdot \text{SL}$	$0.205 + 0.014 \cdot \text{SL}$	$0.213 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.103	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.104	$0.055 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.278	$0.251 + 0.013 \cdot \text{SL}$	$0.254 + 0.012 \cdot \text{SL}$	$0.255 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.227	$0.194 + 0.016 \cdot \text{SL}$	$0.204 + 0.014 \cdot \text{SL}$	$0.212 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.105	$0.052 + 0.026 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.040 + 0.029 \cdot \text{SL}$
	t_F	0.104	$0.055 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.229	$0.201 + 0.014 \cdot \text{SL}$	$0.206 + 0.013 \cdot \text{SL}$	$0.207 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.214	$0.182 + 0.016 \cdot \text{SL}$	$0.191 + 0.014 \cdot \text{SL}$	$0.200 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.105	$0.052 + 0.026 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.040 + 0.029 \cdot \text{SL}$
	t_F	0.104	$0.056 + 0.024 \cdot \text{SL}$	$0.058 + 0.024 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.246	$0.218 + 0.014 \cdot \text{SL}$	$0.223 + 0.013 \cdot \text{SL}$	$0.224 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.211	$0.178 + 0.016 \cdot \text{SL}$	$0.188 + 0.014 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND5/ND5D2/ND5D4

5-Input NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$	$0.036 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.059 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.239	$0.223 + 0.008 \cdot \text{SL}$	$0.228 + 0.007 \cdot \text{SL}$	$0.233 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.233	$0.212 + 0.010 \cdot \text{SL}$	$0.222 + 0.008 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.075	$0.048 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.263	$0.247 + 0.008 \cdot \text{SL}$	$0.252 + 0.006 \cdot \text{SL}$	$0.257 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.237	$0.217 + 0.010 \cdot \text{SL}$	$0.226 + 0.008 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.283	$0.267 + 0.008 \cdot \text{SL}$	$0.272 + 0.007 \cdot \text{SL}$	$0.277 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.236	$0.215 + 0.010 \cdot \text{SL}$	$0.225 + 0.008 \cdot \text{SL}$	$0.242 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.061 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.231	$0.215 + 0.008 \cdot \text{SL}$	$0.221 + 0.007 \cdot \text{SL}$	$0.226 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.223	$0.202 + 0.010 \cdot \text{SL}$	$0.212 + 0.008 \cdot \text{SL}$	$0.229 + 0.007 \cdot \text{SL}$
E to Y	t_R	0.079	$0.052 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.248	$0.232 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.243 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.219	$0.199 + 0.010 \cdot \text{SL}$	$0.209 + 0.008 \cdot \text{SL}$	$0.226 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND5D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.063 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.087 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.269	$0.259 + 0.005 \cdot \text{SL}$	$0.265 + 0.004 \cdot \text{SL}$	$0.276 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.279	$0.266 + 0.007 \cdot \text{SL}$	$0.274 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.076	$0.062 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.089 + 0.007 \cdot \text{SL}$	$0.091 + 0.006 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.294	$0.284 + 0.005 \cdot \text{SL}$	$0.289 + 0.004 \cdot \text{SL}$	$0.301 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.283	$0.270 + 0.006 \cdot \text{SL}$	$0.278 + 0.004 \cdot \text{SL}$	$0.304 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.077	$0.064 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.101	$0.087 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.315	$0.305 + 0.005 \cdot \text{SL}$	$0.310 + 0.004 \cdot \text{SL}$	$0.322 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.269 + 0.007 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.303 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.079	$0.066 + 0.007 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.101	$0.086 + 0.007 \cdot \text{SL}$	$0.091 + 0.006 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.255	$0.244 + 0.005 \cdot \text{SL}$	$0.250 + 0.004 \cdot \text{SL}$	$0.263 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.268	$0.255 + 0.007 \cdot \text{SL}$	$0.263 + 0.004 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.101	$0.088 + 0.007 \cdot \text{SL}$	$0.091 + 0.006 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.273	$0.263 + 0.005 \cdot \text{SL}$	$0.269 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.265	$0.252 + 0.006 \cdot \text{SL}$	$0.260 + 0.004 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND6/ND6D2/ND6D4

6-Input NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	1	1	1	0
Other States						1

Cell Data

Input Load (SL)																	
ND6						ND6D2						ND6D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.7	0.8	0.8	0.7	0.8	0.8	0.7	0.8	0.8	0.7	0.8	0.8	0.7	0.8	0.8	0.7	0.8	0.8
Gate Count																	
ND6						ND6D2						ND6D4					
3.33						3.67						4.33					

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.040 + 0.029 \cdot \text{SL}$
	t_F	0.105	$0.058 + 0.024 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.239	$0.212 + 0.013 \cdot \text{SL}$	$0.216 + 0.013 \cdot \text{SL}$	$0.217 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.225	$0.192 + 0.016 \cdot \text{SL}$	$0.202 + 0.014 \cdot \text{SL}$	$0.210 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.104	$0.051 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.041 + 0.029 \cdot \text{SL}$
	t_F	0.106	$0.058 + 0.024 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.263	$0.236 + 0.013 \cdot \text{SL}$	$0.240 + 0.012 \cdot \text{SL}$	$0.241 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.228	$0.196 + 0.016 \cdot \text{SL}$	$0.205 + 0.014 \cdot \text{SL}$	$0.213 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.105	$0.053 + 0.026 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$	$0.041 + 0.029 \cdot \text{SL}$
	t_F	0.105	$0.058 + 0.024 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.283	$0.256 + 0.013 \cdot \text{SL}$	$0.260 + 0.012 \cdot \text{SL}$	$0.261 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.227	$0.195 + 0.016 \cdot \text{SL}$	$0.204 + 0.014 \cdot \text{SL}$	$0.213 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.107	$0.054 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.056 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.258	$0.231 + 0.014 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$	$0.237 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.235	$0.203 + 0.016 \cdot \text{SL}$	$0.212 + 0.014 \cdot \text{SL}$	$0.221 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.109	$0.057 + 0.026 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.057 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.283	$0.255 + 0.014 \cdot \text{SL}$	$0.260 + 0.013 \cdot \text{SL}$	$0.261 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.239	$0.206 + 0.016 \cdot \text{SL}$	$0.216 + 0.014 \cdot \text{SL}$	$0.224 + 0.013 \cdot \text{SL}$
F to Y	t_R	0.110	$0.057 + 0.026 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.106	$0.058 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.299	$0.272 + 0.014 \cdot \text{SL}$	$0.277 + 0.012 \cdot \text{SL}$	$0.278 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.238	$0.205 + 0.016 \cdot \text{SL}$	$0.215 + 0.014 \cdot \text{SL}$	$0.223 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND6/ND6D2/ND6D4

6-Input NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.075	$0.049 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.243	$0.227 + 0.008 \cdot \text{SL}$	$0.233 + 0.007 \cdot \text{SL}$	$0.237 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.212 + 0.010 \cdot \text{SL}$	$0.221 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.038 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.267	$0.251 + 0.008 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.236	$0.216 + 0.010 \cdot \text{SL}$	$0.225 + 0.008 \cdot \text{SL}$	$0.242 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.059 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.288	$0.272 + 0.008 \cdot \text{SL}$	$0.277 + 0.007 \cdot \text{SL}$	$0.282 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.235	$0.214 + 0.010 \cdot \text{SL}$	$0.224 + 0.008 \cdot \text{SL}$	$0.241 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.261	$0.244 + 0.008 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.256 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.242	$0.222 + 0.010 \cdot \text{SL}$	$0.231 + 0.008 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$
E to Y	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.285	$0.269 + 0.008 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.281 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.246	$0.225 + 0.010 \cdot \text{SL}$	$0.235 + 0.008 \cdot \text{SL}$	$0.252 + 0.007 \cdot \text{SL}$
F to Y	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.302	$0.286 + 0.008 \cdot \text{SL}$	$0.292 + 0.007 \cdot \text{SL}$	$0.298 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.245	$0.225 + 0.010 \cdot \text{SL}$	$0.234 + 0.008 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND6D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.077	$0.063 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.087 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.274	$0.265 + 0.005 \cdot \text{SL}$	$0.270 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.279	$0.266 + 0.007 \cdot \text{SL}$	$0.274 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.078	$0.065 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.089 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.299	$0.289 + 0.005 \cdot \text{SL}$	$0.295 + 0.004 \cdot \text{SL}$	$0.307 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.283	$0.270 + 0.006 \cdot \text{SL}$	$0.278 + 0.004 \cdot \text{SL}$	$0.304 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.080	$0.066 + 0.007 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.088 + 0.007 \cdot \text{SL}$	$0.093 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.321	$0.311 + 0.005 \cdot \text{SL}$	$0.316 + 0.004 \cdot \text{SL}$	$0.328 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.269 + 0.007 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.303 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.069 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.103	$0.090 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.291	$0.281 + 0.005 \cdot \text{SL}$	$0.286 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.290	$0.277 + 0.006 \cdot \text{SL}$	$0.284 + 0.004 \cdot \text{SL}$	$0.311 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.103	$0.088 + 0.007 \cdot \text{SL}$	$0.093 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.305 + 0.005 \cdot \text{SL}$	$0.311 + 0.004 \cdot \text{SL}$	$0.325 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.293	$0.280 + 0.006 \cdot \text{SL}$	$0.288 + 0.004 \cdot \text{SL}$	$0.314 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.088 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.333	$0.323 + 0.005 \cdot \text{SL}$	$0.329 + 0.004 \cdot \text{SL}$	$0.342 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.292	$0.279 + 0.007 \cdot \text{SL}$	$0.287 + 0.004 \cdot \text{SL}$	$0.313 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

ND8/ND8D2/ND8D4

8-Input NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	1	1	1	1	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
ND8								ND8
A	B	C	D	E	F	G	H	
0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	4.00
ND8D2								ND8D2
A	B	C	D	E	F	G	H	
0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	4.33
ND8D4								ND8D4
A	B	C	D	E	F	G	H	
0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	5.00

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	$0.051 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$	$0.041 + 0.029 \cdot \text{SL}$
	t_F	0.106	$0.059 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.257	$0.230 + 0.014 \cdot \text{SL}$	$0.234 + 0.012 \cdot \text{SL}$	$0.235 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.239	$0.207 + 0.016 \cdot \text{SL}$	$0.216 + 0.014 \cdot \text{SL}$	$0.224 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.042 + 0.029 \cdot \text{SL}$
	t_F	0.105	$0.057 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.284	$0.257 + 0.014 \cdot \text{SL}$	$0.261 + 0.013 \cdot \text{SL}$	$0.263 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.249	$0.217 + 0.016 \cdot \text{SL}$	$0.226 + 0.014 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.107	$0.055 + 0.026 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.042 + 0.029 \cdot \text{SL}$
	t_F	0.105	$0.055 + 0.025 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.307	$0.280 + 0.014 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.286 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.256	$0.223 + 0.016 \cdot \text{SL}$	$0.232 + 0.014 \cdot \text{SL}$	$0.241 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.109	$0.057 + 0.026 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.057 + 0.024 \cdot \text{SL}$	$0.060 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.327	$0.299 + 0.014 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$	$0.305 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.258	$0.226 + 0.016 \cdot \text{SL}$	$0.235 + 0.014 \cdot \text{SL}$	$0.243 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.111	$0.059 + 0.026 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.106	$0.058 + 0.024 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.278	$0.250 + 0.014 \cdot \text{SL}$	$0.255 + 0.013 \cdot \text{SL}$	$0.257 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.250	$0.218 + 0.016 \cdot \text{SL}$	$0.227 + 0.014 \cdot \text{SL}$	$0.236 + 0.013 \cdot \text{SL}$
F to Y	t_R	0.112	$0.060 + 0.026 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.106	$0.057 + 0.025 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.305	$0.277 + 0.014 \cdot \text{SL}$	$0.282 + 0.013 \cdot \text{SL}$	$0.284 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.260	$0.228 + 0.016 \cdot \text{SL}$	$0.237 + 0.014 \cdot \text{SL}$	$0.246 + 0.013 \cdot \text{SL}$
G to Y	t_R	0.112	$0.060 + 0.026 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.059 + 0.024 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.329	$0.301 + 0.014 \cdot \text{SL}$	$0.306 + 0.013 \cdot \text{SL}$	$0.308 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.267	$0.235 + 0.016 \cdot \text{SL}$	$0.244 + 0.014 \cdot \text{SL}$	$0.253 + 0.013 \cdot \text{SL}$
H to Y	t_R	0.114	$0.062 + 0.026 \cdot \text{SL}$	$0.056 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.059 + 0.024 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.349	$0.321 + 0.014 \cdot \text{SL}$	$0.326 + 0.013 \cdot \text{SL}$	$0.328 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.270	$0.237 + 0.016 \cdot \text{SL}$	$0.247 + 0.014 \cdot \text{SL}$	$0.255 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ND8/ND8D2/ND8D4

8-Input NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.265	$0.248 + 0.008 \cdot \text{SL}$	$0.254 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.250	$0.230 + 0.010 \cdot \text{SL}$	$0.239 + 0.008 \cdot \text{SL}$	$0.256 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.292	$0.276 + 0.008 \cdot \text{SL}$	$0.282 + 0.007 \cdot \text{SL}$	$0.288 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.260	$0.240 + 0.010 \cdot \text{SL}$	$0.249 + 0.008 \cdot \text{SL}$	$0.266 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.013 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.316	$0.300 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.266	$0.246 + 0.010 \cdot \text{SL}$	$0.256 + 0.008 \cdot \text{SL}$	$0.272 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.083	$0.056 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.336	$0.320 + 0.008 \cdot \text{SL}$	$0.326 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.269	$0.249 + 0.010 \cdot \text{SL}$	$0.258 + 0.008 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$
E to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.063 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.283	$0.266 + 0.008 \cdot \text{SL}$	$0.272 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.259	$0.239 + 0.010 \cdot \text{SL}$	$0.248 + 0.008 \cdot \text{SL}$	$0.265 + 0.007 \cdot \text{SL}$
F to Y	t_R	0.087	$0.060 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.068 + 0.012 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.310	$0.294 + 0.008 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.269	$0.249 + 0.010 \cdot \text{SL}$	$0.258 + 0.008 \cdot \text{SL}$	$0.276 + 0.007 \cdot \text{SL}$
G to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.068 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.335	$0.318 + 0.008 \cdot \text{SL}$	$0.324 + 0.007 \cdot \text{SL}$	$0.332 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.276	$0.255 + 0.010 \cdot \text{SL}$	$0.265 + 0.008 \cdot \text{SL}$	$0.282 + 0.007 \cdot \text{SL}$
H to Y	t_R	0.089	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.355	$0.338 + 0.008 \cdot \text{SL}$	$0.345 + 0.007 \cdot \text{SL}$	$0.352 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.278	$0.258 + 0.010 \cdot \text{SL}$	$0.267 + 0.008 \cdot \text{SL}$	$0.285 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

ND8D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.083	$0.070 + 0.007 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.103	$0.090 + 0.007 \cdot \text{SL}$	$0.093 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.300	$0.290 + 0.005 \cdot \text{SL}$	$0.295 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.298	$0.285 + 0.006 \cdot \text{SL}$	$0.293 + 0.004 \cdot \text{SL}$	$0.319 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.084	$0.071 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.091 + 0.006 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.096 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.328	$0.318 + 0.005 \cdot \text{SL}$	$0.323 + 0.004 \cdot \text{SL}$	$0.337 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.309	$0.296 + 0.006 \cdot \text{SL}$	$0.304 + 0.004 \cdot \text{SL}$	$0.330 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.089 + 0.007 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.353	$0.342 + 0.005 \cdot \text{SL}$	$0.348 + 0.004 \cdot \text{SL}$	$0.362 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.315	$0.302 + 0.006 \cdot \text{SL}$	$0.310 + 0.004 \cdot \text{SL}$	$0.336 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.087	$0.074 + 0.006 \cdot \text{SL}$	$0.073 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.103	$0.089 + 0.007 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.374	$0.363 + 0.005 \cdot \text{SL}$	$0.369 + 0.004 \cdot \text{SL}$	$0.383 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.317	$0.304 + 0.007 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.338 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.007 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.092 + 0.006 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.306 + 0.005 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.327 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.307	$0.294 + 0.006 \cdot \text{SL}$	$0.302 + 0.004 \cdot \text{SL}$	$0.328 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.077 + 0.007 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.089 + 0.007 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$	$0.098 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.344	$0.333 + 0.005 \cdot \text{SL}$	$0.340 + 0.004 \cdot \text{SL}$	$0.355 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.317	$0.304 + 0.007 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.338 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.092	$0.080 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.092 + 0.006 \cdot \text{SL}$	$0.093 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.369	$0.359 + 0.005 \cdot \text{SL}$	$0.365 + 0.004 \cdot \text{SL}$	$0.380 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.311 + 0.006 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.345 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.094	$0.082 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.104	$0.092 + 0.006 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.390	$0.380 + 0.005 \cdot \text{SL}$	$0.386 + 0.004 \cdot \text{SL}$	$0.401 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.326	$0.313 + 0.006 \cdot \text{SL}$	$0.321 + 0.004 \cdot \text{SL}$	$0.347 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A

2-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	0

Cell Data

Input Load (SL)											
NR2DH		NR2		NR2D2		NR2D2B		NR2D4		NR2A	
A	B	A	B	A	B	A	B	A	B	A	B
0.5	0.6	1.1	1.1	2.2	2.3	1.0	1.0	1.0	1.0	1.7	1.8
Gate Count											
NR2DH		NR2		NR2D2		NR2D2B		NR2D4		NR2A	
1.00		1.00		1.67		2.00		2.33		1.67	

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.339	$0.116 + 0.112 \cdot \text{SL}$	$0.099 + 0.116 \cdot \text{SL}$	$0.089 + 0.117 \cdot \text{SL}$
	t_F	0.143	$0.075 + 0.034 \cdot \text{SL}$	$0.061 + 0.038 \cdot \text{SL}$	$0.039 + 0.040 \cdot \text{SL}$
	t_{PLH}	0.178	$0.080 + 0.049 \cdot \text{SL}$	$0.077 + 0.050 \cdot \text{SL}$	$0.074 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.093	$0.044 + 0.024 \cdot \text{SL}$	$0.057 + 0.021 \cdot \text{SL}$	$0.056 + 0.021 \cdot \text{SL}$
B to Y	t_R	0.336	$0.110 + 0.113 \cdot \text{SL}$	$0.098 + 0.116 \cdot \text{SL}$	$0.089 + 0.117 \cdot \text{SL}$
	t_F	0.160	$0.092 + 0.034 \cdot \text{SL}$	$0.078 + 0.038 \cdot \text{SL}$	$0.055 + 0.040 \cdot \text{SL}$
	t_{PLH}	0.177	$0.077 + 0.050 \cdot \text{SL}$	$0.076 + 0.050 \cdot \text{SL}$	$0.076 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.103	$0.057 + 0.023 \cdot \text{SL}$	$0.065 + 0.021 \cdot \text{SL}$	$0.065 + 0.021 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.211	$0.110 + 0.051 \cdot \text{SL}$	$0.099 + 0.053 \cdot \text{SL}$	$0.083 + 0.055 \cdot \text{SL}$
	t_F	0.105	$0.070 + 0.017 \cdot \text{SL}$	$0.071 + 0.017 \cdot \text{SL}$	$0.053 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.119	$0.070 + 0.024 \cdot \text{SL}$	$0.074 + 0.023 \cdot \text{SL}$	$0.070 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.064	$0.034 + 0.015 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.055 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.206	$0.103 + 0.051 \cdot \text{SL}$	$0.093 + 0.054 \cdot \text{SL}$	$0.084 + 0.055 \cdot \text{SL}$
	t_F	0.124	$0.093 + 0.016 \cdot \text{SL}$	$0.089 + 0.017 \cdot \text{SL}$	$0.070 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.117	$0.068 + 0.024 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.070 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.076	$0.048 + 0.014 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.064 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A

2-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.153	$0.103 + 0.025 \cdot \text{SL}$	$0.097 + 0.026 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$
	t_F	0.083	$0.064 + 0.010 \cdot \text{SL}$	$0.068 + 0.008 \cdot \text{SL}$	$0.056 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.091	$0.064 + 0.013 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$	$0.068 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.045	$0.026 + 0.009 \cdot \text{SL}$	$0.039 + 0.006 \cdot \text{SL}$	$0.054 + 0.005 \cdot \text{SL}$
B to Y	t_R	0.148	$0.100 + 0.024 \cdot \text{SL}$	$0.090 + 0.027 \cdot \text{SL}$	$0.077 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.088 + 0.008 \cdot \text{SL}$	$0.089 + 0.008 \cdot \text{SL}$	$0.072 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.067 + 0.012 \cdot \text{SL}$	$0.067 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.059	$0.042 + 0.008 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$	$0.062 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NR2D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.068	$0.041 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$	$0.031 + 0.014 \cdot \text{SL}$
	t_F	0.066	$0.041 + 0.013 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$	$0.037 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.186	$0.171 + 0.007 \cdot \text{SL}$	$0.176 + 0.006 \cdot \text{SL}$	$0.178 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.180	$0.162 + 0.009 \cdot \text{SL}$	$0.169 + 0.007 \cdot \text{SL}$	$0.178 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.068	$0.041 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$	$0.030 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.043 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$	$0.038 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.186	$0.171 + 0.008 \cdot \text{SL}$	$0.176 + 0.006 \cdot \text{SL}$	$0.178 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.199	$0.182 + 0.009 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$	$0.197 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NR2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.066	$0.053 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$	$0.042 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.059 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.213	$0.204 + 0.004 \cdot \text{SL}$	$0.208 + 0.003 \cdot \text{SL}$	$0.216 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.207	$0.196 + 0.005 \cdot \text{SL}$	$0.202 + 0.004 \cdot \text{SL}$	$0.220 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$	$0.042 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.059 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.213	$0.204 + 0.004 \cdot \text{SL}$	$0.208 + 0.003 \cdot \text{SL}$	$0.216 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.226	$0.215 + 0.005 \cdot \text{SL}$	$0.221 + 0.004 \cdot \text{SL}$	$0.239 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A

2-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR2A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.153	$0.107 + 0.023 \cdot \text{SL}$	$0.097 + 0.025 \cdot \text{SL}$	$0.085 + 0.027 \cdot \text{SL}$
	t_F	0.104	$0.072 + 0.016 \cdot \text{SL}$	$0.066 + 0.018 \cdot \text{SL}$	$0.053 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.076	$0.047 + 0.015 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.078	$0.051 + 0.014 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.065 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.143	$0.096 + 0.023 \cdot \text{SL}$	$0.085 + 0.026 \cdot \text{SL}$	$0.075 + 0.027 \cdot \text{SL}$
	t_F	0.135	$0.103 + 0.016 \cdot \text{SL}$	$0.097 + 0.018 \cdot \text{SL}$	$0.086 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.078	$0.050 + 0.014 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.100	$0.077 + 0.012 \cdot \text{SL}$	$0.082 + 0.010 \cdot \text{SL}$	$0.082 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A

3-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	1
Other States			0

Cell Data

Input Load (SL)																	
NR3DH			NR3			NR3D2			NR3D2B			NR3D4			NR3A		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.5	0.5	1.0	1.0	1.0	1.9	2.1	2.2	1.0	1.0	1.0	0.9	1.0	1.0	1.5	1.7	1.7
Gate Count																	
NR3DH			NR3			NR3D2			NR3D2B			NR3D4			NR3A		
1.33			1.33			2.33			2.33			2.67			2.00		

NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A

3-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.532	$0.190 + 0.171 \cdot \text{SL}$	$0.175 + 0.175 \cdot \text{SL}$	$0.177 + 0.175 \cdot \text{SL}$
	t_F	0.167	$0.083 + 0.042 \cdot \text{SL}$	$0.063 + 0.047 \cdot \text{SL}$	$0.044 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.245	$0.097 + 0.074 \cdot \text{SL}$	$0.094 + 0.075 \cdot \text{SL}$	$0.092 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.113	$0.058 + 0.027 \cdot \text{SL}$	$0.065 + 0.025 \cdot \text{SL}$	$0.064 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.535	$0.192 + 0.171 \cdot \text{SL}$	$0.181 + 0.174 \cdot \text{SL}$	$0.177 + 0.175 \cdot \text{SL}$
	t_F	0.185	$0.100 + 0.043 \cdot \text{SL}$	$0.083 + 0.047 \cdot \text{SL}$	$0.062 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.265	$0.115 + 0.075 \cdot \text{SL}$	$0.115 + 0.075 \cdot \text{SL}$	$0.116 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.125	$0.072 + 0.027 \cdot \text{SL}$	$0.076 + 0.026 \cdot \text{SL}$	$0.076 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.532	$0.188 + 0.172 \cdot \text{SL}$	$0.179 + 0.174 \cdot \text{SL}$	$0.177 + 0.175 \cdot \text{SL}$
	t_F	0.206	$0.120 + 0.043 \cdot \text{SL}$	$0.104 + 0.047 \cdot \text{SL}$	$0.083 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.273	$0.122 + 0.076 \cdot \text{SL}$	$0.123 + 0.075 \cdot \text{SL}$	$0.125 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.131	$0.077 + 0.027 \cdot \text{SL}$	$0.081 + 0.026 \cdot \text{SL}$	$0.084 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.327	$0.171 + 0.078 \cdot \text{SL}$	$0.159 + 0.081 \cdot \text{SL}$	$0.147 + 0.082 \cdot \text{SL}$
	t_F	0.118	$0.077 + 0.020 \cdot \text{SL}$	$0.071 + 0.022 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.156	$0.088 + 0.034 \cdot \text{SL}$	$0.084 + 0.035 \cdot \text{SL}$	$0.082 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.080	$0.047 + 0.016 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.329	$0.171 + 0.079 \cdot \text{SL}$	$0.163 + 0.081 \cdot \text{SL}$	$0.152 + 0.082 \cdot \text{SL}$
	t_F	0.138	$0.098 + 0.020 \cdot \text{SL}$	$0.090 + 0.022 \cdot \text{SL}$	$0.075 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.172	$0.101 + 0.035 \cdot \text{SL}$	$0.101 + 0.035 \cdot \text{SL}$	$0.102 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.094	$0.064 + 0.015 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.325	$0.166 + 0.080 \cdot \text{SL}$	$0.159 + 0.081 \cdot \text{SL}$	$0.151 + 0.082 \cdot \text{SL}$
	t_F	0.159	$0.119 + 0.020 \cdot \text{SL}$	$0.110 + 0.022 \cdot \text{SL}$	$0.096 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.179	$0.107 + 0.036 \cdot \text{SL}$	$0.108 + 0.035 \cdot \text{SL}$	$0.109 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.100	$0.070 + 0.015 \cdot \text{SL}$	$0.077 + 0.013 \cdot \text{SL}$	$0.079 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A

3-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t _R	0.231	$0.155 + 0.038 \cdot \text{SL}$	$0.147 + 0.040 \cdot \text{SL}$	$0.130 + 0.041 \cdot \text{SL}$
	t _F	0.092	$0.070 + 0.011 \cdot \text{SL}$	$0.072 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.113	$0.077 + 0.018 \cdot \text{SL}$	$0.078 + 0.017 \cdot \text{SL}$	$0.074 + 0.018 \cdot \text{SL}$
	t _{PHL}	0.058	$0.038 + 0.010 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
B to Y	t _R	0.233	$0.157 + 0.038 \cdot \text{SL}$	$0.148 + 0.040 \cdot \text{SL}$	$0.136 + 0.041 \cdot \text{SL}$
	t _F	0.114	$0.094 + 0.010 \cdot \text{SL}$	$0.093 + 0.010 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.127	$0.090 + 0.019 \cdot \text{SL}$	$0.094 + 0.018 \cdot \text{SL}$	$0.094 + 0.018 \cdot \text{SL}$
	t _{PHL}	0.074	$0.056 + 0.009 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
C to Y	t _R	0.228	$0.151 + 0.039 \cdot \text{SL}$	$0.144 + 0.041 \cdot \text{SL}$	$0.134 + 0.041 \cdot \text{SL}$
	t _F	0.134	$0.114 + 0.010 \cdot \text{SL}$	$0.112 + 0.011 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.135	$0.098 + 0.019 \cdot \text{SL}$	$0.101 + 0.018 \cdot \text{SL}$	$0.102 + 0.018 \cdot \text{SL}$
	t _{PHL}	0.080	$0.062 + 0.009 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : 16 < SL

NR3D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t _R	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$	$0.033 + 0.014 \cdot \text{SL}$
	t _F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.216	$0.201 + 0.008 \cdot \text{SL}$	$0.205 + 0.006 \cdot \text{SL}$	$0.208 + 0.006 \cdot \text{SL}$
	t _{PHL}	0.201	$0.183 + 0.009 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.201 + 0.006 \cdot \text{SL}$
B to Y	t _R	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$	$0.032 + 0.014 \cdot \text{SL}$
	t _F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.232	$0.217 + 0.008 \cdot \text{SL}$	$0.221 + 0.006 \cdot \text{SL}$	$0.224 + 0.006 \cdot \text{SL}$
	t _{PHL}	0.221	$0.202 + 0.009 \cdot \text{SL}$	$0.210 + 0.007 \cdot \text{SL}$	$0.221 + 0.006 \cdot \text{SL}$
C to Y	t _R	0.070	$0.044 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$	$0.033 + 0.014 \cdot \text{SL}$
	t _F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t _{PLH}	0.239	$0.224 + 0.008 \cdot \text{SL}$	$0.228 + 0.006 \cdot \text{SL}$	$0.231 + 0.006 \cdot \text{SL}$
	t _{PHL}	0.232	$0.213 + 0.009 \cdot \text{SL}$	$0.221 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : 16 < SL

NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A

3-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.071	$0.058 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$
	t_F	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.246	$0.237 + 0.005 \cdot \text{SL}$	$0.241 + 0.003 \cdot \text{SL}$	$0.250 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.241	$0.229 + 0.006 \cdot \text{SL}$	$0.236 + 0.004 \cdot \text{SL}$	$0.259 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.071	$0.058 + 0.007 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$
	t_F	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.262	$0.253 + 0.005 \cdot \text{SL}$	$0.257 + 0.003 \cdot \text{SL}$	$0.266 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.260	$0.248 + 0.006 \cdot \text{SL}$	$0.255 + 0.004 \cdot \text{SL}$	$0.277 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.070	$0.057 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$
	t_F	0.086	$0.074 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.269	$0.260 + 0.005 \cdot \text{SL}$	$0.265 + 0.003 \cdot \text{SL}$	$0.273 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.275	$0.263 + 0.006 \cdot \text{SL}$	$0.270 + 0.004 \cdot \text{SL}$	$0.292 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR3A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.221	$0.147 + 0.037 \cdot \text{SL}$	$0.138 + 0.039 \cdot \text{SL}$	$0.124 + 0.041 \cdot \text{SL}$
	t_F	0.114	$0.073 + 0.020 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.096	$0.058 + 0.019 \cdot \text{SL}$	$0.063 + 0.017 \cdot \text{SL}$	$0.061 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.092	$0.062 + 0.015 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.219	$0.144 + 0.038 \cdot \text{SL}$	$0.135 + 0.040 \cdot \text{SL}$	$0.126 + 0.041 \cdot \text{SL}$
	t_F	0.149	$0.108 + 0.021 \cdot \text{SL}$	$0.102 + 0.022 \cdot \text{SL}$	$0.091 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.115	$0.075 + 0.020 \cdot \text{SL}$	$0.082 + 0.018 \cdot \text{SL}$	$0.082 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.118	$0.092 + 0.013 \cdot \text{SL}$	$0.094 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.213	$0.136 + 0.039 \cdot \text{SL}$	$0.130 + 0.040 \cdot \text{SL}$	$0.122 + 0.041 \cdot \text{SL}$
	t_F	0.190	$0.147 + 0.022 \cdot \text{SL}$	$0.143 + 0.023 \cdot \text{SL}$	$0.132 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.124	$0.086 + 0.019 \cdot \text{SL}$	$0.090 + 0.018 \cdot \text{SL}$	$0.091 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.134	$0.106 + 0.014 \cdot \text{SL}$	$0.108 + 0.013 \cdot \text{SL}$	$0.112 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR4DH/NR4/NR4D2/NR4D4

4-Input NOR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	0	1
Other States				0

Cell Data

Input Load (SL)															
NR4DH				NR4				NR4D2				NR4D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0
Gate Count															
NR4DH				NR4				NR4D2				NR4D4			
2.67				2.67				3.00				3.67			

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.174	$0.056 + 0.059 \cdot \text{SL}$	$0.051 + 0.060 \cdot \text{SL}$	$0.043 + 0.061 \cdot \text{SL}$
	t_F	0.147	$0.053 + 0.047 \cdot \text{SL}$	$0.048 + 0.048 \cdot \text{SL}$	$0.039 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.259	$0.203 + 0.028 \cdot \text{SL}$	$0.209 + 0.027 \cdot \text{SL}$	$0.210 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.252	$0.196 + 0.028 \cdot \text{SL}$	$0.205 + 0.026 \cdot \text{SL}$	$0.206 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.175	$0.058 + 0.059 \cdot \text{SL}$	$0.051 + 0.060 \cdot \text{SL}$	$0.043 + 0.061 \cdot \text{SL}$
	t_F	0.147	$0.053 + 0.047 \cdot \text{SL}$	$0.048 + 0.048 \cdot \text{SL}$	$0.039 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.259	$0.203 + 0.028 \cdot \text{SL}$	$0.209 + 0.026 \cdot \text{SL}$	$0.210 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.272	$0.216 + 0.028 \cdot \text{SL}$	$0.225 + 0.026 \cdot \text{SL}$	$0.226 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.175	$0.058 + 0.059 \cdot \text{SL}$	$0.051 + 0.060 \cdot \text{SL}$	$0.043 + 0.061 \cdot \text{SL}$
	t_F	0.152	$0.060 + 0.046 \cdot \text{SL}$	$0.053 + 0.048 \cdot \text{SL}$	$0.041 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.256	$0.200 + 0.028 \cdot \text{SL}$	$0.206 + 0.027 \cdot \text{SL}$	$0.207 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.265	$0.209 + 0.028 \cdot \text{SL}$	$0.219 + 0.026 \cdot \text{SL}$	$0.221 + 0.026 \cdot \text{SL}$
D to Y	t_R	0.175	$0.058 + 0.059 \cdot \text{SL}$	$0.052 + 0.060 \cdot \text{SL}$	$0.043 + 0.061 \cdot \text{SL}$
	t_F	0.152	$0.060 + 0.046 \cdot \text{SL}$	$0.053 + 0.048 \cdot \text{SL}$	$0.041 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.258	$0.202 + 0.028 \cdot \text{SL}$	$0.208 + 0.027 \cdot \text{SL}$	$0.209 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.287	$0.230 + 0.028 \cdot \text{SL}$	$0.240 + 0.026 \cdot \text{SL}$	$0.243 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR4DH/NR4/NR4D2/NR4D4

4-Input NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.105	$0.051 + 0.027 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.201	$0.173 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$	$0.181 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.195	$0.166 + 0.014 \cdot \text{SL}$	$0.173 + 0.013 \cdot \text{SL}$	$0.176 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.106	$0.052 + 0.027 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.202	$0.174 + 0.014 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.182 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.217	$0.188 + 0.014 \cdot \text{SL}$	$0.194 + 0.013 \cdot \text{SL}$	$0.197 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.106	$0.052 + 0.027 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.051 + 0.022 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.201	$0.173 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$	$0.181 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.178 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.189 + 0.012 \cdot \text{SL}$
D to Y	t_R	0.105	$0.051 + 0.027 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.050 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.202	$0.174 + 0.014 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.182 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.229	$0.200 + 0.015 \cdot \text{SL}$	$0.207 + 0.013 \cdot \text{SL}$	$0.211 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.050 + 0.014 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.048 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.208	$0.192 + 0.008 \cdot \text{SL}$	$0.198 + 0.007 \cdot \text{SL}$	$0.206 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.200	$0.182 + 0.009 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.201 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.079	$0.051 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.209	$0.192 + 0.008 \cdot \text{SL}$	$0.198 + 0.007 \cdot \text{SL}$	$0.207 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.221	$0.203 + 0.009 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.222 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.077	$0.050 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.205	$0.188 + 0.008 \cdot \text{SL}$	$0.194 + 0.007 \cdot \text{SL}$	$0.203 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.211	$0.192 + 0.009 \cdot \text{SL}$	$0.200 + 0.007 \cdot \text{SL}$	$0.213 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.079	$0.051 + 0.014 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.205	$0.189 + 0.008 \cdot \text{SL}$	$0.195 + 0.007 \cdot \text{SL}$	$0.204 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.213 + 0.009 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$	$0.234 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NR4DH/NR4/NR4D2/NR4D4

4-Input NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR4D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.069 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.241	$0.230 + 0.005 \cdot \text{SL}$	$0.236 + 0.004 \cdot \text{SL}$	$0.252 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.235	$0.223 + 0.006 \cdot \text{SL}$	$0.230 + 0.004 \cdot \text{SL}$	$0.251 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.082	$0.069 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.067 + 0.007 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.241	$0.231 + 0.005 \cdot \text{SL}$	$0.236 + 0.004 \cdot \text{SL}$	$0.253 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.256	$0.244 + 0.006 \cdot \text{SL}$	$0.251 + 0.004 \cdot \text{SL}$	$0.272 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.082	$0.068 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.087	$0.074 + 0.007 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.236	$0.225 + 0.005 \cdot \text{SL}$	$0.231 + 0.004 \cdot \text{SL}$	$0.247 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.244	$0.232 + 0.006 \cdot \text{SL}$	$0.239 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.081	$0.068 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.236	$0.226 + 0.005 \cdot \text{SL}$	$0.231 + 0.004 \cdot \text{SL}$	$0.248 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.268	$0.256 + 0.006 \cdot \text{SL}$	$0.263 + 0.004 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR5/NR5D2/NR5D4

5-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	0	0	1
Other States					0

Cell Data

Input Load (SL)															Gate Count		
NR5					NR5D2					NR5D4					NR5	NR5D2	NR5D4
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.9	0.9	0.9	0.9	1.0	0.9	0.9	0.9	0.9	1.0	0.9	0.9	0.9	0.9	1.0	3.00	4.00	3.33

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.042 + 0.024 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.231	$0.203 + 0.014 \cdot \text{SL}$	$0.208 + 0.013 \cdot \text{SL}$	$0.211 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.214	$0.185 + 0.015 \cdot \text{SL}$	$0.191 + 0.013 \cdot \text{SL}$	$0.194 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.043 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.249	$0.221 + 0.014 \cdot \text{SL}$	$0.227 + 0.013 \cdot \text{SL}$	$0.230 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.239	$0.210 + 0.015 \cdot \text{SL}$	$0.216 + 0.013 \cdot \text{SL}$	$0.219 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.043 + 0.024 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.257	$0.229 + 0.014 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$	$0.237 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.253	$0.224 + 0.015 \cdot \text{SL}$	$0.230 + 0.013 \cdot \text{SL}$	$0.234 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.104	$0.051 + 0.027 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.040 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.200	$0.172 + 0.014 \cdot \text{SL}$	$0.177 + 0.013 \cdot \text{SL}$	$0.180 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.178 + 0.015 \cdot \text{SL}$	$0.185 + 0.013 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.103	$0.049 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.049 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.201	$0.173 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$	$0.181 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.230	$0.200 + 0.015 \cdot \text{SL}$	$0.207 + 0.013 \cdot \text{SL}$	$0.211 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR5/NR5D2/NR5D4

5-Input NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.240	$0.223 + 0.008 \cdot \text{SL}$	$0.229 + 0.007 \cdot \text{SL}$	$0.238 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.220	$0.202 + 0.009 \cdot \text{SL}$	$0.209 + 0.007 \cdot \text{SL}$	$0.220 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.258	$0.242 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$	$0.256 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.245	$0.227 + 0.009 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$	$0.245 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.082	$0.055 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.266	$0.249 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.264 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.260	$0.242 + 0.009 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.078	$0.051 + 0.014 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.204	$0.187 + 0.008 \cdot \text{SL}$	$0.193 + 0.007 \cdot \text{SL}$	$0.202 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.213	$0.194 + 0.009 \cdot \text{SL}$	$0.202 + 0.007 \cdot \text{SL}$	$0.214 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.079	$0.052 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.205	$0.188 + 0.008 \cdot \text{SL}$	$0.194 + 0.007 \cdot \text{SL}$	$0.203 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.234	$0.215 + 0.009 \cdot \text{SL}$	$0.224 + 0.007 \cdot \text{SL}$	$0.236 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**NR5D4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.088	$0.074 + 0.007 \cdot \text{SL}$	$0.074 + 0.007 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.082	$0.069 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.279	$0.268 + 0.005 \cdot \text{SL}$	$0.274 + 0.004 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.246 + 0.006 \cdot \text{SL}$	$0.252 + 0.004 \cdot \text{SL}$	$0.273 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.074 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.297	$0.287 + 0.005 \cdot \text{SL}$	$0.293 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.271 + 0.006 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.298 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.074 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.071 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.305	$0.294 + 0.005 \cdot \text{SL}$	$0.300 + 0.004 \cdot \text{SL}$	$0.317 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.298	$0.287 + 0.006 \cdot \text{SL}$	$0.293 + 0.004 \cdot \text{SL}$	$0.314 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.083	$0.069 + 0.007 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.237	$0.227 + 0.005 \cdot \text{SL}$	$0.233 + 0.004 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.247	$0.235 + 0.006 \cdot \text{SL}$	$0.242 + 0.004 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.083	$0.069 + 0.007 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.238	$0.228 + 0.005 \cdot \text{SL}$	$0.233 + 0.004 \cdot \text{SL}$	$0.250 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.268	$0.256 + 0.006 \cdot \text{SL}$	$0.263 + 0.004 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR6/NR6D2/NR6D4

6-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	0	0	0	1
Other States						0

Cell Data

Input Load (SL)																	
NR6						NR6D2						NR6D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Gate Count																	
NR6						NR6D2						NR6D4					
3.33						3.67						4.33					

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	$0.054 + 0.026 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.234	$0.206 + 0.014 \cdot \text{SL}$	$0.212 + 0.013 \cdot \text{SL}$	$0.214 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.216	$0.187 + 0.015 \cdot \text{SL}$	$0.193 + 0.013 \cdot \text{SL}$	$0.197 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.107	$0.054 + 0.026 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.253	$0.224 + 0.014 \cdot \text{SL}$	$0.230 + 0.013 \cdot \text{SL}$	$0.233 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.241	$0.211 + 0.015 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$	$0.222 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.107	$0.054 + 0.027 \cdot \text{SL}$	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.044 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.260	$0.232 + 0.014 \cdot \text{SL}$	$0.238 + 0.013 \cdot \text{SL}$	$0.241 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.255	$0.225 + 0.015 \cdot \text{SL}$	$0.233 + 0.013 \cdot \text{SL}$	$0.236 + 0.012 \cdot \text{SL}$
D to Y	t_R	0.106	$0.053 + 0.027 \cdot \text{SL}$	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.052 + 0.022 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.232	$0.204 + 0.014 \cdot \text{SL}$	$0.210 + 0.013 \cdot \text{SL}$	$0.213 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.229	$0.199 + 0.015 \cdot \text{SL}$	$0.207 + 0.013 \cdot \text{SL}$	$0.211 + 0.012 \cdot \text{SL}$
E to Y	t_R	0.107	$0.054 + 0.027 \cdot \text{SL}$	$0.051 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.052 + 0.022 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.250	$0.221 + 0.014 \cdot \text{SL}$	$0.228 + 0.013 \cdot \text{SL}$	$0.231 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.254	$0.224 + 0.015 \cdot \text{SL}$	$0.232 + 0.013 \cdot \text{SL}$	$0.236 + 0.012 \cdot \text{SL}$
F to Y	t_R	0.107	$0.054 + 0.027 \cdot \text{SL}$	$0.051 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.053 + 0.022 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.259	$0.231 + 0.014 \cdot \text{SL}$	$0.237 + 0.013 \cdot \text{SL}$	$0.240 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.270	$0.240 + 0.015 \cdot \text{SL}$	$0.248 + 0.013 \cdot \text{SL}$	$0.252 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR6/NR6D2/NR6D4

6-Input NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.055 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.243	$0.226 + 0.008 \cdot \text{SL}$	$0.232 + 0.007 \cdot \text{SL}$	$0.241 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.221	$0.203 + 0.009 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.222 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.082	$0.055 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.261	$0.244 + 0.008 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.259 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.246	$0.228 + 0.009 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.247 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.083	$0.056 + 0.014 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.269	$0.252 + 0.008 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.267 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.261	$0.243 + 0.009 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.081	$0.053 + 0.014 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.237	$0.220 + 0.008 \cdot \text{SL}$	$0.227 + 0.007 \cdot \text{SL}$	$0.236 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.233	$0.214 + 0.009 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$	$0.235 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.082	$0.054 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.255	$0.238 + 0.008 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$	$0.254 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.258	$0.240 + 0.009 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.082	$0.054 + 0.014 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.265	$0.248 + 0.008 \cdot \text{SL}$	$0.254 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.275	$0.256 + 0.009 \cdot \text{SL}$	$0.264 + 0.007 \cdot \text{SL}$	$0.277 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR6D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.088	$0.075 + 0.007 \cdot \text{SL}$	$0.075 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.082	$0.069 + 0.007 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.280	$0.269 + 0.005 \cdot \text{SL}$	$0.275 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.258	$0.246 + 0.006 \cdot \text{SL}$	$0.253 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.075 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.298	$0.288 + 0.005 \cdot \text{SL}$	$0.293 + 0.004 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.283	$0.272 + 0.006 \cdot \text{SL}$	$0.278 + 0.004 \cdot \text{SL}$	$0.299 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.088	$0.075 + 0.006 \cdot \text{SL}$	$0.075 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.306	$0.295 + 0.005 \cdot \text{SL}$	$0.301 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.299	$0.288 + 0.006 \cdot \text{SL}$	$0.294 + 0.004 \cdot \text{SL}$	$0.315 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.073 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.075 + 0.007 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.269	$0.259 + 0.005 \cdot \text{SL}$	$0.265 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.267	$0.255 + 0.006 \cdot \text{SL}$	$0.262 + 0.004 \cdot \text{SL}$	$0.285 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.086	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.088	$0.075 + 0.007 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.283 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.293	$0.281 + 0.006 \cdot \text{SL}$	$0.287 + 0.004 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.073 + 0.007 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.089	$0.076 + 0.007 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.297	$0.286 + 0.005 \cdot \text{SL}$	$0.292 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.310	$0.298 + 0.006 \cdot \text{SL}$	$0.305 + 0.004 \cdot \text{SL}$	$0.328 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NR8/NR8D2/NR8D4

8-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	0	0	0	0	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
NR8								NR8
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	1.0	1.0	4.33
NR8D2								NR8D2
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	1.0	4.67
NR8D4								NR8D4
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	1.0	5.33

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.052 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.258	$0.227 + 0.015 \cdot \text{SL}$	$0.236 + 0.013 \cdot \text{SL}$	$0.243 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.235	$0.205 + 0.015 \cdot \text{SL}$	$0.212 + 0.013 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.052 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.276	$0.246 + 0.015 \cdot \text{SL}$	$0.254 + 0.013 \cdot \text{SL}$	$0.261 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.260	$0.229 + 0.015 \cdot \text{SL}$	$0.237 + 0.013 \cdot \text{SL}$	$0.243 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.118	$0.063 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.285	$0.254 + 0.015 \cdot \text{SL}$	$0.262 + 0.013 \cdot \text{SL}$	$0.269 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.275	$0.244 + 0.015 \cdot \text{SL}$	$0.253 + 0.013 \cdot \text{SL}$	$0.259 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.119	$0.066 + 0.027 \cdot \text{SL}$	$0.065 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.058 + 0.023 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.051 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.260	$0.229 + 0.015 \cdot \text{SL}$	$0.238 + 0.013 \cdot \text{SL}$	$0.245 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.250	$0.218 + 0.016 \cdot \text{SL}$	$0.228 + 0.013 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.119	$0.065 + 0.027 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.058 + 0.023 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.051 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.278	$0.247 + 0.015 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$	$0.263 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.271	$0.240 + 0.016 \cdot \text{SL}$	$0.249 + 0.013 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
F to Y	t_R	0.119	$0.066 + 0.027 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_F	0.106	$0.060 + 0.023 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.287	$0.256 + 0.015 \cdot \text{SL}$	$0.265 + 0.013 \cdot \text{SL}$	$0.272 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.286	$0.254 + 0.016 \cdot \text{SL}$	$0.264 + 0.013 \cdot \text{SL}$	$0.271 + 0.013 \cdot \text{SL}$
G to Y	t_R	0.117	$0.063 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.109	$0.064 + 0.023 \cdot \text{SL}$	$0.065 + 0.023 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.240	$0.209 + 0.015 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$	$0.225 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.245	$0.213 + 0.016 \cdot \text{SL}$	$0.223 + 0.013 \cdot \text{SL}$	$0.231 + 0.013 \cdot \text{SL}$
H to Y	t_R	0.117	$0.063 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.110	$0.065 + 0.023 \cdot \text{SL}$	$0.065 + 0.023 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.241	$0.210 + 0.015 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$	$0.225 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.266	$0.233 + 0.016 \cdot \text{SL}$	$0.244 + 0.013 \cdot \text{SL}$	$0.252 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NR8/NR8D2/NR8D4

8-Input NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.094	$0.066 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.268	$0.249 + 0.009 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$	$0.271 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.241	$0.222 + 0.010 \cdot \text{SL}$	$0.231 + 0.007 \cdot \text{SL}$	$0.246 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.094	$0.066 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.286	$0.267 + 0.009 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.266	$0.246 + 0.010 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.270 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.095	$0.068 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.294	$0.275 + 0.009 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.298 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.282	$0.263 + 0.010 \cdot \text{SL}$	$0.271 + 0.007 \cdot \text{SL}$	$0.287 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.095	$0.066 + 0.014 \cdot \text{SL}$	$0.069 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.267	$0.248 + 0.010 \cdot \text{SL}$	$0.256 + 0.007 \cdot \text{SL}$	$0.271 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.255	$0.234 + 0.010 \cdot \text{SL}$	$0.244 + 0.008 \cdot \text{SL}$	$0.261 + 0.007 \cdot \text{SL}$
E to Y	t_R	0.094	$0.066 + 0.014 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.064 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.285	$0.266 + 0.010 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.276	$0.255 + 0.010 \cdot \text{SL}$	$0.265 + 0.008 \cdot \text{SL}$	$0.282 + 0.007 \cdot \text{SL}$
F to Y	t_R	0.094	$0.065 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.064 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.064 + 0.012 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.294	$0.274 + 0.010 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.298 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.291	$0.271 + 0.010 \cdot \text{SL}$	$0.281 + 0.008 \cdot \text{SL}$	$0.297 + 0.007 \cdot \text{SL}$
G to Y	t_R	0.092	$0.064 + 0.014 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$
	t_F	0.093	$0.067 + 0.013 \cdot \text{SL}$	$0.073 + 0.011 \cdot \text{SL}$	$0.067 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.246	$0.226 + 0.010 \cdot \text{SL}$	$0.235 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.249	$0.227 + 0.011 \cdot \text{SL}$	$0.238 + 0.008 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$
H to Y	t_R	0.092	$0.063 + 0.014 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$
	t_F	0.093	$0.068 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$	$0.067 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.246	$0.227 + 0.010 \cdot \text{SL}$	$0.235 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.269	$0.248 + 0.011 \cdot \text{SL}$	$0.259 + 0.008 \cdot \text{SL}$	$0.277 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NR8D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	$0.094 + 0.007 \cdot \text{SL}$	$0.093 + 0.007 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.081 + 0.007 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.087 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.304 + 0.006 \cdot \text{SL}$	$0.311 + 0.004 \cdot \text{SL}$	$0.334 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.286	$0.274 + 0.006 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$	$0.306 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.107	$0.094 + 0.007 \cdot \text{SL}$	$0.093 + 0.007 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.082 + 0.007 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.087 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.335	$0.322 + 0.006 \cdot \text{SL}$	$0.330 + 0.004 \cdot \text{SL}$	$0.352 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.311	$0.298 + 0.006 \cdot \text{SL}$	$0.306 + 0.004 \cdot \text{SL}$	$0.331 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.106	$0.094 + 0.006 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$	$0.090 + 0.007 \cdot \text{SL}$
	t_F	0.096	$0.085 + 0.006 \cdot \text{SL}$	$0.084 + 0.006 \cdot \text{SL}$	$0.088 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.343	$0.331 + 0.006 \cdot \text{SL}$	$0.338 + 0.004 \cdot \text{SL}$	$0.361 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.328	$0.316 + 0.006 \cdot \text{SL}$	$0.323 + 0.004 \cdot \text{SL}$	$0.348 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.107	$0.094 + 0.006 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$	$0.091 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.089 + 0.007 \cdot \text{SL}$	$0.092 + 0.006 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.312	$0.300 + 0.006 \cdot \text{SL}$	$0.307 + 0.004 \cdot \text{SL}$	$0.331 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.293	$0.280 + 0.007 \cdot \text{SL}$	$0.288 + 0.004 \cdot \text{SL}$	$0.315 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.107	$0.094 + 0.007 \cdot \text{SL}$	$0.093 + 0.007 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$
	t_F	0.102	$0.088 + 0.007 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.330	$0.318 + 0.006 \cdot \text{SL}$	$0.325 + 0.004 \cdot \text{SL}$	$0.348 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.318	$0.305 + 0.007 \cdot \text{SL}$	$0.313 + 0.004 \cdot \text{SL}$	$0.340 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.106	$0.093 + 0.007 \cdot \text{SL}$	$0.093 + 0.007 \cdot \text{SL}$	$0.092 + 0.007 \cdot \text{SL}$
	t_F	0.103	$0.089 + 0.007 \cdot \text{SL}$	$0.093 + 0.006 \cdot \text{SL}$	$0.095 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.338	$0.326 + 0.006 \cdot \text{SL}$	$0.334 + 0.004 \cdot \text{SL}$	$0.357 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.334	$0.321 + 0.007 \cdot \text{SL}$	$0.329 + 0.004 \cdot \text{SL}$	$0.356 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.105	$0.091 + 0.007 \cdot \text{SL}$	$0.091 + 0.007 \cdot \text{SL}$	$0.089 + 0.007 \cdot \text{SL}$
	t_F	0.109	$0.096 + 0.007 \cdot \text{SL}$	$0.099 + 0.006 \cdot \text{SL}$	$0.101 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.290	$0.278 + 0.006 \cdot \text{SL}$	$0.286 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.292	$0.279 + 0.007 \cdot \text{SL}$	$0.287 + 0.004 \cdot \text{SL}$	$0.316 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.105	$0.091 + 0.007 \cdot \text{SL}$	$0.091 + 0.007 \cdot \text{SL}$	$0.089 + 0.007 \cdot \text{SL}$
	t_F	0.108	$0.093 + 0.008 \cdot \text{SL}$	$0.100 + 0.006 \cdot \text{SL}$	$0.102 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.291	$0.279 + 0.006 \cdot \text{SL}$	$0.286 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.313	$0.299 + 0.007 \cdot \text{SL}$	$0.308 + 0.004 \cdot \text{SL}$	$0.336 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OR2DH/OR2/OR2D2/OR2D4

2-Input OR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	1

Cell Data

Input Load (SL)								Gate Count			
OR2DH		OR2		OR2D2		OR2D4		OR2DH	OR2	OR2D2	OR2D4
A	B	A	B	A	B	A	B				
0.5	0.5	0.9	0.9	0.9	0.9	0.9	0.9	1.33	1.33	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.172	$0.055 + 0.059 \cdot \text{SL}$	$0.047 + 0.061 \cdot \text{SL}$	$0.040 + 0.061 \cdot \text{SL}$
	t_F	0.157	$0.062 + 0.047 \cdot \text{SL}$	$0.060 + 0.048 \cdot \text{SL}$	$0.049 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.176	$0.122 + 0.027 \cdot \text{SL}$	$0.124 + 0.026 \cdot \text{SL}$	$0.124 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.198	$0.139 + 0.029 \cdot \text{SL}$	$0.151 + 0.026 \cdot \text{SL}$	$0.156 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.175	$0.058 + 0.058 \cdot \text{SL}$	$0.050 + 0.060 \cdot \text{SL}$	$0.042 + 0.061 \cdot \text{SL}$
	t_F	0.158	$0.065 + 0.047 \cdot \text{SL}$	$0.061 + 0.048 \cdot \text{SL}$	$0.049 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.199	$0.145 + 0.027 \cdot \text{SL}$	$0.148 + 0.026 \cdot \text{SL}$	$0.148 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.200	$0.141 + 0.029 \cdot \text{SL}$	$0.154 + 0.026 \cdot \text{SL}$	$0.159 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.103	$0.050 + 0.026 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.102	$0.053 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.137	$0.110 + 0.014 \cdot \text{SL}$	$0.114 + 0.012 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.154	$0.121 + 0.016 \cdot \text{SL}$	$0.131 + 0.014 \cdot \text{SL}$	$0.139 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.041 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.053 + 0.024 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.160	$0.133 + 0.014 \cdot \text{SL}$	$0.137 + 0.013 \cdot \text{SL}$	$0.138 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.155	$0.123 + 0.016 \cdot \text{SL}$	$0.133 + 0.014 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR2DH/OR2/OR2D2/OR2D4**2-Input OR with 0.5X/1X/2X/4X Drive****Switching Characteristics**(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**OR2D2**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.059 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.146	$0.130 + 0.008 \cdot \text{SL}$	$0.135 + 0.007 \cdot \text{SL}$	$0.141 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.164	$0.145 + 0.010 \cdot \text{SL}$	$0.153 + 0.007 \cdot \text{SL}$	$0.169 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.167	$0.150 + 0.008 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$	$0.163 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.164	$0.145 + 0.010 \cdot \text{SL}$	$0.154 + 0.008 \cdot \text{SL}$	$0.170 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$ **OR2D4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.084	$0.071 + 0.006 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.100	$0.087 + 0.007 \cdot \text{SL}$	$0.090 + 0.006 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.183	$0.173 + 0.005 \cdot \text{SL}$	$0.178 + 0.004 \cdot \text{SL}$	$0.193 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.210	$0.197 + 0.006 \cdot \text{SL}$	$0.205 + 0.004 \cdot \text{SL}$	$0.230 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.092	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.101	$0.087 + 0.007 \cdot \text{SL}$	$0.091 + 0.006 \cdot \text{SL}$	$0.094 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.203	$0.193 + 0.005 \cdot \text{SL}$	$0.199 + 0.004 \cdot \text{SL}$	$0.215 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.211	$0.198 + 0.006 \cdot \text{SL}$	$0.206 + 0.004 \cdot \text{SL}$	$0.231 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OR3DH/OR3/OR3D2/OR3D4

3-Input OR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	0
1	x	x	1
x	1	x	1
x	x	1	1

Cell Data

Input Load (SL)											
OR3DH			OR3			OR3D2			OR3D4		
A	B	C	A	B	C	A	B	C	A	B	C
0.4	0.5	0.5	0.8	0.9	0.9	0.8	0.9	0.9	0.8	0.9	0.9
Gate Count											
OR3DH			OR3			OR3D2			OR3D4		
1.67			1.67			2.00			2.67		

OR3DH/OR3/OR3D2/OR3D4

3-Input OR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.175	$0.058 + 0.058 \cdot \text{SL}$	$0.051 + 0.060 \cdot \text{SL}$	$0.042 + 0.061 \cdot \text{SL}$
	t_F	0.181	$0.083 + 0.049 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$	$0.080 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.195	$0.140 + 0.028 \cdot \text{SL}$	$0.144 + 0.026 \cdot \text{SL}$	$0.145 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.244	$0.177 + 0.033 \cdot \text{SL}$	$0.198 + 0.028 \cdot \text{SL}$	$0.215 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.181	$0.066 + 0.057 \cdot \text{SL}$	$0.056 + 0.060 \cdot \text{SL}$	$0.045 + 0.061 \cdot \text{SL}$
	t_F	0.181	$0.083 + 0.049 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.080 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.221	$0.165 + 0.028 \cdot \text{SL}$	$0.170 + 0.027 \cdot \text{SL}$	$0.171 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.264	$0.198 + 0.033 \cdot \text{SL}$	$0.219 + 0.028 \cdot \text{SL}$	$0.236 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.186	$0.071 + 0.058 \cdot \text{SL}$	$0.063 + 0.060 \cdot \text{SL}$	$0.052 + 0.061 \cdot \text{SL}$
	t_F	0.181	$0.084 + 0.049 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.080 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.238	$0.180 + 0.029 \cdot \text{SL}$	$0.189 + 0.027 \cdot \text{SL}$	$0.191 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.275	$0.208 + 0.033 \cdot \text{SL}$	$0.229 + 0.028 \cdot \text{SL}$	$0.246 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.054 + 0.026 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.041 + 0.028 \cdot \text{SL}$
	t_F	0.118	$0.068 + 0.025 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$	$0.077 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.154	$0.126 + 0.014 \cdot \text{SL}$	$0.131 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.188	$0.152 + 0.018 \cdot \text{SL}$	$0.164 + 0.015 \cdot \text{SL}$	$0.180 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.112	$0.060 + 0.026 \cdot \text{SL}$	$0.055 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.121	$0.073 + 0.024 \cdot \text{SL}$	$0.077 + 0.023 \cdot \text{SL}$	$0.078 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.179	$0.151 + 0.014 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$	$0.159 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.206	$0.171 + 0.018 \cdot \text{SL}$	$0.183 + 0.015 \cdot \text{SL}$	$0.199 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.118	$0.066 + 0.026 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.121	$0.072 + 0.024 \cdot \text{SL}$	$0.078 + 0.023 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.195	$0.166 + 0.015 \cdot \text{SL}$	$0.173 + 0.013 \cdot \text{SL}$	$0.177 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.215	$0.180 + 0.018 \cdot \text{SL}$	$0.192 + 0.015 \cdot \text{SL}$	$0.207 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR3DH/OR3/OR3D2/OR3D4

3-Input OR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	$0.062 + 0.012 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.110	$0.084 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.164	$0.146 + 0.009 \cdot \text{SL}$	$0.154 + 0.007 \cdot \text{SL}$	$0.162 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.207	$0.185 + 0.011 \cdot \text{SL}$	$0.196 + 0.008 \cdot \text{SL}$	$0.220 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.091	$0.065 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.085 + 0.013 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$	$0.096 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.189	$0.171 + 0.009 \cdot \text{SL}$	$0.178 + 0.007 \cdot \text{SL}$	$0.188 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.227	$0.204 + 0.011 \cdot \text{SL}$	$0.215 + 0.008 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.099	$0.071 + 0.014 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.086 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.096 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.205	$0.187 + 0.009 \cdot \text{SL}$	$0.195 + 0.007 \cdot \text{SL}$	$0.206 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.236	$0.213 + 0.011 \cdot \text{SL}$	$0.224 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OR3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	$0.080 + 0.006 \cdot \text{SL}$	$0.079 + 0.007 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$
	t_F	0.141	$0.127 + 0.007 \cdot \text{SL}$	$0.131 + 0.006 \cdot \text{SL}$	$0.139 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.205	$0.195 + 0.005 \cdot \text{SL}$	$0.201 + 0.004 \cdot \text{SL}$	$0.218 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.274	$0.259 + 0.007 \cdot \text{SL}$	$0.268 + 0.005 \cdot \text{SL}$	$0.301 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.101	$0.089 + 0.006 \cdot \text{SL}$	$0.087 + 0.007 \cdot \text{SL}$	$0.079 + 0.007 \cdot \text{SL}$
	t_F	0.142	$0.127 + 0.007 \cdot \text{SL}$	$0.131 + 0.006 \cdot \text{SL}$	$0.139 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.229	$0.218 + 0.006 \cdot \text{SL}$	$0.225 + 0.004 \cdot \text{SL}$	$0.244 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.295	$0.280 + 0.007 \cdot \text{SL}$	$0.289 + 0.005 \cdot \text{SL}$	$0.322 + 0.004 \cdot \text{SL}$
C to Y	t_R	0.110	$0.099 + 0.006 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.087 + 0.007 \cdot \text{SL}$
	t_F	0.140	$0.125 + 0.007 \cdot \text{SL}$	$0.129 + 0.006 \cdot \text{SL}$	$0.139 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.247	$0.235 + 0.006 \cdot \text{SL}$	$0.243 + 0.004 \cdot \text{SL}$	$0.263 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.304	$0.290 + 0.007 \cdot \text{SL}$	$0.299 + 0.005 \cdot \text{SL}$	$0.332 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OR4DH/OR4/OR4D2/OR4D4

4-Input OR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	0	0
1	x	x	x	1
x	1	x	x	1
x	x	1	x	1
x	x	x	1	1

Cell Data

Input Load (SL)															
OR4DH				OR4				OR4D2				OR4D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Gate Count															
OR4DH				OR4				OR4D2				OR4D4			
2.33				2.33				2.67				4.00			

OR4DH/OR4/OR4D2/OR4D4

4-Input OR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.205	$0.063 + 0.071 \cdot \text{SL}$	$0.056 + 0.073 \cdot \text{SL}$	$0.051 + 0.073 \cdot \text{SL}$
	t_F	0.212	$0.078 + 0.067 \cdot \text{SL}$	$0.074 + 0.068 \cdot \text{SL}$	$0.064 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.195	$0.131 + 0.032 \cdot \text{SL}$	$0.133 + 0.032 \cdot \text{SL}$	$0.133 + 0.032 \cdot \text{SL}$
	t_{PHL}	0.217	$0.145 + 0.036 \cdot \text{SL}$	$0.154 + 0.033 \cdot \text{SL}$	$0.157 + 0.033 \cdot \text{SL}$
B to Y	t_R	0.207	$0.066 + 0.071 \cdot \text{SL}$	$0.059 + 0.073 \cdot \text{SL}$	$0.053 + 0.073 \cdot \text{SL}$
	t_F	0.213	$0.080 + 0.067 \cdot \text{SL}$	$0.074 + 0.068 \cdot \text{SL}$	$0.064 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.218	$0.153 + 0.032 \cdot \text{SL}$	$0.156 + 0.032 \cdot \text{SL}$	$0.156 + 0.032 \cdot \text{SL}$
	t_{PHL}	0.218	$0.146 + 0.036 \cdot \text{SL}$	$0.156 + 0.033 \cdot \text{SL}$	$0.158 + 0.033 \cdot \text{SL}$
C to Y	t_R	0.222	$0.081 + 0.071 \cdot \text{SL}$	$0.074 + 0.073 \cdot \text{SL}$	$0.068 + 0.073 \cdot \text{SL}$
	t_F	0.207	$0.072 + 0.067 \cdot \text{SL}$	$0.067 + 0.069 \cdot \text{SL}$	$0.060 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.204	$0.140 + 0.032 \cdot \text{SL}$	$0.141 + 0.032 \cdot \text{SL}$	$0.142 + 0.032 \cdot \text{SL}$
	t_{PHL}	0.215	$0.144 + 0.035 \cdot \text{SL}$	$0.151 + 0.033 \cdot \text{SL}$	$0.154 + 0.033 \cdot \text{SL}$
D to Y	t_R	0.225	$0.085 + 0.070 \cdot \text{SL}$	$0.076 + 0.073 \cdot \text{SL}$	$0.069 + 0.073 \cdot \text{SL}$
	t_F	0.207	$0.072 + 0.067 \cdot \text{SL}$	$0.067 + 0.069 \cdot \text{SL}$	$0.060 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.227	$0.163 + 0.032 \cdot \text{SL}$	$0.165 + 0.032 \cdot \text{SL}$	$0.166 + 0.032 \cdot \text{SL}$
	t_{PHL}	0.217	$0.146 + 0.035 \cdot \text{SL}$	$0.153 + 0.033 \cdot \text{SL}$	$0.156 + 0.033 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.122	$0.058 + 0.032 \cdot \text{SL}$	$0.052 + 0.034 \cdot \text{SL}$	$0.047 + 0.034 \cdot \text{SL}$
	t_F	0.134	$0.069 + 0.032 \cdot \text{SL}$	$0.069 + 0.032 \cdot \text{SL}$	$0.063 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.150	$0.119 + 0.016 \cdot \text{SL}$	$0.122 + 0.015 \cdot \text{SL}$	$0.122 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.163	$0.126 + 0.019 \cdot \text{SL}$	$0.134 + 0.017 \cdot \text{SL}$	$0.139 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.125	$0.061 + 0.032 \cdot \text{SL}$	$0.057 + 0.033 \cdot \text{SL}$	$0.049 + 0.034 \cdot \text{SL}$
	t_F	0.134	$0.069 + 0.032 \cdot \text{SL}$	$0.069 + 0.032 \cdot \text{SL}$	$0.063 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.173	$0.141 + 0.016 \cdot \text{SL}$	$0.144 + 0.015 \cdot \text{SL}$	$0.146 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.165	$0.127 + 0.019 \cdot \text{SL}$	$0.135 + 0.017 \cdot \text{SL}$	$0.140 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.139	$0.075 + 0.032 \cdot \text{SL}$	$0.069 + 0.034 \cdot \text{SL}$	$0.064 + 0.034 \cdot \text{SL}$
	t_F	0.129	$0.066 + 0.032 \cdot \text{SL}$	$0.061 + 0.033 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.159	$0.128 + 0.015 \cdot \text{SL}$	$0.130 + 0.015 \cdot \text{SL}$	$0.130 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.164	$0.128 + 0.018 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$	$0.137 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.143	$0.079 + 0.032 \cdot \text{SL}$	$0.073 + 0.033 \cdot \text{SL}$	$0.067 + 0.034 \cdot \text{SL}$
	t_F	0.130	$0.067 + 0.032 \cdot \text{SL}$	$0.063 + 0.033 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.182	$0.151 + 0.016 \cdot \text{SL}$	$0.153 + 0.015 \cdot \text{SL}$	$0.154 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.165	$0.129 + 0.018 \cdot \text{SL}$	$0.135 + 0.016 \cdot \text{SL}$	$0.139 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR4DH/OR4/OR4D2/OR4D4

4-Input OR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.092	$0.061 + 0.016 \cdot \text{SL}$	$0.056 + 0.017 \cdot \text{SL}$	$0.049 + 0.017 \cdot \text{SL}$
	t_F	0.105	$0.071 + 0.017 \cdot \text{SL}$	$0.074 + 0.016 \cdot \text{SL}$	$0.071 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.159	$0.141 + 0.009 \cdot \text{SL}$	$0.146 + 0.008 \cdot \text{SL}$	$0.149 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.171	$0.149 + 0.011 \cdot \text{SL}$	$0.157 + 0.009 \cdot \text{SL}$	$0.169 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.097	$0.066 + 0.016 \cdot \text{SL}$	$0.063 + 0.017 \cdot \text{SL}$	$0.052 + 0.017 \cdot \text{SL}$
	t_F	0.106	$0.073 + 0.017 \cdot \text{SL}$	$0.075 + 0.016 \cdot \text{SL}$	$0.072 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.181	$0.162 + 0.009 \cdot \text{SL}$	$0.167 + 0.008 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.172	$0.150 + 0.011 \cdot \text{SL}$	$0.158 + 0.009 \cdot \text{SL}$	$0.171 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.112	$0.080 + 0.016 \cdot \text{SL}$	$0.077 + 0.017 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$
	t_F	0.102	$0.071 + 0.016 \cdot \text{SL}$	$0.069 + 0.016 \cdot \text{SL}$	$0.065 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.170	$0.152 + 0.009 \cdot \text{SL}$	$0.156 + 0.008 \cdot \text{SL}$	$0.158 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.172	$0.152 + 0.010 \cdot \text{SL}$	$0.157 + 0.009 \cdot \text{SL}$	$0.167 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.117	$0.086 + 0.015 \cdot \text{SL}$	$0.083 + 0.016 \cdot \text{SL}$	$0.070 + 0.017 \cdot \text{SL}$
	t_F	0.103	$0.071 + 0.016 \cdot \text{SL}$	$0.069 + 0.016 \cdot \text{SL}$	$0.065 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.191	$0.174 + 0.009 \cdot \text{SL}$	$0.178 + 0.008 \cdot \text{SL}$	$0.181 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.173	$0.152 + 0.010 \cdot \text{SL}$	$0.158 + 0.009 \cdot \text{SL}$	$0.168 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OR4D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.050 + 0.007 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.274	$0.265 + 0.005 \cdot \text{SL}$	$0.269 + 0.003 \cdot \text{SL}$	$0.280 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.281	$0.270 + 0.005 \cdot \text{SL}$	$0.276 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.050 + 0.007 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.298	$0.288 + 0.005 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$	$0.303 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.272 + 0.005 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.051 + 0.007 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.286	$0.277 + 0.005 \cdot \text{SL}$	$0.281 + 0.003 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.280	$0.269 + 0.005 \cdot \text{SL}$	$0.275 + 0.004 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.047 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.050 + 0.007 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.310	$0.301 + 0.005 \cdot \text{SL}$	$0.305 + 0.003 \cdot \text{SL}$	$0.316 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.272 + 0.005 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.292 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OR5/OR5D2/OR5D4

5-Input OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	0	0	0
1	x	x	x	x	1
x	1	x	x	x	1
x	x	1	x	x	1
x	x	x	1	x	1
x	x	x	x	1	1

Cell Data

Input Load (SL)															Gate Count		
OR5					OR5D2					OR5D4					OR5	OR5D2	OR5D4
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	2.67	3.00	4.33

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.125	$0.060 + 0.032 \cdot \text{SL}$	$0.055 + 0.034 \cdot \text{SL}$	$0.050 + 0.034 \cdot \text{SL}$
	t_F	0.150	$0.083 + 0.034 \cdot \text{SL}$	$0.088 + 0.032 \cdot \text{SL}$	$0.085 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.167	$0.135 + 0.016 \cdot \text{SL}$	$0.139 + 0.015 \cdot \text{SL}$	$0.140 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.197	$0.156 + 0.020 \cdot \text{SL}$	$0.167 + 0.018 \cdot \text{SL}$	$0.180 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.130	$0.066 + 0.032 \cdot \text{SL}$	$0.061 + 0.033 \cdot \text{SL}$	$0.053 + 0.034 \cdot \text{SL}$
	t_F	0.153	$0.087 + 0.033 \cdot \text{SL}$	$0.089 + 0.032 \cdot \text{SL}$	$0.087 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.193	$0.160 + 0.016 \cdot \text{SL}$	$0.165 + 0.015 \cdot \text{SL}$	$0.167 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.217	$0.175 + 0.021 \cdot \text{SL}$	$0.187 + 0.018 \cdot \text{SL}$	$0.199 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.137	$0.074 + 0.032 \cdot \text{SL}$	$0.067 + 0.033 \cdot \text{SL}$	$0.061 + 0.034 \cdot \text{SL}$
	t_F	0.153	$0.086 + 0.033 \cdot \text{SL}$	$0.090 + 0.032 \cdot \text{SL}$	$0.086 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.209	$0.175 + 0.017 \cdot \text{SL}$	$0.181 + 0.015 \cdot \text{SL}$	$0.185 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.226	$0.184 + 0.021 \cdot \text{SL}$	$0.196 + 0.018 \cdot \text{SL}$	$0.208 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.140	$0.075 + 0.032 \cdot \text{SL}$	$0.069 + 0.034 \cdot \text{SL}$	$0.064 + 0.034 \cdot \text{SL}$
	t_F	0.130	$0.066 + 0.032 \cdot \text{SL}$	$0.062 + 0.033 \cdot \text{SL}$	$0.060 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.159	$0.128 + 0.015 \cdot \text{SL}$	$0.130 + 0.015 \cdot \text{SL}$	$0.130 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.164	$0.128 + 0.018 \cdot \text{SL}$	$0.134 + 0.017 \cdot \text{SL}$	$0.138 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.143	$0.079 + 0.032 \cdot \text{SL}$	$0.074 + 0.033 \cdot \text{SL}$	$0.067 + 0.034 \cdot \text{SL}$
	t_F	0.130	$0.066 + 0.032 \cdot \text{SL}$	$0.062 + 0.033 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.182	$0.151 + 0.016 \cdot \text{SL}$	$0.153 + 0.015 \cdot \text{SL}$	$0.154 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.165	$0.129 + 0.018 \cdot \text{SL}$	$0.135 + 0.017 \cdot \text{SL}$	$0.140 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OR5/OR5D2/OR5D4

5-Input OR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OR5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	$0.064 + 0.016 \cdot \text{SL}$	$0.063 + 0.017 \cdot \text{SL}$	$0.054 + 0.017 \cdot \text{SL}$
	t_F	0.129	$0.096 + 0.017 \cdot \text{SL}$	$0.097 + 0.016 \cdot \text{SL}$	$0.100 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.178	$0.159 + 0.009 \cdot \text{SL}$	$0.165 + 0.008 \cdot \text{SL}$	$0.170 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.212	$0.187 + 0.012 \cdot \text{SL}$	$0.197 + 0.010 \cdot \text{SL}$	$0.218 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.104	$0.072 + 0.016 \cdot \text{SL}$	$0.070 + 0.016 \cdot \text{SL}$	$0.059 + 0.017 \cdot \text{SL}$
	t_F	0.132	$0.099 + 0.016 \cdot \text{SL}$	$0.099 + 0.016 \cdot \text{SL}$	$0.100 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.203	$0.184 + 0.010 \cdot \text{SL}$	$0.190 + 0.008 \cdot \text{SL}$	$0.196 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.231	$0.206 + 0.012 \cdot \text{SL}$	$0.217 + 0.010 \cdot \text{SL}$	$0.238 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.112	$0.083 + 0.015 \cdot \text{SL}$	$0.076 + 0.016 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$
	t_F	0.132	$0.100 + 0.016 \cdot \text{SL}$	$0.100 + 0.016 \cdot \text{SL}$	$0.101 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.220	$0.200 + 0.010 \cdot \text{SL}$	$0.207 + 0.008 \cdot \text{SL}$	$0.216 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.242	$0.217 + 0.012 \cdot \text{SL}$	$0.227 + 0.010 \cdot \text{SL}$	$0.248 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.111	$0.081 + 0.015 \cdot \text{SL}$	$0.076 + 0.017 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$
	t_F	0.102	$0.070 + 0.016 \cdot \text{SL}$	$0.069 + 0.016 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.169	$0.152 + 0.009 \cdot \text{SL}$	$0.156 + 0.008 \cdot \text{SL}$	$0.158 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.172	$0.152 + 0.010 \cdot \text{SL}$	$0.157 + 0.009 \cdot \text{SL}$	$0.168 + 0.008 \cdot \text{SL}$
E to Y	t_R	0.117	$0.087 + 0.015 \cdot \text{SL}$	$0.082 + 0.016 \cdot \text{SL}$	$0.070 + 0.017 \cdot \text{SL}$
	t_F	0.103	$0.071 + 0.016 \cdot \text{SL}$	$0.069 + 0.016 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.191	$0.174 + 0.009 \cdot \text{SL}$	$0.177 + 0.008 \cdot \text{SL}$	$0.181 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.173	$0.152 + 0.010 \cdot \text{SL}$	$0.158 + 0.009 \cdot \text{SL}$	$0.169 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**OR5D4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.053 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.291	$0.281 + 0.005 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$	$0.296 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.313	$0.303 + 0.005 \cdot \text{SL}$	$0.308 + 0.004 \cdot \text{SL}$	$0.323 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.069	$0.055 + 0.007 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.052 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.317	$0.308 + 0.005 \cdot \text{SL}$	$0.312 + 0.003 \cdot \text{SL}$	$0.322 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.332	$0.321 + 0.005 \cdot \text{SL}$	$0.326 + 0.004 \cdot \text{SL}$	$0.342 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.053 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.333	$0.324 + 0.005 \cdot \text{SL}$	$0.328 + 0.003 \cdot \text{SL}$	$0.338 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.340	$0.329 + 0.005 \cdot \text{SL}$	$0.334 + 0.004 \cdot \text{SL}$	$0.350 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.051 + 0.007 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.286	$0.277 + 0.005 \cdot \text{SL}$	$0.281 + 0.003 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.280	$0.270 + 0.005 \cdot \text{SL}$	$0.275 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.047 + 0.007 \cdot \text{SL}$
	t_F	0.064	$0.050 + 0.007 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.311	$0.301 + 0.005 \cdot \text{SL}$	$0.306 + 0.003 \cdot \text{SL}$	$0.316 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.272 + 0.005 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

XN2/XN2D2/XN2D4

2-Input Exclusive-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	1

Cell Data

Input Load (SL)						Gate Count		
XN2		XN2D2		XN2D4		XN2	XN2D2	XN2D4
A	B	A	B	A	B			
0.7	1.5	0.7	1.5	0.7	1.5	2.33	2.33	3.00

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XN2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	$0.070 + 0.027 \cdot \text{SL}$	$0.069 + 0.027 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.123	$0.075 + 0.024 \cdot \text{SL}$	$0.081 + 0.022 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.238	$0.208 + 0.015 \cdot \text{SL}$	$0.216 + 0.013 \cdot \text{SL}$	$0.222 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.250	$0.216 + 0.017 \cdot \text{SL}$	$0.228 + 0.014 \cdot \text{SL}$	$0.239 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.117	$0.062 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.113	$0.064 + 0.025 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.215	$0.184 + 0.015 \cdot \text{SL}$	$0.193 + 0.013 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.196	$0.161 + 0.018 \cdot \text{SL}$	$0.173 + 0.014 \cdot \text{SL}$	$0.187 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

XN2/XN2D2/XN2D4**2-Input Exclusive-NOR with 1X/2X/4X Drive****Switching Characteristics**(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**XN2D2**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	$0.080 + 0.014 \cdot \text{SL}$	$0.081 + 0.013 \cdot \text{SL}$	$0.077 + 0.014 \cdot \text{SL}$
	t_F	0.113	$0.087 + 0.013 \cdot \text{SL}$	$0.092 + 0.012 \cdot \text{SL}$	$0.096 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.251	$0.232 + 0.009 \cdot \text{SL}$	$0.240 + 0.007 \cdot \text{SL}$	$0.255 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.267	$0.245 + 0.011 \cdot \text{SL}$	$0.256 + 0.008 \cdot \text{SL}$	$0.277 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.102	$0.074 + 0.014 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$	$0.073 + 0.014 \cdot \text{SL}$
	t_F	0.106	$0.080 + 0.013 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$	$0.092 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.228	$0.209 + 0.009 \cdot \text{SL}$	$0.217 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.207	$0.184 + 0.012 \cdot \text{SL}$	$0.196 + 0.008 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$ **XN2D4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.126	$0.114 + 0.006 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$
	t_F	0.136	$0.121 + 0.007 \cdot \text{SL}$	$0.126 + 0.006 \cdot \text{SL}$	$0.138 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.300	$0.288 + 0.006 \cdot \text{SL}$	$0.295 + 0.004 \cdot \text{SL}$	$0.319 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.325	$0.311 + 0.007 \cdot \text{SL}$	$0.320 + 0.005 \cdot \text{SL}$	$0.351 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.125	$0.112 + 0.006 \cdot \text{SL}$	$0.110 + 0.007 \cdot \text{SL}$	$0.110 + 0.007 \cdot \text{SL}$
	t_F	0.134	$0.119 + 0.007 \cdot \text{SL}$	$0.125 + 0.006 \cdot \text{SL}$	$0.136 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.275	$0.263 + 0.006 \cdot \text{SL}$	$0.270 + 0.004 \cdot \text{SL}$	$0.294 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.251	$0.237 + 0.007 \cdot \text{SL}$	$0.246 + 0.005 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

XN3/XN3D2/XN3D4

3-Input Exclusive-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	1
0	0	1	0
0	1	0	0
0	1	1	1
1	0	0	0
1	0	1	1
1	1	0	1
1	1	1	0

Cell Data

Input Load (SL)									Gate Count		
XN3			XN3D2			XN3D4			XN3	XN3D2	XN3D4
A	B	C	A	B	C	A	B	C			
1.4	0.7	1.5	1.4	0.7	1.5	1.3	0.7	1.5	3.67	4.00	4.67

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XN3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.142	$0.083 + 0.029 \cdot \text{SL}$	$0.089 + 0.028 \cdot \text{SL}$	$0.090 + 0.028 \cdot \text{SL}$
	t_F	0.129	$0.075 + 0.027 \cdot \text{SL}$	$0.083 + 0.025 \cdot \text{SL}$	$0.093 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.211	$0.175 + 0.018 \cdot \text{SL}$	$0.187 + 0.015 \cdot \text{SL}$	$0.204 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.224	$0.189 + 0.017 \cdot \text{SL}$	$0.201 + 0.014 \cdot \text{SL}$	$0.212 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.162	$0.106 + 0.028 \cdot \text{SL}$	$0.109 + 0.027 \cdot \text{SL}$	$0.107 + 0.027 \cdot \text{SL}$
	t_F	0.177	$0.125 + 0.026 \cdot \text{SL}$	$0.133 + 0.024 \cdot \text{SL}$	$0.141 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.373	$0.342 + 0.016 \cdot \text{SL}$	$0.351 + 0.013 \cdot \text{SL}$	$0.358 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.375	$0.332 + 0.022 \cdot \text{SL}$	$0.350 + 0.017 \cdot \text{SL}$	$0.374 + 0.014 \cdot \text{SL}$
C to Y	t_R	0.160	$0.105 + 0.028 \cdot \text{SL}$	$0.107 + 0.027 \cdot \text{SL}$	$0.105 + 0.027 \cdot \text{SL}$
	t_F	0.165	$0.114 + 0.026 \cdot \text{SL}$	$0.122 + 0.023 \cdot \text{SL}$	$0.126 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.332	$0.295 + 0.018 \cdot \text{SL}$	$0.309 + 0.015 \cdot \text{SL}$	$0.325 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.353	$0.319 + 0.017 \cdot \text{SL}$	$0.330 + 0.014 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XN3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.131	$0.102 + 0.015 \cdot \text{SL}$	$0.103 + 0.014 \cdot \text{SL}$	$0.110 + 0.014 \cdot \text{SL}$
	t_F	0.122	$0.091 + 0.016 \cdot \text{SL}$	$0.101 + 0.013 \cdot \text{SL}$	$0.117 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.222	$0.197 + 0.012 \cdot \text{SL}$	$0.211 + 0.009 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.235	$0.213 + 0.011 \cdot \text{SL}$	$0.225 + 0.008 \cdot \text{SL}$	$0.246 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.148	$0.121 + 0.014 \cdot \text{SL}$	$0.120 + 0.014 \cdot \text{SL}$	$0.124 + 0.014 \cdot \text{SL}$
	t_F	0.168	$0.136 + 0.016 \cdot \text{SL}$	$0.150 + 0.013 \cdot \text{SL}$	$0.163 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.386	$0.366 + 0.010 \cdot \text{SL}$	$0.376 + 0.007 \cdot \text{SL}$	$0.391 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.390	$0.362 + 0.014 \cdot \text{SL}$	$0.378 + 0.010 \cdot \text{SL}$	$0.413 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.147	$0.120 + 0.014 \cdot \text{SL}$	$0.119 + 0.014 \cdot \text{SL}$	$0.122 + 0.014 \cdot \text{SL}$
	t_F	0.168	$0.137 + 0.015 \cdot \text{SL}$	$0.148 + 0.013 \cdot \text{SL}$	$0.160 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.346	$0.322 + 0.012 \cdot \text{SL}$	$0.336 + 0.008 \cdot \text{SL}$	$0.361 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.367	$0.345 + 0.011 \cdot \text{SL}$	$0.356 + 0.008 \cdot \text{SL}$	$0.378 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$
XN3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.175	$0.163 + 0.006 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.163 + 0.007 \cdot \text{SL}$
	t_F	0.168	$0.152 + 0.008 \cdot \text{SL}$	$0.158 + 0.007 \cdot \text{SL}$	$0.178 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.282	$0.265 + 0.008 \cdot \text{SL}$	$0.276 + 0.005 \cdot \text{SL}$	$0.316 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.293	$0.279 + 0.007 \cdot \text{SL}$	$0.288 + 0.005 \cdot \text{SL}$	$0.320 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.120	$0.107 + 0.007 \cdot \text{SL}$	$0.107 + 0.007 \cdot \text{SL}$	$0.103 + 0.007 \cdot \text{SL}$
	t_F	0.193	$0.177 + 0.008 \cdot \text{SL}$	$0.183 + 0.006 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.438	$0.425 + 0.006 \cdot \text{SL}$	$0.433 + 0.004 \cdot \text{SL}$	$0.458 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.464	$0.446 + 0.009 \cdot \text{SL}$	$0.457 + 0.006 \cdot \text{SL}$	$0.502 + 0.004 \cdot \text{SL}$
C to Y	t_R	0.183	$0.170 + 0.007 \cdot \text{SL}$	$0.169 + 0.007 \cdot \text{SL}$	$0.170 + 0.007 \cdot \text{SL}$
	t_F	0.128	$0.114 + 0.007 \cdot \text{SL}$	$0.118 + 0.006 \cdot \text{SL}$	$0.122 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.408	$0.392 + 0.008 \cdot \text{SL}$	$0.403 + 0.005 \cdot \text{SL}$	$0.438 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.427	$0.413 + 0.007 \cdot \text{SL}$	$0.422 + 0.005 \cdot \text{SL}$	$0.453 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

XO2/XO2D2/XO2D4

2-Input Exclusive-OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	0

Cell Data

Input Load (SL)						Gate Count		
XO2		XO2D2		XO2D4		XO2	XO2D2	XO2D4
A	B	A	B	A	B			
0.7	1.3	0.7	1.3	0.7	1.3	2.33	2.33	3.00

XO2/XO2D2/XO2D4

2-Input Exclusive-OR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XO2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.124	$0.071 + 0.026 \cdot \text{SL}$	$0.071 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.123	$0.076 + 0.024 \cdot \text{SL}$	$0.081 + 0.022 \cdot \text{SL}$	$0.077 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.239	$0.209 + 0.015 \cdot \text{SL}$	$0.217 + 0.013 \cdot \text{SL}$	$0.223 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.254	$0.220 + 0.017 \cdot \text{SL}$	$0.232 + 0.014 \cdot \text{SL}$	$0.243 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.120	$0.067 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.189	$0.158 + 0.016 \cdot \text{SL}$	$0.167 + 0.013 \cdot \text{SL}$	$0.175 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.221	$0.187 + 0.017 \cdot \text{SL}$	$0.199 + 0.014 \cdot \text{SL}$	$0.210 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

XO2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.079 + 0.013 \cdot \text{SL}$	$0.079 + 0.013 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.084 + 0.013 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$	$0.095 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.248	$0.229 + 0.009 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.252 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.265	$0.243 + 0.011 \cdot \text{SL}$	$0.254 + 0.008 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.103	$0.076 + 0.014 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$	$0.073 + 0.014 \cdot \text{SL}$
	t_F	0.103	$0.076 + 0.014 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$	$0.090 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.197	$0.177 + 0.010 \cdot \text{SL}$	$0.186 + 0.007 \cdot \text{SL}$	$0.204 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.211 + 0.011 \cdot \text{SL}$	$0.222 + 0.008 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

XO2D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	$0.115 + 0.006 \cdot \text{SL}$	$0.113 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$
	t_F	0.135	$0.120 + 0.007 \cdot \text{SL}$	$0.125 + 0.006 \cdot \text{SL}$	$0.137 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.299	$0.286 + 0.006 \cdot \text{SL}$	$0.294 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.327	$0.313 + 0.007 \cdot \text{SL}$	$0.322 + 0.005 \cdot \text{SL}$	$0.353 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.125	$0.111 + 0.007 \cdot \text{SL}$	$0.112 + 0.007 \cdot \text{SL}$	$0.111 + 0.007 \cdot \text{SL}$
	t_F	0.132	$0.117 + 0.007 \cdot \text{SL}$	$0.122 + 0.006 \cdot \text{SL}$	$0.135 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.239	$0.226 + 0.007 \cdot \text{SL}$	$0.234 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.295	$0.281 + 0.007 \cdot \text{SL}$	$0.290 + 0.005 \cdot \text{SL}$	$0.321 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

XO3/XO3D2/XO3D4

3-Input Exclusive-OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	0
0	0	1	1
0	1	0	1
0	1	1	0
1	0	0	1
1	0	1	0
1	1	0	0
1	1	1	1

Cell Data

Input Load (SL)									Gate Count		
XO3			XO3D2			XO3D4			XO3	XO3D2	XO3D4
A	B	C	A	B	C	A	B	C			
1.4	0.7	1.5	1.4	0.7	1.5	1.4	0.7	1.5	3.67	4.00	4.67

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XO3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.134	$0.075 + 0.030 \cdot \text{SL}$	$0.080 + 0.028 \cdot \text{SL}$	$0.084 + 0.028 \cdot \text{SL}$
	t_F	0.143	$0.087 + 0.028 \cdot \text{SL}$	$0.097 + 0.025 \cdot \text{SL}$	$0.112 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.217	$0.186 + 0.015 \cdot \text{SL}$	$0.195 + 0.013 \cdot \text{SL}$	$0.201 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.220	$0.177 + 0.022 \cdot \text{SL}$	$0.194 + 0.017 \cdot \text{SL}$	$0.219 + 0.014 \cdot \text{SL}$
B to Y	t_R	0.162	$0.106 + 0.028 \cdot \text{SL}$	$0.109 + 0.027 \cdot \text{SL}$	$0.108 + 0.027 \cdot \text{SL}$
	t_F	0.177	$0.125 + 0.026 \cdot \text{SL}$	$0.134 + 0.024 \cdot \text{SL}$	$0.142 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.374	$0.343 + 0.015 \cdot \text{SL}$	$0.352 + 0.013 \cdot \text{SL}$	$0.359 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.376	$0.333 + 0.022 \cdot \text{SL}$	$0.352 + 0.017 \cdot \text{SL}$	$0.375 + 0.014 \cdot \text{SL}$
C to Y	t_R	0.160	$0.105 + 0.028 \cdot \text{SL}$	$0.107 + 0.027 \cdot \text{SL}$	$0.106 + 0.027 \cdot \text{SL}$
	t_F	0.165	$0.114 + 0.026 \cdot \text{SL}$	$0.122 + 0.023 \cdot \text{SL}$	$0.126 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.331	$0.294 + 0.018 \cdot \text{SL}$	$0.308 + 0.015 \cdot \text{SL}$	$0.324 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.352	$0.318 + 0.017 \cdot \text{SL}$	$0.329 + 0.014 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

XO3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.124	$0.095 + 0.015 \cdot \text{SL}$	$0.096 + 0.014 \cdot \text{SL}$	$0.105 + 0.014 \cdot \text{SL}$
	t_F	0.139	$0.106 + 0.017 \cdot \text{SL}$	$0.119 + 0.013 \cdot \text{SL}$	$0.138 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.228	$0.209 + 0.010 \cdot \text{SL}$	$0.218 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.230	$0.201 + 0.014 \cdot \text{SL}$	$0.217 + 0.010 \cdot \text{SL}$	$0.255 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.148	$0.120 + 0.014 \cdot \text{SL}$	$0.120 + 0.014 \cdot \text{SL}$	$0.124 + 0.014 \cdot \text{SL}$
	t_F	0.169	$0.136 + 0.016 \cdot \text{SL}$	$0.150 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.387	$0.367 + 0.010 \cdot \text{SL}$	$0.376 + 0.007 \cdot \text{SL}$	$0.392 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.392	$0.364 + 0.014 \cdot \text{SL}$	$0.380 + 0.010 \cdot \text{SL}$	$0.415 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.147	$0.120 + 0.014 \cdot \text{SL}$	$0.119 + 0.014 \cdot \text{SL}$	$0.122 + 0.014 \cdot \text{SL}$
	t_F	0.168	$0.137 + 0.015 \cdot \text{SL}$	$0.148 + 0.013 \cdot \text{SL}$	$0.161 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.345	$0.321 + 0.012 \cdot \text{SL}$	$0.335 + 0.008 \cdot \text{SL}$	$0.360 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.366	$0.344 + 0.011 \cdot \text{SL}$	$0.355 + 0.008 \cdot \text{SL}$	$0.377 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

XO3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	$0.141 + 0.006 \cdot \text{SL}$	$0.139 + 0.007 \cdot \text{SL}$	$0.142 + 0.007 \cdot \text{SL}$
	t_F	0.196	$0.180 + 0.008 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$	$0.208 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.278	$0.265 + 0.006 \cdot \text{SL}$	$0.273 + 0.004 \cdot \text{SL}$	$0.298 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.300	$0.281 + 0.009 \cdot \text{SL}$	$0.293 + 0.006 \cdot \text{SL}$	$0.342 + 0.004 \cdot \text{SL}$
B to Y	t_R	0.120	$0.106 + 0.007 \cdot \text{SL}$	$0.108 + 0.007 \cdot \text{SL}$	$0.103 + 0.007 \cdot \text{SL}$
	t_F	0.194	$0.178 + 0.008 \cdot \text{SL}$	$0.184 + 0.006 \cdot \text{SL}$	$0.200 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.439	$0.426 + 0.006 \cdot \text{SL}$	$0.434 + 0.004 \cdot \text{SL}$	$0.459 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.465	$0.448 + 0.009 \cdot \text{SL}$	$0.458 + 0.006 \cdot \text{SL}$	$0.504 + 0.004 \cdot \text{SL}$
C to Y	t_R	0.183	$0.170 + 0.007 \cdot \text{SL}$	$0.169 + 0.007 \cdot \text{SL}$	$0.170 + 0.007 \cdot \text{SL}$
	t_F	0.127	$0.113 + 0.007 \cdot \text{SL}$	$0.118 + 0.006 \cdot \text{SL}$	$0.122 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.406	$0.391 + 0.008 \cdot \text{SL}$	$0.402 + 0.005 \cdot \text{SL}$	$0.437 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.426	$0.412 + 0.007 \cdot \text{SL}$	$0.421 + 0.005 \cdot \text{SL}$	$0.452 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO21DH/AO21/AO21D2/AO21D2B/AO21D4

2-AND into 2-NOR with 0.5X/1X/2X/2X(Bufferd)/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	0	1
x	0	0	1
Other States			0

Cell Data

Input Load (SL)														
AO21DH			AO21			AO21D2			AO21D2B			AO21D4		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.5	0.5	1.0	1.0	1.0	2.0	2.0	2.1	1.0	1.0	1.0	1.0	1.0	1.0
Gate Count														
AO21DH			AO21			AO21D2			AO21D2B			AO21D4		
1.33			1.33			2.33			2.33			2.67		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO21DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.359	$0.129 + 0.115 \cdot \text{SL}$	$0.112 + 0.119 \cdot \text{SL}$	$0.104 + 0.120 \cdot \text{SL}$
	t_F	0.249	$0.091 + 0.079 \cdot \text{SL}$	$0.074 + 0.084 \cdot \text{SL}$	$0.059 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.178	$0.076 + 0.051 \cdot \text{SL}$	$0.074 + 0.051 \cdot \text{SL}$	$0.073 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.152	$0.071 + 0.041 \cdot \text{SL}$	$0.071 + 0.040 \cdot \text{SL}$	$0.071 + 0.041 \cdot \text{SL}$
B to Y	t_R	0.383	$0.153 + 0.115 \cdot \text{SL}$	$0.134 + 0.120 \cdot \text{SL}$	$0.127 + 0.121 \cdot \text{SL}$
	t_F	0.244	$0.083 + 0.080 \cdot \text{SL}$	$0.069 + 0.084 \cdot \text{SL}$	$0.060 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.191	$0.089 + 0.051 \cdot \text{SL}$	$0.087 + 0.052 \cdot \text{SL}$	$0.086 + 0.052 \cdot \text{SL}$
	t_{PHL}	0.146	$0.064 + 0.041 \cdot \text{SL}$	$0.066 + 0.041 \cdot \text{SL}$	$0.065 + 0.041 \cdot \text{SL}$
C to Y	t_R	0.378	$0.143 + 0.118 \cdot \text{SL}$	$0.133 + 0.120 \cdot \text{SL}$	$0.128 + 0.121 \cdot \text{SL}$
	t_F	0.198	$0.111 + 0.044 \cdot \text{SL}$	$0.097 + 0.047 \cdot \text{SL}$	$0.077 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.212	$0.108 + 0.052 \cdot \text{SL}$	$0.109 + 0.052 \cdot \text{SL}$	$0.109 + 0.052 \cdot \text{SL}$
	t_{PHL}	0.138	$0.086 + 0.026 \cdot \text{SL}$	$0.088 + 0.026 \cdot \text{SL}$	$0.088 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO21DH/AO21/AO21D2/AO21D2B/AO21D4

2-AND into 2-NOR with 0.5X/1X/2X/2X(Bufferd)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.228	$0.125 + 0.051 \cdot \text{SL}$	$0.115 + 0.054 \cdot \text{SL}$	$0.097 + 0.056 \cdot \text{SL}$
	t_F	0.164	$0.093 + 0.036 \cdot \text{SL}$	$0.080 + 0.039 \cdot \text{SL}$	$0.065 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.117	$0.068 + 0.025 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$	$0.069 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.105	$0.063 + 0.021 \cdot \text{SL}$	$0.070 + 0.019 \cdot \text{SL}$	$0.068 + 0.020 \cdot \text{SL}$
B to Y	t_R	0.251	$0.148 + 0.052 \cdot \text{SL}$	$0.136 + 0.055 \cdot \text{SL}$	$0.119 + 0.056 \cdot \text{SL}$
	t_F	0.158	$0.085 + 0.036 \cdot \text{SL}$	$0.073 + 0.040 \cdot \text{SL}$	$0.063 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.132	$0.084 + 0.024 \cdot \text{SL}$	$0.084 + 0.024 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.099	$0.057 + 0.021 \cdot \text{SL}$	$0.063 + 0.020 \cdot \text{SL}$	$0.062 + 0.020 \cdot \text{SL}$
C to Y	t_R	0.242	$0.135 + 0.054 \cdot \text{SL}$	$0.128 + 0.056 \cdot \text{SL}$	$0.119 + 0.056 \cdot \text{SL}$
	t_F	0.150	$0.109 + 0.020 \cdot \text{SL}$	$0.103 + 0.022 \cdot \text{SL}$	$0.089 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.148	$0.099 + 0.025 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.107	$0.080 + 0.014 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.177	$0.129 + 0.024 \cdot \text{SL}$	$0.120 + 0.027 \cdot \text{SL}$	$0.101 + 0.028 \cdot \text{SL}$
	t_F	0.130	$0.097 + 0.017 \cdot \text{SL}$	$0.088 + 0.019 \cdot \text{SL}$	$0.069 + 0.020 \cdot \text{SL}$
	t_{PLH}	0.094	$0.067 + 0.013 \cdot \text{SL}$	$0.073 + 0.012 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.084	$0.060 + 0.012 \cdot \text{SL}$	$0.069 + 0.010 \cdot \text{SL}$	$0.069 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.200	$0.150 + 0.025 \cdot \text{SL}$	$0.143 + 0.027 \cdot \text{SL}$	$0.123 + 0.028 \cdot \text{SL}$
	t_F	0.122	$0.089 + 0.017 \cdot \text{SL}$	$0.078 + 0.020 \cdot \text{SL}$	$0.065 + 0.020 \cdot \text{SL}$
	t_{PLH}	0.109	$0.084 + 0.013 \cdot \text{SL}$	$0.087 + 0.012 \cdot \text{SL}$	$0.084 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.078	$0.056 + 0.011 \cdot \text{SL}$	$0.061 + 0.010 \cdot \text{SL}$	$0.063 + 0.010 \cdot \text{SL}$
C to Y	t_R	0.189	$0.136 + 0.026 \cdot \text{SL}$	$0.131 + 0.028 \cdot \text{SL}$	$0.121 + 0.028 \cdot \text{SL}$
	t_F	0.128	$0.108 + 0.010 \cdot \text{SL}$	$0.105 + 0.011 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.120	$0.094 + 0.013 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.094	$0.078 + 0.008 \cdot \text{SL}$	$0.083 + 0.006 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO21DH/AO21/AO21D2/AO21D2B/AO21D4

2-AND into 2-NOR with 0.5X/1X/2X/2X(Bufferd)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20ns$, SL: Standard Load)

AO21D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.051 + 0.013*SL$	$0.050 + 0.014*SL$	$0.040 + 0.014*SL$
	t_F	0.069	$0.044 + 0.013*SL$	$0.048 + 0.012*SL$	$0.040 + 0.012*SL$
	t_{PLH}	0.220	$0.203 + 0.008*SL$	$0.209 + 0.007*SL$	$0.215 + 0.006*SL$
	t_{PHL}	0.201	$0.183 + 0.009*SL$	$0.191 + 0.007*SL$	$0.200 + 0.006*SL$
B to Y	t_R	0.077	$0.051 + 0.013*SL$	$0.049 + 0.014*SL$	$0.041 + 0.014*SL$
	t_F	0.070	$0.046 + 0.012*SL$	$0.047 + 0.012*SL$	$0.041 + 0.012*SL$
	t_{PLH}	0.238	$0.222 + 0.008*SL$	$0.228 + 0.007*SL$	$0.234 + 0.006*SL$
	t_{PHL}	0.196	$0.178 + 0.009*SL$	$0.186 + 0.007*SL$	$0.195 + 0.006*SL$
C to Y	t_R	0.078	$0.051 + 0.013*SL$	$0.051 + 0.013*SL$	$0.039 + 0.014*SL$
	t_F	0.068	$0.042 + 0.013*SL$	$0.047 + 0.012*SL$	$0.039 + 0.012*SL$
	t_{PLH}	0.254	$0.238 + 0.008*SL$	$0.243 + 0.007*SL$	$0.249 + 0.006*SL$
	t_{PHL}	0.208	$0.190 + 0.009*SL$	$0.198 + 0.007*SL$	$0.207 + 0.006*SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 16$, *Group3 : $16 < SL$

AO21D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.072	$0.059 + 0.007*SL$	$0.059 + 0.007*SL$	$0.049 + 0.007*SL$
	t_F	0.065	$0.054 + 0.006*SL$	$0.053 + 0.006*SL$	$0.051 + 0.006*SL$
	t_{PLH}	0.241	$0.231 + 0.005*SL$	$0.236 + 0.004*SL$	$0.247 + 0.003*SL$
	t_{PHL}	0.222	$0.212 + 0.005*SL$	$0.217 + 0.004*SL$	$0.233 + 0.003*SL$
B to Y	t_R	0.073	$0.059 + 0.007*SL$	$0.060 + 0.007*SL$	$0.049 + 0.007*SL$
	t_F	0.065	$0.051 + 0.007*SL$	$0.055 + 0.006*SL$	$0.051 + 0.006*SL$
	t_{PLH}	0.258	$0.248 + 0.005*SL$	$0.253 + 0.004*SL$	$0.264 + 0.003*SL$
	t_{PHL}	0.216	$0.206 + 0.005*SL$	$0.211 + 0.004*SL$	$0.227 + 0.003*SL$
C to Y	t_R	0.073	$0.059 + 0.007*SL$	$0.060 + 0.007*SL$	$0.049 + 0.007*SL$
	t_F	0.064	$0.052 + 0.006*SL$	$0.054 + 0.006*SL$	$0.050 + 0.006*SL$
	t_{PLH}	0.274	$0.265 + 0.005*SL$	$0.269 + 0.003*SL$	$0.280 + 0.003*SL$
	t_{PHL}	0.225	$0.214 + 0.005*SL$	$0.220 + 0.004*SL$	$0.235 + 0.003*SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 27$, *Group3 : $27 < SL$

AO211DH/AO211/AO211D2/AO211D2B/AO211D4

2-AND into 3-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	0	0	1
x	0	0	0	1
Other States				0

Cell Data

Input Load (SL)																			
AO211DH				AO211				AO211D2				AO211D2B				AO211D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.9	0.9	0.9	0.9	2.0	1.9	1.8	1.8	0.9	1.0	0.9	0.9	0.9	0.9	0.9	0.9
Gate Count																			
AO211DH				AO211				AO211D2				AO211D2B				AO211D4			
1.67				1.67				2.67				2.67				3.00			

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO211DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.565	$0.221 + 0.172 \cdot \text{SL}$	$0.206 + 0.176 \cdot \text{SL}$	$0.214 + 0.175 \cdot \text{SL}$
	t_F	0.299	$0.109 + 0.095 \cdot \text{SL}$	$0.093 + 0.099 \cdot \text{SL}$	$0.085 + 0.100 \cdot \text{SL}$
	t_{PLH}	0.238	$0.088 + 0.075 \cdot \text{SL}$	$0.086 + 0.075 \cdot \text{SL}$	$0.086 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.182	$0.088 + 0.047 \cdot \text{SL}$	$0.087 + 0.048 \cdot \text{SL}$	$0.087 + 0.048 \cdot \text{SL}$
B to Y	t_R	0.591	$0.248 + 0.172 \cdot \text{SL}$	$0.233 + 0.176 \cdot \text{SL}$	$0.241 + 0.175 \cdot \text{SL}$
	t_F	0.296	$0.104 + 0.096 \cdot \text{SL}$	$0.092 + 0.099 \cdot \text{SL}$	$0.085 + 0.100 \cdot \text{SL}$
	t_{PLH}	0.253	$0.105 + 0.074 \cdot \text{SL}$	$0.103 + 0.075 \cdot \text{SL}$	$0.102 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.177	$0.082 + 0.048 \cdot \text{SL}$	$0.082 + 0.048 \cdot \text{SL}$	$0.082 + 0.048 \cdot \text{SL}$
C to Y	t_R	0.600	$0.257 + 0.171 \cdot \text{SL}$	$0.246 + 0.174 \cdot \text{SL}$	$0.243 + 0.175 \cdot \text{SL}$
	t_F	0.262	$0.134 + 0.064 \cdot \text{SL}$	$0.121 + 0.067 \cdot \text{SL}$	$0.110 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.309	$0.158 + 0.076 \cdot \text{SL}$	$0.160 + 0.075 \cdot \text{SL}$	$0.162 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.186	$0.115 + 0.036 \cdot \text{SL}$	$0.116 + 0.035 \cdot \text{SL}$	$0.118 + 0.035 \cdot \text{SL}$
D to Y	t_R	0.599	$0.255 + 0.172 \cdot \text{SL}$	$0.246 + 0.174 \cdot \text{SL}$	$0.243 + 0.175 \cdot \text{SL}$
	t_F	0.289	$0.162 + 0.064 \cdot \text{SL}$	$0.149 + 0.067 \cdot \text{SL}$	$0.136 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.316	$0.165 + 0.076 \cdot \text{SL}$	$0.167 + 0.075 \cdot \text{SL}$	$0.169 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.196	$0.123 + 0.037 \cdot \text{SL}$	$0.127 + 0.036 \cdot \text{SL}$	$0.130 + 0.035 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO211DH/AO211/AO211D2/AO211D2B/AO211D4

2-AND into 3-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO211

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.361	$0.202 + 0.080 \cdot \text{SL}$	$0.192 + 0.082 \cdot \text{SL}$	$0.180 + 0.083 \cdot \text{SL}$
	t_F	0.191	$0.106 + 0.043 \cdot \text{SL}$	$0.094 + 0.046 \cdot \text{SL}$	$0.080 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.153	$0.085 + 0.034 \cdot \text{SL}$	$0.079 + 0.035 \cdot \text{SL}$	$0.079 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.126	$0.079 + 0.023 \cdot \text{SL}$	$0.082 + 0.023 \cdot \text{SL}$	$0.081 + 0.023 \cdot \text{SL}$
B to Y	t_R	0.386	$0.230 + 0.078 \cdot \text{SL}$	$0.218 + 0.081 \cdot \text{SL}$	$0.205 + 0.083 \cdot \text{SL}$
	t_F	0.186	$0.097 + 0.044 \cdot \text{SL}$	$0.089 + 0.046 \cdot \text{SL}$	$0.079 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.167	$0.099 + 0.034 \cdot \text{SL}$	$0.095 + 0.035 \cdot \text{SL}$	$0.094 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.120	$0.073 + 0.024 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$	$0.075 + 0.023 \cdot \text{SL}$
C to Y	t_R	0.391	$0.233 + 0.079 \cdot \text{SL}$	$0.225 + 0.081 \cdot \text{SL}$	$0.217 + 0.082 \cdot \text{SL}$
	t_F	0.188	$0.129 + 0.030 \cdot \text{SL}$	$0.123 + 0.031 \cdot \text{SL}$	$0.109 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.213	$0.142 + 0.036 \cdot \text{SL}$	$0.143 + 0.036 \cdot \text{SL}$	$0.145 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.143	$0.108 + 0.017 \cdot \text{SL}$	$0.109 + 0.017 \cdot \text{SL}$	$0.111 + 0.017 \cdot \text{SL}$
D to Y	t_R	0.389	$0.229 + 0.080 \cdot \text{SL}$	$0.223 + 0.082 \cdot \text{SL}$	$0.216 + 0.082 \cdot \text{SL}$
	t_F	0.215	$0.155 + 0.030 \cdot \text{SL}$	$0.150 + 0.031 \cdot \text{SL}$	$0.136 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.221	$0.149 + 0.036 \cdot \text{SL}$	$0.150 + 0.036 \cdot \text{SL}$	$0.152 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.153	$0.116 + 0.018 \cdot \text{SL}$	$0.119 + 0.018 \cdot \text{SL}$	$0.122 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO211D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.277	$0.198 + 0.040 \cdot \text{SL}$	$0.192 + 0.041 \cdot \text{SL}$	$0.175 + 0.042 \cdot \text{SL}$
	t_F	0.147	$0.105 + 0.021 \cdot \text{SL}$	$0.097 + 0.023 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.117	$0.082 + 0.017 \cdot \text{SL}$	$0.081 + 0.018 \cdot \text{SL}$	$0.078 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.102	$0.076 + 0.013 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.302	$0.225 + 0.039 \cdot \text{SL}$	$0.217 + 0.041 \cdot \text{SL}$	$0.200 + 0.042 \cdot \text{SL}$
	t_F	0.142	$0.098 + 0.022 \cdot \text{SL}$	$0.092 + 0.024 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.131	$0.097 + 0.017 \cdot \text{SL}$	$0.095 + 0.018 \cdot \text{SL}$	$0.092 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.095	$0.069 + 0.013 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.306	$0.227 + 0.039 \cdot \text{SL}$	$0.222 + 0.041 \cdot \text{SL}$	$0.211 + 0.042 \cdot \text{SL}$
	t_F	0.159	$0.129 + 0.015 \cdot \text{SL}$	$0.125 + 0.016 \cdot \text{SL}$	$0.110 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.175	$0.138 + 0.018 \cdot \text{SL}$	$0.139 + 0.018 \cdot \text{SL}$	$0.141 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.126	$0.107 + 0.009 \cdot \text{SL}$	$0.109 + 0.009 \cdot \text{SL}$	$0.110 + 0.009 \cdot \text{SL}$
D to Y	t_R	0.304	$0.224 + 0.040 \cdot \text{SL}$	$0.220 + 0.041 \cdot \text{SL}$	$0.210 + 0.042 \cdot \text{SL}$
	t_F	0.185	$0.155 + 0.015 \cdot \text{SL}$	$0.153 + 0.016 \cdot \text{SL}$	$0.139 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.182	$0.145 + 0.018 \cdot \text{SL}$	$0.146 + 0.018 \cdot \text{SL}$	$0.149 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.135	$0.117 + 0.009 \cdot \text{SL}$	$0.118 + 0.009 \cdot \text{SL}$	$0.121 + 0.009 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO211DH/AO211/AO211D2/AO211D2B/AO211D4

2-AND into 3-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO211D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.244 + 0.008 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.257 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.224	$0.206 + 0.009 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$	$0.223 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.280	$0.263 + 0.008 \cdot \text{SL}$	$0.269 + 0.007 \cdot \text{SL}$	$0.276 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.218	$0.200 + 0.009 \cdot \text{SL}$	$0.207 + 0.007 \cdot \text{SL}$	$0.217 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.085	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.069	$0.044 + 0.013 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.325	$0.308 + 0.008 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.321 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.246	$0.228 + 0.009 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.245 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.046 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.331	$0.315 + 0.008 \cdot \text{SL}$	$0.321 + 0.007 \cdot \text{SL}$	$0.328 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.259	$0.241 + 0.009 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$	$0.258 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO211D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.285	$0.276 + 0.005 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$	$0.292 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.244	$0.233 + 0.005 \cdot \text{SL}$	$0.239 + 0.004 \cdot \text{SL}$	$0.254 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.304	$0.294 + 0.005 \cdot \text{SL}$	$0.300 + 0.004 \cdot \text{SL}$	$0.311 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.237	$0.227 + 0.005 \cdot \text{SL}$	$0.232 + 0.004 \cdot \text{SL}$	$0.248 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.054 + 0.005 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.349	$0.340 + 0.005 \cdot \text{SL}$	$0.345 + 0.004 \cdot \text{SL}$	$0.357 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.264	$0.254 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.358	$0.348 + 0.005 \cdot \text{SL}$	$0.353 + 0.004 \cdot \text{SL}$	$0.365 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.279	$0.268 + 0.005 \cdot \text{SL}$	$0.274 + 0.004 \cdot \text{SL}$	$0.289 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO2111/AO2111D2

2-AND into 4-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	0
x	x	1	x	x	0
x	x	x	1	x	0
x	x	x	x	1	0
Other states					1

Cell Data

Input Load (SL)										Gate Count	
AO2111					AO2111D2					AO2111	AO2111D2
A	B	C	D	E	A	B	C	D	E		
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	2.00	2.67

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO2111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.510	$0.293 + 0.108 \cdot \text{SL}$	$0.284 + 0.111 \cdot \text{SL}$	$0.281 + 0.111 \cdot \text{SL}$
	t_F	0.198	$0.112 + 0.043 \cdot \text{SL}$	$0.101 + 0.046 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.183	$0.093 + 0.045 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.130	$0.084 + 0.023 \cdot \text{SL}$	$0.086 + 0.023 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$
B to Y	t_R	0.544	$0.330 + 0.107 \cdot \text{SL}$	$0.318 + 0.110 \cdot \text{SL}$	$0.314 + 0.111 \cdot \text{SL}$
	t_F	0.193	$0.105 + 0.044 \cdot \text{SL}$	$0.096 + 0.046 \cdot \text{SL}$	$0.087 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.201	$0.111 + 0.045 \cdot \text{SL}$	$0.105 + 0.047 \cdot \text{SL}$	$0.103 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.124	$0.078 + 0.023 \cdot \text{SL}$	$0.080 + 0.023 \cdot \text{SL}$	$0.080 + 0.023 \cdot \text{SL}$
C to Y	t_R	0.568	$0.355 + 0.107 \cdot \text{SL}$	$0.347 + 0.109 \cdot \text{SL}$	$0.342 + 0.109 \cdot \text{SL}$
	t_F	0.212	$0.143 + 0.035 \cdot \text{SL}$	$0.137 + 0.036 \cdot \text{SL}$	$0.126 + 0.038 \cdot \text{SL}$
	t_{PLH}	0.278	$0.182 + 0.048 \cdot \text{SL}$	$0.185 + 0.047 \cdot \text{SL}$	$0.187 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.163	$0.123 + 0.020 \cdot \text{SL}$	$0.124 + 0.020 \cdot \text{SL}$	$0.126 + 0.020 \cdot \text{SL}$
D to Y	t_R	0.569	$0.356 + 0.107 \cdot \text{SL}$	$0.349 + 0.109 \cdot \text{SL}$	$0.342 + 0.109 \cdot \text{SL}$
	t_F	0.242	$0.172 + 0.035 \cdot \text{SL}$	$0.167 + 0.036 \cdot \text{SL}$	$0.156 + 0.037 \cdot \text{SL}$
	t_{PLH}	0.307	$0.211 + 0.048 \cdot \text{SL}$	$0.213 + 0.047 \cdot \text{SL}$	$0.216 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.176	$0.135 + 0.021 \cdot \text{SL}$	$0.137 + 0.020 \cdot \text{SL}$	$0.141 + 0.020 \cdot \text{SL}$
E to Y	t_R	0.568	$0.354 + 0.107 \cdot \text{SL}$	$0.348 + 0.109 \cdot \text{SL}$	$0.342 + 0.109 \cdot \text{SL}$
	t_F	0.270	$0.199 + 0.035 \cdot \text{SL}$	$0.195 + 0.037 \cdot \text{SL}$	$0.186 + 0.038 \cdot \text{SL}$
	t_{PLH}	0.319	$0.222 + 0.048 \cdot \text{SL}$	$0.225 + 0.047 \cdot \text{SL}$	$0.228 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.183	$0.140 + 0.022 \cdot \text{SL}$	$0.144 + 0.021 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO2111/AO2111D2

2-AND into 4-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO2111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.088	$0.063 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.282	$0.265 + 0.008 \cdot \text{SL}$	$0.271 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.222	$0.204 + 0.009 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.221 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.091	$0.065 + 0.013 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.309	$0.292 + 0.008 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$	$0.306 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.216	$0.199 + 0.009 \cdot \text{SL}$	$0.206 + 0.007 \cdot \text{SL}$	$0.215 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.092	$0.066 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.382	$0.365 + 0.008 \cdot \text{SL}$	$0.371 + 0.007 \cdot \text{SL}$	$0.379 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.266	$0.248 + 0.009 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.265 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.091	$0.067 + 0.012 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.411	$0.394 + 0.008 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.284	$0.266 + 0.009 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.092	$0.065 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.423	$0.406 + 0.008 \cdot \text{SL}$	$0.413 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.295	$0.277 + 0.009 \cdot \text{SL}$	$0.284 + 0.007 \cdot \text{SL}$	$0.294 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO22DH/AO22/AO22D2/AO22D2B/AO22D4

Two 2-ANDs into 2-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	0
x	x	1	1	0
0	x	0	x	1
0	x	x	0	1
x	0	x	0	1
x	0	0	x	1

Cell Data

Input Load (SL)																			
AO22DH				AO22				AO22D2				AO22D2B				AO22D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.1	1.0	1.1	2.1	2.1	2.1	2.1	1.1	1.1	1.1	1.2	1.1	1.1	1.1	1.2
Gate Count																			
AO22DH				AO22				AO22D2				AO22D2B				AO22D4			
1.67				1.67				2.67				2.67				3.00			

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO22DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.395	$0.162 + 0.116 \cdot \text{SL}$	$0.147 + 0.120 \cdot \text{SL}$	$0.143 + 0.121 \cdot \text{SL}$
	t_F	0.254	$0.116 + 0.069 \cdot \text{SL}$	$0.098 + 0.074 \cdot \text{SL}$	$0.082 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.197	$0.094 + 0.051 \cdot \text{SL}$	$0.093 + 0.052 \cdot \text{SL}$	$0.093 + 0.052 \cdot \text{SL}$
	t_{PHL}	0.146	$0.073 + 0.036 \cdot \text{SL}$	$0.075 + 0.036 \cdot \text{SL}$	$0.075 + 0.036 \cdot \text{SL}$
B to Y	t_R	0.416	$0.185 + 0.115 \cdot \text{SL}$	$0.171 + 0.119 \cdot \text{SL}$	$0.166 + 0.119 \cdot \text{SL}$
	t_F	0.248	$0.106 + 0.071 \cdot \text{SL}$	$0.094 + 0.074 \cdot \text{SL}$	$0.082 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.210	$0.109 + 0.050 \cdot \text{SL}$	$0.107 + 0.051 \cdot \text{SL}$	$0.106 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.141	$0.067 + 0.037 \cdot \text{SL}$	$0.070 + 0.036 \cdot \text{SL}$	$0.070 + 0.036 \cdot \text{SL}$
C to Y	t_R	0.391	$0.159 + 0.116 \cdot \text{SL}$	$0.148 + 0.119 \cdot \text{SL}$	$0.144 + 0.119 \cdot \text{SL}$
	t_F	0.299	$0.159 + 0.070 \cdot \text{SL}$	$0.144 + 0.074 \cdot \text{SL}$	$0.131 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.228	$0.124 + 0.052 \cdot \text{SL}$	$0.126 + 0.051 \cdot \text{SL}$	$0.128 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.187	$0.113 + 0.037 \cdot \text{SL}$	$0.116 + 0.036 \cdot \text{SL}$	$0.118 + 0.036 \cdot \text{SL}$
D to Y	t_R	0.415	$0.182 + 0.116 \cdot \text{SL}$	$0.173 + 0.119 \cdot \text{SL}$	$0.168 + 0.119 \cdot \text{SL}$
	t_F	0.294	$0.151 + 0.072 \cdot \text{SL}$	$0.141 + 0.074 \cdot \text{SL}$	$0.132 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.243	$0.141 + 0.051 \cdot \text{SL}$	$0.141 + 0.051 \cdot \text{SL}$	$0.142 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.181	$0.107 + 0.037 \cdot \text{SL}$	$0.110 + 0.036 \cdot \text{SL}$	$0.113 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO22DH/AO22/AO22D2/AO22D2B/AO22D4

Two 2-ANDs into 2-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.257	$0.151 + 0.053 \cdot \text{SL}$	$0.144 + 0.055 \cdot \text{SL}$	$0.130 + 0.057 \cdot \text{SL}$
	t_F	0.178	$0.117 + 0.031 \cdot \text{SL}$	$0.104 + 0.034 \cdot \text{SL}$	$0.089 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.137	$0.089 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.103	$0.065 + 0.019 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$
B to Y	t_R	0.281	$0.176 + 0.052 \cdot \text{SL}$	$0.167 + 0.055 \cdot \text{SL}$	$0.153 + 0.056 \cdot \text{SL}$
	t_F	0.170	$0.108 + 0.031 \cdot \text{SL}$	$0.096 + 0.035 \cdot \text{SL}$	$0.084 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.151	$0.104 + 0.023 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$	$0.101 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.097	$0.059 + 0.019 \cdot \text{SL}$	$0.065 + 0.017 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$
C to Y	t_R	0.253	$0.146 + 0.053 \cdot \text{SL}$	$0.139 + 0.055 \cdot \text{SL}$	$0.131 + 0.056 \cdot \text{SL}$
	t_F	0.216	$0.151 + 0.033 \cdot \text{SL}$	$0.144 + 0.034 \cdot \text{SL}$	$0.131 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.162	$0.113 + 0.025 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.143	$0.107 + 0.018 \cdot \text{SL}$	$0.108 + 0.017 \cdot \text{SL}$	$0.110 + 0.017 \cdot \text{SL}$
D to Y	t_R	0.275	$0.167 + 0.054 \cdot \text{SL}$	$0.162 + 0.055 \cdot \text{SL}$	$0.155 + 0.056 \cdot \text{SL}$
	t_F	0.210	$0.143 + 0.033 \cdot \text{SL}$	$0.137 + 0.035 \cdot \text{SL}$	$0.129 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.177	$0.128 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.136	$0.100 + 0.018 \cdot \text{SL}$	$0.102 + 0.018 \cdot \text{SL}$	$0.104 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.206	$0.154 + 0.026 \cdot \text{SL}$	$0.149 + 0.027 \cdot \text{SL}$	$0.133 + 0.028 \cdot \text{SL}$
	t_F	0.150	$0.121 + 0.014 \cdot \text{SL}$	$0.112 + 0.017 \cdot \text{SL}$	$0.094 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.115	$0.090 + 0.012 \cdot \text{SL}$	$0.091 + 0.012 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.086	$0.065 + 0.011 \cdot \text{SL}$	$0.072 + 0.009 \cdot \text{SL}$	$0.073 + 0.009 \cdot \text{SL}$
B to Y	t_R	0.230	$0.178 + 0.026 \cdot \text{SL}$	$0.173 + 0.028 \cdot \text{SL}$	$0.158 + 0.028 \cdot \text{SL}$
	t_F	0.142	$0.114 + 0.014 \cdot \text{SL}$	$0.102 + 0.017 \cdot \text{SL}$	$0.089 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.130	$0.107 + 0.012 \cdot \text{SL}$	$0.106 + 0.012 \cdot \text{SL}$	$0.104 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.080	$0.060 + 0.010 \cdot \text{SL}$	$0.065 + 0.009 \cdot \text{SL}$	$0.067 + 0.009 \cdot \text{SL}$
C to Y	t_R	0.201	$0.148 + 0.027 \cdot \text{SL}$	$0.144 + 0.028 \cdot \text{SL}$	$0.134 + 0.028 \cdot \text{SL}$
	t_F	0.184	$0.151 + 0.016 \cdot \text{SL}$	$0.148 + 0.017 \cdot \text{SL}$	$0.133 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.136	$0.110 + 0.013 \cdot \text{SL}$	$0.113 + 0.012 \cdot \text{SL}$	$0.114 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.125	$0.106 + 0.009 \cdot \text{SL}$	$0.108 + 0.009 \cdot \text{SL}$	$0.109 + 0.009 \cdot \text{SL}$
D to Y	t_R	0.224	$0.170 + 0.027 \cdot \text{SL}$	$0.167 + 0.028 \cdot \text{SL}$	$0.158 + 0.029 \cdot \text{SL}$
	t_F	0.177	$0.143 + 0.017 \cdot \text{SL}$	$0.141 + 0.018 \cdot \text{SL}$	$0.129 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.152	$0.127 + 0.012 \cdot \text{SL}$	$0.127 + 0.012 \cdot \text{SL}$	$0.128 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.118	$0.099 + 0.010 \cdot \text{SL}$	$0.101 + 0.009 \cdot \text{SL}$	$0.103 + 0.009 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO22DH/AO22/AO22D2/AO22D2B/AO22D4

Two 2-ANDs into 2-NOR with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO22D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.249	$0.233 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.209	$0.192 + 0.009 \cdot \text{SL}$	$0.199 + 0.007 \cdot \text{SL}$	$0.208 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.266	$0.250 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.204	$0.186 + 0.009 \cdot \text{SL}$	$0.193 + 0.007 \cdot \text{SL}$	$0.202 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.266	$0.249 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.248	$0.230 + 0.009 \cdot \text{SL}$	$0.237 + 0.007 \cdot \text{SL}$	$0.247 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.285	$0.269 + 0.008 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.280 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.241	$0.223 + 0.009 \cdot \text{SL}$	$0.230 + 0.007 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO22D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.060 + 0.007 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.007 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.268	$0.258 + 0.005 \cdot \text{SL}$	$0.263 + 0.003 \cdot \text{SL}$	$0.273 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.225	$0.215 + 0.005 \cdot \text{SL}$	$0.220 + 0.004 \cdot \text{SL}$	$0.235 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.075	$0.061 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.284	$0.275 + 0.005 \cdot \text{SL}$	$0.279 + 0.003 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.219	$0.209 + 0.005 \cdot \text{SL}$	$0.214 + 0.004 \cdot \text{SL}$	$0.229 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.074	$0.060 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.054 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.284	$0.275 + 0.005 \cdot \text{SL}$	$0.279 + 0.003 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.263	$0.253 + 0.005 \cdot \text{SL}$	$0.258 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.075	$0.062 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.301	$0.292 + 0.005 \cdot \text{SL}$	$0.297 + 0.003 \cdot \text{SL}$	$0.307 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.246 + 0.005 \cdot \text{SL}$	$0.251 + 0.004 \cdot \text{SL}$	$0.267 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO22DHA/AO22A/AO22D2A/AO22D4A

2-AND and 2-NOR into 2-NOR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	0
x	x	0	0	0
Other States				1

Cell Data

Input Load (SL)															
AO22DHA				AO22A				AO22D2A				AO22D4A			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.6	0.5	0.5	1.0	1.1	0.9	0.9	2.1	2.1	0.9	0.9	1.1	1.1	0.9	0.9
Gate Count															
AO22DHA				AO22A				AO22D2A				AO22D4A			
2.33				2.67				3.67				4.00			

AO22DHA/AO22A/AO22D2A/AO22D4A

2-AND and 2-NOR into 2-NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO22DHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.383	$0.153 + 0.115 \cdot \text{SL}$	$0.138 + 0.119 \cdot \text{SL}$	$0.133 + 0.119 \cdot \text{SL}$
	t_F	0.252	$0.114 + 0.069 \cdot \text{SL}$	$0.096 + 0.074 \cdot \text{SL}$	$0.080 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.195	$0.094 + 0.051 \cdot \text{SL}$	$0.093 + 0.051 \cdot \text{SL}$	$0.093 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.144	$0.071 + 0.036 \cdot \text{SL}$	$0.073 + 0.036 \cdot \text{SL}$	$0.074 + 0.036 \cdot \text{SL}$
B to Y	t_R	0.405	$0.177 + 0.114 \cdot \text{SL}$	$0.161 + 0.118 \cdot \text{SL}$	$0.156 + 0.119 \cdot \text{SL}$
	t_F	0.246	$0.104 + 0.071 \cdot \text{SL}$	$0.091 + 0.074 \cdot \text{SL}$	$0.080 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.209	$0.108 + 0.050 \cdot \text{SL}$	$0.106 + 0.051 \cdot \text{SL}$	$0.105 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.138	$0.064 + 0.037 \cdot \text{SL}$	$0.067 + 0.036 \cdot \text{SL}$	$0.068 + 0.036 \cdot \text{SL}$
C to Y	t_R	0.382	$0.144 + 0.119 \cdot \text{SL}$	$0.138 + 0.121 \cdot \text{SL}$	$0.136 + 0.121 \cdot \text{SL}$
	t_F	0.277	$0.130 + 0.073 \cdot \text{SL}$	$0.124 + 0.075 \cdot \text{SL}$	$0.120 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.305	$0.200 + 0.053 \cdot \text{SL}$	$0.203 + 0.052 \cdot \text{SL}$	$0.205 + 0.052 \cdot \text{SL}$
	t_{PHL}	0.228	$0.154 + 0.037 \cdot \text{SL}$	$0.157 + 0.036 \cdot \text{SL}$	$0.159 + 0.036 \cdot \text{SL}$
D to Y	t_R	0.399	$0.165 + 0.117 \cdot \text{SL}$	$0.160 + 0.118 \cdot \text{SL}$	$0.158 + 0.119 \cdot \text{SL}$
	t_F	0.276	$0.128 + 0.074 \cdot \text{SL}$	$0.124 + 0.075 \cdot \text{SL}$	$0.120 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.321	$0.218 + 0.051 \cdot \text{SL}$	$0.220 + 0.051 \cdot \text{SL}$	$0.221 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.232	$0.157 + 0.037 \cdot \text{SL}$	$0.161 + 0.036 \cdot \text{SL}$	$0.164 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO22A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.258	$0.152 + 0.053 \cdot \text{SL}$	$0.145 + 0.055 \cdot \text{SL}$	$0.130 + 0.057 \cdot \text{SL}$
	t_F	0.178	$0.117 + 0.031 \cdot \text{SL}$	$0.105 + 0.034 \cdot \text{SL}$	$0.089 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.137	$0.089 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$	$0.087 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.103	$0.065 + 0.019 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$
B to Y	t_R	0.282	$0.177 + 0.052 \cdot \text{SL}$	$0.168 + 0.055 \cdot \text{SL}$	$0.154 + 0.056 \cdot \text{SL}$
	t_F	0.171	$0.108 + 0.032 \cdot \text{SL}$	$0.096 + 0.035 \cdot \text{SL}$	$0.084 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.151	$0.104 + 0.023 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$	$0.101 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.097	$0.059 + 0.019 \cdot \text{SL}$	$0.065 + 0.017 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$
C to Y	t_R	0.248	$0.138 + 0.055 \cdot \text{SL}$	$0.134 + 0.056 \cdot \text{SL}$	$0.130 + 0.056 \cdot \text{SL}$
	t_F	0.202	$0.133 + 0.035 \cdot \text{SL}$	$0.130 + 0.035 \cdot \text{SL}$	$0.125 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.244	$0.194 + 0.025 \cdot \text{SL}$	$0.196 + 0.024 \cdot \text{SL}$	$0.198 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.183	$0.146 + 0.018 \cdot \text{SL}$	$0.149 + 0.018 \cdot \text{SL}$	$0.152 + 0.017 \cdot \text{SL}$
D to Y	t_R	0.271	$0.161 + 0.055 \cdot \text{SL}$	$0.157 + 0.056 \cdot \text{SL}$	$0.153 + 0.056 \cdot \text{SL}$
	t_F	0.200	$0.130 + 0.035 \cdot \text{SL}$	$0.128 + 0.036 \cdot \text{SL}$	$0.124 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.254	$0.204 + 0.025 \cdot \text{SL}$	$0.206 + 0.024 \cdot \text{SL}$	$0.208 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.183	$0.146 + 0.018 \cdot \text{SL}$	$0.149 + 0.018 \cdot \text{SL}$	$0.152 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO22DHA/AO22A/AO22D2A/AO22D4A

2-AND and 2-NOR into 2-NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20ns$, SL: Standard Load)

AO22D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.208	$0.155 + 0.026*SL$	$0.151 + 0.027*SL$	$0.135 + 0.028*SL$
	t_F	0.150	$0.121 + 0.015*SL$	$0.112 + 0.017*SL$	$0.094 + 0.018*SL$
	t_{PLH}	0.114	$0.090 + 0.012*SL$	$0.090 + 0.012*SL$	$0.089 + 0.012*SL$
	t_{PHL}	0.086	$0.064 + 0.011*SL$	$0.071 + 0.009*SL$	$0.073 + 0.009*SL$
B to Y	t_R	0.232	$0.180 + 0.026*SL$	$0.175 + 0.027*SL$	$0.159 + 0.028*SL$
	t_F	0.142	$0.113 + 0.015*SL$	$0.103 + 0.017*SL$	$0.090 + 0.018*SL$
	t_{PLH}	0.130	$0.106 + 0.012*SL$	$0.105 + 0.012*SL$	$0.103 + 0.012*SL$
	t_{PHL}	0.079	$0.059 + 0.010*SL$	$0.064 + 0.009*SL$	$0.067 + 0.009*SL$
C to Y	t_R	0.198	$0.144 + 0.027*SL$	$0.140 + 0.028*SL$	$0.134 + 0.028*SL$
	t_F	0.173	$0.138 + 0.017*SL$	$0.136 + 0.018*SL$	$0.130 + 0.018*SL$
	t_{PLH}	0.238	$0.212 + 0.013*SL$	$0.214 + 0.012*SL$	$0.217 + 0.012*SL$
	t_{PHL}	0.187	$0.168 + 0.010*SL$	$0.170 + 0.009*SL$	$0.173 + 0.009*SL$
D to Y	t_R	0.223	$0.168 + 0.027*SL$	$0.165 + 0.028*SL$	$0.159 + 0.029*SL$
	t_F	0.170	$0.134 + 0.018*SL$	$0.134 + 0.018*SL$	$0.129 + 0.018*SL$
	t_{PLH}	0.252	$0.227 + 0.013*SL$	$0.228 + 0.012*SL$	$0.230 + 0.012*SL$
	t_{PHL}	0.189	$0.170 + 0.010*SL$	$0.172 + 0.009*SL$	$0.176 + 0.009*SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 16$, *Group3 : $16 < SL$

AO22D4A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.060 + 0.007*SL$	$0.061 + 0.007*SL$	$0.049 + 0.007*SL$
	t_F	0.066	$0.052 + 0.007*SL$	$0.056 + 0.006*SL$	$0.051 + 0.006*SL$
	t_{PLH}	0.267	$0.258 + 0.005*SL$	$0.263 + 0.003*SL$	$0.273 + 0.003*SL$
	t_{PHL}	0.225	$0.214 + 0.005*SL$	$0.220 + 0.004*SL$	$0.235 + 0.003*SL$
B to Y	t_R	0.074	$0.061 + 0.007*SL$	$0.061 + 0.007*SL$	$0.050 + 0.007*SL$
	t_F	0.067	$0.056 + 0.006*SL$	$0.055 + 0.006*SL$	$0.051 + 0.006*SL$
	t_{PLH}	0.284	$0.274 + 0.005*SL$	$0.279 + 0.003*SL$	$0.290 + 0.003*SL$
	t_{PHL}	0.219	$0.208 + 0.005*SL$	$0.214 + 0.004*SL$	$0.229 + 0.003*SL$
C to Y	t_R	0.074	$0.061 + 0.007*SL$	$0.060 + 0.007*SL$	$0.050 + 0.007*SL$
	t_F	0.066	$0.053 + 0.007*SL$	$0.056 + 0.006*SL$	$0.052 + 0.006*SL$
	t_{PLH}	0.367	$0.358 + 0.005*SL$	$0.363 + 0.004*SL$	$0.373 + 0.003*SL$
	t_{PHL}	0.306	$0.295 + 0.005*SL$	$0.301 + 0.004*SL$	$0.316 + 0.003*SL$
D to Y	t_R	0.075	$0.062 + 0.006*SL$	$0.061 + 0.007*SL$	$0.050 + 0.007*SL$
	t_F	0.066	$0.053 + 0.007*SL$	$0.057 + 0.006*SL$	$0.052 + 0.006*SL$
	t_{PLH}	0.382	$0.372 + 0.005*SL$	$0.377 + 0.004*SL$	$0.388 + 0.003*SL$
	t_{PHL}	0.307	$0.297 + 0.005*SL$	$0.302 + 0.004*SL$	$0.318 + 0.003*SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 27$, *Group3 : $27 < SL$

AO221/AO221D2/AO221D4

Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	0
x	x	1	1	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)														
AO221					AO221D2					AO221D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.0	1.0
Gate Count														
AO221					AO221D2					AO221D4				
2.00					3.00					3.67				

AO221/AO221D2/AO221D4

Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO221

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.398	$0.235 + 0.081 \cdot \text{SL}$	$0.226 + 0.084 \cdot \text{SL}$	$0.217 + 0.085 \cdot \text{SL}$
	t_F	0.199	$0.124 + 0.038 \cdot \text{SL}$	$0.114 + 0.040 \cdot \text{SL}$	$0.099 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.173	$0.103 + 0.035 \cdot \text{SL}$	$0.100 + 0.036 \cdot \text{SL}$	$0.100 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.120	$0.078 + 0.021 \cdot \text{SL}$	$0.081 + 0.020 \cdot \text{SL}$	$0.081 + 0.020 \cdot \text{SL}$
B to Y	t_R	0.430	$0.267 + 0.082 \cdot \text{SL}$	$0.257 + 0.084 \cdot \text{SL}$	$0.248 + 0.085 \cdot \text{SL}$
	t_F	0.193	$0.116 + 0.038 \cdot \text{SL}$	$0.106 + 0.041 \cdot \text{SL}$	$0.097 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.192	$0.121 + 0.035 \cdot \text{SL}$	$0.118 + 0.036 \cdot \text{SL}$	$0.117 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.114	$0.071 + 0.021 \cdot \text{SL}$	$0.075 + 0.020 \cdot \text{SL}$	$0.076 + 0.020 \cdot \text{SL}$
C to Y	t_R	0.405	$0.244 + 0.081 \cdot \text{SL}$	$0.237 + 0.082 \cdot \text{SL}$	$0.229 + 0.083 \cdot \text{SL}$
	t_F	0.238	$0.160 + 0.039 \cdot \text{SL}$	$0.153 + 0.041 \cdot \text{SL}$	$0.140 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.222	$0.149 + 0.037 \cdot \text{SL}$	$0.151 + 0.036 \cdot \text{SL}$	$0.154 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.160	$0.119 + 0.021 \cdot \text{SL}$	$0.120 + 0.020 \cdot \text{SL}$	$0.121 + 0.020 \cdot \text{SL}$
D to Y	t_R	0.440	$0.275 + 0.082 \cdot \text{SL}$	$0.269 + 0.084 \cdot \text{SL}$	$0.263 + 0.085 \cdot \text{SL}$
	t_F	0.233	$0.153 + 0.040 \cdot \text{SL}$	$0.149 + 0.041 \cdot \text{SL}$	$0.140 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.245	$0.171 + 0.037 \cdot \text{SL}$	$0.172 + 0.036 \cdot \text{SL}$	$0.174 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.154	$0.113 + 0.021 \cdot \text{SL}$	$0.114 + 0.020 \cdot \text{SL}$	$0.116 + 0.020 \cdot \text{SL}$
E to Y	t_R	0.438	$0.273 + 0.083 \cdot \text{SL}$	$0.268 + 0.084 \cdot \text{SL}$	$0.262 + 0.085 \cdot \text{SL}$
	t_F	0.210	$0.160 + 0.025 \cdot \text{SL}$	$0.156 + 0.026 \cdot \text{SL}$	$0.146 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.269	$0.195 + 0.037 \cdot \text{SL}$	$0.196 + 0.037 \cdot \text{SL}$	$0.199 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.144	$0.113 + 0.016 \cdot \text{SL}$	$0.115 + 0.015 \cdot \text{SL}$	$0.120 + 0.015 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**AO221D2**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.290	$0.273 + 0.008 \cdot \text{SL}$	$0.280 + 0.007 \cdot \text{SL}$	$0.287 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.227	$0.209 + 0.009 \cdot \text{SL}$	$0.216 + 0.007 \cdot \text{SL}$	$0.226 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.049 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.313	$0.297 + 0.008 \cdot \text{SL}$	$0.303 + 0.007 \cdot \text{SL}$	$0.310 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.221	$0.203 + 0.009 \cdot \text{SL}$	$0.210 + 0.007 \cdot \text{SL}$	$0.220 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.338	$0.321 + 0.008 \cdot \text{SL}$	$0.327 + 0.007 \cdot \text{SL}$	$0.334 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.272	$0.254 + 0.009 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.271 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.364	$0.347 + 0.008 \cdot \text{SL}$	$0.354 + 0.007 \cdot \text{SL}$	$0.361 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.266	$0.248 + 0.009 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.265 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.390	$0.374 + 0.008 \cdot \text{SL}$	$0.380 + 0.007 \cdot \text{SL}$	$0.387 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.258	$0.240 + 0.009 \cdot \text{SL}$	$0.247 + 0.007 \cdot \text{SL}$	$0.257 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO221/AO221D2/AO221D4

Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO221D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.068 + 0.007 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.306 + 0.005 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.323 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.245	$0.234 + 0.005 \cdot \text{SL}$	$0.240 + 0.004 \cdot \text{SL}$	$0.255 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.084	$0.071 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.057 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.340	$0.330 + 0.005 \cdot \text{SL}$	$0.335 + 0.004 \cdot \text{SL}$	$0.347 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.239	$0.228 + 0.005 \cdot \text{SL}$	$0.234 + 0.004 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.082	$0.070 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.364	$0.355 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.372 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.290	$0.280 + 0.005 \cdot \text{SL}$	$0.285 + 0.004 \cdot \text{SL}$	$0.301 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.057 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.391	$0.381 + 0.005 \cdot \text{SL}$	$0.387 + 0.004 \cdot \text{SL}$	$0.399 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.284	$0.274 + 0.005 \cdot \text{SL}$	$0.279 + 0.004 \cdot \text{SL}$	$0.295 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.083	$0.070 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.417	$0.408 + 0.005 \cdot \text{SL}$	$0.413 + 0.004 \cdot \text{SL}$	$0.425 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.273	$0.263 + 0.005 \cdot \text{SL}$	$0.268 + 0.004 \cdot \text{SL}$	$0.284 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO222/AO222D2/AO222D2B/AO222D4

Three 2-ANDs into 3-NOR with 1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	x	x	x	x	0
x	x	1	1	x	x	0
x	x	x	x	1	1	0
Other States						1

Cell Data

Input Load (SL)												Gate Count	
AO222						AO222D2						AO222	AO222D2
A	B	C	D	E	F	A	B	C	D	E	F		
1.0	1.0	1.0	1.0	1.0	1.1	1.9	2.0	1.9	2.1	2.0	2.1	2.33	4.00
AO222D2B						AO222D4						AO222D2B	AO222D4
A	B	C	D	E	F	A	B	C	D	E	F		
1.0	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.0	1.1	3.33	4.67

AO222/AO222D2/AO222D2B/AO222D4

Three 2-ANDs into 3-NOR with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.451	$0.285 + 0.083 \cdot \text{SL}$	$0.279 + 0.085 \cdot \text{SL}$	$0.272 + 0.085 \cdot \text{SL}$
	t_F	0.216	$0.146 + 0.035 \cdot \text{SL}$	$0.137 + 0.037 \cdot \text{SL}$	$0.123 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.197	$0.126 + 0.035 \cdot \text{SL}$	$0.123 + 0.036 \cdot \text{SL}$	$0.123 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.123	$0.083 + 0.020 \cdot \text{SL}$	$0.086 + 0.019 \cdot \text{SL}$	$0.087 + 0.019 \cdot \text{SL}$
B to Y	t_R	0.482	$0.317 + 0.083 \cdot \text{SL}$	$0.311 + 0.084 \cdot \text{SL}$	$0.303 + 0.085 \cdot \text{SL}$
	t_F	0.210	$0.138 + 0.036 \cdot \text{SL}$	$0.130 + 0.038 \cdot \text{SL}$	$0.120 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.215	$0.144 + 0.035 \cdot \text{SL}$	$0.142 + 0.036 \cdot \text{SL}$	$0.141 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.116	$0.076 + 0.020 \cdot \text{SL}$	$0.080 + 0.019 \cdot \text{SL}$	$0.081 + 0.019 \cdot \text{SL}$
C to Y	t_R	0.460	$0.298 + 0.081 \cdot \text{SL}$	$0.292 + 0.082 \cdot \text{SL}$	$0.287 + 0.083 \cdot \text{SL}$
	t_F	0.265	$0.191 + 0.037 \cdot \text{SL}$	$0.185 + 0.038 \cdot \text{SL}$	$0.173 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.262	$0.189 + 0.037 \cdot \text{SL}$	$0.191 + 0.036 \cdot \text{SL}$	$0.194 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.168	$0.129 + 0.020 \cdot \text{SL}$	$0.131 + 0.019 \cdot \text{SL}$	$0.132 + 0.019 \cdot \text{SL}$
D to Y	t_R	0.499	$0.334 + 0.082 \cdot \text{SL}$	$0.329 + 0.084 \cdot \text{SL}$	$0.324 + 0.084 \cdot \text{SL}$
	t_F	0.261	$0.186 + 0.037 \cdot \text{SL}$	$0.181 + 0.039 \cdot \text{SL}$	$0.172 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.286	$0.212 + 0.037 \cdot \text{SL}$	$0.214 + 0.036 \cdot \text{SL}$	$0.216 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.163	$0.124 + 0.020 \cdot \text{SL}$	$0.126 + 0.019 \cdot \text{SL}$	$0.128 + 0.019 \cdot \text{SL}$
E to Y	t_R	0.462	$0.299 + 0.082 \cdot \text{SL}$	$0.294 + 0.083 \cdot \text{SL}$	$0.289 + 0.083 \cdot \text{SL}$
	t_F	0.304	$0.231 + 0.036 \cdot \text{SL}$	$0.226 + 0.038 \cdot \text{SL}$	$0.214 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.291	$0.216 + 0.037 \cdot \text{SL}$	$0.219 + 0.036 \cdot \text{SL}$	$0.223 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.188	$0.146 + 0.021 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$	$0.157 + 0.019 \cdot \text{SL}$
F to Y	t_R	0.498	$0.333 + 0.083 \cdot \text{SL}$	$0.329 + 0.084 \cdot \text{SL}$	$0.324 + 0.084 \cdot \text{SL}$
	t_F	0.300	$0.225 + 0.037 \cdot \text{SL}$	$0.222 + 0.038 \cdot \text{SL}$	$0.215 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.313	$0.239 + 0.037 \cdot \text{SL}$	$0.241 + 0.036 \cdot \text{SL}$	$0.243 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.182	$0.140 + 0.021 \cdot \text{SL}$	$0.145 + 0.020 \cdot \text{SL}$	$0.151 + 0.019 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO222/AO222D2/AO222D2B/AO222D4

Three 2-ANDs into 3-NOR with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.362	$0.280 + 0.041 \cdot \text{SL}$	$0.277 + 0.042 \cdot \text{SL}$	$0.266 + 0.042 \cdot \text{SL}$
	t_F	0.184	$0.150 + 0.017 \cdot \text{SL}$	$0.144 + 0.018 \cdot \text{SL}$	$0.127 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.166	$0.132 + 0.017 \cdot \text{SL}$	$0.129 + 0.018 \cdot \text{SL}$	$0.128 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.104	$0.082 + 0.011 \cdot \text{SL}$	$0.087 + 0.009 \cdot \text{SL}$	$0.088 + 0.009 \cdot \text{SL}$
B to Y	t_R	0.393	$0.311 + 0.041 \cdot \text{SL}$	$0.308 + 0.042 \cdot \text{SL}$	$0.298 + 0.042 \cdot \text{SL}$
	t_F	0.176	$0.142 + 0.017 \cdot \text{SL}$	$0.136 + 0.019 \cdot \text{SL}$	$0.123 + 0.020 \cdot \text{SL}$
	t_{PLH}	0.185	$0.150 + 0.017 \cdot \text{SL}$	$0.148 + 0.018 \cdot \text{SL}$	$0.147 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.097	$0.076 + 0.011 \cdot \text{SL}$	$0.079 + 0.010 \cdot \text{SL}$	$0.082 + 0.009 \cdot \text{SL}$
C to Y	t_R	0.376	$0.295 + 0.041 \cdot \text{SL}$	$0.291 + 0.042 \cdot \text{SL}$	$0.283 + 0.042 \cdot \text{SL}$
	t_F	0.217	$0.182 + 0.017 \cdot \text{SL}$	$0.176 + 0.019 \cdot \text{SL}$	$0.164 + 0.020 \cdot \text{SL}$
	t_{PLH}	0.217	$0.179 + 0.019 \cdot \text{SL}$	$0.180 + 0.018 \cdot \text{SL}$	$0.184 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.141	$0.122 + 0.010 \cdot \text{SL}$	$0.123 + 0.010 \cdot \text{SL}$	$0.124 + 0.009 \cdot \text{SL}$
D to Y	t_R	0.404	$0.323 + 0.041 \cdot \text{SL}$	$0.320 + 0.041 \cdot \text{SL}$	$0.313 + 0.042 \cdot \text{SL}$
	t_F	0.211	$0.174 + 0.018 \cdot \text{SL}$	$0.171 + 0.019 \cdot \text{SL}$	$0.162 + 0.020 \cdot \text{SL}$
	t_{PLH}	0.236	$0.199 + 0.018 \cdot \text{SL}$	$0.200 + 0.018 \cdot \text{SL}$	$0.202 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.135	$0.115 + 0.010 \cdot \text{SL}$	$0.117 + 0.010 \cdot \text{SL}$	$0.119 + 0.009 \cdot \text{SL}$
E to Y	t_R	0.375	$0.294 + 0.041 \cdot \text{SL}$	$0.290 + 0.042 \cdot \text{SL}$	$0.284 + 0.042 \cdot \text{SL}$
	t_F	0.271	$0.236 + 0.017 \cdot \text{SL}$	$0.232 + 0.018 \cdot \text{SL}$	$0.218 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.249	$0.212 + 0.019 \cdot \text{SL}$	$0.213 + 0.018 \cdot \text{SL}$	$0.217 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.164	$0.143 + 0.011 \cdot \text{SL}$	$0.145 + 0.010 \cdot \text{SL}$	$0.153 + 0.010 \cdot \text{SL}$
F to Y	t_R	0.403	$0.321 + 0.041 \cdot \text{SL}$	$0.318 + 0.042 \cdot \text{SL}$	$0.313 + 0.042 \cdot \text{SL}$
	t_F	0.264	$0.228 + 0.018 \cdot \text{SL}$	$0.224 + 0.019 \cdot \text{SL}$	$0.216 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.269	$0.233 + 0.018 \cdot \text{SL}$	$0.233 + 0.018 \cdot \text{SL}$	$0.236 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.158	$0.137 + 0.011 \cdot \text{SL}$	$0.139 + 0.010 \cdot \text{SL}$	$0.147 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO222/AO222D2/AO222D2B/AO222D4

Three 2-ANDs into 3-NOR with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.321	$0.305 + 0.008 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.318 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.235	$0.217 + 0.009 \cdot \text{SL}$	$0.224 + 0.007 \cdot \text{SL}$	$0.234 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.345	$0.328 + 0.008 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.342 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.229	$0.211 + 0.009 \cdot \text{SL}$	$0.218 + 0.007 \cdot \text{SL}$	$0.228 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.089	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.385	$0.368 + 0.008 \cdot \text{SL}$	$0.375 + 0.007 \cdot \text{SL}$	$0.381 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.285	$0.267 + 0.009 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.284 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.414	$0.398 + 0.008 \cdot \text{SL}$	$0.404 + 0.007 \cdot \text{SL}$	$0.411 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.279	$0.261 + 0.009 \cdot \text{SL}$	$0.269 + 0.007 \cdot \text{SL}$	$0.278 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.412	$0.396 + 0.008 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.409 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.311	$0.293 + 0.009 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.090	$0.065 + 0.013 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.440	$0.423 + 0.008 \cdot \text{SL}$	$0.430 + 0.007 \cdot \text{SL}$	$0.437 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.305	$0.287 + 0.009 \cdot \text{SL}$	$0.294 + 0.007 \cdot \text{SL}$	$0.305 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO222/AO222D2/AO222D2B/AO222D4

Three 2-ANDs into 3-NOR with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.083	$0.070 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.057 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.346	$0.336 + 0.005 \cdot \text{SL}$	$0.342 + 0.004 \cdot \text{SL}$	$0.354 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.253	$0.242 + 0.005 \cdot \text{SL}$	$0.248 + 0.004 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.086	$0.074 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.370	$0.360 + 0.005 \cdot \text{SL}$	$0.366 + 0.004 \cdot \text{SL}$	$0.378 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.247	$0.236 + 0.005 \cdot \text{SL}$	$0.242 + 0.004 \cdot \text{SL}$	$0.258 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.057 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.410	$0.400 + 0.005 \cdot \text{SL}$	$0.406 + 0.004 \cdot \text{SL}$	$0.418 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.303	$0.293 + 0.005 \cdot \text{SL}$	$0.298 + 0.004 \cdot \text{SL}$	$0.314 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.085	$0.071 + 0.007 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.056 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.440	$0.430 + 0.005 \cdot \text{SL}$	$0.435 + 0.004 \cdot \text{SL}$	$0.448 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.297	$0.287 + 0.005 \cdot \text{SL}$	$0.292 + 0.004 \cdot \text{SL}$	$0.308 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.083	$0.070 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.058 + 0.007 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.438	$0.428 + 0.005 \cdot \text{SL}$	$0.433 + 0.004 \cdot \text{SL}$	$0.445 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.330	$0.320 + 0.005 \cdot \text{SL}$	$0.326 + 0.004 \cdot \text{SL}$	$0.342 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.085	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.057 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.466	$0.456 + 0.005 \cdot \text{SL}$	$0.461 + 0.004 \cdot \text{SL}$	$0.473 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.314 + 0.005 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.336 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO222A/AO222D2A/AO222D4A

Inverting 2-of-3 Majority with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	x	0
1	x	1	0
x	1	1	0
0	0	x	1
0	x	0	1
x	0	0	1

Cell Data

Input Load (SL)									Gate Count		
AO222A			AO222D2A			AO222D4A			AO222A	AO222D2A	AO222D4A
A	B	C	A	B	C	A	B	C			
1.8	2.0	2.0	1.8	2.0	2.0	1.8	2.0	2.0	2.00	3.00	3.67

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.366	$0.259 + 0.053 \cdot \text{SL}$	$0.253 + 0.055 \cdot \text{SL}$	$0.242 + 0.056 \cdot \text{SL}$
	t_F	0.227	$0.150 + 0.038 \cdot \text{SL}$	$0.146 + 0.039 \cdot \text{SL}$	$0.137 + 0.040 \cdot \text{SL}$
	t_{PLH}	0.163	$0.115 + 0.024 \cdot \text{SL}$	$0.115 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.157	$0.117 + 0.020 \cdot \text{SL}$	$0.119 + 0.019 \cdot \text{SL}$	$0.120 + 0.019 \cdot \text{SL}$
B to Y	t_R	0.366	$0.259 + 0.053 \cdot \text{SL}$	$0.253 + 0.055 \cdot \text{SL}$	$0.244 + 0.056 \cdot \text{SL}$
	t_F	0.237	$0.162 + 0.038 \cdot \text{SL}$	$0.156 + 0.039 \cdot \text{SL}$	$0.147 + 0.040 \cdot \text{SL}$
	t_{PLH}	0.177	$0.129 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.174	$0.135 + 0.020 \cdot \text{SL}$	$0.136 + 0.019 \cdot \text{SL}$	$0.137 + 0.019 \cdot \text{SL}$
C to Y	t_R	0.340	$0.234 + 0.053 \cdot \text{SL}$	$0.228 + 0.055 \cdot \text{SL}$	$0.218 + 0.056 \cdot \text{SL}$
	t_F	0.240	$0.165 + 0.038 \cdot \text{SL}$	$0.160 + 0.039 \cdot \text{SL}$	$0.151 + 0.040 \cdot \text{SL}$
	t_{PLH}	0.169	$0.121 + 0.024 \cdot \text{SL}$	$0.120 + 0.024 \cdot \text{SL}$	$0.120 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.154	$0.115 + 0.020 \cdot \text{SL}$	$0.116 + 0.019 \cdot \text{SL}$	$0.117 + 0.019 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO222A/AO222D2A/AO222D4A

Inverting 2-of-3 Majority with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO222D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.287	$0.270 + 0.008 \cdot \text{SL}$	$0.276 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.269	$0.251 + 0.009 \cdot \text{SL}$	$0.259 + 0.007 \cdot \text{SL}$	$0.269 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.292	$0.276 + 0.008 \cdot \text{SL}$	$0.282 + 0.007 \cdot \text{SL}$	$0.288 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.286	$0.268 + 0.009 \cdot \text{SL}$	$0.276 + 0.007 \cdot \text{SL}$	$0.285 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.287	$0.271 + 0.008 \cdot \text{SL}$	$0.277 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.266	$0.248 + 0.009 \cdot \text{SL}$	$0.256 + 0.007 \cdot \text{SL}$	$0.266 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO222D4A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.081	$0.068 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.310	$0.300 + 0.005 \cdot \text{SL}$	$0.306 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.289	$0.278 + 0.005 \cdot \text{SL}$	$0.284 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.082	$0.069 + 0.007 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.057 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.316	$0.306 + 0.005 \cdot \text{SL}$	$0.311 + 0.004 \cdot \text{SL}$	$0.322 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.307	$0.297 + 0.005 \cdot \text{SL}$	$0.302 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.311	$0.301 + 0.005 \cdot \text{SL}$	$0.307 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.282 + 0.004 \cdot \text{SL}$	$0.298 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO2222/AO2222D2/AO2222D4

Four 2-ANDs into 4-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	0
x	x	1	1	x	x	x	x	0
x	x	x	x	1	1	x	x	0
x	x	x	x	x	x	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
AO2222								AO2222
A	B	C	D	E	F	G	H	3.00
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	
AO2222D2								AO2222D2
A	B	C	D	E	F	G	H	4.00
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	
AO2222D4								AO2222D4
A	B	C	D	E	F	G	H	4.67
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO2222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.626	$0.399 + 0.113 \cdot \text{SL}$	$0.395 + 0.114 \cdot \text{SL}$	$0.394 + 0.115 \cdot \text{SL}$
	t_F	0.245	$0.172 + 0.037 \cdot \text{SL}$	$0.163 + 0.039 \cdot \text{SL}$	$0.148 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.223	$0.130 + 0.046 \cdot \text{SL}$	$0.122 + 0.048 \cdot \text{SL}$	$0.122 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.133	$0.093 + 0.020 \cdot \text{SL}$	$0.095 + 0.020 \cdot \text{SL}$	$0.095 + 0.020 \cdot \text{SL}$
B to Y	t_R	0.668	$0.442 + 0.113 \cdot \text{SL}$	$0.437 + 0.114 \cdot \text{SL}$	$0.435 + 0.114 \cdot \text{SL}$
	t_F	0.238	$0.163 + 0.038 \cdot \text{SL}$	$0.155 + 0.040 \cdot \text{SL}$	$0.146 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.246	$0.153 + 0.047 \cdot \text{SL}$	$0.147 + 0.048 \cdot \text{SL}$	$0.147 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.127	$0.086 + 0.020 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$	$0.090 + 0.020 \cdot \text{SL}$
C to Y	t_R	0.674	$0.453 + 0.111 \cdot \text{SL}$	$0.448 + 0.112 \cdot \text{SL}$	$0.444 + 0.112 \cdot \text{SL}$
	t_F	0.292	$0.216 + 0.038 \cdot \text{SL}$	$0.210 + 0.040 \cdot \text{SL}$	$0.198 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.330	$0.230 + 0.050 \cdot \text{SL}$	$0.234 + 0.049 \cdot \text{SL}$	$0.239 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.180	$0.140 + 0.020 \cdot \text{SL}$	$0.141 + 0.020 \cdot \text{SL}$	$0.143 + 0.020 \cdot \text{SL}$
D to Y	t_R	0.714	$0.492 + 0.111 \cdot \text{SL}$	$0.488 + 0.112 \cdot \text{SL}$	$0.485 + 0.112 \cdot \text{SL}$
	t_F	0.289	$0.212 + 0.039 \cdot \text{SL}$	$0.206 + 0.040 \cdot \text{SL}$	$0.198 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.356	$0.257 + 0.049 \cdot \text{SL}$	$0.259 + 0.049 \cdot \text{SL}$	$0.263 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.174	$0.133 + 0.020 \cdot \text{SL}$	$0.135 + 0.020 \cdot \text{SL}$	$0.137 + 0.020 \cdot \text{SL}$
E to Y	t_R	0.719	$0.499 + 0.110 \cdot \text{SL}$	$0.494 + 0.111 \cdot \text{SL}$	$0.487 + 0.112 \cdot \text{SL}$
	t_F	0.350	$0.274 + 0.038 \cdot \text{SL}$	$0.268 + 0.040 \cdot \text{SL}$	$0.257 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.426	$0.327 + 0.050 \cdot \text{SL}$	$0.330 + 0.049 \cdot \text{SL}$	$0.335 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.205	$0.162 + 0.021 \cdot \text{SL}$	$0.165 + 0.021 \cdot \text{SL}$	$0.171 + 0.020 \cdot \text{SL}$
F to Y	t_R	0.753	$0.533 + 0.110 \cdot \text{SL}$	$0.529 + 0.111 \cdot \text{SL}$	$0.524 + 0.111 \cdot \text{SL}$
	t_F	0.347	$0.269 + 0.039 \cdot \text{SL}$	$0.265 + 0.040 \cdot \text{SL}$	$0.257 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.450	$0.352 + 0.049 \cdot \text{SL}$	$0.354 + 0.048 \cdot \text{SL}$	$0.357 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.199	$0.156 + 0.021 \cdot \text{SL}$	$0.160 + 0.021 \cdot \text{SL}$	$0.165 + 0.020 \cdot \text{SL}$
G to Y	t_R	0.718	$0.498 + 0.110 \cdot \text{SL}$	$0.493 + 0.111 \cdot \text{SL}$	$0.487 + 0.112 \cdot \text{SL}$
	t_F	0.402	$0.324 + 0.039 \cdot \text{SL}$	$0.321 + 0.040 \cdot \text{SL}$	$0.311 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.456	$0.356 + 0.050 \cdot \text{SL}$	$0.360 + 0.049 \cdot \text{SL}$	$0.365 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.217	$0.171 + 0.023 \cdot \text{SL}$	$0.176 + 0.021 \cdot \text{SL}$	$0.186 + 0.020 \cdot \text{SL}$
H to Y	t_R	0.752	$0.533 + 0.110 \cdot \text{SL}$	$0.529 + 0.111 \cdot \text{SL}$	$0.523 + 0.111 \cdot \text{SL}$
	t_F	0.398	$0.319 + 0.040 \cdot \text{SL}$	$0.316 + 0.040 \cdot \text{SL}$	$0.312 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.480	$0.382 + 0.049 \cdot \text{SL}$	$0.384 + 0.048 \cdot \text{SL}$	$0.388 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.211	$0.165 + 0.023 \cdot \text{SL}$	$0.170 + 0.022 \cdot \text{SL}$	$0.180 + 0.020 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO2222/AO2222D2/AO2222D4

Four 2-ANDs into 4-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO2222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.095	$0.072 + 0.012 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.353	$0.336 + 0.009 \cdot \text{SL}$	$0.343 + 0.007 \cdot \text{SL}$	$0.351 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.250	$0.232 + 0.009 \cdot \text{SL}$	$0.240 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.098	$0.073 + 0.013 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.011 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.383	$0.365 + 0.009 \cdot \text{SL}$	$0.373 + 0.007 \cdot \text{SL}$	$0.381 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.244	$0.226 + 0.009 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.096	$0.070 + 0.013 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.460	$0.443 + 0.009 \cdot \text{SL}$	$0.450 + 0.007 \cdot \text{SL}$	$0.458 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.303	$0.285 + 0.009 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.099	$0.075 + 0.012 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.048 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.492	$0.474 + 0.009 \cdot \text{SL}$	$0.482 + 0.007 \cdot \text{SL}$	$0.490 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.297	$0.279 + 0.009 \cdot \text{SL}$	$0.287 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.099	$0.074 + 0.012 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.560	$0.543 + 0.009 \cdot \text{SL}$	$0.550 + 0.007 \cdot \text{SL}$	$0.559 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.334	$0.316 + 0.009 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.334 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.101	$0.075 + 0.013 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.589	$0.571 + 0.009 \cdot \text{SL}$	$0.579 + 0.007 \cdot \text{SL}$	$0.588 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.328	$0.310 + 0.009 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$	$0.328 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.099	$0.075 + 0.012 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.590	$0.572 + 0.009 \cdot \text{SL}$	$0.580 + 0.007 \cdot \text{SL}$	$0.589 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.352	$0.334 + 0.009 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$	$0.352 + 0.006 \cdot \text{SL}$
H to Y	t_R	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.075 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.620	$0.602 + 0.009 \cdot \text{SL}$	$0.610 + 0.007 \cdot \text{SL}$	$0.620 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.346	$0.328 + 0.009 \cdot \text{SL}$	$0.336 + 0.007 \cdot \text{SL}$	$0.347 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO2222D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	$0.082 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.388	$0.377 + 0.005 \cdot \text{SL}$	$0.383 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.270	$0.259 + 0.005 \cdot \text{SL}$	$0.265 + 0.004 \cdot \text{SL}$	$0.281 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.082 + 0.006 \cdot \text{SL}$	$0.069 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.057 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.417	$0.407 + 0.005 \cdot \text{SL}$	$0.413 + 0.004 \cdot \text{SL}$	$0.427 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.263	$0.253 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.060 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.496	$0.486 + 0.005 \cdot \text{SL}$	$0.492 + 0.004 \cdot \text{SL}$	$0.506 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.323	$0.313 + 0.005 \cdot \text{SL}$	$0.318 + 0.004 \cdot \text{SL}$	$0.334 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.097	$0.084 + 0.006 \cdot \text{SL}$	$0.084 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.060 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.528	$0.517 + 0.005 \cdot \text{SL}$	$0.524 + 0.004 \cdot \text{SL}$	$0.538 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.317	$0.306 + 0.005 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.328 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.097	$0.086 + 0.006 \cdot \text{SL}$	$0.084 + 0.006 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.060 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.596	$0.586 + 0.005 \cdot \text{SL}$	$0.592 + 0.004 \cdot \text{SL}$	$0.607 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.355	$0.344 + 0.005 \cdot \text{SL}$	$0.350 + 0.004 \cdot \text{SL}$	$0.366 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.099	$0.087 + 0.006 \cdot \text{SL}$	$0.086 + 0.006 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.625	$0.614 + 0.005 \cdot \text{SL}$	$0.621 + 0.004 \cdot \text{SL}$	$0.636 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.349	$0.338 + 0.005 \cdot \text{SL}$	$0.344 + 0.004 \cdot \text{SL}$	$0.360 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.096	$0.084 + 0.006 \cdot \text{SL}$	$0.084 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.063 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.625	$0.614 + 0.005 \cdot \text{SL}$	$0.621 + 0.004 \cdot \text{SL}$	$0.635 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.374	$0.363 + 0.005 \cdot \text{SL}$	$0.369 + 0.004 \cdot \text{SL}$	$0.386 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.099	$0.087 + 0.006 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.064 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.657	$0.646 + 0.005 \cdot \text{SL}$	$0.653 + 0.004 \cdot \text{SL}$	$0.668 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.369	$0.358 + 0.005 \cdot \text{SL}$	$0.364 + 0.004 \cdot \text{SL}$	$0.381 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO31DH/AO31/AO31D2/AO31D4

3-AND into 2-NOR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	1	x	0
x	x	x	1	0
Other States				1

Cell Data

Input Load (SL)															
AO31DH				AO31				AO31D2				AO31D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	2.0	2.1	2.2	2.0	1.0	1.0	1.1	1.1
Gate Count															
AO31DH				AO31				AO31D2				AO31D4			
1.67				1.67				2.67				3.00			

AO31DH/AO31/AO31D2/AO31D4

3-AND into 2-NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO31DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.401	$0.165 + 0.118 \cdot \text{SL}$	$0.149 + 0.122 \cdot \text{SL}$	$0.145 + 0.122 \cdot \text{SL}$
	t_F	0.322	$0.134 + 0.094 \cdot \text{SL}$	$0.119 + 0.098 \cdot \text{SL}$	$0.109 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.198	$0.093 + 0.052 \cdot \text{SL}$	$0.092 + 0.052 \cdot \text{SL}$	$0.092 + 0.052 \cdot \text{SL}$
	t_{PHL}	0.178	$0.087 + 0.045 \cdot \text{SL}$	$0.086 + 0.046 \cdot \text{SL}$	$0.085 + 0.046 \cdot \text{SL}$
B to Y	t_R	0.430	$0.193 + 0.119 \cdot \text{SL}$	$0.177 + 0.123 \cdot \text{SL}$	$0.173 + 0.123 \cdot \text{SL}$
	t_F	0.320	$0.130 + 0.095 \cdot \text{SL}$	$0.118 + 0.098 \cdot \text{SL}$	$0.110 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.216	$0.111 + 0.052 \cdot \text{SL}$	$0.110 + 0.053 \cdot \text{SL}$	$0.109 + 0.053 \cdot \text{SL}$
	t_{PHL}	0.181	$0.089 + 0.046 \cdot \text{SL}$	$0.090 + 0.046 \cdot \text{SL}$	$0.090 + 0.046 \cdot \text{SL}$
C to Y	t_R	0.459	$0.222 + 0.118 \cdot \text{SL}$	$0.205 + 0.123 \cdot \text{SL}$	$0.201 + 0.123 \cdot \text{SL}$
	t_F	0.316	$0.124 + 0.096 \cdot \text{SL}$	$0.116 + 0.098 \cdot \text{SL}$	$0.109 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.231	$0.125 + 0.053 \cdot \text{SL}$	$0.125 + 0.053 \cdot \text{SL}$	$0.125 + 0.053 \cdot \text{SL}$
	t_{PHL}	0.179	$0.087 + 0.046 \cdot \text{SL}$	$0.088 + 0.046 \cdot \text{SL}$	$0.089 + 0.046 \cdot \text{SL}$
D to Y	t_R	0.455	$0.214 + 0.120 \cdot \text{SL}$	$0.206 + 0.123 \cdot \text{SL}$	$0.201 + 0.123 \cdot \text{SL}$
	t_F	0.209	$0.123 + 0.043 \cdot \text{SL}$	$0.113 + 0.046 \cdot \text{SL}$	$0.096 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.252	$0.145 + 0.053 \cdot \text{SL}$	$0.147 + 0.053 \cdot \text{SL}$	$0.148 + 0.053 \cdot \text{SL}$
	t_{PHL}	0.150	$0.100 + 0.025 \cdot \text{SL}$	$0.100 + 0.025 \cdot \text{SL}$	$0.101 + 0.025 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO31

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.261	$0.155 + 0.053 \cdot \text{SL}$	$0.145 + 0.056 \cdot \text{SL}$	$0.131 + 0.057 \cdot \text{SL}$
	t_F	0.215	$0.128 + 0.044 \cdot \text{SL}$	$0.119 + 0.046 \cdot \text{SL}$	$0.105 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.135	$0.086 + 0.024 \cdot \text{SL}$	$0.086 + 0.024 \cdot \text{SL}$	$0.085 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.125	$0.080 + 0.022 \cdot \text{SL}$	$0.082 + 0.022 \cdot \text{SL}$	$0.081 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.289	$0.181 + 0.054 \cdot \text{SL}$	$0.172 + 0.056 \cdot \text{SL}$	$0.158 + 0.058 \cdot \text{SL}$
	t_F	0.211	$0.123 + 0.044 \cdot \text{SL}$	$0.115 + 0.046 \cdot \text{SL}$	$0.106 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.152	$0.104 + 0.024 \cdot \text{SL}$	$0.103 + 0.025 \cdot \text{SL}$	$0.102 + 0.025 \cdot \text{SL}$
	t_{PHL}	0.127	$0.081 + 0.023 \cdot \text{SL}$	$0.084 + 0.022 \cdot \text{SL}$	$0.084 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.317	$0.211 + 0.053 \cdot \text{SL}$	$0.200 + 0.056 \cdot \text{SL}$	$0.185 + 0.058 \cdot \text{SL}$
	t_F	0.207	$0.117 + 0.045 \cdot \text{SL}$	$0.111 + 0.047 \cdot \text{SL}$	$0.104 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.166	$0.117 + 0.025 \cdot \text{SL}$	$0.117 + 0.025 \cdot \text{SL}$	$0.116 + 0.025 \cdot \text{SL}$
	t_{PHL}	0.124	$0.079 + 0.023 \cdot \text{SL}$	$0.082 + 0.022 \cdot \text{SL}$	$0.082 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.309	$0.197 + 0.056 \cdot \text{SL}$	$0.193 + 0.057 \cdot \text{SL}$	$0.186 + 0.058 \cdot \text{SL}$
	t_F	0.161	$0.122 + 0.020 \cdot \text{SL}$	$0.117 + 0.021 \cdot \text{SL}$	$0.106 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.185	$0.134 + 0.025 \cdot \text{SL}$	$0.136 + 0.025 \cdot \text{SL}$	$0.137 + 0.025 \cdot \text{SL}$
	t_{PHL}	0.120	$0.095 + 0.012 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO31DH/AO31/AO31D2/AO31D4

3-AND into 2-NOR with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO31D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.201	$0.148 + 0.027 \cdot \text{SL}$	$0.143 + 0.028 \cdot \text{SL}$	$0.126 + 0.029 \cdot \text{SL}$
	t_F	0.165	$0.123 + 0.021 \cdot \text{SL}$	$0.118 + 0.023 \cdot \text{SL}$	$0.101 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.106	$0.080 + 0.013 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.097	$0.073 + 0.012 \cdot \text{SL}$	$0.078 + 0.011 \cdot \text{SL}$	$0.077 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.227	$0.175 + 0.026 \cdot \text{SL}$	$0.168 + 0.028 \cdot \text{SL}$	$0.151 + 0.029 \cdot \text{SL}$
	t_F	0.161	$0.119 + 0.021 \cdot \text{SL}$	$0.113 + 0.023 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.123	$0.098 + 0.012 \cdot \text{SL}$	$0.098 + 0.012 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.099	$0.074 + 0.012 \cdot \text{SL}$	$0.079 + 0.011 \cdot \text{SL}$	$0.079 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.255	$0.204 + 0.026 \cdot \text{SL}$	$0.197 + 0.027 \cdot \text{SL}$	$0.178 + 0.029 \cdot \text{SL}$
	t_F	0.156	$0.113 + 0.021 \cdot \text{SL}$	$0.106 + 0.023 \cdot \text{SL}$	$0.098 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.136	$0.112 + 0.012 \cdot \text{SL}$	$0.112 + 0.012 \cdot \text{SL}$	$0.111 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.097	$0.073 + 0.012 \cdot \text{SL}$	$0.077 + 0.011 \cdot \text{SL}$	$0.078 + 0.011 \cdot \text{SL}$
D to Y	t_R	0.244	$0.189 + 0.027 \cdot \text{SL}$	$0.187 + 0.028 \cdot \text{SL}$	$0.177 + 0.029 \cdot \text{SL}$
	t_F	0.154	$0.135 + 0.010 \cdot \text{SL}$	$0.133 + 0.010 \cdot \text{SL}$	$0.117 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.159	$0.134 + 0.013 \cdot \text{SL}$	$0.135 + 0.012 \cdot \text{SL}$	$0.136 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.109	$0.095 + 0.007 \cdot \text{SL}$	$0.097 + 0.006 \cdot \text{SL}$	$0.098 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO31D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.060 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.054 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.264	$0.254 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.270 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.249	$0.239 + 0.005 \cdot \text{SL}$	$0.244 + 0.004 \cdot \text{SL}$	$0.260 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.076	$0.063 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.282 + 0.004 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.251	$0.240 + 0.005 \cdot \text{SL}$	$0.246 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.077	$0.063 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.054 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.303	$0.294 + 0.005 \cdot \text{SL}$	$0.299 + 0.004 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.249	$0.238 + 0.005 \cdot \text{SL}$	$0.244 + 0.004 \cdot \text{SL}$	$0.259 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.077	$0.063 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.323	$0.314 + 0.005 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.330 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.242	$0.232 + 0.005 \cdot \text{SL}$	$0.237 + 0.004 \cdot \text{SL}$	$0.252 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO311/AO311D2/AO311D4

3-AND into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	1	x	x	0
x	x	x	1	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)														
AO311					AO311D2					AO311D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
1.0	1.0	1.0	0.9	0.9	1.0	1.0	1.0	0.9	1.0	1.0	1.0	1.0	0.9	1.0
Gate Count														
AO311					AO311D2					AO311D4				
2.00					3.00					3.33				

AO311/AO311D2/AO311D4

3-AND into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO311

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.406	$0.245 + 0.081 \cdot \text{SL}$	$0.235 + 0.083 \cdot \text{SL}$	$0.227 + 0.084 \cdot \text{SL}$
	t_F	0.241	$0.142 + 0.050 \cdot \text{SL}$	$0.132 + 0.052 \cdot \text{SL}$	$0.121 + 0.053 \cdot \text{SL}$
	t_{PLH}	0.170	$0.100 + 0.035 \cdot \text{SL}$	$0.096 + 0.036 \cdot \text{SL}$	$0.096 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.144	$0.095 + 0.025 \cdot \text{SL}$	$0.094 + 0.025 \cdot \text{SL}$	$0.094 + 0.025 \cdot \text{SL}$
B to Y	t_R	0.440	$0.278 + 0.081 \cdot \text{SL}$	$0.268 + 0.084 \cdot \text{SL}$	$0.260 + 0.084 \cdot \text{SL}$
	t_F	0.239	$0.138 + 0.051 \cdot \text{SL}$	$0.131 + 0.053 \cdot \text{SL}$	$0.122 + 0.053 \cdot \text{SL}$
	t_{PLH}	0.190	$0.120 + 0.035 \cdot \text{SL}$	$0.117 + 0.036 \cdot \text{SL}$	$0.117 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.145	$0.095 + 0.025 \cdot \text{SL}$	$0.096 + 0.025 \cdot \text{SL}$	$0.096 + 0.025 \cdot \text{SL}$
C to Y	t_R	0.473	$0.314 + 0.080 \cdot \text{SL}$	$0.302 + 0.083 \cdot \text{SL}$	$0.293 + 0.084 \cdot \text{SL}$
	t_F	0.235	$0.132 + 0.051 \cdot \text{SL}$	$0.127 + 0.053 \cdot \text{SL}$	$0.121 + 0.053 \cdot \text{SL}$
	t_{PLH}	0.207	$0.136 + 0.035 \cdot \text{SL}$	$0.135 + 0.036 \cdot \text{SL}$	$0.134 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.142	$0.092 + 0.025 \cdot \text{SL}$	$0.093 + 0.025 \cdot \text{SL}$	$0.094 + 0.025 \cdot \text{SL}$
D to Y	t_R	0.480	$0.318 + 0.081 \cdot \text{SL}$	$0.312 + 0.083 \cdot \text{SL}$	$0.305 + 0.083 \cdot \text{SL}$
	t_F	0.207	$0.148 + 0.030 \cdot \text{SL}$	$0.144 + 0.031 \cdot \text{SL}$	$0.134 + 0.032 \cdot \text{SL}$
	t_{PLH}	0.264	$0.191 + 0.037 \cdot \text{SL}$	$0.193 + 0.036 \cdot \text{SL}$	$0.195 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.161	$0.127 + 0.017 \cdot \text{SL}$	$0.128 + 0.017 \cdot \text{SL}$	$0.129 + 0.017 \cdot \text{SL}$
E to Y	t_R	0.478	$0.316 + 0.081 \cdot \text{SL}$	$0.310 + 0.083 \cdot \text{SL}$	$0.305 + 0.083 \cdot \text{SL}$
	t_F	0.233	$0.174 + 0.030 \cdot \text{SL}$	$0.171 + 0.031 \cdot \text{SL}$	$0.159 + 0.032 \cdot \text{SL}$
	t_{PLH}	0.270	$0.197 + 0.037 \cdot \text{SL}$	$0.199 + 0.036 \cdot \text{SL}$	$0.201 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.171	$0.136 + 0.017 \cdot \text{SL}$	$0.138 + 0.017 \cdot \text{SL}$	$0.140 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO311D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.284	$0.268 + 0.008 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.281 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.250	$0.232 + 0.009 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$	$0.249 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.086	$0.061 + 0.012 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.048 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.310	$0.294 + 0.008 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.251	$0.233 + 0.009 \cdot \text{SL}$	$0.241 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.088	$0.064 + 0.012 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.331	$0.315 + 0.008 \cdot \text{SL}$	$0.321 + 0.007 \cdot \text{SL}$	$0.328 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.248	$0.230 + 0.009 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.248 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.049 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.386	$0.370 + 0.008 \cdot \text{SL}$	$0.376 + 0.007 \cdot \text{SL}$	$0.383 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.270	$0.252 + 0.009 \cdot \text{SL}$	$0.259 + 0.007 \cdot \text{SL}$	$0.269 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.089	$0.064 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.394	$0.377 + 0.008 \cdot \text{SL}$	$0.384 + 0.007 \cdot \text{SL}$	$0.391 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.279	$0.261 + 0.009 \cdot \text{SL}$	$0.268 + 0.007 \cdot \text{SL}$	$0.278 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO311/AO311D2/AO311D4

3-AND into 3-NOR with 1X/2X/4X Drive

Switching Characteristics


(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO311D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.069 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.313	$0.303 + 0.005 \cdot \text{SL}$	$0.308 + 0.004 \cdot \text{SL}$	$0.320 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.272	$0.261 + 0.005 \cdot \text{SL}$	$0.267 + 0.004 \cdot \text{SL}$	$0.283 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.084	$0.071 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.340	$0.330 + 0.005 \cdot \text{SL}$	$0.335 + 0.004 \cdot \text{SL}$	$0.348 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.274	$0.263 + 0.005 \cdot \text{SL}$	$0.269 + 0.004 \cdot \text{SL}$	$0.285 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.085	$0.072 + 0.007 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.361	$0.351 + 0.005 \cdot \text{SL}$	$0.357 + 0.004 \cdot \text{SL}$	$0.369 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.271	$0.261 + 0.005 \cdot \text{SL}$	$0.267 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.417	$0.407 + 0.005 \cdot \text{SL}$	$0.413 + 0.004 \cdot \text{SL}$	$0.425 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.287	$0.276 + 0.005 \cdot \text{SL}$	$0.282 + 0.004 \cdot \text{SL}$	$0.297 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.085	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.425	$0.415 + 0.005 \cdot \text{SL}$	$0.421 + 0.004 \cdot \text{SL}$	$0.433 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.302	$0.291 + 0.005 \cdot \text{SL}$	$0.297 + 0.004 \cdot \text{SL}$	$0.312 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	x	x	0
x	x	x	x	1	x	0
x	x	x	x	x	1	0
Other States						1

Cell Data

Input Load (SL)												Gate Count	
AO3111						AO3111D2						AO3111	AO3111D2
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	1.0	0.8	0.9	0.9	1.0	1.0	1.0	0.8	0.9	0.9	2.33	3.00

AO3111/AO3111D2

3-AND into 4-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO3111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.551	$0.335 + 0.108 \cdot \text{SL}$	$0.326 + 0.111 \cdot \text{SL}$	$0.324 + 0.111 \cdot \text{SL}$
	t_F	0.259	$0.148 + 0.055 \cdot \text{SL}$	$0.141 + 0.057 \cdot \text{SL}$	$0.129 + 0.058 \cdot \text{SL}$
	t_{PLH}	0.193	$0.103 + 0.045 \cdot \text{SL}$	$0.094 + 0.047 \cdot \text{SL}$	$0.095 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.155	$0.101 + 0.027 \cdot \text{SL}$	$0.101 + 0.027 \cdot \text{SL}$	$0.100 + 0.027 \cdot \text{SL}$
B to Y	t_R	0.595	$0.377 + 0.109 \cdot \text{SL}$	$0.368 + 0.111 \cdot \text{SL}$	$0.366 + 0.111 \cdot \text{SL}$
	t_F	0.257	$0.146 + 0.056 \cdot \text{SL}$	$0.138 + 0.058 \cdot \text{SL}$	$0.131 + 0.058 \cdot \text{SL}$
	t_{PLH}	0.217	$0.125 + 0.046 \cdot \text{SL}$	$0.121 + 0.047 \cdot \text{SL}$	$0.121 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.157	$0.103 + 0.027 \cdot \text{SL}$	$0.103 + 0.027 \cdot \text{SL}$	$0.103 + 0.027 \cdot \text{SL}$
C to Y	t_R	0.637	$0.422 + 0.108 \cdot \text{SL}$	$0.410 + 0.111 \cdot \text{SL}$	$0.408 + 0.111 \cdot \text{SL}$
	t_F	0.254	$0.141 + 0.056 \cdot \text{SL}$	$0.136 + 0.058 \cdot \text{SL}$	$0.130 + 0.058 \cdot \text{SL}$
	t_{PLH}	0.239	$0.146 + 0.047 \cdot \text{SL}$	$0.144 + 0.047 \cdot \text{SL}$	$0.144 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.155	$0.100 + 0.027 \cdot \text{SL}$	$0.101 + 0.027 \cdot \text{SL}$	$0.102 + 0.027 \cdot \text{SL}$
D to Y	t_R	0.663	$0.447 + 0.108 \cdot \text{SL}$	$0.442 + 0.109 \cdot \text{SL}$	$0.436 + 0.110 \cdot \text{SL}$
	t_F	0.244	$0.170 + 0.037 \cdot \text{SL}$	$0.166 + 0.038 \cdot \text{SL}$	$0.157 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.331	$0.234 + 0.048 \cdot \text{SL}$	$0.237 + 0.048 \cdot \text{SL}$	$0.240 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.191	$0.149 + 0.021 \cdot \text{SL}$	$0.150 + 0.020 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$
E to Y	t_R	0.664	$0.449 + 0.107 \cdot \text{SL}$	$0.442 + 0.109 \cdot \text{SL}$	$0.436 + 0.110 \cdot \text{SL}$
	t_F	0.274	$0.200 + 0.037 \cdot \text{SL}$	$0.196 + 0.038 \cdot \text{SL}$	$0.187 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.358	$0.262 + 0.048 \cdot \text{SL}$	$0.264 + 0.048 \cdot \text{SL}$	$0.268 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.206	$0.163 + 0.021 \cdot \text{SL}$	$0.165 + 0.021 \cdot \text{SL}$	$0.168 + 0.020 \cdot \text{SL}$
F to Y	t_R	0.663	$0.448 + 0.108 \cdot \text{SL}$	$0.442 + 0.109 \cdot \text{SL}$	$0.436 + 0.110 \cdot \text{SL}$
	t_F	0.308	$0.234 + 0.037 \cdot \text{SL}$	$0.230 + 0.038 \cdot \text{SL}$	$0.220 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.369	$0.272 + 0.048 \cdot \text{SL}$	$0.275 + 0.048 \cdot \text{SL}$	$0.278 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.216	$0.172 + 0.022 \cdot \text{SL}$	$0.175 + 0.021 \cdot \text{SL}$	$0.180 + 0.021 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO3111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	$0.067 + 0.012 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.008 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.261	$0.243 + 0.009 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.094	$0.071 + 0.012 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.342	$0.325 + 0.009 \cdot \text{SL}$	$0.332 + 0.007 \cdot \text{SL}$	$0.340 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.263	$0.245 + 0.009 \cdot \text{SL}$	$0.252 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.096	$0.071 + 0.013 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.369	$0.352 + 0.009 \cdot \text{SL}$	$0.359 + 0.007 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.260	$0.242 + 0.009 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.096	$0.071 + 0.013 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.459	$0.441 + 0.009 \cdot \text{SL}$	$0.449 + 0.007 \cdot \text{SL}$	$0.457 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.302	$0.284 + 0.009 \cdot \text{SL}$	$0.292 + 0.007 \cdot \text{SL}$	$0.301 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.097	$0.072 + 0.013 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.487	$0.469 + 0.009 \cdot \text{SL}$	$0.477 + 0.007 \cdot \text{SL}$	$0.485 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.321	$0.303 + 0.009 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.321 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.097	$0.072 + 0.012 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.013 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.498	$0.480 + 0.009 \cdot \text{SL}$	$0.488 + 0.007 \cdot \text{SL}$	$0.496 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.335	$0.317 + 0.009 \cdot \text{SL}$	$0.324 + 0.007 \cdot \text{SL}$	$0.334 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

AO32/AO32D2/AO32D4

3-AND and 2-AND into 2-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	1	x	x	0
x	x	x	1	1	0
Other States					1

Cell Data

Input Load (SL)														
AO32					AO32D2					AO32D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.9	1.0	1.0	0.9	1.0	1.0	1.0	1.0	0.9	1.0	1.0	1.0	1.0	0.9	1.0
Gate Count														
AO32					AO32D2					AO32D4				
2.00					3.00					3.67				

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO32

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.335	$0.199 + 0.068 \cdot \text{SL}$	$0.192 + 0.070 \cdot \text{SL}$	$0.181 + 0.071 \cdot \text{SL}$
	t_F	0.242	$0.156 + 0.043 \cdot \text{SL}$	$0.146 + 0.046 \cdot \text{SL}$	$0.131 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.173	$0.113 + 0.030 \cdot \text{SL}$	$0.112 + 0.030 \cdot \text{SL}$	$0.112 + 0.030 \cdot \text{SL}$
	t_{PHL}	0.127	$0.083 + 0.022 \cdot \text{SL}$	$0.085 + 0.022 \cdot \text{SL}$	$0.084 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.366	$0.231 + 0.068 \cdot \text{SL}$	$0.223 + 0.070 \cdot \text{SL}$	$0.213 + 0.071 \cdot \text{SL}$
	t_F	0.238	$0.150 + 0.044 \cdot \text{SL}$	$0.140 + 0.046 \cdot \text{SL}$	$0.132 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.193	$0.133 + 0.030 \cdot \text{SL}$	$0.132 + 0.030 \cdot \text{SL}$	$0.132 + 0.030 \cdot \text{SL}$
	t_{PHL}	0.130	$0.084 + 0.023 \cdot \text{SL}$	$0.087 + 0.022 \cdot \text{SL}$	$0.088 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.399	$0.264 + 0.068 \cdot \text{SL}$	$0.256 + 0.070 \cdot \text{SL}$	$0.245 + 0.071 \cdot \text{SL}$
	t_F	0.233	$0.144 + 0.045 \cdot \text{SL}$	$0.137 + 0.047 \cdot \text{SL}$	$0.130 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.210	$0.150 + 0.030 \cdot \text{SL}$	$0.150 + 0.030 \cdot \text{SL}$	$0.150 + 0.030 \cdot \text{SL}$
	t_{PHL}	0.127	$0.082 + 0.023 \cdot \text{SL}$	$0.085 + 0.022 \cdot \text{SL}$	$0.086 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.367	$0.230 + 0.069 \cdot \text{SL}$	$0.225 + 0.070 \cdot \text{SL}$	$0.219 + 0.071 \cdot \text{SL}$
	t_F	0.215	$0.155 + 0.030 \cdot \text{SL}$	$0.148 + 0.032 \cdot \text{SL}$	$0.137 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.227	$0.164 + 0.031 \cdot \text{SL}$	$0.166 + 0.031 \cdot \text{SL}$	$0.169 + 0.030 \cdot \text{SL}$
	t_{PHL}	0.142	$0.109 + 0.016 \cdot \text{SL}$	$0.110 + 0.016 \cdot \text{SL}$	$0.111 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.398	$0.260 + 0.069 \cdot \text{SL}$	$0.255 + 0.070 \cdot \text{SL}$	$0.250 + 0.071 \cdot \text{SL}$
	t_F	0.208	$0.146 + 0.031 \cdot \text{SL}$	$0.142 + 0.032 \cdot \text{SL}$	$0.134 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.247	$0.185 + 0.031 \cdot \text{SL}$	$0.187 + 0.031 \cdot \text{SL}$	$0.188 + 0.030 \cdot \text{SL}$
	t_{PHL}	0.136	$0.102 + 0.017 \cdot \text{SL}$	$0.104 + 0.016 \cdot \text{SL}$	$0.105 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO32/AO32D2/AO32D4

3-AND and 2-AND into 2-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO32D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.284	$0.267 + 0.008 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.237	$0.219 + 0.009 \cdot \text{SL}$	$0.226 + 0.007 \cdot \text{SL}$	$0.236 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.309	$0.293 + 0.008 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$	$0.305 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.239	$0.221 + 0.009 \cdot \text{SL}$	$0.228 + 0.007 \cdot \text{SL}$	$0.238 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.331	$0.314 + 0.008 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.237	$0.219 + 0.009 \cdot \text{SL}$	$0.226 + 0.007 \cdot \text{SL}$	$0.236 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.340	$0.324 + 0.008 \cdot \text{SL}$	$0.330 + 0.007 \cdot \text{SL}$	$0.336 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.253	$0.235 + 0.009 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$	$0.253 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.366	$0.349 + 0.008 \cdot \text{SL}$	$0.355 + 0.007 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.247	$0.229 + 0.009 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.246 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO32D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.065 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.057 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.308	$0.298 + 0.005 \cdot \text{SL}$	$0.303 + 0.004 \cdot \text{SL}$	$0.314 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.246 + 0.005 \cdot \text{SL}$	$0.252 + 0.004 \cdot \text{SL}$	$0.268 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.333	$0.323 + 0.005 \cdot \text{SL}$	$0.328 + 0.004 \cdot \text{SL}$	$0.340 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.259	$0.248 + 0.005 \cdot \text{SL}$	$0.254 + 0.004 \cdot \text{SL}$	$0.270 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.080	$0.067 + 0.007 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.355	$0.345 + 0.005 \cdot \text{SL}$	$0.351 + 0.004 \cdot \text{SL}$	$0.362 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.257	$0.246 + 0.005 \cdot \text{SL}$	$0.252 + 0.004 \cdot \text{SL}$	$0.268 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.056 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.365	$0.356 + 0.005 \cdot \text{SL}$	$0.361 + 0.004 \cdot \text{SL}$	$0.372 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.270	$0.260 + 0.005 \cdot \text{SL}$	$0.265 + 0.004 \cdot \text{SL}$	$0.281 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.391	$0.381 + 0.005 \cdot \text{SL}$	$0.386 + 0.004 \cdot \text{SL}$	$0.398 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.264	$0.253 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO321/AO321D2/AO321D4

3-AND and 2-AND into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	1	x	0
x	x	x	x	x	1	0
Other States						1

Cell Data

Input Load (SL)																	
AO321						AO321D2						AO321D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.0
Gate Count																	
AO321						AO321D2						AO321D4					
2.33						3.33						4.00					

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO321

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.458	$0.294 + 0.082 \cdot \text{SL}$	$0.287 + 0.084 \cdot \text{SL}$	$0.281 + 0.085 \cdot \text{SL}$
	t_F	0.262	$0.171 + 0.046 \cdot \text{SL}$	$0.163 + 0.048 \cdot \text{SL}$	$0.150 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.190	$0.120 + 0.035 \cdot \text{SL}$	$0.117 + 0.036 \cdot \text{SL}$	$0.117 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.144	$0.098 + 0.023 \cdot \text{SL}$	$0.099 + 0.023 \cdot \text{SL}$	$0.099 + 0.023 \cdot \text{SL}$
B to Y	t_R	0.496	$0.331 + 0.082 \cdot \text{SL}$	$0.324 + 0.084 \cdot \text{SL}$	$0.318 + 0.085 \cdot \text{SL}$
	t_F	0.259	$0.166 + 0.047 \cdot \text{SL}$	$0.160 + 0.048 \cdot \text{SL}$	$0.151 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.213	$0.142 + 0.035 \cdot \text{SL}$	$0.140 + 0.036 \cdot \text{SL}$	$0.140 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.146	$0.100 + 0.023 \cdot \text{SL}$	$0.101 + 0.023 \cdot \text{SL}$	$0.102 + 0.023 \cdot \text{SL}$
C to Y	t_R	0.536	$0.371 + 0.082 \cdot \text{SL}$	$0.364 + 0.084 \cdot \text{SL}$	$0.356 + 0.085 \cdot \text{SL}$
	t_F	0.255	$0.160 + 0.047 \cdot \text{SL}$	$0.155 + 0.049 \cdot \text{SL}$	$0.149 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.234	$0.162 + 0.036 \cdot \text{SL}$	$0.162 + 0.036 \cdot \text{SL}$	$0.162 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.144	$0.097 + 0.023 \cdot \text{SL}$	$0.099 + 0.023 \cdot \text{SL}$	$0.100 + 0.023 \cdot \text{SL}$
D to Y	t_R	0.513	$0.350 + 0.081 \cdot \text{SL}$	$0.345 + 0.082 \cdot \text{SL}$	$0.339 + 0.083 \cdot \text{SL}$
	t_F	0.267	$0.193 + 0.037 \cdot \text{SL}$	$0.188 + 0.038 \cdot \text{SL}$	$0.179 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.286	$0.213 + 0.037 \cdot \text{SL}$	$0.215 + 0.036 \cdot \text{SL}$	$0.219 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.184	$0.145 + 0.019 \cdot \text{SL}$	$0.146 + 0.019 \cdot \text{SL}$	$0.148 + 0.019 \cdot \text{SL}$
E to Y	t_R	0.550	$0.386 + 0.082 \cdot \text{SL}$	$0.381 + 0.084 \cdot \text{SL}$	$0.376 + 0.084 \cdot \text{SL}$
	t_F	0.263	$0.188 + 0.038 \cdot \text{SL}$	$0.185 + 0.039 \cdot \text{SL}$	$0.179 + 0.039 \cdot \text{SL}$
	t_{PLH}	0.310	$0.236 + 0.037 \cdot \text{SL}$	$0.238 + 0.036 \cdot \text{SL}$	$0.241 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.178	$0.139 + 0.019 \cdot \text{SL}$	$0.140 + 0.019 \cdot \text{SL}$	$0.142 + 0.019 \cdot \text{SL}$
F to Y	t_R	0.550	$0.385 + 0.083 \cdot \text{SL}$	$0.381 + 0.084 \cdot \text{SL}$	$0.376 + 0.084 \cdot \text{SL}$
	t_F	0.255	$0.207 + 0.024 \cdot \text{SL}$	$0.202 + 0.026 \cdot \text{SL}$	$0.192 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.333	$0.259 + 0.037 \cdot \text{SL}$	$0.261 + 0.037 \cdot \text{SL}$	$0.264 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.162	$0.132 + 0.015 \cdot \text{SL}$	$0.134 + 0.015 \cdot \text{SL}$	$0.138 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO321/AO321D2/AO321D4

3-AND and 2-AND into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO321D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.315	$0.298 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.259	$0.241 + 0.009 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$	$0.259 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.343	$0.327 + 0.008 \cdot \text{SL}$	$0.333 + 0.007 \cdot \text{SL}$	$0.341 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.261	$0.243 + 0.009 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.092	$0.067 + 0.012 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.368	$0.352 + 0.008 \cdot \text{SL}$	$0.358 + 0.007 \cdot \text{SL}$	$0.365 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.259	$0.241 + 0.009 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$	$0.259 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.091	$0.065 + 0.013 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.418	$0.401 + 0.008 \cdot \text{SL}$	$0.408 + 0.007 \cdot \text{SL}$	$0.415 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.304	$0.286 + 0.009 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.093	$0.067 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.446	$0.429 + 0.008 \cdot \text{SL}$	$0.436 + 0.007 \cdot \text{SL}$	$0.443 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.298	$0.280 + 0.009 \cdot \text{SL}$	$0.288 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.093	$0.066 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.469	$0.452 + 0.008 \cdot \text{SL}$	$0.459 + 0.007 \cdot \text{SL}$	$0.466 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.280	$0.262 + 0.009 \cdot \text{SL}$	$0.270 + 0.007 \cdot \text{SL}$	$0.280 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO321D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.342	$0.332 + 0.005 \cdot \text{SL}$	$0.338 + 0.004 \cdot \text{SL}$	$0.350 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.280	$0.270 + 0.005 \cdot \text{SL}$	$0.276 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.371	$0.361 + 0.005 \cdot \text{SL}$	$0.366 + 0.004 \cdot \text{SL}$	$0.379 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.272 + 0.005 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.089	$0.077 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.396	$0.386 + 0.005 \cdot \text{SL}$	$0.392 + 0.004 \cdot \text{SL}$	$0.404 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.280	$0.269 + 0.005 \cdot \text{SL}$	$0.275 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.087	$0.076 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.446	$0.435 + 0.005 \cdot \text{SL}$	$0.441 + 0.004 \cdot \text{SL}$	$0.454 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.323	$0.312 + 0.005 \cdot \text{SL}$	$0.318 + 0.004 \cdot \text{SL}$	$0.333 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.089	$0.076 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.055 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.474	$0.463 + 0.005 \cdot \text{SL}$	$0.469 + 0.004 \cdot \text{SL}$	$0.482 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.317	$0.306 + 0.005 \cdot \text{SL}$	$0.312 + 0.004 \cdot \text{SL}$	$0.327 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.054 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.496	$0.486 + 0.005 \cdot \text{SL}$	$0.492 + 0.004 \cdot \text{SL}$	$0.505 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.297	$0.286 + 0.005 \cdot \text{SL}$	$0.292 + 0.004 \cdot \text{SL}$	$0.307 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO322/AO322D2/AO322D4

3-AND and Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	x	x	x	x	0
x	x	x	1	1	x	x	0
x	x	x	x	x	1	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO322							AO322
A	B	C	D	E	F	G	2.67
1.0	1.0	1.1	1.1	1.1	1.1	1.1	
AO322D2							AO322D2
A	B	C	D	E	F	G	4.00
1.0	1.1	1.0	1.1	1.1	1.1	1.1	
AO322D4							AO322D4
A	B	C	D	E	F	G	4.33
1.0	1.0	1.1	1.1	1.1	1.1	1.1	

3-AND and Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO322

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.512	$0.343 + 0.084 \cdot \text{SL}$	$0.338 + 0.086 \cdot \text{SL}$	$0.334 + 0.086 \cdot \text{SL}$
	t_F	0.294	$0.207 + 0.044 \cdot \text{SL}$	$0.199 + 0.046 \cdot \text{SL}$	$0.185 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.226	$0.153 + 0.036 \cdot \text{SL}$	$0.152 + 0.037 \cdot \text{SL}$	$0.153 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.149	$0.105 + 0.022 \cdot \text{SL}$	$0.105 + 0.022 \cdot \text{SL}$	$0.106 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.551	$0.382 + 0.085 \cdot \text{SL}$	$0.377 + 0.086 \cdot \text{SL}$	$0.374 + 0.086 \cdot \text{SL}$
	t_F	0.291	$0.202 + 0.045 \cdot \text{SL}$	$0.195 + 0.046 \cdot \text{SL}$	$0.186 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.250	$0.177 + 0.036 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.151	$0.107 + 0.022 \cdot \text{SL}$	$0.108 + 0.022 \cdot \text{SL}$	$0.109 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.593	$0.424 + 0.085 \cdot \text{SL}$	$0.418 + 0.086 \cdot \text{SL}$	$0.415 + 0.087 \cdot \text{SL}$
	t_F	0.286	$0.195 + 0.046 \cdot \text{SL}$	$0.190 + 0.047 \cdot \text{SL}$	$0.185 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.274	$0.200 + 0.037 \cdot \text{SL}$	$0.200 + 0.037 \cdot \text{SL}$	$0.201 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.149	$0.104 + 0.023 \cdot \text{SL}$	$0.105 + 0.022 \cdot \text{SL}$	$0.107 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.570	$0.402 + 0.084 \cdot \text{SL}$	$0.399 + 0.085 \cdot \text{SL}$	$0.394 + 0.085 \cdot \text{SL}$
	t_F	0.275	$0.215 + 0.030 \cdot \text{SL}$	$0.209 + 0.032 \cdot \text{SL}$	$0.196 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.324	$0.249 + 0.038 \cdot \text{SL}$	$0.251 + 0.037 \cdot \text{SL}$	$0.254 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.163	$0.130 + 0.017 \cdot \text{SL}$	$0.131 + 0.016 \cdot \text{SL}$	$0.133 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.609	$0.440 + 0.085 \cdot \text{SL}$	$0.437 + 0.085 \cdot \text{SL}$	$0.433 + 0.086 \cdot \text{SL}$
	t_F	0.269	$0.207 + 0.031 \cdot \text{SL}$	$0.201 + 0.032 \cdot \text{SL}$	$0.195 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.350	$0.275 + 0.038 \cdot \text{SL}$	$0.276 + 0.037 \cdot \text{SL}$	$0.278 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.157	$0.124 + 0.017 \cdot \text{SL}$	$0.125 + 0.016 \cdot \text{SL}$	$0.127 + 0.016 \cdot \text{SL}$
F to Y	t_R	0.571	$0.402 + 0.084 \cdot \text{SL}$	$0.399 + 0.085 \cdot \text{SL}$	$0.394 + 0.086 \cdot \text{SL}$
	t_F	0.331	$0.270 + 0.031 \cdot \text{SL}$	$0.264 + 0.032 \cdot \text{SL}$	$0.254 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.362	$0.286 + 0.038 \cdot \text{SL}$	$0.288 + 0.037 \cdot \text{SL}$	$0.292 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.184	$0.148 + 0.018 \cdot \text{SL}$	$0.151 + 0.017 \cdot \text{SL}$	$0.156 + 0.016 \cdot \text{SL}$
G to Y	t_R	0.610	$0.440 + 0.085 \cdot \text{SL}$	$0.438 + 0.085 \cdot \text{SL}$	$0.434 + 0.086 \cdot \text{SL}$
	t_F	0.325	$0.262 + 0.032 \cdot \text{SL}$	$0.258 + 0.033 \cdot \text{SL}$	$0.252 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.387	$0.312 + 0.038 \cdot \text{SL}$	$0.314 + 0.037 \cdot \text{SL}$	$0.316 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.178	$0.143 + 0.018 \cdot \text{SL}$	$0.146 + 0.017 \cdot \text{SL}$	$0.151 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO322/AO322D2/AO322D4

3-AND and Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO322D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.352	$0.335 + 0.008 \cdot \text{SL}$	$0.342 + 0.007 \cdot \text{SL}$	$0.350 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.268	$0.250 + 0.009 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.268 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.093	$0.067 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.382	$0.365 + 0.008 \cdot \text{SL}$	$0.372 + 0.007 \cdot \text{SL}$	$0.380 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.270	$0.252 + 0.009 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$	$0.270 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.095	$0.071 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.411	$0.394 + 0.009 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.268	$0.250 + 0.009 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.268 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.093	$0.070 + 0.012 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.454	$0.437 + 0.009 \cdot \text{SL}$	$0.444 + 0.007 \cdot \text{SL}$	$0.452 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.286	$0.268 + 0.009 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.285 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.095	$0.069 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.486	$0.468 + 0.009 \cdot \text{SL}$	$0.476 + 0.007 \cdot \text{SL}$	$0.483 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.279	$0.261 + 0.009 \cdot \text{SL}$	$0.269 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.093	$0.068 + 0.012 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.490	$0.473 + 0.009 \cdot \text{SL}$	$0.480 + 0.007 \cdot \text{SL}$	$0.487 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.314	$0.296 + 0.009 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.314 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.095	$0.069 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.523	$0.506 + 0.009 \cdot \text{SL}$	$0.513 + 0.007 \cdot \text{SL}$	$0.520 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.309	$0.291 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

3-AND and Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO322D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.087	$0.074 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.377	$0.367 + 0.005 \cdot \text{SL}$	$0.373 + 0.004 \cdot \text{SL}$	$0.385 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.283 + 0.004 \cdot \text{SL}$	$0.299 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.089	$0.077 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.058 + 0.007 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.407	$0.396 + 0.005 \cdot \text{SL}$	$0.402 + 0.004 \cdot \text{SL}$	$0.415 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.289	$0.278 + 0.005 \cdot \text{SL}$	$0.285 + 0.004 \cdot \text{SL}$	$0.301 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.434	$0.424 + 0.005 \cdot \text{SL}$	$0.430 + 0.004 \cdot \text{SL}$	$0.443 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.288	$0.277 + 0.005 \cdot \text{SL}$	$0.283 + 0.004 \cdot \text{SL}$	$0.299 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.089	$0.077 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.055 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.479	$0.468 + 0.005 \cdot \text{SL}$	$0.474 + 0.004 \cdot \text{SL}$	$0.487 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.301	$0.291 + 0.005 \cdot \text{SL}$	$0.297 + 0.004 \cdot \text{SL}$	$0.312 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.091	$0.080 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.057 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.509	$0.498 + 0.005 \cdot \text{SL}$	$0.504 + 0.004 \cdot \text{SL}$	$0.518 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.295	$0.285 + 0.005 \cdot \text{SL}$	$0.291 + 0.004 \cdot \text{SL}$	$0.306 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.059 + 0.007 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.514	$0.504 + 0.005 \cdot \text{SL}$	$0.510 + 0.004 \cdot \text{SL}$	$0.523 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.332	$0.321 + 0.005 \cdot \text{SL}$	$0.327 + 0.004 \cdot \text{SL}$	$0.343 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.546	$0.536 + 0.005 \cdot \text{SL}$	$0.542 + 0.004 \cdot \text{SL}$	$0.555 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.326	$0.316 + 0.005 \cdot \text{SL}$	$0.322 + 0.004 \cdot \text{SL}$	$0.338 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO33/AO33D2/AO33D4

Two 3-ANDs into 2-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	1	1	0
Other States						1

Cell Data

Input Load (SL)																	
AO33						AO33D2						AO33D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.9	0.9	1.0	0.9	1.0	1.0	0.9	0.9	1.0	0.9	1.0	1.0	0.9	0.9	1.0	0.9	1.0	1.0
Gate Count																	
AO33						AO33D2						AO33D4					
2.33						3.00						3.67					

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO33

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.372	$0.232 + 0.070 \cdot \text{SL}$	$0.225 + 0.072 \cdot \text{SL}$	$0.217 + 0.073 \cdot \text{SL}$
	t_F	0.275	$0.190 + 0.043 \cdot \text{SL}$	$0.179 + 0.046 \cdot \text{SL}$	$0.163 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.197	$0.134 + 0.031 \cdot \text{SL}$	$0.135 + 0.031 \cdot \text{SL}$	$0.136 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.128	$0.082 + 0.023 \cdot \text{SL}$	$0.084 + 0.022 \cdot \text{SL}$	$0.086 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.404	$0.264 + 0.070 \cdot \text{SL}$	$0.256 + 0.072 \cdot \text{SL}$	$0.249 + 0.073 \cdot \text{SL}$
	t_F	0.271	$0.184 + 0.044 \cdot \text{SL}$	$0.174 + 0.046 \cdot \text{SL}$	$0.164 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.218	$0.156 + 0.031 \cdot \text{SL}$	$0.156 + 0.031 \cdot \text{SL}$	$0.156 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.130	$0.083 + 0.023 \cdot \text{SL}$	$0.086 + 0.023 \cdot \text{SL}$	$0.089 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.437	$0.297 + 0.070 \cdot \text{SL}$	$0.290 + 0.072 \cdot \text{SL}$	$0.282 + 0.073 \cdot \text{SL}$
	t_F	0.266	$0.177 + 0.045 \cdot \text{SL}$	$0.169 + 0.047 \cdot \text{SL}$	$0.161 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.236	$0.174 + 0.031 \cdot \text{SL}$	$0.174 + 0.031 \cdot \text{SL}$	$0.175 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.127	$0.081 + 0.023 \cdot \text{SL}$	$0.084 + 0.023 \cdot \text{SL}$	$0.087 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.372	$0.231 + 0.070 \cdot \text{SL}$	$0.225 + 0.072 \cdot \text{SL}$	$0.219 + 0.073 \cdot \text{SL}$
	t_F	0.292	$0.203 + 0.044 \cdot \text{SL}$	$0.196 + 0.046 \cdot \text{SL}$	$0.185 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.233	$0.168 + 0.032 \cdot \text{SL}$	$0.171 + 0.032 \cdot \text{SL}$	$0.174 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.178	$0.133 + 0.022 \cdot \text{SL}$	$0.134 + 0.022 \cdot \text{SL}$	$0.136 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.404	$0.262 + 0.071 \cdot \text{SL}$	$0.257 + 0.072 \cdot \text{SL}$	$0.252 + 0.073 \cdot \text{SL}$
	t_F	0.290	$0.199 + 0.045 \cdot \text{SL}$	$0.194 + 0.047 \cdot \text{SL}$	$0.186 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.255	$0.191 + 0.032 \cdot \text{SL}$	$0.193 + 0.031 \cdot \text{SL}$	$0.195 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.181	$0.136 + 0.023 \cdot \text{SL}$	$0.138 + 0.022 \cdot \text{SL}$	$0.139 + 0.022 \cdot \text{SL}$
F to Y	t_R	0.438	$0.295 + 0.071 \cdot \text{SL}$	$0.292 + 0.072 \cdot \text{SL}$	$0.286 + 0.073 \cdot \text{SL}$
	t_F	0.286	$0.195 + 0.046 \cdot \text{SL}$	$0.190 + 0.047 \cdot \text{SL}$	$0.185 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.275	$0.211 + 0.032 \cdot \text{SL}$	$0.213 + 0.031 \cdot \text{SL}$	$0.215 + 0.031 \cdot \text{SL}$
	t_{PHL}	0.179	$0.134 + 0.023 \cdot \text{SL}$	$0.136 + 0.022 \cdot \text{SL}$	$0.138 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO33/AO33D2/AO33D4

Two 3-ANDs into 2-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO33D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.315	$0.299 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.250	$0.232 + 0.009 \cdot \text{SL}$	$0.240 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.325 + 0.008 \cdot \text{SL}$	$0.331 + 0.007 \cdot \text{SL}$	$0.337 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.253	$0.235 + 0.009 \cdot \text{SL}$	$0.242 + 0.007 \cdot \text{SL}$	$0.252 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.363	$0.346 + 0.008 \cdot \text{SL}$	$0.352 + 0.007 \cdot \text{SL}$	$0.359 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.251	$0.232 + 0.009 \cdot \text{SL}$	$0.240 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.349	$0.333 + 0.008 \cdot \text{SL}$	$0.339 + 0.007 \cdot \text{SL}$	$0.345 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.302	$0.283 + 0.009 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.301 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.086	$0.059 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.378	$0.362 + 0.008 \cdot \text{SL}$	$0.368 + 0.007 \cdot \text{SL}$	$0.375 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.304	$0.286 + 0.009 \cdot \text{SL}$	$0.294 + 0.007 \cdot \text{SL}$	$0.304 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.088	$0.061 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.401	$0.384 + 0.008 \cdot \text{SL}$	$0.390 + 0.007 \cdot \text{SL}$	$0.397 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.303	$0.285 + 0.009 \cdot \text{SL}$	$0.292 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO33D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.067 + 0.007 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.340	$0.330 + 0.005 \cdot \text{SL}$	$0.335 + 0.004 \cdot \text{SL}$	$0.346 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.271	$0.260 + 0.005 \cdot \text{SL}$	$0.266 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.081	$0.069 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.366	$0.356 + 0.005 \cdot \text{SL}$	$0.361 + 0.004 \cdot \text{SL}$	$0.373 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.273	$0.262 + 0.005 \cdot \text{SL}$	$0.268 + 0.004 \cdot \text{SL}$	$0.284 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.387	$0.377 + 0.005 \cdot \text{SL}$	$0.383 + 0.004 \cdot \text{SL}$	$0.394 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.271	$0.260 + 0.005 \cdot \text{SL}$	$0.265 + 0.004 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.374	$0.364 + 0.005 \cdot \text{SL}$	$0.369 + 0.004 \cdot \text{SL}$	$0.381 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.322	$0.311 + 0.005 \cdot \text{SL}$	$0.317 + 0.004 \cdot \text{SL}$	$0.333 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.081	$0.069 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.403	$0.393 + 0.005 \cdot \text{SL}$	$0.399 + 0.004 \cdot \text{SL}$	$0.410 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.314 + 0.005 \cdot \text{SL}$	$0.320 + 0.004 \cdot \text{SL}$	$0.335 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.425	$0.415 + 0.005 \cdot \text{SL}$	$0.421 + 0.004 \cdot \text{SL}$	$0.432 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.323	$0.313 + 0.005 \cdot \text{SL}$	$0.318 + 0.004 \cdot \text{SL}$	$0.334 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO331/AO331D2/AO331D4

Two 3-ANDs into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	x	x	x	x	0
x	x	x	1	1	1	x	0
x	x	x	x	x	x	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO331							AO331
A	B	C	D	E	F	G	2.67
1.0	1.0	1.0	1.0	1.0	1.0	1.0	
AO331D2							AO331D2
A	B	C	D	E	F	G	3.33
1.0	1.0	1.0	1.0	1.0	1.1	1.0	
AO331D4							AO331D4
A	B	C	D	E	F	G	4.00
1.0	1.0	1.0	1.0	1.0	1.1	1.0	

AO331/AO331D2/AO331D4

Two 3-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO331

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.527	$0.355 + 0.086 \cdot \text{SL}$	$0.349 + 0.088 \cdot \text{SL}$	$0.346 + 0.088 \cdot \text{SL}$
	t_F	0.296	$0.209 + 0.043 \cdot \text{SL}$	$0.200 + 0.046 \cdot \text{SL}$	$0.186 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.228	$0.153 + 0.037 \cdot \text{SL}$	$0.152 + 0.038 \cdot \text{SL}$	$0.154 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.143	$0.098 + 0.022 \cdot \text{SL}$	$0.099 + 0.022 \cdot \text{SL}$	$0.101 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.565	$0.393 + 0.086 \cdot \text{SL}$	$0.387 + 0.088 \cdot \text{SL}$	$0.384 + 0.088 \cdot \text{SL}$
	t_F	0.293	$0.204 + 0.044 \cdot \text{SL}$	$0.196 + 0.046 \cdot \text{SL}$	$0.187 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.252	$0.177 + 0.037 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.145	$0.099 + 0.023 \cdot \text{SL}$	$0.101 + 0.023 \cdot \text{SL}$	$0.104 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.602	$0.431 + 0.085 \cdot \text{SL}$	$0.425 + 0.087 \cdot \text{SL}$	$0.421 + 0.087 \cdot \text{SL}$
	t_F	0.288	$0.197 + 0.045 \cdot \text{SL}$	$0.192 + 0.047 \cdot \text{SL}$	$0.186 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.272	$0.198 + 0.037 \cdot \text{SL}$	$0.198 + 0.037 \cdot \text{SL}$	$0.198 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.142	$0.097 + 0.023 \cdot \text{SL}$	$0.098 + 0.023 \cdot \text{SL}$	$0.101 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.540	$0.371 + 0.084 \cdot \text{SL}$	$0.366 + 0.086 \cdot \text{SL}$	$0.360 + 0.086 \cdot \text{SL}$
	t_F	0.329	$0.238 + 0.046 \cdot \text{SL}$	$0.234 + 0.047 \cdot \text{SL}$	$0.225 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.305	$0.228 + 0.038 \cdot \text{SL}$	$0.230 + 0.038 \cdot \text{SL}$	$0.235 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.207	$0.162 + 0.023 \cdot \text{SL}$	$0.163 + 0.022 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.583	$0.411 + 0.086 \cdot \text{SL}$	$0.408 + 0.087 \cdot \text{SL}$	$0.403 + 0.087 \cdot \text{SL}$
	t_F	0.328	$0.236 + 0.046 \cdot \text{SL}$	$0.233 + 0.047 \cdot \text{SL}$	$0.227 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.334	$0.257 + 0.038 \cdot \text{SL}$	$0.260 + 0.038 \cdot \text{SL}$	$0.263 + 0.038 \cdot \text{SL}$
	t_{PHL}	0.211	$0.165 + 0.023 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$	$0.169 + 0.022 \cdot \text{SL}$
F to Y	t_R	0.620	$0.449 + 0.085 \cdot \text{SL}$	$0.446 + 0.086 \cdot \text{SL}$	$0.441 + 0.086 \cdot \text{SL}$
	t_F	0.326	$0.232 + 0.047 \cdot \text{SL}$	$0.231 + 0.047 \cdot \text{SL}$	$0.226 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.356	$0.280 + 0.038 \cdot \text{SL}$	$0.282 + 0.038 \cdot \text{SL}$	$0.285 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.209	$0.163 + 0.023 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
G to Y	t_R	0.619	$0.449 + 0.085 \cdot \text{SL}$	$0.446 + 0.086 \cdot \text{SL}$	$0.441 + 0.086 \cdot \text{SL}$
	t_F	0.249	$0.205 + 0.022 \cdot \text{SL}$	$0.200 + 0.023 \cdot \text{SL}$	$0.190 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.383	$0.307 + 0.038 \cdot \text{SL}$	$0.309 + 0.038 \cdot \text{SL}$	$0.312 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.150	$0.121 + 0.014 \cdot \text{SL}$	$0.123 + 0.014 \cdot \text{SL}$	$0.128 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO331/AO331D2/AO331D4

Two 3-ANDs into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20ns$, SL: Standard Load)

AO331D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.092	$0.066 + 0.013 \cdot SL$	$0.065 + 0.013 \cdot SL$	$0.050 + 0.014 \cdot SL$
	t_F	0.077	$0.054 + 0.012 \cdot SL$	$0.054 + 0.012 \cdot SL$	$0.047 + 0.012 \cdot SL$
	t_{PLH}	0.358	$0.341 + 0.008 \cdot SL$	$0.348 + 0.007 \cdot SL$	$0.355 + 0.006 \cdot SL$
	t_{PHL}	0.268	$0.250 + 0.009 \cdot SL$	$0.258 + 0.007 \cdot SL$	$0.268 + 0.006 \cdot SL$
B to Y	t_R	0.094	$0.069 + 0.013 \cdot SL$	$0.068 + 0.013 \cdot SL$	$0.052 + 0.014 \cdot SL$
	t_F	0.077	$0.054 + 0.012 \cdot SL$	$0.054 + 0.012 \cdot SL$	$0.047 + 0.012 \cdot SL$
	t_{PLH}	0.388	$0.371 + 0.009 \cdot SL$	$0.378 + 0.007 \cdot SL$	$0.385 + 0.006 \cdot SL$
	t_{PHL}	0.270	$0.252 + 0.009 \cdot SL$	$0.260 + 0.007 \cdot SL$	$0.270 + 0.006 \cdot SL$
C to Y	t_R	0.096	$0.073 + 0.012 \cdot SL$	$0.067 + 0.013 \cdot SL$	$0.054 + 0.014 \cdot SL$
	t_F	0.077	$0.053 + 0.012 \cdot SL$	$0.055 + 0.011 \cdot SL$	$0.046 + 0.012 \cdot SL$
	t_{PLH}	0.413	$0.396 + 0.009 \cdot SL$	$0.403 + 0.007 \cdot SL$	$0.411 + 0.006 \cdot SL$
	t_{PHL}	0.268	$0.250 + 0.009 \cdot SL$	$0.257 + 0.007 \cdot SL$	$0.268 + 0.006 \cdot SL$
D to Y	t_R	0.092	$0.069 + 0.012 \cdot SL$	$0.063 + 0.013 \cdot SL$	$0.050 + 0.014 \cdot SL$
	t_F	0.075	$0.050 + 0.013 \cdot SL$	$0.055 + 0.011 \cdot SL$	$0.046 + 0.012 \cdot SL$
	t_{PLH}	0.433	$0.417 + 0.008 \cdot SL$	$0.423 + 0.007 \cdot SL$	$0.431 + 0.006 \cdot SL$
	t_{PHL}	0.333	$0.315 + 0.009 \cdot SL$	$0.322 + 0.007 \cdot SL$	$0.333 + 0.006 \cdot SL$
E to Y	t_R	0.094	$0.069 + 0.013 \cdot SL$	$0.068 + 0.013 \cdot SL$	$0.052 + 0.014 \cdot SL$
	t_F	0.077	$0.053 + 0.012 \cdot SL$	$0.054 + 0.012 \cdot SL$	$0.047 + 0.012 \cdot SL$
	t_{PLH}	0.468	$0.451 + 0.009 \cdot SL$	$0.458 + 0.007 \cdot SL$	$0.466 + 0.006 \cdot SL$
	t_{PHL}	0.336	$0.318 + 0.009 \cdot SL$	$0.325 + 0.007 \cdot SL$	$0.336 + 0.006 \cdot SL$
F to Y	t_R	0.096	$0.073 + 0.012 \cdot SL$	$0.067 + 0.013 \cdot SL$	$0.054 + 0.014 \cdot SL$
	t_F	0.076	$0.051 + 0.012 \cdot SL$	$0.055 + 0.011 \cdot SL$	$0.046 + 0.012 \cdot SL$
	t_{PLH}	0.496	$0.479 + 0.009 \cdot SL$	$0.486 + 0.007 \cdot SL$	$0.494 + 0.006 \cdot SL$
	t_{PHL}	0.334	$0.316 + 0.009 \cdot SL$	$0.324 + 0.007 \cdot SL$	$0.334 + 0.006 \cdot SL$
G to Y	t_R	0.096	$0.073 + 0.012 \cdot SL$	$0.068 + 0.013 \cdot SL$	$0.054 + 0.014 \cdot SL$
	t_F	0.076	$0.052 + 0.012 \cdot SL$	$0.054 + 0.011 \cdot SL$	$0.045 + 0.012 \cdot SL$
	t_{PLH}	0.522	$0.505 + 0.009 \cdot SL$	$0.512 + 0.007 \cdot SL$	$0.520 + 0.006 \cdot SL$
	t_{PHL}	0.279	$0.261 + 0.009 \cdot SL$	$0.268 + 0.007 \cdot SL$	$0.278 + 0.006 \cdot SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 16$, *Group3 : $16 < SL$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO331D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.060 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.386	$0.376 + 0.005 \cdot \text{SL}$	$0.382 + 0.004 \cdot \text{SL}$	$0.395 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.289	$0.278 + 0.005 \cdot \text{SL}$	$0.284 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.417	$0.406 + 0.005 \cdot \text{SL}$	$0.412 + 0.004 \cdot \text{SL}$	$0.425 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.291	$0.280 + 0.005 \cdot \text{SL}$	$0.286 + 0.004 \cdot \text{SL}$	$0.302 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.442	$0.431 + 0.005 \cdot \text{SL}$	$0.437 + 0.004 \cdot \text{SL}$	$0.451 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.289	$0.278 + 0.005 \cdot \text{SL}$	$0.284 + 0.004 \cdot \text{SL}$	$0.300 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.088	$0.075 + 0.007 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.060 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.463	$0.452 + 0.005 \cdot \text{SL}$	$0.458 + 0.004 \cdot \text{SL}$	$0.471 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.354	$0.343 + 0.005 \cdot \text{SL}$	$0.349 + 0.004 \cdot \text{SL}$	$0.365 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.061 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.497	$0.487 + 0.005 \cdot \text{SL}$	$0.493 + 0.004 \cdot \text{SL}$	$0.506 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.357	$0.346 + 0.005 \cdot \text{SL}$	$0.352 + 0.004 \cdot \text{SL}$	$0.368 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.092	$0.079 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.525	$0.514 + 0.005 \cdot \text{SL}$	$0.521 + 0.004 \cdot \text{SL}$	$0.534 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.355	$0.344 + 0.005 \cdot \text{SL}$	$0.350 + 0.004 \cdot \text{SL}$	$0.366 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.092	$0.080 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.059 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.551	$0.541 + 0.005 \cdot \text{SL}$	$0.547 + 0.004 \cdot \text{SL}$	$0.560 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.291	$0.281 + 0.005 \cdot \text{SL}$	$0.286 + 0.004 \cdot \text{SL}$	$0.302 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO332/AO332D2/AO332D4

Two 3-ANDs and 2-AND into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	1	x	x	x	x	x	0
x	x	x	1	1	1	x	x	0
x	x	x	x	x	x	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
AO332								AO332
A	B	C	D	E	F	G	H	3.00
1.0	1.0	1.0	1.0	1.0	1.1	1.1	1.1	
AO332D2								AO332D2
A	B	C	D	E	F	G	H	4.00
1.0	1.0	1.0	1.0	1.0	1.1	1.1	1.1	
AO332D4								AO332D4
A	B	C	D	E	F	G	H	4.67
1.0	1.0	1.0	1.0	1.0	1.1	1.1	1.1	

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO332

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.529	$0.356 + 0.086 \cdot \text{SL}$	$0.351 + 0.088 \cdot \text{SL}$	$0.348 + 0.088 \cdot \text{SL}$
	t_F	0.328	$0.241 + 0.044 \cdot \text{SL}$	$0.233 + 0.046 \cdot \text{SL}$	$0.219 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.228	$0.154 + 0.037 \cdot \text{SL}$	$0.153 + 0.037 \cdot \text{SL}$	$0.154 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.152	$0.107 + 0.023 \cdot \text{SL}$	$0.108 + 0.022 \cdot \text{SL}$	$0.110 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.567	$0.394 + 0.086 \cdot \text{SL}$	$0.389 + 0.088 \cdot \text{SL}$	$0.386 + 0.088 \cdot \text{SL}$
	t_F	0.325	$0.236 + 0.044 \cdot \text{SL}$	$0.229 + 0.046 \cdot \text{SL}$	$0.220 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.252	$0.177 + 0.037 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$	$0.177 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.154	$0.109 + 0.023 \cdot \text{SL}$	$0.109 + 0.023 \cdot \text{SL}$	$0.113 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.608	$0.435 + 0.086 \cdot \text{SL}$	$0.429 + 0.088 \cdot \text{SL}$	$0.426 + 0.088 \cdot \text{SL}$
	t_F	0.320	$0.229 + 0.045 \cdot \text{SL}$	$0.225 + 0.047 \cdot \text{SL}$	$0.218 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.273	$0.199 + 0.037 \cdot \text{SL}$	$0.199 + 0.037 \cdot \text{SL}$	$0.199 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.151	$0.105 + 0.023 \cdot \text{SL}$	$0.107 + 0.023 \cdot \text{SL}$	$0.111 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.587	$0.416 + 0.086 \cdot \text{SL}$	$0.413 + 0.087 \cdot \text{SL}$	$0.408 + 0.087 \cdot \text{SL}$
	t_F	0.383	$0.294 + 0.045 \cdot \text{SL}$	$0.287 + 0.046 \cdot \text{SL}$	$0.277 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.335	$0.258 + 0.039 \cdot \text{SL}$	$0.261 + 0.038 \cdot \text{SL}$	$0.264 + 0.038 \cdot \text{SL}$
	t_{PHL}	0.213	$0.168 + 0.023 \cdot \text{SL}$	$0.169 + 0.022 \cdot \text{SL}$	$0.170 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.626	$0.454 + 0.086 \cdot \text{SL}$	$0.451 + 0.087 \cdot \text{SL}$	$0.448 + 0.087 \cdot \text{SL}$
	t_F	0.382	$0.291 + 0.045 \cdot \text{SL}$	$0.286 + 0.047 \cdot \text{SL}$	$0.279 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.362	$0.285 + 0.038 \cdot \text{SL}$	$0.287 + 0.038 \cdot \text{SL}$	$0.290 + 0.038 \cdot \text{SL}$
	t_{PHL}	0.216	$0.171 + 0.023 \cdot \text{SL}$	$0.172 + 0.022 \cdot \text{SL}$	$0.174 + 0.022 \cdot \text{SL}$
F to Y	t_R	0.663	$0.492 + 0.086 \cdot \text{SL}$	$0.489 + 0.086 \cdot \text{SL}$	$0.486 + 0.087 \cdot \text{SL}$
	t_F	0.380	$0.288 + 0.046 \cdot \text{SL}$	$0.284 + 0.047 \cdot \text{SL}$	$0.278 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.384	$0.308 + 0.038 \cdot \text{SL}$	$0.310 + 0.038 \cdot \text{SL}$	$0.312 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.214	$0.169 + 0.023 \cdot \text{SL}$	$0.170 + 0.022 \cdot \text{SL}$	$0.173 + 0.022 \cdot \text{SL}$
G to Y	t_R	0.626	$0.456 + 0.085 \cdot \text{SL}$	$0.452 + 0.086 \cdot \text{SL}$	$0.448 + 0.086 \cdot \text{SL}$
	t_F	0.337	$0.276 + 0.031 \cdot \text{SL}$	$0.271 + 0.032 \cdot \text{SL}$	$0.260 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.400	$0.323 + 0.039 \cdot \text{SL}$	$0.326 + 0.038 \cdot \text{SL}$	$0.330 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.181	$0.145 + 0.018 \cdot \text{SL}$	$0.148 + 0.017 \cdot \text{SL}$	$0.155 + 0.017 \cdot \text{SL}$
H to Y	t_R	0.663	$0.492 + 0.085 \cdot \text{SL}$	$0.490 + 0.086 \cdot \text{SL}$	$0.486 + 0.087 \cdot \text{SL}$
	t_F	0.331	$0.268 + 0.031 \cdot \text{SL}$	$0.265 + 0.032 \cdot \text{SL}$	$0.258 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.425	$0.349 + 0.038 \cdot \text{SL}$	$0.350 + 0.038 \cdot \text{SL}$	$0.353 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.175	$0.139 + 0.018 \cdot \text{SL}$	$0.142 + 0.017 \cdot \text{SL}$	$0.150 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO332/AO332D2/AO332D4

Two 3-ANDs and 2-AND into 3-NOR with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO332D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.351	$0.334 + 0.008 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$	$0.348 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.280	$0.262 + 0.009 \cdot \text{SL}$	$0.270 + 0.007 \cdot \text{SL}$	$0.280 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.093	$0.068 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.379	$0.362 + 0.008 \cdot \text{SL}$	$0.369 + 0.007 \cdot \text{SL}$	$0.377 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.281	$0.263 + 0.009 \cdot \text{SL}$	$0.271 + 0.007 \cdot \text{SL}$	$0.281 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.095	$0.069 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.406	$0.389 + 0.009 \cdot \text{SL}$	$0.396 + 0.007 \cdot \text{SL}$	$0.404 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.279	$0.261 + 0.009 \cdot \text{SL}$	$0.268 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.093	$0.068 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.460	$0.443 + 0.008 \cdot \text{SL}$	$0.450 + 0.007 \cdot \text{SL}$	$0.458 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.345	$0.326 + 0.009 \cdot \text{SL}$	$0.334 + 0.007 \cdot \text{SL}$	$0.345 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.095	$0.072 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.492	$0.475 + 0.009 \cdot \text{SL}$	$0.483 + 0.007 \cdot \text{SL}$	$0.490 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.348	$0.329 + 0.009 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$	$0.348 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.096	$0.072 + 0.012 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.519	$0.502 + 0.009 \cdot \text{SL}$	$0.509 + 0.007 \cdot \text{SL}$	$0.517 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.346	$0.328 + 0.009 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.346 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.095	$0.071 + 0.012 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.530	$0.513 + 0.009 \cdot \text{SL}$	$0.520 + 0.007 \cdot \text{SL}$	$0.527 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.315	$0.297 + 0.009 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.315 + 0.006 \cdot \text{SL}$
H to Y	t_R	0.096	$0.071 + 0.013 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.559	$0.542 + 0.009 \cdot \text{SL}$	$0.549 + 0.007 \cdot \text{SL}$	$0.557 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.308	$0.290 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO332D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	$0.074 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.061 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.376	$0.366 + 0.005 \cdot \text{SL}$	$0.372 + 0.004 \cdot \text{SL}$	$0.384 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.298	$0.287 + 0.005 \cdot \text{SL}$	$0.293 + 0.004 \cdot \text{SL}$	$0.309 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.405	$0.395 + 0.005 \cdot \text{SL}$	$0.401 + 0.004 \cdot \text{SL}$	$0.413 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.299	$0.288 + 0.005 \cdot \text{SL}$	$0.294 + 0.004 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.091	$0.080 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.432	$0.421 + 0.005 \cdot \text{SL}$	$0.427 + 0.004 \cdot \text{SL}$	$0.440 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.296	$0.285 + 0.005 \cdot \text{SL}$	$0.291 + 0.004 \cdot \text{SL}$	$0.308 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.088	$0.077 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.486	$0.476 + 0.005 \cdot \text{SL}$	$0.482 + 0.004 \cdot \text{SL}$	$0.495 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.362	$0.352 + 0.005 \cdot \text{SL}$	$0.357 + 0.004 \cdot \text{SL}$	$0.374 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.519	$0.508 + 0.005 \cdot \text{SL}$	$0.514 + 0.004 \cdot \text{SL}$	$0.527 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.365	$0.355 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.377 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.093	$0.080 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.546	$0.535 + 0.005 \cdot \text{SL}$	$0.541 + 0.004 \cdot \text{SL}$	$0.555 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.364	$0.353 + 0.005 \cdot \text{SL}$	$0.359 + 0.004 \cdot \text{SL}$	$0.375 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.062 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.556	$0.546 + 0.005 \cdot \text{SL}$	$0.552 + 0.004 \cdot \text{SL}$	$0.565 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.331	$0.320 + 0.005 \cdot \text{SL}$	$0.326 + 0.004 \cdot \text{SL}$	$0.343 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.093	$0.080 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.064 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.586	$0.575 + 0.005 \cdot \text{SL}$	$0.582 + 0.004 \cdot \text{SL}$	$0.595 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.314 + 0.005 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.336 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

AO4111/AO4111D2

4-AND into 4-NOR with 1X/2X Drive

Logic SymbolCell Data



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	1	x	x	x	0
x	x	x	x	1	x	x	0
x	x	x	x	x	1	x	0
x	x	x	x	x	x	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO4111							AO4111
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	0.8	0.8	0.9	2.67
AO4111D2							AO4111D2
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	0.8	0.9	0.9	3.33

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO4111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.595	$0.376 + 0.110 \cdot \text{SL}$	$0.370 + 0.111 \cdot \text{SL}$	$0.368 + 0.111 \cdot \text{SL}$
	t_F	0.319	$0.191 + 0.064 \cdot \text{SL}$	$0.184 + 0.066 \cdot \text{SL}$	$0.175 + 0.067 \cdot \text{SL}$
	t_{PLH}	0.195	$0.106 + 0.044 \cdot \text{SL}$	$0.095 + 0.047 \cdot \text{SL}$	$0.096 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.172	$0.112 + 0.030 \cdot \text{SL}$	$0.112 + 0.030 \cdot \text{SL}$	$0.111 + 0.030 \cdot \text{SL}$
B to Y	t_R	0.644	$0.424 + 0.110 \cdot \text{SL}$	$0.418 + 0.112 \cdot \text{SL}$	$0.416 + 0.112 \cdot \text{SL}$
	t_F	0.320	$0.191 + 0.065 \cdot \text{SL}$	$0.186 + 0.066 \cdot \text{SL}$	$0.178 + 0.067 \cdot \text{SL}$
	t_{PLH}	0.222	$0.130 + 0.046 \cdot \text{SL}$	$0.125 + 0.047 \cdot \text{SL}$	$0.126 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.182	$0.121 + 0.030 \cdot \text{SL}$	$0.121 + 0.030 \cdot \text{SL}$	$0.122 + 0.030 \cdot \text{SL}$
C to Y	t_R	0.692	$0.474 + 0.109 \cdot \text{SL}$	$0.465 + 0.111 \cdot \text{SL}$	$0.463 + 0.112 \cdot \text{SL}$
	t_F	0.318	$0.188 + 0.065 \cdot \text{SL}$	$0.185 + 0.066 \cdot \text{SL}$	$0.178 + 0.067 \cdot \text{SL}$
	t_{PLH}	0.247	$0.154 + 0.047 \cdot \text{SL}$	$0.152 + 0.047 \cdot \text{SL}$	$0.153 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.187	$0.125 + 0.031 \cdot \text{SL}$	$0.126 + 0.030 \cdot \text{SL}$	$0.127 + 0.030 \cdot \text{SL}$
D to Y	t_R	0.744	$0.527 + 0.109 \cdot \text{SL}$	$0.516 + 0.111 \cdot \text{SL}$	$0.513 + 0.112 \cdot \text{SL}$
	t_F	0.316	$0.185 + 0.066 \cdot \text{SL}$	$0.182 + 0.066 \cdot \text{SL}$	$0.177 + 0.067 \cdot \text{SL}$
	t_{PLH}	0.273	$0.177 + 0.048 \cdot \text{SL}$	$0.178 + 0.048 \cdot \text{SL}$	$0.180 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.189	$0.127 + 0.031 \cdot \text{SL}$	$0.128 + 0.031 \cdot \text{SL}$	$0.130 + 0.030 \cdot \text{SL}$
E to Y	t_R	0.780	$0.564 + 0.108 \cdot \text{SL}$	$0.559 + 0.109 \cdot \text{SL}$	$0.553 + 0.110 \cdot \text{SL}$
	t_F	0.286	$0.205 + 0.041 \cdot \text{SL}$	$0.201 + 0.042 \cdot \text{SL}$	$0.195 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.400	$0.302 + 0.049 \cdot \text{SL}$	$0.305 + 0.048 \cdot \text{SL}$	$0.310 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.221	$0.176 + 0.022 \cdot \text{SL}$	$0.177 + 0.022 \cdot \text{SL}$	$0.179 + 0.022 \cdot \text{SL}$
F to Y	t_R	0.781	$0.566 + 0.108 \cdot \text{SL}$	$0.560 + 0.109 \cdot \text{SL}$	$0.553 + 0.110 \cdot \text{SL}$
	t_F	0.318	$0.237 + 0.041 \cdot \text{SL}$	$0.233 + 0.042 \cdot \text{SL}$	$0.228 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.427	$0.329 + 0.049 \cdot \text{SL}$	$0.332 + 0.048 \cdot \text{SL}$	$0.337 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.238	$0.192 + 0.023 \cdot \text{SL}$	$0.194 + 0.022 \cdot \text{SL}$	$0.197 + 0.022 \cdot \text{SL}$
G to Y	t_R	0.781	$0.565 + 0.108 \cdot \text{SL}$	$0.559 + 0.109 \cdot \text{SL}$	$0.553 + 0.110 \cdot \text{SL}$
	t_F	0.357	$0.277 + 0.040 \cdot \text{SL}$	$0.272 + 0.041 \cdot \text{SL}$	$0.265 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.437	$0.339 + 0.049 \cdot \text{SL}$	$0.343 + 0.048 \cdot \text{SL}$	$0.347 + 0.048 \cdot \text{SL}$
	t_{PHL}	0.249	$0.202 + 0.024 \cdot \text{SL}$	$0.205 + 0.023 \cdot \text{SL}$	$0.210 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

AO4111/AO4111D2

4-AND into 4-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

AO4111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	$0.068 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.316	$0.299 + 0.009 \cdot \text{SL}$	$0.306 + 0.007 \cdot \text{SL}$	$0.314 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.284	$0.265 + 0.009 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.096	$0.071 + 0.012 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.351	$0.334 + 0.009 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$	$0.349 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.293	$0.274 + 0.009 \cdot \text{SL}$	$0.282 + 0.007 \cdot \text{SL}$	$0.292 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.098	$0.073 + 0.013 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.381	$0.364 + 0.009 \cdot \text{SL}$	$0.371 + 0.007 \cdot \text{SL}$	$0.380 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.297	$0.279 + 0.009 \cdot \text{SL}$	$0.287 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.075 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.410	$0.392 + 0.009 \cdot \text{SL}$	$0.400 + 0.007 \cdot \text{SL}$	$0.410 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.298	$0.280 + 0.009 \cdot \text{SL}$	$0.288 + 0.007 \cdot \text{SL}$	$0.298 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.101	$0.079 + 0.011 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.537	$0.519 + 0.009 \cdot \text{SL}$	$0.527 + 0.007 \cdot \text{SL}$	$0.536 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.346	$0.328 + 0.009 \cdot \text{SL}$	$0.336 + 0.007 \cdot \text{SL}$	$0.346 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.564	$0.546 + 0.009 \cdot \text{SL}$	$0.554 + 0.007 \cdot \text{SL}$	$0.564 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.366	$0.348 + 0.009 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$	$0.366 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.100	$0.074 + 0.013 \cdot \text{SL}$	$0.075 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.055 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.575	$0.557 + 0.009 \cdot \text{SL}$	$0.565 + 0.007 \cdot \text{SL}$	$0.574 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.381	$0.363 + 0.009 \cdot \text{SL}$	$0.371 + 0.007 \cdot \text{SL}$	$0.381 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA21DH/OA21/OA21D2/OA21D2B/OA21D4

2-OR into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	x	1
x	x	0	1
Others States			0

Cell Data

Input Load (SL)														
OA21DH			OA21			OA21D2			OA21D2B			OA21D4		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.6	0.6	0.9	1.0	1.1	1.9	1.9	2.3	0.9	1.0	1.1	0.9	1.0	1.1
Gate Count														
OA21DH			OA21			OA21D2			OA21D2B			OA21D4		
1.33			1.33			2.33			2.33			3.00		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA21DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.347	$0.125 + 0.111 \cdot \text{SL}$	$0.105 + 0.116 \cdot \text{SL}$	$0.094 + 0.117 \cdot \text{SL}$
	t_F	0.257	$0.092 + 0.082 \cdot \text{SL}$	$0.073 + 0.087 \cdot \text{SL}$	$0.061 + 0.089 \cdot \text{SL}$
	t_{PLH}	0.176	$0.077 + 0.050 \cdot \text{SL}$	$0.076 + 0.050 \cdot \text{SL}$	$0.075 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.159	$0.074 + 0.043 \cdot \text{SL}$	$0.074 + 0.043 \cdot \text{SL}$	$0.074 + 0.043 \cdot \text{SL}$
B to Y	t_R	0.341	$0.115 + 0.113 \cdot \text{SL}$	$0.103 + 0.116 \cdot \text{SL}$	$0.095 + 0.117 \cdot \text{SL}$
	t_F	0.292	$0.127 + 0.082 \cdot \text{SL}$	$0.106 + 0.088 \cdot \text{SL}$	$0.093 + 0.089 \cdot \text{SL}$
	t_{PLH}	0.177	$0.076 + 0.050 \cdot \text{SL}$	$0.077 + 0.050 \cdot \text{SL}$	$0.077 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.179	$0.093 + 0.043 \cdot \text{SL}$	$0.093 + 0.043 \cdot \text{SL}$	$0.093 + 0.043 \cdot \text{SL}$
C to Y	t_R	0.250	$0.142 + 0.054 \cdot \text{SL}$	$0.124 + 0.059 \cdot \text{SL}$	$0.101 + 0.061 \cdot \text{SL}$
	t_F	0.281	$0.109 + 0.086 \cdot \text{SL}$	$0.101 + 0.088 \cdot \text{SL}$	$0.093 + 0.089 \cdot \text{SL}$
	t_{PLH}	0.131	$0.077 + 0.027 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$	$0.081 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.174	$0.088 + 0.043 \cdot \text{SL}$	$0.089 + 0.043 \cdot \text{SL}$	$0.090 + 0.043 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA21DH/OA21/OA21D2/OA21D2B/OA21D4

2-OR into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.220	$0.121 + 0.050 \cdot \text{SL}$	$0.108 + 0.053 \cdot \text{SL}$	$0.090 + 0.055 \cdot \text{SL}$
	t_F	0.166	$0.090 + 0.038 \cdot \text{SL}$	$0.079 + 0.041 \cdot \text{SL}$	$0.062 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.116	$0.067 + 0.025 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.070 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.110	$0.066 + 0.022 \cdot \text{SL}$	$0.071 + 0.021 \cdot \text{SL}$	$0.071 + 0.021 \cdot \text{SL}$
B to Y	t_R	0.212	$0.109 + 0.052 \cdot \text{SL}$	$0.099 + 0.054 \cdot \text{SL}$	$0.090 + 0.055 \cdot \text{SL}$
	t_F	0.200	$0.124 + 0.038 \cdot \text{SL}$	$0.113 + 0.041 \cdot \text{SL}$	$0.095 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.116	$0.067 + 0.025 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.131	$0.089 + 0.021 \cdot \text{SL}$	$0.090 + 0.021 \cdot \text{SL}$	$0.089 + 0.021 \cdot \text{SL}$
C to Y	t_R	0.154	$0.108 + 0.023 \cdot \text{SL}$	$0.096 + 0.026 \cdot \text{SL}$	$0.082 + 0.028 \cdot \text{SL}$
	t_F	0.188	$0.108 + 0.040 \cdot \text{SL}$	$0.099 + 0.042 \cdot \text{SL}$	$0.092 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.096	$0.068 + 0.014 \cdot \text{SL}$	$0.075 + 0.012 \cdot \text{SL}$	$0.075 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.122	$0.079 + 0.022 \cdot \text{SL}$	$0.081 + 0.021 \cdot \text{SL}$	$0.082 + 0.021 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.173	$0.126 + 0.023 \cdot \text{SL}$	$0.117 + 0.026 \cdot \text{SL}$	$0.096 + 0.027 \cdot \text{SL}$
	t_F	0.129	$0.094 + 0.018 \cdot \text{SL}$	$0.086 + 0.020 \cdot \text{SL}$	$0.066 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.092	$0.065 + 0.014 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.088	$0.063 + 0.012 \cdot \text{SL}$	$0.072 + 0.010 \cdot \text{SL}$	$0.072 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.164	$0.115 + 0.024 \cdot \text{SL}$	$0.106 + 0.027 \cdot \text{SL}$	$0.093 + 0.027 \cdot \text{SL}$
	t_F	0.165	$0.129 + 0.018 \cdot \text{SL}$	$0.121 + 0.020 \cdot \text{SL}$	$0.100 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.092	$0.066 + 0.013 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.110	$0.088 + 0.011 \cdot \text{SL}$	$0.091 + 0.010 \cdot \text{SL}$	$0.090 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.129	$0.107 + 0.011 \cdot \text{SL}$	$0.101 + 0.012 \cdot \text{SL}$	$0.082 + 0.014 \cdot \text{SL}$
	t_F	0.148	$0.108 + 0.020 \cdot \text{SL}$	$0.105 + 0.021 \cdot \text{SL}$	$0.095 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.082	$0.066 + 0.008 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.100	$0.077 + 0.011 \cdot \text{SL}$	$0.081 + 0.011 \cdot \text{SL}$	$0.081 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA21DH/OA21/OA21D2/OA21D2B/OA21D4

2-OR into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA21D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.069	$0.044 + 0.013 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.219	$0.203 + 0.008 \cdot \text{SL}$	$0.208 + 0.007 \cdot \text{SL}$	$0.214 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.206	$0.188 + 0.009 \cdot \text{SL}$	$0.195 + 0.007 \cdot \text{SL}$	$0.205 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.048 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.220	$0.203 + 0.008 \cdot \text{SL}$	$0.209 + 0.007 \cdot \text{SL}$	$0.215 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.214 + 0.009 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$	$0.231 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.077	$0.050 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.207	$0.191 + 0.008 \cdot \text{SL}$	$0.196 + 0.007 \cdot \text{SL}$	$0.202 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.223	$0.205 + 0.009 \cdot \text{SL}$	$0.212 + 0.007 \cdot \text{SL}$	$0.222 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA21D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.054 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.240	$0.231 + 0.005 \cdot \text{SL}$	$0.236 + 0.003 \cdot \text{SL}$	$0.246 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.225	$0.215 + 0.005 \cdot \text{SL}$	$0.220 + 0.004 \cdot \text{SL}$	$0.235 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.241	$0.231 + 0.005 \cdot \text{SL}$	$0.236 + 0.003 \cdot \text{SL}$	$0.246 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.251	$0.241 + 0.005 \cdot \text{SL}$	$0.246 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.071	$0.058 + 0.007 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$	$0.047 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.054 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.222	$0.213 + 0.005 \cdot \text{SL}$	$0.217 + 0.003 \cdot \text{SL}$	$0.227 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.242	$0.232 + 0.005 \cdot \text{SL}$	$0.237 + 0.004 \cdot \text{SL}$	$0.252 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA211DH/OA211/OA211D2/OA211D2B/OA211D4

2-OR into 3-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)																			
OA211DH				OA211				OA211D2				OA211D2B				OA211D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.1	0.9	0.9	2.1	2.1	1.9	1.8	1.0	1.1	0.9	1.0	1.0	1.1	0.9	1.0
Gate Count																			
OA211DH				OA211				OA211D2				OA211D2B				OA211D4			
1.67				1.67				2.67				2.67				3.00			

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA211DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.373	$0.148 + 0.112 \cdot \text{SL}$	$0.132 + 0.116 \cdot \text{SL}$	$0.125 + 0.117 \cdot \text{SL}$
	t_F	0.329	$0.134 + 0.098 \cdot \text{SL}$	$0.118 + 0.102 \cdot \text{SL}$	$0.110 + 0.103 \cdot \text{SL}$
	t_{PLH}	0.191	$0.091 + 0.050 \cdot \text{SL}$	$0.090 + 0.050 \cdot \text{SL}$	$0.090 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.179	$0.085 + 0.047 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$	$0.083 + 0.047 \cdot \text{SL}$
B to Y	t_R	0.370	$0.142 + 0.114 \cdot \text{SL}$	$0.132 + 0.116 \cdot \text{SL}$	$0.125 + 0.117 \cdot \text{SL}$
	t_F	0.364	$0.172 + 0.096 \cdot \text{SL}$	$0.154 + 0.101 \cdot \text{SL}$	$0.145 + 0.102 \cdot \text{SL}$
	t_{PLH}	0.192	$0.092 + 0.050 \cdot \text{SL}$	$0.092 + 0.050 \cdot \text{SL}$	$0.092 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.199	$0.105 + 0.047 \cdot \text{SL}$	$0.104 + 0.047 \cdot \text{SL}$	$0.104 + 0.047 \cdot \text{SL}$
C to Y	t_R	0.346	$0.187 + 0.079 \cdot \text{SL}$	$0.170 + 0.084 \cdot \text{SL}$	$0.155 + 0.085 \cdot \text{SL}$
	t_F	0.360	$0.163 + 0.099 \cdot \text{SL}$	$0.153 + 0.101 \cdot \text{SL}$	$0.146 + 0.102 \cdot \text{SL}$
	t_{PLH}	0.182	$0.107 + 0.037 \cdot \text{SL}$	$0.109 + 0.037 \cdot \text{SL}$	$0.111 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.211	$0.116 + 0.048 \cdot \text{SL}$	$0.117 + 0.047 \cdot \text{SL}$	$0.118 + 0.047 \cdot \text{SL}$
D to Y	t_R	0.368	$0.210 + 0.079 \cdot \text{SL}$	$0.192 + 0.084 \cdot \text{SL}$	$0.176 + 0.085 \cdot \text{SL}$
	t_F	0.358	$0.158 + 0.100 \cdot \text{SL}$	$0.151 + 0.101 \cdot \text{SL}$	$0.146 + 0.102 \cdot \text{SL}$
	t_{PLH}	0.192	$0.117 + 0.038 \cdot \text{SL}$	$0.119 + 0.037 \cdot \text{SL}$	$0.121 + 0.037 \cdot \text{SL}$
	t_{PHL}	0.209	$0.114 + 0.048 \cdot \text{SL}$	$0.115 + 0.047 \cdot \text{SL}$	$0.116 + 0.047 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA211DH/OA211/OA211D2/OA211D2B/OA211D4

2-OR into 3-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA211

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.242	$0.139 + 0.051 \cdot \text{SL}$	$0.129 + 0.054 \cdot \text{SL}$	$0.114 + 0.056 \cdot \text{SL}$
	t_F	0.218	$0.126 + 0.046 \cdot \text{SL}$	$0.116 + 0.049 \cdot \text{SL}$	$0.101 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.130	$0.081 + 0.024 \cdot \text{SL}$	$0.083 + 0.024 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.126	$0.079 + 0.024 \cdot \text{SL}$	$0.080 + 0.023 \cdot \text{SL}$	$0.079 + 0.023 \cdot \text{SL}$
B to Y	t_R	0.236	$0.130 + 0.053 \cdot \text{SL}$	$0.123 + 0.055 \cdot \text{SL}$	$0.114 + 0.056 \cdot \text{SL}$
	t_F	0.254	$0.163 + 0.045 \cdot \text{SL}$	$0.153 + 0.048 \cdot \text{SL}$	$0.137 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.130	$0.080 + 0.025 \cdot \text{SL}$	$0.083 + 0.024 \cdot \text{SL}$	$0.083 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.145	$0.100 + 0.023 \cdot \text{SL}$	$0.099 + 0.023 \cdot \text{SL}$	$0.099 + 0.023 \cdot \text{SL}$
C to Y	t_R	0.203	$0.133 + 0.035 \cdot \text{SL}$	$0.125 + 0.037 \cdot \text{SL}$	$0.111 + 0.039 \cdot \text{SL}$
	t_F	0.246	$0.152 + 0.047 \cdot \text{SL}$	$0.145 + 0.049 \cdot \text{SL}$	$0.138 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.132	$0.097 + 0.017 \cdot \text{SL}$	$0.099 + 0.017 \cdot \text{SL}$	$0.098 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.153	$0.106 + 0.024 \cdot \text{SL}$	$0.107 + 0.023 \cdot \text{SL}$	$0.108 + 0.023 \cdot \text{SL}$
D to Y	t_R	0.222	$0.152 + 0.035 \cdot \text{SL}$	$0.144 + 0.037 \cdot \text{SL}$	$0.129 + 0.039 \cdot \text{SL}$
	t_F	0.242	$0.147 + 0.048 \cdot \text{SL}$	$0.141 + 0.049 \cdot \text{SL}$	$0.136 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.140	$0.106 + 0.017 \cdot \text{SL}$	$0.107 + 0.017 \cdot \text{SL}$	$0.107 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.151	$0.104 + 0.024 \cdot \text{SL}$	$0.105 + 0.023 \cdot \text{SL}$	$0.106 + 0.023 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA211D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.193	$0.142 + 0.025 \cdot \text{SL}$	$0.137 + 0.026 \cdot \text{SL}$	$0.119 + 0.028 \cdot \text{SL}$
	t_F	0.173	$0.128 + 0.023 \cdot \text{SL}$	$0.123 + 0.024 \cdot \text{SL}$	$0.107 + 0.025 \cdot \text{SL}$
	t_{PLH}	0.106	$0.080 + 0.013 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$	$0.084 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.103	$0.078 + 0.012 \cdot \text{SL}$	$0.081 + 0.011 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$
B to Y	t_R	0.185	$0.135 + 0.025 \cdot \text{SL}$	$0.129 + 0.027 \cdot \text{SL}$	$0.118 + 0.028 \cdot \text{SL}$
	t_F	0.214	$0.169 + 0.023 \cdot \text{SL}$	$0.163 + 0.024 \cdot \text{SL}$	$0.145 + 0.025 \cdot \text{SL}$
	t_{PLH}	0.106	$0.080 + 0.013 \cdot \text{SL}$	$0.084 + 0.012 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.125	$0.102 + 0.012 \cdot \text{SL}$	$0.102 + 0.012 \cdot \text{SL}$	$0.102 + 0.012 \cdot \text{SL}$
C to Y	t_R	0.171	$0.138 + 0.017 \cdot \text{SL}$	$0.131 + 0.018 \cdot \text{SL}$	$0.116 + 0.019 \cdot \text{SL}$
	t_F	0.205	$0.158 + 0.023 \cdot \text{SL}$	$0.153 + 0.025 \cdot \text{SL}$	$0.144 + 0.025 \cdot \text{SL}$
	t_{PLH}	0.115	$0.098 + 0.009 \cdot \text{SL}$	$0.100 + 0.008 \cdot \text{SL}$	$0.099 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.132	$0.108 + 0.012 \cdot \text{SL}$	$0.110 + 0.012 \cdot \text{SL}$	$0.111 + 0.012 \cdot \text{SL}$
D to Y	t_R	0.190	$0.157 + 0.017 \cdot \text{SL}$	$0.151 + 0.018 \cdot \text{SL}$	$0.136 + 0.019 \cdot \text{SL}$
	t_F	0.201	$0.152 + 0.024 \cdot \text{SL}$	$0.149 + 0.025 \cdot \text{SL}$	$0.142 + 0.025 \cdot \text{SL}$
	t_{PLH}	0.125	$0.107 + 0.009 \cdot \text{SL}$	$0.108 + 0.008 \cdot \text{SL}$	$0.108 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.130	$0.106 + 0.012 \cdot \text{SL}$	$0.107 + 0.012 \cdot \text{SL}$	$0.109 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA211DH/OA211/OA211D2/OA211D2B/OA211D4

2-OR into 3-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA211D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.237	$0.221 + 0.008 \cdot \text{SL}$	$0.227 + 0.007 \cdot \text{SL}$	$0.233 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.230	$0.212 + 0.009 \cdot \text{SL}$	$0.219 + 0.007 \cdot \text{SL}$	$0.229 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.238	$0.222 + 0.008 \cdot \text{SL}$	$0.227 + 0.007 \cdot \text{SL}$	$0.233 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.256	$0.238 + 0.009 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$	$0.255 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.248	$0.232 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.243 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.263	$0.245 + 0.009 \cdot \text{SL}$	$0.252 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.258	$0.242 + 0.008 \cdot \text{SL}$	$0.247 + 0.007 \cdot \text{SL}$	$0.253 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.261	$0.243 + 0.009 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA211D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.260	$0.250 + 0.005 \cdot \text{SL}$	$0.255 + 0.003 \cdot \text{SL}$	$0.265 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.251	$0.240 + 0.005 \cdot \text{SL}$	$0.246 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.056 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.260	$0.250 + 0.005 \cdot \text{SL}$	$0.255 + 0.003 \cdot \text{SL}$	$0.266 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.277	$0.266 + 0.005 \cdot \text{SL}$	$0.272 + 0.004 \cdot \text{SL}$	$0.287 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.267	$0.258 + 0.005 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$	$0.273 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.285	$0.275 + 0.005 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$	$0.296 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.055 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.279	$0.269 + 0.005 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$	$0.285 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.284	$0.273 + 0.005 \cdot \text{SL}$	$0.279 + 0.004 \cdot \text{SL}$	$0.294 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA2111/OA2111D2

2-OR into 4-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	1
x	x	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
OA2111					OA2111D2					OA2111	OA2111D2
A	B	C	D	E	A	B	C	D	E		
1.0	1.0	0.8	0.8	0.9	1.0	1.0	0.8	0.8	0.9	2.00	2.67

OA2111/OA2111D2

2-OR into 4-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA2111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.279	$0.161 + 0.059 \cdot \text{SL}$	$0.151 + 0.062 \cdot \text{SL}$	$0.138 + 0.063 \cdot \text{SL}$
	t_F	0.291	$0.172 + 0.059 \cdot \text{SL}$	$0.163 + 0.062 \cdot \text{SL}$	$0.150 + 0.063 \cdot \text{SL}$
	t_{PLH}	0.150	$0.096 + 0.027 \cdot \text{SL}$	$0.096 + 0.027 \cdot \text{SL}$	$0.096 + 0.027 \cdot \text{SL}$
	t_{PHL}	0.146	$0.091 + 0.028 \cdot \text{SL}$	$0.089 + 0.028 \cdot \text{SL}$	$0.088 + 0.028 \cdot \text{SL}$
B to Y	t_R	0.274	$0.154 + 0.060 \cdot \text{SL}$	$0.147 + 0.062 \cdot \text{SL}$	$0.140 + 0.063 \cdot \text{SL}$
	t_F	0.330	$0.214 + 0.058 \cdot \text{SL}$	$0.203 + 0.061 \cdot \text{SL}$	$0.189 + 0.063 \cdot \text{SL}$
	t_{PLH}	0.150	$0.095 + 0.027 \cdot \text{SL}$	$0.097 + 0.027 \cdot \text{SL}$	$0.097 + 0.027 \cdot \text{SL}$
	t_{PHL}	0.167	$0.111 + 0.028 \cdot \text{SL}$	$0.110 + 0.028 \cdot \text{SL}$	$0.110 + 0.028 \cdot \text{SL}$
C to Y	t_R	0.249	$0.160 + 0.044 \cdot \text{SL}$	$0.153 + 0.046 \cdot \text{SL}$	$0.141 + 0.048 \cdot \text{SL}$
	t_F	0.328	$0.207 + 0.060 \cdot \text{SL}$	$0.202 + 0.062 \cdot \text{SL}$	$0.194 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.159	$0.118 + 0.021 \cdot \text{SL}$	$0.118 + 0.021 \cdot \text{SL}$	$0.118 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.188	$0.130 + 0.029 \cdot \text{SL}$	$0.131 + 0.029 \cdot \text{SL}$	$0.132 + 0.028 \cdot \text{SL}$
D to Y	t_R	0.271	$0.182 + 0.044 \cdot \text{SL}$	$0.175 + 0.046 \cdot \text{SL}$	$0.163 + 0.048 \cdot \text{SL}$
	t_F	0.326	$0.205 + 0.060 \cdot \text{SL}$	$0.201 + 0.062 \cdot \text{SL}$	$0.194 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.171	$0.129 + 0.021 \cdot \text{SL}$	$0.130 + 0.021 \cdot \text{SL}$	$0.130 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.193	$0.135 + 0.029 \cdot \text{SL}$	$0.136 + 0.029 \cdot \text{SL}$	$0.138 + 0.028 \cdot \text{SL}$
E to Y	t_R	0.295	$0.206 + 0.044 \cdot \text{SL}$	$0.199 + 0.046 \cdot \text{SL}$	$0.186 + 0.048 \cdot \text{SL}$
	t_F	0.323	$0.202 + 0.061 \cdot \text{SL}$	$0.198 + 0.062 \cdot \text{SL}$	$0.193 + 0.062 \cdot \text{SL}$
	t_{PLH}	0.180	$0.138 + 0.021 \cdot \text{SL}$	$0.139 + 0.021 \cdot \text{SL}$	$0.141 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.195	$0.137 + 0.029 \cdot \text{SL}$	$0.139 + 0.029 \cdot \text{SL}$	$0.141 + 0.028 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA2111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.052 + 0.014 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.250	$0.233 + 0.008 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$	$0.245 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.246	$0.228 + 0.009 \cdot \text{SL}$	$0.235 + 0.007 \cdot \text{SL}$	$0.245 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.080	$0.053 + 0.014 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.049 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.250	$0.233 + 0.008 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$	$0.245 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.276	$0.258 + 0.009 \cdot \text{SL}$	$0.266 + 0.007 \cdot \text{SL}$	$0.276 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.271	$0.255 + 0.008 \cdot \text{SL}$	$0.261 + 0.007 \cdot \text{SL}$	$0.267 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.295	$0.277 + 0.009 \cdot \text{SL}$	$0.285 + 0.007 \cdot \text{SL}$	$0.295 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.283	$0.267 + 0.008 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.300	$0.282 + 0.009 \cdot \text{SL}$	$0.290 + 0.007 \cdot \text{SL}$	$0.300 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.295	$0.279 + 0.008 \cdot \text{SL}$	$0.284 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.303	$0.285 + 0.009 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA22DH/OA22/OA22D2/OA22D2B/OA22D4

Two 2-ORs into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	0	0	1
Other States				0

Cell Data

Input Load (SL)																			
OA22DH				OA22				OA22D2				OA22D2B				OA22D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.9	1.0	0.9	1.0	1.8	1.9	1.8	1.9	0.9	1.0	1.0	1.0	0.9	1.0	1.0	1.0
Gate Count																			
OA22DH				OA22				OA22D2				OA22D2B				OA22D4			
1.67				1.67				3.00				2.67				3.00			

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA22DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.411	$0.191 + 0.110 \cdot \text{SL}$	$0.169 + 0.116 \cdot \text{SL}$	$0.158 + 0.117 \cdot \text{SL}$
	t_F	0.358	$0.141 + 0.108 \cdot \text{SL}$	$0.127 + 0.112 \cdot \text{SL}$	$0.124 + 0.112 \cdot \text{SL}$
	t_{PLH}	0.186	$0.084 + 0.051 \cdot \text{SL}$	$0.086 + 0.050 \cdot \text{SL}$	$0.089 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.218	$0.110 + 0.054 \cdot \text{SL}$	$0.111 + 0.054 \cdot \text{SL}$	$0.112 + 0.054 \cdot \text{SL}$
B to Y	t_R	0.406	$0.181 + 0.113 \cdot \text{SL}$	$0.167 + 0.116 \cdot \text{SL}$	$0.158 + 0.117 \cdot \text{SL}$
	t_F	0.398	$0.182 + 0.108 \cdot \text{SL}$	$0.168 + 0.112 \cdot \text{SL}$	$0.164 + 0.112 \cdot \text{SL}$
	t_{PLH}	0.187	$0.084 + 0.052 \cdot \text{SL}$	$0.088 + 0.051 \cdot \text{SL}$	$0.091 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.242	$0.134 + 0.054 \cdot \text{SL}$	$0.135 + 0.054 \cdot \text{SL}$	$0.136 + 0.054 \cdot \text{SL}$
C to Y	t_R	0.460	$0.240 + 0.110 \cdot \text{SL}$	$0.218 + 0.116 \cdot \text{SL}$	$0.207 + 0.117 \cdot \text{SL}$
	t_F	0.355	$0.135 + 0.110 \cdot \text{SL}$	$0.127 + 0.112 \cdot \text{SL}$	$0.124 + 0.112 \cdot \text{SL}$
	t_{PLH}	0.216	$0.114 + 0.051 \cdot \text{SL}$	$0.117 + 0.050 \cdot \text{SL}$	$0.119 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.235	$0.126 + 0.055 \cdot \text{SL}$	$0.129 + 0.054 \cdot \text{SL}$	$0.131 + 0.054 \cdot \text{SL}$
D to Y	t_R	0.455	$0.230 + 0.113 \cdot \text{SL}$	$0.217 + 0.116 \cdot \text{SL}$	$0.207 + 0.117 \cdot \text{SL}$
	t_F	0.395	$0.175 + 0.110 \cdot \text{SL}$	$0.167 + 0.112 \cdot \text{SL}$	$0.164 + 0.112 \cdot \text{SL}$
	t_{PLH}	0.218	$0.115 + 0.052 \cdot \text{SL}$	$0.119 + 0.051 \cdot \text{SL}$	$0.122 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.259	$0.151 + 0.054 \cdot \text{SL}$	$0.153 + 0.054 \cdot \text{SL}$	$0.155 + 0.054 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA22DH/OA22/OA22D2/OA22D2B/OA22D4

Two 2-ORs into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.283	$0.185 + 0.049 \cdot \text{SL}$	$0.171 + 0.053 \cdot \text{SL}$	$0.152 + 0.055 \cdot \text{SL}$
	t_F	0.236	$0.133 + 0.052 \cdot \text{SL}$	$0.126 + 0.054 \cdot \text{SL}$	$0.113 + 0.055 \cdot \text{SL}$
	t_{PLH}	0.125	$0.075 + 0.025 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$	$0.081 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.160	$0.107 + 0.026 \cdot \text{SL}$	$0.107 + 0.026 \cdot \text{SL}$	$0.108 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.274	$0.172 + 0.051 \cdot \text{SL}$	$0.161 + 0.054 \cdot \text{SL}$	$0.152 + 0.055 \cdot \text{SL}$
	t_F	0.275	$0.173 + 0.051 \cdot \text{SL}$	$0.165 + 0.053 \cdot \text{SL}$	$0.152 + 0.055 \cdot \text{SL}$
	t_{PLH}	0.125	$0.075 + 0.025 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.182	$0.130 + 0.026 \cdot \text{SL}$	$0.130 + 0.026 \cdot \text{SL}$	$0.131 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.315	$0.216 + 0.050 \cdot \text{SL}$	$0.204 + 0.053 \cdot \text{SL}$	$0.184 + 0.055 \cdot \text{SL}$
	t_F	0.231	$0.127 + 0.052 \cdot \text{SL}$	$0.121 + 0.054 \cdot \text{SL}$	$0.113 + 0.055 \cdot \text{SL}$
	t_{PLH}	0.147	$0.098 + 0.024 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.164	$0.110 + 0.027 \cdot \text{SL}$	$0.112 + 0.026 \cdot \text{SL}$	$0.114 + 0.026 \cdot \text{SL}$
D to Y	t_R	0.307	$0.203 + 0.052 \cdot \text{SL}$	$0.195 + 0.054 \cdot \text{SL}$	$0.184 + 0.055 \cdot \text{SL}$
	t_F	0.270	$0.166 + 0.052 \cdot \text{SL}$	$0.160 + 0.054 \cdot \text{SL}$	$0.153 + 0.054 \cdot \text{SL}$
	t_{PLH}	0.147	$0.098 + 0.025 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$	$0.103 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.187	$0.134 + 0.027 \cdot \text{SL}$	$0.136 + 0.026 \cdot \text{SL}$	$0.137 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.236	$0.189 + 0.024 \cdot \text{SL}$	$0.180 + 0.026 \cdot \text{SL}$	$0.158 + 0.027 \cdot \text{SL}$
	t_F	0.189	$0.138 + 0.026 \cdot \text{SL}$	$0.132 + 0.027 \cdot \text{SL}$	$0.118 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.100	$0.072 + 0.014 \cdot \text{SL}$	$0.078 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.135	$0.108 + 0.014 \cdot \text{SL}$	$0.109 + 0.013 \cdot \text{SL}$	$0.110 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.226	$0.176 + 0.025 \cdot \text{SL}$	$0.169 + 0.027 \cdot \text{SL}$	$0.156 + 0.028 \cdot \text{SL}$
	t_F	0.228	$0.177 + 0.025 \cdot \text{SL}$	$0.172 + 0.027 \cdot \text{SL}$	$0.157 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.100	$0.073 + 0.013 \cdot \text{SL}$	$0.078 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.158	$0.131 + 0.013 \cdot \text{SL}$	$0.132 + 0.013 \cdot \text{SL}$	$0.133 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.265	$0.218 + 0.024 \cdot \text{SL}$	$0.209 + 0.026 \cdot \text{SL}$	$0.186 + 0.027 \cdot \text{SL}$
	t_F	0.183	$0.130 + 0.026 \cdot \text{SL}$	$0.126 + 0.027 \cdot \text{SL}$	$0.117 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.120	$0.094 + 0.013 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$	$0.099 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.137	$0.109 + 0.014 \cdot \text{SL}$	$0.111 + 0.013 \cdot \text{SL}$	$0.114 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.254	$0.204 + 0.025 \cdot \text{SL}$	$0.198 + 0.027 \cdot \text{SL}$	$0.184 + 0.028 \cdot \text{SL}$
	t_F	0.221	$0.169 + 0.026 \cdot \text{SL}$	$0.165 + 0.027 \cdot \text{SL}$	$0.157 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.120	$0.094 + 0.013 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$	$0.100 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.161	$0.134 + 0.014 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$	$0.138 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA22DH/OA22/OA22D2/OA22D2B/OA22D4

Two 2-ORs into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA22D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.081	$0.056 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.243	$0.227 + 0.008 \cdot \text{SL}$	$0.232 + 0.007 \cdot \text{SL}$	$0.239 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.259	$0.242 + 0.009 \cdot \text{SL}$	$0.249 + 0.007 \cdot \text{SL}$	$0.258 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.244	$0.227 + 0.008 \cdot \text{SL}$	$0.233 + 0.007 \cdot \text{SL}$	$0.239 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.290	$0.272 + 0.009 \cdot \text{SL}$	$0.280 + 0.007 \cdot \text{SL}$	$0.289 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.266	$0.249 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.263	$0.245 + 0.009 \cdot \text{SL}$	$0.253 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.266	$0.250 + 0.008 \cdot \text{SL}$	$0.256 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.291	$0.273 + 0.009 \cdot \text{SL}$	$0.281 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA22D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.062 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.057 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.262	$0.253 + 0.005 \cdot \text{SL}$	$0.258 + 0.004 \cdot \text{SL}$	$0.269 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.282	$0.271 + 0.005 \cdot \text{SL}$	$0.277 + 0.004 \cdot \text{SL}$	$0.292 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.076	$0.062 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.263	$0.254 + 0.005 \cdot \text{SL}$	$0.259 + 0.004 \cdot \text{SL}$	$0.270 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.313	$0.302 + 0.005 \cdot \text{SL}$	$0.307 + 0.004 \cdot \text{SL}$	$0.323 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.056 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.283	$0.274 + 0.005 \cdot \text{SL}$	$0.279 + 0.004 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.278	$0.267 + 0.005 \cdot \text{SL}$	$0.273 + 0.004 \cdot \text{SL}$	$0.288 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.007 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.285	$0.275 + 0.005 \cdot \text{SL}$	$0.280 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.316	$0.305 + 0.005 \cdot \text{SL}$	$0.311 + 0.004 \cdot \text{SL}$	$0.326 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA22DHA/OA22A/OA22D2A/OA22D4A

2-OR and 2-NAND into 2-NAND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	1	1	1
Other States				0

Cell Data

Input Load (SL)															
OA22DHA				OA22A				OA22D2A				OA22D4A			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.6	0.9	1.0	1.1	1.1	1.9	1.9	1.1	1.1	0.9	1.0	1.1	1.1
Gate Count															
OA22DHA				OA22A				OA22D2A				OA22D4A			
2.00				2.00				2.67				3.67			

OA22DHA/OA22A/OA22D2A/OA22D4A

2-OR and 2-NAND into 2-NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA22DHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.349	$0.127 + 0.111 \cdot \text{SL}$	$0.107 + 0.116 \cdot \text{SL}$	$0.097 + 0.117 \cdot \text{SL}$
	t_F	0.255	$0.093 + 0.081 \cdot \text{SL}$	$0.074 + 0.086 \cdot \text{SL}$	$0.062 + 0.087 \cdot \text{SL}$
	t_{PLH}	0.177	$0.078 + 0.050 \cdot \text{SL}$	$0.077 + 0.050 \cdot \text{SL}$	$0.076 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.159	$0.075 + 0.042 \cdot \text{SL}$	$0.075 + 0.042 \cdot \text{SL}$	$0.074 + 0.042 \cdot \text{SL}$
B to Y	t_R	0.344	$0.118 + 0.113 \cdot \text{SL}$	$0.106 + 0.116 \cdot \text{SL}$	$0.097 + 0.117 \cdot \text{SL}$
	t_F	0.289	$0.127 + 0.081 \cdot \text{SL}$	$0.107 + 0.086 \cdot \text{SL}$	$0.094 + 0.088 \cdot \text{SL}$
	t_{PLH}	0.178	$0.077 + 0.050 \cdot \text{SL}$	$0.078 + 0.050 \cdot \text{SL}$	$0.077 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.177	$0.093 + 0.042 \cdot \text{SL}$	$0.093 + 0.042 \cdot \text{SL}$	$0.093 + 0.042 \cdot \text{SL}$
C to Y	t_R	0.237	$0.122 + 0.058 \cdot \text{SL}$	$0.111 + 0.061 \cdot \text{SL}$	$0.103 + 0.061 \cdot \text{SL}$
	t_F	0.273	$0.100 + 0.087 \cdot \text{SL}$	$0.097 + 0.087 \cdot \text{SL}$	$0.094 + 0.088 \cdot \text{SL}$
	t_{PLH}	0.194	$0.138 + 0.028 \cdot \text{SL}$	$0.142 + 0.027 \cdot \text{SL}$	$0.145 + 0.027 \cdot \text{SL}$
	t_{PHL}	0.246	$0.160 + 0.043 \cdot \text{SL}$	$0.163 + 0.043 \cdot \text{SL}$	$0.165 + 0.042 \cdot \text{SL}$
D to Y	t_R	0.237	$0.121 + 0.058 \cdot \text{SL}$	$0.111 + 0.061 \cdot \text{SL}$	$0.103 + 0.061 \cdot \text{SL}$
	t_F	0.274	$0.102 + 0.086 \cdot \text{SL}$	$0.098 + 0.087 \cdot \text{SL}$	$0.095 + 0.088 \cdot \text{SL}$
	t_{PLH}	0.190	$0.133 + 0.028 \cdot \text{SL}$	$0.138 + 0.027 \cdot \text{SL}$	$0.141 + 0.027 \cdot \text{SL}$
	t_{PHL}	0.259	$0.172 + 0.043 \cdot \text{SL}$	$0.175 + 0.042 \cdot \text{SL}$	$0.177 + 0.042 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA22A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.222	$0.122 + 0.050 \cdot \text{SL}$	$0.109 + 0.053 \cdot \text{SL}$	$0.092 + 0.055 \cdot \text{SL}$
	t_F	0.166	$0.091 + 0.038 \cdot \text{SL}$	$0.080 + 0.041 \cdot \text{SL}$	$0.063 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.117	$0.068 + 0.025 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.070 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.111	$0.067 + 0.022 \cdot \text{SL}$	$0.072 + 0.021 \cdot \text{SL}$	$0.071 + 0.021 \cdot \text{SL}$
B to Y	t_R	0.213	$0.110 + 0.052 \cdot \text{SL}$	$0.101 + 0.054 \cdot \text{SL}$	$0.092 + 0.055 \cdot \text{SL}$
	t_F	0.200	$0.124 + 0.038 \cdot \text{SL}$	$0.113 + 0.041 \cdot \text{SL}$	$0.096 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.117	$0.067 + 0.025 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.130	$0.088 + 0.021 \cdot \text{SL}$	$0.090 + 0.021 \cdot \text{SL}$	$0.089 + 0.021 \cdot \text{SL}$
C to Y	t_R	0.133	$0.079 + 0.027 \cdot \text{SL}$	$0.076 + 0.028 \cdot \text{SL}$	$0.070 + 0.028 \cdot \text{SL}$
	t_F	0.178	$0.094 + 0.042 \cdot \text{SL}$	$0.091 + 0.043 \cdot \text{SL}$	$0.088 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.152	$0.125 + 0.014 \cdot \text{SL}$	$0.129 + 0.013 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.188	$0.145 + 0.022 \cdot \text{SL}$	$0.147 + 0.021 \cdot \text{SL}$	$0.150 + 0.021 \cdot \text{SL}$
D to Y	t_R	0.133	$0.079 + 0.027 \cdot \text{SL}$	$0.075 + 0.028 \cdot \text{SL}$	$0.070 + 0.028 \cdot \text{SL}$
	t_F	0.178	$0.094 + 0.042 \cdot \text{SL}$	$0.092 + 0.043 \cdot \text{SL}$	$0.089 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.147	$0.120 + 0.014 \cdot \text{SL}$	$0.124 + 0.013 \cdot \text{SL}$	$0.126 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.201	$0.157 + 0.022 \cdot \text{SL}$	$0.160 + 0.021 \cdot \text{SL}$	$0.162 + 0.021 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA22DHA/OA22A/OA22D2A/OA22D4A

2-OR and 2-NAND into 2-NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA22D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.172	$0.124 + 0.024 \cdot \text{SL}$	$0.115 + 0.026 \cdot \text{SL}$	$0.094 + 0.028 \cdot \text{SL}$
	t_F	0.128	$0.093 + 0.018 \cdot \text{SL}$	$0.084 + 0.020 \cdot \text{SL}$	$0.066 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.092	$0.065 + 0.014 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.088	$0.063 + 0.013 \cdot \text{SL}$	$0.071 + 0.010 \cdot \text{SL}$	$0.071 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.163	$0.114 + 0.025 \cdot \text{SL}$	$0.105 + 0.027 \cdot \text{SL}$	$0.092 + 0.028 \cdot \text{SL}$
	t_F	0.164	$0.129 + 0.018 \cdot \text{SL}$	$0.120 + 0.020 \cdot \text{SL}$	$0.099 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.092	$0.065 + 0.013 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.109	$0.087 + 0.011 \cdot \text{SL}$	$0.090 + 0.010 \cdot \text{SL}$	$0.090 + 0.010 \cdot \text{SL}$
C to Y	t_R	0.113	$0.087 + 0.013 \cdot \text{SL}$	$0.085 + 0.014 \cdot \text{SL}$	$0.078 + 0.014 \cdot \text{SL}$
	t_F	0.138	$0.096 + 0.021 \cdot \text{SL}$	$0.094 + 0.022 \cdot \text{SL}$	$0.090 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.167	$0.152 + 0.008 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$	$0.161 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.181	$0.158 + 0.011 \cdot \text{SL}$	$0.160 + 0.011 \cdot \text{SL}$	$0.163 + 0.011 \cdot \text{SL}$
D to Y	t_R	0.113	$0.086 + 0.013 \cdot \text{SL}$	$0.086 + 0.014 \cdot \text{SL}$	$0.078 + 0.014 \cdot \text{SL}$
	t_F	0.140	$0.098 + 0.021 \cdot \text{SL}$	$0.096 + 0.021 \cdot \text{SL}$	$0.090 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.161	$0.145 + 0.008 \cdot \text{SL}$	$0.149 + 0.007 \cdot \text{SL}$	$0.155 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.191	$0.168 + 0.011 \cdot \text{SL}$	$0.170 + 0.011 \cdot \text{SL}$	$0.173 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA22D4A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.243	$0.234 + 0.005 \cdot \text{SL}$	$0.238 + 0.003 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.229	$0.218 + 0.005 \cdot \text{SL}$	$0.223 + 0.004 \cdot \text{SL}$	$0.239 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.053 + 0.007 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.244	$0.234 + 0.005 \cdot \text{SL}$	$0.239 + 0.003 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.254	$0.243 + 0.005 \cdot \text{SL}$	$0.249 + 0.004 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.072	$0.059 + 0.007 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.054 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.283	$0.274 + 0.005 \cdot \text{SL}$	$0.279 + 0.003 \cdot \text{SL}$	$0.289 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.311	$0.301 + 0.005 \cdot \text{SL}$	$0.306 + 0.004 \cdot \text{SL}$	$0.321 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.072	$0.058 + 0.007 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.048 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.278	$0.269 + 0.005 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$	$0.284 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.324	$0.313 + 0.005 \cdot \text{SL}$	$0.319 + 0.004 \cdot \text{SL}$	$0.334 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA221/OA221D2/OA221D4

Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	1
x	x	0	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)														
OA221					OA221D2					OA221D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.1	1.0
Gate Count														
OA221					OA221D2					OA221D4				
2.00					3.00					3.67				

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA221

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.317	$0.215 + 0.051 \cdot \text{SL}$	$0.205 + 0.054 \cdot \text{SL}$	$0.189 + 0.055 \cdot \text{SL}$
	t_F	0.286	$0.177 + 0.054 \cdot \text{SL}$	$0.171 + 0.056 \cdot \text{SL}$	$0.161 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.141	$0.092 + 0.025 \cdot \text{SL}$	$0.093 + 0.024 \cdot \text{SL}$	$0.096 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.173	$0.120 + 0.026 \cdot \text{SL}$	$0.121 + 0.026 \cdot \text{SL}$	$0.121 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.310	$0.205 + 0.052 \cdot \text{SL}$	$0.198 + 0.054 \cdot \text{SL}$	$0.188 + 0.055 \cdot \text{SL}$
	t_F	0.333	$0.224 + 0.054 \cdot \text{SL}$	$0.217 + 0.056 \cdot \text{SL}$	$0.206 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.144	$0.094 + 0.025 \cdot \text{SL}$	$0.096 + 0.024 \cdot \text{SL}$	$0.100 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.200	$0.147 + 0.027 \cdot \text{SL}$	$0.148 + 0.027 \cdot \text{SL}$	$0.148 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.351	$0.250 + 0.051 \cdot \text{SL}$	$0.239 + 0.054 \cdot \text{SL}$	$0.223 + 0.055 \cdot \text{SL}$
	t_F	0.280	$0.173 + 0.054 \cdot \text{SL}$	$0.168 + 0.055 \cdot \text{SL}$	$0.161 + 0.056 \cdot \text{SL}$
	t_{PLH}	0.164	$0.115 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$	$0.118 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.182	$0.129 + 0.026 \cdot \text{SL}$	$0.130 + 0.026 \cdot \text{SL}$	$0.132 + 0.026 \cdot \text{SL}$
D to Y	t_R	0.345	$0.240 + 0.052 \cdot \text{SL}$	$0.233 + 0.054 \cdot \text{SL}$	$0.223 + 0.055 \cdot \text{SL}$
	t_F	0.330	$0.219 + 0.056 \cdot \text{SL}$	$0.215 + 0.057 \cdot \text{SL}$	$0.208 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.166	$0.117 + 0.025 \cdot \text{SL}$	$0.118 + 0.024 \cdot \text{SL}$	$0.121 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.213	$0.159 + 0.027 \cdot \text{SL}$	$0.160 + 0.027 \cdot \text{SL}$	$0.162 + 0.027 \cdot \text{SL}$
E to Y	t_R	0.283	$0.228 + 0.027 \cdot \text{SL}$	$0.219 + 0.030 \cdot \text{SL}$	$0.200 + 0.032 \cdot \text{SL}$
	t_F	0.327	$0.214 + 0.056 \cdot \text{SL}$	$0.212 + 0.057 \cdot \text{SL}$	$0.207 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.133	$0.103 + 0.015 \cdot \text{SL}$	$0.104 + 0.015 \cdot \text{SL}$	$0.107 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.213	$0.159 + 0.027 \cdot \text{SL}$	$0.161 + 0.027 \cdot \text{SL}$	$0.163 + 0.027 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA221/OA221D2/OA221D4

Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA221D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.262	$0.245 + 0.008 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.258 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.283	$0.265 + 0.009 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.265	$0.248 + 0.008 \cdot \text{SL}$	$0.254 + 0.007 \cdot \text{SL}$	$0.260 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.317	$0.300 + 0.009 \cdot \text{SL}$	$0.307 + 0.007 \cdot \text{SL}$	$0.317 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.048 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.289	$0.273 + 0.008 \cdot \text{SL}$	$0.279 + 0.007 \cdot \text{SL}$	$0.286 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.291	$0.273 + 0.009 \cdot \text{SL}$	$0.281 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.291	$0.275 + 0.008 \cdot \text{SL}$	$0.281 + 0.007 \cdot \text{SL}$	$0.287 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.329	$0.311 + 0.009 \cdot \text{SL}$	$0.319 + 0.007 \cdot \text{SL}$	$0.329 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.082	$0.056 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.261	$0.245 + 0.008 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.256 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.330	$0.312 + 0.009 \cdot \text{SL}$	$0.319 + 0.007 \cdot \text{SL}$	$0.329 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA221D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.065 + 0.007 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.058 + 0.007 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.285	$0.275 + 0.005 \cdot \text{SL}$	$0.280 + 0.004 \cdot \text{SL}$	$0.291 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.309	$0.298 + 0.005 \cdot \text{SL}$	$0.304 + 0.004 \cdot \text{SL}$	$0.320 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.288	$0.278 + 0.005 \cdot \text{SL}$	$0.283 + 0.004 \cdot \text{SL}$	$0.294 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.345	$0.334 + 0.005 \cdot \text{SL}$	$0.340 + 0.004 \cdot \text{SL}$	$0.356 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.057 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.314	$0.304 + 0.005 \cdot \text{SL}$	$0.309 + 0.004 \cdot \text{SL}$	$0.320 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.319	$0.308 + 0.005 \cdot \text{SL}$	$0.314 + 0.004 \cdot \text{SL}$	$0.330 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.060 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.314	$0.305 + 0.005 \cdot \text{SL}$	$0.310 + 0.004 \cdot \text{SL}$	$0.321 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.356	$0.346 + 0.005 \cdot \text{SL}$	$0.351 + 0.004 \cdot \text{SL}$	$0.367 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.279	$0.269 + 0.005 \cdot \text{SL}$	$0.274 + 0.003 \cdot \text{SL}$	$0.284 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.358	$0.348 + 0.005 \cdot \text{SL}$	$0.353 + 0.004 \cdot \text{SL}$	$0.369 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	x	x	x	x	1
x	x	0	0	x	x	1
x	x	x	x	0	0	1
Other States						0

Cell Data

Input Load (SL)												Gate Count	
OA222						OA222D2						OA222	OA222D2
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	0.9	1.0	0.9	1.0	1.8	2.0	1.8	2.0	1.8	2.0	2.67	4.33
OA222D2B						OA222D4						OA222D2B	OA222D4
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0	0.9	1.0	3.33	4.00

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.374	$0.273 + 0.050 \cdot \text{SL}$	$0.263 + 0.053 \cdot \text{SL}$	$0.246 + 0.055 \cdot \text{SL}$
	t_F	0.398	$0.260 + 0.069 \cdot \text{SL}$	$0.255 + 0.071 \cdot \text{SL}$	$0.252 + 0.071 \cdot \text{SL}$
	t_{PLH}	0.152	$0.102 + 0.025 \cdot \text{SL}$	$0.104 + 0.024 \cdot \text{SL}$	$0.108 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.243	$0.176 + 0.033 \cdot \text{SL}$	$0.178 + 0.033 \cdot \text{SL}$	$0.179 + 0.033 \cdot \text{SL}$
B to Y	t_R	0.367	$0.263 + 0.052 \cdot \text{SL}$	$0.256 + 0.054 \cdot \text{SL}$	$0.246 + 0.055 \cdot \text{SL}$
	t_F	0.447	$0.309 + 0.069 \cdot \text{SL}$	$0.304 + 0.070 \cdot \text{SL}$	$0.301 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.153	$0.103 + 0.025 \cdot \text{SL}$	$0.105 + 0.024 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.272	$0.206 + 0.033 \cdot \text{SL}$	$0.207 + 0.033 \cdot \text{SL}$	$0.208 + 0.032 \cdot \text{SL}$
C to Y	t_R	0.411	$0.310 + 0.050 \cdot \text{SL}$	$0.299 + 0.053 \cdot \text{SL}$	$0.282 + 0.055 \cdot \text{SL}$
	t_F	0.401	$0.262 + 0.070 \cdot \text{SL}$	$0.258 + 0.071 \cdot \text{SL}$	$0.255 + 0.071 \cdot \text{SL}$
	t_{PLH}	0.176	$0.126 + 0.025 \cdot \text{SL}$	$0.128 + 0.024 \cdot \text{SL}$	$0.132 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.264	$0.197 + 0.034 \cdot \text{SL}$	$0.199 + 0.033 \cdot \text{SL}$	$0.202 + 0.033 \cdot \text{SL}$
D to Y	t_R	0.403	$0.299 + 0.052 \cdot \text{SL}$	$0.292 + 0.054 \cdot \text{SL}$	$0.282 + 0.055 \cdot \text{SL}$
	t_F	0.448	$0.309 + 0.069 \cdot \text{SL}$	$0.306 + 0.070 \cdot \text{SL}$	$0.302 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.177	$0.127 + 0.025 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$	$0.134 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.294	$0.228 + 0.033 \cdot \text{SL}$	$0.229 + 0.033 \cdot \text{SL}$	$0.231 + 0.033 \cdot \text{SL}$
E to Y	t_R	0.441	$0.341 + 0.050 \cdot \text{SL}$	$0.330 + 0.053 \cdot \text{SL}$	$0.312 + 0.055 \cdot \text{SL}$
	t_F	0.396	$0.258 + 0.069 \cdot \text{SL}$	$0.254 + 0.070 \cdot \text{SL}$	$0.252 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.191	$0.142 + 0.025 \cdot \text{SL}$	$0.144 + 0.024 \cdot \text{SL}$	$0.148 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.269	$0.201 + 0.034 \cdot \text{SL}$	$0.204 + 0.033 \cdot \text{SL}$	$0.207 + 0.033 \cdot \text{SL}$
F to Y	t_R	0.434	$0.330 + 0.052 \cdot \text{SL}$	$0.323 + 0.054 \cdot \text{SL}$	$0.312 + 0.055 \cdot \text{SL}$
	t_F	0.446	$0.307 + 0.070 \cdot \text{SL}$	$0.305 + 0.070 \cdot \text{SL}$	$0.302 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.193	$0.143 + 0.025 \cdot \text{SL}$	$0.145 + 0.024 \cdot \text{SL}$	$0.150 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.300	$0.234 + 0.033 \cdot \text{SL}$	$0.236 + 0.033 \cdot \text{SL}$	$0.238 + 0.033 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.318	$0.269 + 0.024 \cdot \text{SL}$	$0.263 + 0.026 \cdot \text{SL}$	$0.242 + 0.027 \cdot \text{SL}$
	t_F	0.319	$0.250 + 0.034 \cdot \text{SL}$	$0.247 + 0.035 \cdot \text{SL}$	$0.240 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.123	$0.097 + 0.013 \cdot \text{SL}$	$0.099 + 0.012 \cdot \text{SL}$	$0.104 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.205	$0.171 + 0.017 \cdot \text{SL}$	$0.172 + 0.016 \cdot \text{SL}$	$0.174 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.309	$0.257 + 0.026 \cdot \text{SL}$	$0.253 + 0.027 \cdot \text{SL}$	$0.240 + 0.028 \cdot \text{SL}$
	t_F	0.367	$0.298 + 0.034 \cdot \text{SL}$	$0.297 + 0.035 \cdot \text{SL}$	$0.290 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.125	$0.098 + 0.013 \cdot \text{SL}$	$0.101 + 0.012 \cdot \text{SL}$	$0.107 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.235	$0.202 + 0.017 \cdot \text{SL}$	$0.203 + 0.016 \cdot \text{SL}$	$0.204 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.351	$0.302 + 0.025 \cdot \text{SL}$	$0.295 + 0.026 \cdot \text{SL}$	$0.275 + 0.028 \cdot \text{SL}$
	t_F	0.322	$0.253 + 0.035 \cdot \text{SL}$	$0.250 + 0.035 \cdot \text{SL}$	$0.244 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.145	$0.121 + 0.012 \cdot \text{SL}$	$0.122 + 0.012 \cdot \text{SL}$	$0.126 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.222	$0.188 + 0.017 \cdot \text{SL}$	$0.190 + 0.017 \cdot \text{SL}$	$0.193 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.342	$0.291 + 0.025 \cdot \text{SL}$	$0.286 + 0.027 \cdot \text{SL}$	$0.274 + 0.028 \cdot \text{SL}$
	t_F	0.368	$0.298 + 0.035 \cdot \text{SL}$	$0.297 + 0.035 \cdot \text{SL}$	$0.291 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.147	$0.122 + 0.013 \cdot \text{SL}$	$0.123 + 0.012 \cdot \text{SL}$	$0.127 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.252	$0.219 + 0.017 \cdot \text{SL}$	$0.220 + 0.016 \cdot \text{SL}$	$0.223 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.382	$0.334 + 0.024 \cdot \text{SL}$	$0.327 + 0.026 \cdot \text{SL}$	$0.305 + 0.027 \cdot \text{SL}$
	t_F	0.316	$0.247 + 0.034 \cdot \text{SL}$	$0.245 + 0.035 \cdot \text{SL}$	$0.241 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.161	$0.136 + 0.013 \cdot \text{SL}$	$0.137 + 0.012 \cdot \text{SL}$	$0.142 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.227	$0.193 + 0.017 \cdot \text{SL}$	$0.195 + 0.017 \cdot \text{SL}$	$0.199 + 0.016 \cdot \text{SL}$
F to Y	t_R	0.373	$0.322 + 0.025 \cdot \text{SL}$	$0.317 + 0.027 \cdot \text{SL}$	$0.304 + 0.028 \cdot \text{SL}$
	t_F	0.366	$0.296 + 0.035 \cdot \text{SL}$	$0.295 + 0.035 \cdot \text{SL}$	$0.291 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.163	$0.138 + 0.013 \cdot \text{SL}$	$0.139 + 0.012 \cdot \text{SL}$	$0.144 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.260	$0.226 + 0.017 \cdot \text{SL}$	$0.227 + 0.016 \cdot \text{SL}$	$0.230 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA222D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.283	$0.266 + 0.008 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.359	$0.341 + 0.009 \cdot \text{SL}$	$0.349 + 0.007 \cdot \text{SL}$	$0.360 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.285	$0.268 + 0.008 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.281 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.398	$0.380 + 0.009 \cdot \text{SL}$	$0.388 + 0.007 \cdot \text{SL}$	$0.399 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.088	$0.063 + 0.012 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.056 + 0.011 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.008 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.380	$0.362 + 0.009 \cdot \text{SL}$	$0.370 + 0.007 \cdot \text{SL}$	$0.381 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.312	$0.296 + 0.008 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.419	$0.401 + 0.009 \cdot \text{SL}$	$0.408 + 0.007 \cdot \text{SL}$	$0.419 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.056 + 0.011 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.329	$0.313 + 0.008 \cdot \text{SL}$	$0.319 + 0.007 \cdot \text{SL}$	$0.326 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.384	$0.366 + 0.009 \cdot \text{SL}$	$0.373 + 0.007 \cdot \text{SL}$	$0.384 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.057 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.330	$0.314 + 0.008 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.424	$0.406 + 0.009 \cdot \text{SL}$	$0.413 + 0.007 \cdot \text{SL}$	$0.424 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA222D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.069 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.064 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.304	$0.294 + 0.005 \cdot \text{SL}$	$0.299 + 0.004 \cdot \text{SL}$	$0.311 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.386	$0.375 + 0.005 \cdot \text{SL}$	$0.381 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.082	$0.069 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.305	$0.296 + 0.005 \cdot \text{SL}$	$0.301 + 0.004 \cdot \text{SL}$	$0.313 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.425	$0.414 + 0.005 \cdot \text{SL}$	$0.420 + 0.004 \cdot \text{SL}$	$0.436 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.083	$0.069 + 0.007 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.064 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.332	$0.322 + 0.005 \cdot \text{SL}$	$0.327 + 0.004 \cdot \text{SL}$	$0.339 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.407	$0.396 + 0.005 \cdot \text{SL}$	$0.402 + 0.004 \cdot \text{SL}$	$0.418 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.084	$0.070 + 0.007 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.333	$0.323 + 0.005 \cdot \text{SL}$	$0.328 + 0.004 \cdot \text{SL}$	$0.340 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.446	$0.435 + 0.005 \cdot \text{SL}$	$0.440 + 0.004 \cdot \text{SL}$	$0.457 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.350	$0.340 + 0.005 \cdot \text{SL}$	$0.346 + 0.004 \cdot \text{SL}$	$0.358 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.410	$0.400 + 0.005 \cdot \text{SL}$	$0.406 + 0.004 \cdot \text{SL}$	$0.422 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.084	$0.071 + 0.007 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.352	$0.342 + 0.005 \cdot \text{SL}$	$0.347 + 0.004 \cdot \text{SL}$	$0.359 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.451	$0.440 + 0.005 \cdot \text{SL}$	$0.446 + 0.004 \cdot \text{SL}$	$0.462 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA2222/OA2222D2/OA2222D4

Four 2-ORs into 4-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	x	x	x	x	x	x	1
x	x	0	0	x	x	x	x	1
x	x	x	x	0	0	x	x	1
x	x	x	x	x	x	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
OA2222								OA2222
A	B	C	D	E	F	G	H	3.33
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
OA2222D2								OA2222D2
A	B	C	D	E	F	G	H	4.00
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
OA2222D4								OA2222D4
A	B	C	D	E	F	G	H	4.67
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	

OA2222/OA2222D2/OA2222D4

Four 2-ORs into 4-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA2222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.446	$0.344 + 0.051 \cdot \text{SL}$	$0.334 + 0.053 \cdot \text{SL}$	$0.318 + 0.055 \cdot \text{SL}$
	t_F	0.420	$0.283 + 0.069 \cdot \text{SL}$	$0.278 + 0.070 \cdot \text{SL}$	$0.275 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.172	$0.122 + 0.025 \cdot \text{SL}$	$0.125 + 0.024 \cdot \text{SL}$	$0.129 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.240	$0.176 + 0.032 \cdot \text{SL}$	$0.177 + 0.032 \cdot \text{SL}$	$0.178 + 0.032 \cdot \text{SL}$
B to Y	t_R	0.439	$0.335 + 0.052 \cdot \text{SL}$	$0.328 + 0.054 \cdot \text{SL}$	$0.318 + 0.055 \cdot \text{SL}$
	t_F	0.469	$0.332 + 0.069 \cdot \text{SL}$	$0.327 + 0.070 \cdot \text{SL}$	$0.324 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.174	$0.123 + 0.025 \cdot \text{SL}$	$0.126 + 0.024 \cdot \text{SL}$	$0.131 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.270	$0.206 + 0.032 \cdot \text{SL}$	$0.207 + 0.032 \cdot \text{SL}$	$0.208 + 0.032 \cdot \text{SL}$
C to Y	t_R	0.483	$0.381 + 0.051 \cdot \text{SL}$	$0.371 + 0.054 \cdot \text{SL}$	$0.356 + 0.055 \cdot \text{SL}$
	t_F	0.422	$0.285 + 0.069 \cdot \text{SL}$	$0.281 + 0.070 \cdot \text{SL}$	$0.277 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.200	$0.150 + 0.025 \cdot \text{SL}$	$0.152 + 0.024 \cdot \text{SL}$	$0.156 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.266	$0.200 + 0.033 \cdot \text{SL}$	$0.203 + 0.032 \cdot \text{SL}$	$0.205 + 0.032 \cdot \text{SL}$
D to Y	t_R	0.477	$0.372 + 0.052 \cdot \text{SL}$	$0.366 + 0.054 \cdot \text{SL}$	$0.357 + 0.055 \cdot \text{SL}$
	t_F	0.472	$0.335 + 0.069 \cdot \text{SL}$	$0.332 + 0.070 \cdot \text{SL}$	$0.328 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.202	$0.152 + 0.025 \cdot \text{SL}$	$0.154 + 0.024 \cdot \text{SL}$	$0.158 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.297	$0.232 + 0.033 \cdot \text{SL}$	$0.234 + 0.032 \cdot \text{SL}$	$0.236 + 0.032 \cdot \text{SL}$
E to Y	t_R	0.521	$0.420 + 0.050 \cdot \text{SL}$	$0.409 + 0.053 \cdot \text{SL}$	$0.393 + 0.055 \cdot \text{SL}$
	t_F	0.423	$0.285 + 0.069 \cdot \text{SL}$	$0.281 + 0.070 \cdot \text{SL}$	$0.279 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.220	$0.171 + 0.025 \cdot \text{SL}$	$0.172 + 0.024 \cdot \text{SL}$	$0.176 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.280	$0.214 + 0.033 \cdot \text{SL}$	$0.216 + 0.032 \cdot \text{SL}$	$0.219 + 0.032 \cdot \text{SL}$
F to Y	t_R	0.516	$0.411 + 0.052 \cdot \text{SL}$	$0.404 + 0.054 \cdot \text{SL}$	$0.394 + 0.055 \cdot \text{SL}$
	t_F	0.471	$0.333 + 0.069 \cdot \text{SL}$	$0.330 + 0.070 \cdot \text{SL}$	$0.328 + 0.070 \cdot \text{SL}$
	t_{PLH}	0.222	$0.172 + 0.025 \cdot \text{SL}$	$0.174 + 0.024 \cdot \text{SL}$	$0.178 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.311	$0.246 + 0.033 \cdot \text{SL}$	$0.247 + 0.032 \cdot \text{SL}$	$0.250 + 0.032 \cdot \text{SL}$
G to Y	t_R	0.562	$0.460 + 0.051 \cdot \text{SL}$	$0.449 + 0.054 \cdot \text{SL}$	$0.433 + 0.056 \cdot \text{SL}$
	t_F	0.538	$0.381 + 0.079 \cdot \text{SL}$	$0.380 + 0.079 \cdot \text{SL}$	$0.378 + 0.079 \cdot \text{SL}$
	t_{PLH}	0.239	$0.188 + 0.025 \cdot \text{SL}$	$0.190 + 0.025 \cdot \text{SL}$	$0.195 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.367	$0.293 + 0.037 \cdot \text{SL}$	$0.295 + 0.036 \cdot \text{SL}$	$0.299 + 0.036 \cdot \text{SL}$
H to Y	t_R	0.556	$0.451 + 0.053 \cdot \text{SL}$	$0.444 + 0.054 \cdot \text{SL}$	$0.434 + 0.056 \cdot \text{SL}$
	t_F	0.600	$0.440 + 0.080 \cdot \text{SL}$	$0.440 + 0.080 \cdot \text{SL}$	$0.439 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.241	$0.190 + 0.025 \cdot \text{SL}$	$0.193 + 0.025 \cdot \text{SL}$	$0.197 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.405	$0.331 + 0.037 \cdot \text{SL}$	$0.333 + 0.036 \cdot \text{SL}$	$0.335 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA2222/OA2222D2/OA2222D4

Four 2-ORs into 4-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA2222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.011 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.008 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.364	$0.346 + 0.009 \cdot \text{SL}$	$0.353 + 0.007 \cdot \text{SL}$	$0.364 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.056 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.008 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.401	$0.383 + 0.009 \cdot \text{SL}$	$0.391 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.091	$0.066 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.342	$0.325 + 0.008 \cdot \text{SL}$	$0.332 + 0.007 \cdot \text{SL}$	$0.339 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.389	$0.371 + 0.009 \cdot \text{SL}$	$0.378 + 0.007 \cdot \text{SL}$	$0.389 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.058 + 0.011 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.343	$0.326 + 0.008 \cdot \text{SL}$	$0.333 + 0.007 \cdot \text{SL}$	$0.340 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.428	$0.410 + 0.009 \cdot \text{SL}$	$0.417 + 0.007 \cdot \text{SL}$	$0.428 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.093	$0.067 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.365	$0.348 + 0.008 \cdot \text{SL}$	$0.355 + 0.007 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.403	$0.384 + 0.009 \cdot \text{SL}$	$0.392 + 0.007 \cdot \text{SL}$	$0.403 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.092	$0.068 + 0.012 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.056 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.366	$0.349 + 0.009 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$	$0.363 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.441	$0.423 + 0.009 \cdot \text{SL}$	$0.431 + 0.007 \cdot \text{SL}$	$0.442 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.094	$0.068 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.059 + 0.012 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.386	$0.369 + 0.009 \cdot \text{SL}$	$0.376 + 0.007 \cdot \text{SL}$	$0.383 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.500	$0.482 + 0.009 \cdot \text{SL}$	$0.490 + 0.007 \cdot \text{SL}$	$0.501 + 0.006 \cdot \text{SL}$
H to Y	t_R	0.094	$0.069 + 0.013 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.063 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.388	$0.371 + 0.009 \cdot \text{SL}$	$0.378 + 0.007 \cdot \text{SL}$	$0.385 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.547	$0.529 + 0.009 \cdot \text{SL}$	$0.536 + 0.007 \cdot \text{SL}$	$0.548 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA2222/OA2222D2/OA2222D4

Four 2-ORs into 4-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA2222D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.074 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.076	$0.064 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.334	$0.323 + 0.005 \cdot \text{SL}$	$0.329 + 0.004 \cdot \text{SL}$	$0.341 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.391	$0.380 + 0.005 \cdot \text{SL}$	$0.386 + 0.004 \cdot \text{SL}$	$0.402 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.085	$0.073 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.079	$0.067 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.334	$0.324 + 0.005 \cdot \text{SL}$	$0.330 + 0.004 \cdot \text{SL}$	$0.342 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.428	$0.418 + 0.005 \cdot \text{SL}$	$0.423 + 0.004 \cdot \text{SL}$	$0.440 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.088	$0.077 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.365	$0.355 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.373 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.416	$0.405 + 0.005 \cdot \text{SL}$	$0.411 + 0.004 \cdot \text{SL}$	$0.427 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$
	t_F	0.078	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.366	$0.356 + 0.005 \cdot \text{SL}$	$0.362 + 0.004 \cdot \text{SL}$	$0.374 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.455	$0.444 + 0.005 \cdot \text{SL}$	$0.450 + 0.004 \cdot \text{SL}$	$0.467 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.089	$0.078 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.388	$0.378 + 0.005 \cdot \text{SL}$	$0.384 + 0.004 \cdot \text{SL}$	$0.396 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.429	$0.419 + 0.005 \cdot \text{SL}$	$0.425 + 0.004 \cdot \text{SL}$	$0.441 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.089	$0.078 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.079	$0.067 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.389	$0.379 + 0.005 \cdot \text{SL}$	$0.385 + 0.004 \cdot \text{SL}$	$0.398 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.469	$0.458 + 0.005 \cdot \text{SL}$	$0.464 + 0.004 \cdot \text{SL}$	$0.480 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.091	$0.080 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.082	$0.070 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.409	$0.399 + 0.005 \cdot \text{SL}$	$0.405 + 0.004 \cdot \text{SL}$	$0.418 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.530	$0.519 + 0.006 \cdot \text{SL}$	$0.525 + 0.004 \cdot \text{SL}$	$0.542 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.091	$0.080 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.085	$0.074 + 0.005 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.412	$0.401 + 0.005 \cdot \text{SL}$	$0.407 + 0.004 \cdot \text{SL}$	$0.420 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.577	$0.566 + 0.006 \cdot \text{SL}$	$0.573 + 0.004 \cdot \text{SL}$	$0.590 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA31DH/OA31/OA31D2/OA31D4

3-OR into 2-NAND with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)															
OA31DH				OA31				OA31D2				OA31D4			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.4	0.5	0.5	0.5	0.8	0.9	0.9	1.1	1.7	1.8	1.8	2.1	0.8	0.9	0.9	1.1
Gate Count															
OA31DH				OA31				OA31D2				OA31D4			
1.67				1.67				3.00				3.33			

OA31DH/OA31/OA31D2/OA31D4

3-OR into 2-NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA31DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.538	$0.197 + 0.171 \cdot \text{SL}$	$0.181 + 0.175 \cdot \text{SL}$	$0.183 + 0.175 \cdot \text{SL}$
	t_F	0.302	$0.105 + 0.098 \cdot \text{SL}$	$0.088 + 0.103 \cdot \text{SL}$	$0.082 + 0.104 \cdot \text{SL}$
	t_{PLH}	0.241	$0.093 + 0.074 \cdot \text{SL}$	$0.091 + 0.075 \cdot \text{SL}$	$0.090 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.189	$0.089 + 0.050 \cdot \text{SL}$	$0.088 + 0.050 \cdot \text{SL}$	$0.088 + 0.050 \cdot \text{SL}$
B to Y	t_R	0.541	$0.198 + 0.171 \cdot \text{SL}$	$0.187 + 0.174 \cdot \text{SL}$	$0.183 + 0.175 \cdot \text{SL}$
	t_F	0.341	$0.144 + 0.099 \cdot \text{SL}$	$0.126 + 0.104 \cdot \text{SL}$	$0.120 + 0.104 \cdot \text{SL}$
	t_{PLH}	0.265	$0.114 + 0.075 \cdot \text{SL}$	$0.116 + 0.075 \cdot \text{SL}$	$0.117 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.214	$0.112 + 0.051 \cdot \text{SL}$	$0.113 + 0.051 \cdot \text{SL}$	$0.113 + 0.051 \cdot \text{SL}$
C to Y	t_R	0.538	$0.194 + 0.172 \cdot \text{SL}$	$0.185 + 0.174 \cdot \text{SL}$	$0.183 + 0.175 \cdot \text{SL}$
	t_F	0.383	$0.186 + 0.099 \cdot \text{SL}$	$0.167 + 0.103 \cdot \text{SL}$	$0.160 + 0.104 \cdot \text{SL}$
	t_{PLH}	0.275	$0.123 + 0.076 \cdot \text{SL}$	$0.125 + 0.075 \cdot \text{SL}$	$0.127 + 0.075 \cdot \text{SL}$
	t_{PHL}	0.230	$0.125 + 0.052 \cdot \text{SL}$	$0.131 + 0.051 \cdot \text{SL}$	$0.134 + 0.051 \cdot \text{SL}$
D to Y	t_R	0.260	$0.150 + 0.055 \cdot \text{SL}$	$0.135 + 0.059 \cdot \text{SL}$	$0.115 + 0.061 \cdot \text{SL}$
	t_F	0.374	$0.170 + 0.102 \cdot \text{SL}$	$0.164 + 0.104 \cdot \text{SL}$	$0.159 + 0.104 \cdot \text{SL}$
	t_{PLH}	0.141	$0.087 + 0.027 \cdot \text{SL}$	$0.088 + 0.027 \cdot \text{SL}$	$0.090 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.228	$0.123 + 0.053 \cdot \text{SL}$	$0.129 + 0.051 \cdot \text{SL}$	$0.133 + 0.051 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA31

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.334	$0.178 + 0.078 \cdot \text{SL}$	$0.166 + 0.081 \cdot \text{SL}$	$0.151 + 0.082 \cdot \text{SL}$
	t_F	0.197	$0.100 + 0.049 \cdot \text{SL}$	$0.087 + 0.052 \cdot \text{SL}$	$0.072 + 0.054 \cdot \text{SL}$
	t_{PLH}	0.150	$0.080 + 0.035 \cdot \text{SL}$	$0.079 + 0.035 \cdot \text{SL}$	$0.078 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.137	$0.084 + 0.026 \cdot \text{SL}$	$0.085 + 0.026 \cdot \text{SL}$	$0.085 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.334	$0.177 + 0.079 \cdot \text{SL}$	$0.167 + 0.081 \cdot \text{SL}$	$0.157 + 0.082 \cdot \text{SL}$
	t_F	0.238	$0.138 + 0.050 \cdot \text{SL}$	$0.127 + 0.053 \cdot \text{SL}$	$0.113 + 0.054 \cdot \text{SL}$
	t_{PLH}	0.170	$0.099 + 0.036 \cdot \text{SL}$	$0.100 + 0.035 \cdot \text{SL}$	$0.101 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.163	$0.110 + 0.027 \cdot \text{SL}$	$0.111 + 0.027 \cdot \text{SL}$	$0.111 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.330	$0.170 + 0.080 \cdot \text{SL}$	$0.163 + 0.081 \cdot \text{SL}$	$0.156 + 0.082 \cdot \text{SL}$
	t_F	0.282	$0.183 + 0.049 \cdot \text{SL}$	$0.172 + 0.052 \cdot \text{SL}$	$0.156 + 0.054 \cdot \text{SL}$
	t_{PLH}	0.179	$0.107 + 0.036 \cdot \text{SL}$	$0.109 + 0.035 \cdot \text{SL}$	$0.110 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.179	$0.123 + 0.028 \cdot \text{SL}$	$0.127 + 0.027 \cdot \text{SL}$	$0.131 + 0.027 \cdot \text{SL}$
D to Y	t_R	0.186	$0.139 + 0.024 \cdot \text{SL}$	$0.130 + 0.026 \cdot \text{SL}$	$0.114 + 0.028 \cdot \text{SL}$
	t_F	0.270	$0.164 + 0.053 \cdot \text{SL}$	$0.162 + 0.053 \cdot \text{SL}$	$0.156 + 0.054 \cdot \text{SL}$
	t_{PLH}	0.100	$0.071 + 0.014 \cdot \text{SL}$	$0.077 + 0.012 \cdot \text{SL}$	$0.078 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.167	$0.111 + 0.028 \cdot \text{SL}$	$0.115 + 0.027 \cdot \text{SL}$	$0.119 + 0.027 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA31DH/OA31/OA31D2/OA31D4

3-OR into 2-NAND with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA31D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.268	$0.192 + 0.038 \cdot \text{SL}$	$0.185 + 0.040 \cdot \text{SL}$	$0.166 + 0.041 \cdot \text{SL}$
	t_F	0.155	$0.108 + 0.023 \cdot \text{SL}$	$0.099 + 0.026 \cdot \text{SL}$	$0.082 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.119	$0.084 + 0.018 \cdot \text{SL}$	$0.085 + 0.018 \cdot \text{SL}$	$0.083 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.116	$0.088 + 0.014 \cdot \text{SL}$	$0.091 + 0.013 \cdot \text{SL}$	$0.090 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.267	$0.190 + 0.039 \cdot \text{SL}$	$0.183 + 0.040 \cdot \text{SL}$	$0.171 + 0.041 \cdot \text{SL}$
	t_F	0.195	$0.147 + 0.024 \cdot \text{SL}$	$0.139 + 0.026 \cdot \text{SL}$	$0.122 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.138	$0.101 + 0.018 \cdot \text{SL}$	$0.104 + 0.018 \cdot \text{SL}$	$0.105 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.141	$0.114 + 0.013 \cdot \text{SL}$	$0.115 + 0.013 \cdot \text{SL}$	$0.116 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.262	$0.184 + 0.039 \cdot \text{SL}$	$0.178 + 0.040 \cdot \text{SL}$	$0.169 + 0.041 \cdot \text{SL}$
	t_F	0.239	$0.191 + 0.024 \cdot \text{SL}$	$0.185 + 0.026 \cdot \text{SL}$	$0.167 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.146	$0.109 + 0.018 \cdot \text{SL}$	$0.112 + 0.018 \cdot \text{SL}$	$0.113 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.156	$0.127 + 0.014 \cdot \text{SL}$	$0.130 + 0.014 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.168	$0.144 + 0.012 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$	$0.123 + 0.014 \cdot \text{SL}$
	t_F	0.224	$0.171 + 0.026 \cdot \text{SL}$	$0.170 + 0.027 \cdot \text{SL}$	$0.165 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.088	$0.073 + 0.008 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.146	$0.117 + 0.014 \cdot \text{SL}$	$0.119 + 0.014 \cdot \text{SL}$	$0.125 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA31D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.064 + 0.007 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.280	$0.271 + 0.005 \cdot \text{SL}$	$0.276 + 0.004 \cdot \text{SL}$	$0.287 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.252	$0.241 + 0.005 \cdot \text{SL}$	$0.247 + 0.004 \cdot \text{SL}$	$0.262 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.078	$0.065 + 0.007 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.301	$0.291 + 0.005 \cdot \text{SL}$	$0.297 + 0.004 \cdot \text{SL}$	$0.308 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.286	$0.276 + 0.005 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$	$0.297 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.078	$0.065 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.311	$0.301 + 0.005 \cdot \text{SL}$	$0.306 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.310	$0.300 + 0.005 \cdot \text{SL}$	$0.305 + 0.004 \cdot \text{SL}$	$0.321 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.069	$0.056 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.228	$0.219 + 0.005 \cdot \text{SL}$	$0.223 + 0.003 \cdot \text{SL}$	$0.234 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.299	$0.288 + 0.005 \cdot \text{SL}$	$0.294 + 0.004 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA311/OA311D2/OA311D4

3-OR into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)														
OA311					OA311D2					OA311D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.9	0.9	1.0	1.0	1.0	0.9	0.9	1.0	1.0	1.0	0.9	0.9	1.0	1.0	1.0
Gate Count														
OA311					OA311D2					OA311D4				
2.00					2.67					3.33				

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA311

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.379	$0.222 + 0.079 \cdot \text{SL}$	$0.211 + 0.081 \cdot \text{SL}$	$0.201 + 0.082 \cdot \text{SL}$
	t_F	0.245	$0.139 + 0.053 \cdot \text{SL}$	$0.130 + 0.055 \cdot \text{SL}$	$0.118 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.172	$0.102 + 0.035 \cdot \text{SL}$	$0.100 + 0.035 \cdot \text{SL}$	$0.100 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.150	$0.097 + 0.026 \cdot \text{SL}$	$0.097 + 0.026 \cdot \text{SL}$	$0.096 + 0.026 \cdot \text{SL}$
B to Y	t_R	0.380	$0.221 + 0.080 \cdot \text{SL}$	$0.215 + 0.081 \cdot \text{SL}$	$0.206 + 0.082 \cdot \text{SL}$
	t_F	0.288	$0.182 + 0.053 \cdot \text{SL}$	$0.173 + 0.055 \cdot \text{SL}$	$0.161 + 0.057 \cdot \text{SL}$
	t_{PLH}	0.193	$0.122 + 0.036 \cdot \text{SL}$	$0.123 + 0.036 \cdot \text{SL}$	$0.124 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.176	$0.122 + 0.027 \cdot \text{SL}$	$0.123 + 0.026 \cdot \text{SL}$	$0.123 + 0.026 \cdot \text{SL}$
C to Y	t_R	0.377	$0.216 + 0.080 \cdot \text{SL}$	$0.211 + 0.082 \cdot \text{SL}$	$0.205 + 0.082 \cdot \text{SL}$
	t_F	0.333	$0.230 + 0.052 \cdot \text{SL}$	$0.220 + 0.054 \cdot \text{SL}$	$0.206 + 0.056 \cdot \text{SL}$
	t_{PLH}	0.202	$0.131 + 0.036 \cdot \text{SL}$	$0.132 + 0.036 \cdot \text{SL}$	$0.133 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.191	$0.135 + 0.028 \cdot \text{SL}$	$0.139 + 0.027 \cdot \text{SL}$	$0.142 + 0.026 \cdot \text{SL}$
D to Y	t_R	0.233	$0.172 + 0.031 \cdot \text{SL}$	$0.163 + 0.033 \cdot \text{SL}$	$0.150 + 0.034 \cdot \text{SL}$
	t_F	0.325	$0.216 + 0.054 \cdot \text{SL}$	$0.213 + 0.055 \cdot \text{SL}$	$0.206 + 0.056 \cdot \text{SL}$
	t_{PLH}	0.128	$0.097 + 0.016 \cdot \text{SL}$	$0.098 + 0.015 \cdot \text{SL}$	$0.099 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.196	$0.140 + 0.028 \cdot \text{SL}$	$0.144 + 0.027 \cdot \text{SL}$	$0.148 + 0.026 \cdot \text{SL}$
E to Y	t_R	0.253	$0.193 + 0.030 \cdot \text{SL}$	$0.182 + 0.033 \cdot \text{SL}$	$0.167 + 0.034 \cdot \text{SL}$
	t_F	0.323	$0.214 + 0.054 \cdot \text{SL}$	$0.211 + 0.055 \cdot \text{SL}$	$0.205 + 0.056 \cdot \text{SL}$
	t_{PLH}	0.137	$0.106 + 0.015 \cdot \text{SL}$	$0.106 + 0.015 \cdot \text{SL}$	$0.107 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.197	$0.141 + 0.028 \cdot \text{SL}$	$0.145 + 0.027 \cdot \text{SL}$	$0.149 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA311/OA311D2/OA311D4

3-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA311D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.284	$0.267 + 0.008 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.280 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.252	$0.234 + 0.009 \cdot \text{SL}$	$0.241 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.052 + 0.011 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.303	$0.287 + 0.008 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.300 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.284	$0.266 + 0.009 \cdot \text{SL}$	$0.274 + 0.007 \cdot \text{SL}$	$0.284 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.085	$0.058 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.295 + 0.008 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.304	$0.286 + 0.009 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.304 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.247	$0.231 + 0.008 \cdot \text{SL}$	$0.237 + 0.007 \cdot \text{SL}$	$0.243 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.308	$0.290 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.258	$0.242 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$	$0.253 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.308	$0.291 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA311/OA311D2/OA311D4

3-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA311D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.068	$0.055 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.311	$0.301 + 0.005 \cdot \text{SL}$	$0.307 + 0.004 \cdot \text{SL}$	$0.318 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.275	$0.264 + 0.005 \cdot \text{SL}$	$0.270 + 0.004 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.057 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.331	$0.322 + 0.005 \cdot \text{SL}$	$0.327 + 0.004 \cdot \text{SL}$	$0.338 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.308	$0.297 + 0.005 \cdot \text{SL}$	$0.303 + 0.004 \cdot \text{SL}$	$0.319 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.081	$0.068 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.340	$0.330 + 0.005 \cdot \text{SL}$	$0.335 + 0.004 \cdot \text{SL}$	$0.347 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.329	$0.318 + 0.005 \cdot \text{SL}$	$0.324 + 0.004 \cdot \text{SL}$	$0.340 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.076	$0.063 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.265	$0.255 + 0.005 \cdot \text{SL}$	$0.260 + 0.004 \cdot \text{SL}$	$0.271 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.333	$0.322 + 0.005 \cdot \text{SL}$	$0.328 + 0.004 \cdot \text{SL}$	$0.344 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.077	$0.064 + 0.007 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.072	$0.059 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.273	$0.263 + 0.005 \cdot \text{SL}$	$0.269 + 0.004 \cdot \text{SL}$	$0.279 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.334	$0.323 + 0.005 \cdot \text{SL}$	$0.329 + 0.004 \cdot \text{SL}$	$0.345 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA3111/OA3111D2

3-OR into 4-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	x	x	1
x	x	x	x	0	x	1
x	x	x	x	x	0	1
Other States						0

Cell Data

Input Load (SL)												Gate Count	
OA3111						OA3111D2						OA3111	OA3111D2
A	B	C	D	E	F	A	B	C	D	E	F		
1.0	1.0	1.0	0.8	0.8	0.9	1.0	1.0	1.0	0.8	0.9	0.9	2.33	3.33

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA3111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.400	$0.241 + 0.079 \cdot \text{SL}$	$0.233 + 0.082 \cdot \text{SL}$	$0.225 + 0.082 \cdot \text{SL}$
	t_F	0.313	$0.186 + 0.063 \cdot \text{SL}$	$0.179 + 0.065 \cdot \text{SL}$	$0.170 + 0.066 \cdot \text{SL}$
	t_{PLH}	0.184	$0.114 + 0.035 \cdot \text{SL}$	$0.113 + 0.035 \cdot \text{SL}$	$0.113 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.165	$0.106 + 0.030 \cdot \text{SL}$	$0.105 + 0.030 \cdot \text{SL}$	$0.105 + 0.030 \cdot \text{SL}$
B to Y	t_R	0.403	$0.243 + 0.080 \cdot \text{SL}$	$0.238 + 0.081 \cdot \text{SL}$	$0.229 + 0.082 \cdot \text{SL}$
	t_F	0.363	$0.237 + 0.063 \cdot \text{SL}$	$0.229 + 0.065 \cdot \text{SL}$	$0.219 + 0.066 \cdot \text{SL}$
	t_{PLH}	0.206	$0.134 + 0.036 \cdot \text{SL}$	$0.135 + 0.036 \cdot \text{SL}$	$0.137 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.195	$0.135 + 0.030 \cdot \text{SL}$	$0.135 + 0.030 \cdot \text{SL}$	$0.135 + 0.030 \cdot \text{SL}$
C to Y	t_R	0.400	$0.239 + 0.080 \cdot \text{SL}$	$0.234 + 0.082 \cdot \text{SL}$	$0.229 + 0.082 \cdot \text{SL}$
	t_F	0.415	$0.293 + 0.061 \cdot \text{SL}$	$0.283 + 0.064 \cdot \text{SL}$	$0.270 + 0.065 \cdot \text{SL}$
	t_{PLH}	0.214	$0.142 + 0.036 \cdot \text{SL}$	$0.144 + 0.036 \cdot \text{SL}$	$0.146 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.214	$0.152 + 0.031 \cdot \text{SL}$	$0.155 + 0.030 \cdot \text{SL}$	$0.158 + 0.030 \cdot \text{SL}$
D to Y	t_R	0.314	$0.226 + 0.044 \cdot \text{SL}$	$0.218 + 0.046 \cdot \text{SL}$	$0.206 + 0.048 \cdot \text{SL}$
	t_F	0.412	$0.285 + 0.063 \cdot \text{SL}$	$0.281 + 0.064 \cdot \text{SL}$	$0.274 + 0.065 \cdot \text{SL}$
	t_{PLH}	0.171	$0.129 + 0.021 \cdot \text{SL}$	$0.130 + 0.021 \cdot \text{SL}$	$0.132 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.234	$0.171 + 0.031 \cdot \text{SL}$	$0.175 + 0.030 \cdot \text{SL}$	$0.179 + 0.030 \cdot \text{SL}$
E to Y	t_R	0.337	$0.249 + 0.044 \cdot \text{SL}$	$0.241 + 0.046 \cdot \text{SL}$	$0.228 + 0.048 \cdot \text{SL}$
	t_F	0.411	$0.284 + 0.063 \cdot \text{SL}$	$0.280 + 0.064 \cdot \text{SL}$	$0.273 + 0.065 \cdot \text{SL}$
	t_{PLH}	0.184	$0.142 + 0.021 \cdot \text{SL}$	$0.142 + 0.021 \cdot \text{SL}$	$0.145 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.241	$0.178 + 0.031 \cdot \text{SL}$	$0.182 + 0.030 \cdot \text{SL}$	$0.186 + 0.030 \cdot \text{SL}$
F to Y	t_R	0.361	$0.273 + 0.044 \cdot \text{SL}$	$0.265 + 0.046 \cdot \text{SL}$	$0.252 + 0.048 \cdot \text{SL}$
	t_F	0.409	$0.282 + 0.064 \cdot \text{SL}$	$0.278 + 0.065 \cdot \text{SL}$	$0.273 + 0.065 \cdot \text{SL}$
	t_{PLH}	0.195	$0.152 + 0.021 \cdot \text{SL}$	$0.153 + 0.021 \cdot \text{SL}$	$0.156 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.243	$0.181 + 0.031 \cdot \text{SL}$	$0.184 + 0.030 \cdot \text{SL}$	$0.189 + 0.030 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OA3111/OA3111D2

3-OR into 4-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA3111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.049 + 0.013 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.298	$0.281 + 0.008 \cdot \text{SL}$	$0.288 + 0.007 \cdot \text{SL}$	$0.294 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.275	$0.257 + 0.009 \cdot \text{SL}$	$0.265 + 0.007 \cdot \text{SL}$	$0.275 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.319	$0.303 + 0.008 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$	$0.315 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.312	$0.294 + 0.009 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.084	$0.059 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.328	$0.311 + 0.008 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$	$0.324 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.338	$0.320 + 0.009 \cdot \text{SL}$	$0.328 + 0.007 \cdot \text{SL}$	$0.339 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.083	$0.056 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.297	$0.280 + 0.008 \cdot \text{SL}$	$0.286 + 0.007 \cdot \text{SL}$	$0.293 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.358	$0.340 + 0.009 \cdot \text{SL}$	$0.347 + 0.007 \cdot \text{SL}$	$0.358 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.312	$0.296 + 0.008 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.365	$0.347 + 0.009 \cdot \text{SL}$	$0.354 + 0.007 \cdot \text{SL}$	$0.365 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.326	$0.310 + 0.008 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.322 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.367	$0.349 + 0.009 \cdot \text{SL}$	$0.357 + 0.007 \cdot \text{SL}$	$0.368 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA32/OA32D2/OA32D4

3-OR and 2-OR into 2-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	x	x	1
x	x	x	0	0	1
Other States					0

Cell Data

Input Load (SL)														
OA32					OA32D2					OA32D4				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.8	0.8	0.9	0.9	0.9	0.8	0.8	0.9	0.9	0.9	0.8	0.8	0.9	0.9	0.9
Gate Count														
OA32					OA32D2					OA32D4				
2.00					3.33					4.00				

OA32/OA32D2/OA32D4

3-OR and 2-OR into 2-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA32

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.429	$0.274 + 0.078 \cdot \text{SL}$	$0.261 + 0.081 \cdot \text{SL}$	$0.246 + 0.083 \cdot \text{SL}$
	t_F	0.311	$0.170 + 0.071 \cdot \text{SL}$	$0.162 + 0.073 \cdot \text{SL}$	$0.157 + 0.073 \cdot \text{SL}$
	t_{PLH}	0.167	$0.094 + 0.036 \cdot \text{SL}$	$0.097 + 0.036 \cdot \text{SL}$	$0.100 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.209	$0.138 + 0.036 \cdot \text{SL}$	$0.140 + 0.035 \cdot \text{SL}$	$0.141 + 0.035 \cdot \text{SL}$
B to Y	t_R	0.429	$0.272 + 0.079 \cdot \text{SL}$	$0.262 + 0.081 \cdot \text{SL}$	$0.251 + 0.083 \cdot \text{SL}$
	t_F	0.367	$0.223 + 0.072 \cdot \text{SL}$	$0.216 + 0.074 \cdot \text{SL}$	$0.212 + 0.074 \cdot \text{SL}$
	t_{PLH}	0.189	$0.115 + 0.037 \cdot \text{SL}$	$0.118 + 0.036 \cdot \text{SL}$	$0.123 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.247	$0.175 + 0.036 \cdot \text{SL}$	$0.177 + 0.036 \cdot \text{SL}$	$0.178 + 0.036 \cdot \text{SL}$
C to Y	t_R	0.425	$0.266 + 0.080 \cdot \text{SL}$	$0.258 + 0.082 \cdot \text{SL}$	$0.250 + 0.083 \cdot \text{SL}$
	t_F	0.424	$0.280 + 0.072 \cdot \text{SL}$	$0.274 + 0.073 \cdot \text{SL}$	$0.269 + 0.074 \cdot \text{SL}$
	t_{PLH}	0.198	$0.123 + 0.037 \cdot \text{SL}$	$0.128 + 0.036 \cdot \text{SL}$	$0.133 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.274	$0.200 + 0.037 \cdot \text{SL}$	$0.204 + 0.036 \cdot \text{SL}$	$0.208 + 0.036 \cdot \text{SL}$
D to Y	t_R	0.322	$0.221 + 0.050 \cdot \text{SL}$	$0.210 + 0.053 \cdot \text{SL}$	$0.193 + 0.055 \cdot \text{SL}$
	t_F	0.369	$0.224 + 0.073 \cdot \text{SL}$	$0.220 + 0.074 \cdot \text{SL}$	$0.215 + 0.074 \cdot \text{SL}$
	t_{PLH}	0.151	$0.102 + 0.024 \cdot \text{SL}$	$0.103 + 0.024 \cdot \text{SL}$	$0.105 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.245	$0.169 + 0.038 \cdot \text{SL}$	$0.175 + 0.036 \cdot \text{SL}$	$0.181 + 0.036 \cdot \text{SL}$
E to Y	t_R	0.314	$0.210 + 0.052 \cdot \text{SL}$	$0.202 + 0.054 \cdot \text{SL}$	$0.192 + 0.055 \cdot \text{SL}$
	t_F	0.420	$0.274 + 0.073 \cdot \text{SL}$	$0.271 + 0.074 \cdot \text{SL}$	$0.268 + 0.074 \cdot \text{SL}$
	t_{PLH}	0.152	$0.102 + 0.025 \cdot \text{SL}$	$0.104 + 0.024 \cdot \text{SL}$	$0.107 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.280	$0.206 + 0.037 \cdot \text{SL}$	$0.210 + 0.036 \cdot \text{SL}$	$0.215 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA32D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.013 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.286	$0.270 + 0.008 \cdot \text{SL}$	$0.276 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.313	$0.295 + 0.009 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.307	$0.291 + 0.008 \cdot \text{SL}$	$0.297 + 0.007 \cdot \text{SL}$	$0.304 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.359	$0.341 + 0.009 \cdot \text{SL}$	$0.348 + 0.007 \cdot \text{SL}$	$0.358 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.087	$0.062 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.318	$0.302 + 0.008 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.314 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.395	$0.377 + 0.009 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.395 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.087	$0.062 + 0.013 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.011 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.275	$0.259 + 0.008 \cdot \text{SL}$	$0.265 + 0.007 \cdot \text{SL}$	$0.272 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.357	$0.340 + 0.009 \cdot \text{SL}$	$0.347 + 0.007 \cdot \text{SL}$	$0.357 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.011 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.277	$0.260 + 0.008 \cdot \text{SL}$	$0.267 + 0.007 \cdot \text{SL}$	$0.273 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.402	$0.384 + 0.009 \cdot \text{SL}$	$0.391 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA32/OA32D2/OA32D4

3-OR and 2-OR into 2-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA32D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.082	$0.070 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.060 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.315	$0.305 + 0.005 \cdot \text{SL}$	$0.310 + 0.004 \cdot \text{SL}$	$0.322 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.339	$0.329 + 0.005 \cdot \text{SL}$	$0.334 + 0.004 \cdot \text{SL}$	$0.350 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.057 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.336	$0.326 + 0.005 \cdot \text{SL}$	$0.331 + 0.004 \cdot \text{SL}$	$0.343 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.386	$0.375 + 0.005 \cdot \text{SL}$	$0.381 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.347	$0.337 + 0.005 \cdot \text{SL}$	$0.343 + 0.004 \cdot \text{SL}$	$0.354 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.424	$0.413 + 0.005 \cdot \text{SL}$	$0.419 + 0.004 \cdot \text{SL}$	$0.435 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.299	$0.289 + 0.005 \cdot \text{SL}$	$0.295 + 0.004 \cdot \text{SL}$	$0.307 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.386	$0.375 + 0.005 \cdot \text{SL}$	$0.380 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.301	$0.291 + 0.005 \cdot \text{SL}$	$0.296 + 0.004 \cdot \text{SL}$	$0.308 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.430	$0.419 + 0.005 \cdot \text{SL}$	$0.425 + 0.004 \cdot \text{SL}$	$0.441 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA321/OA321D2/OA321D4

3-OR and 2-OR into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	0	x	1
x	x	x	x	x	0	1
Other States						0

Cell Data

Input Load (SL)																	
OA321						OA321D2						OA321D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.9	0.9	0.9	0.9	1.0	1.0	0.9	0.9	0.9	0.9	1.0	1.0	0.9	0.9	0.9	0.9	1.0	1.0
Gate Count																	
OA321						OA321D2						OA321D4					
2.67						3.33						4.00					

OA321/OA321D2/OA321D4

3-OR and 2-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA321

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.474	$0.318 + 0.078 \cdot \text{SL}$	$0.306 + 0.081 \cdot \text{SL}$	$0.294 + 0.082 \cdot \text{SL}$
	t_F	0.337	$0.205 + 0.066 \cdot \text{SL}$	$0.199 + 0.068 \cdot \text{SL}$	$0.193 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.188	$0.116 + 0.036 \cdot \text{SL}$	$0.118 + 0.036 \cdot \text{SL}$	$0.121 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.210	$0.146 + 0.032 \cdot \text{SL}$	$0.147 + 0.032 \cdot \text{SL}$	$0.148 + 0.032 \cdot \text{SL}$
B to Y	t_R	0.474	$0.316 + 0.079 \cdot \text{SL}$	$0.309 + 0.081 \cdot \text{SL}$	$0.299 + 0.082 \cdot \text{SL}$
	t_F	0.385	$0.253 + 0.066 \cdot \text{SL}$	$0.246 + 0.068 \cdot \text{SL}$	$0.242 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.209	$0.136 + 0.037 \cdot \text{SL}$	$0.139 + 0.036 \cdot \text{SL}$	$0.143 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.241	$0.177 + 0.032 \cdot \text{SL}$	$0.178 + 0.032 \cdot \text{SL}$	$0.179 + 0.032 \cdot \text{SL}$
C to Y	t_R	0.471	$0.311 + 0.080 \cdot \text{SL}$	$0.305 + 0.082 \cdot \text{SL}$	$0.298 + 0.082 \cdot \text{SL}$
	t_F	0.438	$0.307 + 0.066 \cdot \text{SL}$	$0.300 + 0.067 \cdot \text{SL}$	$0.294 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.218	$0.144 + 0.037 \cdot \text{SL}$	$0.147 + 0.036 \cdot \text{SL}$	$0.152 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.265	$0.199 + 0.033 \cdot \text{SL}$	$0.202 + 0.032 \cdot \text{SL}$	$0.205 + 0.032 \cdot \text{SL}$
D to Y	t_R	0.357	$0.255 + 0.051 \cdot \text{SL}$	$0.245 + 0.054 \cdot \text{SL}$	$0.231 + 0.055 \cdot \text{SL}$
	t_F	0.385	$0.253 + 0.066 \cdot \text{SL}$	$0.249 + 0.067 \cdot \text{SL}$	$0.244 + 0.067 \cdot \text{SL}$
	t_{PLH}	0.172	$0.124 + 0.024 \cdot \text{SL}$	$0.125 + 0.024 \cdot \text{SL}$	$0.126 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.244	$0.177 + 0.033 \cdot \text{SL}$	$0.182 + 0.032 \cdot \text{SL}$	$0.187 + 0.032 \cdot \text{SL}$
E to Y	t_R	0.351	$0.246 + 0.053 \cdot \text{SL}$	$0.240 + 0.054 \cdot \text{SL}$	$0.232 + 0.055 \cdot \text{SL}$
	t_F	0.436	$0.302 + 0.067 \cdot \text{SL}$	$0.299 + 0.068 \cdot \text{SL}$	$0.294 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.173	$0.124 + 0.024 \cdot \text{SL}$	$0.126 + 0.024 \cdot \text{SL}$	$0.128 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.278	$0.211 + 0.033 \cdot \text{SL}$	$0.215 + 0.032 \cdot \text{SL}$	$0.219 + 0.032 \cdot \text{SL}$
F to Y	t_R	0.290	$0.238 + 0.026 \cdot \text{SL}$	$0.227 + 0.029 \cdot \text{SL}$	$0.207 + 0.031 \cdot \text{SL}$
	t_F	0.434	$0.300 + 0.067 \cdot \text{SL}$	$0.298 + 0.068 \cdot \text{SL}$	$0.294 + 0.068 \cdot \text{SL}$
	t_{PLH}	0.136	$0.107 + 0.015 \cdot \text{SL}$	$0.108 + 0.014 \cdot \text{SL}$	$0.110 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.278	$0.211 + 0.033 \cdot \text{SL}$	$0.214 + 0.033 \cdot \text{SL}$	$0.219 + 0.032 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA321D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	$0.065 + 0.013 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.312	$0.296 + 0.008 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.321	$0.303 + 0.009 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$	$0.321 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.333	$0.317 + 0.008 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.362	$0.344 + 0.009 \cdot \text{SL}$	$0.351 + 0.007 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.089	$0.065 + 0.012 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.342	$0.325 + 0.008 \cdot \text{SL}$	$0.332 + 0.007 \cdot \text{SL}$	$0.339 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.391	$0.373 + 0.009 \cdot \text{SL}$	$0.380 + 0.007 \cdot \text{SL}$	$0.391 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.089	$0.064 + 0.012 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.300	$0.283 + 0.008 \cdot \text{SL}$	$0.289 + 0.007 \cdot \text{SL}$	$0.296 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.360	$0.343 + 0.009 \cdot \text{SL}$	$0.350 + 0.007 \cdot \text{SL}$	$0.360 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.089	$0.064 + 0.012 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.057 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.301	$0.284 + 0.008 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.403	$0.385 + 0.009 \cdot \text{SL}$	$0.392 + 0.007 \cdot \text{SL}$	$0.403 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.057 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.263	$0.247 + 0.008 \cdot \text{SL}$	$0.252 + 0.007 \cdot \text{SL}$	$0.258 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.402	$0.384 + 0.009 \cdot \text{SL}$	$0.392 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA321/OA321D2/OA321D4

3-OR and 2-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA321D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	$0.075 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.342	$0.332 + 0.005 \cdot \text{SL}$	$0.338 + 0.004 \cdot \text{SL}$	$0.350 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.346	$0.335 + 0.005 \cdot \text{SL}$	$0.341 + 0.004 \cdot \text{SL}$	$0.357 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.363	$0.353 + 0.005 \cdot \text{SL}$	$0.359 + 0.004 \cdot \text{SL}$	$0.371 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.387	$0.376 + 0.005 \cdot \text{SL}$	$0.382 + 0.004 \cdot \text{SL}$	$0.398 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.372	$0.362 + 0.005 \cdot \text{SL}$	$0.368 + 0.004 \cdot \text{SL}$	$0.380 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.416	$0.405 + 0.005 \cdot \text{SL}$	$0.412 + 0.004 \cdot \text{SL}$	$0.428 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.324	$0.314 + 0.005 \cdot \text{SL}$	$0.320 + 0.004 \cdot \text{SL}$	$0.332 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.386	$0.375 + 0.005 \cdot \text{SL}$	$0.381 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.085	$0.072 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.325	$0.315 + 0.005 \cdot \text{SL}$	$0.321 + 0.004 \cdot \text{SL}$	$0.333 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.428	$0.418 + 0.005 \cdot \text{SL}$	$0.423 + 0.004 \cdot \text{SL}$	$0.440 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.079	$0.067 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.279	$0.270 + 0.005 \cdot \text{SL}$	$0.275 + 0.004 \cdot \text{SL}$	$0.286 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.427	$0.417 + 0.005 \cdot \text{SL}$	$0.422 + 0.004 \cdot \text{SL}$	$0.439 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA322/OA322D2/OA322D4

3-OR and Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	x	x	x	x	1
x	x	x	0	0	x	x	1
x	x	x	x	x	0	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA322							OA322
A	B	C	D	E	F	G	
0.8	0.9	0.9	0.9	0.9	0.9	1.0	3.00
OA322D2							OA322D2
A	B	C	D	E	F	G	
0.8	0.9	0.9	0.9	0.9	0.9	1.0	4.00
OA322D4							OA322D4
A	B	C	D	E	F	G	
0.8	0.9	0.9	0.9	0.9	0.9	1.0	4.67

OA322/OA322D2/OA322D4

3-OR and Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA322

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.560	$0.404 + 0.078 \cdot \text{SL}$	$0.391 + 0.081 \cdot \text{SL}$	$0.379 + 0.082 \cdot \text{SL}$
	t_F	0.474	$0.305 + 0.085 \cdot \text{SL}$	$0.301 + 0.086 \cdot \text{SL}$	$0.301 + 0.086 \cdot \text{SL}$
	t_{PLH}	0.205	$0.131 + 0.037 \cdot \text{SL}$	$0.135 + 0.036 \cdot \text{SL}$	$0.139 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.296	$0.215 + 0.040 \cdot \text{SL}$	$0.217 + 0.040 \cdot \text{SL}$	$0.219 + 0.040 \cdot \text{SL}$
B to Y	t_R	0.560	$0.402 + 0.079 \cdot \text{SL}$	$0.394 + 0.081 \cdot \text{SL}$	$0.383 + 0.082 \cdot \text{SL}$
	t_F	0.533	$0.363 + 0.085 \cdot \text{SL}$	$0.361 + 0.086 \cdot \text{SL}$	$0.361 + 0.086 \cdot \text{SL}$
	t_{PLH}	0.226	$0.152 + 0.037 \cdot \text{SL}$	$0.156 + 0.036 \cdot \text{SL}$	$0.161 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.336	$0.255 + 0.040 \cdot \text{SL}$	$0.257 + 0.040 \cdot \text{SL}$	$0.258 + 0.040 \cdot \text{SL}$
C to Y	t_R	0.556	$0.397 + 0.080 \cdot \text{SL}$	$0.390 + 0.081 \cdot \text{SL}$	$0.383 + 0.082 \cdot \text{SL}$
	t_F	0.597	$0.427 + 0.085 \cdot \text{SL}$	$0.425 + 0.086 \cdot \text{SL}$	$0.426 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.235	$0.160 + 0.037 \cdot \text{SL}$	$0.165 + 0.036 \cdot \text{SL}$	$0.170 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.368	$0.287 + 0.041 \cdot \text{SL}$	$0.289 + 0.040 \cdot \text{SL}$	$0.292 + 0.040 \cdot \text{SL}$
D to Y	t_R	0.413	$0.310 + 0.052 \cdot \text{SL}$	$0.301 + 0.054 \cdot \text{SL}$	$0.285 + 0.056 \cdot \text{SL}$
	t_F	0.537	$0.368 + 0.084 \cdot \text{SL}$	$0.365 + 0.085 \cdot \text{SL}$	$0.363 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.179	$0.129 + 0.025 \cdot \text{SL}$	$0.131 + 0.024 \cdot \text{SL}$	$0.135 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.346	$0.263 + 0.042 \cdot \text{SL}$	$0.267 + 0.040 \cdot \text{SL}$	$0.272 + 0.040 \cdot \text{SL}$
E to Y	t_R	0.407	$0.301 + 0.053 \cdot \text{SL}$	$0.294 + 0.055 \cdot \text{SL}$	$0.285 + 0.056 \cdot \text{SL}$
	t_F	0.598	$0.428 + 0.085 \cdot \text{SL}$	$0.426 + 0.085 \cdot \text{SL}$	$0.425 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.183	$0.133 + 0.025 \cdot \text{SL}$	$0.134 + 0.025 \cdot \text{SL}$	$0.138 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.387	$0.305 + 0.041 \cdot \text{SL}$	$0.308 + 0.040 \cdot \text{SL}$	$0.312 + 0.040 \cdot \text{SL}$
F to Y	t_R	0.446	$0.345 + 0.051 \cdot \text{SL}$	$0.335 + 0.053 \cdot \text{SL}$	$0.318 + 0.055 \cdot \text{SL}$
	t_F	0.535	$0.366 + 0.084 \cdot \text{SL}$	$0.365 + 0.085 \cdot \text{SL}$	$0.363 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.197	$0.148 + 0.025 \cdot \text{SL}$	$0.150 + 0.024 \cdot \text{SL}$	$0.153 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.360	$0.277 + 0.041 \cdot \text{SL}$	$0.282 + 0.040 \cdot \text{SL}$	$0.287 + 0.040 \cdot \text{SL}$
G to Y	t_R	0.440	$0.335 + 0.052 \cdot \text{SL}$	$0.329 + 0.054 \cdot \text{SL}$	$0.319 + 0.055 \cdot \text{SL}$
	t_F	0.597	$0.426 + 0.085 \cdot \text{SL}$	$0.426 + 0.085 \cdot \text{SL}$	$0.425 + 0.086 \cdot \text{SL}$
	t_{PLH}	0.199	$0.149 + 0.025 \cdot \text{SL}$	$0.151 + 0.024 \cdot \text{SL}$	$0.155 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.402	$0.320 + 0.041 \cdot \text{SL}$	$0.323 + 0.040 \cdot \text{SL}$	$0.327 + 0.040 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA322D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.095	$0.069 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.057 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.324 + 0.008 \cdot \text{SL}$	$0.331 + 0.007 \cdot \text{SL}$	$0.338 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.416	$0.398 + 0.009 \cdot \text{SL}$	$0.406 + 0.007 \cdot \text{SL}$	$0.417 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.095	$0.070 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.060 + 0.012 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.362	$0.345 + 0.008 \cdot \text{SL}$	$0.352 + 0.007 \cdot \text{SL}$	$0.360 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.466	$0.448 + 0.009 \cdot \text{SL}$	$0.455 + 0.007 \cdot \text{SL}$	$0.466 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.095	$0.070 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.062 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.371	$0.354 + 0.008 \cdot \text{SL}$	$0.361 + 0.007 \cdot \text{SL}$	$0.368 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.506	$0.488 + 0.009 \cdot \text{SL}$	$0.496 + 0.007 \cdot \text{SL}$	$0.507 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.093	$0.066 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.061 + 0.011 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.318	$0.302 + 0.008 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.315 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.473	$0.455 + 0.009 \cdot \text{SL}$	$0.463 + 0.007 \cdot \text{SL}$	$0.474 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.092	$0.069 + 0.012 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.062 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.321	$0.304 + 0.008 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.318 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.525	$0.507 + 0.009 \cdot \text{SL}$	$0.514 + 0.007 \cdot \text{SL}$	$0.526 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.094	$0.070 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.060 + 0.012 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.340	$0.323 + 0.008 \cdot \text{SL}$	$0.330 + 0.007 \cdot \text{SL}$	$0.337 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.488	$0.469 + 0.009 \cdot \text{SL}$	$0.477 + 0.007 \cdot \text{SL}$	$0.488 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.094	$0.070 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.063 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.324 + 0.008 \cdot \text{SL}$	$0.331 + 0.007 \cdot \text{SL}$	$0.338 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.539	$0.521 + 0.009 \cdot \text{SL}$	$0.529 + 0.007 \cdot \text{SL}$	$0.540 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA322/OA322D2/OA322D4

3-OR and Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA322D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	$0.080 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.367	$0.357 + 0.005 \cdot \text{SL}$	$0.363 + 0.004 \cdot \text{SL}$	$0.376 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.446	$0.435 + 0.005 \cdot \text{SL}$	$0.440 + 0.004 \cdot \text{SL}$	$0.457 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.091	$0.078 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.081	$0.069 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.389	$0.379 + 0.005 \cdot \text{SL}$	$0.384 + 0.004 \cdot \text{SL}$	$0.398 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.495	$0.484 + 0.006 \cdot \text{SL}$	$0.491 + 0.004 \cdot \text{SL}$	$0.507 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.073 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.398	$0.387 + 0.005 \cdot \text{SL}$	$0.393 + 0.004 \cdot \text{SL}$	$0.406 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.537	$0.526 + 0.006 \cdot \text{SL}$	$0.532 + 0.004 \cdot \text{SL}$	$0.549 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.088	$0.077 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.340	$0.330 + 0.005 \cdot \text{SL}$	$0.336 + 0.004 \cdot \text{SL}$	$0.348 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.503	$0.493 + 0.005 \cdot \text{SL}$	$0.498 + 0.004 \cdot \text{SL}$	$0.515 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.088	$0.076 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.343	$0.333 + 0.005 \cdot \text{SL}$	$0.339 + 0.004 \cdot \text{SL}$	$0.351 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.556	$0.544 + 0.006 \cdot \text{SL}$	$0.551 + 0.004 \cdot \text{SL}$	$0.568 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.081	$0.069 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.362	$0.352 + 0.005 \cdot \text{SL}$	$0.358 + 0.004 \cdot \text{SL}$	$0.371 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.518	$0.507 + 0.005 \cdot \text{SL}$	$0.513 + 0.004 \cdot \text{SL}$	$0.530 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.090	$0.078 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.363	$0.353 + 0.005 \cdot \text{SL}$	$0.359 + 0.004 \cdot \text{SL}$	$0.372 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.570	$0.559 + 0.005 \cdot \text{SL}$	$0.565 + 0.004 \cdot \text{SL}$	$0.582 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA33/OA33D2/OA33D4

Two 3-ORs into 2-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	0	0	1
Other States						0

Cell Data

Input Load (SL)																	
OA33						OA33D2						OA33D4					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9
Gate Count																	
OA33						OA33D2						OA33D4					
2.33						3.33						4.00					

OA33/OA33D2/OA33D4

Two 3-ORs into 2-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA33

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.537	$0.385 + 0.076 \cdot \text{SL}$	$0.369 + 0.080 \cdot \text{SL}$	$0.350 + 0.082 \cdot \text{SL}$
	t_F	0.401	$0.247 + 0.077 \cdot \text{SL}$	$0.242 + 0.078 \cdot \text{SL}$	$0.239 + 0.078 \cdot \text{SL}$
	t_{PLH}	0.170	$0.096 + 0.037 \cdot \text{SL}$	$0.098 + 0.037 \cdot \text{SL}$	$0.102 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.259	$0.180 + 0.040 \cdot \text{SL}$	$0.185 + 0.038 \cdot \text{SL}$	$0.191 + 0.038 \cdot \text{SL}$
B to Y	t_R	0.537	$0.382 + 0.077 \cdot \text{SL}$	$0.370 + 0.080 \cdot \text{SL}$	$0.356 + 0.082 \cdot \text{SL}$
	t_F	0.461	$0.303 + 0.079 \cdot \text{SL}$	$0.300 + 0.080 \cdot \text{SL}$	$0.299 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.192	$0.117 + 0.037 \cdot \text{SL}$	$0.120 + 0.037 \cdot \text{SL}$	$0.125 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.302	$0.223 + 0.040 \cdot \text{SL}$	$0.227 + 0.039 \cdot \text{SL}$	$0.232 + 0.038 \cdot \text{SL}$
C to Y	t_R	0.533	$0.376 + 0.078 \cdot \text{SL}$	$0.366 + 0.081 \cdot \text{SL}$	$0.355 + 0.082 \cdot \text{SL}$
	t_F	0.520	$0.363 + 0.079 \cdot \text{SL}$	$0.360 + 0.079 \cdot \text{SL}$	$0.358 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.200	$0.125 + 0.037 \cdot \text{SL}$	$0.128 + 0.037 \cdot \text{SL}$	$0.134 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.334	$0.254 + 0.040 \cdot \text{SL}$	$0.258 + 0.039 \cdot \text{SL}$	$0.264 + 0.038 \cdot \text{SL}$
D to Y	t_R	0.478	$0.323 + 0.078 \cdot \text{SL}$	$0.310 + 0.081 \cdot \text{SL}$	$0.297 + 0.082 \cdot \text{SL}$
	t_F	0.401	$0.244 + 0.078 \cdot \text{SL}$	$0.240 + 0.079 \cdot \text{SL}$	$0.237 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.200	$0.128 + 0.036 \cdot \text{SL}$	$0.130 + 0.036 \cdot \text{SL}$	$0.132 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.271	$0.190 + 0.040 \cdot \text{SL}$	$0.196 + 0.039 \cdot \text{SL}$	$0.202 + 0.038 \cdot \text{SL}$
E to Y	t_R	0.478	$0.319 + 0.079 \cdot \text{SL}$	$0.312 + 0.081 \cdot \text{SL}$	$0.302 + 0.082 \cdot \text{SL}$
	t_F	0.459	$0.301 + 0.079 \cdot \text{SL}$	$0.299 + 0.080 \cdot \text{SL}$	$0.297 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.224	$0.151 + 0.037 \cdot \text{SL}$	$0.154 + 0.036 \cdot \text{SL}$	$0.157 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.314	$0.234 + 0.040 \cdot \text{SL}$	$0.238 + 0.039 \cdot \text{SL}$	$0.243 + 0.038 \cdot \text{SL}$
F to Y	t_R	0.474	$0.314 + 0.080 \cdot \text{SL}$	$0.309 + 0.081 \cdot \text{SL}$	$0.301 + 0.082 \cdot \text{SL}$
	t_F	0.520	$0.363 + 0.079 \cdot \text{SL}$	$0.361 + 0.079 \cdot \text{SL}$	$0.358 + 0.080 \cdot \text{SL}$
	t_{PLH}	0.234	$0.161 + 0.037 \cdot \text{SL}$	$0.164 + 0.036 \cdot \text{SL}$	$0.168 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.346	$0.266 + 0.040 \cdot \text{SL}$	$0.271 + 0.039 \cdot \text{SL}$	$0.277 + 0.038 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA33D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.094	$0.069 + 0.013 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.305	$0.288 + 0.008 \cdot \text{SL}$	$0.295 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.368	$0.350 + 0.009 \cdot \text{SL}$	$0.358 + 0.007 \cdot \text{SL}$	$0.368 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.095	$0.071 + 0.012 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.326	$0.309 + 0.008 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.324 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.420	$0.402 + 0.009 \cdot \text{SL}$	$0.410 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.095	$0.071 + 0.012 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.058 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.334	$0.317 + 0.008 \cdot \text{SL}$	$0.324 + 0.007 \cdot \text{SL}$	$0.332 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.459	$0.441 + 0.009 \cdot \text{SL}$	$0.449 + 0.007 \cdot \text{SL}$	$0.459 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.095	$0.071 + 0.012 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.055 + 0.011 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.332	$0.315 + 0.008 \cdot \text{SL}$	$0.322 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.378	$0.361 + 0.009 \cdot \text{SL}$	$0.368 + 0.007 \cdot \text{SL}$	$0.378 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.096	$0.071 + 0.013 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.355	$0.338 + 0.008 \cdot \text{SL}$	$0.345 + 0.007 \cdot \text{SL}$	$0.353 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.431	$0.413 + 0.009 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.431 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.096	$0.073 + 0.011 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.060 + 0.011 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.366	$0.349 + 0.008 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$	$0.364 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.471	$0.453 + 0.009 \cdot \text{SL}$	$0.461 + 0.007 \cdot \text{SL}$	$0.471 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA33/OA33D2/OA33D4

Two 3-ORs into 2-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA33D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.092	$0.079 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.062 + 0.007 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.337	$0.327 + 0.005 \cdot \text{SL}$	$0.333 + 0.004 \cdot \text{SL}$	$0.346 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.397	$0.386 + 0.005 \cdot \text{SL}$	$0.392 + 0.004 \cdot \text{SL}$	$0.408 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.358	$0.348 + 0.005 \cdot \text{SL}$	$0.354 + 0.004 \cdot \text{SL}$	$0.367 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.450	$0.439 + 0.005 \cdot \text{SL}$	$0.445 + 0.004 \cdot \text{SL}$	$0.461 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.091	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.067 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.367	$0.356 + 0.005 \cdot \text{SL}$	$0.362 + 0.004 \cdot \text{SL}$	$0.376 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.489	$0.478 + 0.005 \cdot \text{SL}$	$0.484 + 0.004 \cdot \text{SL}$	$0.501 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.093	$0.082 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.364	$0.354 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.374 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.407	$0.397 + 0.005 \cdot \text{SL}$	$0.402 + 0.004 \cdot \text{SL}$	$0.419 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.093	$0.082 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.064 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.387	$0.377 + 0.005 \cdot \text{SL}$	$0.383 + 0.004 \cdot \text{SL}$	$0.397 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.460	$0.449 + 0.005 \cdot \text{SL}$	$0.455 + 0.004 \cdot \text{SL}$	$0.471 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.093	$0.081 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.065 + 0.007 \cdot \text{SL}$
	t_F	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.398	$0.388 + 0.005 \cdot \text{SL}$	$0.394 + 0.004 \cdot \text{SL}$	$0.408 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.501	$0.491 + 0.005 \cdot \text{SL}$	$0.496 + 0.004 \cdot \text{SL}$	$0.513 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA331/OA331D2/OA331D4

Two 3-ORs into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	x	x	x	x	1
x	x	x	0	0	0	x	1
x	x	x	x	x	x	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA331							OA331
A	B	C	D	E	F	G	2.67
0.8	0.9	0.9	0.8	0.9	0.9	1.1	
OA331D2							OA331D2
A	B	C	D	E	F	G	3.33
0.8	0.9	0.9	0.8	0.9	0.9	1.1	
OA331D4							OA331D4
A	B	C	D	E	F	G	4.00
0.8	0.9	0.9	0.8	0.9	0.9	1.1	

OA331/OA331D2/OA331D4

Two 3-ORs into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA331

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.583	$0.428 + 0.077 \cdot \text{SL}$	$0.413 + 0.081 \cdot \text{SL}$	$0.399 + 0.083 \cdot \text{SL}$
	t_F	0.445	$0.294 + 0.076 \cdot \text{SL}$	$0.289 + 0.077 \cdot \text{SL}$	$0.287 + 0.077 \cdot \text{SL}$
	t_{PLH}	0.191	$0.117 + 0.037 \cdot \text{SL}$	$0.118 + 0.037 \cdot \text{SL}$	$0.122 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.268	$0.193 + 0.038 \cdot \text{SL}$	$0.197 + 0.037 \cdot \text{SL}$	$0.202 + 0.036 \cdot \text{SL}$
B to Y	t_R	0.583	$0.425 + 0.079 \cdot \text{SL}$	$0.417 + 0.081 \cdot \text{SL}$	$0.403 + 0.083 \cdot \text{SL}$
	t_F	0.504	$0.349 + 0.077 \cdot \text{SL}$	$0.345 + 0.078 \cdot \text{SL}$	$0.344 + 0.079 \cdot \text{SL}$
	t_{PLH}	0.213	$0.138 + 0.038 \cdot \text{SL}$	$0.140 + 0.037 \cdot \text{SL}$	$0.145 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.310	$0.235 + 0.038 \cdot \text{SL}$	$0.238 + 0.037 \cdot \text{SL}$	$0.242 + 0.037 \cdot \text{SL}$
C to Y	t_R	0.580	$0.421 + 0.080 \cdot \text{SL}$	$0.413 + 0.082 \cdot \text{SL}$	$0.403 + 0.083 \cdot \text{SL}$
	t_F	0.561	$0.407 + 0.077 \cdot \text{SL}$	$0.403 + 0.078 \cdot \text{SL}$	$0.402 + 0.078 \cdot \text{SL}$
	t_{PLH}	0.223	$0.147 + 0.038 \cdot \text{SL}$	$0.150 + 0.037 \cdot \text{SL}$	$0.156 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.341	$0.264 + 0.038 \cdot \text{SL}$	$0.268 + 0.037 \cdot \text{SL}$	$0.273 + 0.037 \cdot \text{SL}$
D to Y	t_R	0.531	$0.373 + 0.079 \cdot \text{SL}$	$0.364 + 0.081 \cdot \text{SL}$	$0.355 + 0.082 \cdot \text{SL}$
	t_F	0.444	$0.291 + 0.076 \cdot \text{SL}$	$0.287 + 0.077 \cdot \text{SL}$	$0.284 + 0.078 \cdot \text{SL}$
	t_{PLH}	0.227	$0.155 + 0.036 \cdot \text{SL}$	$0.157 + 0.036 \cdot \text{SL}$	$0.159 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.287	$0.210 + 0.038 \cdot \text{SL}$	$0.215 + 0.037 \cdot \text{SL}$	$0.221 + 0.037 \cdot \text{SL}$
E to Y	t_R	0.533	$0.373 + 0.080 \cdot \text{SL}$	$0.368 + 0.081 \cdot \text{SL}$	$0.360 + 0.082 \cdot \text{SL}$
	t_F	0.504	$0.349 + 0.078 \cdot \text{SL}$	$0.346 + 0.078 \cdot \text{SL}$	$0.344 + 0.079 \cdot \text{SL}$
	t_{PLH}	0.252	$0.179 + 0.036 \cdot \text{SL}$	$0.181 + 0.036 \cdot \text{SL}$	$0.185 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.330	$0.254 + 0.038 \cdot \text{SL}$	$0.257 + 0.037 \cdot \text{SL}$	$0.262 + 0.037 \cdot \text{SL}$
F to Y	t_R	0.530	$0.370 + 0.080 \cdot \text{SL}$	$0.365 + 0.082 \cdot \text{SL}$	$0.359 + 0.082 \cdot \text{SL}$
	t_F	0.561	$0.407 + 0.077 \cdot \text{SL}$	$0.405 + 0.078 \cdot \text{SL}$	$0.402 + 0.078 \cdot \text{SL}$
	t_{PLH}	0.262	$0.189 + 0.037 \cdot \text{SL}$	$0.192 + 0.036 \cdot \text{SL}$	$0.195 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.361	$0.284 + 0.038 \cdot \text{SL}$	$0.288 + 0.037 \cdot \text{SL}$	$0.294 + 0.037 \cdot \text{SL}$
G to Y	t_R	0.266	$0.220 + 0.023 \cdot \text{SL}$	$0.211 + 0.025 \cdot \text{SL}$	$0.193 + 0.027 \cdot \text{SL}$
	t_F	0.560	$0.406 + 0.077 \cdot \text{SL}$	$0.404 + 0.078 \cdot \text{SL}$	$0.402 + 0.078 \cdot \text{SL}$
	t_{PLH}	0.125	$0.098 + 0.013 \cdot \text{SL}$	$0.100 + 0.013 \cdot \text{SL}$	$0.102 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.356	$0.278 + 0.039 \cdot \text{SL}$	$0.283 + 0.037 \cdot \text{SL}$	$0.289 + 0.037 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA331D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	$0.072 + 0.013 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.057 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.336	$0.318 + 0.009 \cdot \text{SL}$	$0.326 + 0.007 \cdot \text{SL}$	$0.334 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.391	$0.373 + 0.009 \cdot \text{SL}$	$0.380 + 0.007 \cdot \text{SL}$	$0.391 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.097	$0.072 + 0.013 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.356	$0.339 + 0.009 \cdot \text{SL}$	$0.346 + 0.007 \cdot \text{SL}$	$0.355 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.436	$0.418 + 0.009 \cdot \text{SL}$	$0.426 + 0.007 \cdot \text{SL}$	$0.437 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.097	$0.073 + 0.012 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.062 + 0.011 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.366	$0.348 + 0.009 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$	$0.364 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.473	$0.455 + 0.009 \cdot \text{SL}$	$0.463 + 0.007 \cdot \text{SL}$	$0.474 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.099	$0.074 + 0.013 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.057 + 0.011 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.368	$0.351 + 0.009 \cdot \text{SL}$	$0.358 + 0.007 \cdot \text{SL}$	$0.366 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.403	$0.386 + 0.009 \cdot \text{SL}$	$0.393 + 0.007 \cdot \text{SL}$	$0.404 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.099	$0.075 + 0.012 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.012 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.391	$0.374 + 0.009 \cdot \text{SL}$	$0.381 + 0.007 \cdot \text{SL}$	$0.390 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.455	$0.437 + 0.009 \cdot \text{SL}$	$0.445 + 0.007 \cdot \text{SL}$	$0.456 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.099	$0.074 + 0.013 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.062 + 0.011 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.401	$0.384 + 0.009 \cdot \text{SL}$	$0.392 + 0.007 \cdot \text{SL}$	$0.400 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.492	$0.474 + 0.009 \cdot \text{SL}$	$0.482 + 0.007 \cdot \text{SL}$	$0.493 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.061 + 0.012 \cdot \text{SL}$	$0.064 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.255	$0.239 + 0.008 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$	$0.252 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.488	$0.470 + 0.009 \cdot \text{SL}$	$0.477 + 0.007 \cdot \text{SL}$	$0.489 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA331/OA331D2/OA331D4

Two 3-ORs into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA331D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.094	$0.083 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_F	0.078	$0.066 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.366	$0.355 + 0.005 \cdot \text{SL}$	$0.361 + 0.004 \cdot \text{SL}$	$0.375 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.424	$0.414 + 0.005 \cdot \text{SL}$	$0.419 + 0.004 \cdot \text{SL}$	$0.436 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.093	$0.082 + 0.006 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.387	$0.377 + 0.005 \cdot \text{SL}$	$0.383 + 0.004 \cdot \text{SL}$	$0.396 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.471	$0.460 + 0.005 \cdot \text{SL}$	$0.466 + 0.004 \cdot \text{SL}$	$0.483 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.093	$0.081 + 0.006 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$
	t_F	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.396	$0.386 + 0.005 \cdot \text{SL}$	$0.392 + 0.004 \cdot \text{SL}$	$0.406 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.508	$0.497 + 0.005 \cdot \text{SL}$	$0.503 + 0.004 \cdot \text{SL}$	$0.520 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.078	$0.066 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.398	$0.387 + 0.005 \cdot \text{SL}$	$0.394 + 0.004 \cdot \text{SL}$	$0.408 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.437	$0.426 + 0.005 \cdot \text{SL}$	$0.433 + 0.004 \cdot \text{SL}$	$0.449 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.082 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.422	$0.411 + 0.005 \cdot \text{SL}$	$0.417 + 0.004 \cdot \text{SL}$	$0.431 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.489	$0.478 + 0.005 \cdot \text{SL}$	$0.484 + 0.004 \cdot \text{SL}$	$0.501 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.095	$0.083 + 0.006 \cdot \text{SL}$	$0.082 + 0.006 \cdot \text{SL}$	$0.068 + 0.007 \cdot \text{SL}$
	t_F	0.083	$0.070 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.432	$0.421 + 0.005 \cdot \text{SL}$	$0.427 + 0.004 \cdot \text{SL}$	$0.441 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.527	$0.516 + 0.005 \cdot \text{SL}$	$0.522 + 0.004 \cdot \text{SL}$	$0.539 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.055 + 0.007 \cdot \text{SL}$
	t_F	0.082	$0.070 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.271	$0.261 + 0.005 \cdot \text{SL}$	$0.266 + 0.004 \cdot \text{SL}$	$0.277 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.523	$0.512 + 0.005 \cdot \text{SL}$	$0.518 + 0.004 \cdot \text{SL}$	$0.535 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA332/OA332D2/OA332D4

Two 3-ORs and 2-OR into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	0	x	x	x	x	x	1
x	x	x	0	0	0	x	x	1
x	x	x	x	x	x	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
OA332								OA332
A	B	C	D	E	F	G	H	
0.8	0.8	0.9	0.8	0.9	0.9	0.9	0.9	3.00
OA332D2								OA332D2
A	B	C	D	E	F	G	H	
0.8	0.9	0.9	0.8	0.9	0.9	0.9	0.9	4.00
OA332D4								OA332D4
A	B	C	D	E	F	G	H	
0.8	0.9	0.9	0.8	0.9	0.9	0.9	0.9	4.67

OA332/OA332D2/OA332D4

Two 3-ORs and 2-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA332

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.667	$0.511 + 0.078 \cdot \text{SL}$	$0.497 + 0.081 \cdot \text{SL}$	$0.482 + 0.083 \cdot \text{SL}$
	t_F	0.480	$0.312 + 0.084 \cdot \text{SL}$	$0.308 + 0.085 \cdot \text{SL}$	$0.307 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.209	$0.134 + 0.038 \cdot \text{SL}$	$0.137 + 0.037 \cdot \text{SL}$	$0.142 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.293	$0.210 + 0.042 \cdot \text{SL}$	$0.214 + 0.040 \cdot \text{SL}$	$0.219 + 0.040 \cdot \text{SL}$
B to Y	t_R	0.667	$0.509 + 0.079 \cdot \text{SL}$	$0.500 + 0.081 \cdot \text{SL}$	$0.487 + 0.083 \cdot \text{SL}$
	t_F	0.543	$0.373 + 0.085 \cdot \text{SL}$	$0.370 + 0.086 \cdot \text{SL}$	$0.370 + 0.086 \cdot \text{SL}$
	t_{PLH}	0.232	$0.156 + 0.038 \cdot \text{SL}$	$0.159 + 0.037 \cdot \text{SL}$	$0.166 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.339	$0.255 + 0.042 \cdot \text{SL}$	$0.259 + 0.041 \cdot \text{SL}$	$0.263 + 0.040 \cdot \text{SL}$
C to Y	t_R	0.663	$0.504 + 0.080 \cdot \text{SL}$	$0.496 + 0.082 \cdot \text{SL}$	$0.486 + 0.083 \cdot \text{SL}$
	t_F	0.605	$0.436 + 0.085 \cdot \text{SL}$	$0.433 + 0.085 \cdot \text{SL}$	$0.433 + 0.085 \cdot \text{SL}$
	t_{PLH}	0.242	$0.165 + 0.038 \cdot \text{SL}$	$0.169 + 0.037 \cdot \text{SL}$	$0.177 + 0.036 \cdot \text{SL}$
	t_{PHL}	0.373	$0.289 + 0.042 \cdot \text{SL}$	$0.293 + 0.041 \cdot \text{SL}$	$0.298 + 0.040 \cdot \text{SL}$
D to Y	t_R	0.615	$0.457 + 0.079 \cdot \text{SL}$	$0.447 + 0.081 \cdot \text{SL}$	$0.437 + 0.082 \cdot \text{SL}$
	t_F	0.634	$0.435 + 0.100 \cdot \text{SL}$	$0.435 + 0.100 \cdot \text{SL}$	$0.433 + 0.100 \cdot \text{SL}$
	t_{PLH}	0.244	$0.171 + 0.036 \cdot \text{SL}$	$0.173 + 0.036 \cdot \text{SL}$	$0.176 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.416	$0.319 + 0.048 \cdot \text{SL}$	$0.324 + 0.047 \cdot \text{SL}$	$0.330 + 0.046 \cdot \text{SL}$
E to Y	t_R	0.616	$0.456 + 0.080 \cdot \text{SL}$	$0.451 + 0.081 \cdot \text{SL}$	$0.442 + 0.082 \cdot \text{SL}$
	t_F	0.706	$0.506 + 0.100 \cdot \text{SL}$	$0.506 + 0.100 \cdot \text{SL}$	$0.506 + 0.100 \cdot \text{SL}$
	t_{PLH}	0.269	$0.196 + 0.037 \cdot \text{SL}$	$0.199 + 0.036 \cdot \text{SL}$	$0.202 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.468	$0.372 + 0.048 \cdot \text{SL}$	$0.375 + 0.047 \cdot \text{SL}$	$0.380 + 0.046 \cdot \text{SL}$
F to Y	t_R	0.613	$0.452 + 0.080 \cdot \text{SL}$	$0.447 + 0.082 \cdot \text{SL}$	$0.441 + 0.082 \cdot \text{SL}$
	t_F	0.777	$0.578 + 0.099 \cdot \text{SL}$	$0.579 + 0.099 \cdot \text{SL}$	$0.578 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.279	$0.206 + 0.037 \cdot \text{SL}$	$0.209 + 0.036 \cdot \text{SL}$	$0.213 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.509	$0.414 + 0.048 \cdot \text{SL}$	$0.417 + 0.047 \cdot \text{SL}$	$0.423 + 0.046 \cdot \text{SL}$
G to Y	t_R	0.456	$0.354 + 0.051 \cdot \text{SL}$	$0.344 + 0.054 \cdot \text{SL}$	$0.327 + 0.055 \cdot \text{SL}$
	t_F	0.702	$0.505 + 0.098 \cdot \text{SL}$	$0.505 + 0.098 \cdot \text{SL}$	$0.503 + 0.098 \cdot \text{SL}$
	t_{PLH}	0.202	$0.152 + 0.025 \cdot \text{SL}$	$0.154 + 0.024 \cdot \text{SL}$	$0.158 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.468	$0.372 + 0.048 \cdot \text{SL}$	$0.377 + 0.047 \cdot \text{SL}$	$0.385 + 0.046 \cdot \text{SL}$
H to Y	t_R	0.450	$0.345 + 0.053 \cdot \text{SL}$	$0.338 + 0.054 \cdot \text{SL}$	$0.328 + 0.055 \cdot \text{SL}$
	t_F	0.777	$0.578 + 0.100 \cdot \text{SL}$	$0.579 + 0.099 \cdot \text{SL}$	$0.578 + 0.099 \cdot \text{SL}$
	t_{PLH}	0.204	$0.154 + 0.025 \cdot \text{SL}$	$0.156 + 0.024 \cdot \text{SL}$	$0.160 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.521	$0.425 + 0.048 \cdot \text{SL}$	$0.428 + 0.047 \cdot \text{SL}$	$0.434 + 0.046 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA332D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	$0.075 + 0.012 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.057 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.356	$0.338 + 0.009 \cdot \text{SL}$	$0.346 + 0.007 \cdot \text{SL}$	$0.355 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.409	$0.391 + 0.009 \cdot \text{SL}$	$0.399 + 0.007 \cdot \text{SL}$	$0.409 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.099	$0.077 + 0.011 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.058 + 0.012 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.377	$0.360 + 0.009 \cdot \text{SL}$	$0.367 + 0.007 \cdot \text{SL}$	$0.376 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.463	$0.445 + 0.009 \cdot \text{SL}$	$0.453 + 0.007 \cdot \text{SL}$	$0.464 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.100	$0.075 + 0.012 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.060 + 0.012 \cdot \text{SL}$	$0.065 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.387	$0.370 + 0.009 \cdot \text{SL}$	$0.377 + 0.007 \cdot \text{SL}$	$0.386 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.505	$0.487 + 0.009 \cdot \text{SL}$	$0.494 + 0.007 \cdot \text{SL}$	$0.506 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.075 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.063 + 0.011 \cdot \text{SL}$	$0.064 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.389	$0.371 + 0.009 \cdot \text{SL}$	$0.379 + 0.007 \cdot \text{SL}$	$0.388 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.540	$0.522 + 0.009 \cdot \text{SL}$	$0.530 + 0.007 \cdot \text{SL}$	$0.541 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.101	$0.076 + 0.012 \cdot \text{SL}$	$0.074 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.090	$0.067 + 0.012 \cdot \text{SL}$	$0.069 + 0.011 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.412	$0.394 + 0.009 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.411 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.605	$0.586 + 0.009 \cdot \text{SL}$	$0.594 + 0.007 \cdot \text{SL}$	$0.606 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.093	$0.071 + 0.011 \cdot \text{SL}$	$0.071 + 0.011 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.423	$0.406 + 0.009 \cdot \text{SL}$	$0.414 + 0.007 \cdot \text{SL}$	$0.423 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.656	$0.637 + 0.009 \cdot \text{SL}$	$0.646 + 0.007 \cdot \text{SL}$	$0.658 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.097	$0.072 + 0.013 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.090	$0.067 + 0.011 \cdot \text{SL}$	$0.068 + 0.011 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.346	$0.329 + 0.009 \cdot \text{SL}$	$0.336 + 0.007 \cdot \text{SL}$	$0.344 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.604	$0.585 + 0.009 \cdot \text{SL}$	$0.593 + 0.007 \cdot \text{SL}$	$0.605 + 0.006 \cdot \text{SL}$
H to Y	t_R	0.097	$0.072 + 0.012 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.093	$0.070 + 0.012 \cdot \text{SL}$	$0.072 + 0.011 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.348	$0.331 + 0.009 \cdot \text{SL}$	$0.339 + 0.007 \cdot \text{SL}$	$0.346 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.668	$0.649 + 0.009 \cdot \text{SL}$	$0.657 + 0.007 \cdot \text{SL}$	$0.669 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OA332/OA332D2/OA332D4

Two 3-ORs and 2-OR into 3-NAND with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA332D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	$0.087 + 0.006 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$
	t_F	0.078	$0.066 + 0.006 \cdot \text{SL}$	$0.068 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.391	$0.381 + 0.005 \cdot \text{SL}$	$0.387 + 0.004 \cdot \text{SL}$	$0.402 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.441	$0.430 + 0.005 \cdot \text{SL}$	$0.436 + 0.004 \cdot \text{SL}$	$0.453 + 0.003 \cdot \text{SL}$
B to Y	t_R	0.098	$0.087 + 0.006 \cdot \text{SL}$	$0.084 + 0.006 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$
	t_F	0.081	$0.070 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.413	$0.403 + 0.005 \cdot \text{SL}$	$0.409 + 0.004 \cdot \text{SL}$	$0.424 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.496	$0.485 + 0.006 \cdot \text{SL}$	$0.491 + 0.004 \cdot \text{SL}$	$0.508 + 0.003 \cdot \text{SL}$
C to Y	t_R	0.098	$0.085 + 0.006 \cdot \text{SL}$	$0.085 + 0.006 \cdot \text{SL}$	$0.069 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.073 + 0.005 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.423	$0.412 + 0.005 \cdot \text{SL}$	$0.419 + 0.004 \cdot \text{SL}$	$0.434 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.538	$0.527 + 0.006 \cdot \text{SL}$	$0.533 + 0.004 \cdot \text{SL}$	$0.550 + 0.003 \cdot \text{SL}$
D to Y	t_R	0.100	$0.088 + 0.006 \cdot \text{SL}$	$0.086 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$
	t_F	0.085	$0.073 + 0.006 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.425	$0.414 + 0.005 \cdot \text{SL}$	$0.420 + 0.004 \cdot \text{SL}$	$0.435 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.574	$0.563 + 0.006 \cdot \text{SL}$	$0.570 + 0.004 \cdot \text{SL}$	$0.587 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.100	$0.088 + 0.006 \cdot \text{SL}$	$0.087 + 0.006 \cdot \text{SL}$	$0.072 + 0.007 \cdot \text{SL}$
	t_F	0.089	$0.078 + 0.005 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.448	$0.437 + 0.005 \cdot \text{SL}$	$0.444 + 0.004 \cdot \text{SL}$	$0.458 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.639	$0.628 + 0.006 \cdot \text{SL}$	$0.634 + 0.004 \cdot \text{SL}$	$0.652 + 0.003 \cdot \text{SL}$
F to Y	t_R	0.100	$0.088 + 0.006 \cdot \text{SL}$	$0.086 + 0.006 \cdot \text{SL}$	$0.071 + 0.007 \cdot \text{SL}$
	t_F	0.092	$0.080 + 0.006 \cdot \text{SL}$	$0.083 + 0.005 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.459	$0.448 + 0.005 \cdot \text{SL}$	$0.455 + 0.004 \cdot \text{SL}$	$0.470 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.691	$0.680 + 0.006 \cdot \text{SL}$	$0.686 + 0.004 \cdot \text{SL}$	$0.704 + 0.003 \cdot \text{SL}$
G to Y	t_R	0.094	$0.083 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.089	$0.078 + 0.005 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.376	$0.366 + 0.005 \cdot \text{SL}$	$0.372 + 0.004 \cdot \text{SL}$	$0.386 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.641	$0.630 + 0.006 \cdot \text{SL}$	$0.637 + 0.004 \cdot \text{SL}$	$0.654 + 0.003 \cdot \text{SL}$
H to Y	t_R	0.094	$0.083 + 0.006 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.067 + 0.007 \cdot \text{SL}$
	t_F	0.093	$0.083 + 0.005 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.378	$0.368 + 0.005 \cdot \text{SL}$	$0.374 + 0.004 \cdot \text{SL}$	$0.388 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.702	$0.690 + 0.006 \cdot \text{SL}$	$0.697 + 0.004 \cdot \text{SL}$	$0.715 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OA4111/OA4111D2

4-OR into 4-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	0	x	x	x	1
x	x	x	x	0	x	x	1
x	x	x	x	x	0	x	1
x	x	x	x	x	x	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA4111							OA4111
A	B	C	D	E	F	G	2.67
0.9	0.9	0.9	1.0	0.8	0.8	0.9	
OA4111D2							OA4111D2
A	B	C	D	E	F	G	3.67
0.9	0.9	0.9	1.0	0.8	0.8	0.9	

OA4111/OA4111D2

4-OR into 4-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA4111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.544	$0.329 + 0.107 \cdot \text{SL}$	$0.321 + 0.110 \cdot \text{SL}$	$0.320 + 0.110 \cdot \text{SL}$
	t_F	0.328	$0.192 + 0.068 \cdot \text{SL}$	$0.184 + 0.070 \cdot \text{SL}$	$0.176 + 0.071 \cdot \text{SL}$
	t_{PLH}	0.215	$0.121 + 0.047 \cdot \text{SL}$	$0.120 + 0.047 \cdot \text{SL}$	$0.120 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.177	$0.113 + 0.032 \cdot \text{SL}$	$0.111 + 0.032 \cdot \text{SL}$	$0.112 + 0.032 \cdot \text{SL}$
B to Y	t_R	0.557	$0.343 + 0.107 \cdot \text{SL}$	$0.337 + 0.109 \cdot \text{SL}$	$0.332 + 0.109 \cdot \text{SL}$
	t_F	0.380	$0.245 + 0.068 \cdot \text{SL}$	$0.236 + 0.070 \cdot \text{SL}$	$0.230 + 0.071 \cdot \text{SL}$
	t_{PLH}	0.257	$0.161 + 0.048 \cdot \text{SL}$	$0.163 + 0.047 \cdot \text{SL}$	$0.165 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.210	$0.145 + 0.033 \cdot \text{SL}$	$0.145 + 0.032 \cdot \text{SL}$	$0.146 + 0.032 \cdot \text{SL}$
C to Y	t_R	0.558	$0.344 + 0.107 \cdot \text{SL}$	$0.337 + 0.109 \cdot \text{SL}$	$0.332 + 0.109 \cdot \text{SL}$
	t_F	0.439	$0.305 + 0.067 \cdot \text{SL}$	$0.296 + 0.070 \cdot \text{SL}$	$0.287 + 0.071 \cdot \text{SL}$
	t_{PLH}	0.287	$0.190 + 0.048 \cdot \text{SL}$	$0.193 + 0.048 \cdot \text{SL}$	$0.197 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.235	$0.167 + 0.034 \cdot \text{SL}$	$0.171 + 0.033 \cdot \text{SL}$	$0.175 + 0.032 \cdot \text{SL}$
D to Y	t_R	0.556	$0.341 + 0.107 \cdot \text{SL}$	$0.336 + 0.109 \cdot \text{SL}$	$0.332 + 0.109 \cdot \text{SL}$
	t_F	0.491	$0.359 + 0.066 \cdot \text{SL}$	$0.351 + 0.068 \cdot \text{SL}$	$0.341 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.299	$0.202 + 0.048 \cdot \text{SL}$	$0.205 + 0.048 \cdot \text{SL}$	$0.209 + 0.047 \cdot \text{SL}$
	t_{PHL}	0.246	$0.176 + 0.035 \cdot \text{SL}$	$0.183 + 0.033 \cdot \text{SL}$	$0.192 + 0.032 \cdot \text{SL}$
E to Y	t_R	0.322	$0.233 + 0.045 \cdot \text{SL}$	$0.226 + 0.046 \cdot \text{SL}$	$0.214 + 0.048 \cdot \text{SL}$
	t_F	0.488	$0.353 + 0.068 \cdot \text{SL}$	$0.350 + 0.068 \cdot \text{SL}$	$0.343 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.178	$0.136 + 0.021 \cdot \text{SL}$	$0.137 + 0.021 \cdot \text{SL}$	$0.139 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.272	$0.202 + 0.035 \cdot \text{SL}$	$0.208 + 0.033 \cdot \text{SL}$	$0.217 + 0.032 \cdot \text{SL}$
F to Y	t_R	0.344	$0.255 + 0.044 \cdot \text{SL}$	$0.248 + 0.046 \cdot \text{SL}$	$0.236 + 0.048 \cdot \text{SL}$
	t_F	0.487	$0.352 + 0.068 \cdot \text{SL}$	$0.349 + 0.068 \cdot \text{SL}$	$0.343 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.190	$0.148 + 0.021 \cdot \text{SL}$	$0.149 + 0.021 \cdot \text{SL}$	$0.151 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.279	$0.209 + 0.035 \cdot \text{SL}$	$0.216 + 0.033 \cdot \text{SL}$	$0.225 + 0.032 \cdot \text{SL}$
G to Y	t_R	0.368	$0.280 + 0.044 \cdot \text{SL}$	$0.272 + 0.046 \cdot \text{SL}$	$0.259 + 0.048 \cdot \text{SL}$
	t_F	0.486	$0.350 + 0.068 \cdot \text{SL}$	$0.347 + 0.069 \cdot \text{SL}$	$0.343 + 0.069 \cdot \text{SL}$
	t_{PLH}	0.202	$0.159 + 0.021 \cdot \text{SL}$	$0.160 + 0.021 \cdot \text{SL}$	$0.163 + 0.021 \cdot \text{SL}$
	t_{PHL}	0.283	$0.212 + 0.035 \cdot \text{SL}$	$0.219 + 0.033 \cdot \text{SL}$	$0.229 + 0.032 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OA4111D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	$0.065 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.332	$0.315 + 0.008 \cdot \text{SL}$	$0.322 + 0.007 \cdot \text{SL}$	$0.329 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.286	$0.267 + 0.009 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.286 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.091	$0.067 + 0.012 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.055 + 0.011 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.373	$0.356 + 0.008 \cdot \text{SL}$	$0.363 + 0.007 \cdot \text{SL}$	$0.370 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.327	$0.309 + 0.009 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.092	$0.066 + 0.013 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.403	$0.386 + 0.008 \cdot \text{SL}$	$0.393 + 0.007 \cdot \text{SL}$	$0.400 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.359	$0.341 + 0.009 \cdot \text{SL}$	$0.349 + 0.007 \cdot \text{SL}$	$0.360 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.091	$0.067 + 0.012 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.012 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.415	$0.398 + 0.008 \cdot \text{SL}$	$0.405 + 0.007 \cdot \text{SL}$	$0.412 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.376	$0.358 + 0.009 \cdot \text{SL}$	$0.366 + 0.007 \cdot \text{SL}$	$0.377 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.086	$0.061 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.057 + 0.012 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.308	$0.291 + 0.008 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.304 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.401	$0.383 + 0.009 \cdot \text{SL}$	$0.391 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$
F to Y	t_R	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.060 + 0.011 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.323	$0.307 + 0.008 \cdot \text{SL}$	$0.313 + 0.007 \cdot \text{SL}$	$0.320 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.409	$0.390 + 0.009 \cdot \text{SL}$	$0.398 + 0.007 \cdot \text{SL}$	$0.409 + 0.006 \cdot \text{SL}$
G to Y	t_R	0.088	$0.064 + 0.012 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.060 + 0.011 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.337	$0.321 + 0.008 \cdot \text{SL}$	$0.327 + 0.007 \cdot \text{SL}$	$0.334 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.412	$0.394 + 0.009 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.413 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG1/SCG1D2

2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	1
x	x	1	1	x	x	x	x	1
x	x	x	x	1	x	x	x	1
x	x	x	x	x	1	1	x	1
x	x	x	x	x	x	x	1	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
SCG1								SCG1
A	B	C	D	E	F	G	H	3.67
0.8	0.9	0.8	0.8	0.8	0.8	0.8	0.8	
SCG1D2								SCG1D2
A	B	C	D	E	F	G	H	4.67
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	

2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 1X/2X Drive

Switching Characteristics
SCG1(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.170	$0.080 + 0.045 \cdot \text{SL}$	$0.076 + 0.046 \cdot \text{SL}$	$0.071 + 0.046 \cdot \text{SL}$
	t_F	0.186	$0.093 + 0.046 \cdot \text{SL}$	$0.089 + 0.048 \cdot \text{SL}$	$0.084 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.168	$0.126 + 0.021 \cdot \text{SL}$	$0.129 + 0.020 \cdot \text{SL}$	$0.131 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.175	$0.129 + 0.023 \cdot \text{SL}$	$0.132 + 0.022 \cdot \text{SL}$	$0.132 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.170	$0.081 + 0.045 \cdot \text{SL}$	$0.076 + 0.046 \cdot \text{SL}$	$0.071 + 0.046 \cdot \text{SL}$
	t_F	0.188	$0.096 + 0.046 \cdot \text{SL}$	$0.090 + 0.048 \cdot \text{SL}$	$0.085 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.164	$0.122 + 0.021 \cdot \text{SL}$	$0.126 + 0.020 \cdot \text{SL}$	$0.127 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.188	$0.142 + 0.023 \cdot \text{SL}$	$0.145 + 0.022 \cdot \text{SL}$	$0.145 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.193	$0.106 + 0.044 \cdot \text{SL}$	$0.102 + 0.045 \cdot \text{SL}$	$0.094 + 0.045 \cdot \text{SL}$
	t_F	0.195	$0.102 + 0.047 \cdot \text{SL}$	$0.100 + 0.047 \cdot \text{SL}$	$0.094 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.205	$0.163 + 0.021 \cdot \text{SL}$	$0.167 + 0.020 \cdot \text{SL}$	$0.168 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.209	$0.161 + 0.024 \cdot \text{SL}$	$0.167 + 0.023 \cdot \text{SL}$	$0.170 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.193	$0.107 + 0.043 \cdot \text{SL}$	$0.102 + 0.045 \cdot \text{SL}$	$0.094 + 0.045 \cdot \text{SL}$
	t_F	0.198	$0.106 + 0.046 \cdot \text{SL}$	$0.103 + 0.047 \cdot \text{SL}$	$0.095 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.199	$0.158 + 0.021 \cdot \text{SL}$	$0.161 + 0.020 \cdot \text{SL}$	$0.163 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.225	$0.177 + 0.024 \cdot \text{SL}$	$0.183 + 0.023 \cdot \text{SL}$	$0.187 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.190	$0.102 + 0.044 \cdot \text{SL}$	$0.098 + 0.045 \cdot \text{SL}$	$0.092 + 0.046 \cdot \text{SL}$
	t_F	0.199	$0.107 + 0.046 \cdot \text{SL}$	$0.103 + 0.047 \cdot \text{SL}$	$0.096 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.205	$0.164 + 0.021 \cdot \text{SL}$	$0.167 + 0.020 \cdot \text{SL}$	$0.168 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.240	$0.192 + 0.024 \cdot \text{SL}$	$0.198 + 0.023 \cdot \text{SL}$	$0.201 + 0.022 \cdot \text{SL}$
F to Y	t_R	0.214	$0.129 + 0.043 \cdot \text{SL}$	$0.125 + 0.044 \cdot \text{SL}$	$0.116 + 0.045 \cdot \text{SL}$
	t_F	0.192	$0.098 + 0.047 \cdot \text{SL}$	$0.097 + 0.047 \cdot \text{SL}$	$0.092 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.218	$0.177 + 0.021 \cdot \text{SL}$	$0.180 + 0.020 \cdot \text{SL}$	$0.182 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.216	$0.168 + 0.024 \cdot \text{SL}$	$0.173 + 0.023 \cdot \text{SL}$	$0.177 + 0.022 \cdot \text{SL}$
G to Y	t_R	0.215	$0.130 + 0.043 \cdot \text{SL}$	$0.125 + 0.044 \cdot \text{SL}$	$0.116 + 0.045 \cdot \text{SL}$
	t_F	0.196	$0.103 + 0.046 \cdot \text{SL}$	$0.100 + 0.047 \cdot \text{SL}$	$0.094 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.212	$0.170 + 0.021 \cdot \text{SL}$	$0.174 + 0.020 \cdot \text{SL}$	$0.176 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.230	$0.182 + 0.024 \cdot \text{SL}$	$0.187 + 0.023 \cdot \text{SL}$	$0.191 + 0.022 \cdot \text{SL}$
H to Y	t_R	0.211	$0.126 + 0.043 \cdot \text{SL}$	$0.120 + 0.044 \cdot \text{SL}$	$0.113 + 0.045 \cdot \text{SL}$
	t_F	0.196	$0.104 + 0.046 \cdot \text{SL}$	$0.100 + 0.047 \cdot \text{SL}$	$0.094 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.217	$0.176 + 0.020 \cdot \text{SL}$	$0.179 + 0.020 \cdot \text{SL}$	$0.180 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.246	$0.198 + 0.024 \cdot \text{SL}$	$0.203 + 0.023 \cdot \text{SL}$	$0.206 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG1/SCG1D2

2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 1X/2X Drive


Switching Characteristics SCG1D2

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20ns$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.119	$0.077 + 0.021*SL$	$0.073 + 0.022*SL$	$0.065 + 0.023*SL$
	t_F	0.131	$0.085 + 0.023*SL$	$0.084 + 0.023*SL$	$0.078 + 0.024*SL$
	t_{PLH}	0.164	$0.142 + 0.011*SL$	$0.147 + 0.010*SL$	$0.151 + 0.010*SL$
	t_{PHL}	0.166	$0.141 + 0.012*SL$	$0.146 + 0.011*SL$	$0.148 + 0.011*SL$
B to Y	t_R	0.118	$0.075 + 0.022*SL$	$0.074 + 0.022*SL$	$0.065 + 0.023*SL$
	t_F	0.134	$0.089 + 0.023*SL$	$0.087 + 0.023*SL$	$0.079 + 0.024*SL$
	t_{PLH}	0.159	$0.135 + 0.012*SL$	$0.141 + 0.010*SL$	$0.146 + 0.010*SL$
	t_{PHL}	0.177	$0.152 + 0.012*SL$	$0.157 + 0.011*SL$	$0.159 + 0.011*SL$
C to Y	t_R	0.153	$0.112 + 0.021*SL$	$0.107 + 0.022*SL$	$0.095 + 0.023*SL$
	t_F	0.148	$0.102 + 0.023*SL$	$0.102 + 0.023*SL$	$0.094 + 0.024*SL$
	t_{PLH}	0.215	$0.192 + 0.012*SL$	$0.197 + 0.010*SL$	$0.203 + 0.010*SL$
	t_{PHL}	0.210	$0.183 + 0.013*SL$	$0.190 + 0.012*SL$	$0.199 + 0.011*SL$
D to Y	t_R	0.153	$0.111 + 0.021*SL$	$0.107 + 0.022*SL$	$0.096 + 0.023*SL$
	t_F	0.152	$0.107 + 0.023*SL$	$0.107 + 0.023*SL$	$0.096 + 0.024*SL$
	t_{PLH}	0.208	$0.185 + 0.012*SL$	$0.190 + 0.010*SL$	$0.196 + 0.010*SL$
	t_{PHL}	0.224	$0.197 + 0.014*SL$	$0.204 + 0.012*SL$	$0.214 + 0.011*SL$
E to Y	t_R	0.143	$0.102 + 0.021*SL$	$0.097 + 0.022*SL$	$0.086 + 0.023*SL$
	t_F	0.153	$0.109 + 0.022*SL$	$0.106 + 0.023*SL$	$0.096 + 0.024*SL$
	t_{PLH}	0.201	$0.179 + 0.011*SL$	$0.182 + 0.010*SL$	$0.185 + 0.010*SL$
	t_{PHL}	0.241	$0.214 + 0.013*SL$	$0.220 + 0.012*SL$	$0.230 + 0.011*SL$
F to Y	t_R	0.180	$0.138 + 0.021*SL$	$0.134 + 0.022*SL$	$0.120 + 0.023*SL$
	t_F	0.147	$0.102 + 0.023*SL$	$0.099 + 0.023*SL$	$0.093 + 0.024*SL$
	t_{PLH}	0.232	$0.208 + 0.012*SL$	$0.213 + 0.010*SL$	$0.219 + 0.010*SL$
	t_{PHL}	0.219	$0.193 + 0.013*SL$	$0.198 + 0.012*SL$	$0.207 + 0.011*SL$
G to Y	t_R	0.180	$0.138 + 0.021*SL$	$0.134 + 0.022*SL$	$0.120 + 0.023*SL$
	t_F	0.151	$0.107 + 0.022*SL$	$0.103 + 0.023*SL$	$0.096 + 0.024*SL$
	t_{PLH}	0.226	$0.203 + 0.012*SL$	$0.207 + 0.010*SL$	$0.213 + 0.010*SL$
	t_{PHL}	0.233	$0.207 + 0.013*SL$	$0.212 + 0.012*SL$	$0.222 + 0.011*SL$
H to Y	t_R	0.167	$0.126 + 0.021*SL$	$0.120 + 0.022*SL$	$0.110 + 0.023*SL$
	t_F	0.151	$0.107 + 0.022*SL$	$0.104 + 0.023*SL$	$0.095 + 0.024*SL$
	t_{PLH}	0.214	$0.192 + 0.011*SL$	$0.195 + 0.010*SL$	$0.199 + 0.010*SL$
	t_{PHL}	0.250	$0.223 + 0.013*SL$	$0.229 + 0.012*SL$	$0.239 + 0.011*SL$

*Group1 : $SL < 4$, *Group2 : $4 \leq SL \leq 16$, *Group3 : $16 < SL$

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	1
x	x	1	1	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG2				SCG2D2				SCG2	SCG2D2
A	B	C	D	A	B	C	D		
0.8	0.9	0.9	0.9	0.8	0.9	0.9	0.9	2.00	2.00

SCG2/SCG2D2

Two 2-ANDs into 2-OR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	$0.066 + 0.026 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.068 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.161	$0.131 + 0.015 \cdot \text{SL}$	$0.139 + 0.013 \cdot \text{SL}$	$0.146 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.200	$0.165 + 0.017 \cdot \text{SL}$	$0.177 + 0.014 \cdot \text{SL}$	$0.190 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.119	$0.068 + 0.026 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.123	$0.076 + 0.023 \cdot \text{SL}$	$0.080 + 0.022 \cdot \text{SL}$	$0.075 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.155	$0.125 + 0.015 \cdot \text{SL}$	$0.133 + 0.013 \cdot \text{SL}$	$0.140 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.218	$0.183 + 0.017 \cdot \text{SL}$	$0.195 + 0.014 \cdot \text{SL}$	$0.209 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.122	$0.070 + 0.026 \cdot \text{SL}$	$0.067 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.117	$0.070 + 0.024 \cdot \text{SL}$	$0.074 + 0.023 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.201	$0.170 + 0.015 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.185 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.219	$0.185 + 0.017 \cdot \text{SL}$	$0.196 + 0.014 \cdot \text{SL}$	$0.209 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.123	$0.071 + 0.026 \cdot \text{SL}$	$0.067 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_F	0.122	$0.076 + 0.023 \cdot \text{SL}$	$0.079 + 0.022 \cdot \text{SL}$	$0.074 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.193	$0.163 + 0.015 \cdot \text{SL}$	$0.171 + 0.013 \cdot \text{SL}$	$0.177 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.236	$0.201 + 0.018 \cdot \text{SL}$	$0.213 + 0.014 \cdot \text{SL}$	$0.227 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.094	$0.067 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.104	$0.078 + 0.013 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.172	$0.154 + 0.009 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.209	$0.187 + 0.011 \cdot \text{SL}$	$0.198 + 0.008 \cdot \text{SL}$	$0.220 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.097	$0.071 + 0.013 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.109	$0.083 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.166	$0.146 + 0.010 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$	$0.170 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.226	$0.203 + 0.012 \cdot \text{SL}$	$0.216 + 0.008 \cdot \text{SL}$	$0.239 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.102	$0.075 + 0.014 \cdot \text{SL}$	$0.077 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.104	$0.078 + 0.013 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.208	$0.189 + 0.010 \cdot \text{SL}$	$0.198 + 0.007 \cdot \text{SL}$	$0.213 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.227	$0.205 + 0.011 \cdot \text{SL}$	$0.216 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.102	$0.075 + 0.013 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.110	$0.084 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.201	$0.182 + 0.010 \cdot \text{SL}$	$0.191 + 0.007 \cdot \text{SL}$	$0.206 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.242	$0.219 + 0.011 \cdot \text{SL}$	$0.232 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	1
x	x	1	1	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
SCG3					SCG3D2					SCG3	SCG3D2
A	B	C	D	E	A	B	C	D	E		
0.8	0.8	0.8	0.8	0.9	0.8	0.9	0.8	0.8	1.9	2.67	3.33

SCG3/SCG3D2

Two 2-NANDs into 3-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.167	$0.080 + 0.043 \cdot \text{SL}$	$0.076 + 0.045 \cdot \text{SL}$	$0.071 + 0.045 \cdot \text{SL}$
	t_F	0.185	$0.093 + 0.046 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$	$0.084 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.165	$0.124 + 0.021 \cdot \text{SL}$	$0.127 + 0.020 \cdot \text{SL}$	$0.128 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.173	$0.128 + 0.023 \cdot \text{SL}$	$0.130 + 0.022 \cdot \text{SL}$	$0.131 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.167	$0.080 + 0.043 \cdot \text{SL}$	$0.076 + 0.045 \cdot \text{SL}$	$0.070 + 0.045 \cdot \text{SL}$
	t_F	0.187	$0.096 + 0.045 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.161	$0.119 + 0.021 \cdot \text{SL}$	$0.123 + 0.020 \cdot \text{SL}$	$0.124 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.188	$0.142 + 0.023 \cdot \text{SL}$	$0.145 + 0.022 \cdot \text{SL}$	$0.146 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.191	$0.102 + 0.044 \cdot \text{SL}$	$0.098 + 0.045 \cdot \text{SL}$	$0.092 + 0.046 \cdot \text{SL}$
	t_F	0.185	$0.093 + 0.046 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.180	$0.139 + 0.021 \cdot \text{SL}$	$0.141 + 0.020 \cdot \text{SL}$	$0.142 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.183	$0.137 + 0.023 \cdot \text{SL}$	$0.140 + 0.022 \cdot \text{SL}$	$0.142 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.191	$0.103 + 0.044 \cdot \text{SL}$	$0.098 + 0.045 \cdot \text{SL}$	$0.092 + 0.046 \cdot \text{SL}$
	t_F	0.186	$0.093 + 0.046 \cdot \text{SL}$	$0.091 + 0.047 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.176	$0.134 + 0.021 \cdot \text{SL}$	$0.137 + 0.020 \cdot \text{SL}$	$0.138 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.197	$0.150 + 0.023 \cdot \text{SL}$	$0.154 + 0.022 \cdot \text{SL}$	$0.155 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.225	$0.146 + 0.040 \cdot \text{SL}$	$0.134 + 0.043 \cdot \text{SL}$	$0.116 + 0.045 \cdot \text{SL}$
	t_F	0.193	$0.104 + 0.045 \cdot \text{SL}$	$0.096 + 0.047 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.137	$0.098 + 0.020 \cdot \text{SL}$	$0.099 + 0.019 \cdot \text{SL}$	$0.099 + 0.019 \cdot \text{SL}$
	t_{PHL}	0.110	$0.064 + 0.023 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG3D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	$0.077 + 0.021 \cdot \text{SL}$	$0.074 + 0.022 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_F	0.132	$0.087 + 0.023 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$	$0.078 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.166	$0.142 + 0.012 \cdot \text{SL}$	$0.148 + 0.010 \cdot \text{SL}$	$0.152 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.165	$0.140 + 0.012 \cdot \text{SL}$	$0.144 + 0.011 \cdot \text{SL}$	$0.147 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.120	$0.077 + 0.022 \cdot \text{SL}$	$0.074 + 0.022 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_F	0.135	$0.090 + 0.023 \cdot \text{SL}$	$0.088 + 0.023 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.160	$0.136 + 0.012 \cdot \text{SL}$	$0.142 + 0.010 \cdot \text{SL}$	$0.147 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.176	$0.152 + 0.012 \cdot \text{SL}$	$0.156 + 0.011 \cdot \text{SL}$	$0.159 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.145	$0.102 + 0.021 \cdot \text{SL}$	$0.098 + 0.022 \cdot \text{SL}$	$0.089 + 0.023 \cdot \text{SL}$
	t_F	0.132	$0.087 + 0.023 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.183	$0.160 + 0.011 \cdot \text{SL}$	$0.164 + 0.010 \cdot \text{SL}$	$0.168 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.176	$0.150 + 0.013 \cdot \text{SL}$	$0.156 + 0.011 \cdot \text{SL}$	$0.160 + 0.011 \cdot \text{SL}$
D to Y	t_R	0.145	$0.104 + 0.021 \cdot \text{SL}$	$0.098 + 0.022 \cdot \text{SL}$	$0.089 + 0.023 \cdot \text{SL}$
	t_F	0.135	$0.089 + 0.023 \cdot \text{SL}$	$0.087 + 0.023 \cdot \text{SL}$	$0.081 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.177	$0.154 + 0.011 \cdot \text{SL}$	$0.158 + 0.010 \cdot \text{SL}$	$0.162 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.188	$0.163 + 0.013 \cdot \text{SL}$	$0.168 + 0.011 \cdot \text{SL}$	$0.173 + 0.011 \cdot \text{SL}$
E to Y	t_R	0.179	$0.141 + 0.019 \cdot \text{SL}$	$0.133 + 0.021 \cdot \text{SL}$	$0.110 + 0.022 \cdot \text{SL}$
	t_F	0.139	$0.096 + 0.022 \cdot \text{SL}$	$0.090 + 0.023 \cdot \text{SL}$	$0.081 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.113	$0.092 + 0.011 \cdot \text{SL}$	$0.095 + 0.010 \cdot \text{SL}$	$0.095 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.082	$0.057 + 0.013 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG4/SCG4D2

Two (two 2-ANDs into 2-NOR)s into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	1
x	x	1	1	x	x	x	x	1
x	x	x	x	1	1	x	x	1
x	x	x	x	x	x	1	1	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
SCG4								SCG4
A	B	C	D	E	F	G	H	3.67
0.8	0.9	0.9	0.9	0.8	0.8	0.9	0.9	
SCG4D2								SCG4D2
A	B	C	D	E	F	G	H	4.67
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	

Two (two 2-ANDs into 2-NOR)s into 2-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.138	$0.072 + 0.033 \cdot \text{SL}$	$0.070 + 0.033 \cdot \text{SL}$	$0.063 + 0.034 \cdot \text{SL}$
	t_F	0.148	$0.083 + 0.033 \cdot \text{SL}$	$0.084 + 0.032 \cdot \text{SL}$	$0.079 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.179	$0.144 + 0.018 \cdot \text{SL}$	$0.152 + 0.016 \cdot \text{SL}$	$0.157 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.211	$0.171 + 0.020 \cdot \text{SL}$	$0.182 + 0.017 \cdot \text{SL}$	$0.192 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.138	$0.074 + 0.032 \cdot \text{SL}$	$0.070 + 0.033 \cdot \text{SL}$	$0.063 + 0.034 \cdot \text{SL}$
	t_F	0.153	$0.089 + 0.032 \cdot \text{SL}$	$0.090 + 0.032 \cdot \text{SL}$	$0.084 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.173	$0.137 + 0.018 \cdot \text{SL}$	$0.146 + 0.016 \cdot \text{SL}$	$0.151 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.228	$0.188 + 0.020 \cdot \text{SL}$	$0.199 + 0.017 \cdot \text{SL}$	$0.209 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.142	$0.078 + 0.032 \cdot \text{SL}$	$0.073 + 0.033 \cdot \text{SL}$	$0.065 + 0.034 \cdot \text{SL}$
	t_F	0.149	$0.084 + 0.032 \cdot \text{SL}$	$0.085 + 0.032 \cdot \text{SL}$	$0.080 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.220	$0.184 + 0.018 \cdot \text{SL}$	$0.192 + 0.016 \cdot \text{SL}$	$0.197 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.231	$0.192 + 0.020 \cdot \text{SL}$	$0.202 + 0.017 \cdot \text{SL}$	$0.212 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.144	$0.081 + 0.032 \cdot \text{SL}$	$0.075 + 0.033 \cdot \text{SL}$	$0.065 + 0.034 \cdot \text{SL}$
	t_F	0.154	$0.090 + 0.032 \cdot \text{SL}$	$0.090 + 0.032 \cdot \text{SL}$	$0.084 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.211	$0.176 + 0.018 \cdot \text{SL}$	$0.184 + 0.016 \cdot \text{SL}$	$0.189 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.247	$0.207 + 0.020 \cdot \text{SL}$	$0.218 + 0.017 \cdot \text{SL}$	$0.228 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.156	$0.091 + 0.032 \cdot \text{SL}$	$0.087 + 0.033 \cdot \text{SL}$	$0.079 + 0.034 \cdot \text{SL}$
	t_F	0.140	$0.076 + 0.032 \cdot \text{SL}$	$0.074 + 0.032 \cdot \text{SL}$	$0.068 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.189	$0.155 + 0.017 \cdot \text{SL}$	$0.161 + 0.015 \cdot \text{SL}$	$0.164 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.204	$0.167 + 0.019 \cdot \text{SL}$	$0.174 + 0.017 \cdot \text{SL}$	$0.180 + 0.016 \cdot \text{SL}$
F to Y	t_R	0.156	$0.091 + 0.032 \cdot \text{SL}$	$0.086 + 0.034 \cdot \text{SL}$	$0.079 + 0.034 \cdot \text{SL}$
	t_F	0.145	$0.083 + 0.031 \cdot \text{SL}$	$0.079 + 0.032 \cdot \text{SL}$	$0.071 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.183	$0.148 + 0.017 \cdot \text{SL}$	$0.154 + 0.015 \cdot \text{SL}$	$0.158 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.220	$0.183 + 0.019 \cdot \text{SL}$	$0.190 + 0.017 \cdot \text{SL}$	$0.197 + 0.016 \cdot \text{SL}$
G to Y	t_R	0.165	$0.101 + 0.032 \cdot \text{SL}$	$0.097 + 0.033 \cdot \text{SL}$	$0.086 + 0.034 \cdot \text{SL}$
	t_F	0.141	$0.078 + 0.031 \cdot \text{SL}$	$0.074 + 0.032 \cdot \text{SL}$	$0.069 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.223	$0.188 + 0.017 \cdot \text{SL}$	$0.195 + 0.016 \cdot \text{SL}$	$0.200 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.224	$0.186 + 0.019 \cdot \text{SL}$	$0.194 + 0.017 \cdot \text{SL}$	$0.200 + 0.016 \cdot \text{SL}$
H to Y	t_R	0.166	$0.102 + 0.032 \cdot \text{SL}$	$0.097 + 0.033 \cdot \text{SL}$	$0.088 + 0.034 \cdot \text{SL}$
	t_F	0.146	$0.084 + 0.031 \cdot \text{SL}$	$0.080 + 0.032 \cdot \text{SL}$	$0.072 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.217	$0.182 + 0.018 \cdot \text{SL}$	$0.189 + 0.016 \cdot \text{SL}$	$0.194 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.240	$0.202 + 0.019 \cdot \text{SL}$	$0.210 + 0.017 \cdot \text{SL}$	$0.217 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG4/SCG4D2

Two (two 2-ANDs into 2-NOR)s into 2-NAND with 1X/2X Drive

Switching Characteristics


(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.109	$0.076 + 0.017 \cdot \text{SL}$	$0.076 + 0.016 \cdot \text{SL}$	$0.068 + 0.017 \cdot \text{SL}$
	t_F	0.126	$0.094 + 0.016 \cdot \text{SL}$	$0.094 + 0.016 \cdot \text{SL}$	$0.093 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.185	$0.165 + 0.010 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$	$0.184 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.216	$0.192 + 0.012 \cdot \text{SL}$	$0.202 + 0.009 \cdot \text{SL}$	$0.221 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.109	$0.076 + 0.017 \cdot \text{SL}$	$0.077 + 0.016 \cdot \text{SL}$	$0.068 + 0.017 \cdot \text{SL}$
	t_F	0.133	$0.102 + 0.016 \cdot \text{SL}$	$0.100 + 0.016 \cdot \text{SL}$	$0.098 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.179	$0.158 + 0.010 \cdot \text{SL}$	$0.165 + 0.008 \cdot \text{SL}$	$0.178 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.234	$0.209 + 0.012 \cdot \text{SL}$	$0.220 + 0.010 \cdot \text{SL}$	$0.239 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.120	$0.088 + 0.016 \cdot \text{SL}$	$0.087 + 0.016 \cdot \text{SL}$	$0.075 + 0.017 \cdot \text{SL}$
	t_F	0.127	$0.095 + 0.016 \cdot \text{SL}$	$0.095 + 0.016 \cdot \text{SL}$	$0.093 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.232	$0.211 + 0.011 \cdot \text{SL}$	$0.219 + 0.008 \cdot \text{SL}$	$0.231 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.246	$0.222 + 0.012 \cdot \text{SL}$	$0.232 + 0.009 \cdot \text{SL}$	$0.251 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.120	$0.089 + 0.015 \cdot \text{SL}$	$0.086 + 0.016 \cdot \text{SL}$	$0.074 + 0.017 \cdot \text{SL}$
	t_F	0.135	$0.103 + 0.016 \cdot \text{SL}$	$0.103 + 0.016 \cdot \text{SL}$	$0.099 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.225	$0.205 + 0.010 \cdot \text{SL}$	$0.212 + 0.008 \cdot \text{SL}$	$0.225 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.263	$0.238 + 0.012 \cdot \text{SL}$	$0.248 + 0.010 \cdot \text{SL}$	$0.268 + 0.008 \cdot \text{SL}$
E to Y	t_R	0.130	$0.098 + 0.016 \cdot \text{SL}$	$0.098 + 0.016 \cdot \text{SL}$	$0.086 + 0.017 \cdot \text{SL}$
	t_F	0.122	$0.092 + 0.015 \cdot \text{SL}$	$0.088 + 0.016 \cdot \text{SL}$	$0.083 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.199	$0.180 + 0.010 \cdot \text{SL}$	$0.185 + 0.008 \cdot \text{SL}$	$0.195 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.217	$0.194 + 0.011 \cdot \text{SL}$	$0.203 + 0.009 \cdot \text{SL}$	$0.216 + 0.008 \cdot \text{SL}$
F to Y	t_R	0.130	$0.098 + 0.016 \cdot \text{SL}$	$0.098 + 0.016 \cdot \text{SL}$	$0.087 + 0.017 \cdot \text{SL}$
	t_F	0.129	$0.099 + 0.015 \cdot \text{SL}$	$0.095 + 0.016 \cdot \text{SL}$	$0.088 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.193	$0.174 + 0.010 \cdot \text{SL}$	$0.179 + 0.008 \cdot \text{SL}$	$0.189 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.233	$0.210 + 0.012 \cdot \text{SL}$	$0.219 + 0.009 \cdot \text{SL}$	$0.233 + 0.008 \cdot \text{SL}$
G to Y	t_R	0.144	$0.112 + 0.016 \cdot \text{SL}$	$0.112 + 0.016 \cdot \text{SL}$	$0.101 + 0.017 \cdot \text{SL}$
	t_F	0.123	$0.093 + 0.015 \cdot \text{SL}$	$0.090 + 0.016 \cdot \text{SL}$	$0.083 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.241	$0.221 + 0.010 \cdot \text{SL}$	$0.227 + 0.008 \cdot \text{SL}$	$0.239 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.247	$0.224 + 0.011 \cdot \text{SL}$	$0.232 + 0.009 \cdot \text{SL}$	$0.246 + 0.008 \cdot \text{SL}$
H to Y	t_R	0.145	$0.114 + 0.016 \cdot \text{SL}$	$0.113 + 0.016 \cdot \text{SL}$	$0.100 + 0.017 \cdot \text{SL}$
	t_F	0.130	$0.100 + 0.015 \cdot \text{SL}$	$0.097 + 0.016 \cdot \text{SL}$	$0.088 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.235	$0.215 + 0.010 \cdot \text{SL}$	$0.221 + 0.008 \cdot \text{SL}$	$0.233 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.262	$0.238 + 0.012 \cdot \text{SL}$	$0.248 + 0.009 \cdot \text{SL}$	$0.262 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	x	x	x	x	1
x	x	1	1	x	x	1
x	x	x	x	1	1	1
Other States						0

Cell Data

Input Load (SL)						Gate Count
SCG5						SCG5
A	B	C	D	E	F	2.67
0.8	0.8	0.8	0.8	0.8	0.8	
SCG5D2						SCG5D2
A	B	C	D	E	F	3.00
0.8	0.8	0.8	0.8	0.8	0.8	

SCG5/SCG5D2

Three 2-ANDs into 3-OR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.125	$0.071 + 0.027 \cdot \text{SL}$	$0.071 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$
	t_F	0.158	$0.106 + 0.026 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$	$0.121 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.182	$0.150 + 0.016 \cdot \text{SL}$	$0.159 + 0.013 \cdot \text{SL}$	$0.170 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.268	$0.225 + 0.021 \cdot \text{SL}$	$0.243 + 0.017 \cdot \text{SL}$	$0.266 + 0.014 \cdot \text{SL}$
B to Y	t_R	0.128	$0.076 + 0.026 \cdot \text{SL}$	$0.072 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$
	t_F	0.170	$0.119 + 0.025 \cdot \text{SL}$	$0.125 + 0.024 \cdot \text{SL}$	$0.131 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.175	$0.142 + 0.017 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.291	$0.246 + 0.022 \cdot \text{SL}$	$0.267 + 0.017 \cdot \text{SL}$	$0.291 + 0.014 \cdot \text{SL}$
C to Y	t_R	0.135	$0.083 + 0.026 \cdot \text{SL}$	$0.082 + 0.026 \cdot \text{SL}$	$0.073 + 0.027 \cdot \text{SL}$
	t_F	0.164	$0.113 + 0.026 \cdot \text{SL}$	$0.120 + 0.024 \cdot \text{SL}$	$0.125 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.232	$0.199 + 0.017 \cdot \text{SL}$	$0.211 + 0.014 \cdot \text{SL}$	$0.221 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.341	$0.298 + 0.021 \cdot \text{SL}$	$0.316 + 0.017 \cdot \text{SL}$	$0.339 + 0.014 \cdot \text{SL}$
D to Y	t_R	0.135	$0.083 + 0.026 \cdot \text{SL}$	$0.081 + 0.026 \cdot \text{SL}$	$0.073 + 0.027 \cdot \text{SL}$
	t_F	0.172	$0.121 + 0.026 \cdot \text{SL}$	$0.130 + 0.023 \cdot \text{SL}$	$0.133 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.227	$0.194 + 0.016 \cdot \text{SL}$	$0.205 + 0.014 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.363	$0.319 + 0.022 \cdot \text{SL}$	$0.339 + 0.017 \cdot \text{SL}$	$0.363 + 0.014 \cdot \text{SL}$
E to Y	t_R	0.147	$0.093 + 0.027 \cdot \text{SL}$	$0.095 + 0.026 \cdot \text{SL}$	$0.086 + 0.027 \cdot \text{SL}$
	t_F	0.163	$0.112 + 0.026 \cdot \text{SL}$	$0.119 + 0.024 \cdot \text{SL}$	$0.124 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.258	$0.223 + 0.017 \cdot \text{SL}$	$0.236 + 0.014 \cdot \text{SL}$	$0.249 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.367	$0.324 + 0.021 \cdot \text{SL}$	$0.342 + 0.017 \cdot \text{SL}$	$0.365 + 0.014 \cdot \text{SL}$
F to Y	t_R	0.147	$0.094 + 0.026 \cdot \text{SL}$	$0.094 + 0.026 \cdot \text{SL}$	$0.087 + 0.027 \cdot \text{SL}$
	t_F	0.173	$0.121 + 0.026 \cdot \text{SL}$	$0.130 + 0.023 \cdot \text{SL}$	$0.133 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.253	$0.218 + 0.017 \cdot \text{SL}$	$0.231 + 0.014 \cdot \text{SL}$	$0.244 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.391	$0.347 + 0.022 \cdot \text{SL}$	$0.367 + 0.017 \cdot \text{SL}$	$0.391 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG5D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	$0.076 + 0.014 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.156	$0.126 + 0.015 \cdot \text{SL}$	$0.135 + 0.012 \cdot \text{SL}$	$0.146 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.189	$0.169 + 0.010 \cdot \text{SL}$	$0.179 + 0.008 \cdot \text{SL}$	$0.196 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.290	$0.262 + 0.014 \cdot \text{SL}$	$0.279 + 0.010 \cdot \text{SL}$	$0.313 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.103	$0.075 + 0.014 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.073 + 0.014 \cdot \text{SL}$
	t_F	0.166	$0.137 + 0.015 \cdot \text{SL}$	$0.147 + 0.012 \cdot \text{SL}$	$0.156 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.184	$0.164 + 0.010 \cdot \text{SL}$	$0.173 + 0.008 \cdot \text{SL}$	$0.191 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.312	$0.283 + 0.014 \cdot \text{SL}$	$0.300 + 0.010 \cdot \text{SL}$	$0.336 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.116	$0.089 + 0.013 \cdot \text{SL}$	$0.089 + 0.013 \cdot \text{SL}$	$0.084 + 0.014 \cdot \text{SL}$
	t_F	0.160	$0.131 + 0.015 \cdot \text{SL}$	$0.140 + 0.012 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.240	$0.219 + 0.011 \cdot \text{SL}$	$0.230 + 0.008 \cdot \text{SL}$	$0.249 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.365	$0.338 + 0.014 \cdot \text{SL}$	$0.353 + 0.010 \cdot \text{SL}$	$0.388 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.116	$0.089 + 0.013 \cdot \text{SL}$	$0.090 + 0.013 \cdot \text{SL}$	$0.083 + 0.014 \cdot \text{SL}$
	t_F	0.169	$0.139 + 0.015 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$	$0.159 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.234	$0.213 + 0.011 \cdot \text{SL}$	$0.224 + 0.008 \cdot \text{SL}$	$0.243 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.386	$0.357 + 0.014 \cdot \text{SL}$	$0.374 + 0.010 \cdot \text{SL}$	$0.411 + 0.008 \cdot \text{SL}$
E to Y	t_R	0.125	$0.098 + 0.013 \cdot \text{SL}$	$0.099 + 0.013 \cdot \text{SL}$	$0.093 + 0.014 \cdot \text{SL}$
	t_F	0.159	$0.130 + 0.015 \cdot \text{SL}$	$0.140 + 0.012 \cdot \text{SL}$	$0.148 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.267	$0.245 + 0.011 \cdot \text{SL}$	$0.257 + 0.008 \cdot \text{SL}$	$0.277 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.391	$0.363 + 0.014 \cdot \text{SL}$	$0.379 + 0.010 \cdot \text{SL}$	$0.413 + 0.008 \cdot \text{SL}$
F to Y	t_R	0.125	$0.099 + 0.013 \cdot \text{SL}$	$0.098 + 0.013 \cdot \text{SL}$	$0.094 + 0.014 \cdot \text{SL}$
	t_F	0.169	$0.139 + 0.015 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$	$0.159 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.261	$0.239 + 0.011 \cdot \text{SL}$	$0.252 + 0.008 \cdot \text{SL}$	$0.272 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.414	$0.385 + 0.014 \cdot \text{SL}$	$0.402 + 0.010 \cdot \text{SL}$	$0.438 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG6/SCG6D2

2-AND into 2-OR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	x	1
x	x	1	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG6			SCG6D2			SCG6	SCG6D2
A	B	C	A	B	C	1.67	2.00
0.8	0.8	0.8	0.8	0.8	0.8		

Switching Characteristics(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**SCG6**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	$0.058 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.110	$0.061 + 0.024 \cdot \text{SL}$	$0.065 + 0.023 \cdot \text{SL}$	$0.062 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.157	$0.128 + 0.015 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$	$0.139 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.177	$0.143 + 0.017 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.165 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.113	$0.060 + 0.026 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.066 + 0.025 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.151	$0.121 + 0.015 \cdot \text{SL}$	$0.128 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.193	$0.159 + 0.017 \cdot \text{SL}$	$0.170 + 0.014 \cdot \text{SL}$	$0.182 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.106	$0.052 + 0.027 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.068 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.067 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.160	$0.133 + 0.014 \cdot \text{SL}$	$0.137 + 0.013 \cdot \text{SL}$	$0.138 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.211	$0.176 + 0.017 \cdot \text{SL}$	$0.187 + 0.014 \cdot \text{SL}$	$0.199 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$ **SCG6D2**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	$0.060 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.096	$0.069 + 0.013 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$	$0.076 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.169	$0.150 + 0.009 \cdot \text{SL}$	$0.158 + 0.007 \cdot \text{SL}$	$0.171 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.190	$0.169 + 0.011 \cdot \text{SL}$	$0.179 + 0.008 \cdot \text{SL}$	$0.200 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.092	$0.067 + 0.013 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.102	$0.077 + 0.013 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.161	$0.142 + 0.009 \cdot \text{SL}$	$0.151 + 0.007 \cdot \text{SL}$	$0.164 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.205	$0.183 + 0.011 \cdot \text{SL}$	$0.195 + 0.008 \cdot \text{SL}$	$0.216 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.083	$0.060 + 0.012 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.102	$0.077 + 0.012 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.162	$0.145 + 0.009 \cdot \text{SL}$	$0.152 + 0.007 \cdot \text{SL}$	$0.158 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.223	$0.201 + 0.011 \cdot \text{SL}$	$0.212 + 0.008 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG7/SCG7D2

2-NAND and (2-AND into 2-NOR) into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	1
x	x	1	1	x	1
x	x	x	x	1	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
SCG7					SCG7D2					SCG7	SCG7D2
A	B	C	D	E	A	B	C	D	E	2.67	3.00
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8		

2-NAND and (2-AND into 2-NOR) into 2-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	$0.062 + 0.032 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$	$0.051 + 0.034 \cdot \text{SL}$
	t_F	0.128	$0.063 + 0.032 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$	$0.053 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.148	$0.115 + 0.017 \cdot \text{SL}$	$0.121 + 0.015 \cdot \text{SL}$	$0.123 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.154	$0.119 + 0.018 \cdot \text{SL}$	$0.124 + 0.016 \cdot \text{SL}$	$0.125 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.126	$0.061 + 0.033 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$	$0.051 + 0.034 \cdot \text{SL}$
	t_F	0.130	$0.067 + 0.032 \cdot \text{SL}$	$0.061 + 0.033 \cdot \text{SL}$	$0.055 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.143	$0.110 + 0.017 \cdot \text{SL}$	$0.115 + 0.015 \cdot \text{SL}$	$0.118 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.169	$0.134 + 0.018 \cdot \text{SL}$	$0.139 + 0.016 \cdot \text{SL}$	$0.141 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.148	$0.083 + 0.033 \cdot \text{SL}$	$0.080 + 0.034 \cdot \text{SL}$	$0.072 + 0.035 \cdot \text{SL}$
	t_F	0.135	$0.071 + 0.032 \cdot \text{SL}$	$0.068 + 0.033 \cdot \text{SL}$	$0.062 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.180	$0.147 + 0.017 \cdot \text{SL}$	$0.152 + 0.015 \cdot \text{SL}$	$0.154 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.183	$0.146 + 0.019 \cdot \text{SL}$	$0.152 + 0.017 \cdot \text{SL}$	$0.158 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.152	$0.091 + 0.031 \cdot \text{SL}$	$0.079 + 0.034 \cdot \text{SL}$	$0.073 + 0.034 \cdot \text{SL}$
	t_F	0.139	$0.075 + 0.032 \cdot \text{SL}$	$0.072 + 0.033 \cdot \text{SL}$	$0.065 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.174	$0.141 + 0.017 \cdot \text{SL}$	$0.146 + 0.015 \cdot \text{SL}$	$0.148 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.199	$0.161 + 0.019 \cdot \text{SL}$	$0.168 + 0.017 \cdot \text{SL}$	$0.173 + 0.016 \cdot \text{SL}$
E to Y	t_R	0.143	$0.078 + 0.033 \cdot \text{SL}$	$0.072 + 0.034 \cdot \text{SL}$	$0.066 + 0.035 \cdot \text{SL}$
	t_F	0.140	$0.076 + 0.032 \cdot \text{SL}$	$0.074 + 0.033 \cdot \text{SL}$	$0.065 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.185	$0.153 + 0.016 \cdot \text{SL}$	$0.156 + 0.015 \cdot \text{SL}$	$0.156 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.216	$0.178 + 0.019 \cdot \text{SL}$	$0.185 + 0.017 \cdot \text{SL}$	$0.190 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG7/SCG7D2

2-NAND and (2-AND into 2-NOR) into 2-NAND with 1X/2X Drive

Switching Characteristics


(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG7D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	$0.065 + 0.017 \cdot \text{SL}$	$0.065 + 0.017 \cdot \text{SL}$	$0.056 + 0.017 \cdot \text{SL}$
	t_F	0.098	$0.066 + 0.016 \cdot \text{SL}$	$0.064 + 0.016 \cdot \text{SL}$	$0.057 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.156	$0.137 + 0.010 \cdot \text{SL}$	$0.143 + 0.008 \cdot \text{SL}$	$0.150 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.158	$0.138 + 0.010 \cdot \text{SL}$	$0.144 + 0.009 \cdot \text{SL}$	$0.150 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.099	$0.066 + 0.016 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$	$0.056 + 0.017 \cdot \text{SL}$
	t_F	0.100	$0.067 + 0.017 \cdot \text{SL}$	$0.067 + 0.016 \cdot \text{SL}$	$0.060 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.150	$0.131 + 0.010 \cdot \text{SL}$	$0.136 + 0.008 \cdot \text{SL}$	$0.144 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.171	$0.150 + 0.010 \cdot \text{SL}$	$0.157 + 0.009 \cdot \text{SL}$	$0.163 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.127	$0.095 + 0.016 \cdot \text{SL}$	$0.094 + 0.016 \cdot \text{SL}$	$0.083 + 0.017 \cdot \text{SL}$
	t_F	0.115	$0.084 + 0.015 \cdot \text{SL}$	$0.080 + 0.016 \cdot \text{SL}$	$0.074 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.198	$0.179 + 0.009 \cdot \text{SL}$	$0.184 + 0.008 \cdot \text{SL}$	$0.192 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.199	$0.177 + 0.011 \cdot \text{SL}$	$0.184 + 0.009 \cdot \text{SL}$	$0.195 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.128	$0.095 + 0.016 \cdot \text{SL}$	$0.095 + 0.016 \cdot \text{SL}$	$0.083 + 0.017 \cdot \text{SL}$
	t_F	0.120	$0.089 + 0.015 \cdot \text{SL}$	$0.086 + 0.016 \cdot \text{SL}$	$0.078 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.191	$0.172 + 0.009 \cdot \text{SL}$	$0.177 + 0.008 \cdot \text{SL}$	$0.185 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.213	$0.191 + 0.011 \cdot \text{SL}$	$0.199 + 0.009 \cdot \text{SL}$	$0.210 + 0.008 \cdot \text{SL}$
E to Y	t_R	0.116	$0.086 + 0.015 \cdot \text{SL}$	$0.081 + 0.016 \cdot \text{SL}$	$0.069 + 0.017 \cdot \text{SL}$
	t_F	0.121	$0.091 + 0.015 \cdot \text{SL}$	$0.087 + 0.016 \cdot \text{SL}$	$0.078 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.191	$0.174 + 0.009 \cdot \text{SL}$	$0.177 + 0.008 \cdot \text{SL}$	$0.180 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.231	$0.208 + 0.011 \cdot \text{SL}$	$0.217 + 0.009 \cdot \text{SL}$	$0.228 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	1
x	x	1	x	1
x	x	x	1	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG8				SCG8D2				SCG8	SCG8D2
A	B	C	D	A	B	C	D		
0.7	0.8	0.7	0.8	0.7	0.8	0.7	0.8	2.00	2.33

SCG8/SCG8D2

2-AND into 3-OR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.135	$0.082 + 0.026 \cdot \text{SL}$	$0.090 + 0.024 \cdot \text{SL}$	$0.096 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.178	$0.147 + 0.015 \cdot \text{SL}$	$0.156 + 0.013 \cdot \text{SL}$	$0.162 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.218	$0.178 + 0.020 \cdot \text{SL}$	$0.192 + 0.016 \cdot \text{SL}$	$0.212 + 0.014 \cdot \text{SL}$
B to Y	t_R	0.119	$0.065 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.143	$0.092 + 0.026 \cdot \text{SL}$	$0.097 + 0.024 \cdot \text{SL}$	$0.103 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.171	$0.141 + 0.015 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.156 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.236	$0.195 + 0.020 \cdot \text{SL}$	$0.211 + 0.016 \cdot \text{SL}$	$0.231 + 0.014 \cdot \text{SL}$
C to Y	t_R	0.115	$0.064 + 0.026 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$
	t_F	0.146	$0.094 + 0.026 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$	$0.105 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.195	$0.166 + 0.015 \cdot \text{SL}$	$0.173 + 0.013 \cdot \text{SL}$	$0.175 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.284	$0.244 + 0.020 \cdot \text{SL}$	$0.259 + 0.016 \cdot \text{SL}$	$0.280 + 0.014 \cdot \text{SL}$
D to Y	t_R	0.121	$0.069 + 0.026 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.147	$0.096 + 0.025 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$	$0.105 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.207	$0.177 + 0.015 \cdot \text{SL}$	$0.185 + 0.013 \cdot \text{SL}$	$0.189 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.292	$0.252 + 0.020 \cdot \text{SL}$	$0.267 + 0.016 \cdot \text{SL}$	$0.288 + 0.014 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	$0.070 + 0.013 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$
	t_F	0.131	$0.103 + 0.014 \cdot \text{SL}$	$0.109 + 0.012 \cdot \text{SL}$	$0.118 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.191	$0.172 + 0.010 \cdot \text{SL}$	$0.181 + 0.007 \cdot \text{SL}$	$0.196 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.241	$0.215 + 0.013 \cdot \text{SL}$	$0.229 + 0.009 \cdot \text{SL}$	$0.259 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.097	$0.069 + 0.014 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$
	t_F	0.138	$0.109 + 0.015 \cdot \text{SL}$	$0.118 + 0.012 \cdot \text{SL}$	$0.126 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.185	$0.165 + 0.010 \cdot \text{SL}$	$0.174 + 0.007 \cdot \text{SL}$	$0.190 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.258	$0.231 + 0.013 \cdot \text{SL}$	$0.246 + 0.009 \cdot \text{SL}$	$0.277 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.093	$0.066 + 0.013 \cdot \text{SL}$	$0.067 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.140	$0.112 + 0.014 \cdot \text{SL}$	$0.120 + 0.012 \cdot \text{SL}$	$0.127 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.201	$0.182 + 0.009 \cdot \text{SL}$	$0.191 + 0.007 \cdot \text{SL}$	$0.201 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.309	$0.282 + 0.013 \cdot \text{SL}$	$0.297 + 0.009 \cdot \text{SL}$	$0.328 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.098	$0.073 + 0.012 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.140	$0.111 + 0.014 \cdot \text{SL}$	$0.118 + 0.012 \cdot \text{SL}$	$0.127 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.213	$0.194 + 0.009 \cdot \text{SL}$	$0.203 + 0.007 \cdot \text{SL}$	$0.215 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.317	$0.290 + 0.013 \cdot \text{SL}$	$0.305 + 0.009 \cdot \text{SL}$	$0.336 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	Y
0	0	x	0
x	x	0	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG9			SCG9D2			SCG9	SCG9D2
A	B	C	A	B	C	2.00	2.33
0.7	0.8	0.9	0.7	0.8	0.9		

SCG9/SCG9D2

2-OR into 2-AND with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG9

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.116	$0.063 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.112	$0.062 + 0.025 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.171	$0.141 + 0.015 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.154 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.188	$0.155 + 0.017 \cdot \text{SL}$	$0.166 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.121	$0.068 + 0.026 \cdot \text{SL}$	$0.065 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.113	$0.064 + 0.024 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.192	$0.162 + 0.015 \cdot \text{SL}$	$0.170 + 0.013 \cdot \text{SL}$	$0.176 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.189	$0.155 + 0.017 \cdot \text{SL}$	$0.166 + 0.014 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.121	$0.067 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.058 + 0.023 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.185	$0.154 + 0.015 \cdot \text{SL}$	$0.163 + 0.013 \cdot \text{SL}$	$0.169 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.166	$0.134 + 0.016 \cdot \text{SL}$	$0.144 + 0.013 \cdot \text{SL}$	$0.152 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG9D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.095	$0.067 + 0.014 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$
	t_F	0.101	$0.075 + 0.013 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.184	$0.166 + 0.009 \cdot \text{SL}$	$0.174 + 0.007 \cdot \text{SL}$	$0.187 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.205	$0.183 + 0.011 \cdot \text{SL}$	$0.193 + 0.008 \cdot \text{SL}$	$0.215 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.102	$0.074 + 0.014 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.102	$0.077 + 0.013 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.205	$0.186 + 0.010 \cdot \text{SL}$	$0.195 + 0.007 \cdot \text{SL}$	$0.209 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.206	$0.184 + 0.011 \cdot \text{SL}$	$0.195 + 0.008 \cdot \text{SL}$	$0.217 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.102	$0.076 + 0.013 \cdot \text{SL}$	$0.075 + 0.013 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.058 + 0.013 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.198	$0.179 + 0.010 \cdot \text{SL}$	$0.187 + 0.007 \cdot \text{SL}$	$0.202 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.167	$0.147 + 0.010 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$	$0.172 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG10/SCG10D2

Two 2-ORs into 2-AND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	0
x	x	0	0	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG10				SCG10D2				SCG10	SCG10D2
A	B	C	D	A	B	C	D		
0.7	0.8	0.7	0.8	0.7	0.8	0.7	0.8	2.33	2.67

SCG10/SCG10D2

Two 2-ORs into 2-AND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG10

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.126	$0.072 + 0.027 \cdot \text{SL}$	$0.072 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.126	$0.076 + 0.025 \cdot \text{SL}$	$0.083 + 0.023 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.207	$0.175 + 0.016 \cdot \text{SL}$	$0.185 + 0.013 \cdot \text{SL}$	$0.193 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.194	$0.157 + 0.019 \cdot \text{SL}$	$0.170 + 0.015 \cdot \text{SL}$	$0.187 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.136	$0.083 + 0.026 \cdot \text{SL}$	$0.083 + 0.027 \cdot \text{SL}$	$0.071 + 0.028 \cdot \text{SL}$
	t_F	0.126	$0.075 + 0.025 \cdot \text{SL}$	$0.082 + 0.023 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.237	$0.204 + 0.016 \cdot \text{SL}$	$0.215 + 0.014 \cdot \text{SL}$	$0.225 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.197	$0.160 + 0.019 \cdot \text{SL}$	$0.173 + 0.015 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.127	$0.073 + 0.027 \cdot \text{SL}$	$0.072 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.135	$0.085 + 0.025 \cdot \text{SL}$	$0.091 + 0.023 \cdot \text{SL}$	$0.089 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.215	$0.183 + 0.016 \cdot \text{SL}$	$0.193 + 0.013 \cdot \text{SL}$	$0.202 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.221	$0.183 + 0.019 \cdot \text{SL}$	$0.197 + 0.015 \cdot \text{SL}$	$0.215 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.135	$0.082 + 0.026 \cdot \text{SL}$	$0.080 + 0.027 \cdot \text{SL}$	$0.071 + 0.028 \cdot \text{SL}$
	t_F	0.136	$0.087 + 0.024 \cdot \text{SL}$	$0.092 + 0.023 \cdot \text{SL}$	$0.089 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.245	$0.212 + 0.016 \cdot \text{SL}$	$0.223 + 0.014 \cdot \text{SL}$	$0.232 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.223	$0.185 + 0.019 \cdot \text{SL}$	$0.199 + 0.015 \cdot \text{SL}$	$0.217 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG10D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.109	$0.082 + 0.013 \cdot \text{SL}$	$0.082 + 0.014 \cdot \text{SL}$	$0.077 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.083 + 0.014 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$	$0.093 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.223	$0.202 + 0.010 \cdot \text{SL}$	$0.213 + 0.008 \cdot \text{SL}$	$0.230 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.205	$0.181 + 0.012 \cdot \text{SL}$	$0.194 + 0.009 \cdot \text{SL}$	$0.219 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.119	$0.093 + 0.013 \cdot \text{SL}$	$0.093 + 0.013 \cdot \text{SL}$	$0.085 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.086 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.252	$0.230 + 0.011 \cdot \text{SL}$	$0.242 + 0.008 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.208	$0.184 + 0.012 \cdot \text{SL}$	$0.197 + 0.009 \cdot \text{SL}$	$0.222 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.109	$0.081 + 0.014 \cdot \text{SL}$	$0.083 + 0.013 \cdot \text{SL}$	$0.077 + 0.014 \cdot \text{SL}$
	t_F	0.122	$0.095 + 0.013 \cdot \text{SL}$	$0.100 + 0.012 \cdot \text{SL}$	$0.105 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.232	$0.211 + 0.010 \cdot \text{SL}$	$0.222 + 0.008 \cdot \text{SL}$	$0.239 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.230	$0.205 + 0.013 \cdot \text{SL}$	$0.220 + 0.009 \cdot \text{SL}$	$0.246 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.119	$0.092 + 0.013 \cdot \text{SL}$	$0.092 + 0.013 \cdot \text{SL}$	$0.087 + 0.014 \cdot \text{SL}$
	t_F	0.122	$0.096 + 0.013 \cdot \text{SL}$	$0.101 + 0.012 \cdot \text{SL}$	$0.105 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.238 + 0.011 \cdot \text{SL}$	$0.250 + 0.008 \cdot \text{SL}$	$0.270 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.232	$0.208 + 0.012 \cdot \text{SL}$	$0.222 + 0.009 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	0
x	x	0	0	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)										Gate Count	
SCG11					SCG11D2					SCG11	SCG11D2
A	B	C	D	E	A	B	C	D	E	2.67	3.67
0.9	0.9	0.9	0.9	1.0	0.9	0.9	0.9	0.9	2.2		

SCG11/SCG11D2

Two 2-NORs into 3-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG11

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.320	$0.155 + 0.082 \cdot \text{SL}$	$0.154 + 0.083 \cdot \text{SL}$	$0.156 + 0.082 \cdot \text{SL}$
	t_F	0.115	$0.067 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.067 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.186	$0.114 + 0.036 \cdot \text{SL}$	$0.115 + 0.036 \cdot \text{SL}$	$0.117 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.190	$0.157 + 0.016 \cdot \text{SL}$	$0.167 + 0.014 \cdot \text{SL}$	$0.177 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.321	$0.156 + 0.082 \cdot \text{SL}$	$0.154 + 0.083 \cdot \text{SL}$	$0.156 + 0.082 \cdot \text{SL}$
	t_F	0.115	$0.068 + 0.024 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.067 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.200	$0.128 + 0.036 \cdot \text{SL}$	$0.129 + 0.035 \cdot \text{SL}$	$0.130 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.188	$0.155 + 0.016 \cdot \text{SL}$	$0.165 + 0.014 \cdot \text{SL}$	$0.175 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.326	$0.163 + 0.081 \cdot \text{SL}$	$0.160 + 0.082 \cdot \text{SL}$	$0.157 + 0.082 \cdot \text{SL}$
	t_F	0.136	$0.090 + 0.023 \cdot \text{SL}$	$0.092 + 0.022 \cdot \text{SL}$	$0.084 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.216	$0.144 + 0.036 \cdot \text{SL}$	$0.146 + 0.036 \cdot \text{SL}$	$0.148 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.201	$0.170 + 0.016 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.326	$0.164 + 0.081 \cdot \text{SL}$	$0.161 + 0.082 \cdot \text{SL}$	$0.158 + 0.082 \cdot \text{SL}$
	t_F	0.136	$0.090 + 0.023 \cdot \text{SL}$	$0.092 + 0.022 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.229	$0.156 + 0.036 \cdot \text{SL}$	$0.158 + 0.036 \cdot \text{SL}$	$0.160 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.199	$0.168 + 0.016 \cdot \text{SL}$	$0.176 + 0.013 \cdot \text{SL}$	$0.184 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.332	$0.173 + 0.080 \cdot \text{SL}$	$0.166 + 0.082 \cdot \text{SL}$	$0.159 + 0.082 \cdot \text{SL}$
	t_F	0.159	$0.120 + 0.019 \cdot \text{SL}$	$0.112 + 0.021 \cdot \text{SL}$	$0.098 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.183	$0.111 + 0.036 \cdot \text{SL}$	$0.112 + 0.036 \cdot \text{SL}$	$0.114 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.099	$0.069 + 0.015 \cdot \text{SL}$	$0.077 + 0.013 \cdot \text{SL}$	$0.079 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG11D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.222	$0.141 + 0.041 \cdot \text{SL}$	$0.138 + 0.041 \cdot \text{SL}$	$0.137 + 0.041 \cdot \text{SL}$
	t_F	0.103	$0.078 + 0.013 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.163	$0.128 + 0.018 \cdot \text{SL}$	$0.127 + 0.018 \cdot \text{SL}$	$0.128 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.205	$0.185 + 0.010 \cdot \text{SL}$	$0.194 + 0.008 \cdot \text{SL}$	$0.214 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.223	$0.141 + 0.041 \cdot \text{SL}$	$0.139 + 0.041 \cdot \text{SL}$	$0.138 + 0.041 \cdot \text{SL}$
	t_F	0.104	$0.079 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.175	$0.141 + 0.017 \cdot \text{SL}$	$0.139 + 0.018 \cdot \text{SL}$	$0.140 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.203	$0.183 + 0.010 \cdot \text{SL}$	$0.192 + 0.008 \cdot \text{SL}$	$0.212 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.230	$0.151 + 0.040 \cdot \text{SL}$	$0.147 + 0.041 \cdot \text{SL}$	$0.141 + 0.041 \cdot \text{SL}$
	t_F	0.128	$0.105 + 0.012 \cdot \text{SL}$	$0.106 + 0.011 \cdot \text{SL}$	$0.105 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.194	$0.157 + 0.019 \cdot \text{SL}$	$0.159 + 0.018 \cdot \text{SL}$	$0.162 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.221	$0.202 + 0.010 \cdot \text{SL}$	$0.210 + 0.008 \cdot \text{SL}$	$0.227 + 0.007 \cdot \text{SL}$
D to Y	t_R	0.231	$0.152 + 0.040 \cdot \text{SL}$	$0.148 + 0.041 \cdot \text{SL}$	$0.142 + 0.041 \cdot \text{SL}$
	t_F	0.129	$0.106 + 0.012 \cdot \text{SL}$	$0.107 + 0.011 \cdot \text{SL}$	$0.105 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.204	$0.167 + 0.019 \cdot \text{SL}$	$0.170 + 0.018 \cdot \text{SL}$	$0.173 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.220	$0.200 + 0.010 \cdot \text{SL}$	$0.208 + 0.008 \cdot \text{SL}$	$0.225 + 0.007 \cdot \text{SL}$
E to Y	t_R	0.237	$0.159 + 0.039 \cdot \text{SL}$	$0.154 + 0.041 \cdot \text{SL}$	$0.143 + 0.041 \cdot \text{SL}$
	t_F	0.136	$0.117 + 0.010 \cdot \text{SL}$	$0.114 + 0.010 \cdot \text{SL}$	$0.096 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.141	$0.103 + 0.019 \cdot \text{SL}$	$0.106 + 0.018 \cdot \text{SL}$	$0.108 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.079	$0.062 + 0.009 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.075 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG12/SCG12D2

2-NAND into 2-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	0	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG12			SCG12D2			SCG12	SCG12D2
A	B	C	A	B	C	1.67	2.33
0.8	0.8	1.1	0.8	0.8	2.3		

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG12

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.203	$0.095 + 0.054 \cdot \text{SL}$	$0.091 + 0.055 \cdot \text{SL}$	$0.087 + 0.055 \cdot \text{SL}$
	t_F	0.085	$0.048 + 0.018 \cdot \text{SL}$	$0.047 + 0.019 \cdot \text{SL}$	$0.041 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.173	$0.124 + 0.024 \cdot \text{SL}$	$0.127 + 0.024 \cdot \text{SL}$	$0.127 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.141	$0.116 + 0.012 \cdot \text{SL}$	$0.123 + 0.011 \cdot \text{SL}$	$0.128 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.203	$0.095 + 0.054 \cdot \text{SL}$	$0.091 + 0.055 \cdot \text{SL}$	$0.086 + 0.055 \cdot \text{SL}$
	t_F	0.087	$0.051 + 0.018 \cdot \text{SL}$	$0.049 + 0.018 \cdot \text{SL}$	$0.043 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.169	$0.120 + 0.024 \cdot \text{SL}$	$0.122 + 0.024 \cdot \text{SL}$	$0.123 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.155	$0.129 + 0.013 \cdot \text{SL}$	$0.137 + 0.011 \cdot \text{SL}$	$0.143 + 0.010 \cdot \text{SL}$
C to Y	t_R	0.212	$0.108 + 0.052 \cdot \text{SL}$	$0.100 + 0.054 \cdot \text{SL}$	$0.090 + 0.055 \cdot \text{SL}$
	t_F	0.127	$0.096 + 0.015 \cdot \text{SL}$	$0.092 + 0.016 \cdot \text{SL}$	$0.074 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.121	$0.072 + 0.025 \cdot \text{SL}$	$0.076 + 0.024 \cdot \text{SL}$	$0.075 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.076	$0.049 + 0.014 \cdot \text{SL}$	$0.061 + 0.010 \cdot \text{SL}$	$0.064 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG12D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.147	$0.093 + 0.027 \cdot \text{SL}$	$0.092 + 0.027 \cdot \text{SL}$	$0.083 + 0.028 \cdot \text{SL}$
	t_F	0.074	$0.055 + 0.010 \cdot \text{SL}$	$0.056 + 0.009 \cdot \text{SL}$	$0.054 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.179	$0.153 + 0.013 \cdot \text{SL}$	$0.156 + 0.012 \cdot \text{SL}$	$0.159 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.154	$0.138 + 0.008 \cdot \text{SL}$	$0.146 + 0.006 \cdot \text{SL}$	$0.158 + 0.005 \cdot \text{SL}$
B to Y	t_R	0.147	$0.095 + 0.026 \cdot \text{SL}$	$0.092 + 0.027 \cdot \text{SL}$	$0.083 + 0.028 \cdot \text{SL}$
	t_F	0.078	$0.058 + 0.010 \cdot \text{SL}$	$0.061 + 0.009 \cdot \text{SL}$	$0.058 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.173	$0.146 + 0.013 \cdot \text{SL}$	$0.151 + 0.012 \cdot \text{SL}$	$0.153 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.165	$0.149 + 0.008 \cdot \text{SL}$	$0.157 + 0.006 \cdot \text{SL}$	$0.171 + 0.005 \cdot \text{SL}$
C to Y	t_R	0.153	$0.102 + 0.025 \cdot \text{SL}$	$0.096 + 0.027 \cdot \text{SL}$	$0.085 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.090 + 0.008 \cdot \text{SL}$	$0.091 + 0.008 \cdot \text{SL}$	$0.074 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.092	$0.065 + 0.014 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.057	$0.041 + 0.008 \cdot \text{SL}$	$0.050 + 0.006 \cdot \text{SL}$	$0.061 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG13/SCG13D2

2-NOR into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG13			SCG13D2			SCG13	SCG13D2
A	B	C	A	B	C	1.67	2.33
0.9	0.9	1.0	0.9	0.9	2.1		

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG13

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.122	$0.057 + 0.032 \cdot \text{SL}$	$0.050 + 0.034 \cdot \text{SL}$	$0.047 + 0.034 \cdot \text{SL}$
	t_F	0.141	$0.075 + 0.033 \cdot \text{SL}$	$0.077 + 0.032 \cdot \text{SL}$	$0.071 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.124	$0.092 + 0.016 \cdot \text{SL}$	$0.095 + 0.015 \cdot \text{SL}$	$0.095 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.193	$0.155 + 0.019 \cdot \text{SL}$	$0.163 + 0.017 \cdot \text{SL}$	$0.170 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.122	$0.058 + 0.032 \cdot \text{SL}$	$0.052 + 0.034 \cdot \text{SL}$	$0.048 + 0.034 \cdot \text{SL}$
	t_F	0.142	$0.077 + 0.032 \cdot \text{SL}$	$0.078 + 0.032 \cdot \text{SL}$	$0.071 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.137	$0.106 + 0.016 \cdot \text{SL}$	$0.108 + 0.015 \cdot \text{SL}$	$0.109 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.191	$0.152 + 0.019 \cdot \text{SL}$	$0.161 + 0.017 \cdot \text{SL}$	$0.169 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.165	$0.107 + 0.029 \cdot \text{SL}$	$0.096 + 0.032 \cdot \text{SL}$	$0.079 + 0.034 \cdot \text{SL}$
	t_F	0.141	$0.082 + 0.030 \cdot \text{SL}$	$0.073 + 0.032 \cdot \text{SL}$	$0.063 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.102	$0.069 + 0.016 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.082	$0.045 + 0.018 \cdot \text{SL}$	$0.053 + 0.016 \cdot \text{SL}$	$0.055 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG13D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	$0.058 + 0.015 \cdot \text{SL}$	$0.054 + 0.017 \cdot \text{SL}$	$0.045 + 0.017 \cdot \text{SL}$
	t_F	0.119	$0.086 + 0.016 \cdot \text{SL}$	$0.087 + 0.016 \cdot \text{SL}$	$0.084 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.127	$0.110 + 0.008 \cdot \text{SL}$	$0.113 + 0.008 \cdot \text{SL}$	$0.115 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.205	$0.182 + 0.011 \cdot \text{SL}$	$0.190 + 0.009 \cdot \text{SL}$	$0.206 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.090	$0.059 + 0.016 \cdot \text{SL}$	$0.055 + 0.017 \cdot \text{SL}$	$0.047 + 0.017 \cdot \text{SL}$
	t_F	0.119	$0.087 + 0.016 \cdot \text{SL}$	$0.087 + 0.016 \cdot \text{SL}$	$0.085 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.139	$0.122 + 0.009 \cdot \text{SL}$	$0.126 + 0.008 \cdot \text{SL}$	$0.127 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.203	$0.180 + 0.011 \cdot \text{SL}$	$0.188 + 0.009 \cdot \text{SL}$	$0.204 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.133	$0.107 + 0.013 \cdot \text{SL}$	$0.098 + 0.016 \cdot \text{SL}$	$0.080 + 0.017 \cdot \text{SL}$
	t_F	0.107	$0.076 + 0.016 \cdot \text{SL}$	$0.075 + 0.016 \cdot \text{SL}$	$0.064 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.084	$0.065 + 0.009 \cdot \text{SL}$	$0.072 + 0.008 \cdot \text{SL}$	$0.073 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.062	$0.042 + 0.010 \cdot \text{SL}$	$0.049 + 0.009 \cdot \text{SL}$	$0.057 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG14/SCG14D2

2-NAND into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	1	0
x	0	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG14			SCG14D2			SCG14	SCG14D2
A	B	C	A	B	C	1.67	2.33
0.8	0.8	1.0	0.8	0.8	2.0		

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG14

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.128	$0.062 + 0.033 \cdot \text{SL}$	$0.058 + 0.034 \cdot \text{SL}$	$0.051 + 0.035 \cdot \text{SL}$
	t_F	0.126	$0.064 + 0.031 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$	$0.052 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.146	$0.113 + 0.017 \cdot \text{SL}$	$0.118 + 0.015 \cdot \text{SL}$	$0.120 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.154	$0.119 + 0.017 \cdot \text{SL}$	$0.124 + 0.016 \cdot \text{SL}$	$0.126 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.127	$0.061 + 0.033 \cdot \text{SL}$	$0.058 + 0.034 \cdot \text{SL}$	$0.051 + 0.035 \cdot \text{SL}$
	t_F	0.128	$0.067 + 0.031 \cdot \text{SL}$	$0.060 + 0.033 \cdot \text{SL}$	$0.053 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.142	$0.108 + 0.017 \cdot \text{SL}$	$0.114 + 0.015 \cdot \text{SL}$	$0.116 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.169	$0.134 + 0.018 \cdot \text{SL}$	$0.139 + 0.016 \cdot \text{SL}$	$0.141 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.164	$0.106 + 0.029 \cdot \text{SL}$	$0.094 + 0.032 \cdot \text{SL}$	$0.076 + 0.034 \cdot \text{SL}$
	t_F	0.138	$0.080 + 0.029 \cdot \text{SL}$	$0.070 + 0.032 \cdot \text{SL}$	$0.058 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.102	$0.069 + 0.016 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.080	$0.043 + 0.018 \cdot \text{SL}$	$0.052 + 0.016 \cdot \text{SL}$	$0.053 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG14D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	$0.066 + 0.017 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$	$0.057 + 0.017 \cdot \text{SL}$
	t_F	0.098	$0.067 + 0.016 \cdot \text{SL}$	$0.065 + 0.016 \cdot \text{SL}$	$0.058 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.156	$0.137 + 0.009 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.149 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.159	$0.139 + 0.010 \cdot \text{SL}$	$0.145 + 0.008 \cdot \text{SL}$	$0.151 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.100	$0.067 + 0.016 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$	$0.057 + 0.017 \cdot \text{SL}$
	t_F	0.101	$0.069 + 0.016 \cdot \text{SL}$	$0.068 + 0.016 \cdot \text{SL}$	$0.062 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.150	$0.131 + 0.010 \cdot \text{SL}$	$0.136 + 0.008 \cdot \text{SL}$	$0.143 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.172	$0.152 + 0.010 \cdot \text{SL}$	$0.158 + 0.008 \cdot \text{SL}$	$0.165 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.133	$0.106 + 0.013 \cdot \text{SL}$	$0.097 + 0.016 \cdot \text{SL}$	$0.078 + 0.017 \cdot \text{SL}$
	t_F	0.106	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.016 \cdot \text{SL}$	$0.060 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.084	$0.066 + 0.009 \cdot \text{SL}$	$0.072 + 0.008 \cdot \text{SL}$	$0.074 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.061	$0.041 + 0.010 \cdot \text{SL}$	$0.048 + 0.008 \cdot \text{SL}$	$0.054 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG15/SCG15D2

2-NAND into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	1	1	0
x	0	1	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG15				SCG15D2				SCG15	SCG15D2
A	B	C	D	A	B	C	D		
0.8	0.8	0.9	0.9	0.8	0.8	1.8	1.8	2.00	2.67

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG15

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.167	$0.080 + 0.043 \cdot \text{SL}$	$0.076 + 0.045 \cdot \text{SL}$	$0.071 + 0.045 \cdot \text{SL}$
	t_F	0.186	$0.094 + 0.046 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.167	$0.126 + 0.021 \cdot \text{SL}$	$0.129 + 0.020 \cdot \text{SL}$	$0.131 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.176	$0.130 + 0.023 \cdot \text{SL}$	$0.133 + 0.022 \cdot \text{SL}$	$0.134 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.167	$0.081 + 0.043 \cdot \text{SL}$	$0.076 + 0.045 \cdot \text{SL}$	$0.071 + 0.045 \cdot \text{SL}$
	t_F	0.187	$0.096 + 0.045 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.163	$0.121 + 0.021 \cdot \text{SL}$	$0.125 + 0.020 \cdot \text{SL}$	$0.126 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.188	$0.143 + 0.023 \cdot \text{SL}$	$0.146 + 0.022 \cdot \text{SL}$	$0.147 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.203	$0.122 + 0.040 \cdot \text{SL}$	$0.112 + 0.043 \cdot \text{SL}$	$0.094 + 0.045 \cdot \text{SL}$
	t_F	0.198	$0.111 + 0.044 \cdot \text{SL}$	$0.101 + 0.046 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.127	$0.087 + 0.020 \cdot \text{SL}$	$0.089 + 0.019 \cdot \text{SL}$	$0.088 + 0.019 \cdot \text{SL}$
	t_{PHL}	0.111	$0.064 + 0.023 \cdot \text{SL}$	$0.069 + 0.022 \cdot \text{SL}$	$0.069 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.229	$0.147 + 0.041 \cdot \text{SL}$	$0.135 + 0.044 \cdot \text{SL}$	$0.117 + 0.046 \cdot \text{SL}$
	t_F	0.192	$0.103 + 0.045 \cdot \text{SL}$	$0.095 + 0.047 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.140	$0.100 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.110	$0.064 + 0.023 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG15D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	$0.077 + 0.022 \cdot \text{SL}$	$0.074 + 0.023 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_F	0.132	$0.087 + 0.023 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$	$0.078 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.165	$0.142 + 0.012 \cdot \text{SL}$	$0.147 + 0.010 \cdot \text{SL}$	$0.152 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.165	$0.140 + 0.012 \cdot \text{SL}$	$0.144 + 0.011 \cdot \text{SL}$	$0.147 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.120	$0.076 + 0.022 \cdot \text{SL}$	$0.075 + 0.022 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$
	t_F	0.135	$0.090 + 0.023 \cdot \text{SL}$	$0.088 + 0.023 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.160	$0.136 + 0.012 \cdot \text{SL}$	$0.142 + 0.010 \cdot \text{SL}$	$0.146 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.178	$0.153 + 0.012 \cdot \text{SL}$	$0.158 + 0.011 \cdot \text{SL}$	$0.161 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.155	$0.116 + 0.020 \cdot \text{SL}$	$0.109 + 0.021 \cdot \text{SL}$	$0.088 + 0.023 \cdot \text{SL}$
	t_F	0.144	$0.102 + 0.021 \cdot \text{SL}$	$0.095 + 0.023 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.103	$0.081 + 0.011 \cdot \text{SL}$	$0.086 + 0.010 \cdot \text{SL}$	$0.085 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$
D to Y	t_R	0.179	$0.142 + 0.019 \cdot \text{SL}$	$0.132 + 0.021 \cdot \text{SL}$	$0.110 + 0.023 \cdot \text{SL}$
	t_F	0.136	$0.093 + 0.021 \cdot \text{SL}$	$0.087 + 0.023 \cdot \text{SL}$	$0.079 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.115	$0.094 + 0.011 \cdot \text{SL}$	$0.096 + 0.010 \cdot \text{SL}$	$0.096 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.082	$0.057 + 0.013 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.065 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG16/SCG16D2

2-OR with one inverted input into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	1	0
x	1	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG16			SCG16D2			SCG16	SCG16D2
A	B	C	A	B	C	2.00	2.67
0.8	1.0	1.1	0.8	2.0	2.3		

2-OR with one inverted input into 2-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.226	$0.117 + 0.054 \cdot \text{SL}$	$0.114 + 0.055 \cdot \text{SL}$	$0.111 + 0.056 \cdot \text{SL}$
	t_F	0.166	$0.084 + 0.041 \cdot \text{SL}$	$0.080 + 0.042 \cdot \text{SL}$	$0.077 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.168	$0.120 + 0.024 \cdot \text{SL}$	$0.120 + 0.024 \cdot \text{SL}$	$0.121 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.173	$0.131 + 0.021 \cdot \text{SL}$	$0.133 + 0.021 \cdot \text{SL}$	$0.134 + 0.020 \cdot \text{SL}$
B to Y	t_R	0.239	$0.134 + 0.052 \cdot \text{SL}$	$0.126 + 0.054 \cdot \text{SL}$	$0.117 + 0.055 \cdot \text{SL}$
	t_F	0.212	$0.138 + 0.037 \cdot \text{SL}$	$0.127 + 0.040 \cdot \text{SL}$	$0.111 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.128	$0.079 + 0.025 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.137	$0.096 + 0.020 \cdot \text{SL}$	$0.097 + 0.020 \cdot \text{SL}$	$0.097 + 0.020 \cdot \text{SL}$
C to Y	t_R	0.165	$0.117 + 0.024 \cdot \text{SL}$	$0.108 + 0.026 \cdot \text{SL}$	$0.095 + 0.028 \cdot \text{SL}$
	t_F	0.199	$0.121 + 0.039 \cdot \text{SL}$	$0.115 + 0.041 \cdot \text{SL}$	$0.108 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.103	$0.075 + 0.014 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.129	$0.088 + 0.021 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$	$0.090 + 0.020 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG16D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.165	$0.113 + 0.026 \cdot \text{SL}$	$0.107 + 0.028 \cdot \text{SL}$	$0.102 + 0.028 \cdot \text{SL}$
	t_F	0.124	$0.083 + 0.020 \cdot \text{SL}$	$0.080 + 0.021 \cdot \text{SL}$	$0.074 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.162	$0.137 + 0.012 \cdot \text{SL}$	$0.139 + 0.012 \cdot \text{SL}$	$0.140 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.171	$0.147 + 0.012 \cdot \text{SL}$	$0.151 + 0.011 \cdot \text{SL}$	$0.154 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.178	$0.128 + 0.025 \cdot \text{SL}$	$0.120 + 0.027 \cdot \text{SL}$	$0.109 + 0.028 \cdot \text{SL}$
	t_F	0.171	$0.136 + 0.018 \cdot \text{SL}$	$0.128 + 0.019 \cdot \text{SL}$	$0.107 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.101	$0.074 + 0.013 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.113	$0.091 + 0.011 \cdot \text{SL}$	$0.093 + 0.010 \cdot \text{SL}$	$0.094 + 0.010 \cdot \text{SL}$
C to Y	t_R	0.135	$0.112 + 0.011 \cdot \text{SL}$	$0.107 + 0.013 \cdot \text{SL}$	$0.090 + 0.014 \cdot \text{SL}$
	t_F	0.156	$0.118 + 0.019 \cdot \text{SL}$	$0.112 + 0.020 \cdot \text{SL}$	$0.102 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.084	$0.068 + 0.008 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.102	$0.080 + 0.011 \cdot \text{SL}$	$0.083 + 0.010 \cdot \text{SL}$	$0.084 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG17/SCG17D2

2-AND into 2-NOR into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	0	1	0
x	0	0	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG17				SCG17D2				SCG17	SCG17D2
A	B	C	D	A	B	C	D		
0.8	0.8	0.8	1.0	0.8	0.8	0.8	2.1	2.00	2.67

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG17

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.136	$0.073 + 0.031 \cdot \text{SL}$	$0.063 + 0.034 \cdot \text{SL}$	$0.056 + 0.035 \cdot \text{SL}$
	t_F	0.141	$0.075 + 0.033 \cdot \text{SL}$	$0.077 + 0.033 \cdot \text{SL}$	$0.072 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.172	$0.138 + 0.017 \cdot \text{SL}$	$0.145 + 0.015 \cdot \text{SL}$	$0.148 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.186	$0.147 + 0.020 \cdot \text{SL}$	$0.156 + 0.017 \cdot \text{SL}$	$0.165 + 0.016 \cdot \text{SL}$
B to Y	t_R	0.131	$0.065 + 0.033 \cdot \text{SL}$	$0.061 + 0.034 \cdot \text{SL}$	$0.056 + 0.035 \cdot \text{SL}$
	t_F	0.145	$0.079 + 0.033 \cdot \text{SL}$	$0.081 + 0.032 \cdot \text{SL}$	$0.076 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.166	$0.131 + 0.017 \cdot \text{SL}$	$0.138 + 0.015 \cdot \text{SL}$	$0.142 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.202	$0.163 + 0.020 \cdot \text{SL}$	$0.173 + 0.017 \cdot \text{SL}$	$0.182 + 0.016 \cdot \text{SL}$
C to Y	t_R	0.128	$0.066 + 0.031 \cdot \text{SL}$	$0.055 + 0.034 \cdot \text{SL}$	$0.049 + 0.035 \cdot \text{SL}$
	t_F	0.146	$0.081 + 0.033 \cdot \text{SL}$	$0.083 + 0.032 \cdot \text{SL}$	$0.076 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.173	$0.141 + 0.016 \cdot \text{SL}$	$0.144 + 0.015 \cdot \text{SL}$	$0.146 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.219	$0.179 + 0.020 \cdot \text{SL}$	$0.190 + 0.017 \cdot \text{SL}$	$0.198 + 0.016 \cdot \text{SL}$
D to Y	t_R	0.165	$0.106 + 0.029 \cdot \text{SL}$	$0.095 + 0.032 \cdot \text{SL}$	$0.077 + 0.034 \cdot \text{SL}$
	t_F	0.139	$0.079 + 0.030 \cdot \text{SL}$	$0.070 + 0.032 \cdot \text{SL}$	$0.061 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.102	$0.070 + 0.016 \cdot \text{SL}$	$0.076 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.082	$0.045 + 0.019 \cdot \text{SL}$	$0.053 + 0.016 \cdot \text{SL}$	$0.055 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG17D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	$0.075 + 0.016 \cdot \text{SL}$	$0.075 + 0.017 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$
	t_F	0.118	$0.086 + 0.016 \cdot \text{SL}$	$0.086 + 0.016 \cdot \text{SL}$	$0.085 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.186	$0.166 + 0.010 \cdot \text{SL}$	$0.173 + 0.008 \cdot \text{SL}$	$0.183 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.197	$0.175 + 0.011 \cdot \text{SL}$	$0.183 + 0.009 \cdot \text{SL}$	$0.199 + 0.008 \cdot \text{SL}$
B to Y	t_R	0.108	$0.075 + 0.017 \cdot \text{SL}$	$0.076 + 0.017 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$
	t_F	0.125	$0.094 + 0.016 \cdot \text{SL}$	$0.093 + 0.016 \cdot \text{SL}$	$0.090 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.179	$0.159 + 0.010 \cdot \text{SL}$	$0.166 + 0.008 \cdot \text{SL}$	$0.176 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.212	$0.189 + 0.012 \cdot \text{SL}$	$0.198 + 0.009 \cdot \text{SL}$	$0.215 + 0.008 \cdot \text{SL}$
C to Y	t_R	0.098	$0.067 + 0.016 \cdot \text{SL}$	$0.064 + 0.017 \cdot \text{SL}$	$0.053 + 0.017 \cdot \text{SL}$
	t_F	0.126	$0.094 + 0.016 \cdot \text{SL}$	$0.094 + 0.016 \cdot \text{SL}$	$0.091 + 0.016 \cdot \text{SL}$
	t_{PLH}	0.178	$0.160 + 0.009 \cdot \text{SL}$	$0.164 + 0.008 \cdot \text{SL}$	$0.168 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.230	$0.207 + 0.012 \cdot \text{SL}$	$0.216 + 0.009 \cdot \text{SL}$	$0.233 + 0.008 \cdot \text{SL}$
D to Y	t_R	0.133	$0.106 + 0.013 \cdot \text{SL}$	$0.098 + 0.016 \cdot \text{SL}$	$0.079 + 0.017 \cdot \text{SL}$
	t_F	0.107	$0.076 + 0.016 \cdot \text{SL}$	$0.075 + 0.016 \cdot \text{SL}$	$0.063 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.083	$0.064 + 0.009 \cdot \text{SL}$	$0.070 + 0.008 \cdot \text{SL}$	$0.072 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.061	$0.040 + 0.010 \cdot \text{SL}$	$0.047 + 0.009 \cdot \text{SL}$	$0.055 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG18/SCG18D2

2-AND into 2-NOR into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	0	1	1	0
x	0	0	1	1	0
Other States					1

Cell Data

Input Load (SL)										Gate Count	
SCG18					SCG18D2					SCG18	SCG18D2
A	B	C	D	E	A	B	C	D	E	2.33	3.00
0.8	0.8	0.8	0.9	0.9	0.8	0.8	0.8	1.8	1.8		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG18

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.173	$0.085 + 0.044 \cdot \text{SL}$	$0.082 + 0.045 \cdot \text{SL}$	$0.074 + 0.046 \cdot \text{SL}$
	t_F	0.198	$0.104 + 0.047 \cdot \text{SL}$	$0.105 + 0.047 \cdot \text{SL}$	$0.099 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.193	$0.150 + 0.021 \cdot \text{SL}$	$0.155 + 0.020 \cdot \text{SL}$	$0.157 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.205	$0.156 + 0.025 \cdot \text{SL}$	$0.163 + 0.023 \cdot \text{SL}$	$0.168 + 0.022 \cdot \text{SL}$
B to Y	t_R	0.173	$0.085 + 0.044 \cdot \text{SL}$	$0.081 + 0.045 \cdot \text{SL}$	$0.074 + 0.046 \cdot \text{SL}$
	t_F	0.203	$0.110 + 0.046 \cdot \text{SL}$	$0.108 + 0.047 \cdot \text{SL}$	$0.102 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.187	$0.144 + 0.021 \cdot \text{SL}$	$0.149 + 0.020 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.221	$0.172 + 0.025 \cdot \text{SL}$	$0.180 + 0.023 \cdot \text{SL}$	$0.185 + 0.022 \cdot \text{SL}$
C to Y	t_R	0.167	$0.077 + 0.045 \cdot \text{SL}$	$0.074 + 0.046 \cdot \text{SL}$	$0.070 + 0.046 \cdot \text{SL}$
	t_F	0.203	$0.111 + 0.046 \cdot \text{SL}$	$0.109 + 0.046 \cdot \text{SL}$	$0.101 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.194	$0.153 + 0.021 \cdot \text{SL}$	$0.155 + 0.020 \cdot \text{SL}$	$0.156 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.238	$0.189 + 0.025 \cdot \text{SL}$	$0.196 + 0.023 \cdot \text{SL}$	$0.202 + 0.022 \cdot \text{SL}$
D to Y	t_R	0.206	$0.124 + 0.041 \cdot \text{SL}$	$0.112 + 0.044 \cdot \text{SL}$	$0.095 + 0.046 \cdot \text{SL}$
	t_F	0.199	$0.110 + 0.044 \cdot \text{SL}$	$0.102 + 0.046 \cdot \text{SL}$	$0.092 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.128	$0.088 + 0.020 \cdot \text{SL}$	$0.090 + 0.020 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.111	$0.064 + 0.024 \cdot \text{SL}$	$0.069 + 0.022 \cdot \text{SL}$	$0.070 + 0.022 \cdot \text{SL}$
E to Y	t_R	0.230	$0.149 + 0.041 \cdot \text{SL}$	$0.137 + 0.044 \cdot \text{SL}$	$0.119 + 0.046 \cdot \text{SL}$
	t_F	0.193	$0.102 + 0.045 \cdot \text{SL}$	$0.096 + 0.047 \cdot \text{SL}$	$0.089 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.140	$0.100 + 0.020 \cdot \text{SL}$	$0.101 + 0.020 \cdot \text{SL}$	$0.101 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.112	$0.066 + 0.023 \cdot \text{SL}$	$0.070 + 0.022 \cdot \text{SL}$	$0.071 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG18/SCG18D2

2-AND into 2-NOR into 3-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG18D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.126	$0.083 + 0.022 \cdot \text{SL}$	$0.081 + 0.022 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$
	t_F	0.148	$0.100 + 0.024 \cdot \text{SL}$	$0.103 + 0.023 \cdot \text{SL}$	$0.097 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.193	$0.169 + 0.012 \cdot \text{SL}$	$0.176 + 0.010 \cdot \text{SL}$	$0.183 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.200	$0.173 + 0.014 \cdot \text{SL}$	$0.180 + 0.012 \cdot \text{SL}$	$0.192 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.127	$0.084 + 0.021 \cdot \text{SL}$	$0.081 + 0.022 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$
	t_F	0.153	$0.106 + 0.024 \cdot \text{SL}$	$0.108 + 0.023 \cdot \text{SL}$	$0.101 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.187	$0.162 + 0.012 \cdot \text{SL}$	$0.169 + 0.010 \cdot \text{SL}$	$0.176 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.216	$0.188 + 0.014 \cdot \text{SL}$	$0.196 + 0.012 \cdot \text{SL}$	$0.208 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.117	$0.074 + 0.021 \cdot \text{SL}$	$0.070 + 0.022 \cdot \text{SL}$	$0.061 + 0.023 \cdot \text{SL}$
	t_F	0.154	$0.107 + 0.024 \cdot \text{SL}$	$0.109 + 0.023 \cdot \text{SL}$	$0.101 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.186	$0.163 + 0.011 \cdot \text{SL}$	$0.167 + 0.010 \cdot \text{SL}$	$0.170 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.233	$0.205 + 0.014 \cdot \text{SL}$	$0.213 + 0.012 \cdot \text{SL}$	$0.226 + 0.011 \cdot \text{SL}$
D to Y	t_R	0.155	$0.116 + 0.019 \cdot \text{SL}$	$0.109 + 0.021 \cdot \text{SL}$	$0.087 + 0.023 \cdot \text{SL}$
	t_F	0.143	$0.100 + 0.021 \cdot \text{SL}$	$0.094 + 0.023 \cdot \text{SL}$	$0.083 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.100	$0.078 + 0.011 \cdot \text{SL}$	$0.083 + 0.010 \cdot \text{SL}$	$0.082 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.065 + 0.011 \cdot \text{SL}$
E to Y	t_R	0.179	$0.141 + 0.019 \cdot \text{SL}$	$0.132 + 0.021 \cdot \text{SL}$	$0.109 + 0.023 \cdot \text{SL}$
	t_F	0.136	$0.093 + 0.022 \cdot \text{SL}$	$0.086 + 0.024 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.114	$0.093 + 0.011 \cdot \text{SL}$	$0.095 + 0.010 \cdot \text{SL}$	$0.095 + 0.010 \cdot \text{SL}$
	t_{PHL}	0.082	$0.057 + 0.013 \cdot \text{SL}$	$0.062 + 0.011 \cdot \text{SL}$	$0.067 + 0.011 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG19/SCG19D2

2-AND into 2-AND into 2-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	1	x	0
x	x	x	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG19				SCG19D2				SCG19	SCG19D2
A	B	C	D	A	B	C	D		
0.8	0.8	1.0	1.0	0.8	0.8	2.0	2.2	2.33	3.00

SCG19/SCG19D2

2-AND into 2-AND into 2-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG19

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.204	$0.093 + 0.055 \cdot \text{SL}$	$0.091 + 0.056 \cdot \text{SL}$	$0.090 + 0.056 \cdot \text{SL}$
	t_F	0.146	$0.066 + 0.040 \cdot \text{SL}$	$0.062 + 0.041 \cdot \text{SL}$	$0.057 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.223	$0.174 + 0.025 \cdot \text{SL}$	$0.176 + 0.024 \cdot \text{SL}$	$0.177 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.210	$0.168 + 0.021 \cdot \text{SL}$	$0.171 + 0.020 \cdot \text{SL}$	$0.173 + 0.020 \cdot \text{SL}$
B to Y	t_R	0.204	$0.093 + 0.055 \cdot \text{SL}$	$0.091 + 0.056 \cdot \text{SL}$	$0.090 + 0.056 \cdot \text{SL}$
	t_F	0.145	$0.064 + 0.040 \cdot \text{SL}$	$0.062 + 0.041 \cdot \text{SL}$	$0.057 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.237	$0.188 + 0.025 \cdot \text{SL}$	$0.190 + 0.024 \cdot \text{SL}$	$0.191 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.205	$0.163 + 0.021 \cdot \text{SL}$	$0.167 + 0.020 \cdot \text{SL}$	$0.168 + 0.020 \cdot \text{SL}$
C to Y	t_R	0.248	$0.146 + 0.051 \cdot \text{SL}$	$0.134 + 0.055 \cdot \text{SL}$	$0.116 + 0.056 \cdot \text{SL}$
	t_F	0.159	$0.084 + 0.037 \cdot \text{SL}$	$0.073 + 0.040 \cdot \text{SL}$	$0.063 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.130	$0.081 + 0.024 \cdot \text{SL}$	$0.082 + 0.024 \cdot \text{SL}$	$0.080 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.100	$0.056 + 0.022 \cdot \text{SL}$	$0.063 + 0.020 \cdot \text{SL}$	$0.063 + 0.020 \cdot \text{SL}$
D to Y	t_R	0.240	$0.133 + 0.053 \cdot \text{SL}$	$0.125 + 0.055 \cdot \text{SL}$	$0.116 + 0.056 \cdot \text{SL}$
	t_F	0.152	$0.111 + 0.020 \cdot \text{SL}$	$0.103 + 0.023 \cdot \text{SL}$	$0.090 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.145	$0.096 + 0.025 \cdot \text{SL}$	$0.098 + 0.024 \cdot \text{SL}$	$0.098 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.109	$0.081 + 0.014 \cdot \text{SL}$	$0.085 + 0.013 \cdot \text{SL}$	$0.086 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG19D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.155	$0.100 + 0.027 \cdot \text{SL}$	$0.099 + 0.028 \cdot \text{SL}$	$0.093 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.074 + 0.020 \cdot \text{SL}$	$0.072 + 0.020 \cdot \text{SL}$	$0.065 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.229	$0.204 + 0.013 \cdot \text{SL}$	$0.206 + 0.012 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.218	$0.196 + 0.011 \cdot \text{SL}$	$0.200 + 0.010 \cdot \text{SL}$	$0.204 + 0.010 \cdot \text{SL}$
B to Y	t_R	0.155	$0.102 + 0.027 \cdot \text{SL}$	$0.099 + 0.028 \cdot \text{SL}$	$0.093 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.076 + 0.019 \cdot \text{SL}$	$0.073 + 0.020 \cdot \text{SL}$	$0.066 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.242	$0.217 + 0.013 \cdot \text{SL}$	$0.219 + 0.012 \cdot \text{SL}$	$0.220 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.214	$0.191 + 0.011 \cdot \text{SL}$	$0.196 + 0.010 \cdot \text{SL}$	$0.200 + 0.010 \cdot \text{SL}$
C to Y	t_R	0.199	$0.150 + 0.025 \cdot \text{SL}$	$0.142 + 0.027 \cdot \text{SL}$	$0.121 + 0.028 \cdot \text{SL}$
	t_F	0.124	$0.088 + 0.018 \cdot \text{SL}$	$0.081 + 0.020 \cdot \text{SL}$	$0.068 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.107	$0.081 + 0.013 \cdot \text{SL}$	$0.084 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.079	$0.055 + 0.012 \cdot \text{SL}$	$0.062 + 0.010 \cdot \text{SL}$	$0.065 + 0.010 \cdot \text{SL}$
D to Y	t_R	0.188	$0.136 + 0.026 \cdot \text{SL}$	$0.131 + 0.028 \cdot \text{SL}$	$0.119 + 0.028 \cdot \text{SL}$
	t_F	0.128	$0.108 + 0.010 \cdot \text{SL}$	$0.106 + 0.011 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.118	$0.091 + 0.013 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.091	$0.076 + 0.008 \cdot \text{SL}$	$0.081 + 0.006 \cdot \text{SL}$	$0.083 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	Y
1	x	0	1
x	1	0	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG20			SCG20D2			SCG20	SCG20D2
A	B	C	A	B	C	1.67	2.33
0.9	0.9	1.1	0.9	0.9	2.3		

SCG20/SCG20D2

2-NOR into 2-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG20

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.195	$0.087 + 0.054 \cdot \text{SL}$	$0.083 + 0.055 \cdot \text{SL}$	$0.081 + 0.055 \cdot \text{SL}$
	t_F	0.100	$0.061 + 0.020 \cdot \text{SL}$	$0.062 + 0.019 \cdot \text{SL}$	$0.062 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.149	$0.101 + 0.024 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$	$0.103 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.175	$0.146 + 0.014 \cdot \text{SL}$	$0.156 + 0.012 \cdot \text{SL}$	$0.168 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.196	$0.089 + 0.054 \cdot \text{SL}$	$0.084 + 0.055 \cdot \text{SL}$	$0.082 + 0.055 \cdot \text{SL}$
	t_F	0.100	$0.061 + 0.019 \cdot \text{SL}$	$0.062 + 0.019 \cdot \text{SL}$	$0.062 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.163	$0.115 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.173	$0.144 + 0.015 \cdot \text{SL}$	$0.155 + 0.012 \cdot \text{SL}$	$0.166 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.209	$0.106 + 0.052 \cdot \text{SL}$	$0.097 + 0.054 \cdot \text{SL}$	$0.088 + 0.055 \cdot \text{SL}$
	t_F	0.126	$0.094 + 0.016 \cdot \text{SL}$	$0.090 + 0.017 \cdot \text{SL}$	$0.072 + 0.019 \cdot \text{SL}$
	t_{PLH}	0.118	$0.069 + 0.024 \cdot \text{SL}$	$0.073 + 0.024 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.077	$0.049 + 0.014 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.064 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG20D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.135	$0.082 + 0.027 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$	$0.073 + 0.028 \cdot \text{SL}$
	t_F	0.094	$0.072 + 0.011 \cdot \text{SL}$	$0.076 + 0.010 \cdot \text{SL}$	$0.081 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.144	$0.119 + 0.012 \cdot \text{SL}$	$0.121 + 0.012 \cdot \text{SL}$	$0.121 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.194	$0.175 + 0.009 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$	$0.205 + 0.006 \cdot \text{SL}$
B to Y	t_R	0.136	$0.083 + 0.026 \cdot \text{SL}$	$0.080 + 0.027 \cdot \text{SL}$	$0.074 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.073 + 0.011 \cdot \text{SL}$	$0.079 + 0.010 \cdot \text{SL}$	$0.081 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.155	$0.131 + 0.012 \cdot \text{SL}$	$0.132 + 0.012 \cdot \text{SL}$	$0.132 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.192	$0.173 + 0.009 \cdot \text{SL}$	$0.183 + 0.007 \cdot \text{SL}$	$0.203 + 0.006 \cdot \text{SL}$
C to Y	t_R	0.150	$0.100 + 0.025 \cdot \text{SL}$	$0.094 + 0.027 \cdot \text{SL}$	$0.081 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.090 + 0.008 \cdot \text{SL}$	$0.090 + 0.008 \cdot \text{SL}$	$0.073 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.069 + 0.012 \cdot \text{SL}$	$0.069 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.059	$0.042 + 0.008 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$	$0.062 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

SCG21/SCG21D2

2-NOR into 3-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	x	0	0	1
x	1	0	0	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG21				SCG21D2				SCG21	SCG21D2
A	B	C	D	A	B	C	D		
0.9	0.9	1.0	1.0	0.9	0.9	2.1	2.2	2.00	2.67

SCG21/SCG21D2

2-NOR into 3-NOR with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.317	$0.153 + 0.082 \cdot \text{SL}$	$0.152 + 0.083 \cdot \text{SL}$	$0.154 + 0.082 \cdot \text{SL}$
	t_F	0.116	$0.067 + 0.025 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.065 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.185	$0.113 + 0.036 \cdot \text{SL}$	$0.114 + 0.036 \cdot \text{SL}$	$0.115 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.189	$0.156 + 0.016 \cdot \text{SL}$	$0.166 + 0.014 \cdot \text{SL}$	$0.175 + 0.013 \cdot \text{SL}$
B to Y	t_R	0.318	$0.154 + 0.082 \cdot \text{SL}$	$0.152 + 0.083 \cdot \text{SL}$	$0.154 + 0.082 \cdot \text{SL}$
	t_F	0.116	$0.068 + 0.024 \cdot \text{SL}$	$0.071 + 0.024 \cdot \text{SL}$	$0.067 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.198	$0.126 + 0.036 \cdot \text{SL}$	$0.127 + 0.036 \cdot \text{SL}$	$0.128 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.188	$0.155 + 0.017 \cdot \text{SL}$	$0.164 + 0.014 \cdot \text{SL}$	$0.174 + 0.013 \cdot \text{SL}$
C to Y	t_R	0.333	$0.175 + 0.079 \cdot \text{SL}$	$0.167 + 0.081 \cdot \text{SL}$	$0.157 + 0.082 \cdot \text{SL}$
	t_F	0.139	$0.099 + 0.020 \cdot \text{SL}$	$0.092 + 0.022 \cdot \text{SL}$	$0.076 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.174	$0.102 + 0.036 \cdot \text{SL}$	$0.103 + 0.035 \cdot \text{SL}$	$0.103 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.094	$0.064 + 0.015 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$
D to Y	t_R	0.329	$0.170 + 0.080 \cdot \text{SL}$	$0.163 + 0.082 \cdot \text{SL}$	$0.156 + 0.082 \cdot \text{SL}$
	t_F	0.160	$0.120 + 0.020 \cdot \text{SL}$	$0.111 + 0.022 \cdot \text{SL}$	$0.098 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.181	$0.109 + 0.036 \cdot \text{SL}$	$0.111 + 0.036 \cdot \text{SL}$	$0.112 + 0.035 \cdot \text{SL}$
	t_{PHL}	0.101	$0.071 + 0.015 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.080 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.216	$0.135 + 0.040 \cdot \text{SL}$	$0.132 + 0.041 \cdot \text{SL}$	$0.131 + 0.041 \cdot \text{SL}$
	t_F	0.101	$0.075 + 0.013 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.158	$0.123 + 0.018 \cdot \text{SL}$	$0.122 + 0.018 \cdot \text{SL}$	$0.123 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.203	$0.182 + 0.010 \cdot \text{SL}$	$0.191 + 0.008 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$
B to Y	t_R	0.217	$0.136 + 0.040 \cdot \text{SL}$	$0.133 + 0.041 \cdot \text{SL}$	$0.132 + 0.041 \cdot \text{SL}$
	t_F	0.102	$0.077 + 0.012 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.171	$0.136 + 0.018 \cdot \text{SL}$	$0.136 + 0.018 \cdot \text{SL}$	$0.136 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.201	$0.180 + 0.010 \cdot \text{SL}$	$0.190 + 0.008 \cdot \text{SL}$	$0.209 + 0.007 \cdot \text{SL}$
C to Y	t_R	0.235	$0.158 + 0.038 \cdot \text{SL}$	$0.151 + 0.040 \cdot \text{SL}$	$0.138 + 0.041 \cdot \text{SL}$
	t_F	0.116	$0.095 + 0.010 \cdot \text{SL}$	$0.094 + 0.010 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.128	$0.090 + 0.019 \cdot \text{SL}$	$0.094 + 0.018 \cdot \text{SL}$	$0.095 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.074	$0.056 + 0.009 \cdot \text{SL}$	$0.064 + 0.007 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
D to Y	t_R	0.230	$0.152 + 0.039 \cdot \text{SL}$	$0.146 + 0.041 \cdot \text{SL}$	$0.136 + 0.041 \cdot \text{SL}$
	t_F	0.136	$0.116 + 0.010 \cdot \text{SL}$	$0.113 + 0.011 \cdot \text{SL}$	$0.096 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.137	$0.099 + 0.019 \cdot \text{SL}$	$0.103 + 0.018 \cdot \text{SL}$	$0.105 + 0.018 \cdot \text{SL}$
	t_{PHL}	0.080	$0.062 + 0.009 \cdot \text{SL}$	$0.070 + 0.007 \cdot \text{SL}$	$0.076 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG22				SCG22D2				SCG22	SCG22D2
A	B	C	D	A	B	C	D		
0.8	0.9	1.0	1.1	0.8	0.8	2.0	2.3	2.00	3.00

SCG22/SCG22D2

2-NAND into 2-OR into 2-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

SCG22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.236	$0.128 + 0.054 \cdot \text{SL}$	$0.124 + 0.055 \cdot \text{SL}$	$0.119 + 0.056 \cdot \text{SL}$
	t_F	0.174	$0.090 + 0.042 \cdot \text{SL}$	$0.088 + 0.043 \cdot \text{SL}$	$0.082 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.182	$0.133 + 0.025 \cdot \text{SL}$	$0.135 + 0.024 \cdot \text{SL}$	$0.136 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.195	$0.151 + 0.022 \cdot \text{SL}$	$0.154 + 0.021 \cdot \text{SL}$	$0.155 + 0.021 \cdot \text{SL}$
B to Y	t_R	0.236	$0.128 + 0.054 \cdot \text{SL}$	$0.124 + 0.055 \cdot \text{SL}$	$0.119 + 0.056 \cdot \text{SL}$
	t_F	0.175	$0.092 + 0.042 \cdot \text{SL}$	$0.088 + 0.043 \cdot \text{SL}$	$0.083 + 0.043 \cdot \text{SL}$
	t_{PLH}	0.179	$0.129 + 0.025 \cdot \text{SL}$	$0.131 + 0.024 \cdot \text{SL}$	$0.132 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.207	$0.163 + 0.022 \cdot \text{SL}$	$0.166 + 0.021 \cdot \text{SL}$	$0.168 + 0.021 \cdot \text{SL}$
C to Y	t_R	0.245	$0.139 + 0.053 \cdot \text{SL}$	$0.132 + 0.055 \cdot \text{SL}$	$0.123 + 0.056 \cdot \text{SL}$
	t_F	0.214	$0.141 + 0.037 \cdot \text{SL}$	$0.130 + 0.040 \cdot \text{SL}$	$0.113 + 0.041 \cdot \text{SL}$
	t_{PLH}	0.131	$0.081 + 0.025 \cdot \text{SL}$	$0.085 + 0.024 \cdot \text{SL}$	$0.085 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.139	$0.098 + 0.020 \cdot \text{SL}$	$0.098 + 0.020 \cdot \text{SL}$	$0.098 + 0.020 \cdot \text{SL}$
D to Y	t_R	0.167	$0.118 + 0.024 \cdot \text{SL}$	$0.111 + 0.026 \cdot \text{SL}$	$0.097 + 0.028 \cdot \text{SL}$
	t_F	0.203	$0.124 + 0.039 \cdot \text{SL}$	$0.118 + 0.041 \cdot \text{SL}$	$0.111 + 0.042 \cdot \text{SL}$
	t_{PLH}	0.104	$0.076 + 0.014 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.131	$0.089 + 0.021 \cdot \text{SL}$	$0.091 + 0.020 \cdot \text{SL}$	$0.092 + 0.020 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SCG22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.172	$0.119 + 0.026 \cdot \text{SL}$	$0.115 + 0.028 \cdot \text{SL}$	$0.108 + 0.028 \cdot \text{SL}$
	t_F	0.129	$0.087 + 0.021 \cdot \text{SL}$	$0.087 + 0.021 \cdot \text{SL}$	$0.078 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.174	$0.148 + 0.013 \cdot \text{SL}$	$0.152 + 0.012 \cdot \text{SL}$	$0.154 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.191	$0.167 + 0.012 \cdot \text{SL}$	$0.171 + 0.011 \cdot \text{SL}$	$0.176 + 0.011 \cdot \text{SL}$
B to Y	t_R	0.173	$0.121 + 0.026 \cdot \text{SL}$	$0.115 + 0.027 \cdot \text{SL}$	$0.107 + 0.028 \cdot \text{SL}$
	t_F	0.131	$0.091 + 0.020 \cdot \text{SL}$	$0.088 + 0.021 \cdot \text{SL}$	$0.079 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.169	$0.143 + 0.013 \cdot \text{SL}$	$0.146 + 0.012 \cdot \text{SL}$	$0.149 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.201	$0.177 + 0.012 \cdot \text{SL}$	$0.182 + 0.011 \cdot \text{SL}$	$0.186 + 0.011 \cdot \text{SL}$
C to Y	t_R	0.178	$0.127 + 0.026 \cdot \text{SL}$	$0.121 + 0.027 \cdot \text{SL}$	$0.110 + 0.028 \cdot \text{SL}$
	t_F	0.169	$0.134 + 0.017 \cdot \text{SL}$	$0.128 + 0.019 \cdot \text{SL}$	$0.107 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.100	$0.073 + 0.014 \cdot \text{SL}$	$0.078 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.110	$0.088 + 0.011 \cdot \text{SL}$	$0.091 + 0.010 \cdot \text{SL}$	$0.091 + 0.010 \cdot \text{SL}$
D to Y	t_R	0.134	$0.112 + 0.011 \cdot \text{SL}$	$0.106 + 0.013 \cdot \text{SL}$	$0.090 + 0.014 \cdot \text{SL}$
	t_F	0.155	$0.118 + 0.018 \cdot \text{SL}$	$0.112 + 0.020 \cdot \text{SL}$	$0.101 + 0.021 \cdot \text{SL}$
	t_{PLH}	0.085	$0.069 + 0.008 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.101	$0.079 + 0.011 \cdot \text{SL}$	$0.082 + 0.010 \cdot \text{SL}$	$0.083 + 0.010 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL1D2	DL1D4	DL1D2	DL1D4
A	A	3.33	4.00
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.047 + 0.013 \cdot \text{SL}$	$0.047 + 0.013 \cdot \text{SL}$	$0.036 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.042 + 0.012 \cdot \text{SL}$	$0.047 + 0.011 \cdot \text{SL}$	$0.039 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.996	$0.981 + 0.008 \cdot \text{SL}$	$0.986 + 0.006 \cdot \text{SL}$	$0.989 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.998	$0.982 + 0.008 \cdot \text{SL}$	$0.988 + 0.007 \cdot \text{SL}$	$0.995 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL1D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.075	$0.063 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.056 + 0.007 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.027	$1.018 + 0.005 \cdot \text{SL}$	$1.023 + 0.003 \cdot \text{SL}$	$1.033 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.025	$1.015 + 0.005 \cdot \text{SL}$	$1.020 + 0.004 \cdot \text{SL}$	$1.036 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

DL2D2/DL2D4

2ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL2D2	DL2D4	DL2D2	DL2D4
A	A	3.67	4.33
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.049 + 0.013 \cdot \text{SL}$	$0.038 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	1.990	$1.975 + 0.008 \cdot \text{SL}$	$1.979 + 0.006 \cdot \text{SL}$	$1.983 + 0.006 \cdot \text{SL}$
	t_{PHL}	2.012	$1.995 + 0.009 \cdot \text{SL}$	$2.001 + 0.007 \cdot \text{SL}$	$2.010 + 0.006 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.065 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.067 + 0.005 \cdot \text{SL}$	$0.060 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.020	$2.011 + 0.005 \cdot \text{SL}$	$2.016 + 0.003 \cdot \text{SL}$	$2.026 + 0.003 \cdot \text{SL}$
	t_{PHL}	2.040	$2.030 + 0.005 \cdot \text{SL}$	$2.035 + 0.004 \cdot \text{SL}$	$2.051 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL3D2	DL3D4	DL3D2	DL3D4
A	A	4.67	5.33
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.048 + 0.013 \cdot \text{SL}$	$0.038 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.050 + 0.011 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	3.020	$3.004 + 0.008 \cdot \text{SL}$	$3.009 + 0.006 \cdot \text{SL}$	$3.013 + 0.006 \cdot \text{SL}$
	t_{PHL}	3.029	$3.012 + 0.008 \cdot \text{SL}$	$3.018 + 0.007 \cdot \text{SL}$	$3.026 + 0.006 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL3D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.063 + 0.007 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.064 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	3.049	$3.040 + 0.005 \cdot \text{SL}$	$3.044 + 0.003 \cdot \text{SL}$	$3.055 + 0.003 \cdot \text{SL}$
	t_{PHL}	3.057	$3.047 + 0.005 \cdot \text{SL}$	$3.052 + 0.004 \cdot \text{SL}$	$3.068 + 0.003 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

DL4D2/DL4D4

4ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL4D2	DL4D4	DL4D2	DL4D4
A	A	5.00	5.67
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.047 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	3.997	$3.981 + 0.008 \cdot \text{SL}$	$3.986 + 0.006 \cdot \text{SL}$	$3.990 + 0.006 \cdot \text{SL}$
	t_{PHL}	4.030	$4.013 + 0.009 \cdot \text{SL}$	$4.020 + 0.007 \cdot \text{SL}$	$4.028 + 0.006 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	$0.064 + 0.007 \cdot \text{SL}$	$0.065 + 0.006 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.077	$0.065 + 0.006 \cdot \text{SL}$	$0.067 + 0.005 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	4.027	$4.018 + 0.005 \cdot \text{SL}$	$4.022 + 0.003 \cdot \text{SL}$	$4.033 + 0.003 \cdot \text{SL}$
	t_{PHL}	4.061	$4.050 + 0.005 \cdot \text{SL}$	$4.056 + 0.004 \cdot \text{SL}$	$4.072 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL5D2	DL5D4	DL5D2	DL5D4
A	A	5.00	5.67
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$	$0.038 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	5.043	$5.027 + 0.008 \cdot \text{SL}$	$5.032 + 0.006 \cdot \text{SL}$	$5.037 + 0.006 \cdot \text{SL}$
	t_{PHL}	5.033	$5.015 + 0.009 \cdot \text{SL}$	$5.022 + 0.007 \cdot \text{SL}$	$5.031 + 0.006 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL5D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.066 + 0.007 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	5.074	$5.064 + 0.005 \cdot \text{SL}$	$5.069 + 0.003 \cdot \text{SL}$	$5.080 + 0.003 \cdot \text{SL}$
	t_{PHL}	5.064	$5.054 + 0.005 \cdot \text{SL}$	$5.059 + 0.004 \cdot \text{SL}$	$5.076 + 0.003 \cdot \text{SL}$

*Group1 : SL < 4, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

DL10D2/DL10D4

10ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL10D2	DL10D4	DL10D2	DL2D4
A	A	6.67	4.33
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DL10D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.048 + 0.013 \cdot \text{SL}$	$0.038 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	10.012	$9.997 + 0.008 \cdot \text{SL}$	$10.001 + 0.007 \cdot \text{SL}$	$10.007 + 0.006 \cdot \text{SL}$
	t_{PHL}	10.056	$10.038 + 0.009 \cdot \text{SL}$	$10.046 + 0.007 \cdot \text{SL}$	$10.054 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

DL10D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.066 + 0.006 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.081	$0.070 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_{PLH}	10.042	$10.033 + 0.005 \cdot \text{SL}$	$10.038 + 0.004 \cdot \text{SL}$	$10.049 + 0.003 \cdot \text{SL}$
	t_{PHL}	10.088	$10.077 + 0.006 \cdot \text{SL}$	$10.084 + 0.004 \cdot \text{SL}$	$10.100 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16

Inverter with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Logic Symbol



Truth Table

A	Y
0	1
1	0

Cell Data

Input Load (SL)							
IVDH	IV	IVD2	IVD3	IVD4	IVD6	IVD8	IVD16
A	A	A	A	A	A	A	A
0.5	1.0	2.0	3.0	4.0	6.0	8.1	16.5
Gate Count							
IVDH	IV	IVD2	IVD3	IVD4	IVD6	IVD8	IVD16
0.67	0.67	1.00	1.33	1.67	2.33	2.67	5.00

IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16

Inverter with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.191	$0.085 + 0.053 \cdot \text{SL}$	$0.064 + 0.059 \cdot \text{SL}$	$0.042 + 0.061 \cdot \text{SL}$
	t_F	0.177	$0.077 + 0.050 \cdot \text{SL}$	$0.055 + 0.056 \cdot \text{SL}$	$0.033 + 0.058 \cdot \text{SL}$
	t_{PLH}	0.109	$0.052 + 0.028 \cdot \text{SL}$	$0.061 + 0.026 \cdot \text{SL}$	$0.059 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.118	$0.056 + 0.031 \cdot \text{SL}$	$0.061 + 0.030 \cdot \text{SL}$	$0.059 + 0.030 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

IV

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.132	$0.084 + 0.024 \cdot \text{SL}$	$0.076 + 0.026 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.117	$0.075 + 0.021 \cdot \text{SL}$	$0.068 + 0.023 \cdot \text{SL}$	$0.052 + 0.025 \cdot \text{SL}$
	t_{PLH}	0.077	$0.045 + 0.016 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.079	$0.046 + 0.017 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

IVD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	$0.069 + 0.014 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.062 + 0.012 \cdot \text{SL}$	$0.067 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.053	$0.033 + 0.010 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.053	$0.032 + 0.011 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

IVD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	$0.073 + 0.009 \cdot \text{SL}$	$0.076 + 0.008 \cdot \text{SL}$	$0.053 + 0.009 \cdot \text{SL}$
	t_F	0.082	$0.065 + 0.008 \cdot \text{SL}$	$0.069 + 0.007 \cdot \text{SL}$	$0.045 + 0.008 \cdot \text{SL}$
	t_{PLH}	0.049	$0.035 + 0.007 \cdot \text{SL}$	$0.045 + 0.005 \cdot \text{SL}$	$0.057 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.050	$0.035 + 0.007 \cdot \text{SL}$	$0.045 + 0.005 \cdot \text{SL}$	$0.055 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16

Inverter with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.084	$0.070 + 0.007 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_F	0.075	$0.061 + 0.007 \cdot \text{SL}$	$0.066 + 0.006 \cdot \text{SL}$	$0.049 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.043	$0.031 + 0.006 \cdot \text{SL}$	$0.040 + 0.004 \cdot \text{SL}$	$0.056 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.043	$0.031 + 0.006 \cdot \text{SL}$	$0.039 + 0.004 \cdot \text{SL}$	$0.055 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.070 + 0.005 \cdot \text{SL}$	$0.071 + 0.004 \cdot \text{SL}$	$0.037 + 0.005 \cdot \text{SL}$
	t_F	0.070	$0.061 + 0.005 \cdot \text{SL}$	$0.064 + 0.004 \cdot \text{SL}$	$0.030 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.039	$0.030 + 0.004 \cdot \text{SL}$	$0.038 + 0.002 \cdot \text{SL}$	$0.054 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.038	$0.030 + 0.004 \cdot \text{SL}$	$0.037 + 0.002 \cdot \text{SL}$	$0.053 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.077	$0.070 + 0.003 \cdot \text{SL}$	$0.070 + 0.003 \cdot \text{SL}$	$0.046 + 0.004 \cdot \text{SL}$
	t_F	0.068	$0.061 + 0.004 \cdot \text{SL}$	$0.064 + 0.003 \cdot \text{SL}$	$0.038 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.037	$0.031 + 0.003 \cdot \text{SL}$	$0.037 + 0.002 \cdot \text{SL}$	$0.055 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.036	$0.030 + 0.003 \cdot \text{SL}$	$0.035 + 0.002 \cdot \text{SL}$	$0.053 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVD16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.073	$0.069 + 0.002 \cdot \text{SL}$	$0.071 + 0.002 \cdot \text{SL}$	$0.061 + 0.002 \cdot \text{SL}$
	t_F	0.064	$0.061 + 0.002 \cdot \text{SL}$	$0.062 + 0.001 \cdot \text{SL}$	$0.055 + 0.002 \cdot \text{SL}$
	t_{PLH}	0.033	$0.030 + 0.002 \cdot \text{SL}$	$0.033 + 0.001 \cdot \text{SL}$	$0.056 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.032	$0.029 + 0.002 \cdot \text{SL}$	$0.031 + 0.001 \cdot \text{SL}$	$0.055 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVCD(11/13)/IVCD(22/26)/IVCD44

1X IV into (1X/3X) IV/2X IV into (2X/6X) IV/4X IV into 4X IV

Logic Symbol



Truth Table

A	Y	YN
1	0	1
0	1	0

Cell Data

Input Load (SL)					Gate Count				
IVCD11	IVCD13	IVCD22	IVCD26	IVCD44	IVCD11	IVCD13	IVCD22	IVCD26	IVCD44
A	A	A	A	A					
1.0	0.9	1.9	1.9	3.7	1.00	1.67	1.67	2.67	2.67

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVCD11

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.161	$0.114 + 0.024 \cdot \text{SL}$	$0.105 + 0.026 \cdot \text{SL}$	$0.089 + 0.028 \cdot \text{SL}$
	t_F	0.157	$0.107 + 0.025 \cdot \text{SL}$	$0.097 + 0.028 \cdot \text{SL}$	$0.081 + 0.029 \cdot \text{SL}$
	t_{PLH}	0.090	$0.060 + 0.015 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.105	$0.071 + 0.017 \cdot \text{SL}$	$0.076 + 0.015 \cdot \text{SL}$	$0.075 + 0.016 \cdot \text{SL}$
Y to YN	t_R	0.124	$0.074 + 0.025 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$	$0.046 + 0.029 \cdot \text{SL}$
	t_F	0.130	$0.083 + 0.024 \cdot \text{SL}$	$0.074 + 0.026 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.087	$0.050 + 0.019 \cdot \text{SL}$	$0.062 + 0.015 \cdot \text{SL}$	$0.060 + 0.016 \cdot \text{SL}$
	t_{PHL}	0.073	$0.040 + 0.016 \cdot \text{SL}$	$0.055 + 0.013 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

IVCD13

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.216	$0.168 + 0.024 \cdot \text{SL}$	$0.154 + 0.028 \cdot \text{SL}$	$0.123 + 0.029 \cdot \text{SL}$
	t_F	0.215	$0.163 + 0.026 \cdot \text{SL}$	$0.151 + 0.029 \cdot \text{SL}$	$0.127 + 0.030 \cdot \text{SL}$
	t_{PLH}	0.117	$0.091 + 0.013 \cdot \text{SL}$	$0.094 + 0.012 \cdot \text{SL}$	$0.093 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.134	$0.103 + 0.016 \cdot \text{SL}$	$0.103 + 0.016 \cdot \text{SL}$	$0.102 + 0.016 \cdot \text{SL}$
Y to YN	t_R	0.084	$0.065 + 0.010 \cdot \text{SL}$	$0.068 + 0.009 \cdot \text{SL}$	$0.041 + 0.010 \cdot \text{SL}$
	t_F	0.092	$0.074 + 0.009 \cdot \text{SL}$	$0.076 + 0.008 \cdot \text{SL}$	$0.052 + 0.009 \cdot \text{SL}$
	t_{PLH}	0.056	$0.040 + 0.008 \cdot \text{SL}$	$0.049 + 0.005 \cdot \text{SL}$	$0.057 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.046	$0.031 + 0.007 \cdot \text{SL}$	$0.041 + 0.005 \cdot \text{SL}$	$0.056 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVCD(11/13)/IVCD(22/26)/IVCD44

1X IV into (1X/3X) IV/2X IV into (2X/6X) IV/4X IV into 4X IV

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVCD22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.129	$0.106 + 0.012 \cdot \text{SL}$	$0.102 + 0.013 \cdot \text{SL}$	$0.083 + 0.014 \cdot \text{SL}$
	t_F	0.124	$0.101 + 0.012 \cdot \text{SL}$	$0.094 + 0.013 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$
	t_{PLH}	0.069	$0.052 + 0.009 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.081	$0.061 + 0.010 \cdot \text{SL}$	$0.068 + 0.008 \cdot \text{SL}$	$0.070 + 0.008 \cdot \text{SL}$
Y to YN	t_R	0.091	$0.064 + 0.014 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.044 + 0.015 \cdot \text{SL}$
	t_F	0.099	$0.073 + 0.013 \cdot \text{SL}$	$0.075 + 0.012 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.061	$0.038 + 0.011 \cdot \text{SL}$	$0.050 + 0.008 \cdot \text{SL}$	$0.056 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.050	$0.030 + 0.010 \cdot \text{SL}$	$0.043 + 0.007 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

IVCD26

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.185	$0.163 + 0.011 \cdot \text{SL}$	$0.152 + 0.014 \cdot \text{SL}$	$0.114 + 0.015 \cdot \text{SL}$
	t_F	0.184	$0.159 + 0.013 \cdot \text{SL}$	$0.151 + 0.015 \cdot \text{SL}$	$0.119 + 0.015 \cdot \text{SL}$
	t_{PLH}	0.100	$0.086 + 0.007 \cdot \text{SL}$	$0.089 + 0.006 \cdot \text{SL}$	$0.090 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.113	$0.097 + 0.008 \cdot \text{SL}$	$0.098 + 0.008 \cdot \text{SL}$	$0.098 + 0.008 \cdot \text{SL}$
Y to YN	t_R	0.072	$0.062 + 0.005 \cdot \text{SL}$	$0.064 + 0.005 \cdot \text{SL}$	$0.027 + 0.005 \cdot \text{SL}$
	t_F	0.080	$0.070 + 0.005 \cdot \text{SL}$	$0.071 + 0.004 \cdot \text{SL}$	$0.037 + 0.005 \cdot \text{SL}$
	t_{PLH}	0.045	$0.035 + 0.005 \cdot \text{SL}$	$0.043 + 0.003 \cdot \text{SL}$	$0.055 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.037	$0.028 + 0.004 \cdot \text{SL}$	$0.036 + 0.002 \cdot \text{SL}$	$0.054 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVCD44


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	$0.107 + 0.006 \cdot \text{SL}$	$0.106 + 0.006 \cdot \text{SL}$	$0.086 + 0.007 \cdot \text{SL}$
	t_F	0.112	$0.100 + 0.006 \cdot \text{SL}$	$0.099 + 0.007 \cdot \text{SL}$	$0.078 + 0.007 \cdot \text{SL}$
	t_{PLH}	0.061	$0.051 + 0.005 \cdot \text{SL}$	$0.056 + 0.003 \cdot \text{SL}$	$0.067 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.071	$0.060 + 0.005 \cdot \text{SL}$	$0.065 + 0.004 \cdot \text{SL}$	$0.070 + 0.004 \cdot \text{SL}$
Y to YN	t_R	0.077	$0.062 + 0.008 \cdot \text{SL}$	$0.066 + 0.007 \cdot \text{SL}$	$0.045 + 0.007 \cdot \text{SL}$
	t_F	0.084	$0.070 + 0.007 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.056 + 0.007 \cdot \text{SL}$
	t_{PLH}	0.049	$0.036 + 0.007 \cdot \text{SL}$	$0.045 + 0.004 \cdot \text{SL}$	$0.056 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.040	$0.027 + 0.006 \cdot \text{SL}$	$0.037 + 0.004 \cdot \text{SL}$	$0.055 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVT/IVTD2/IVTD4/IVTD8/IVTD16

Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	E	Y
x	0	Hi-Z
0	1	1
1	1	0

Cell Data

Input Load (SL)										Output Load (SL)				
IVT		IVTD2		IVTD4		IVTD8		IVTD16		IVT	IVTD2	IVTD4	IVTD8	IVTD16
A	E	A	E	A	E	A	E	A	E	Y	Y	Y	Y	Y
0.7	1.3	0.7	1.5	0.8	1.7	1.0	2.8	1.0	2.8	0.9	1.1	2.1	4.3	8.3
Gate Count														
IVT		IVTD2		IVTD4		IVTD8		IVTD16						
2.67		3.00		3.67		5.67		8.00						

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.105	$0.050 + 0.027 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.197	$0.169 + 0.014 \cdot \text{SL}$	$0.175 + 0.013 \cdot \text{SL}$	$0.178 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.228	$0.196 + 0.016 \cdot \text{SL}$	$0.206 + 0.014 \cdot \text{SL}$	$0.214 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.118	$0.063 + 0.028 \cdot \text{SL}$	$0.057 + 0.029 \cdot \text{SL}$	$0.050 + 0.030 \cdot \text{SL}$
	t_F	0.106	$0.056 + 0.025 \cdot \text{SL}$	$0.060 + 0.024 \cdot \text{SL}$	$0.055 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.120	$0.090 + 0.015 \cdot \text{SL}$	$0.098 + 0.013 \cdot \text{SL}$	$0.101 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.191	$0.158 + 0.017 \cdot \text{SL}$	$0.169 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$
	t_{PLZ}	0.140	$0.140 + 0.000 \cdot \text{SL}$	$0.140 + 0.000 \cdot \text{SL}$	$0.141 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.142	$0.142 + 0.000 \cdot \text{SL}$	$0.142 + 0.000 \cdot \text{SL}$	$0.142 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

IVTD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.072	$0.042 + 0.015 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.041 + 0.015 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.194	$0.177 + 0.009 \cdot \text{SL}$	$0.184 + 0.007 \cdot \text{SL}$	$0.192 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.219	$0.202 + 0.009 \cdot \text{SL}$	$0.207 + 0.007 \cdot \text{SL}$	$0.223 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.082	$0.054 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.047 + 0.014 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.108	$0.090 + 0.009 \cdot \text{SL}$	$0.099 + 0.007 \cdot \text{SL}$	$0.110 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.182	$0.160 + 0.011 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_{PLZ}	0.150	$0.150 + 0.000 \cdot \text{SL}$	$0.149 + 0.000 \cdot \text{SL}$	$0.149 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.153	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

IVT/IVTD2/IVTD4/IVTD8/IVTD16

Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVTD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.063	$0.046 + 0.008 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.053 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.200	$0.190 + 0.005 \cdot \text{SL}$	$0.196 + 0.004 \cdot \text{SL}$	$0.212 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.228	$0.217 + 0.005 \cdot \text{SL}$	$0.222 + 0.004 \cdot \text{SL}$	$0.240 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.073	$0.059 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.049 + 0.008 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.114	$0.101 + 0.006 \cdot \text{SL}$	$0.111 + 0.004 \cdot \text{SL}$	$0.130 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.175	$0.161 + 0.007 \cdot \text{SL}$	$0.170 + 0.004 \cdot \text{SL}$	$0.196 + 0.003 \cdot \text{SL}$
	t_{PLZ}	0.171	$0.171 + 0.000 \cdot \text{SL}$	$0.171 + 0.000 \cdot \text{SL}$	$0.171 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.186	$0.186 + 0.000 \cdot \text{SL}$	$0.186 + 0.000 \cdot \text{SL}$	$0.187 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVTD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.055	$0.046 + 0.005 \cdot \text{SL}$	$0.050 + 0.003 \cdot \text{SL}$	$0.046 + 0.004 \cdot \text{SL}$
	t_F	0.061	$0.056 + 0.003 \cdot \text{SL}$	$0.055 + 0.003 \cdot \text{SL}$	$0.051 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.220	$0.214 + 0.003 \cdot \text{SL}$	$0.218 + 0.002 \cdot \text{SL}$	$0.241 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.242	$0.237 + 0.003 \cdot \text{SL}$	$0.240 + 0.002 \cdot \text{SL}$	$0.262 + 0.002 \cdot \text{SL}$
E to Y	t_R	0.066	$0.058 + 0.004 \cdot \text{SL}$	$0.059 + 0.003 \cdot \text{SL}$	$0.047 + 0.004 \cdot \text{SL}$
	t_F	0.054	$0.046 + 0.004 \cdot \text{SL}$	$0.050 + 0.003 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.107	$0.099 + 0.004 \cdot \text{SL}$	$0.106 + 0.002 \cdot \text{SL}$	$0.132 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.185	$0.178 + 0.004 \cdot \text{SL}$	$0.184 + 0.002 \cdot \text{SL}$	$0.218 + 0.002 \cdot \text{SL}$
	t_{PLZ}	0.181	$0.181 + 0.000 \cdot \text{SL}$	$0.181 + 0.000 \cdot \text{SL}$	$0.181 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.181	$0.181 + 0.000 \cdot \text{SL}$	$0.182 + 0.000 \cdot \text{SL}$	$0.182 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVTD16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.061	$0.056 + 0.003 \cdot \text{SL}$	$0.059 + 0.002 \cdot \text{SL}$	$0.076 + 0.002 \cdot \text{SL}$
	t_F	0.087	$0.084 + 0.002 \cdot \text{SL}$	$0.085 + 0.001 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.251	$0.247 + 0.002 \cdot \text{SL}$	$0.249 + 0.001 \cdot \text{SL}$	$0.280 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.280	$0.277 + 0.002 \cdot \text{SL}$	$0.279 + 0.001 \cdot \text{SL}$	$0.298 + 0.001 \cdot \text{SL}$
E to Y	t_R	0.074	$0.068 + 0.003 \cdot \text{SL}$	$0.073 + 0.002 \cdot \text{SL}$	$0.079 + 0.002 \cdot \text{SL}$
	t_F	0.061	$0.056 + 0.003 \cdot \text{SL}$	$0.059 + 0.002 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.135	$0.129 + 0.003 \cdot \text{SL}$	$0.134 + 0.001 \cdot \text{SL}$	$0.172 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.203	$0.198 + 0.002 \cdot \text{SL}$	$0.202 + 0.001 \cdot \text{SL}$	$0.242 + 0.001 \cdot \text{SL}$
	t_{PLZ}	0.215	$0.215 + 0.000 \cdot \text{SL}$	$0.215 + 0.000 \cdot \text{SL}$	$0.216 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.269	$0.268 + 0.000 \cdot \text{SL}$	$0.269 + 0.000 \cdot \text{SL}$	$0.270 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVTN/IVTND2/IVTND4/IVTND8/IVTND16

Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	EN	Y
x	1	Hi-Z
0	0	1
1	0	0

Cell Data

Input Load (SL)										Output Load (SL)				
IVTN		IVTND2		IVTND4		IVTND8		IVTND16		IVTN	IVTND2	IVTND4	IVTND8	IVTND16
A	EN	A	EN	A	EN	A	EN	A	EN	Y	Y	Y	Y	Y
0.7	1.4	0.7	1.6	0.8	1.1	1.0	3.0	1.0	3.0	0.9	1.1	2.1	4.3	8.3
Gate Count														
IVTN		IVTND2		IVTND4		IVTND8		IVTND16						
2.67		3.00		3.67		5.67		8.00						

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVTN

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.050 + 0.028 \cdot \text{SL}$	$0.049 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.048 + 0.024 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.198	$0.169 + 0.014 \cdot \text{SL}$	$0.175 + 0.013 \cdot \text{SL}$	$0.179 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.227	$0.195 + 0.016 \cdot \text{SL}$	$0.204 + 0.013 \cdot \text{SL}$	$0.212 + 0.013 \cdot \text{SL}$
EN to Y	t_R	0.114	$0.056 + 0.029 \cdot \text{SL}$	$0.054 + 0.029 \cdot \text{SL}$	$0.047 + 0.030 \cdot \text{SL}$
	t_F	0.108	$0.060 + 0.024 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.174	$0.145 + 0.015 \cdot \text{SL}$	$0.152 + 0.013 \cdot \text{SL}$	$0.155 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.147	$0.113 + 0.017 \cdot \text{SL}$	$0.125 + 0.014 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$
	t_{PLZ}	0.079	$0.079 + 0.000 \cdot \text{SL}$	$0.079 + 0.000 \cdot \text{SL}$	$0.079 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.178	$0.178 + 0.000 \cdot \text{SL}$	$0.178 + 0.000 \cdot \text{SL}$	$0.178 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

IVTND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.072	$0.044 + 0.014 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.042 + 0.014 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.196	$0.178 + 0.009 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$	$0.195 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.219	$0.200 + 0.009 \cdot \text{SL}$	$0.208 + 0.007 \cdot \text{SL}$	$0.222 + 0.006 \cdot \text{SL}$
EN to Y	t_R	0.084	$0.059 + 0.012 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.049 + 0.014 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.166	$0.147 + 0.009 \cdot \text{SL}$	$0.157 + 0.007 \cdot \text{SL}$	$0.167 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.131	$0.109 + 0.011 \cdot \text{SL}$	$0.121 + 0.008 \cdot \text{SL}$	$0.139 + 0.007 \cdot \text{SL}$
	t_{PLZ}	0.086	$0.086 + 0.000 \cdot \text{SL}$	$0.086 + 0.000 \cdot \text{SL}$	$0.086 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.203	$0.203 + 0.000 \cdot \text{SL}$	$0.204 + 0.000 \cdot \text{SL}$	$0.202 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

IVTN/IVTND2/IVTND4/IVTND8/IVTND16

Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

IVTND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.062	$0.046 + 0.008 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.006 \cdot \text{SL}$	$0.054 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.202	$0.191 + 0.005 \cdot \text{SL}$	$0.197 + 0.004 \cdot \text{SL}$	$0.214 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.226	$0.216 + 0.005 \cdot \text{SL}$	$0.221 + 0.004 \cdot \text{SL}$	$0.238 + 0.003 \cdot \text{SL}$
EN to Y	t_R	0.070	$0.053 + 0.008 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.050 + 0.008 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.172	$0.159 + 0.006 \cdot \text{SL}$	$0.168 + 0.004 \cdot \text{SL}$	$0.186 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.127	$0.113 + 0.007 \cdot \text{SL}$	$0.123 + 0.004 \cdot \text{SL}$	$0.149 + 0.003 \cdot \text{SL}$
	t_{PLZ}	0.100	$0.100 + 0.000 \cdot \text{SL}$	$0.100 + 0.000 \cdot \text{SL}$	$0.101 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.231	$0.230 + 0.000 \cdot \text{SL}$	$0.231 + 0.000 \cdot \text{SL}$	$0.231 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

IVTND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.055	$0.045 + 0.005 \cdot \text{SL}$	$0.051 + 0.003 \cdot \text{SL}$	$0.047 + 0.004 \cdot \text{SL}$
	t_F	0.061	$0.056 + 0.003 \cdot \text{SL}$	$0.055 + 0.003 \cdot \text{SL}$	$0.050 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.221	$0.215 + 0.003 \cdot \text{SL}$	$0.220 + 0.002 \cdot \text{SL}$	$0.243 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.240	$0.235 + 0.003 \cdot \text{SL}$	$0.238 + 0.002 \cdot \text{SL}$	$0.259 + 0.002 \cdot \text{SL}$
EN to Y	t_R	0.062	$0.054 + 0.004 \cdot \text{SL}$	$0.057 + 0.003 \cdot \text{SL}$	$0.047 + 0.004 \cdot \text{SL}$
	t_F	0.056	$0.048 + 0.004 \cdot \text{SL}$	$0.053 + 0.003 \cdot \text{SL}$	$0.053 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.182	$0.175 + 0.004 \cdot \text{SL}$	$0.181 + 0.002 \cdot \text{SL}$	$0.207 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.115	$0.107 + 0.004 \cdot \text{SL}$	$0.114 + 0.002 \cdot \text{SL}$	$0.149 + 0.002 \cdot \text{SL}$
	t_{PLZ}	0.096	$0.096 + 0.000 \cdot \text{SL}$	$0.096 + 0.000 \cdot \text{SL}$	$0.096 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.251	$0.251 + 0.000 \cdot \text{SL}$	$0.251 + 0.000 \cdot \text{SL}$	$0.251 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

IVTND16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.062	$0.056 + 0.003 \cdot \text{SL}$	$0.060 + 0.002 \cdot \text{SL}$	$0.077 + 0.002 \cdot \text{SL}$
	t_F	0.089	$0.086 + 0.001 \cdot \text{SL}$	$0.086 + 0.001 \cdot \text{SL}$	$0.080 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.252	$0.248 + 0.002 \cdot \text{SL}$	$0.251 + 0.001 \cdot \text{SL}$	$0.282 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.279	$0.275 + 0.002 \cdot \text{SL}$	$0.277 + 0.001 \cdot \text{SL}$	$0.296 + 0.001 \cdot \text{SL}$
EN to Y	t_R	0.073	$0.067 + 0.003 \cdot \text{SL}$	$0.071 + 0.002 \cdot \text{SL}$	$0.080 + 0.002 \cdot \text{SL}$
	t_F	0.062	$0.056 + 0.003 \cdot \text{SL}$	$0.061 + 0.002 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.209	$0.203 + 0.003 \cdot \text{SL}$	$0.208 + 0.001 \cdot \text{SL}$	$0.246 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.134	$0.129 + 0.002 \cdot \text{SL}$	$0.133 + 0.001 \cdot \text{SL}$	$0.173 + 0.001 \cdot \text{SL}$
	t_{PLZ}	0.133	$0.133 + 0.000 \cdot \text{SL}$	$0.133 + 0.000 \cdot \text{SL}$	$0.133 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.339	$0.339 + 0.000 \cdot \text{SL}$	$0.340 + 0.000 \cdot \text{SL}$	$0.340 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16

Non-Inverting Buffer with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)							
NIDH	NID	NID2	NID3	NID4	NID6	NID8	NID16
A	A	A	A	A	A	A	A
0.3	0.6	0.7	0.8	1.0	1.5	1.9	3.7
Gate Count							
NIDH	NID	NID2	NID3	NID4	NID6	NID8	NID16
1.00	1.00	1.33	1.67	2.00	2.67	3.33	6.00

NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16

Non-Inverting Buffer with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NIDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.169	$0.056 + 0.056 \cdot \text{SL}$	$0.046 + 0.059 \cdot \text{SL}$	$0.040 + 0.060 \cdot \text{SL}$
	t_F	0.166	$0.057 + 0.055 \cdot \text{SL}$	$0.048 + 0.057 \cdot \text{SL}$	$0.039 + 0.058 \cdot \text{SL}$
	t_{PLH}	0.168	$0.115 + 0.027 \cdot \text{SL}$	$0.118 + 0.026 \cdot \text{SL}$	$0.118 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.195	$0.132 + 0.032 \cdot \text{SL}$	$0.137 + 0.030 \cdot \text{SL}$	$0.138 + 0.030 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NID

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	$0.053 + 0.026 \cdot \text{SL}$	$0.047 + 0.027 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_{PLH}	0.138	$0.110 + 0.014 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$	$0.116 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.144	$0.110 + 0.017 \cdot \text{SL}$	$0.116 + 0.015 \cdot \text{SL}$	$0.118 + 0.015 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.049 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.038 + 0.015 \cdot \text{SL}$
	t_{PLH}	0.145	$0.128 + 0.008 \cdot \text{SL}$	$0.135 + 0.007 \cdot \text{SL}$	$0.141 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.141	$0.121 + 0.010 \cdot \text{SL}$	$0.128 + 0.008 \cdot \text{SL}$	$0.134 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NID3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.062 + 0.009 \cdot \text{SL}$	$0.060 + 0.009 \cdot \text{SL}$	$0.047 + 0.009 \cdot \text{SL}$
	t_F	0.073	$0.053 + 0.010 \cdot \text{SL}$	$0.055 + 0.010 \cdot \text{SL}$	$0.044 + 0.010 \cdot \text{SL}$
	t_{PLH}	0.153	$0.141 + 0.006 \cdot \text{SL}$	$0.147 + 0.005 \cdot \text{SL}$	$0.157 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.151	$0.136 + 0.007 \cdot \text{SL}$	$0.143 + 0.006 \cdot \text{SL}$	$0.153 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16

Non-Inverting Buffer with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NID4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.051 + 0.008 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_{PLH}	0.152	$0.142 + 0.005 \cdot \text{SL}$	$0.147 + 0.004 \cdot \text{SL}$	$0.160 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.147	$0.136 + 0.006 \cdot \text{SL}$	$0.141 + 0.004 \cdot \text{SL}$	$0.154 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NID6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.067	$0.057 + 0.005 \cdot \text{SL}$	$0.059 + 0.005 \cdot \text{SL}$	$0.037 + 0.005 \cdot \text{SL}$
	t_F	0.059	$0.049 + 0.005 \cdot \text{SL}$	$0.051 + 0.005 \cdot \text{SL}$	$0.034 + 0.005 \cdot \text{SL}$
	t_{PLH}	0.143	$0.136 + 0.003 \cdot \text{SL}$	$0.140 + 0.002 \cdot \text{SL}$	$0.153 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.138	$0.130 + 0.004 \cdot \text{SL}$	$0.134 + 0.003 \cdot \text{SL}$	$0.147 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NID8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.065	$0.058 + 0.003 \cdot \text{SL}$	$0.058 + 0.003 \cdot \text{SL}$	$0.041 + 0.004 \cdot \text{SL}$
	t_F	0.057	$0.048 + 0.004 \cdot \text{SL}$	$0.051 + 0.004 \cdot \text{SL}$	$0.038 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.141	$0.136 + 0.003 \cdot \text{SL}$	$0.140 + 0.002 \cdot \text{SL}$	$0.154 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.137	$0.131 + 0.003 \cdot \text{SL}$	$0.134 + 0.002 \cdot \text{SL}$	$0.149 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NID16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.063	$0.058 + 0.003 \cdot \text{SL}$	$0.062 + 0.002 \cdot \text{SL}$	$0.052 + 0.002 \cdot \text{SL}$
	t_F	0.054	$0.050 + 0.002 \cdot \text{SL}$	$0.050 + 0.002 \cdot \text{SL}$	$0.048 + 0.002 \cdot \text{SL}$
	t_{PLH}	0.140	$0.137 + 0.001 \cdot \text{SL}$	$0.138 + 0.001 \cdot \text{SL}$	$0.153 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.135	$0.132 + 0.002 \cdot \text{SL}$	$0.133 + 0.001 \cdot \text{SL}$	$0.148 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

OAK_NID10P/OAK_NID20P

Clock Buffer for 10pF/20pF Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
OAK_NID10P	OAK_NID20P	OAK_NID10P	OAK_NID20P
A	A	17.18	31.64
1.0	1.9		

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_NID10P

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.060	$0.058 + 0.001 \cdot \text{SL}$	$0.047 + 0.001 \cdot \text{SL}$	$0.041 + 0.001 \cdot \text{SL}$
	t_F	0.049	$0.047 + 0.001 \cdot \text{SL}$	$0.037 + 0.001 \cdot \text{SL}$	$0.033 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.346	$0.345 + 0.000 \cdot \text{SL}$	$0.351 + 0.000 \cdot \text{SL}$	$0.351 + 0.000 \cdot \text{SL}$
	t_{PHL}	0.262	$0.261 + 0.001 \cdot \text{SL}$	$0.265 + 0.001 \cdot \text{SL}$	$0.265 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 361$, *Group2 : $361 \leq \text{SL} \leq 541$, *Group3 : $541 < \text{SL}$

OAK_NID20P


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.058	$0.057 + 0.000 \cdot \text{SL}$	$0.047 + 0.000 \cdot \text{SL}$	$0.041 + 0.001 \cdot \text{SL}$
	t_F	0.050	$0.049 + 0.000 \cdot \text{SL}$	$0.040 + 0.000 \cdot \text{SL}$	$0.034 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.327	$0.326 + 0.000 \cdot \text{SL}$	$0.335 + 0.000 \cdot \text{SL}$	$0.335 + 0.000 \cdot \text{SL}$
	t_{PHL}	0.248	$0.248 + 0.000 \cdot \text{SL}$	$0.256 + 0.000 \cdot \text{SL}$	$0.257 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 451$, *Group2 : $451 \leq \text{SL} \leq 902$, *Group3 : $902 < \text{SL}$

NIT/NITD2/NITD4/NITD8/NITD16

Non-Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	E	Y
x	0	Hi-Z
0	1	0
1	1	1

Cell Data

Input Load (SL)										Output Load (SL)				
NIT		NITD2		NITD4		NITD8		NITD16		NIT	NITD2	NITD4	NITD8	NITD16
A	E	A	E	A	E	A	E	A	E	Y	Y	Y	Y	Y
1.6	1.3	1.9	1.5	2.2	1.7	4.6	2.8	4.4	2.9	0.9	1.1	2.2	4.3	8.4
Gate Count														
NIT		NITD2		NITD4		NITD8		NITD16						
2.33		2.67		3.33		5.33		7.33						

NIT/NITD2/NITD4/NITD8/NITD16

Non-Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.052 + 0.027 \cdot \text{SL}$	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.051 + 0.024 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.120	$0.092 + 0.014 \cdot \text{SL}$	$0.098 + 0.013 \cdot \text{SL}$	$0.101 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.157	$0.125 + 0.016 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$	$0.142 + 0.013 \cdot \text{SL}$
E to Y	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.055 + 0.029 \cdot \text{SL}$	$0.048 + 0.030 \cdot \text{SL}$
	t_F	0.104	$0.055 + 0.025 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.119	$0.089 + 0.015 \cdot \text{SL}$	$0.097 + 0.013 \cdot \text{SL}$	$0.101 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.190	$0.156 + 0.017 \cdot \text{SL}$	$0.168 + 0.014 \cdot \text{SL}$	$0.177 + 0.013 \cdot \text{SL}$
	t_{PLZ}	0.140	$0.140 + 0.000 \cdot \text{SL}$	$0.140 + 0.000 \cdot \text{SL}$	$0.140 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.142	$0.142 + 0.000 \cdot \text{SL}$	$0.143 + 0.000 \cdot \text{SL}$	$0.143 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NITD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.045 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.111	$0.093 + 0.009 \cdot \text{SL}$	$0.101 + 0.007 \cdot \text{SL}$	$0.110 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.144	$0.126 + 0.009 \cdot \text{SL}$	$0.132 + 0.007 \cdot \text{SL}$	$0.146 + 0.006 \cdot \text{SL}$
E to Y	t_R	0.082	$0.055 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.047 + 0.014 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.109	$0.090 + 0.009 \cdot \text{SL}$	$0.100 + 0.007 \cdot \text{SL}$	$0.110 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.182	$0.160 + 0.011 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_{PLZ}	0.150	$0.150 + 0.000 \cdot \text{SL}$	$0.150 + 0.000 \cdot \text{SL}$	$0.149 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.153	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NITD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.065	$0.048 + 0.008 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.070	$0.058 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.118	$0.107 + 0.005 \cdot \text{SL}$	$0.114 + 0.004 \cdot \text{SL}$	$0.130 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.151	$0.141 + 0.005 \cdot \text{SL}$	$0.145 + 0.004 \cdot \text{SL}$	$0.161 + 0.003 \cdot \text{SL}$
E to Y	t_R	0.074	$0.059 + 0.008 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.065	$0.048 + 0.008 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.062 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.116	$0.103 + 0.006 \cdot \text{SL}$	$0.113 + 0.004 \cdot \text{SL}$	$0.132 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.180	$0.166 + 0.007 \cdot \text{SL}$	$0.176 + 0.004 \cdot \text{SL}$	$0.202 + 0.003 \cdot \text{SL}$
	t_{PLZ}	0.171	$0.171 + 0.000 \cdot \text{SL}$	$0.171 + 0.000 \cdot \text{SL}$	$0.171 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.188	$0.187 + 0.000 \cdot \text{SL}$	$0.188 + 0.000 \cdot \text{SL}$	$0.188 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NIT/NITD2/NITD4/NITD8/NITD16

Non-Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NITD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.056	$0.047 + 0.004 \cdot \text{SL}$	$0.050 + 0.003 \cdot \text{SL}$	$0.045 + 0.004 \cdot \text{SL}$
	t_F	0.065	$0.060 + 0.002 \cdot \text{SL}$	$0.058 + 0.003 \cdot \text{SL}$	$0.049 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.108	$0.102 + 0.003 \cdot \text{SL}$	$0.106 + 0.002 \cdot \text{SL}$	$0.127 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.137	$0.132 + 0.003 \cdot \text{SL}$	$0.135 + 0.002 \cdot \text{SL}$	$0.155 + 0.002 \cdot \text{SL}$
E to Y	t_R	0.065	$0.057 + 0.004 \cdot \text{SL}$	$0.060 + 0.003 \cdot \text{SL}$	$0.047 + 0.004 \cdot \text{SL}$
	t_F	0.054	$0.046 + 0.004 \cdot \text{SL}$	$0.050 + 0.003 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.107	$0.100 + 0.004 \cdot \text{SL}$	$0.106 + 0.002 \cdot \text{SL}$	$0.132 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.184	$0.177 + 0.004 \cdot \text{SL}$	$0.183 + 0.002 \cdot \text{SL}$	$0.217 + 0.002 \cdot \text{SL}$
	t_{PLZ}	0.180	$0.180 + 0.000 \cdot \text{SL}$	$0.180 + 0.000 \cdot \text{SL}$	$0.180 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.181	$0.181 + 0.000 \cdot \text{SL}$	$0.182 + 0.000 \cdot \text{SL}$	$0.182 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NITD16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.063	$0.061 + 0.001 \cdot \text{SL}$	$0.057 + 0.002 \cdot \text{SL}$	$0.075 + 0.002 \cdot \text{SL}$
	t_F	0.086	$0.083 + 0.001 \cdot \text{SL}$	$0.083 + 0.001 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.138	$0.134 + 0.002 \cdot \text{SL}$	$0.137 + 0.001 \cdot \text{SL}$	$0.166 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.175	$0.172 + 0.002 \cdot \text{SL}$	$0.174 + 0.001 \cdot \text{SL}$	$0.192 + 0.001 \cdot \text{SL}$
E to Y	t_R	0.073	$0.067 + 0.003 \cdot \text{SL}$	$0.071 + 0.002 \cdot \text{SL}$	$0.079 + 0.002 \cdot \text{SL}$
	t_F	0.060	$0.054 + 0.003 \cdot \text{SL}$	$0.059 + 0.002 \cdot \text{SL}$	$0.078 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.135	$0.130 + 0.002 \cdot \text{SL}$	$0.134 + 0.001 \cdot \text{SL}$	$0.172 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.202	$0.198 + 0.002 \cdot \text{SL}$	$0.202 + 0.001 \cdot \text{SL}$	$0.241 + 0.001 \cdot \text{SL}$
	t_{PLZ}	0.215	$0.215 + 0.000 \cdot \text{SL}$	$0.215 + 0.000 \cdot \text{SL}$	$0.215 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.269	$0.268 + 0.000 \cdot \text{SL}$	$0.269 + 0.000 \cdot \text{SL}$	$0.270 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NITN/NITND2/NITND4/NITND8/NITND16

Non-Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	EN	Y
x	1	Hi-Z
0	0	0
1	0	1

Cell Data

Input Load (SL)										Output Load (SL)				
NITN		NITND2		NITND4		NITND8		NITND16		NITN	NITND2	NITND4	NITND8	NITND16
A	EN	A	EN	A	EN	A	EN	A	EN	Y	Y	Y	Y	Y
1.6	1.4	1.9	1.6	2.2	1.9	4.6	3.0	4.4	3.0	0.9	1.1	2.2	4.3	8.4
Gate Count														
NITN				NITND2				NITND4				NITND8		NITND16
2.33				2.67				3.33				5.33		7.33

NITN/NITND2/NITND4/NITND8/NITND16

Non-Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NITN

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	$0.053 + 0.026 \cdot \text{SL}$	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.121	$0.092 + 0.014 \cdot \text{SL}$	$0.099 + 0.013 \cdot \text{SL}$	$0.102 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.156	$0.124 + 0.016 \cdot \text{SL}$	$0.133 + 0.013 \cdot \text{SL}$	$0.141 + 0.012 \cdot \text{SL}$
EN to Y	t_R	0.111	$0.054 + 0.029 \cdot \text{SL}$	$0.053 + 0.029 \cdot \text{SL}$	$0.046 + 0.030 \cdot \text{SL}$
	t_F	0.106	$0.058 + 0.024 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.173	$0.144 + 0.015 \cdot \text{SL}$	$0.151 + 0.013 \cdot \text{SL}$	$0.154 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.146	$0.112 + 0.017 \cdot \text{SL}$	$0.124 + 0.014 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$
	t_{PLZ}	0.079	$0.079 + 0.000 \cdot \text{SL}$	$0.079 + 0.000 \cdot \text{SL}$	$0.079 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.178	$0.178 + 0.000 \cdot \text{SL}$	$0.178 + 0.000 \cdot \text{SL}$	$0.178 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

NITND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.075	$0.048 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.111	$0.094 + 0.009 \cdot \text{SL}$	$0.101 + 0.007 \cdot \text{SL}$	$0.111 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.143	$0.125 + 0.009 \cdot \text{SL}$	$0.132 + 0.007 \cdot \text{SL}$	$0.145 + 0.006 \cdot \text{SL}$
EN to Y	t_R	0.084	$0.059 + 0.012 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.049 + 0.014 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.165	$0.146 + 0.009 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$	$0.166 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.130	$0.109 + 0.011 \cdot \text{SL}$	$0.121 + 0.008 \cdot \text{SL}$	$0.138 + 0.007 \cdot \text{SL}$
	t_{PLZ}	0.085	$0.085 + 0.000 \cdot \text{SL}$	$0.085 + 0.000 \cdot \text{SL}$	$0.085 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.202	$0.202 + 0.000 \cdot \text{SL}$	$0.202 + 0.000 \cdot \text{SL}$	$0.202 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

NITND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.064	$0.047 + 0.009 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$	$0.052 + 0.007 \cdot \text{SL}$
	t_F	0.071	$0.059 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.119	$0.108 + 0.006 \cdot \text{SL}$	$0.114 + 0.004 \cdot \text{SL}$	$0.131 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.149	$0.138 + 0.005 \cdot \text{SL}$	$0.144 + 0.004 \cdot \text{SL}$	$0.159 + 0.003 \cdot \text{SL}$
EN to Y	t_R	0.070	$0.054 + 0.008 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$	$0.054 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.050 + 0.008 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.175	$0.162 + 0.006 \cdot \text{SL}$	$0.171 + 0.004 \cdot \text{SL}$	$0.189 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.127	$0.113 + 0.007 \cdot \text{SL}$	$0.123 + 0.004 \cdot \text{SL}$	$0.149 + 0.003 \cdot \text{SL}$
	t_{PLZ}	0.100	$0.100 + 0.000 \cdot \text{SL}$	$0.100 + 0.000 \cdot \text{SL}$	$0.101 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.235	$0.234 + 0.000 \cdot \text{SL}$	$0.235 + 0.000 \cdot \text{SL}$	$0.235 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

NITN/NITND2/NITND4/NITND8/NITND16

Non-Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

NITND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.056	$0.047 + 0.004 \cdot \text{SL}$	$0.051 + 0.003 \cdot \text{SL}$	$0.046 + 0.004 \cdot \text{SL}$
	t_F	0.063	$0.056 + 0.003 \cdot \text{SL}$	$0.057 + 0.003 \cdot \text{SL}$	$0.049 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.109	$0.103 + 0.003 \cdot \text{SL}$	$0.107 + 0.002 \cdot \text{SL}$	$0.129 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.136	$0.131 + 0.003 \cdot \text{SL}$	$0.134 + 0.002 \cdot \text{SL}$	$0.153 + 0.002 \cdot \text{SL}$
EN to Y	t_R	0.062	$0.054 + 0.004 \cdot \text{SL}$	$0.057 + 0.003 \cdot \text{SL}$	$0.047 + 0.004 \cdot \text{SL}$
	t_F	0.056	$0.047 + 0.004 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$
	t_{PLH}	0.182	$0.175 + 0.004 \cdot \text{SL}$	$0.181 + 0.002 \cdot \text{SL}$	$0.206 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.114	$0.107 + 0.004 \cdot \text{SL}$	$0.114 + 0.002 \cdot \text{SL}$	$0.148 + 0.002 \cdot \text{SL}$
	t_{PLZ}	0.096	$0.096 + 0.000 \cdot \text{SL}$	$0.096 + 0.000 \cdot \text{SL}$	$0.096 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.251	$0.250 + 0.000 \cdot \text{SL}$	$0.251 + 0.000 \cdot \text{SL}$	$0.251 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

NITND16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.064	$0.061 + 0.002 \cdot \text{SL}$	$0.060 + 0.002 \cdot \text{SL}$	$0.076 + 0.002 \cdot \text{SL}$
	t_F	0.087	$0.083 + 0.002 \cdot \text{SL}$	$0.084 + 0.001 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.139	$0.135 + 0.002 \cdot \text{SL}$	$0.138 + 0.001 \cdot \text{SL}$	$0.169 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.173	$0.170 + 0.002 \cdot \text{SL}$	$0.172 + 0.001 \cdot \text{SL}$	$0.190 + 0.001 \cdot \text{SL}$
EN to Y	t_R	0.073	$0.068 + 0.003 \cdot \text{SL}$	$0.071 + 0.002 \cdot \text{SL}$	$0.080 + 0.002 \cdot \text{SL}$
	t_F	0.062	$0.057 + 0.002 \cdot \text{SL}$	$0.060 + 0.002 \cdot \text{SL}$	$0.079 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.210	$0.205 + 0.003 \cdot \text{SL}$	$0.209 + 0.001 \cdot \text{SL}$	$0.247 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.133	$0.128 + 0.002 \cdot \text{SL}$	$0.132 + 0.001 \cdot \text{SL}$	$0.172 + 0.001 \cdot \text{SL}$
	t_{PLZ}	0.132	$0.132 + 0.000 \cdot \text{SL}$	$0.132 + 0.000 \cdot \text{SL}$	$0.132 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.341	$0.341 + 0.000 \cdot \text{SL}$	$0.341 + 0.000 \cdot \text{SL}$	$0.342 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

OAK_DUCLK10/OAK_DUCLK16

2 Phase Clock Generator Buffer (1ns/1.6ns Non-overlapped)

Logic Symbol



Truth Table

A	CK	CKB
0	0	1
1	1	0

Cell Data

Input Load (SL)		Gate Count	
OAK_DUCLK10	OAK_DUCLK16	OAK_DUCLK10	OAK_DUCLK16
A	A	10.67	11.67
2.0	2.0		

OAK_DUCLK10/OAK_DUCLK16

2 Phase Clock Generator Buffer (1ns/1.6ns Non-overlapped)

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_DUCLK10

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to CK	t_R	0.083	$0.071 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$
	t_F	0.080	$0.068 + 0.006 \cdot \text{SL}$	$0.067 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.214	$2.204 + 0.005 \cdot \text{SL}$	$2.210 + 0.003 \cdot \text{SL}$	$2.221 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.235	$1.224 + 0.005 \cdot \text{SL}$	$1.230 + 0.004 \cdot \text{SL}$	$1.244 + 0.003 \cdot \text{SL}$
A to CKB	t_R	0.082	$0.069 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_F	0.081	$0.068 + 0.006 \cdot \text{SL}$	$0.069 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.274	$2.265 + 0.005 \cdot \text{SL}$	$2.270 + 0.003 \cdot \text{SL}$	$2.281 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.165	$1.155 + 0.005 \cdot \text{SL}$	$1.160 + 0.004 \cdot \text{SL}$	$1.174 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

OAK_DUCLK16


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to CK	t_R	0.090	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.064 + 0.006 \cdot \text{SL}$
	t_F	0.092	$0.081 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$
	t_{PLH}	3.167	$3.157 + 0.005 \cdot \text{SL}$	$3.162 + 0.003 \cdot \text{SL}$	$3.176 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.694	$1.682 + 0.006 \cdot \text{SL}$	$1.688 + 0.004 \cdot \text{SL}$	$1.704 + 0.003 \cdot \text{SL}$
A to CKB	t_R	0.090	$0.079 + 0.006 \cdot \text{SL}$	$0.078 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$
	t_F	0.092	$0.080 + 0.006 \cdot \text{SL}$	$0.080 + 0.006 \cdot \text{SL}$	$0.070 + 0.006 \cdot \text{SL}$
	t_{PLH}	3.229	$3.219 + 0.005 \cdot \text{SL}$	$3.225 + 0.003 \cdot \text{SL}$	$3.238 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.619	$1.608 + 0.006 \cdot \text{SL}$	$1.613 + 0.004 \cdot \text{SL}$	$1.629 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/CTSBD8/CTSBD16

Clock Tree Synthesis Buffers

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)						
CTSB	CTSBD2	CTSBD3	CTSBD4	CTSBD6	CTSBD8	CTSBD16
A	A	A	A	A	A	A
0.6	0.7	0.8	1.0	1.5	1.9	3.7
Gate Count						
CTSB	CTSBD2	CTSBD3	CTSBD4	CTSBD6	CTSBD8	CTSBD16
1.00	1.33	1.67	2.00	2.67	3.33	6.00

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

CTSB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	$0.053 + 0.026 \cdot \text{SL}$	$0.047 + 0.027 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_{PLH}	0.138	$0.110 + 0.014 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$	$0.116 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.144	$0.110 + 0.017 \cdot \text{SL}$	$0.116 + 0.015 \cdot \text{SL}$	$0.118 + 0.015 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

CTSBD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	$0.053 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.049 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.038 + 0.015 \cdot \text{SL}$
	t_{PLH}	0.145	$0.128 + 0.008 \cdot \text{SL}$	$0.135 + 0.007 \cdot \text{SL}$	$0.141 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.141	$0.121 + 0.010 \cdot \text{SL}$	$0.128 + 0.008 \cdot \text{SL}$	$0.134 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

CTSBD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.079	$0.062 + 0.009 \cdot \text{SL}$	$0.060 + 0.009 \cdot \text{SL}$	$0.047 + 0.009 \cdot \text{SL}$
	t_F	0.073	$0.053 + 0.010 \cdot \text{SL}$	$0.055 + 0.010 \cdot \text{SL}$	$0.044 + 0.010 \cdot \text{SL}$
	t_{PLH}	0.153	$0.141 + 0.006 \cdot \text{SL}$	$0.147 + 0.005 \cdot \text{SL}$	$0.157 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.151	$0.136 + 0.007 \cdot \text{SL}$	$0.143 + 0.006 \cdot \text{SL}$	$0.153 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/CTSBD8/CTSBD16

Clock Tree Synthesis Buffers

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

CTSBD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.051 + 0.008 \cdot \text{SL}$	$0.053 + 0.007 \cdot \text{SL}$	$0.046 + 0.007 \cdot \text{SL}$
	t_{PLH}	0.152	$0.142 + 0.005 \cdot \text{SL}$	$0.147 + 0.004 \cdot \text{SL}$	$0.160 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.147	$0.136 + 0.006 \cdot \text{SL}$	$0.141 + 0.004 \cdot \text{SL}$	$0.154 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

CTSBD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.067	$0.057 + 0.005 \cdot \text{SL}$	$0.059 + 0.005 \cdot \text{SL}$	$0.037 + 0.005 \cdot \text{SL}$
	t_F	0.059	$0.049 + 0.005 \cdot \text{SL}$	$0.051 + 0.005 \cdot \text{SL}$	$0.034 + 0.005 \cdot \text{SL}$
	t_{PLH}	0.143	$0.136 + 0.003 \cdot \text{SL}$	$0.140 + 0.002 \cdot \text{SL}$	$0.153 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.138	$0.130 + 0.004 \cdot \text{SL}$	$0.134 + 0.003 \cdot \text{SL}$	$0.147 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

CTSBD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.065	$0.058 + 0.003 \cdot \text{SL}$	$0.058 + 0.003 \cdot \text{SL}$	$0.041 + 0.004 \cdot \text{SL}$
	t_F	0.057	$0.048 + 0.004 \cdot \text{SL}$	$0.051 + 0.004 \cdot \text{SL}$	$0.038 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.141	$0.136 + 0.003 \cdot \text{SL}$	$0.140 + 0.002 \cdot \text{SL}$	$0.154 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.137	$0.131 + 0.003 \cdot \text{SL}$	$0.134 + 0.002 \cdot \text{SL}$	$0.149 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

CTSBD16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.063	$0.058 + 0.003 \cdot \text{SL}$	$0.062 + 0.002 \cdot \text{SL}$	$0.052 + 0.002 \cdot \text{SL}$
	t_F	0.054	$0.050 + 0.002 \cdot \text{SL}$	$0.050 + 0.002 \cdot \text{SL}$	$0.048 + 0.002 \cdot \text{SL}$
	t_{PLH}	0.140	$0.137 + 0.001 \cdot \text{SL}$	$0.138 + 0.001 \cdot \text{SL}$	$0.153 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.135	$0.132 + 0.002 \cdot \text{SL}$	$0.133 + 0.001 \cdot \text{SL}$	$0.148 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 85$, *Group3 : $85 < \text{SL}$

FLIP-FLOPS

Cell List

Cell Name	Function Description
FD1	D Flip-Flop
FD1D2	D Flip-Flop with 2X Drive
FD1CS	D Flip-Flop with Scan Clock
FD1CSD2	D Flip-Flop with Scan Clock, 2X Drive
FD1S	D Flip-Flop with Scan
FD1SD2	D Flip-Flop with Scan, 2X Drive
FD1SQ	D Flip-Flop with Scan, Q Output Only
FD1SQD2	D Flip-Flop with Scan, Q Output Only, 2X Drive
FD1Q	D Flip-Flop with Q Output Only
FD1QD2	D Flip-Flop with Q Output Only, 2X Drive
FD2	D Flip-Flop with Reset
FD2D2	D Flip-Flop with Reset, 2X Drive
FD2CS	D Flip-Flop with Reset, Scan Clock
FD2CSD2	D Flip-Flop with Reset, Scan Clock, 2X Drive
FD2S	D Flip-Flop with Reset, Scan
FD2SD2	D Flip-Flop with Reset, Scan, 2X Drive
FD2SQ	D Flip-Flop with Reset, Scan, Q Output Only
FD2SQD2	D Flip-Flop with Reset, Scan, Q Output Only, 2X Drive
FD2Q	D Flip-Flop with Reset, Q Output Only
FD2QD2	D Flip-Flop with Reset, Q Output Only, 2X Drive
FD3	D Flip-Flop with Set
FD3D2	D Flip-Flop with Set, 2X Drive
FD3CS	D Flip-Flop with Set, Scan Clock
FD3CSD2	D Flip-Flop with Set, Scan Clock, 2X Drive
FD3S	D Flip-Flop with Set, Scan
FD3SD2	D Flip-Flop with Set, Scan, 2X Drive
FD3SQ	D Flip-Flop with Set, Scan, Q Output Only
FD3SQD2	D Flip-Flop with Set, Scan, Q Output Only, 2X Drive
FD3Q	D Flip-Flop with Set, Q Output Only
FD3QD2	D Flip-Flop with Set, Q Output Only, 2X Drive
FD4	D Flip-Flop with Reset, Set
FD4D2	D Flip-Flop with Reset, Set, 2X Drive
FD4CS	D Flip-Flop with Reset, Set, Scan Clock
FD4CSD2	D Flip-Flop with Reset, Set, Scan Clock, 2X Drive
FD4S	D Flip-Flop with Reset, Set, Scan
FD4SD2	D Flip-Flop with Reset, Set, Scan, 2X Drive
FD4SQ	D Flip-Flop with Reset, Set, Scan, Q Output Only
FD4SQD2	D Flip-Flop with Reset, Set, Scan, Q Output Only, 2X Drive

Cell List (Cont.)

Cell Name	Function Description
FD4Q	D Flip-Flop with Reset, Set, Q Output Only
FD4QD2	D Flip-Flop with Reset, Set, Q Output Only, 2X Drive
FD5	D Flip-Flop with Negative Edge Trigger
FD5D2	D Flip-Flop with Negative Edge Trigger, 2X Drive
FD5S	D Flip-Flop with Negative Edge Trigger, Scan
FD5SD2	D Flip-Flop with Negative Edge Trigger, Scan, 2X Drive
FD6	D Flip-Flop with Negative Edge Trigger, Reset
FD6D2	D Flip-Flop with Negative Edge Trigger, Reset, 2X Drive
FD6S	D Flip-Flop with Negative Edge Trigger, Reset, Scan
FD6SD2	D Flip-Flop with Negative Edge Trigger, Reset, Scan, 2X Drive
FD7	D Flip-Flop with Negative Edge Trigger, Set
FD7D2	D Flip-Flop with Negative Edge Trigger, Set, 2X Drive
FD7S	D Flip-Flop with Negative Edge Trigger, Set, Scan
FD7SD2	D Flip-Flop with Negative Edge Trigger, Set, Scan, 2X Drive
FD8	D Flip-Flop with Negative Edge Trigger, Reset, Set
FD8D2	D Flip-Flop with Negative Edge Trigger, Reset, Set, 2X Drive
FD8S	D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan
FD8SD2	D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 2X Drive
FDS2	D Flip-Flop with Synchronous Clear
FDS2D2	D Flip-Flop with Synchronous Clear, 2X Drive
FDS2CS	D Flip-Flop with Synchronous Clear, Scan Clock
FDS2CSD2	D Flip-Flop with Synchronous Clear, Scan Clock, 2X Drive
FDS2S	D Flip-Flop with Synchronous Clear, Scan
FDS2SD2	D Flip-Flop with Synchronous Clear, Scan, 2X Drive
FDS3	D Flip-Flop with Synchronous Set
FDS3D2	D Flip-Flop with Synchronous Set, 2X Drive
FDS3CS	D Flip-Flop with Synchronous Set, Scan Clock
FDS3CSD2	D Flip-Flop with Synchronous Set, Scan Clock, 2X Drive
FDS3S	Flip-Flop with Synchronous Set, Scan
FDS3SD2	Flip-Flop with Synchronous Set, Scan, 2x Drive
FJ1	JK Flip-Flop
FJ1D2	JK Flip-Flop with 2X Drive
FJ1S	JK Flip-Flop with Scan
FJ1SD2	JK Flip-Flop with Scan, 2X Drive
FJ2	JK Flip-Flop with Reset
FJ2D2	JK Flip-Flop with Reset, 2X Drive
FJ2S	JK Flip-Flop with Reset, Scan
FJ2SD2	JK Flip-Flop with Reset, Scan, 2X Drive

FLIP-FLOPS


Cell List (Cont.)

Cell Name	Function Description
FJ4	JK Flip-Flop with Reset, Set
FJ4D2	JK Flip-Flop with Reset, Set, 2X Drive
FJ4S	JK Flip-Flop with Reset, Set, Scan
FJ4SD2	JK Flip-Flop with Reset, Set, Scan, 2X Drive
FT2	Toggle Flip-Flop with Reset
FT2D2	Toggle Flip-Flop with Reset, 2X Drive

FD1/FD1D2

D Flip-Flop with 1X/2X Drive

Logic Symbol




Truth Table

D	CK	Q (n+1)	QN (n+1)
0		0	1
1		1	0
x		Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
FD1		FD1D2		FD1	FD1D2
D	CK	D	CK		
0.6	0.7	0.7	0.7	5.00	5.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1	FD1D2
Input Setup Time (D to CK)	t_{SU}	0.180	0.177
Input Hold Time (D to CK)	t_{HD}	0.117	0.116
Pulse Width Low (CK)	t_{PWL}	0.252	0.255
Pulse Width High (CK)	t_{PWH}	0.244	0.265

FD1/FD1D2

D Flip-Flop with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.050 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.304	$0.276 + 0.014 \cdot \text{SL}$	$0.281 + 0.013 \cdot \text{SL}$	$0.285 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.303	$0.272 + 0.016 \cdot \text{SL}$	$0.279 + 0.013 \cdot \text{SL}$	$0.286 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.100	$0.046 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.044 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.354	$0.327 + 0.013 \cdot \text{SL}$	$0.331 + 0.012 \cdot \text{SL}$	$0.331 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.361	$0.332 + 0.015 \cdot \text{SL}$	$0.338 + 0.013 \cdot \text{SL}$	$0.340 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD1D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.084	$0.056 + 0.014 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.318	$0.301 + 0.009 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.307	$0.289 + 0.009 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.394	$0.377 + 0.008 \cdot \text{SL}$	$0.383 + 0.007 \cdot \text{SL}$	$0.389 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.402	$0.385 + 0.009 \cdot \text{SL}$	$0.392 + 0.007 \cdot \text{SL}$	$0.401 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD1CS/FD1CSD2

D Flip-Flop with Scan Clock, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CK	Q (n+1)	QN (n+1)
x	0	0		0	1
x	0	1		1	0
0		x	0	0	1
1		x	0	1	0
x	0	x		Q(n)	QN(n)
x		x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)								Gate Count	
FD1CS				FD1CSD2				FD1CS	FD1CSD2
D	SI	CK	SCK	D	SI	CK	SCK		
0.6	0.6	0.7	1.5	0.7	0.7	0.7	1.5	7.33	7.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1CS	FD1CSD2
Input Setup Time (D to CK)	t_{SU}	0.180	0.178
Input Hold Time (D to CK)	t_{HD}	0.118	0.117
Input Setup Time (SI to SCK)	t_{SU}	0.291	0.291
Input Hold Time (SI to SCK)	t_{HD}	0.056	0.056
Pulse Width Low (CK)	t_{PWL}	0.252	0.253
Pulse Width High (CK)	t_{PWH}	0.250	0.266
Pulse Width Low (SCK)	t_{PWL}	0.219	0.219
Pulse Width High (SCK)	t_{PWH}	0.307	0.334

FD1CS/FD1CSD2

D Flip-Flop with Scan Clock, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD1CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.309	$0.281 + 0.014 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$	$0.290 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.309	$0.278 + 0.016 \cdot \text{SL}$	$0.286 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
SCK to Q	t_R	0.127	$0.077 + 0.025 \cdot \text{SL}$	$0.072 + 0.026 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.058 + 0.023 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.051 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.396	$0.366 + 0.015 \cdot \text{SL}$	$0.375 + 0.013 \cdot \text{SL}$	$0.380 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.324	$0.293 + 0.016 \cdot \text{SL}$	$0.301 + 0.014 \cdot \text{SL}$	$0.309 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.110	$0.054 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.372	$0.343 + 0.015 \cdot \text{SL}$	$0.349 + 0.013 \cdot \text{SL}$	$0.356 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.382	$0.351 + 0.016 \cdot \text{SL}$	$0.358 + 0.014 \cdot \text{SL}$	$0.364 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.101	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.093	$0.047 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.376	$0.349 + 0.013 \cdot \text{SL}$	$0.353 + 0.012 \cdot \text{SL}$	$0.354 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.455	$0.426 + 0.015 \cdot \text{SL}$	$0.432 + 0.013 \cdot \text{SL}$	$0.435 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD1CSD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.316	$0.299 + 0.009 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$	$0.313 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.311	$0.292 + 0.009 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.313 + 0.007 \cdot \text{SL}$
SCK to Q	t_R	0.103	$0.077 + 0.013 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.406	$0.388 + 0.009 \cdot \text{SL}$	$0.397 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.327	$0.307 + 0.010 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.085	$0.056 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.410	$0.393 + 0.009 \cdot \text{SL}$	$0.399 + 0.007 \cdot \text{SL}$	$0.411 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.417	$0.398 + 0.009 \cdot \text{SL}$	$0.406 + 0.007 \cdot \text{SL}$	$0.418 + 0.007 \cdot \text{SL}$
SCK to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.415	$0.399 + 0.008 \cdot \text{SL}$	$0.405 + 0.007 \cdot \text{SL}$	$0.410 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.498	$0.480 + 0.009 \cdot \text{SL}$	$0.487 + 0.007 \cdot \text{SL}$	$0.496 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD1S/FD1SD2

D Flip-Flop with Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	Q (n+1)	QN (n+1)
0	x	0		0	1
1	x	0		1	0
x	0	1		0	1
x	1	1		1	0
x	x	x		Q(n)	QN(n)

Cell Data

Input Load (SL)								Gate Count	
FD1S				FD1SD2				FD1S	FD1SD2
D	CK	TI	TE	D	CK	TI	TE		
0.6	0.7	0.6	1.4	0.6	0.7	0.6	1.4	6.33	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1S	FD1SD2
Input Setup Time (D to CK)	t _{SU}	0.268	0.269
Input Hold Time (D to CK)	t _{HD}	0.063	0.062
Input Setup Time (TI to CK)	t _{SU}	0.314	0.315
Input Hold Time (TI to CK)	t _{HD}	0.034	0.033
Input Setup Time (TE to CK)	t _{SU}	0.312	0.314
Input Hold Time (TE to CK)	t _{HD}	0.029	0.029
Pulse Width Low (CK)	t _{PWL}	0.330	0.333
Pulse Width High (CK)	t _{PWH}	0.245	0.262

FD1S/FD1SD2

D Flip-Flop with Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD1S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.048 + 0.024 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.306	$0.278 + 0.014 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$	$0.286 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.309	$0.278 + 0.015 \cdot \text{SL}$	$0.286 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.360	$0.333 + 0.014 \cdot \text{SL}$	$0.337 + 0.012 \cdot \text{SL}$	$0.338 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.364	$0.334 + 0.015 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$	$0.343 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD1SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.083	$0.056 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.049 + 0.013 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.315	$0.298 + 0.009 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.312	$0.293 + 0.009 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.314 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.046 + 0.012 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.398	$0.382 + 0.008 \cdot \text{SL}$	$0.387 + 0.007 \cdot \text{SL}$	$0.392 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.400	$0.382 + 0.009 \cdot \text{SL}$	$0.389 + 0.007 \cdot \text{SL}$	$0.399 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD1SQ/FD1SQD2

D Flip-Flop with Scan, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	Q (n+1)
0	x	0		0
1	x	0		1
x	0	1		0
x	1	1		1
x	x	x		Q(n)

Cell Data

Input Load (SL)								Gate Count	
FD1SQ				FD1SQD2				FD1SQ	FD1SQD2
D	CK	TI	TE	D	CK	TI	TE		
0.6	0.7	0.6	1.4	0.6	0.7	0.6	1.4	5.67	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1SQ	FD1SQD2
Input Setup Time (D to CK)	t_{SU}	0.268	0.268
Input Hold Time (D to CK)	t_{HD}	0.062	0.063
Input Setup Time (TI to CK)	t_{SU}	0.310	0.314
Input Hold Time (TI to CK)	t_{HD}	0.035	0.035
Input Setup Time (TE to CK)	t_{SU}	0.310	0.312
Input Hold Time (TE to CK)	t_{HD}	0.030	0.030
Pulse Width Low (CK)	t_{PWL}	0.332	0.329
Pulse Width High (CK)	t_{PWH}	0.237	0.243

FD1SQ/FD1SQD2

D Flip-Flop with Scan, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD1SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.104	$0.050 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.040 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.043 + 0.024 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.292	$0.265 + 0.014 \cdot \text{SL}$	$0.269 + 0.013 \cdot \text{SL}$	$0.271 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.295	$0.265 + 0.015 \cdot \text{SL}$	$0.272 + 0.013 \cdot \text{SL}$	$0.275 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD1SQD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.079	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.069	$0.045 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.296	$0.279 + 0.008 \cdot \text{SL}$	$0.285 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.294	$0.277 + 0.009 \cdot \text{SL}$	$0.284 + 0.007 \cdot \text{SL}$	$0.293 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD1Q/FD1QD2

D Flip-Flop with Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	CK	Q (n+1)
0		0
1		1
x		Q (n)

Cell Data

Input Load (SL)				Gate Count	
FD1Q		FD1QD2		FD1Q	FD1QD2
D	CK	D	CK		
0.7	0.7	0.7	0.7	4.33	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1Q	FD1QD2
Input Setup Time (D to CK)	t_{SU}	0.177	0.178
Input Hold Time (D to CK)	t_{HD}	0.113	0.114
Pulse Width Low (CK)	t_{PWL}	0.253	0.251
Pulse Width High (CK)	t_{PWH}	0.234	0.243

FD1Q/FD1QD2

D Flip-Flop with Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD1Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.103	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.043 + 0.023 \cdot \text{SL}$	$0.042 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.286	$0.259 + 0.014 \cdot \text{SL}$	$0.263 + 0.013 \cdot \text{SL}$	$0.265 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.287	$0.258 + 0.015 \cdot \text{SL}$	$0.264 + 0.013 \cdot \text{SL}$	$0.267 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD1QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.077	$0.050 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.068	$0.043 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.294	$0.278 + 0.008 \cdot \text{SL}$	$0.284 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.291	$0.273 + 0.009 \cdot \text{SL}$	$0.280 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol




Truth Table

D	CK	RN	Q (n+1)	QN (n+1)
0		1	0	1
1		1	1	0
x	x	0	0	1
x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD2			FD2D2			FD2	FD2D2
D	CK	RN	D	CK	RN		
0.6	0.7	1.3	0.7	0.7	1.4	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2	FD2D2
Input Setup Time (D to CK)	t_{SU}	0.185	0.183
Input Hold Time (D to CK)	t_{HD}	0.128	0.132
Pulse Width Low (CK)	t_{PWL}	0.259	0.371
Pulse Width High (CK)	t_{PWH}	0.251	0.269
Pulse Width Low (RN)	t_{PWL}	0.250	0.289
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.526	0.522

FD2/FD2D2

D Flip-Flop with Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	$0.060 + 0.028 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.319	$0.289 + 0.015 \cdot \text{SL}$	$0.296 + 0.013 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.317	$0.287 + 0.015 \cdot \text{SL}$	$0.294 + 0.013 \cdot \text{SL}$	$0.301 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.169	$0.138 + 0.016 \cdot \text{SL}$	$0.146 + 0.013 \cdot \text{SL}$	$0.153 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.044 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.370	$0.343 + 0.013 \cdot \text{SL}$	$0.347 + 0.013 \cdot \text{SL}$	$0.348 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.377	$0.348 + 0.015 \cdot \text{SL}$	$0.355 + 0.013 \cdot \text{SL}$	$0.357 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.114	$0.056 + 0.029 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.244	$0.213 + 0.015 \cdot \text{SL}$	$0.219 + 0.014 \cdot \text{SL}$	$0.229 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD2D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.089	$0.061 + 0.014 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.326	$0.307 + 0.009 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.322	$0.303 + 0.010 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.171	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.174 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.407	$0.391 + 0.008 \cdot \text{SL}$	$0.397 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.415	$0.397 + 0.009 \cdot \text{SL}$	$0.405 + 0.007 \cdot \text{SL}$	$0.414 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.088	$0.059 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.278	$0.261 + 0.009 \cdot \text{SL}$	$0.267 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD2CS/FD2CSD2

D Flip-Flop with Reset, Scan Clock, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CK	RN	Q (n+1)	QN (n+1)
x	0	0		1	0	1
x	0	1		1	1	0
0		x	0	1	0	1
1		x	0	1	1	0
x	x	x	x	0	0	1
x		x	0	1	Q(n)	QN(n)
x	0	x		1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD2CS					FD2CSD2					FD2CS	FD2CSD2
D	SI	CK	SCK	RN	D	SI	CK	SCK	RN		
0.7	0.6	0.7	1.6	1.9	0.7	0.6	0.7	1.6	1.9	8.33	8.67

Schematic Diagram



FD2CS/FD2CSD2

D Flip-Flop with Reset, Scan Clock, 1X/2X Drive

Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2CS	FD2CSD2
Input Setup Time (D to CK)	t_{SU}	0.186	0.186
Input Hold Time (D to CK)	t_{HD}	0.132	0.131
Input Setup Time (SI to SCK)	t_{SU}	0.291	0.291
Input Hold Time (SI to SCK)	t_{HD}	0.053	0.053
Pulse Width Low (CK)	t_{PWL}	0.257	0.257
Pulse Width High (CK)	t_{PWH}	0.254	0.269
Pulse Width Low (SCK)	t_{PWL}	0.223	0.224
Pulse Width High (SCK)	t_{PWH}	0.315	0.344
Pulse Width Low (RN)	t_{PWL}	0.324	0.355
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.524	0.524
Recovery Time (RN to SCK)	t_{RC}	0.000	0.000
Removal Time (RN to SCK)	t_{RM}	0.493	0.491

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	$0.062 + 0.027 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.052 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.320	$0.290 + 0.015 \cdot \text{SL}$	$0.298 + 0.013 \cdot \text{SL}$	$0.305 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.319	$0.288 + 0.016 \cdot \text{SL}$	$0.297 + 0.013 \cdot \text{SL}$	$0.304 + 0.012 \cdot \text{SL}$
SCK to Q	t_R	0.132	$0.079 + 0.026 \cdot \text{SL}$	$0.078 + 0.026 \cdot \text{SL}$	$0.069 + 0.027 \cdot \text{SL}$
	t_F	0.103	$0.058 + 0.023 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.411	$0.379 + 0.016 \cdot \text{SL}$	$0.389 + 0.013 \cdot \text{SL}$	$0.398 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.342	$0.311 + 0.016 \cdot \text{SL}$	$0.320 + 0.013 \cdot \text{SL}$	$0.329 + 0.012 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.053 + 0.024 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.172	$0.140 + 0.016 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.156 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.111	$0.055 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.048 + 0.024 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.385	$0.354 + 0.015 \cdot \text{SL}$	$0.361 + 0.013 \cdot \text{SL}$	$0.369 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.394	$0.363 + 0.016 \cdot \text{SL}$	$0.370 + 0.014 \cdot \text{SL}$	$0.376 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.092	$0.045 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.395	$0.368 + 0.014 \cdot \text{SL}$	$0.372 + 0.012 \cdot \text{SL}$	$0.373 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.468	$0.439 + 0.015 \cdot \text{SL}$	$0.445 + 0.013 \cdot \text{SL}$	$0.448 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.114	$0.056 + 0.029 \cdot \text{SL}$	$0.054 + 0.030 \cdot \text{SL}$	$0.063 + 0.029 \cdot \text{SL}$
	t_{PLH}	0.242	$0.211 + 0.015 \cdot \text{SL}$	$0.216 + 0.014 \cdot \text{SL}$	$0.223 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD2CS/FD2CSD2

D Flip-Flop with Reset, Scan Clock, 1X/2X Drive

Switching Characteristics


(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.090	$0.062 + 0.014 \cdot \text{SL}$	$0.063 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.324	$0.306 + 0.009 \cdot \text{SL}$	$0.314 + 0.007 \cdot \text{SL}$	$0.326 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.319	$0.301 + 0.009 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$	$0.322 + 0.006 \cdot \text{SL}$
SCK to Q	t_R	0.108	$0.080 + 0.014 \cdot \text{SL}$	$0.083 + 0.013 \cdot \text{SL}$	$0.072 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.061 + 0.012 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.421	$0.402 + 0.010 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.426 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.346	$0.326 + 0.010 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.350 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.170	$0.151 + 0.010 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$	$0.174 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.086	$0.057 + 0.014 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.419	$0.402 + 0.009 \cdot \text{SL}$	$0.408 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.428	$0.409 + 0.009 \cdot \text{SL}$	$0.417 + 0.007 \cdot \text{SL}$	$0.429 + 0.007 \cdot \text{SL}$
SCK to QN	t_R	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.011 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.434	$0.418 + 0.008 \cdot \text{SL}$	$0.424 + 0.007 \cdot \text{SL}$	$0.429 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.512	$0.494 + 0.009 \cdot \text{SL}$	$0.501 + 0.007 \cdot \text{SL}$	$0.511 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.089	$0.060 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.276	$0.258 + 0.009 \cdot \text{SL}$	$0.264 + 0.007 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol




Truth Table

D	TI	TE	CK	RN	Q (n+1)	QN (n+1)
0	x	0		1	0	1
1	x	0		1	1	0
x	0	1		1	0	1
x	1	1		1	1	0
x	x	x	x	0	0	1
x	x	x		1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD2S					FD2SD2					FD2S	FD2SD2
D	CK	RN	TI	TE	D	CK	RN	TI	TE		
0.6	0.7	1.3	0.6	1.4	0.6	0.7	1.4	0.6	1.4	7.00	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2S	FD2SD2
Input Setup Time (D to CK)	t_{SU}	0.286	0.283
Input Hold Time (D to CK)	t_{HD}	0.081	0.087
Input Setup Time (TI to CK)	t_{SU}	0.330	0.333
Input Hold Time (TI to CK)	t_{HD}	0.052	0.057
Input Setup Time (TE to CK)	t_{SU}	0.322	0.321
Input Hold Time (TE to CK)	t_{HD}	0.053	0.058
Pulse Width Low (CK)	t_{PWL}	0.353	0.342
Pulse Width High (CK)	t_{PWH}	0.254	0.271
Pulse Width Low (RN)	t_{PWL}	0.250	0.290
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.532	0.524

FD2S/FD2SD2

D Flip-Flop with Reset, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.052 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.324	$0.294 + 0.015 \cdot \text{SL}$	$0.301 + 0.013 \cdot \text{SL}$	$0.308 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.323	$0.292 + 0.015 \cdot \text{SL}$	$0.300 + 0.013 \cdot \text{SL}$	$0.307 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.169	$0.138 + 0.016 \cdot \text{SL}$	$0.146 + 0.013 \cdot \text{SL}$	$0.153 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.376	$0.349 + 0.014 \cdot \text{SL}$	$0.353 + 0.012 \cdot \text{SL}$	$0.354 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.382	$0.353 + 0.015 \cdot \text{SL}$	$0.360 + 0.013 \cdot \text{SL}$	$0.363 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.114	$0.056 + 0.029 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.244	$0.213 + 0.015 \cdot \text{SL}$	$0.219 + 0.014 \cdot \text{SL}$	$0.229 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD2SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.090	$0.063 + 0.014 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.330	$0.312 + 0.009 \cdot \text{SL}$	$0.319 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.327	$0.307 + 0.010 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.329 + 0.007 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.171	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.174 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.049 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.413	$0.397 + 0.008 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.420	$0.402 + 0.009 \cdot \text{SL}$	$0.409 + 0.007 \cdot \text{SL}$	$0.419 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.088	$0.060 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.280	$0.262 + 0.009 \cdot \text{SL}$	$0.268 + 0.007 \cdot \text{SL}$	$0.281 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD2SQ/FD2SQD2

D Flip-Flop with Reset, Scan, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	RN	Q (n+1)
0	x	0		1	0
1	x	0		1	1
x	0	1		1	0
x	1	1		1	1
x	x	x	x	0	0
x	x	x		1	Q(n)

Cell Data

Input Load (SL)										Gate Count	
FD2SQ					FD2SQD2					FD2SQ	FD2SQD2
D	CK	RN	TI	TE	D	CK	RN	TI	TE		
0.6	0.7	1.4	0.6	1.4	0.6	0.7	1.4	0.6	1.4	6.33	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2SQ	FD2SQD2
Input Setup Time (D to CK)	t_{SU}	0.284	0.281
Input Hold Time (D to CK)	t_{HD}	0.084	0.084
Input Setup Time (TI to CK)	t_{SU}	0.335	0.333
Input Hold Time (TI to CK)	t_{HD}	0.055	0.056
Input Setup Time (TE to CK)	t_{SU}	0.324	0.323
Input Hold Time (TE to CK)	t_{HD}	0.054	0.054
Pulse Width Low (CK)	t_{PWL}	0.344	0.342
Pulse Width High (CK)	t_{PWH}	0.247	0.255
Pulse Width Low (RN)	t_{PWL}	0.254	0.266
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.527	0.526

FD2SQ/FD2SQD2

D Flip-Flop with Reset, Scan, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.110	$0.057 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$
	t_F	0.093	$0.045 + 0.024 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$	$0.040 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.312	$0.283 + 0.014 \cdot \text{SL}$	$0.289 + 0.013 \cdot \text{SL}$	$0.293 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.311	$0.281 + 0.015 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.157	$0.126 + 0.015 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$	$0.137 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD2SQD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.084	$0.057 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.319	$0.302 + 0.009 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.314	$0.296 + 0.009 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.315 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.157	$0.138 + 0.009 \cdot \text{SL}$	$0.147 + 0.007 \cdot \text{SL}$	$0.158 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD2Q/FD2QD2

D Flip-Flop with Reset, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	CK	RN	Q (n+1)
0		1	0
1		1	1
x	x	0	0
x		x	Q (n)

Cell Data

Input Load (SL)						Gate Count	
FD2Q			FD2QD2			FD2Q	FD2QD2
D	CK	RN	D	CK	RN		
0.7	0.7	1.4	0.7	0.7	1.4	4.67	5.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2Q	FD2QD2
Input Setup Time (D to CK)	t_{SU}	0.184	0.281
Input Hold Time (D to CK)	t_{HD}	0.132	0.084
Pulse Width Low (CK)	t_{PWL}	0.260	0.342
Pulse Width High (CK)	t_{PWH}	0.245	0.255
Pulse Width Low (RN)	t_{PWL}	0.256	0.266
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.516	0.526

FD2Q/FD2QD2

D Flip-Flop with Reset, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD2Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.045 + 0.024 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.307	$0.279 + 0.014 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.289 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.309	$0.279 + 0.015 \cdot \text{SL}$	$0.286 + 0.013 \cdot \text{SL}$	$0.289 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.157	$0.127 + 0.015 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$	$0.138 + 0.013 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD2QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.056 + 0.014 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.009 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.307	$0.289 + 0.009 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.158	$0.140 + 0.009 \cdot \text{SL}$	$0.148 + 0.007 \cdot \text{SL}$	$0.160 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol




Truth Table

D	CK	SN	Q (n+1)	QN (n+1)
0		1	0	1
1		1	1	0
x	x	0	1	0
x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD3			FD3D2			FD3	FD3D2
D	CK	SN	D	CK	SN		
0.7	0.7	1.7	0.7	0.7	1.7	5.67	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3	FD3D2
Input Setup Time (D to CK)	t_{SU}	0.178	0.178
Input Hold Time (D to CK)	t_{HD}	0.111	0.111
Pulse Width Low (CK)	t_{PWL}	0.274	0.274
Pulse Width High (CK)	t_{PWH}	0.254	0.272
Pulse Width Low (SN)	t_{PWL}	0.285	0.322
Recovery Time (SN to CK)	t_{RC}	0.004	0.004
Removal Time (SN to CK)	t_{RM}	0.227	0.227

FD3/FD3D2

D Flip-Flop with Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.110	$0.057 + 0.026 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.024 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.314	$0.285 + 0.014 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$	$0.294 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.327	$0.295 + 0.016 \cdot \text{SL}$	$0.303 + 0.014 \cdot \text{SL}$	$0.311 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.120	$0.069 + 0.025 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.365	$0.336 + 0.015 \cdot \text{SL}$	$0.343 + 0.013 \cdot \text{SL}$	$0.347 + 0.012 \cdot \text{SL}$
CK to QN	t_R	0.108	$0.054 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.044 + 0.024 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.395	$0.366 + 0.015 \cdot \text{SL}$	$0.373 + 0.013 \cdot \text{SL}$	$0.377 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.384	$0.354 + 0.015 \cdot \text{SL}$	$0.361 + 0.013 \cdot \text{SL}$	$0.365 + 0.013 \cdot \text{SL}$
SN to QN	t_F	0.105	$0.056 + 0.025 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$	$0.058 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.178	$0.145 + 0.016 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.163 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD3D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.321	$0.303 + 0.009 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.327	$0.308 + 0.010 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$	$0.329 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.098	$0.074 + 0.012 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.405	$0.387 + 0.009 \cdot \text{SL}$	$0.395 + 0.007 \cdot \text{SL}$	$0.406 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.084	$0.056 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.428	$0.410 + 0.009 \cdot \text{SL}$	$0.417 + 0.007 \cdot \text{SL}$	$0.428 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.419	$0.401 + 0.009 \cdot \text{SL}$	$0.408 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.178	$0.158 + 0.010 \cdot \text{SL}$	$0.167 + 0.008 \cdot \text{SL}$	$0.182 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD3CS/FD3CSD2

D Flip-Flop with Set, Scan Clock, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CK	SN	Q (n+1)	QN (n+1)
x	0	0		1	0	1
x	0	1		1	1	0
0		x	0	1	0	1
1		x	0	1	1	0
x	x	x	x	0	1	0
x	0	x		1	Q(n)	QN(n)
x		x	0	1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD3CS					FD3CSD2					FD3CS	FD3CSD2
D	SI	CK	SCK	SN	D	SI	CK	SCK	SN		
0.7	0.7	0.7	1.6	2.6	0.7	0.7	0.7	1.5	2.6	8.33	8.67

Schematic Diagram



FD3CS/FD3CSD2

D Flip-Flop with Set, Scan Clock, 1X/2X Drive

Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3CS	FD3CSD2
Input Setup Time (D to CK)	t_{SU}	0.179	0.179
Input Hold Time (D to CK)	t_{HD}	0.111	0.111
Input Setup Time (SI to SCK)	t_{SU}	0.301	0.301
Input Hold Time (SI to SCK)	t_{HD}	0.060	0.060
Pulse Width Low (CK)	t_{PWL}	0.275	0.273
Pulse Width High (CK)	t_{PWH}	0.260	0.279
Pulse Width Low (SCK)	t_{PWL}	0.245	0.245
Pulse Width High (SCK)	t_{PWH}	0.325	0.361
Pulse Width Low (SN)	t_{PWL}	0.411	0.454
Recovery Time (SN to CK)	t_{RC}	0.003	0.001
Removal Time (SN to CK)	t_{RM}	0.227	0.229
Recovery Time (SN to SCK)	t_{RC}	0.130	0.130
Removal Time (SN to SCK)	t_{RM}	0.098	0.099

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.111	$0.059 + 0.026 \cdot \text{SL}$	$0.055 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.318	$0.290 + 0.014 \cdot \text{SL}$	$0.296 + 0.013 \cdot \text{SL}$	$0.299 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.329	$0.298 + 0.015 \cdot \text{SL}$	$0.306 + 0.013 \cdot \text{SL}$	$0.313 + 0.013 \cdot \text{SL}$
SCK to Q	t_R	0.128	$0.077 + 0.026 \cdot \text{SL}$	$0.074 + 0.026 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.058 + 0.023 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.410	$0.380 + 0.015 \cdot \text{SL}$	$0.388 + 0.013 \cdot \text{SL}$	$0.394 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.361	$0.329 + 0.016 \cdot \text{SL}$	$0.337 + 0.014 \cdot \text{SL}$	$0.346 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.141	$0.091 + 0.025 \cdot \text{SL}$	$0.087 + 0.026 \cdot \text{SL}$	$0.077 + 0.027 \cdot \text{SL}$
	t_{PLH}	0.549	$0.517 + 0.016 \cdot \text{SL}$	$0.527 + 0.013 \cdot \text{SL}$	$0.535 + 0.012 \cdot \text{SL}$
CK to QN	t_R	0.123	$0.067 + 0.028 \cdot \text{SL}$	$0.069 + 0.027 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.055 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.417	$0.385 + 0.016 \cdot \text{SL}$	$0.394 + 0.014 \cdot \text{SL}$	$0.406 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.408	$0.376 + 0.016 \cdot \text{SL}$	$0.385 + 0.014 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.111	$0.058 + 0.027 \cdot \text{SL}$	$0.056 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.050 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.436	$0.407 + 0.015 \cdot \text{SL}$	$0.414 + 0.013 \cdot \text{SL}$	$0.418 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.488	$0.458 + 0.015 \cdot \text{SL}$	$0.465 + 0.013 \cdot \text{SL}$	$0.470 + 0.013 \cdot \text{SL}$
SN to QN	t_F	0.109	$0.059 + 0.025 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.063 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.185	$0.152 + 0.017 \cdot \text{SL}$	$0.160 + 0.014 \cdot \text{SL}$	$0.169 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD3CS/FD3CSD2

D Flip-Flop with Set, Scan Clock, 1X/2X Drive

Switching Characteristics


(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.087	$0.060 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.054 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.327	$0.309 + 0.009 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$	$0.326 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.330	$0.311 + 0.010 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.333 + 0.006 \cdot \text{SL}$
SCK to Q	t_R	0.108	$0.082 + 0.013 \cdot \text{SL}$	$0.081 + 0.013 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.062 + 0.012 \cdot \text{SL}$	$0.065 + 0.011 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.430	$0.411 + 0.010 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.433 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.363	$0.343 + 0.010 \cdot \text{SL}$	$0.353 + 0.007 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.126	$0.101 + 0.013 \cdot \text{SL}$	$0.101 + 0.013 \cdot \text{SL}$	$0.089 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.601	$0.579 + 0.011 \cdot \text{SL}$	$0.591 + 0.007 \cdot \text{SL}$	$0.609 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.094	$0.065 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.448	$0.429 + 0.010 \cdot \text{SL}$	$0.437 + 0.008 \cdot \text{SL}$	$0.454 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.441	$0.422 + 0.010 \cdot \text{SL}$	$0.430 + 0.007 \cdot \text{SL}$	$0.444 + 0.007 \cdot \text{SL}$
SCK to QN	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.468	$0.451 + 0.009 \cdot \text{SL}$	$0.458 + 0.007 \cdot \text{SL}$	$0.468 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.534	$0.516 + 0.009 \cdot \text{SL}$	$0.523 + 0.007 \cdot \text{SL}$	$0.535 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.181	$0.160 + 0.010 \cdot \text{SL}$	$0.170 + 0.008 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol




Truth Table

D	TI	TE	CK	SN	Q (n+1)	QN (n+1)
0	x	0		1	0	1
1	x	0		1	1	0
x	0	1		1	0	1
x	1	1		1	1	0
x	x	x	x	0	1	0
x	x	x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD3S					FD3SD2					FD3S	FD3SD2
D	CK	SN	TI	TE	D	CK	SN	TI	TE		
0.6	0.7	1.7	0.7	1.4	0.6	0.7	1.7	0.7	1.4	7.33	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3S	FD3SD2
Input Setup Time (D to CK)	t_{SU}	0.310	0.311
Input Hold Time (D to CK)	t_{HD}	0.051	0.051
Pulse Width Low (CK)	t_{PWL}	0.369	0.371
Pulse Width High (CK)	t_{PWH}	0.257	0.278
Pulse Width Low (SN)	t_{PWL}	0.285	0.327
Recovery Time (SN to CK)	t_{RC}	0.001	0.003
Removal Time (SN to CK)	t_{RM}	0.230	0.228
Input Setup Time (TI to CK)	t_{SU}	0.312	0.312
Input Hold Time (TI to CK)	t_{HD}	0.024	0.022
Input Setup Time (TE to CK)	t_{SU}	0.327	0.328
Input Hold Time (TE to CK)	t_{HD}	0.013	0.013

FD3S/FD3SD2

D Flip-Flop with Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.051 + 0.024 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.318	$0.289 + 0.014 \cdot \text{SL}$	$0.295 + 0.013 \cdot \text{SL}$	$0.298 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.328	$0.298 + 0.015 \cdot \text{SL}$	$0.305 + 0.013 \cdot \text{SL}$	$0.313 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.119	$0.069 + 0.025 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.364	$0.335 + 0.015 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.346 + 0.012 \cdot \text{SL}$
CK to QN	t_R	0.108	$0.054 + 0.027 \cdot \text{SL}$	$0.052 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.046 + 0.023 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.398	$0.369 + 0.014 \cdot \text{SL}$	$0.376 + 0.013 \cdot \text{SL}$	$0.379 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.389	$0.359 + 0.015 \cdot \text{SL}$	$0.367 + 0.013 \cdot \text{SL}$	$0.371 + 0.012 \cdot \text{SL}$
SN to QN	t_F	0.104	$0.056 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.177	$0.145 + 0.016 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.163 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$


FD3SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.055 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.331	$0.313 + 0.009 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.329 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.337	$0.318 + 0.010 \cdot \text{SL}$	$0.326 + 0.007 \cdot \text{SL}$	$0.339 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.099	$0.074 + 0.012 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.408	$0.390 + 0.009 \cdot \text{SL}$	$0.399 + 0.007 \cdot \text{SL}$	$0.410 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.083	$0.054 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.438	$0.421 + 0.009 \cdot \text{SL}$	$0.428 + 0.007 \cdot \text{SL}$	$0.438 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.431	$0.412 + 0.009 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.432 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.176	$0.156 + 0.010 \cdot \text{SL}$	$0.165 + 0.008 \cdot \text{SL}$	$0.180 + 0.007 \cdot \text{SL}$






*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Set, Scan, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	SN	Q (n+1)
0	x	0		1	0
1	x	0		1	1
x	0	1		1	0
x	1	1		1	1
x	x	x	x	0	1
x	x	x		1	Q (n)

Cell Data

Input Load (SL)										Gate Count	
<i>FD3SQ</i>					<i>FD3SQD2</i>					<i>FD3SQ</i>	<i>FD3SQD2</i>
D	CK	SN	TI	TE	D	CK	SN	TI	TE		
0.6	0.7	1.1	0.7	1.4	0.6	0.7	1.0	0.7	1.4	6.33	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3SQ	FD3SQD2
Input Setup Time (D to CK)	t_{SU}	0.313	0.310
Input Hold Time (D to CK)	t_{HD}	0.049	0.051
Pulse Width Low (CK)	t_{PWL}	0.375	0.370
Pulse Width High (CK)	t_{PWH}	0.241	0.252
Pulse Width Low (SN)	t_{PWL}	0.683	0.731
Recovery Time (SN to CK)	t_{RC}	0.000	0.001
Removal Time (SN to CK)	t_{RM}	0.231	0.230
Input Setup Time (TI to CK)	t_{SU}	0.316	0.313
Input Hold Time (TI to CK)	t_{HD}	0.021	0.025
Input Setup Time (TE to CK)	t_{SU}	0.327	0.327
Input Hold Time (TE to CK)	t_{HD}	0.010	0.015

FD3SQ/FD3SQD2

D Flip-Flop with Set, Scan, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.104	$0.051 + 0.026 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.093	$0.047 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.299	$0.271 + 0.014 \cdot \text{SL}$	$0.276 + 0.013 \cdot \text{SL}$	$0.277 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.311	$0.281 + 0.015 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.134	$0.083 + 0.025 \cdot \text{SL}$	$0.080 + 0.026 \cdot \text{SL}$	$0.065 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.718	$0.687 + 0.015 \cdot \text{SL}$	$0.696 + 0.013 \cdot \text{SL}$	$0.702 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD3SQD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.079	$0.054 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.310	$0.293 + 0.008 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$	$0.305 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.319	$0.301 + 0.009 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.115	$0.091 + 0.012 \cdot \text{SL}$	$0.090 + 0.013 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.762	$0.743 + 0.010 \cdot \text{SL}$	$0.753 + 0.007 \cdot \text{SL}$	$0.765 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD3Q/FD3QD2

D Flip-Flop with Set, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	CK	SN	Q (n+1)
0		1	0
1		1	1
x	x	0	1
x		x	Q (n)

Cell Data

Input Load (SL)						Gate Count	
FD3Q			FD3QD2			FD3Q	FD3QD2
D	CK	SN	D	CK	SN		
0.7	0.7	1.0	0.7	0.7	1.0	5.00	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25°2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3Q	FD3QD2
Input Setup Time (D to CK)	t_{SU}	0.180	0.179
Input Hold Time (D to CK)	t_{HD}	0.110	0.110
Pulse Width Low (CK)	t_{PWL}	0.273	0.273
Pulse Width High (CK)	t_{PWH}	0.237	0.246
Pulse Width Low (SN)	t_{PWL}	0.678	0.708
Recovery Time (SN to CK)	t_{RC}	0.003	0.003
Removal Time (SN to CK)	t_{RM}	0.227	0.227

FD3Q/FD3QD2

D Flip-Flop with Set, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD3Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.104	$0.051 + 0.026 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.092	$0.046 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.293	$0.265 + 0.014 \cdot \text{SL}$	$0.270 + 0.013 \cdot \text{SL}$	$0.271 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.303	$0.273 + 0.015 \cdot \text{SL}$	$0.280 + 0.013 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.133	$0.083 + 0.025 \cdot \text{SL}$	$0.078 + 0.026 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.705	$0.674 + 0.016 \cdot \text{SL}$	$0.684 + 0.013 \cdot \text{SL}$	$0.690 + 0.012 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD3QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.301	$0.285 + 0.008 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.309	$0.291 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.308 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.113	$0.088 + 0.013 \cdot \text{SL}$	$0.088 + 0.013 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.727	$0.707 + 0.010 \cdot \text{SL}$	$0.719 + 0.007 \cdot \text{SL}$	$0.732 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol




Truth Table

D	CK	RN	SN	Q (n+1)	QN (n+1)
0		1	1	0	1
1		1	1	1	0
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	0	0
x		1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD4				FD4D2				FD4	FD4D2
D	CK	RN	SN	D	CK	RN	SN		
0.7	0.7	1.4	1.7	0.7	0.7	1.4	1.7	6.00	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4	FD4D2
Input Setup Time (D to CK)	t_{SU}	0.183	0.183
Input Hold Time (D to CK)	t_{HD}	0.125	0.125
Pulse Width Low (CK)	t_{PWL}	0.271	0.271
Pulse Width High (CK)	t_{PWH}	0.266	0.283
Pulse Width Low (RN)	t_{PWL}	0.268	0.304
Pulse Width Low (SN)	t_{PWL}	0.299	0.332
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.558	0.558
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.263	0.263
Removal Time (SN to RN)	t_{RM}	0.137	0.136
Recovery Time (SN to RN)	t_{RC}	0.083	0.084

FD4/FD4D2

D Flip-Flop with Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.063 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.056 + 0.024 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.052 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.334	$0.304 + 0.015 \cdot \text{SL}$	$0.312 + 0.013 \cdot \text{SL}$	$0.318 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.350	$0.318 + 0.016 \cdot \text{SL}$	$0.326 + 0.014 \cdot \text{SL}$	$0.335 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.115	$0.060 + 0.027 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.057 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$	$0.052 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.147	$0.117 + 0.015 \cdot \text{SL}$	$0.125 + 0.013 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.174	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.126	$0.074 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.387	$0.356 + 0.016 \cdot \text{SL}$	$0.364 + 0.013 \cdot \text{SL}$	$0.371 + 0.012 \cdot \text{SL}$
CK to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.094	$0.046 + 0.024 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.419	$0.390 + 0.015 \cdot \text{SL}$	$0.397 + 0.013 \cdot \text{SL}$	$0.401 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.409	$0.378 + 0.015 \cdot \text{SL}$	$0.386 + 0.013 \cdot \text{SL}$	$0.390 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.123	$0.064 + 0.029 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$	$0.072 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.267	$0.234 + 0.017 \cdot \text{SL}$	$0.242 + 0.015 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.121	$0.063 + 0.029 \cdot \text{SL}$	$0.066 + 0.028 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.056 + 0.025 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.060 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.152	$0.119 + 0.016 \cdot \text{SL}$	$0.127 + 0.014 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.182	$0.148 + 0.017 \cdot \text{SL}$	$0.157 + 0.014 \cdot \text{SL}$	$0.167 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.092	$0.064 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.059 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.339	$0.321 + 0.009 \cdot \text{SL}$	$0.328 + 0.007 \cdot \text{SL}$	$0.341 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.352	$0.333 + 0.010 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$	$0.355 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.089	$0.062 + 0.013 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.151	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.153 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.076 + 0.013 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.423	$0.404 + 0.009 \cdot \text{SL}$	$0.413 + 0.007 \cdot \text{SL}$	$0.427 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.086	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.455	$0.438 + 0.009 \cdot \text{SL}$	$0.445 + 0.007 \cdot \text{SL}$	$0.456 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.443	$0.425 + 0.009 \cdot \text{SL}$	$0.433 + 0.007 \cdot \text{SL}$	$0.445 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.097	$0.069 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.299	$0.279 + 0.010 \cdot \text{SL}$	$0.287 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.093	$0.063 + 0.015 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.154	$0.135 + 0.010 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.181	$0.160 + 0.010 \cdot \text{SL}$	$0.170 + 0.008 \cdot \text{SL}$	$0.186 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD4CS/FD4CSD2

D Flip-Flop with Reset, Set, Scan Clock, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CK	RN	SN	Q (n+1)	QN (n+1)
x	0	0		1	1	0	1
x	0	1		1	1	1	0
0		x	0	1	1	0	1
1		x	0	1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	0	x		1	1	Q(n)	QN(n)
x		x	0	1	1	Q(n)	QN(n)

Cell Data

Input Load (SL)												Gate Count	
FD4CS						FD4CSD2						FD4CS	FD4CSD2
D	SI	CK	SCK	SN	RN	D	SI	CK	SCK	SN	RN		
0.6	0.7	0.7	1.4	2.7	1.8	0.7	0.7	0.7	1.5	2.7	1.8	9.33	9.67

Schematic Diagram



FD4CS/FD4CSD2**D Flip-Flop with Reset, Set, Scan Clock, 1X/2X Drive****Timing Requirements**

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4CS	FD4CSD2
Input Setup Time (D to CK)	t_{SU}	0.185	0.185
Input Hold Time (D to CK)	t_{HD}	0.122	0.123
Input Setup Time (SI to SCK)	t_{SU}	0.301	0.300
Input Hold Time (SI to SCK)	t_{HD}	0.057	0.057
Pulse Width Low (CK)	t_{PWL}	0.270	0.270
Pulse Width High (CK)	t_{PWH}	0.267	0.285
Pulse Width Low (SCK)	t_{PWL}	0.242	0.242
Pulse Width High (SCK)	t_{PWH}	0.333	0.363
Pulse Width Low (SN)	t_{PWL}	0.420	0.451
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.260	0.260
Recovery Time (SN to SCK)	t_{RC}	0.116	0.116
Removal Time (SN to SCK)	t_{RM}	0.129	0.129
Pulse Width Low (RN)	t_{PWL}	0.341	0.371
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.553	0.553
Recovery Time (RN to SCK)	t_{RC}	0.000	0.000
Removal Time (RN to SCK)	t_{RM}	0.549	0.549
Removal Time (SN to RN)	t_{RM}	0.136	0.135
Recovery Time (SN to RN)	t_{RC}	0.084	0.085

FD4CS/FD4CSD2

D Flip-Flop with Reset, Set, Scan Clock, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.056 + 0.023 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.335	$0.304 + 0.015 \cdot \text{SL}$	$0.312 + 0.013 \cdot \text{SL}$	$0.319 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.344	$0.312 + 0.016 \cdot \text{SL}$	$0.321 + 0.013 \cdot \text{SL}$	$0.329 + 0.013 \cdot \text{SL}$
SCK to Q	t_R	0.134	$0.081 + 0.026 \cdot \text{SL}$	$0.079 + 0.027 \cdot \text{SL}$	$0.070 + 0.028 \cdot \text{SL}$
	t_F	0.108	$0.061 + 0.023 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.424	$0.392 + 0.016 \cdot \text{SL}$	$0.401 + 0.014 \cdot \text{SL}$	$0.411 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.383	$0.352 + 0.016 \cdot \text{SL}$	$0.360 + 0.014 \cdot \text{SL}$	$0.371 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.146	$0.093 + 0.027 \cdot \text{SL}$	$0.093 + 0.027 \cdot \text{SL}$	$0.085 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.555	$0.521 + 0.017 \cdot \text{SL}$	$0.532 + 0.014 \cdot \text{SL}$	$0.542 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.114	$0.059 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.056 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.148	$0.118 + 0.015 \cdot \text{SL}$	$0.126 + 0.013 \cdot \text{SL}$	$0.131 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.173	$0.141 + 0.016 \cdot \text{SL}$	$0.150 + 0.013 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.120	$0.063 + 0.029 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$	$0.063 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.055 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.429	$0.396 + 0.016 \cdot \text{SL}$	$0.405 + 0.014 \cdot \text{SL}$	$0.417 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.426	$0.394 + 0.016 \cdot \text{SL}$	$0.403 + 0.014 \cdot \text{SL}$	$0.410 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.111	$0.057 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.053 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.456	$0.427 + 0.015 \cdot \text{SL}$	$0.434 + 0.013 \cdot \text{SL}$	$0.438 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.502	$0.471 + 0.015 \cdot \text{SL}$	$0.479 + 0.013 \cdot \text{SL}$	$0.484 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.123	$0.064 + 0.030 \cdot \text{SL}$	$0.064 + 0.030 \cdot \text{SL}$	$0.072 + 0.029 \cdot \text{SL}$
	t_F	0.109	$0.058 + 0.025 \cdot \text{SL}$	$0.061 + 0.025 \cdot \text{SL}$	$0.062 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.153	$0.120 + 0.016 \cdot \text{SL}$	$0.127 + 0.015 \cdot \text{SL}$	$0.136 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.185	$0.151 + 0.017 \cdot \text{SL}$	$0.160 + 0.015 \cdot \text{SL}$	$0.169 + 0.014 \cdot \text{SL}$
RN to QN	t_R	0.124	$0.065 + 0.030 \cdot \text{SL}$	$0.064 + 0.030 \cdot \text{SL}$	$0.075 + 0.029 \cdot \text{SL}$
	t_{PLH}	0.264	$0.230 + 0.017 \cdot \text{SL}$	$0.237 + 0.015 \cdot \text{SL}$	$0.247 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Flip-Flop with Reset, Set, Scan Clock, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4CSD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.092	$0.065 + 0.014 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.011 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.322 + 0.009 \cdot \text{SL}$	$0.330 + 0.007 \cdot \text{SL}$	$0.343 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.347	$0.328 + 0.010 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$	$0.351 + 0.006 \cdot \text{SL}$
SCK to Q	t_R	0.111	$0.085 + 0.013 \cdot \text{SL}$	$0.084 + 0.013 \cdot \text{SL}$	$0.077 + 0.014 \cdot \text{SL}$
	t_F	0.088	$0.065 + 0.012 \cdot \text{SL}$	$0.066 + 0.011 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.436	$0.416 + 0.010 \cdot \text{SL}$	$0.425 + 0.007 \cdot \text{SL}$	$0.440 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.390	$0.370 + 0.010 \cdot \text{SL}$	$0.379 + 0.007 \cdot \text{SL}$	$0.394 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.127	$0.102 + 0.013 \cdot \text{SL}$	$0.100 + 0.013 \cdot \text{SL}$	$0.094 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.596	$0.575 + 0.010 \cdot \text{SL}$	$0.586 + 0.008 \cdot \text{SL}$	$0.603 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.089	$0.062 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.152	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.172	$0.153 + 0.010 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$	$0.175 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.095	$0.068 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.059 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.464	$0.445 + 0.010 \cdot \text{SL}$	$0.453 + 0.008 \cdot \text{SL}$	$0.469 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.460	$0.441 + 0.010 \cdot \text{SL}$	$0.450 + 0.007 \cdot \text{SL}$	$0.464 + 0.006 \cdot \text{SL}$
SCK to QN	t_R	0.087	$0.059 + 0.014 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.495	$0.478 + 0.009 \cdot \text{SL}$	$0.485 + 0.007 \cdot \text{SL}$	$0.496 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.545	$0.526 + 0.009 \cdot \text{SL}$	$0.534 + 0.007 \cdot \text{SL}$	$0.547 + 0.006 \cdot \text{SL}$
SN to QN	t_R	0.096	$0.070 + 0.013 \cdot \text{SL}$	$0.064 + 0.015 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$
	t_F	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.066 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.155	$0.135 + 0.010 \cdot \text{SL}$	$0.143 + 0.008 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.183	$0.163 + 0.010 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$	$0.187 + 0.007 \cdot \text{SL}$
RN to QN	t_R	0.098	$0.069 + 0.015 \cdot \text{SL}$	$0.069 + 0.015 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.295	$0.276 + 0.010 \cdot \text{SL}$	$0.283 + 0.008 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD4S/FD4SD2

D Flip-Flop with Reset, Set, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	RN	SN	Q (n+1)	QN (n+1)
0	x	0		1	1	0	1
1	x	0		1	1	1	0
x	0	1		1	1	0	1
x	1	1		1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	x	x		1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)												Gate Count	
FD4S						FD4SD2						FD4S	FD4SD2
D	CK	RN	SN	TI	IE	D	CK	RN	SN	TI	IE		
0.6	0.7	1.4	1.7	0.7	1.4	0.6	0.7	1.4	1.7	0.7	1.4	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4S	FD4SD2
Input Setup Time (D to CK)	t_{SU}	0.303	0.303
Input Hold Time (D to CK)	t_{HD}	0.071	0.070
Pulse Width Low (CK)	t_{PWL}	0.364	0.364
Pulse Width High (CK)	t_{PWH}	0.268	0.285
Pulse Width Low (RN)	t_{PWL}	0.268	0.304
Pulse Width Low (SN)	t_{PWL}	0.300	0.332
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.564	0.564
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.265	0.265
Input Setup Time (TI to CK)	t_{SU}	0.323	0.323
Input Hold Time (TI to CK)	t_{HD}	0.042	0.042
Input Setup Time (TE to CK)	t_{SU}	0.319	0.319
Input Hold Time (TE to CK)	t_{HD}	0.034	0.034
Recovery Time (SN to RN)	t_{RC}	0.083	0.084
Removal Time (SN to RN)	t_{RM}	0.137	0.136

FD4S/FD4SD2

D Flip-Flop with Reset, Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	$0.062 + 0.028 \cdot \text{SL}$	$0.063 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.056 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.339	$0.308 + 0.015 \cdot \text{SL}$	$0.316 + 0.013 \cdot \text{SL}$	$0.323 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.354	$0.322 + 0.016 \cdot \text{SL}$	$0.330 + 0.014 \cdot \text{SL}$	$0.339 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.114	$0.060 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.057 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$	$0.052 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.148	$0.117 + 0.015 \cdot \text{SL}$	$0.125 + 0.013 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.174	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.126	$0.074 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.387	$0.356 + 0.016 \cdot \text{SL}$	$0.365 + 0.013 \cdot \text{SL}$	$0.372 + 0.012 \cdot \text{SL}$
CK to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.048 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.423	$0.394 + 0.015 \cdot \text{SL}$	$0.401 + 0.013 \cdot \text{SL}$	$0.405 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.413	$0.383 + 0.015 \cdot \text{SL}$	$0.390 + 0.013 \cdot \text{SL}$	$0.395 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.123	$0.064 + 0.029 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$	$0.072 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.267	$0.234 + 0.017 \cdot \text{SL}$	$0.242 + 0.015 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.121	$0.063 + 0.029 \cdot \text{SL}$	$0.066 + 0.028 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.056 + 0.025 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.060 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.152	$0.119 + 0.016 \cdot \text{SL}$	$0.127 + 0.014 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.182	$0.149 + 0.017 \cdot \text{SL}$	$0.157 + 0.014 \cdot \text{SL}$	$0.167 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.092	$0.066 + 0.013 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.057 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.344	$0.325 + 0.009 \cdot \text{SL}$	$0.333 + 0.007 \cdot \text{SL}$	$0.346 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.356	$0.337 + 0.010 \cdot \text{SL}$	$0.345 + 0.007 \cdot \text{SL}$	$0.359 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.089	$0.062 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.151	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.153 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.076 + 0.014 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.423	$0.404 + 0.009 \cdot \text{SL}$	$0.413 + 0.007 \cdot \text{SL}$	$0.427 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.086	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.459	$0.442 + 0.009 \cdot \text{SL}$	$0.449 + 0.007 \cdot \text{SL}$	$0.459 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.447	$0.429 + 0.009 \cdot \text{SL}$	$0.437 + 0.007 \cdot \text{SL}$	$0.449 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.097	$0.069 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.299	$0.279 + 0.010 \cdot \text{SL}$	$0.287 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.093	$0.063 + 0.015 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.154	$0.135 + 0.010 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.180	$0.160 + 0.010 \cdot \text{SL}$	$0.170 + 0.008 \cdot \text{SL}$	$0.186 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD4SQ/FD4SQD2

D Flip-Flop with Reset, Set, Scan, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CK	RN	SN	Q (n+1)
0	x	0		1	1	0
1	x	0		1	1	1
x	0	1		1	1	0
x	1	1		1	1	1
x	x	x	x	1	0	1
x	x	x	x	0	1	0
x	x	x	x	0	0	0
x	x	x		1	1	Q (n)

Cell Data

Input Load (SL)												Gate Count	
FD4SQ						FD4SQD2						FD4SQ	FD4SQD2
D	CK	RN	SN	TI	TE	D	CK	RN	SN	TI	TE		
0.6	0.9	1.5	1.4	0.7	1.7	0.6	0.9	1.5	1.4	0.7	1.7	7.00	7.33

Schematic Diagram



FD4SQ/FD4SQD2**D Flip-Flop with Reset, Set, Scan, Q Output Only, 1X/2X Drive****Timing Requirements**

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4SQ	FD4SQD2
Input Setup Time (D to CK)	t_{SU}	0.303	0.303
Input Hold Time (D to CK)	t_{HD}	0.069	0.069
Pulse Width Low (CK)	t_{PWL}	0.362	0.362
Pulse Width High (CK)	t_{PWH}	0.247	0.255
Pulse Width Low (RN)	t_{PWL}	0.311	0.316
Pulse Width Low (SN)	t_{PWL}	0.699	0.726
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.563	0.563
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.268	0.268
Input Setup Time (TI to CK)	t_{SU}	0.323	0.323
Input Hold Time (TI to CK)	t_{HD}	0.041	0.041
Input Setup Time (TE to CK)	t_{SU}	0.319	0.319
Input Hold Time (TE to CK)	t_{HD}	0.035	0.035
Removal Time (SN to RN)	t_{RM}	0.139	0.137
Recovery Time (SN to RN)	t_{RC}	0.081	0.083

FD4SQ/FD4SQD2

D Flip-Flop with Reset, Set, Scan, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.048 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.315	$0.285 + 0.015 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$	$0.296 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.326	$0.296 + 0.015 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$	$0.308 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.052 + 0.022 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.134	$0.105 + 0.015 \cdot \text{SL}$	$0.111 + 0.013 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.157	$0.127 + 0.015 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$	$0.138 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.139	$0.087 + 0.026 \cdot \text{SL}$	$0.085 + 0.026 \cdot \text{SL}$	$0.073 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.741	$0.710 + 0.016 \cdot \text{SL}$	$0.718 + 0.013 \cdot \text{SL}$	$0.727 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD4SQD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.322	$0.304 + 0.009 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.322 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.330	$0.312 + 0.009 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.332 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.085	$0.055 + 0.015 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.139	$0.122 + 0.008 \cdot \text{SL}$	$0.128 + 0.007 \cdot \text{SL}$	$0.139 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.158	$0.139 + 0.009 \cdot \text{SL}$	$0.148 + 0.007 \cdot \text{SL}$	$0.159 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.117	$0.092 + 0.013 \cdot \text{SL}$	$0.091 + 0.013 \cdot \text{SL}$	$0.080 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.758	$0.738 + 0.010 \cdot \text{SL}$	$0.748 + 0.007 \cdot \text{SL}$	$0.763 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD4Q/FD4QD2

D Flip-Flop with Reset, Set, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	CK	RN	SN	Q (n+1)
0		1	1	0
1		1	1	1
x	x	1	0	1
x	x	0	1	0
x	x	0	0	0
x		1	1	Q (n)

Cell Data

Input Load (SL)								Gate Count	
FD4Q				FD4QD2				FD4Q	FD4QD2
D	CK	RN	SN	D	CK	RN	SN		
0.7	0.7	1.4	1.0	0.7	0.7	1.4	1.0	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4Q	FD4QD2
Input Setup Time (D to CK)	t_{SU}	0.184	0.184
Input Hold Time (D to CK)	t_{HD}	0.122	0.122
Pulse Width Low (CK)	t_{PWL}	0.270	0.270
Pulse Width High (CK)	t_{PWH}	0.244	0.252
Pulse Width Low (RN)	t_{PWL}	0.311	0.316
Pulse Width Low (SN)	t_{PWL}	0.699	0.726
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.557	0.557
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.262	0.262
Recovery Time (SN to RN)	t_{RC}	0.081	0.083
Removal Time (SN to RN)	t_{RM}	0.139	0.137

FD4Q/FD4QD2

D Flip-Flop with Reset, Set, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD4Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.110	$0.057 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.048 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.311	$0.282 + 0.015 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.292 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.321	$0.291 + 0.015 \cdot \text{SL}$	$0.299 + 0.013 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.053 + 0.022 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.134	$0.105 + 0.015 \cdot \text{SL}$	$0.111 + 0.013 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.157	$0.127 + 0.015 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$	$0.138 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.138	$0.087 + 0.025 \cdot \text{SL}$	$0.082 + 0.027 \cdot \text{SL}$	$0.074 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.735	$0.702 + 0.016 \cdot \text{SL}$	$0.713 + 0.014 \cdot \text{SL}$	$0.722 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$


FD4QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.318	$0.300 + 0.009 \cdot \text{SL}$	$0.307 + 0.007 \cdot \text{SL}$	$0.318 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.325	$0.307 + 0.009 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.085	$0.055 + 0.015 \cdot \text{SL}$	$0.061 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.139	$0.122 + 0.008 \cdot \text{SL}$	$0.128 + 0.007 \cdot \text{SL}$	$0.139 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.158	$0.139 + 0.009 \cdot \text{SL}$	$0.148 + 0.007 \cdot \text{SL}$	$0.159 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.117	$0.091 + 0.013 \cdot \text{SL}$	$0.091 + 0.013 \cdot \text{SL}$	$0.079 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.752	$0.731 + 0.010 \cdot \text{SL}$	$0.743 + 0.007 \cdot \text{SL}$	$0.758 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, 1X/2X Drive

Logic Symbol




Truth Table

D	CKN	Q (n+1)	QN (n+1)
0		0	1
1		1	0
x		Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
FD5		FD5D2		FD5	FD5D2
D	CKN	D	CKN		
0.7	0.7	0.7	0.7	5.00	5.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD5	FD5D2
Input Setup Time (D to CKN)	t_{SU}	0.196	0.191
Input Hold Time (D to CKN)	t_{HD}	0.138	0.140
Pulse Width Low (CKN)	t_{PWL}	0.227	0.245
Pulse Width High (CKN)	t_{PWH}	0.227	0.245

FD5/FD5D2

D Flip-Flop with Negative Edge Trigger, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.049 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.322	$0.294 + 0.014 \cdot \text{SL}$	$0.299 + 0.013 \cdot \text{SL}$	$0.303 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.284	$0.253 + 0.015 \cdot \text{SL}$	$0.261 + 0.013 \cdot \text{SL}$	$0.267 + 0.013 \cdot \text{SL}$
CKN to QN	t_R	0.100	$0.046 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.088	$0.041 + 0.024 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.335	$0.308 + 0.013 \cdot \text{SL}$	$0.311 + 0.012 \cdot \text{SL}$	$0.312 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.379	$0.350 + 0.015 \cdot \text{SL}$	$0.356 + 0.013 \cdot \text{SL}$	$0.358 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD5D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.048 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.335	$0.318 + 0.009 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.333 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.289	$0.270 + 0.009 \cdot \text{SL}$	$0.279 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.376	$0.360 + 0.008 \cdot \text{SL}$	$0.366 + 0.007 \cdot \text{SL}$	$0.371 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.420	$0.403 + 0.009 \cdot \text{SL}$	$0.410 + 0.007 \cdot \text{SL}$	$0.419 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$






FD5S/FD5SD2

D Flip-Flop with Negative Edge Trigger, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CKN	Q (n+1)	QN (n+1)
0	x	0		0	1
1	x	0		1	0
x	0	1		0	1
x	1	1		1	0
x	x	x		Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD5S				FD5SD2				FD5S	FD5SD2
D	CKN	TI	TE	D	CKN	TI	TE		
0.6	0.7	0.6	1.4	0.6	0.7	0.6	1.4	6.33	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD5S	FD5SD2
Input Setup Time (D to CKN)	t _{SU}	0.349	0.347
Input Hold Time (D to CKN)	t _{HD}	0.091	0.091
Pulse Width Low (CKN)	t _{PWL}	0.231	0.244
Pulse Width High (CKN)	t _{PWH}	0.231	0.244
Input Setup Time (TI to CKN)	t _{SU}	0.334	0.333
Input Hold Time (TI to CKN)	t _{HD}	0.083	0.082
Input Setup Time (TE to CKN)	t _{SU}	0.352	0.352
Input Hold Time (TE to CKN)	t _{HD}	0.107	0.109

FD5S/FD5SD2

D Flip-Flop with Negative Edge Trigger, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD5S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.048 + 0.024 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.331	$0.303 + 0.014 \cdot \text{SL}$	$0.308 + 0.013 \cdot \text{SL}$	$0.311 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.292	$0.261 + 0.015 \cdot \text{SL}$	$0.268 + 0.013 \cdot \text{SL}$	$0.275 + 0.013 \cdot \text{SL}$
CKN to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.090	$0.045 + 0.023 \cdot \text{SL}$	$0.040 + 0.024 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.343	$0.316 + 0.013 \cdot \text{SL}$	$0.319 + 0.013 \cdot \text{SL}$	$0.321 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.388	$0.359 + 0.015 \cdot \text{SL}$	$0.365 + 0.013 \cdot \text{SL}$	$0.368 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$


FD5SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.049 + 0.013 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.336	$0.319 + 0.009 \cdot \text{SL}$	$0.326 + 0.007 \cdot \text{SL}$	$0.333 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.293	$0.274 + 0.010 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.296 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.046 + 0.012 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.380	$0.364 + 0.008 \cdot \text{SL}$	$0.369 + 0.007 \cdot \text{SL}$	$0.375 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.421	$0.403 + 0.009 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Reset, 1X/2X Drive

Logic Symbol




Truth Table

D	CKN	RN	Q (n+1)	QN (n+1)
0		1	0	1
1		1	1	0
x	x	0	0	1
x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD6			FD6D2			FD6	FD6D2
D	CKN	RN	D	CKN	RN		
0.7	0.7	1.3	0.7	0.7	1.3	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD6	FD6D2
Input Setup Time (D to CKN)	t_{SU}	0.203	0.195
Input Hold Time (D to CKN)	t_{HD}	0.134	0.136
Pulse Width Low (CKN)	t_{PWL}	0.232	0.247
Pulse Width High (CKN)	t_{PWH}	0.232	0.247
Pulse Width Low (RN)	t_{PWL}	0.486	0.484
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.601	0.600

FD6/FD6D2

D Flip-Flop with Negative Edge Trigger, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.337	$0.307 + 0.015 \cdot \text{SL}$	$0.314 + 0.013 \cdot \text{SL}$	$0.321 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.299	$0.268 + 0.015 \cdot \text{SL}$	$0.276 + 0.013 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.056 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.170	$0.138 + 0.016 \cdot \text{SL}$	$0.146 + 0.013 \cdot \text{SL}$	$0.153 + 0.013 \cdot \text{SL}$
CKN to QN	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.047 + 0.022 \cdot \text{SL}$	$0.042 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.351	$0.324 + 0.014 \cdot \text{SL}$	$0.328 + 0.012 \cdot \text{SL}$	$0.329 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.395	$0.366 + 0.015 \cdot \text{SL}$	$0.373 + 0.013 \cdot \text{SL}$	$0.376 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.115	$0.057 + 0.029 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.244	$0.213 + 0.015 \cdot \text{SL}$	$0.219 + 0.014 \cdot \text{SL}$	$0.229 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$


FD6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.089	$0.062 + 0.014 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.343	$0.325 + 0.009 \cdot \text{SL}$	$0.333 + 0.007 \cdot \text{SL}$	$0.345 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.302	$0.283 + 0.009 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.170	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.173 + 0.007 \cdot \text{SL}$
CKN to QN	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.049 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.387	$0.372 + 0.008 \cdot \text{SL}$	$0.377 + 0.007 \cdot \text{SL}$	$0.383 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.433	$0.415 + 0.009 \cdot \text{SL}$	$0.422 + 0.007 \cdot \text{SL}$	$0.432 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.088	$0.059 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.278	$0.260 + 0.009 \cdot \text{SL}$	$0.266 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Reset, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CKN	RN	Q (n+1)	QN (n+1)
0	x	0		1	0	1
1	x	0		1	1	0
x	0	1		1	0	1
x	1	1		1	1	0
x	x	x	x	0	0	1
x	x	x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD6S					FD6SD2					FD6S	FD6SD2
D	CKN	RN	TI	TE	D	CKN	RN	TI	TE		
0.6	0.7	1.3	0.7	1.4	0.7	0.7	1.4	0.6	1.4	7.00	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD6S	FD6SD2
Input Setup Time (D to CKN)	t_{SU}	0.359	0.357
Input Hold Time (D to CKN)	t_{HD}	0.082	0.080
Pulse Width Low (CKN)	t_{PWL}	0.236	0.249
Pulse Width High (CKN)	t_{PWH}	0.236	0.249
Pulse Width Low (RN)	t_{PWL}	0.500	0.500
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.610	0.619
Input Setup Time (TI to CKN)	t_{SU}	0.345	0.344
Input Hold Time (TI to CKN)	t_{HD}	0.073	0.072
Input Setup Time (TE to CKN)	t_{SU}	0.361	0.362
Input Hold Time (TE to CKN)	t_{HD}	0.099	0.094

FD6S/FD6SD2

D Flip-Flop with Negative Edge Trigger, Reset, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD6S


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.343	$0.313 + 0.015 \cdot \text{SL}$	$0.320 + 0.013 \cdot \text{SL}$	$0.327 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.300	$0.270 + 0.015 \cdot \text{SL}$	$0.277 + 0.013 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.169	$0.138 + 0.016 \cdot \text{SL}$	$0.146 + 0.013 \cdot \text{SL}$	$0.153 + 0.013 \cdot \text{SL}$
CKN to QN	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.046 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.353	$0.326 + 0.014 \cdot \text{SL}$	$0.330 + 0.012 \cdot \text{SL}$	$0.331 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.402	$0.372 + 0.015 \cdot \text{SL}$	$0.379 + 0.013 \cdot \text{SL}$	$0.382 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.114	$0.056 + 0.029 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.244	$0.213 + 0.015 \cdot \text{SL}$	$0.219 + 0.014 \cdot \text{SL}$	$0.229 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD6SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.089	$0.061 + 0.014 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.349	$0.331 + 0.009 \cdot \text{SL}$	$0.338 + 0.007 \cdot \text{SL}$	$0.350 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.304	$0.285 + 0.009 \cdot \text{SL}$	$0.293 + 0.007 \cdot \text{SL}$	$0.307 + 0.007 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.170	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.173 + 0.007 \cdot \text{SL}$
CKN to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.392	$0.376 + 0.008 \cdot \text{SL}$	$0.382 + 0.007 \cdot \text{SL}$	$0.388 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.438	$0.420 + 0.009 \cdot \text{SL}$	$0.428 + 0.007 \cdot \text{SL}$	$0.438 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.089	$0.060 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.282	$0.264 + 0.009 \cdot \text{SL}$	$0.270 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Set, 1X/2X Drive**Logic Symbol****Truth Table**

D	CKN	SN	Q (n+1)	QN (n+1)
0		1	0	1
1		1	1	0
x	x	0	1	0
x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD7			FD7D2			FD7	FD7D2
D	CKN	SN	D	CKN	SN		
0.7	0.7	1.7	0.7	0.7	1.7	5.67	6.00

Schematic Diagram**Timing Requirements**

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD7	FD7D2
Input Setup Time (D to CKN)	t_{SU}	0.213	0.214
Input Hold Time (D to CKN)	t_{HD}	0.142	0.143
Pulse Width Low (CKN)	t_{PWL}	0.237	0.253
Pulse Width High (CKN)	t_{PWH}	0.237	0.253
Pulse Width Low (SN)	t_{PWL}	0.256	0.254
Recovery Time (SN to CKN)	t_{RC}	0.046	0.047
Removal Time (SN to CKN)	t_{RM}	0.182	0.181

FD7/FD7D2

D Flip-Flop with Negative Edge Trigger, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.110	$0.057 + 0.026 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.024 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.333	$0.304 + 0.014 \cdot \text{SL}$	$0.310 + 0.013 \cdot \text{SL}$	$0.313 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.306	$0.275 + 0.016 \cdot \text{SL}$	$0.282 + 0.014 \cdot \text{SL}$	$0.290 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.119	$0.068 + 0.025 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.365	$0.336 + 0.015 \cdot \text{SL}$	$0.343 + 0.013 \cdot \text{SL}$	$0.347 + 0.012 \cdot \text{SL}$
CKN to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.043 + 0.024 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.374	$0.345 + 0.015 \cdot \text{SL}$	$0.352 + 0.013 \cdot \text{SL}$	$0.356 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.404	$0.373 + 0.015 \cdot \text{SL}$	$0.381 + 0.013 \cdot \text{SL}$	$0.385 + 0.013 \cdot \text{SL}$
SN to QN	t_F	0.105	$0.056 + 0.025 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$	$0.058 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.178	$0.145 + 0.016 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.163 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$


FD7D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.340	$0.323 + 0.009 \cdot \text{SL}$	$0.330 + 0.007 \cdot \text{SL}$	$0.338 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.307	$0.288 + 0.010 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.098	$0.074 + 0.012 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.405	$0.387 + 0.009 \cdot \text{SL}$	$0.395 + 0.007 \cdot \text{SL}$	$0.406 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.084	$0.056 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.408	$0.390 + 0.009 \cdot \text{SL}$	$0.397 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.439	$0.420 + 0.009 \cdot \text{SL}$	$0.428 + 0.007 \cdot \text{SL}$	$0.439 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.062 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.178	$0.158 + 0.010 \cdot \text{SL}$	$0.167 + 0.008 \cdot \text{SL}$	$0.182 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Set, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CKN	SN	Q (n+1)	QN (n+1)
0	x	0		1	0	1
1	x	0		1	1	0
x	0	1		1	0	1
x	1	1		1	1	0
x	x	x	x	0	1	0
x	x	x		1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD7S					FD7SD2					FD7S	FD7SD2
D	CKN	SN	TI	TE	D	CKN	SN	TI	TE		
0.6	0.7	1.7	0.7	1.4	0.6	0.7	1.7	0.7	1.4	7.33	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD7S	FD7SD2
Input Setup Time (D to CKN)	t_{SU}	0.376	0.377
Input Hold Time (D to CKN)	t_{HD}	0.090	0.089
Pulse Width Low (CKN)	t_{PWL}	0.237	0.256
Pulse Width High (CKN)	t_{PWH}	0.237	0.256
Pulse Width Low (SN)	t_{PWL}	0.257	0.257
Recovery Time (SN to CKN)	t_{RC}	0.041	0.044
Removal Time (SN to CKN)	t_{RM}	0.189	0.186
Input Setup Time (TI to CKN)	t_{SU}	0.358	0.359
Input Hold Time (TI to CKN)	t_{HD}	0.082	0.080
Input Setup Time (TE to CKN)	t_{SU}	0.376	0.377
Input Hold Time (TE to CKN)	t_{HD}	0.106	0.106

FD7S/FD7SD2

D Flip-Flop with Negative Edge Trigger, Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD7S


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.110	$0.057 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.024 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.334	$0.306 + 0.014 \cdot \text{SL}$	$0.312 + 0.013 \cdot \text{SL}$	$0.315 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.307	$0.276 + 0.015 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.119	$0.068 + 0.025 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.364	$0.335 + 0.015 \cdot \text{SL}$	$0.343 + 0.013 \cdot \text{SL}$	$0.346 + 0.012 \cdot \text{SL}$
CKN to QN	t_R	0.110	$0.057 + 0.027 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.045 + 0.024 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.377	$0.348 + 0.014 \cdot \text{SL}$	$0.355 + 0.013 \cdot \text{SL}$	$0.359 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.407	$0.377 + 0.015 \cdot \text{SL}$	$0.385 + 0.013 \cdot \text{SL}$	$0.389 + 0.012 \cdot \text{SL}$
SN to QN	t_F	0.105	$0.057 + 0.024 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.179	$0.147 + 0.016 \cdot \text{SL}$	$0.155 + 0.014 \cdot \text{SL}$	$0.164 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FD7SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.054 + 0.012 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.345	$0.328 + 0.009 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.344 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.314	$0.295 + 0.010 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.099	$0.074 + 0.012 \cdot \text{SL}$	$0.071 + 0.013 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.409	$0.391 + 0.009 \cdot \text{SL}$	$0.399 + 0.007 \cdot \text{SL}$	$0.411 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.416	$0.398 + 0.009 \cdot \text{SL}$	$0.405 + 0.007 \cdot \text{SL}$	$0.416 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.446	$0.427 + 0.009 \cdot \text{SL}$	$0.435 + 0.007 \cdot \text{SL}$	$0.447 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.177	$0.157 + 0.010 \cdot \text{SL}$	$0.165 + 0.008 \cdot \text{SL}$	$0.181 + 0.007 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Reset, Set, 1X/2X Drive**Logic Symbol****Truth Table**

D	CKN	RN	SN	Q (n+1)	QN (n+1)
0		1	1	0	1
1		1	1	1	0
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	0	0
x		1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD8				FD8D2				FD8	FD8D2
D	CKN	RN	SN	D	CKN	RN	SN		
0.7	0.7	1.4	1.7	0.7	0.7	1.4	1.7	6.00	6.33

Schematic Diagram**Timing Requirements**

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD8	FD8D2
Input Setup Time (D to CKN)	t_{SU}	0.206	0.206
Input Hold Time (D to CKN)	t_{HD}	0.139	0.139
Pulse Width Low (CKN)	t_{PWL}	0.253	0.267
Pulse Width High (CKN)	t_{PWH}	0.253	0.267
Pulse Width Low (RN)	t_{PWL}	0.508	0.508
Pulse Width Low (SN)	t_{PWL}	0.298	0.297
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.632	0.632
Recovery Time (SN to CKN)	t_{RC}	0.026	0.026
Removal Time (SN to CKN)	t_{RM}	0.222	0.221
Recovery Time (SN to RN)	t_{RC}	0.083	0.084
Removal Time (SN to RN)	t_{RM}	0.137	0.136

FD8/FD8D2

D Flip-Flop with Negative Edge Trigger, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.118	$0.063 + 0.028 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.055 + 0.024 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.357	$0.326 + 0.015 \cdot \text{SL}$	$0.334 + 0.013 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.331	$0.299 + 0.016 \cdot \text{SL}$	$0.308 + 0.014 \cdot \text{SL}$	$0.317 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.114	$0.059 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.057 + 0.024 \cdot \text{SL}$	$0.057 + 0.024 \cdot \text{SL}$	$0.052 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.148	$0.118 + 0.015 \cdot \text{SL}$	$0.125 + 0.013 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.174	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.126	$0.074 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.385	$0.354 + 0.016 \cdot \text{SL}$	$0.363 + 0.013 \cdot \text{SL}$	$0.370 + 0.012 \cdot \text{SL}$
CKN to QN	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.049 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.401	$0.372 + 0.015 \cdot \text{SL}$	$0.379 + 0.013 \cdot \text{SL}$	$0.383 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.430	$0.400 + 0.015 \cdot \text{SL}$	$0.408 + 0.013 \cdot \text{SL}$	$0.412 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.123	$0.064 + 0.029 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$	$0.072 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.267	$0.234 + 0.017 \cdot \text{SL}$	$0.242 + 0.015 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.121	$0.063 + 0.029 \cdot \text{SL}$	$0.066 + 0.028 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.056 + 0.025 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.152	$0.119 + 0.016 \cdot \text{SL}$	$0.127 + 0.014 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.181	$0.148 + 0.017 \cdot \text{SL}$	$0.156 + 0.014 \cdot \text{SL}$	$0.166 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Reset, Set, 1X/2X Drive**Switching Characteristics**(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**FD8D2**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.094	$0.067 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.362	$0.343 + 0.009 \cdot \text{SL}$	$0.351 + 0.007 \cdot \text{SL}$	$0.364 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.333	$0.314 + 0.010 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.089	$0.062 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.152	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.153 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.076 + 0.014 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.421	$0.402 + 0.009 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.425 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.085	$0.058 + 0.013 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.437	$0.420 + 0.009 \cdot \text{SL}$	$0.427 + 0.007 \cdot \text{SL}$	$0.437 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.465	$0.447 + 0.009 \cdot \text{SL}$	$0.454 + 0.007 \cdot \text{SL}$	$0.467 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.097	$0.069 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.299	$0.279 + 0.010 \cdot \text{SL}$	$0.287 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.093	$0.064 + 0.015 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.154	$0.135 + 0.010 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.179	$0.159 + 0.010 \cdot \text{SL}$	$0.169 + 0.008 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FD8S/FD8SD2

D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	TI	TE	CKN	RN	SN	Q (n+1)	QN (n+1)
0	x	0		1	1	0	1
1	x	0		1	1	1	0
x	0	1		1	1	0	1
x	1	1		1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	x	x		1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)												Gate Count	
FD8S						FD8SD2						FD8S	FD8SD2
D	CKN	RN	SN	TI	TE	D	CKN	RN	SN	TI	TE		
0.6	0.7	1.4	1.7	0.7	1.4	0.6	0.7	1.4	1.7	0.7	1.4	7.67	8.00

Schematic Diagram



D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 1X/2X Drive
Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD8S	FD8SD2
Input Setup Time (D to CKN)	t_{SU}	0.366	0.367
Input Hold Time (D to CKN)	t_{HD}	0.086	0.086
Pulse Width Low (CKN)	t_{PWL}	0.254	0.267
Pulse Width High (CKN)	t_{PWH}	0.254	0.267
Pulse Width Low (RN)	t_{PWL}	0.509	0.509
Pulse Width Low (SN)	t_{PWL}	0.299	0.298
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.636	0.635
Recovery Time (SN to CKN)	t_{RC}	0.026	0.026
Removal Time (SN to CKN)	t_{RM}	0.224	0.224
Input Setup Time (TI to CKN)	t_{SU}	0.349	0.350
Input Hold Time (TI to CKN)	t_{HD}	0.077	0.077
Input Setup Time (TE to CKN)	t_{SU}	0.366	0.366
Input Hold Time (TE to CKN)	t_{HD}	0.103	0.103
Recovery Time (SN to RN)	t_{RC}	0.082	0.084
Removal Time (SN to RN)	t_{RM}	0.138	0.136

FD8S/FD8SD2

D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD8S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.055 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.053 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.359	$0.329 + 0.015 \cdot \text{SL}$	$0.336 + 0.013 \cdot \text{SL}$	$0.343 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.333	$0.301 + 0.016 \cdot \text{SL}$	$0.309 + 0.014 \cdot \text{SL}$	$0.319 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.114	$0.059 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.057 + 0.024 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$	$0.052 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.148	$0.118 + 0.015 \cdot \text{SL}$	$0.125 + 0.013 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.174	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.126	$0.074 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.385	$0.354 + 0.016 \cdot \text{SL}$	$0.363 + 0.013 \cdot \text{SL}$	$0.370 + 0.012 \cdot \text{SL}$
CKN to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.049 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.403	$0.374 + 0.015 \cdot \text{SL}$	$0.381 + 0.013 \cdot \text{SL}$	$0.385 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.433	$0.402 + 0.015 \cdot \text{SL}$	$0.410 + 0.013 \cdot \text{SL}$	$0.415 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.123	$0.064 + 0.029 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$	$0.072 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.267	$0.233 + 0.017 \cdot \text{SL}$	$0.242 + 0.015 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.121	$0.063 + 0.029 \cdot \text{SL}$	$0.066 + 0.028 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$
	t_F	0.106	$0.056 + 0.025 \cdot \text{SL}$	$0.061 + 0.024 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.152	$0.119 + 0.016 \cdot \text{SL}$	$0.127 + 0.014 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.181	$0.148 + 0.017 \cdot \text{SL}$	$0.156 + 0.014 \cdot \text{SL}$	$0.166 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FD8SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.094	$0.067 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.011 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.365	$0.346 + 0.009 \cdot \text{SL}$	$0.354 + 0.007 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.336	$0.317 + 0.010 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.339 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.089	$0.061 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.152	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.153 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.076 + 0.014 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.421	$0.402 + 0.009 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.425 + 0.006 \cdot \text{SL}$
CKN to QN	t_R	0.085	$0.058 + 0.014 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.439	$0.422 + 0.009 \cdot \text{SL}$	$0.429 + 0.007 \cdot \text{SL}$	$0.440 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.468	$0.449 + 0.009 \cdot \text{SL}$	$0.457 + 0.007 \cdot \text{SL}$	$0.470 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.097	$0.069 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.299	$0.279 + 0.010 \cdot \text{SL}$	$0.287 + 0.008 \cdot \text{SL}$	$0.305 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.093	$0.063 + 0.015 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.154	$0.135 + 0.010 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.179	$0.159 + 0.010 \cdot \text{SL}$	$0.169 + 0.008 \cdot \text{SL}$	$0.185 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS2/FDS2D2

D Flip-Flop with Synchronous Clear, 1X/2X Drive

Logic Symbol




Truth Table

D	CRN	CK	Q (n+1)	QN (n+1)
0	1		0	1
1	1		1	0
x	0		0	1
x	x		Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FDS2			FDS2D2			FDS2	FDS2D2
D	CRN	CK	D	CRN	CK		
0.6	0.6	0.7	0.6	0.6	0.7	5.33	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2	FDS2D2
Input Setup Time (D to CK)	t _{SU}	0.240	0.235
Input Hold Time (D to CK)	t _{HD}	0.100	0.111
Pulse Width Low (CK)	t _{PWL}	0.272	0.274
Pulse Width High (CK)	t _{PWH}	0.244	0.268
Input Setup Time (CRN to CK)	t _{SU}	0.238	0.233
Input Hold Time (CRN to CK)	t _{HD}	0.097	0.106

D Flip-Flop with Synchronous Clear, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.047 + 0.024 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.305	$0.277 + 0.014 \cdot \text{SL}$	$0.282 + 0.013 \cdot \text{SL}$	$0.286 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.304	$0.273 + 0.015 \cdot \text{SL}$	$0.280 + 0.013 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.090	$0.043 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.354	$0.327 + 0.013 \cdot \text{SL}$	$0.331 + 0.012 \cdot \text{SL}$	$0.332 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.361	$0.332 + 0.015 \cdot \text{SL}$	$0.338 + 0.013 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FDS2D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.058 + 0.013 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.326	$0.309 + 0.009 \cdot \text{SL}$	$0.316 + 0.007 \cdot \text{SL}$	$0.324 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.310	$0.292 + 0.009 \cdot \text{SL}$	$0.300 + 0.007 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.397	$0.381 + 0.008 \cdot \text{SL}$	$0.386 + 0.007 \cdot \text{SL}$	$0.392 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.412	$0.394 + 0.009 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.410 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS2CS/FDS2CSD2

D Flip-Flop with Synchronous Clear, Scan Clock, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CRN	CK	Q (n+1)	QN (n+1)
x	0	0	1		0	1
x	0	1	1		1	0
0		x	x	0	0	1
1		x	x	0	1	0
x	0	x	0		0	1
x	0	x	x		Q(n)	QN(n)
x		x	x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FDS2CS					FDS2CSD2					FDS2CS	FDS2CSD2
D	SI	CK	SCK	CRN	D	SI	CK	SCK	CRN		
0.6	0.6	0.7	1.5	0.6	0.6	0.6	0.8	1.5	0.6	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2CS	FDS2CSD2
Input Setup Time (D to CK)	t_{SU}	0.241	0.238
Input Hold Time (D to CK)	t_{HD}	0.101	0.107
Input Setup Time (SI to SCK)	t_{SU}	0.290	0.290
Input Hold Time (SI to SCK)	t_{HD}	0.056	0.056
Pulse Width Low (CK)	t_{PWL}	0.272	0.273
Pulse Width High (CK)	t_{PWH}	0.249	0.268
Pulse Width Low (SCK)	t_{PWL}	0.218	0.219
Pulse Width High (SCK)	t_{PWH}	0.304	0.339
Input Setup Time (CRN to CK)	t_{SU}	0.238	0.236
Input Hold Time (CRN to CK)	t_{HD}	0.097	0.102

D Flip-Flop with Synchronous Clear, Scan Clock, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS2CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.056 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.024 \cdot \text{SL}$	$0.051 + 0.024 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.307	$0.279 + 0.014 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.288 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.309	$0.278 + 0.016 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
SCK to Q	t_R	0.126	$0.075 + 0.025 \cdot \text{SL}$	$0.071 + 0.026 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.057 + 0.023 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.393	$0.362 + 0.015 \cdot \text{SL}$	$0.371 + 0.013 \cdot \text{SL}$	$0.377 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.321	$0.289 + 0.016 \cdot \text{SL}$	$0.298 + 0.014 \cdot \text{SL}$	$0.305 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.110	$0.053 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.372	$0.343 + 0.015 \cdot \text{SL}$	$0.349 + 0.013 \cdot \text{SL}$	$0.357 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.380	$0.348 + 0.016 \cdot \text{SL}$	$0.357 + 0.014 \cdot \text{SL}$	$0.362 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.101	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.045 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.373	$0.346 + 0.013 \cdot \text{SL}$	$0.350 + 0.012 \cdot \text{SL}$	$0.351 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.452	$0.422 + 0.015 \cdot \text{SL}$	$0.428 + 0.013 \cdot \text{SL}$	$0.431 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FDS2CSD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.085	$0.058 + 0.014 \cdot \text{SL}$	$0.058 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.318	$0.301 + 0.009 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.315	$0.295 + 0.010 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$
SCK to Q	t_R	0.105	$0.080 + 0.013 \cdot \text{SL}$	$0.078 + 0.013 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.059 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.411	$0.392 + 0.010 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.413 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.331	$0.312 + 0.010 \cdot \text{SL}$	$0.320 + 0.007 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.087	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.416	$0.398 + 0.009 \cdot \text{SL}$	$0.404 + 0.007 \cdot \text{SL}$	$0.417 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.422	$0.403 + 0.009 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.422 + 0.007 \cdot \text{SL}$
SCK to QN	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.422	$0.406 + 0.008 \cdot \text{SL}$	$0.411 + 0.007 \cdot \text{SL}$	$0.417 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.504	$0.486 + 0.009 \cdot \text{SL}$	$0.494 + 0.007 \cdot \text{SL}$	$0.503 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS2S/FDS2SD2

D Flip-Flop with Synchronous Clear, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	CRN	TI	TE	CK	Q (n+1)	QN (n+1)
0	1	x	0		0	1
1	1	x	0		1	0
x	0	x	0		0	1
x	x	0	1		0	1
x	x	1	1		1	0
x	x	x	x		Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FDS2S					FDS2SD2					FDS2S	FDS2SD2
D	CRN	CK	TI	TE	D	CRN	CK	TI	TE		
0.6	0.7	0.7	0.6	1.4	0.7	0.6	0.7	0.7	1.4	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2S	FDS2SD2
Input Setup Time (D to CK)	t_{SU}	0.338	0.343
Input Hold Time (D to CK)	t_{HD}	0.000	0.000
Input Setup Time (CRN to CK)	t_{SU}	0.339	0.343
Input Hold Time (CRN to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.316	0.319
Pulse Width High (CK)	t_{PWH}	0.246	0.259
Input Setup Time (TI to CK)	t_{SU}	0.375	0.377
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.315	0.315
Input Hold Time (TE to CK)	t_{HD}	0.018	0.016

D Flip-Flop with Synchronous Clear, Scan, 1X/2X Drive
Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.101	$0.047 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.090	$0.042 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.362	$0.335 + 0.014 \cdot \text{SL}$	$0.339 + 0.012 \cdot \text{SL}$	$0.340 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.365	$0.336 + 0.015 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.308	$0.279 + 0.014 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.288 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.311	$0.280 + 0.015 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.294 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$
FDS2SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.395	$0.379 + 0.008 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.390 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.397	$0.380 + 0.009 \cdot \text{SL}$	$0.387 + 0.007 \cdot \text{SL}$	$0.396 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.083	$0.056 + 0.014 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.013 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.312	$0.294 + 0.009 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.309	$0.290 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS3/FDS3D2

D Flip-Flop with Synchronous Set, 1X/2X Drive

Logic Symbol




Truth Table

D	CSN	CK	Q (n+1)	QN (n+1)
0	1		0	1
1	1		1	0
x	0		1	0
x	x		Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FDS3			FDS3D2			FDS3	FDS3D2
D	CSN	CK	D	CSN	CK		
0.7	0.6	0.7	0.7	0.6	0.7	5.67	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3	FDS3D2
Input Setup Time (D to CK)	t_{SU}	0.297	0.293
Input Hold Time (D to CK)	t_{HD}	0.052	0.057
Input Setup Time (CSN to CK)	t_{SU}	0.238	0.234
Input Hold Time (CSN to CK)	t_{HD}	0.100	0.105
Pulse Width Low (CK)	t_{PWL}	0.276	0.277
Pulse Width High (CK)	t_{PWH}	0.247	0.265

D Flip-Flop with Synchronous Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.101	$0.048 + 0.026 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.041 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.360	$0.333 + 0.014 \cdot \text{SL}$	$0.337 + 0.013 \cdot \text{SL}$	$0.338 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.366	$0.337 + 0.014 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.308	$0.280 + 0.014 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.289 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.308	$0.277 + 0.016 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FDS3D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.398	$0.382 + 0.008 \cdot \text{SL}$	$0.387 + 0.007 \cdot \text{SL}$	$0.393 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.406	$0.389 + 0.009 \cdot \text{SL}$	$0.396 + 0.007 \cdot \text{SL}$	$0.405 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.322	$0.305 + 0.008 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.312	$0.293 + 0.009 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.313 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS3CS/FDS3CSD2

D Flip-Flop with Synchronous Set, 1X/2X Drive

Logic Symbol




Truth Table

SI	SCK	D	CSN	CK	Q(n+1)	QN(n+1)
x	0	0	1		0	1
x	0	1	1		1	0
0		x	x	0	0	1
1		x	x	0	1	0
x	0	x	0		1	0
x	0	x	x		Q(n)	QN(n)
x		x	x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FDS3CS					FDS3CSD2					FDS3CS	FDS3CSD2
D	SI	CK	SCK	CSN	D	SI	CK	SCK	CSN		
0.7	0.7	0.8	1.8	0.6	0.7	0.7	0.7	1.7	0.7	8.67	9.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3CS	FDS3CSD2
Input Setup Time (D to CK)	t _{SU}	0.299	0.300
Input Hold Time (D to CK)	t _{HD}	0.045	0.047
Input Setup Time (SI to SCK)	t _{SU}	0.343	0.342
Input Hold Time (SI to SCK)	t _{HD}	0.003	0.003
Pulse Width Low (CK)	t _{PWL}	0.278	0.276
Pulse Width High (CK)	t _{PWH}	0.250	0.266
Pulse Width Low (SCK)	t _{PWL}	0.222	0.221
Pulse Width High (SCK)	t _{PWH}	0.309	0.339
Input Setup Time (CSN to CK)	t _{SU}	0.240	0.239
Input Hold Time (CSN to CK)	t _{HD}	0.096	0.097

D Flip-Flop with Synchronous Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS3CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.111	$0.055 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.375	$0.345 + 0.015 \cdot \text{SL}$	$0.351 + 0.013 \cdot \text{SL}$	$0.360 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.384	$0.353 + 0.015 \cdot \text{SL}$	$0.360 + 0.013 \cdot \text{SL}$	$0.366 + 0.013 \cdot \text{SL}$
SCK to Q	t_R	0.102	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.048 + 0.022 \cdot \text{SL}$	$0.042 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.387	$0.360 + 0.013 \cdot \text{SL}$	$0.364 + 0.012 \cdot \text{SL}$	$0.365 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.458	$0.429 + 0.014 \cdot \text{SL}$	$0.436 + 0.013 \cdot \text{SL}$	$0.438 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.052 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.309	$0.281 + 0.014 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$	$0.290 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.309	$0.278 + 0.015 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$	$0.293 + 0.013 \cdot \text{SL}$
SCK to QN	t_R	0.127	$0.076 + 0.025 \cdot \text{SL}$	$0.072 + 0.026 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.103	$0.055 + 0.024 \cdot \text{SL}$	$0.059 + 0.023 \cdot \text{SL}$	$0.050 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.399	$0.369 + 0.015 \cdot \text{SL}$	$0.377 + 0.013 \cdot \text{SL}$	$0.383 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.332	$0.301 + 0.016 \cdot \text{SL}$	$0.310 + 0.013 \cdot \text{SL}$	$0.318 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FDS3CSD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.086	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.412	$0.395 + 0.009 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.413 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.420	$0.401 + 0.009 \cdot \text{SL}$	$0.409 + 0.007 \cdot \text{SL}$	$0.421 + 0.007 \cdot \text{SL}$
SCK to Q	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.425	$0.408 + 0.008 \cdot \text{SL}$	$0.414 + 0.007 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.505	$0.487 + 0.009 \cdot \text{SL}$	$0.494 + 0.007 \cdot \text{SL}$	$0.503 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.084	$0.057 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.316	$0.299 + 0.009 \cdot \text{SL}$	$0.306 + 0.007 \cdot \text{SL}$	$0.314 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.310	$0.291 + 0.010 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$	$0.313 + 0.007 \cdot \text{SL}$
SCK to QN	t_R	0.105	$0.080 + 0.013 \cdot \text{SL}$	$0.079 + 0.013 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$
	t_F	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.411	$0.392 + 0.010 \cdot \text{SL}$	$0.401 + 0.007 \cdot \text{SL}$	$0.413 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.333	$0.313 + 0.010 \cdot \text{SL}$	$0.322 + 0.007 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FDS3S/FDS3SD2

Flip-Flop with Synchronous Set, Scan, 1X/2X Drive

Logic Symbol




Truth Table

D	CSN	TI	TE	CK	Q(n+1)	QN(n+1)
0	1	x	0		0	1
1	1	x	0		1	0
x	x	0	1		0	1
x	x	1	1		1	0
x	0	x	0		1	0
x	x	x	x		Q(n)	QN(n+1)

Cell Data

Input Load (SL)										Gate Count	
FDS3S					FDS3SD2					FDS3S	FDS3SD2
D	CSN	CK	TI	TE	D	CSN	CK	TI	TE		
0.6	0.6	0.7	0.7	1.4	0.6	0.6	0.7	0.7	1.3	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3S	FDS3SD2
Input Setup Time (D to CK)	t _{SU}	0.387	0.392
Input Hold Time (D to CK)	t _{HD}	0.000	0.000
Input Setup Time (CSN to CK)	t _{SU}	0.340	0.344
Input Hold Time (CSN to CK)	t _{HD}	0.000	0.000
Pulse Width Low (CK)	t _{PWL}	0.317	0.320
Pulse Width High (CK)	t _{PWH}	0.246	0.259
Input Setup Time (TI to CK)	t _{SU}	0.316	0.317
Input Hold Time (TI to CK)	t _{HD}	0.037	0.033
Input Setup Time (TE to CK)	t _{SU}	0.315	0.316
Input Hold Time (TE to CK)	t _{HD}	0.017	0.016

Flip-Flop with Synchronous Set, Scan, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FDS3S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.048 + 0.024 \cdot \text{SL}$	$0.051 + 0.024 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.308	$0.279 + 0.014 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.288 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.311	$0.280 + 0.015 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.294 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.090	$0.042 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.362	$0.335 + 0.014 \cdot \text{SL}$	$0.339 + 0.013 \cdot \text{SL}$	$0.340 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.365	$0.336 + 0.015 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FDS3SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.083	$0.056 + 0.014 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.311	$0.294 + 0.009 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.309	$0.290 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.311 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.395	$0.379 + 0.008 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.390 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.397	$0.380 + 0.009 \cdot \text{SL}$	$0.387 + 0.007 \cdot \text{SL}$	$0.396 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ1/FJ1D2

JK Flip-Flop with 1X/2X Drive

Logic Symbol




Truth Table

J	CK	K	Q (n+1)	QN (n+1)
0		1	0	1
1		0	1	0
0		0	Q (n)	QN (n)
1		1	QN (n)	Q (n)
x		x	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FJ1			FJ1D2			FJ1	FJ1D2
J	K	CK	J	K	CK		
0.5	0.6	0.7	0.5	0.6	0.7	6.67	7.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ1	FJ1D2
Input Setup Time (J to CK)	t_{SU}	0.287	0.291
Input Hold Time (J to CK)	t_{HD}	0.037	0.034
Input Setup Time (K to CK)	t_{SU}	0.287	0.291
Input Hold Time (K to CK)	t_{HD}	0.037	0.034
Pulse Width Low (CK)	t_{PWL}	0.310	0.312
Pulse Width High (CK)	t_{PWH}	0.253	0.271

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**FJ1**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.111	$0.057 + 0.027 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.024 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.399	$0.372 + 0.014 \cdot \text{SL}$	$0.374 + 0.013 \cdot \text{SL}$	$0.378 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.397	$0.366 + 0.016 \cdot \text{SL}$	$0.375 + 0.013 \cdot \text{SL}$	$0.381 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.108	$0.056 + 0.026 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.049 + 0.024 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.310	$0.282 + 0.014 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.290 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.315	$0.284 + 0.015 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$	$0.297 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$ **FJ1D2**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.086	$0.059 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.433	$0.415 + 0.009 \cdot \text{SL}$	$0.422 + 0.007 \cdot \text{SL}$	$0.432 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.431	$0.412 + 0.010 \cdot \text{SL}$	$0.421 + 0.007 \cdot \text{SL}$	$0.435 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.320	$0.302 + 0.009 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$	$0.318 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.318	$0.299 + 0.010 \cdot \text{SL}$	$0.308 + 0.007 \cdot \text{SL}$	$0.320 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ1S/FJ1SD2

JK Flip-Flop with Scan, 1X/2X Drive

Logic Symbol




Truth Table

J	CK	K	TI	TE	Q (n+1)	QN (n+1)
0		1	x	0	0	1
1		0	x	0	1	0
0		0	x	0	Q (n)	QN (n)
1		1	x	0	QN (n)	Q (n)
x		x	x	x	Q (n)	QN (n)
x		x	0	1	0	1
x		x	1	1	1	0

Cell Data

Input Load (SL)										Gate Count	
FJ1S					FJ1SD2					FJ1S	FJ1SD2
J	K	CK	TI	TE	J	K	CK	TI	TE		
0.6	0.5	0.7	0.7	1.4	0.6	0.5	0.7	0.7	1.4	8.67	9.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ1S	FJ1SD2
Input Setup Time (J to CK)	t_{SU}	0.452	0.452
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.452	0.452
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.318	0.318
Pulse Width High (CK)	t_{PWH}	0.261	0.278
Input Setup Time (TI to CK)	t_{SU}	0.318	0.317
Input Hold Time (TI to CK)	t_{HD}	0.034	0.034
Input Setup Time (TE to CK)	t_{SU}	0.318	0.317
Input Hold Time (TE to CK)	t_{HD}	0.015	0.016

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ1S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.120	$0.067 + 0.026 \cdot \text{SL}$	$0.065 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.107	$0.059 + 0.024 \cdot \text{SL}$	$0.063 + 0.023 \cdot \text{SL}$	$0.056 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.344	$0.313 + 0.015 \cdot \text{SL}$	$0.321 + 0.013 \cdot \text{SL}$	$0.327 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.341	$0.308 + 0.017 \cdot \text{SL}$	$0.318 + 0.014 \cdot \text{SL}$	$0.328 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.104	$0.051 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.040 + 0.029 \cdot \text{SL}$
	t_F	0.092	$0.045 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.394	$0.368 + 0.013 \cdot \text{SL}$	$0.371 + 0.012 \cdot \text{SL}$	$0.372 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.402	$0.373 + 0.014 \cdot \text{SL}$	$0.379 + 0.013 \cdot \text{SL}$	$0.381 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FJ1SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.095	$0.066 + 0.014 \cdot \text{SL}$	$0.070 + 0.013 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.085	$0.060 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.348	$0.329 + 0.009 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$	$0.350 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.341	$0.320 + 0.010 \cdot \text{SL}$	$0.330 + 0.008 \cdot \text{SL}$	$0.347 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.046 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.430	$0.414 + 0.008 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.426 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.436	$0.418 + 0.009 \cdot \text{SL}$	$0.425 + 0.007 \cdot \text{SL}$	$0.435 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ2/FJ2D2

JK Flip-Flop with Reset, 1X/2X Drive

Logic Symbol




Truth Table

J	CK	K	RN	Q (n+1)	QN (n+1)
0		1	1	0	1
1		0	1	1	0
0		0	1	Q (n)	QN (n)
1		1	1	QN (n)	Q (n)
x		x	1	Q (n)	QN (n)
x	x	x	0	0	1

Cell Data

Input Load (SL)								Gate Count	
FJ2				FJ2D2				FJ2	FJ2D2
J	K	CK	RN	J	K	CK	RN		
0.6	0.6	0.7	1.8	0.6	0.6	0.7	1.8	7.33	7.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ2	FJ2D2
Input Setup Time (J to CK)	t_{SU}	0.287	0.288
Input Hold Time (J to CK)	t_{HD}	0.023	0.022
Input Setup Time (K to CK)	t_{SU}	0.287	0.288
Input Hold Time (K to CK)	t_{HD}	0.023	0.022
Pulse Width Low (CK)	t_{PWL}	0.309	0.309
Pulse Width High (CK)	t_{PWH}	0.259	0.276
Pulse Width Low (RN)	t_{PWL}	0.302	0.336
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.234	0.234

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.120	$0.065 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.055 + 0.024 \cdot \text{SL}$	$0.058 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.436	$0.404 + 0.016 \cdot \text{SL}$	$0.413 + 0.013 \cdot \text{SL}$	$0.422 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.414	$0.383 + 0.016 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$	$0.401 + 0.012 \cdot \text{SL}$
RN to Q	t_F	0.117	$0.071 + 0.023 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$
	t_{PHL}	0.210	$0.175 + 0.017 \cdot \text{SL}$	$0.187 + 0.014 \cdot \text{SL}$	$0.200 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.054 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.314	$0.286 + 0.014 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$	$0.294 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.331	$0.301 + 0.015 \cdot \text{SL}$	$0.309 + 0.013 \cdot \text{SL}$	$0.315 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.120	$0.070 + 0.025 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.397	$0.367 + 0.015 \cdot \text{SL}$	$0.375 + 0.013 \cdot \text{SL}$	$0.379 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FJ2D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.095	$0.067 + 0.014 \cdot \text{SL}$	$0.068 + 0.014 \cdot \text{SL}$	$0.064 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.057 + 0.013 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.468	$0.449 + 0.010 \cdot \text{SL}$	$0.458 + 0.007 \cdot \text{SL}$	$0.473 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.445	$0.426 + 0.010 \cdot \text{SL}$	$0.434 + 0.007 \cdot \text{SL}$	$0.451 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.097	$0.073 + 0.012 \cdot \text{SL}$	$0.074 + 0.012 \cdot \text{SL}$	$0.077 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.206	$0.184 + 0.011 \cdot \text{SL}$	$0.195 + 0.008 \cdot \text{SL}$	$0.216 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.085	$0.059 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.320	$0.303 + 0.009 \cdot \text{SL}$	$0.309 + 0.007 \cdot \text{SL}$	$0.317 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.335	$0.316 + 0.010 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.338 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.099	$0.074 + 0.012 \cdot \text{SL}$	$0.072 + 0.013 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.432	$0.414 + 0.009 \cdot \text{SL}$	$0.422 + 0.007 \cdot \text{SL}$	$0.433 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ2S/FJ2SD2

JK Flip-Flop with Reset, Scan, 1X/2X Drive

Logic Symbol




Truth Table

J	CK	K	TI	TE	RN	Q (n+1)	QN (n+1)
0		1	x	0	1	0	1
1		0	x	0	1	1	0
0		0	x	0	1	Q (n)	QN (n)
1		1	x	0	1	QN (n)	Q (n)
x		x	x	x	1	Q (n)	QN (n)
x	x	x	x	x	0	0	1
x		x	0	1	1	0	1
x		x	1	1	1	1	0

Cell Data

Input Load (SL)												Gate Count	
FJ2S						FJ2SD2						FJ2S	FJ2SD2
J	K	CK	RN	TI	TE	J	K	CK	RN	TI	TE		
0.7	0.5	0.7	1.3	0.6	1.4	0.7	0.5	0.7	1.3	0.7	1.4	9.00	9.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ2S	FJ2SD2
Input Setup Time (J to CK)	t_{SU}	0.445	0.437
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.445	0.437
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.322	0.321
Pulse Width High (CK)	t_{PWH}	0.265	0.283
Pulse Width Low (RN)	t_{PWL}	0.278	0.317
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.520	0.534
Input Setup Time (TI to CK)	t_{SU}	0.328	0.318
Input Hold Time (TI to CK)	t_{HD}	0.051	0.052
Input Setup Time (TE to CK)	t_{SU}	0.324	0.317
Input Hold Time (TE to CK)	t_{HD}	0.033	0.029

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.128	$0.074 + 0.027 \cdot \text{SL}$	$0.074 + 0.027 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$
	t_F	0.108	$0.059 + 0.024 \cdot \text{SL}$	$0.064 + 0.023 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.356	$0.323 + 0.016 \cdot \text{SL}$	$0.333 + 0.014 \cdot \text{SL}$	$0.344 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.353	$0.319 + 0.017 \cdot \text{SL}$	$0.330 + 0.014 \cdot \text{SL}$	$0.341 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.113	$0.064 + 0.025 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.063 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.203	$0.168 + 0.017 \cdot \text{SL}$	$0.180 + 0.014 \cdot \text{SL}$	$0.191 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.405	$0.378 + 0.013 \cdot \text{SL}$	$0.382 + 0.012 \cdot \text{SL}$	$0.383 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.414	$0.386 + 0.014 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$	$0.395 + 0.012 \cdot \text{SL}$
RN to QN	t_R	0.115	$0.058 + 0.029 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.278	$0.247 + 0.015 \cdot \text{SL}$	$0.253 + 0.014 \cdot \text{SL}$	$0.263 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FJ2SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.100	$0.070 + 0.015 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$
	t_F	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.064 + 0.012 \cdot \text{SL}$	$0.065 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.362	$0.342 + 0.010 \cdot \text{SL}$	$0.351 + 0.008 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.353	$0.333 + 0.010 \cdot \text{SL}$	$0.343 + 0.008 \cdot \text{SL}$	$0.361 + 0.007 \cdot \text{SL}$
RN to Q	t_F	0.092	$0.067 + 0.012 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$	$0.071 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.198	$0.176 + 0.011 \cdot \text{SL}$	$0.187 + 0.008 \cdot \text{SL}$	$0.207 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.445	$0.429 + 0.008 \cdot \text{SL}$	$0.435 + 0.007 \cdot \text{SL}$	$0.440 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.454	$0.436 + 0.009 \cdot \text{SL}$	$0.443 + 0.007 \cdot \text{SL}$	$0.454 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.090	$0.061 + 0.014 \cdot \text{SL}$	$0.064 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.315	$0.297 + 0.009 \cdot \text{SL}$	$0.303 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ4/FJ4D2

JK Flip-Flop with Reset, Set, 1X/2X Drive

Logic Symbol5




Truth Table

J	CK	K	RN	SN	Q (n+1)	QN (n+1)
0		1	1	1	0	1
1		0	1	1	1	0
0		0	1	1	Q (n)	QN (n)
1		1	1	1	QN (n)	Q (n)
x		x	1	1	Q (n)	QN (n)
x	x	x	0	1	0	1
x	x	x	1	0	1	0
x	x	x	0	0	0	0

Cell Data

Input Load (SL)										Gate Count	
FJ4					FJ4D2					FJ4	FJ4D2
J	K	CK	RN	SN	J	K	CK	RN	SN		
0.6	0.6	0.7	1.7	1.4	0.6	0.6	0.7	1.7	1.4	8.00	8.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ4	FJ4D2
Input Setup Time (J to CK)	t_{SU}	0.294	0.294
Input Hold Time (J to CK)	t_{HD}	0.042	0.041
Input Setup Time (K to CK)	t_{SU}	0.294	0.294
Input Hold Time (K to CK)	t_{HD}	0.042	0.041
Pulse Width Low (CK)	t_{PWL}	0.319	0.319
Pulse Width High (CK)	t_{PWH}	0.270	0.286
Pulse Width Low (RN)	t_{PWL}	0.317	0.349
Pulse Width Low (SN)	t_{PWL}	0.288	0.319
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.268	0.319
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.556	0.556
Recovery Time (SN to RN)	t_{RC}	0.133	0.131
Removal Time (SN to RN)	t_{RM}	0.087	0.089

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.121	$0.066 + 0.028 \cdot \text{SL}$	$0.067 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$
	t_F	0.104	$0.058 + 0.023 \cdot \text{SL}$	$0.060 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.460	$0.428 + 0.016 \cdot \text{SL}$	$0.437 + 0.013 \cdot \text{SL}$	$0.446 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.440	$0.408 + 0.016 \cdot \text{SL}$	$0.418 + 0.013 \cdot \text{SL}$	$0.427 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.132	$0.074 + 0.029 \cdot \text{SL}$	$0.079 + 0.028 \cdot \text{SL}$	$0.079 + 0.028 \cdot \text{SL}$
	t_F	0.119	$0.072 + 0.023 \cdot \text{SL}$	$0.075 + 0.023 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.186	$0.151 + 0.017 \cdot \text{SL}$	$0.162 + 0.015 \cdot \text{SL}$	$0.177 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.213	$0.178 + 0.018 \cdot \text{SL}$	$0.190 + 0.014 \cdot \text{SL}$	$0.204 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.134	$0.076 + 0.029 \cdot \text{SL}$	$0.081 + 0.028 \cdot \text{SL}$	$0.082 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.306	$0.271 + 0.017 \cdot \text{SL}$	$0.281 + 0.015 \cdot \text{SL}$	$0.297 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.117	$0.062 + 0.027 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.057 + 0.022 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.334	$0.303 + 0.015 \cdot \text{SL}$	$0.311 + 0.013 \cdot \text{SL}$	$0.317 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.351	$0.320 + 0.016 \cdot \text{SL}$	$0.329 + 0.013 \cdot \text{SL}$	$0.336 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.126	$0.074 + 0.026 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.063 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.420	$0.388 + 0.016 \cdot \text{SL}$	$0.397 + 0.013 \cdot \text{SL}$	$0.405 + 0.012 \cdot \text{SL}$
SN to QN	t_R	0.114	$0.060 + 0.027 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.056 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.128 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.173	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.013 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FJ4/FJ4D2

JK Flip-Flop with Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ4D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.095	$0.067 + 0.014 \cdot \text{SL}$	$0.070 + 0.014 \cdot \text{SL}$	$0.064 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.059 + 0.012 \cdot \text{SL}$	$0.063 + 0.011 \cdot \text{SL}$	$0.060 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.488	$0.469 + 0.010 \cdot \text{SL}$	$0.478 + 0.007 \cdot \text{SL}$	$0.493 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.468	$0.449 + 0.010 \cdot \text{SL}$	$0.458 + 0.007 \cdot \text{SL}$	$0.475 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.103	$0.074 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$	$0.081 + 0.014 \cdot \text{SL}$
	t_F	0.098	$0.072 + 0.013 \cdot \text{SL}$	$0.077 + 0.011 \cdot \text{SL}$	$0.077 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.184	$0.163 + 0.010 \cdot \text{SL}$	$0.172 + 0.008 \cdot \text{SL}$	$0.192 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.208	$0.186 + 0.011 \cdot \text{SL}$	$0.197 + 0.008 \cdot \text{SL}$	$0.219 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.107	$0.078 + 0.015 \cdot \text{SL}$	$0.081 + 0.014 \cdot \text{SL}$	$0.084 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.330	$0.309 + 0.011 \cdot \text{SL}$	$0.319 + 0.008 \cdot \text{SL}$	$0.340 + 0.007 \cdot \text{SL}$
CK to QN	t_R	0.092	$0.063 + 0.014 \cdot \text{SL}$	$0.066 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.058 + 0.012 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.337	$0.318 + 0.009 \cdot \text{SL}$	$0.326 + 0.007 \cdot \text{SL}$	$0.339 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.353	$0.333 + 0.010 \cdot \text{SL}$	$0.342 + 0.007 \cdot \text{SL}$	$0.356 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.103	$0.077 + 0.013 \cdot \text{SL}$	$0.076 + 0.013 \cdot \text{SL}$	$0.069 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.450	$0.431 + 0.010 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$	$0.454 + 0.006 \cdot \text{SL}$
SN to QN	t_R	0.087	$0.060 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.060 + 0.011 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.153	$0.135 + 0.009 \cdot \text{SL}$	$0.142 + 0.007 \cdot \text{SL}$	$0.155 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.172	$0.152 + 0.010 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$	$0.175 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FJ4S/FJ4SD2

JK Flip-Flop with Reset, Set, Scan, 1X/2X Drive

Logic Symbol




Truth Table

J	CK	K	TI	TE	RN	SN	Q (n+1)	QN (n+1)
0		1	x	0	1	1	0	1
1		0	x	0	1	1	1	0
0		0	x	0	1	1	Q (n)	QN (n)
1		1	x	0	1	1	QN (n)	Q (n)
x		x	x	x	1	1	Q (n)	QN (n)
x	x	x	x	x	0	1	0	1
x	x	x	x	x	1	0	1	0
x	x	x	x	x	0	0	0	0
x		x	0	1	1	1	0	1
x		x	1	1	1	1	1	0

Cell Data

Input Load (SL)														Gate Count	
FJ4S							FJ4SD2							FJ4S	FJ4SD2
J	K	CK	RN	SN	TI	TE	J	K	CK	RN	SN	TI	TE		
0.7	0.5	0.7	1.4	1.7	0.7	1.4	0.6	0.5	0.7	1.4	1.7	0.7	1.4	10.00	10.33

Schematic Diagram



FJ4S/FJ4SD2

JK Flip-Flop with Reset, Set, Scan, 1X/2X Drive

Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ4S	FJ4SD2
Input Setup Time (J to CK)	t_{SU}	0.450	0.449
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.450	0.449
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.354	0.354
Pulse Width High (CK)	t_{PWH}	0.279	0.298
Pulse Width Low (RN)	t_{PWL}	0.291	0.327
Pulse Width Low (SN)	t_{PWL}	0.318	0.347
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.538	0.539
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.271	0.271
Input Setup Time (TI to CK)	t_{SU}	0.330	0.330
Input Hold Time (TI to CK)	t_{HD}	0.048	0.048
Input Setup Time (TE to CK)	t_{SU}	0.336	0.336
Input Hold Time (TE to CK)	t_{HD}	0.029	0.029
Recovery Time (SN to RN)	t_{RC}	0.087	0.087
Removal Time (SN to RN)	t_{RM}	0.133	0.133

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ4S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.131	$0.076 + 0.027 \cdot \text{SL}$	$0.078 + 0.027 \cdot \text{SL}$	$0.071 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.067 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.368	$0.335 + 0.016 \cdot \text{SL}$	$0.345 + 0.014 \cdot \text{SL}$	$0.356 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.380	$0.346 + 0.017 \cdot \text{SL}$	$0.357 + 0.014 \cdot \text{SL}$	$0.369 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.126	$0.072 + 0.027 \cdot \text{SL}$	$0.071 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.066 + 0.024 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.067 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.181	$0.149 + 0.016 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.167 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.206	$0.171 + 0.017 \cdot \text{SL}$	$0.183 + 0.014 \cdot \text{SL}$	$0.195 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.137	$0.085 + 0.026 \cdot \text{SL}$	$0.083 + 0.027 \cdot \text{SL}$	$0.074 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.422	$0.389 + 0.016 \cdot \text{SL}$	$0.400 + 0.014 \cdot \text{SL}$	$0.410 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.111	$0.057 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.450	$0.421 + 0.015 \cdot \text{SL}$	$0.428 + 0.013 \cdot \text{SL}$	$0.432 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.445	$0.414 + 0.015 \cdot \text{SL}$	$0.422 + 0.013 \cdot \text{SL}$	$0.427 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.125	$0.066 + 0.029 \cdot \text{SL}$	$0.071 + 0.028 \cdot \text{SL}$	$0.073 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.301	$0.268 + 0.017 \cdot \text{SL}$	$0.276 + 0.014 \cdot \text{SL}$	$0.290 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.121	$0.062 + 0.030 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$	$0.068 + 0.028 \cdot \text{SL}$
	t_F	0.105	$0.055 + 0.025 \cdot \text{SL}$	$0.059 + 0.024 \cdot \text{SL}$	$0.057 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.153	$0.120 + 0.016 \cdot \text{SL}$	$0.128 + 0.014 \cdot \text{SL}$	$0.141 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.181	$0.148 + 0.016 \cdot \text{SL}$	$0.156 + 0.014 \cdot \text{SL}$	$0.165 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FJ4SD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.103	$0.074 + 0.014 \cdot \text{SL}$	$0.077 + 0.014 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.091	$0.066 + 0.013 \cdot \text{SL}$	$0.070 + 0.012 \cdot \text{SL}$	$0.069 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.367	$0.347 + 0.010 \cdot \text{SL}$	$0.357 + 0.008 \cdot \text{SL}$	$0.374 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.377	$0.356 + 0.011 \cdot \text{SL}$	$0.366 + 0.008 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.098	$0.068 + 0.015 \cdot \text{SL}$	$0.074 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.093	$0.067 + 0.013 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$	$0.072 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.180	$0.160 + 0.010 \cdot \text{SL}$	$0.169 + 0.007 \cdot \text{SL}$	$0.186 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.200	$0.178 + 0.011 \cdot \text{SL}$	$0.189 + 0.008 \cdot \text{SL}$	$0.209 + 0.007 \cdot \text{SL}$
SN to Q	t_R	0.112	$0.086 + 0.013 \cdot \text{SL}$	$0.086 + 0.013 \cdot \text{SL}$	$0.079 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.450	$0.430 + 0.010 \cdot \text{SL}$	$0.440 + 0.008 \cdot \text{SL}$	$0.458 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.087	$0.058 + 0.014 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.053 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.483	$0.465 + 0.009 \cdot \text{SL}$	$0.473 + 0.007 \cdot \text{SL}$	$0.484 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.478	$0.459 + 0.009 \cdot \text{SL}$	$0.467 + 0.007 \cdot \text{SL}$	$0.480 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.099	$0.071 + 0.014 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.331	$0.311 + 0.010 \cdot \text{SL}$	$0.319 + 0.008 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.093	$0.064 + 0.014 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$	$0.069 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.058 + 0.013 \cdot \text{SL}$	$0.063 + 0.012 \cdot \text{SL}$	$0.061 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.154	$0.134 + 0.010 \cdot \text{SL}$	$0.142 + 0.008 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.179	$0.159 + 0.010 \cdot \text{SL}$	$0.168 + 0.008 \cdot \text{SL}$	$0.183 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

FT2/FT2D2

Toggle Flip-Flop with Reset, 1X/2X Drive

Logic Symbol




Truth Table

CK	RN	Q (n+1)	QN (n+1)
	1	QN (n)	Q (n)
	1	Q (n)	QN (n)
x	0	0	1

Cell Data

Input Load (SL)				Gate Count	
FT2		FT2D2		FT2	FT2D2
CK	RN	CK	RN		
0.7	1.8	0.7	1.8	5.67	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FT2	FT2D2
Pulse Width Low (CK)	t _{PWL}	0.210	0.230
Pulse Width High (CK)	t _{PWH}	0.262	0.256
Pulse Width Low (RN)	t _{PWL}	0.316	0.353
Recovery Time (RN to CK)	t _{RC}	0.000	0.000
Removal Time (RN to CK)	t _{RM}	0.229	0.230

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FT2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.113	$0.060 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.100	$0.053 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.410	$0.379 + 0.015 \cdot \text{SL}$	$0.387 + 0.013 \cdot \text{SL}$	$0.392 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.402	$0.371 + 0.016 \cdot \text{SL}$	$0.379 + 0.013 \cdot \text{SL}$	$0.385 + 0.013 \cdot \text{SL}$
RN to Q	t_F	0.101	$0.053 + 0.024 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.174	$0.142 + 0.016 \cdot \text{SL}$	$0.151 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
CK to QN	t_R	0.112	$0.060 + 0.026 \cdot \text{SL}$	$0.055 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.055 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.315	$0.286 + 0.014 \cdot \text{SL}$	$0.293 + 0.013 \cdot \text{SL}$	$0.296 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.325	$0.293 + 0.016 \cdot \text{SL}$	$0.302 + 0.014 \cdot \text{SL}$	$0.309 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.110	$0.058 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_{PLH}	0.299	$0.270 + 0.014 \cdot \text{SL}$	$0.277 + 0.013 \cdot \text{SL}$	$0.279 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$
FT2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.086	$0.058 + 0.014 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$	$0.054 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.438	$0.420 + 0.009 \cdot \text{SL}$	$0.427 + 0.007 \cdot \text{SL}$	$0.440 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.431	$0.412 + 0.010 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.434 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.171	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.174 + 0.006 \cdot \text{SL}$
CK to QN	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.321	$0.303 + 0.009 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.326	$0.307 + 0.010 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.328 + 0.007 \cdot \text{SL}$
RN to QN	t_R	0.085	$0.058 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_{PLH}	0.308	$0.291 + 0.009 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.307 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LATCHES

Cell List

Cell Name	Function Description
LD1	D Latch with Active High
LD1D2	D Latch with Active High, 2X Drive
LD1A	D Latch with Active High, Tri-State Output
LD1D2A	D Latch with Active High, Tri-State Output, 2x Drive
LD1Q	D Latch with Active High, Q Output Only
LD1QD2	D Latch with Active High, Q Output Only, 2X Drive
LD2	D Latch with Active High, Reset
LD2D2	D Latch with Active High, Reset, 2X Drive
LD2Q	D Latch with Active High, Reset, Q Output Only
LD2QD2	D Latch with Active High, Reset, Q Output Only, 2X Drive
LD3	D Latch with Active High, Set
LD3D2	D Latch with Active High, Set, 2X Drive
LD4	D Latch with Active High, Reset, Set
LD4D2	D Latch with Active High, Reset, Set, 2X Drive
LD5	D Latch with Active Low
LD5D2	D Latch with Active Low, 2X Drive
LD5Q	D Latch with Active Low, Q Output Only
LD5QD2	D Latch with Active Low, Q Output Only, 2X Drive
LD6	D Latch with Active Low, Reset
LD6D2	D Latch with Active Low, Reset, 2X Drive
LD6Q	D Latch with Active Low, Reset, Q Output Only
LD6QD2	D Latch with Active Low, Reset, Q Output Only, 2X Drive
LD7	D Latch with Active Low, Set
LD7D2	D Latch with Active Low, Set, 2X Drive
LD8	D Latch with Active Low, Reset, Set
LD8D2	D Latch with Active Low, Reset, Set, 2X Drive
OAK_LDI2	D Latch with 2 Input, 2 Active High (for OAK core only)
OAK_LDI2D2	D Latch with 2 Input, 2 Active High, 2X Drive (for OAK core only)
OAK_LDI3	D Latch with 3 Input, 3 Active High (for OAK core only)
OAK_LDI3D2	D Latch with 3 Input, 3 Active High, 2X Drive (for OAK core only)


Cell List

Cell Name	Function Description
LS0	SR Latch
LS0D2	SR Latch with 2X Drive
LS1	SR Latch with Separate Inputs
LS1D2	SR Latch with Separate Inputs, 2X Drive

LD1/LD1D2

D Latch with Active High, 1X/2X Drive

Logic Symbol




Truth Table

D	G	Q (n+1)	QN (n+1)
0	1	0	1
1	1	1	0
x	0	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
LD1		LD1D2		LD1	LD1D2
D	G	D	G		
0.8	0.7	0.8	0.7	4.00	4.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1	LD1D2
Input Setup Time (D to G)	t _{SU}	0.199	0.214
Input Hold Time (D to G)	t _{HD}	0.077	0.057
Pulse Width High (G)	t _{PWH}	0.235	0.251

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.101	$0.047 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.043 + 0.023 \cdot \text{SL}$	$0.040 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.291	$0.264 + 0.014 \cdot \text{SL}$	$0.268 + 0.012 \cdot \text{SL}$	$0.269 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.304	$0.275 + 0.015 \cdot \text{SL}$	$0.280 + 0.013 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$
G to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.042 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.335	$0.308 + 0.014 \cdot \text{SL}$	$0.312 + 0.012 \cdot \text{SL}$	$0.313 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.346	$0.317 + 0.015 \cdot \text{SL}$	$0.323 + 0.013 \cdot \text{SL}$	$0.325 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.247	$0.219 + 0.014 \cdot \text{SL}$	$0.224 + 0.013 \cdot \text{SL}$	$0.228 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.240	$0.209 + 0.016 \cdot \text{SL}$	$0.217 + 0.013 \cdot \text{SL}$	$0.223 + 0.013 \cdot \text{SL}$
G to QN	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.050 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.290	$0.261 + 0.014 \cdot \text{SL}$	$0.267 + 0.013 \cdot \text{SL}$	$0.270 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.284	$0.253 + 0.015 \cdot \text{SL}$	$0.261 + 0.013 \cdot \text{SL}$	$0.267 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD1D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.329	$0.313 + 0.008 \cdot \text{SL}$	$0.318 + 0.007 \cdot \text{SL}$	$0.324 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.337	$0.320 + 0.009 \cdot \text{SL}$	$0.327 + 0.007 \cdot \text{SL}$	$0.336 + 0.006 \cdot \text{SL}$
G to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.370	$0.354 + 0.008 \cdot \text{SL}$	$0.360 + 0.007 \cdot \text{SL}$	$0.365 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.381	$0.363 + 0.009 \cdot \text{SL}$	$0.370 + 0.007 \cdot \text{SL}$	$0.379 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.253	$0.236 + 0.009 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.242	$0.223 + 0.009 \cdot \text{SL}$	$0.231 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
G to QN	t_R	0.082	$0.055 + 0.014 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.297	$0.280 + 0.009 \cdot \text{SL}$	$0.287 + 0.007 \cdot \text{SL}$	$0.294 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.284	$0.265 + 0.009 \cdot \text{SL}$	$0.273 + 0.007 \cdot \text{SL}$	$0.285 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD1A/LD1D2A

D Latch with Active High, Tri-State Output, 1x/2x Drive

Logic Symbol




Truth Table

D	G	E	Q (n+1)
x	x	0	Hi-Z
0	1	1	0
1	1	1	1
x	0	1	Q (n)

Cell Data

Input Load (SL)						Output Load (SL)		Gate Count	
LD1A			LD1D2A			LD1A	LD1D2A	LD1A	LD1D2A
D	G	E	D	G	E	Q	Q	4.33	4.67
0.8	0.7	1.4	0.6	0.6	1.6	0.9	1.2		

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1A	LD1D2A
Input Setup Time (D to G)	t _{SU}	0.195	0.197
Input Hold Time (D to G)	t _{HD}	0.081	0.074
Pulse Width High (G)	t _{PWH}	0.230	0.233

D Latch with Active High, Tri-State Output 1x/2x Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD1A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.117	$0.063 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.049 + 0.033 \cdot \text{SL}$	$0.045 + 0.034 \cdot \text{SL}$	$0.042 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.295	$0.268 + 0.014 \cdot \text{SL}$	$0.272 + 0.013 \cdot \text{SL}$	$0.275 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.302	$0.269 + 0.017 \cdot \text{SL}$	$0.271 + 0.016 \cdot \text{SL}$	$0.272 + 0.016 \cdot \text{SL}$
G to Q	t_R	0.117	$0.063 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.113	$0.048 + 0.033 \cdot \text{SL}$	$0.045 + 0.034 \cdot \text{SL}$	$0.042 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.339	$0.312 + 0.014 \cdot \text{SL}$	$0.316 + 0.013 \cdot \text{SL}$	$0.319 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.345	$0.311 + 0.017 \cdot \text{SL}$	$0.313 + 0.016 \cdot \text{SL}$	$0.314 + 0.016 \cdot \text{SL}$
E to Q	t_R	0.134	$0.082 + 0.026 \cdot \text{SL}$	$0.071 + 0.029 \cdot \text{SL}$	$0.062 + 0.030 \cdot \text{SL}$
	t_F	0.158	$0.096 + 0.031 \cdot \text{SL}$	$0.088 + 0.033 \cdot \text{SL}$	$0.069 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.117	$0.089 + 0.014 \cdot \text{SL}$	$0.095 + 0.013 \cdot \text{SL}$	$0.098 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.070	$0.026 + 0.022 \cdot \text{SL}$	$0.047 + 0.016 \cdot \text{SL}$	$0.048 + 0.016 \cdot \text{SL}$
	t_{PLZ}	0.099	$0.099 + 0.000 \cdot \text{SL}$	$0.099 + 0.000 \cdot \text{SL}$	$0.099 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.143	$0.143 + 0.000 \cdot \text{SL}$	$0.143 + 0.000 \cdot \text{SL}$	$0.143 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD1D2A


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.087	$0.059 + 0.014 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.047 + 0.015 \cdot \text{SL}$	$0.043 + 0.017 \cdot \text{SL}$	$0.035 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.294	$0.279 + 0.008 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.289 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.295	$0.277 + 0.009 \cdot \text{SL}$	$0.279 + 0.008 \cdot \text{SL}$	$0.281 + 0.008 \cdot \text{SL}$
G to Q	t_R	0.085	$0.058 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.047 + 0.016 \cdot \text{SL}$	$0.043 + 0.017 \cdot \text{SL}$	$0.035 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.336	$0.320 + 0.008 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.338	$0.321 + 0.009 \cdot \text{SL}$	$0.323 + 0.008 \cdot \text{SL}$	$0.325 + 0.008 \cdot \text{SL}$
E to Q	t_R	0.109	$0.090 + 0.009 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$	$0.060 + 0.015 \cdot \text{SL}$
	t_F	0.111	$0.075 + 0.018 \cdot \text{SL}$	$0.085 + 0.016 \cdot \text{SL}$	$0.061 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.105	$0.087 + 0.009 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.104 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.036	$0.006 + 0.015 \cdot \text{SL}$	$0.028 + 0.009 \cdot \text{SL}$	$0.042 + 0.008 \cdot \text{SL}$
	t_{PLZ}	0.099	$0.099 + 0.000 \cdot \text{SL}$	$0.099 + 0.000 \cdot \text{SL}$	$0.099 + 0.000 \cdot \text{SL}$
	t_{PHZ}	0.163	$0.163 + 0.000 \cdot \text{SL}$	$0.163 + 0.000 \cdot \text{SL}$	$0.163 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD1Q/LD1QD2

D Latch with Active High, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	G	Q (n+1)
0	1	0
1	1	1
x	0	Q (n)

Cell Data

Input Load (SL)				Gate Count	
LD1Q		LD1QD2		LD1Q	LD1QD2
D	G	D	G		
0.8	0.7	0.8	0.7	3.33	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1Q	LD1QD2
Input Setup Time (D to G)	t _{SU}	0.184	0.189
Input Hold Time (D to G)	t _{HD}	0.088	0.082
Pulse Width High (G)	t _{PWH}	0.223	0.226

D Latch with Active High, Q Output Only, 1X/2X Drive**Switching Characteristics**(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**LD1Q**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.099	$0.046 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.028 \cdot \text{SL}$
	t_F	0.087	$0.041 + 0.023 \cdot \text{SL}$	$0.040 + 0.023 \cdot \text{SL}$	$0.033 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.257	$0.231 + 0.013 \cdot \text{SL}$	$0.234 + 0.012 \cdot \text{SL}$	$0.235 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.270	$0.242 + 0.014 \cdot \text{SL}$	$0.247 + 0.013 \cdot \text{SL}$	$0.250 + 0.012 \cdot \text{SL}$
G to Q	t_R	0.099	$0.046 + 0.026 \cdot \text{SL}$	$0.041 + 0.028 \cdot \text{SL}$	$0.037 + 0.028 \cdot \text{SL}$
	t_F	0.086	$0.040 + 0.023 \cdot \text{SL}$	$0.041 + 0.023 \cdot \text{SL}$	$0.034 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.307	$0.280 + 0.013 \cdot \text{SL}$	$0.284 + 0.012 \cdot \text{SL}$	$0.285 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.315	$0.287 + 0.014 \cdot \text{SL}$	$0.293 + 0.013 \cdot \text{SL}$	$0.295 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$ **LD1QD2**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.073	$0.046 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$	$0.036 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.042 + 0.012 \cdot \text{SL}$	$0.045 + 0.011 \cdot \text{SL}$	$0.039 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.267	$0.251 + 0.008 \cdot \text{SL}$	$0.256 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.273	$0.255 + 0.009 \cdot \text{SL}$	$0.263 + 0.007 \cdot \text{SL}$	$0.272 + 0.006 \cdot \text{SL}$
G to Q	t_R	0.072	$0.044 + 0.014 \cdot \text{SL}$	$0.045 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.044 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$	$0.039 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.309	$0.293 + 0.008 \cdot \text{SL}$	$0.298 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.317	$0.299 + 0.009 \cdot \text{SL}$	$0.307 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD2/LD2D2

D Latch with Active High, Reset, 1X/2X Drive

Logic Symbol




Truth Table

D	G	RN	Q (n+1)	QN (n+1)
0	1	1	0	1
1	1	1	1	0
x	0	1	Q (n)	QN (n)
x	x	0	0	1

Cell Data

Input Load (SL)						Gate Count	
LD2			LD2D2			LD2	LD2D2
D	G	RN	D	G	RN		
0.7	0.7	1.0	0.7	0.7	1.0	4.33	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD2	LD2D2
Input Setup Time (D to G)	t_{SU}	0.253	0.260
Input Hold Time (D to G)	t_{HD}	0.011	0.003
Pulse Width High (G)	t_{PWH}	0.238	0.256
Pulse Width Low (RN)	t_{PWL}	0.250	0.290
Recovery Time (RN to G)	t_{RC}	0.047	0.070
Removal Time (RN to G)	t_{RM}	0.173	0.150

D Latch with Active High, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.115	$0.060 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.308	$0.278 + 0.015 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.307	$0.276 + 0.015 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$
G to Q	t_R	0.115	$0.059 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.024 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.300	$0.270 + 0.015 \cdot \text{SL}$	$0.277 + 0.013 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.294	$0.263 + 0.015 \cdot \text{SL}$	$0.271 + 0.013 \cdot \text{SL}$	$0.278 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.115	$0.060 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.054 + 0.023 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.151	$0.121 + 0.015 \cdot \text{SL}$	$0.128 + 0.013 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.170	$0.139 + 0.016 \cdot \text{SL}$	$0.147 + 0.013 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.360	$0.333 + 0.014 \cdot \text{SL}$	$0.337 + 0.012 \cdot \text{SL}$	$0.338 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.366	$0.337 + 0.015 \cdot \text{SL}$	$0.344 + 0.013 \cdot \text{SL}$	$0.347 + 0.013 \cdot \text{SL}$
G to QN	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.023 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.347	$0.320 + 0.014 \cdot \text{SL}$	$0.324 + 0.012 \cdot \text{SL}$	$0.325 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.358	$0.329 + 0.015 \cdot \text{SL}$	$0.336 + 0.013 \cdot \text{SL}$	$0.339 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.103	$0.049 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.040 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.222	$0.195 + 0.013 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.209	$0.180 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD2/LD2D2

D Latch with Active High, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD2D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.088	$0.061 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.307	$0.289 + 0.009 \cdot \text{SL}$	$0.297 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.307	$0.288 + 0.010 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$
G to Q	t_R	0.087	$0.059 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.305	$0.287 + 0.009 \cdot \text{SL}$	$0.294 + 0.007 \cdot \text{SL}$	$0.306 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.300	$0.280 + 0.010 \cdot \text{SL}$	$0.289 + 0.007 \cdot \text{SL}$	$0.302 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.090	$0.065 + 0.012 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.150	$0.132 + 0.009 \cdot \text{SL}$	$0.139 + 0.007 \cdot \text{SL}$	$0.152 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.170	$0.151 + 0.010 \cdot \text{SL}$	$0.159 + 0.007 \cdot \text{SL}$	$0.173 + 0.007 \cdot \text{SL}$
D to QN	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.395	$0.379 + 0.008 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.390 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.399	$0.380 + 0.009 \cdot \text{SL}$	$0.388 + 0.007 \cdot \text{SL}$	$0.398 + 0.006 \cdot \text{SL}$
G to QN	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.388	$0.371 + 0.008 \cdot \text{SL}$	$0.377 + 0.007 \cdot \text{SL}$	$0.383 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.396	$0.378 + 0.009 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.395 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.259	$0.242 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$	$0.254 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.241	$0.223 + 0.009 \cdot \text{SL}$	$0.231 + 0.007 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD2Q/LD2QD2

D Latch with Active High, Reset, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	G	RN	Q (n+1)
0	1	1	0
1	1	1	1
x	0	1	Q (n)
x	x	0	0

Cell Data

Input Load (SL)						Gate Count	
LD2Q			LD2QD2			LD2Q	LD2QD2
D	G	RN	D	G	RN		
0.8	0.7	1.0	0.9	0.8	1.0	3.67	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD2Q	LD2QD2
Input Setup Time (D to G)	t_{SU}	0.192	0.194
Input Hold Time (D to G)	t_{HD}	0.081	0.080
Pulse Width High (G)	t_{PWH}	0.229	0.232
Pulse Width Low (RN)	t_{PWL}	0.269	0.285
Recovery Time (RN to G)	t_{RC}	0.000	0.000
Removal Time (RN to G)	t_{RM}	0.337	0.321

LD2Q/LD2QD2

D Latch with Active High, Reset, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD2Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.107	$0.053 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.285	$0.256 + 0.015 \cdot \text{SL}$	$0.263 + 0.013 \cdot \text{SL}$	$0.266 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.293	$0.263 + 0.015 \cdot \text{SL}$	$0.270 + 0.013 \cdot \text{SL}$	$0.274 + 0.013 \cdot \text{SL}$
G to Q	t_R	0.107	$0.053 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.327	$0.297 + 0.015 \cdot \text{SL}$	$0.304 + 0.013 \cdot \text{SL}$	$0.308 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.338	$0.308 + 0.015 \cdot \text{SL}$	$0.315 + 0.013 \cdot \text{SL}$	$0.319 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.053 + 0.022 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.135	$0.105 + 0.015 \cdot \text{SL}$	$0.112 + 0.013 \cdot \text{SL}$	$0.116 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.159	$0.129 + 0.015 \cdot \text{SL}$	$0.137 + 0.013 \cdot \text{SL}$	$0.141 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD2QD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.081	$0.053 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.044 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.289	$0.272 + 0.009 \cdot \text{SL}$	$0.279 + 0.007 \cdot \text{SL}$	$0.289 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.294	$0.275 + 0.009 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.295 + 0.006 \cdot \text{SL}$
G to Q	t_R	0.080	$0.052 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.044 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.331	$0.314 + 0.009 \cdot \text{SL}$	$0.321 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.339	$0.320 + 0.009 \cdot \text{SL}$	$0.328 + 0.007 \cdot \text{SL}$	$0.340 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.083	$0.056 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.142	$0.124 + 0.009 \cdot \text{SL}$	$0.131 + 0.007 \cdot \text{SL}$	$0.142 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.161	$0.142 + 0.009 \cdot \text{SL}$	$0.150 + 0.007 \cdot \text{SL}$	$0.162 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD3/LD3D2

D Latch with Active High, Set, 1X/2X Drive

Logic Symbol




Truth Table

D	G	SN	Q (n+1)	QN (n+1)
0	1	1	0	1
1	1	1	1	0
x	0	1	Q (n)	QN (n)
x	x	0	1	0

Cell Data

Input Load (SL)						Gate Count	
LD3			LD3D2			LD3	LD3D2
D	G	SN	D	G	SN		
0.8	0.7	1.0	0.8	0.7	1.0	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD3	LD3D2
Input Setup Time (D to G)	t_{SU}	0.204	0.218
Input Hold Time (D to G)	t_{HD}	0.065	0.047
Pulse Width High (G)	t_{PWH}	0.238	0.253
Pulse Width Low (SN)	t_{PWL}	0.250	0.292
Recovery Time (SN to G)	t_{RC}	0.049	0.073
Removal Time (SN to G)	t_{RM}	0.170	0.146

LD3/LD3D2

D Latch with Active High, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.304	$0.277 + 0.013 \cdot \text{SL}$	$0.281 + 0.012 \cdot \text{SL}$	$0.282 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.317	$0.287 + 0.015 \cdot \text{SL}$	$0.294 + 0.013 \cdot \text{SL}$	$0.297 + 0.013 \cdot \text{SL}$
G to Q	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.047 + 0.022 \cdot \text{SL}$	$0.042 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.345	$0.318 + 0.014 \cdot \text{SL}$	$0.322 + 0.012 \cdot \text{SL}$	$0.323 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.357	$0.328 + 0.015 \cdot \text{SL}$	$0.334 + 0.013 \cdot \text{SL}$	$0.338 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.049 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.040 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.047 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.222	$0.195 + 0.013 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.209	$0.180 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.116	$0.061 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.258	$0.228 + 0.015 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$	$0.242 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.251	$0.220 + 0.015 \cdot \text{SL}$	$0.228 + 0.013 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$
G to QN	t_R	0.115	$0.059 + 0.028 \cdot \text{SL}$	$0.059 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.299	$0.269 + 0.015 \cdot \text{SL}$	$0.276 + 0.013 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.292	$0.262 + 0.015 \cdot \text{SL}$	$0.269 + 0.013 \cdot \text{SL}$	$0.276 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.115	$0.060 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.054 + 0.023 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.151	$0.121 + 0.015 \cdot \text{SL}$	$0.128 + 0.013 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.170	$0.139 + 0.016 \cdot \text{SL}$	$0.147 + 0.013 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Latch with Active High, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD3D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.325 + 0.008 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$	$0.336 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.350	$0.333 + 0.009 \cdot \text{SL}$	$0.340 + 0.007 \cdot \text{SL}$	$0.349 + 0.006 \cdot \text{SL}$
G to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.384	$0.368 + 0.008 \cdot \text{SL}$	$0.373 + 0.007 \cdot \text{SL}$	$0.379 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.392	$0.374 + 0.009 \cdot \text{SL}$	$0.381 + 0.007 \cdot \text{SL}$	$0.391 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.244 + 0.008 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$	$0.255 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.240	$0.223 + 0.009 \cdot \text{SL}$	$0.230 + 0.007 \cdot \text{SL}$	$0.239 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.088	$0.061 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.242 + 0.009 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.254	$0.235 + 0.010 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$
G to QN	t_R	0.089	$0.061 + 0.014 \cdot \text{SL}$	$0.062 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.302	$0.283 + 0.009 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.303 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.297	$0.277 + 0.010 \cdot \text{SL}$	$0.286 + 0.007 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.150	$0.132 + 0.009 \cdot \text{SL}$	$0.140 + 0.007 \cdot \text{SL}$	$0.152 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.172	$0.153 + 0.010 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD4/LD4D2

D Latch with Active High, Reset, Set, 1X/2X Drive

Logic Symbol




Truth Table

D	G	RN	SN	Q (n+1)	QN (n+1)
0	1	1	1	0	1
1	1	1	1	1	0
x	0	1	1	Q (n)	QN (n)
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	1	0

Cell Data

Input Load (SL)								Gate Count	
LD4				LD4D2				LD4	LD4D2
D	G	SN	RN	D	G	SN	RN		
0.7	0.7	1.0	1.0	0.7	0.7	1.0	1.0	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD4	LD4D2
Input Setup Time (D to G)	t_{SU}	0.262	0.282
Input Hold Time (D to G)	t_{HD}	0.026	0.015
Pulse Width High (G)	t_{PWH}	0.256	0.276
Pulse Width Low (SN)	t_{PWL}	0.658	0.705
Recovery Time (SN to G)	t_{RC}	0.000	0.000
Removal Time (SN to G)	t_{RM}	0.599	0.576
Pulse Width Low (RN)	t_{PWL}	0.313	0.350
Recovery Time (RN to G)	t_{RC}	0.066	0.081
Removal Time (RN to G)	t_{RM}	0.163	0.149
Recovery Time (SN to RN)	t_{RC}	0.233	0.275
Removal Time (SN to RN)	t_{RM}	0.000	0.000

D Latch with Active High, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.422	$0.395 + 0.013 \cdot \text{SL}$	$0.399 + 0.012 \cdot \text{SL}$	$0.401 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.431	$0.402 + 0.015 \cdot \text{SL}$	$0.408 + 0.013 \cdot \text{SL}$	$0.412 + 0.012 \cdot \text{SL}$
G to Q	t_R	0.102	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.418	$0.391 + 0.014 \cdot \text{SL}$	$0.395 + 0.012 \cdot \text{SL}$	$0.397 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.417	$0.388 + 0.015 \cdot \text{SL}$	$0.395 + 0.013 \cdot \text{SL}$	$0.398 + 0.012 \cdot \text{SL}$
SN to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.230	$0.203 + 0.014 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.212	$0.183 + 0.015 \cdot \text{SL}$	$0.190 + 0.013 \cdot \text{SL}$	$0.193 + 0.012 \cdot \text{SL}$
RN to Q	t_R	0.102	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.266	$0.239 + 0.014 \cdot \text{SL}$	$0.243 + 0.012 \cdot \text{SL}$	$0.245 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.291	$0.261 + 0.015 \cdot \text{SL}$	$0.268 + 0.013 \cdot \text{SL}$	$0.272 + 0.012 \cdot \text{SL}$
D to QN	t_R	0.112	$0.057 + 0.027 \cdot \text{SL}$	$0.057 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.368	$0.338 + 0.015 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$	$0.352 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.364	$0.334 + 0.015 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.349 + 0.012 \cdot \text{SL}$
G to QN	t_R	0.112	$0.057 + 0.027 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.355	$0.325 + 0.015 \cdot \text{SL}$	$0.332 + 0.013 \cdot \text{SL}$	$0.339 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.360	$0.329 + 0.015 \cdot \text{SL}$	$0.337 + 0.013 \cdot \text{SL}$	$0.345 + 0.012 \cdot \text{SL}$
SN to QN	t_R	0.113	$0.060 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.100	$0.055 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.127 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.172	$0.141 + 0.016 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.157 + 0.012 \cdot \text{SL}$
RN to QN	t_R	0.112	$0.058 + 0.027 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.228	$0.198 + 0.015 \cdot \text{SL}$	$0.205 + 0.013 \cdot \text{SL}$	$0.212 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.178 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.193 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD4/LD4D2

D Latch with Active High, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD4D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.464	$0.448 + 0.008 \cdot \text{SL}$	$0.454 + 0.007 \cdot \text{SL}$	$0.460 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.466	$0.448 + 0.009 \cdot \text{SL}$	$0.456 + 0.007 \cdot \text{SL}$	$0.466 + 0.006 \cdot \text{SL}$
G to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.463	$0.446 + 0.008 \cdot \text{SL}$	$0.452 + 0.007 \cdot \text{SL}$	$0.458 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.454	$0.437 + 0.009 \cdot \text{SL}$	$0.444 + 0.007 \cdot \text{SL}$	$0.455 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.265	$0.249 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.247	$0.229 + 0.009 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.247 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.301	$0.285 + 0.008 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.325	$0.307 + 0.009 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.325 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.086	$0.059 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.372	$0.354 + 0.009 \cdot \text{SL}$	$0.361 + 0.007 \cdot \text{SL}$	$0.373 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.372	$0.353 + 0.009 \cdot \text{SL}$	$0.361 + 0.007 \cdot \text{SL}$	$0.375 + 0.006 \cdot \text{SL}$
G to QN	t_R	0.087	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.360	$0.342 + 0.009 \cdot \text{SL}$	$0.350 + 0.007 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.370	$0.351 + 0.009 \cdot \text{SL}$	$0.359 + 0.007 \cdot \text{SL}$	$0.373 + 0.006 \cdot \text{SL}$
SN to QN	t_R	0.088	$0.060 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.055 + 0.012 \cdot \text{SL}$	$0.059 + 0.011 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.152	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.154 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.087	$0.058 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.231	$0.213 + 0.009 \cdot \text{SL}$	$0.221 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.209	$0.190 + 0.009 \cdot \text{SL}$	$0.198 + 0.007 \cdot \text{SL}$	$0.212 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD5/LD5D2

D Latch with Active Low, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	Q (n+1)	QN (n+1)
0	0	0	1
1	0	1	0
x	1	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
LD5		LD5D2		LD5	LD5D2
D	GN	D	GN		
0.9	0.7	0.9	0.7	4.00	4.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD5	LD5D2
Input Setup Time (D to GN)	t_{SU}	0.189	0.201
Input Hold Time (D to GN)	t_{HD}	0.058	0.039
Pulse Width Low (GN)	t_{PWL}	0.217	0.234

LD5/LD5D2

D Latch with Active Low, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.101	$0.047 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.043 + 0.023 \cdot \text{SL}$	$0.040 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.291	$0.264 + 0.014 \cdot \text{SL}$	$0.267 + 0.012 \cdot \text{SL}$	$0.268 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.303	$0.274 + 0.015 \cdot \text{SL}$	$0.280 + 0.013 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$
GN to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.042 + 0.023 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.321	$0.294 + 0.014 \cdot \text{SL}$	$0.298 + 0.012 \cdot \text{SL}$	$0.299 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.358	$0.329 + 0.015 \cdot \text{SL}$	$0.335 + 0.013 \cdot \text{SL}$	$0.338 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.247	$0.219 + 0.014 \cdot \text{SL}$	$0.224 + 0.013 \cdot \text{SL}$	$0.227 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.240	$0.209 + 0.015 \cdot \text{SL}$	$0.217 + 0.013 \cdot \text{SL}$	$0.223 + 0.013 \cdot \text{SL}$
GN to QN	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.049 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.302	$0.274 + 0.014 \cdot \text{SL}$	$0.279 + 0.013 \cdot \text{SL}$	$0.282 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.271	$0.240 + 0.015 \cdot \text{SL}$	$0.248 + 0.013 \cdot \text{SL}$	$0.254 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD5D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.329	$0.313 + 0.008 \cdot \text{SL}$	$0.319 + 0.007 \cdot \text{SL}$	$0.324 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.338	$0.320 + 0.009 \cdot \text{SL}$	$0.327 + 0.007 \cdot \text{SL}$	$0.336 + 0.006 \cdot \text{SL}$
GN to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.364	$0.348 + 0.008 \cdot \text{SL}$	$0.353 + 0.007 \cdot \text{SL}$	$0.359 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.393	$0.375 + 0.009 \cdot \text{SL}$	$0.383 + 0.007 \cdot \text{SL}$	$0.392 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.084	$0.057 + 0.013 \cdot \text{SL}$	$0.057 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.254	$0.237 + 0.009 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.243	$0.224 + 0.009 \cdot \text{SL}$	$0.232 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
GN to QN	t_R	0.083	$0.057 + 0.013 \cdot \text{SL}$	$0.056 + 0.013 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.049 + 0.013 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.309	$0.292 + 0.009 \cdot \text{SL}$	$0.299 + 0.007 \cdot \text{SL}$	$0.306 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.277	$0.259 + 0.009 \cdot \text{SL}$	$0.267 + 0.007 \cdot \text{SL}$	$0.279 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD5Q/LD5QD2

D Latch with Active Low, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	Q (n+1)
0	0	0
1	0	1
x	1	Q (n)

Cell Data

Input Load (SL)				Gate Count	
LD5Q		LD5QD2		LD5Q	LD5QD2
D	GN	D	GN		
0.9	0.7	0.9	0.7	3.33	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD5Q	LD5QD2
Input Setup Time (D to GN)	t _{SU}	0.179	0.184
Input Hold Time (D to GN)	t _{HD}	0.074	0.066
Pulse Width Low (GN)	t _{PWL}	0.208	0.212

LD5Q/LD5QD2

D Latch with Active Low, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD5Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.099	$0.045 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.028 \cdot \text{SL}$
	t_F	0.087	$0.042 + 0.023 \cdot \text{SL}$	$0.040 + 0.023 \cdot \text{SL}$	$0.033 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.258	$0.231 + 0.013 \cdot \text{SL}$	$0.235 + 0.012 \cdot \text{SL}$	$0.236 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.270	$0.242 + 0.014 \cdot \text{SL}$	$0.248 + 0.013 \cdot \text{SL}$	$0.250 + 0.012 \cdot \text{SL}$
GN to Q	t_R	0.099	$0.045 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.028 \cdot \text{SL}$
	t_F	0.088	$0.043 + 0.022 \cdot \text{SL}$	$0.039 + 0.023 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.294	$0.267 + 0.013 \cdot \text{SL}$	$0.270 + 0.012 \cdot \text{SL}$	$0.271 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.327	$0.298 + 0.014 \cdot \text{SL}$	$0.304 + 0.013 \cdot \text{SL}$	$0.306 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD5QD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.073	$0.046 + 0.013 \cdot \text{SL}$	$0.044 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.043 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$	$0.039 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.272	$0.256 + 0.008 \cdot \text{SL}$	$0.261 + 0.007 \cdot \text{SL}$	$0.266 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.276	$0.258 + 0.009 \cdot \text{SL}$	$0.265 + 0.007 \cdot \text{SL}$	$0.274 + 0.006 \cdot \text{SL}$
GN to Q	t_R	0.073	$0.046 + 0.014 \cdot \text{SL}$	$0.046 + 0.014 \cdot \text{SL}$	$0.037 + 0.014 \cdot \text{SL}$
	t_F	0.067	$0.044 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$	$0.039 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.307	$0.291 + 0.008 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.301 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.332	$0.314 + 0.009 \cdot \text{SL}$	$0.321 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD6/LD6D2

D Latch with Active Low, Reset, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	RN	Q (n+1)	QN (n+1)
0	0	1	0	1
1	0	1	1	0
x	1	1	Q (n)	QN (n)
x	x	0	0	1

Cell Data

Input Load (SL)						Gate Count	
LD6			LD6D2			LD6	LD6D2
D	GN	RN	D	GN	RN		
0.7	0.7	1.0	0.7	0.7	1.0	4.33	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD6	LD6D2
Input Setup Time (D to GN)	t_{SU}	0.252	0.260
Input Hold Time (D to GN)	t_{HD}	0.007	0.000
Pulse Width Low (GN)	t_{PWL}	0.220	0.233
Pulse Width Low (RN)	t_{PWL}	0.252	0.291
Recovery Time (RN to GN)	t_{RC}	0.025	0.046
Removal Time (RN to GN)	t_{RM}	0.195	0.174

LD6/LD6D2

D Latch with Active Low, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.116	$0.061 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.309	$0.279 + 0.015 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.307	$0.277 + 0.015 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.291 + 0.013 \cdot \text{SL}$
GN to Q	t_R	0.115	$0.060 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.313	$0.283 + 0.015 \cdot \text{SL}$	$0.290 + 0.013 \cdot \text{SL}$	$0.297 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.283	$0.253 + 0.015 \cdot \text{SL}$	$0.260 + 0.013 \cdot \text{SL}$	$0.267 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.115	$0.060 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.054 + 0.023 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.127 + 0.013 \cdot \text{SL}$	$0.133 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.170	$0.139 + 0.015 \cdot \text{SL}$	$0.147 + 0.013 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.022 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.360	$0.333 + 0.014 \cdot \text{SL}$	$0.337 + 0.012 \cdot \text{SL}$	$0.338 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.367	$0.338 + 0.015 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$	$0.348 + 0.013 \cdot \text{SL}$
GN to QN	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.337	$0.309 + 0.014 \cdot \text{SL}$	$0.314 + 0.012 \cdot \text{SL}$	$0.315 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.372	$0.343 + 0.015 \cdot \text{SL}$	$0.350 + 0.013 \cdot \text{SL}$	$0.353 + 0.013 \cdot \text{SL}$
RN to QN	t_R	0.104	$0.051 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$	$0.040 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.222	$0.195 + 0.013 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$	$0.200 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.209	$0.180 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Latch with Active Low, Reset, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD6D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.089	$0.061 + 0.014 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.307	$0.289 + 0.009 \cdot \text{SL}$	$0.297 + 0.007 \cdot \text{SL}$	$0.309 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.307	$0.288 + 0.010 \cdot \text{SL}$	$0.296 + 0.007 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$
GN to Q	t_R	0.089	$0.062 + 0.014 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.317	$0.299 + 0.009 \cdot \text{SL}$	$0.306 + 0.007 \cdot \text{SL}$	$0.319 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.286	$0.267 + 0.010 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.289 + 0.007 \cdot \text{SL}$
RN to Q	t_R	0.090	$0.065 + 0.012 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.150	$0.132 + 0.009 \cdot \text{SL}$	$0.140 + 0.007 \cdot \text{SL}$	$0.152 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.170	$0.151 + 0.010 \cdot \text{SL}$	$0.160 + 0.007 \cdot \text{SL}$	$0.173 + 0.007 \cdot \text{SL}$
D to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.395	$0.379 + 0.008 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.390 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.399	$0.381 + 0.009 \cdot \text{SL}$	$0.388 + 0.007 \cdot \text{SL}$	$0.398 + 0.006 \cdot \text{SL}$
GN to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.374	$0.358 + 0.008 \cdot \text{SL}$	$0.364 + 0.007 \cdot \text{SL}$	$0.370 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.408	$0.390 + 0.009 \cdot \text{SL}$	$0.398 + 0.007 \cdot \text{SL}$	$0.407 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.259	$0.243 + 0.008 \cdot \text{SL}$	$0.248 + 0.007 \cdot \text{SL}$	$0.254 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.241	$0.223 + 0.009 \cdot \text{SL}$	$0.231 + 0.007 \cdot \text{SL}$	$0.241 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD6Q/LD6QD2

D Latch with Active Low, Reset, Q Output Only, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	RN	Q (n+1)
0	0	1	0
1	0	1	1
x	1	1	Q (n)
x	x	0	0

Cell Data

Input Load (SL)						Gate Count	
LD6Q			LD6QD2			LD6Q	LD6QD2
D	GN	RN	D	GN	RN		
0.9	0.7	1.0	0.9	0.8	1.0	3.67	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD6Q	LD6QD2
Input Setup Time (D to GN)	t_{SU}	0.182	0.184
Input Hold Time (D to GN)	t_{HD}	0.062	0.060
Pulse Width Low (GN)	t_{PWL}	0.212	0.213
Pulse Width Low (RN)	t_{PWL}	0.269	0.286
Recovery Time (RN to GN)	t_{RC}	0.000	0.000
Removal Time (RN to GN)	t_{RM}	0.329	0.316

D Latch with Active Low, Reset, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD6Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.107	$0.053 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.047 + 0.023 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.285	$0.256 + 0.015 \cdot \text{SL}$	$0.263 + 0.013 \cdot \text{SL}$	$0.266 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.293	$0.263 + 0.015 \cdot \text{SL}$	$0.270 + 0.013 \cdot \text{SL}$	$0.274 + 0.013 \cdot \text{SL}$
GN to Q	t_R	0.107	$0.052 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$
	t_F	0.092	$0.046 + 0.023 \cdot \text{SL}$	$0.045 + 0.024 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.318	$0.289 + 0.015 \cdot \text{SL}$	$0.296 + 0.013 \cdot \text{SL}$	$0.299 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.347	$0.317 + 0.015 \cdot \text{SL}$	$0.325 + 0.013 \cdot \text{SL}$	$0.328 + 0.013 \cdot \text{SL}$
RN to Q	t_R	0.109	$0.055 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.053 + 0.022 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.135	$0.105 + 0.015 \cdot \text{SL}$	$0.112 + 0.013 \cdot \text{SL}$	$0.116 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.159	$0.129 + 0.015 \cdot \text{SL}$	$0.137 + 0.013 \cdot \text{SL}$	$0.141 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD6QD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.081	$0.053 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.044 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.289	$0.272 + 0.009 \cdot \text{SL}$	$0.279 + 0.007 \cdot \text{SL}$	$0.289 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.294	$0.275 + 0.009 \cdot \text{SL}$	$0.283 + 0.007 \cdot \text{SL}$	$0.295 + 0.006 \cdot \text{SL}$
GN to Q	t_R	0.080	$0.052 + 0.014 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.043 + 0.013 \cdot \text{SL}$	$0.050 + 0.012 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.323	$0.305 + 0.009 \cdot \text{SL}$	$0.312 + 0.007 \cdot \text{SL}$	$0.323 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.347	$0.329 + 0.009 \cdot \text{SL}$	$0.337 + 0.007 \cdot \text{SL}$	$0.348 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.083	$0.056 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.141	$0.124 + 0.009 \cdot \text{SL}$	$0.131 + 0.007 \cdot \text{SL}$	$0.141 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.160	$0.142 + 0.009 \cdot \text{SL}$	$0.150 + 0.007 \cdot \text{SL}$	$0.162 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD7/LD7D2

D Latch with Active Low, Set, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	SN	Q (n+1)	QN (n+1)
0	0	1	0	1
1	0	1	1	0
x	1	1	Q (n)	QN (n)
x	x	0	1	0

Cell Data

Input Load (SL)						Gate Count	
LD7			LD7D2			LD7	LD7D2
D	GN	SN	D	GN	SN		
0.8	0.7	1.0	0.9	0.7	1.0	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD7	LD7D2
Input Setup Time (D to GN)	t _{SU}	0.197	0.209
Input Hold Time (D to GN)	t _{HD}	0.054	0.039
Pulse Width Low (GN)	t _{PWL}	0.220	0.234
Pulse Width Low (SN)	t _{PWL}	0.252	0.292
Recovery Time (SN to GN)	t _{RC}	0.028	0.052
Removal Time (SN to GN)	t _{RM}	0.192	0.168

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.023 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.304	$0.277 + 0.014 \cdot \text{SL}$	$0.281 + 0.012 \cdot \text{SL}$	$0.282 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.317	$0.288 + 0.015 \cdot \text{SL}$	$0.295 + 0.013 \cdot \text{SL}$	$0.298 + 0.013 \cdot \text{SL}$
GN to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.044 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.037 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.335	$0.308 + 0.014 \cdot \text{SL}$	$0.312 + 0.012 \cdot \text{SL}$	$0.313 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.371	$0.342 + 0.015 \cdot \text{SL}$	$0.348 + 0.013 \cdot \text{SL}$	$0.351 + 0.013 \cdot \text{SL}$
SN to Q	t_R	0.103	$0.050 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.047 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.222	$0.195 + 0.013 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$	$0.199 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.179 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.189 + 0.013 \cdot \text{SL}$
D to QN	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.049 + 0.024 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.259	$0.229 + 0.015 \cdot \text{SL}$	$0.236 + 0.013 \cdot \text{SL}$	$0.242 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.251	$0.221 + 0.015 \cdot \text{SL}$	$0.228 + 0.013 \cdot \text{SL}$	$0.235 + 0.013 \cdot \text{SL}$
GN to QN	t_R	0.115	$0.060 + 0.028 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.312	$0.282 + 0.015 \cdot \text{SL}$	$0.289 + 0.013 \cdot \text{SL}$	$0.296 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.282	$0.252 + 0.015 \cdot \text{SL}$	$0.259 + 0.013 \cdot \text{SL}$	$0.266 + 0.013 \cdot \text{SL}$
SN to QN	t_R	0.115	$0.060 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.054 + 0.023 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.127 + 0.013 \cdot \text{SL}$	$0.133 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.169	$0.138 + 0.015 \cdot \text{SL}$	$0.147 + 0.013 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LD7/LD7D2

D Latch with Active Low, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD7D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.341	$0.325 + 0.008 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$	$0.336 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.350	$0.332 + 0.009 \cdot \text{SL}$	$0.340 + 0.007 \cdot \text{SL}$	$0.349 + 0.006 \cdot \text{SL}$
GN to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.372	$0.356 + 0.008 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.404	$0.386 + 0.009 \cdot \text{SL}$	$0.394 + 0.007 \cdot \text{SL}$	$0.403 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.244 + 0.008 \cdot \text{SL}$	$0.249 + 0.006 \cdot \text{SL}$	$0.255 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.240	$0.222 + 0.009 \cdot \text{SL}$	$0.229 + 0.007 \cdot \text{SL}$	$0.239 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.088	$0.061 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.050 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.051 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.260	$0.242 + 0.009 \cdot \text{SL}$	$0.250 + 0.007 \cdot \text{SL}$	$0.262 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.254	$0.235 + 0.010 \cdot \text{SL}$	$0.243 + 0.007 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$
GN to QN	t_R	0.088	$0.061 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.314	$0.296 + 0.009 \cdot \text{SL}$	$0.304 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.285	$0.266 + 0.010 \cdot \text{SL}$	$0.275 + 0.007 \cdot \text{SL}$	$0.288 + 0.007 \cdot \text{SL}$
SN to QN	t_R	0.090	$0.066 + 0.012 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.150	$0.132 + 0.009 \cdot \text{SL}$	$0.140 + 0.007 \cdot \text{SL}$	$0.152 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.172	$0.153 + 0.010 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LD8/LD8D2

D Latch with Active Low, Reset, Set, 1X/2X Drive

Logic Symbol




Truth Table

D	GN	RN	SN	Q (n+1)	QN (n+1)
0	0	1	1	0	1
1	0	1	1	1	0
x	1	1	1	Q (n)	QN (n)
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	1	0

Cell Data

Input Load (SL)								Gate Count	
LD8				LD8D2				LD8	LD8D2
D	GN	SN	RN	D	GN	SN	RN		
0.7	0.7	1.0	1.0	0.7	0.7	0.9	1.0	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD8	LD8D2
Input Setup Time (D to GN)	t_{SU}	0.252	0.259
Input Hold Time (D to GN)	t_{HD}	0.000	0.000
Pulse Width Low (GN)	t_{PWL}	0.231	0.252
Pulse Width Low (SN)	t_{PWL}	0.657	0.706
Recovery Time (SN to GN)	t_{RC}	0.000	0.000
Removal Time (SN to GN)	t_{RM}	0.523	0.522
Pulse Width Low (RN)	t_{PWL}	0.313	0.350
Recovery Time (RN to GN)	t_{RC}	0.027	0.054
Removal Time (RN to GN)	t_{RM}	0.198	0.172
Recovery Time (SN to RN)	t_{RC}	0.233	0.275
Removal Time (SN to RN)	t_{RM}	0.000	0.000

LD8/LD8D2

D Latch with Active Low, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.043 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.422	$0.395 + 0.013 \cdot \text{SL}$	$0.400 + 0.012 \cdot \text{SL}$	$0.401 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.431	$0.402 + 0.015 \cdot \text{SL}$	$0.408 + 0.013 \cdot \text{SL}$	$0.412 + 0.012 \cdot \text{SL}$
GN to Q	t_R	0.102	$0.049 + 0.027 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.044 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.430	$0.403 + 0.013 \cdot \text{SL}$	$0.407 + 0.012 \cdot \text{SL}$	$0.409 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.406	$0.377 + 0.015 \cdot \text{SL}$	$0.384 + 0.013 \cdot \text{SL}$	$0.387 + 0.012 \cdot \text{SL}$
SN to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.046 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.230	$0.203 + 0.014 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.212	$0.183 + 0.015 \cdot \text{SL}$	$0.190 + 0.013 \cdot \text{SL}$	$0.193 + 0.012 \cdot \text{SL}$
RN to Q	t_R	0.102	$0.050 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.045 + 0.023 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.038 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.266	$0.239 + 0.014 \cdot \text{SL}$	$0.243 + 0.012 \cdot \text{SL}$	$0.245 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.291	$0.261 + 0.015 \cdot \text{SL}$	$0.268 + 0.013 \cdot \text{SL}$	$0.272 + 0.012 \cdot \text{SL}$
D to QN	t_R	0.112	$0.057 + 0.028 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.368	$0.338 + 0.015 \cdot \text{SL}$	$0.345 + 0.013 \cdot \text{SL}$	$0.352 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.365	$0.334 + 0.015 \cdot \text{SL}$	$0.342 + 0.013 \cdot \text{SL}$	$0.349 + 0.012 \cdot \text{SL}$
GN to QN	t_R	0.112	$0.057 + 0.027 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.344	$0.314 + 0.015 \cdot \text{SL}$	$0.321 + 0.013 \cdot \text{SL}$	$0.328 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.372	$0.341 + 0.015 \cdot \text{SL}$	$0.350 + 0.013 \cdot \text{SL}$	$0.357 + 0.012 \cdot \text{SL}$
SN to QN	t_R	0.113	$0.060 + 0.027 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.100	$0.054 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.127 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.172	$0.141 + 0.016 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$	$0.157 + 0.012 \cdot \text{SL}$
RN to QN	t_R	0.112	$0.058 + 0.027 \cdot \text{SL}$	$0.058 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.050 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.228	$0.198 + 0.015 \cdot \text{SL}$	$0.205 + 0.013 \cdot \text{SL}$	$0.212 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.208	$0.178 + 0.015 \cdot \text{SL}$	$0.186 + 0.013 \cdot \text{SL}$	$0.193 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

D Latch with Active Low, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LD8D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.462	$0.446 + 0.008 \cdot \text{SL}$	$0.451 + 0.007 \cdot \text{SL}$	$0.457 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.470	$0.452 + 0.009 \cdot \text{SL}$	$0.459 + 0.007 \cdot \text{SL}$	$0.470 + 0.006 \cdot \text{SL}$
GN to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.469	$0.453 + 0.008 \cdot \text{SL}$	$0.459 + 0.007 \cdot \text{SL}$	$0.465 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.452	$0.434 + 0.009 \cdot \text{SL}$	$0.442 + 0.007 \cdot \text{SL}$	$0.452 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.013 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.265	$0.249 + 0.008 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.261 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.247	$0.229 + 0.009 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.247 + 0.006 \cdot \text{SL}$
RN to Q	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.051 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.301	$0.285 + 0.008 \cdot \text{SL}$	$0.291 + 0.007 \cdot \text{SL}$	$0.297 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.325	$0.308 + 0.009 \cdot \text{SL}$	$0.315 + 0.007 \cdot \text{SL}$	$0.326 + 0.006 \cdot \text{SL}$
D to QN	t_R	0.086	$0.059 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.375	$0.357 + 0.009 \cdot \text{SL}$	$0.364 + 0.007 \cdot \text{SL}$	$0.377 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.369	$0.350 + 0.009 \cdot \text{SL}$	$0.358 + 0.007 \cdot \text{SL}$	$0.372 + 0.006 \cdot \text{SL}$
GN to QN	t_R	0.086	$0.058 + 0.014 \cdot \text{SL}$	$0.060 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.011 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.358	$0.340 + 0.009 \cdot \text{SL}$	$0.347 + 0.007 \cdot \text{SL}$	$0.359 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.377	$0.358 + 0.009 \cdot \text{SL}$	$0.366 + 0.007 \cdot \text{SL}$	$0.380 + 0.006 \cdot \text{SL}$
SN to QN	t_R	0.088	$0.060 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.057 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.055 + 0.012 \cdot \text{SL}$	$0.059 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.152	$0.134 + 0.009 \cdot \text{SL}$	$0.141 + 0.007 \cdot \text{SL}$	$0.153 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.173	$0.154 + 0.010 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$	$0.176 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.087	$0.058 + 0.014 \cdot \text{SL}$	$0.061 + 0.014 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.052 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.231	$0.213 + 0.009 \cdot \text{SL}$	$0.221 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.209	$0.190 + 0.009 \cdot \text{SL}$	$0.198 + 0.007 \cdot \text{SL}$	$0.212 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OAK_LDI2/OAK_LDI2D2

D Latch with 2 Input, 2 Active High, 1X/2X Drive

Logic Symbol




Truth Table

D1	G1	D2	G2	Q (n+1)	QN (n+1)
x	0	x	0	Q (n)	QN (n)
1	1	x	x	1	0
0	1	x	0	0	1
x	x	1	1	1	0
x	0	0	1	0	1
0	1	0	1	0	1

Cell Data

Input Load (SL)								Gate Count	
OAK_LDI2				OAK_LDI2D2				OAK_LDI2	OAK_LDI2D2
D1	D2	G1	G2	D1	D2	G1	G2		
0.8	0.8	1.6	1.5	0.8	0.8	1.6	1.5	5.00	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		OAK_LDI2	OAK_LDI2D2
Input Setup Time (D1 to G1)	t_{SU}	0.325	0.343
Input Hold Time (D1 to G1)	t_{HD}	0.000	0.000
Input Setup Time (D2 to G2)	t_{SU}	0.360	0.385
Input Hold Time (D2 to G2)	t_{HD}	0.000	0.000
Pulse Width High (G1)	t_{PWH}	0.300	0.325
Pulse Width High (G2)	t_{PWH}	0.341	0.363

OAK_LDI2/OAK_LDI2D2

D Latch with 2 Input, 2 Active High, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D1 to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.041 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.369	$0.342 + 0.014 \cdot \text{SL}$	$0.346 + 0.012 \cdot \text{SL}$	$0.347 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.419	$0.390 + 0.015 \cdot \text{SL}$	$0.396 + 0.013 \cdot \text{SL}$	$0.399 + 0.013 \cdot \text{SL}$
D2 to Q	t_R	0.101	$0.049 + 0.026 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.038 + 0.029 \cdot \text{SL}$
	t_F	0.091	$0.044 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.413	$0.386 + 0.014 \cdot \text{SL}$	$0.390 + 0.012 \cdot \text{SL}$	$0.391 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.443	$0.413 + 0.015 \cdot \text{SL}$	$0.420 + 0.013 \cdot \text{SL}$	$0.422 + 0.013 \cdot \text{SL}$
G1 to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.041 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.370	$0.343 + 0.013 \cdot \text{SL}$	$0.347 + 0.013 \cdot \text{SL}$	$0.348 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.369	$0.339 + 0.015 \cdot \text{SL}$	$0.346 + 0.013 \cdot \text{SL}$	$0.348 + 0.013 \cdot \text{SL}$
G2 to Q	t_R	0.101	$0.049 + 0.026 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$	$0.037 + 0.029 \cdot \text{SL}$
	t_F	0.089	$0.041 + 0.024 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.414	$0.387 + 0.014 \cdot \text{SL}$	$0.391 + 0.012 \cdot \text{SL}$	$0.392 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.386	$0.357 + 0.015 \cdot \text{SL}$	$0.364 + 0.013 \cdot \text{SL}$	$0.364 + 0.013 \cdot \text{SL}$
D1 to QN	t_R	0.117	$0.066 + 0.026 \cdot \text{SL}$	$0.060 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.361	$0.332 + 0.015 \cdot \text{SL}$	$0.338 + 0.013 \cdot \text{SL}$	$0.342 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.318	$0.287 + 0.016 \cdot \text{SL}$	$0.295 + 0.014 \cdot \text{SL}$	$0.302 + 0.013 \cdot \text{SL}$
D2 to QN	t_R	0.118	$0.067 + 0.026 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$
	t_F	0.101	$0.055 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.048 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.384	$0.355 + 0.015 \cdot \text{SL}$	$0.362 + 0.013 \cdot \text{SL}$	$0.366 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.362	$0.330 + 0.016 \cdot \text{SL}$	$0.339 + 0.014 \cdot \text{SL}$	$0.346 + 0.013 \cdot \text{SL}$
G1 to QN	t_R	0.111	$0.057 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.050 + 0.024 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.046 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.311	$0.282 + 0.014 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$	$0.292 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.319	$0.288 + 0.016 \cdot \text{SL}$	$0.296 + 0.014 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$
G2 to QN	t_R	0.111	$0.058 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.100	$0.053 + 0.023 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.329	$0.300 + 0.014 \cdot \text{SL}$	$0.306 + 0.013 \cdot \text{SL}$	$0.308 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.362	$0.331 + 0.016 \cdot \text{SL}$	$0.339 + 0.014 \cdot \text{SL}$	$0.346 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OAK_LDI2/OAK_LDI2D2

D Latch with 2 Input, 2 Active High, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI2D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D1 to Q	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.069	$0.043 + 0.013 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.412	$0.396 + 0.008 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.407 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.455	$0.438 + 0.009 \cdot \text{SL}$	$0.445 + 0.007 \cdot \text{SL}$	$0.454 + 0.006 \cdot \text{SL}$
D2 to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.049 + 0.011 \cdot \text{SL}$	$0.041 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.453	$0.437 + 0.008 \cdot \text{SL}$	$0.443 + 0.007 \cdot \text{SL}$	$0.448 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.475	$0.458 + 0.009 \cdot \text{SL}$	$0.465 + 0.007 \cdot \text{SL}$	$0.474 + 0.006 \cdot \text{SL}$
G1 to Q	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.044 + 0.013 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.413	$0.397 + 0.008 \cdot \text{SL}$	$0.402 + 0.007 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.403	$0.385 + 0.009 \cdot \text{SL}$	$0.393 + 0.007 \cdot \text{SL}$	$0.402 + 0.006 \cdot \text{SL}$
G2 to Q	t_R	0.078	$0.051 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.039 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.046 + 0.012 \cdot \text{SL}$	$0.049 + 0.012 \cdot \text{SL}$	$0.040 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.455	$0.439 + 0.008 \cdot \text{SL}$	$0.445 + 0.007 \cdot \text{SL}$	$0.450 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.420	$0.403 + 0.008 \cdot \text{SL}$	$0.408 + 0.007 \cdot \text{SL}$	$0.417 + 0.006 \cdot \text{SL}$
D1 to QN	t_R	0.093	$0.066 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.368	$0.350 + 0.009 \cdot \text{SL}$	$0.358 + 0.007 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.324	$0.304 + 0.010 \cdot \text{SL}$	$0.313 + 0.007 \cdot \text{SL}$	$0.326 + 0.006 \cdot \text{SL}$
D2 to QN	t_R	0.093	$0.066 + 0.013 \cdot \text{SL}$	$0.066 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.081	$0.058 + 0.011 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.388	$0.370 + 0.009 \cdot \text{SL}$	$0.378 + 0.007 \cdot \text{SL}$	$0.387 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.364	$0.345 + 0.009 \cdot \text{SL}$	$0.353 + 0.007 \cdot \text{SL}$	$0.367 + 0.006 \cdot \text{SL}$
G1 to QN	t_R	0.086	$0.061 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.317	$0.300 + 0.009 \cdot \text{SL}$	$0.307 + 0.007 \cdot \text{SL}$	$0.316 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.324	$0.305 + 0.010 \cdot \text{SL}$	$0.313 + 0.007 \cdot \text{SL}$	$0.327 + 0.006 \cdot \text{SL}$
G2 to QN	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.048 + 0.014 \cdot \text{SL}$
	t_F	0.079	$0.054 + 0.013 \cdot \text{SL}$	$0.057 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.334	$0.318 + 0.008 \cdot \text{SL}$	$0.322 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.366	$0.347 + 0.010 \cdot \text{SL}$	$0.355 + 0.007 \cdot \text{SL}$	$0.369 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

OAK_LDI3/OAK_LDI3D2

D Latch with 3 Input, 3 Active High, 1X/2X Drive

Logic Symbol




Truth Table

D1	G1	D2	G2	D3	G3	Q (n+1)	QN (n+1)
x	0	x	0	x	0	Q (n)	QN (n)
1	1	x	x	x	x	1	0
0	1	x	0	x	0	0	1
x	x	1	1	x	x	1	0
x	0	0	1	x	0	0	1
x	x	x	x	1	1	1	0
x	0	x	0	0	1	0	1
0	1	0	1	x	0	0	1
x	0	0	1	0	1	0	1
0	1	x	0	0	1	0	1
0	1	0	1	0	1	0	1

Cell Data

Input Load (SL)												Gate Count	
OAK_LDI3						OAK_LDI3D2						OAK_LDI3	OAK_LDI3D2
D1	D2	D3	G1	G2	G3	D1	D2	D3	G1	G2	G3		
0.8	0.8	0.8	1.5	1.5	1.6	0.8	0.8	0.8	1.5	1.5	1.6	6.00	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		OAK_LDI3	OAK_LDI3D2
Input Setup Time (D1 to G1)	t_{SU}	0.340	0.351
Input Hold Time (D1 to G1)	t_{HD}	0.000	0.000
Input Setup Time (D2 to G2)	t_{SU}	0.385	0.387
Input Hold Time (D2 to G2)	t_{HD}	0.000	0.000
Input Setup Time (D3 to G3)	t_{SU}	0.442	0.456
Input Hold Time (D3 to G3)	t_{HD}	0.000	0.000
Pulse Width High (G1)	t_{PWH}	0.310	0.329
Pulse Width High (G2)	t_{PWH}	0.353	0.369
Pulse Width High (G3)	t_{PWH}	0.399	0.416

OAK_LDI3/OAK_LDI3D2

D Latch with 3 Input, 3 Active High, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D1 to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.046 + 0.022 \cdot \text{SL}$	$0.041 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.375	$0.348 + 0.013 \cdot \text{SL}$	$0.352 + 0.012 \cdot \text{SL}$	$0.353 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.400	$0.372 + 0.014 \cdot \text{SL}$	$0.378 + 0.013 \cdot \text{SL}$	$0.380 + 0.012 \cdot \text{SL}$
D2 to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.045 + 0.022 \cdot \text{SL}$	$0.042 + 0.023 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.433	$0.406 + 0.013 \cdot \text{SL}$	$0.410 + 0.012 \cdot \text{SL}$	$0.411 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.443	$0.415 + 0.014 \cdot \text{SL}$	$0.421 + 0.013 \cdot \text{SL}$	$0.424 + 0.012 \cdot \text{SL}$
D3 to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.044 + 0.023 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.481	$0.454 + 0.013 \cdot \text{SL}$	$0.457 + 0.012 \cdot \text{SL}$	$0.459 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.477	$0.449 + 0.014 \cdot \text{SL}$	$0.454 + 0.013 \cdot \text{SL}$	$0.457 + 0.012 \cdot \text{SL}$
G1 to Q	t_R	0.102	$0.049 + 0.026 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.045 + 0.022 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.387	$0.360 + 0.013 \cdot \text{SL}$	$0.364 + 0.012 \cdot \text{SL}$	$0.365 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.381	$0.352 + 0.015 \cdot \text{SL}$	$0.359 + 0.013 \cdot \text{SL}$	$0.361 + 0.012 \cdot \text{SL}$
G2 to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.089	$0.042 + 0.023 \cdot \text{SL}$	$0.043 + 0.023 \cdot \text{SL}$	$0.035 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.431	$0.404 + 0.013 \cdot \text{SL}$	$0.408 + 0.012 \cdot \text{SL}$	$0.409 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.400	$0.371 + 0.014 \cdot \text{SL}$	$0.377 + 0.013 \cdot \text{SL}$	$0.380 + 0.012 \cdot \text{SL}$
G3 to Q	t_R	0.101	$0.048 + 0.027 \cdot \text{SL}$	$0.044 + 0.028 \cdot \text{SL}$	$0.038 + 0.028 \cdot \text{SL}$
	t_F	0.090	$0.045 + 0.022 \cdot \text{SL}$	$0.041 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.475	$0.448 + 0.013 \cdot \text{SL}$	$0.452 + 0.012 \cdot \text{SL}$	$0.453 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.413	$0.384 + 0.014 \cdot \text{SL}$	$0.390 + 0.013 \cdot \text{SL}$	$0.393 + 0.012 \cdot \text{SL}$
D1 to QN	t_R	0.116	$0.065 + 0.025 \cdot \text{SL}$	$0.059 + 0.027 \cdot \text{SL}$	$0.050 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.052 + 0.023 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.344	$0.316 + 0.014 \cdot \text{SL}$	$0.322 + 0.013 \cdot \text{SL}$	$0.325 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.324	$0.294 + 0.015 \cdot \text{SL}$	$0.301 + 0.013 \cdot \text{SL}$	$0.308 + 0.012 \cdot \text{SL}$
D2 to QN	t_R	0.118	$0.068 + 0.025 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$
	t_F	0.100	$0.056 + 0.022 \cdot \text{SL}$	$0.053 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.387	$0.359 + 0.014 \cdot \text{SL}$	$0.365 + 0.013 \cdot \text{SL}$	$0.368 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.382	$0.352 + 0.015 \cdot \text{SL}$	$0.359 + 0.013 \cdot \text{SL}$	$0.366 + 0.012 \cdot \text{SL}$
D3 to QN	t_R	0.119	$0.069 + 0.025 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.057 + 0.022 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.050 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.420	$0.392 + 0.014 \cdot \text{SL}$	$0.398 + 0.013 \cdot \text{SL}$	$0.402 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.429	$0.399 + 0.015 \cdot \text{SL}$	$0.407 + 0.013 \cdot \text{SL}$	$0.413 + 0.012 \cdot \text{SL}$
G1 to QN	t_R	0.111	$0.059 + 0.026 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.053 + 0.023 \cdot \text{SL}$	$0.054 + 0.023 \cdot \text{SL}$	$0.046 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.325	$0.297 + 0.014 \cdot \text{SL}$	$0.303 + 0.013 \cdot \text{SL}$	$0.306 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.336	$0.306 + 0.015 \cdot \text{SL}$	$0.313 + 0.013 \cdot \text{SL}$	$0.320 + 0.012 \cdot \text{SL}$

Switching Characteristics (Cont.)(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
G2 to QN	t_R	0.111	$0.059 + 0.026 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.051 + 0.024 \cdot \text{SL}$	$0.055 + 0.023 \cdot \text{SL}$	$0.047 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.344	$0.316 + 0.014 \cdot \text{SL}$	$0.321 + 0.013 \cdot \text{SL}$	$0.325 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.380	$0.349 + 0.015 \cdot \text{SL}$	$0.357 + 0.013 \cdot \text{SL}$	$0.364 + 0.012 \cdot \text{SL}$
G3 to QN	t_R	0.111	$0.058 + 0.026 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.102	$0.057 + 0.023 \cdot \text{SL}$	$0.056 + 0.023 \cdot \text{SL}$	$0.049 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.357	$0.329 + 0.014 \cdot \text{SL}$	$0.334 + 0.013 \cdot \text{SL}$	$0.338 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.424	$0.393 + 0.015 \cdot \text{SL}$	$0.401 + 0.013 \cdot \text{SL}$	$0.408 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

OAK_LDI3/OAK_LDI3D2

D Latch with 3 Input, 3 Active High, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D1 to Q	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.413	$0.398 + 0.008 \cdot \text{SL}$	$0.403 + 0.006 \cdot \text{SL}$	$0.408 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.440	$0.422 + 0.009 \cdot \text{SL}$	$0.429 + 0.007 \cdot \text{SL}$	$0.438 + 0.006 \cdot \text{SL}$
D2 to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.011 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.472	$0.456 + 0.008 \cdot \text{SL}$	$0.462 + 0.006 \cdot \text{SL}$	$0.467 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.484	$0.467 + 0.009 \cdot \text{SL}$	$0.474 + 0.007 \cdot \text{SL}$	$0.483 + 0.006 \cdot \text{SL}$
D3 to Q	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.050 + 0.012 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.521	$0.505 + 0.008 \cdot \text{SL}$	$0.511 + 0.006 \cdot \text{SL}$	$0.516 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.518	$0.501 + 0.009 \cdot \text{SL}$	$0.508 + 0.007 \cdot \text{SL}$	$0.517 + 0.006 \cdot \text{SL}$
G1 to Q	t_R	0.077	$0.051 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.425	$0.410 + 0.008 \cdot \text{SL}$	$0.415 + 0.006 \cdot \text{SL}$	$0.420 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.419	$0.401 + 0.009 \cdot \text{SL}$	$0.409 + 0.007 \cdot \text{SL}$	$0.418 + 0.006 \cdot \text{SL}$
G2 to Q	t_R	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.470	$0.454 + 0.008 \cdot \text{SL}$	$0.459 + 0.006 \cdot \text{SL}$	$0.465 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.438	$0.420 + 0.009 \cdot \text{SL}$	$0.427 + 0.007 \cdot \text{SL}$	$0.436 + 0.006 \cdot \text{SL}$
G3 to Q	t_R	0.078	$0.053 + 0.013 \cdot \text{SL}$	$0.050 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.515	$0.499 + 0.008 \cdot \text{SL}$	$0.505 + 0.006 \cdot \text{SL}$	$0.510 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.451	$0.433 + 0.009 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$	$0.449 + 0.006 \cdot \text{SL}$
D1 to QN	t_R	0.092	$0.068 + 0.012 \cdot \text{SL}$	$0.065 + 0.013 \cdot \text{SL}$	$0.053 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.353	$0.335 + 0.009 \cdot \text{SL}$	$0.343 + 0.007 \cdot \text{SL}$	$0.351 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.327	$0.309 + 0.009 \cdot \text{SL}$	$0.317 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
D2 to QN	t_R	0.095	$0.070 + 0.012 \cdot \text{SL}$	$0.068 + 0.013 \cdot \text{SL}$	$0.055 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.059 + 0.011 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.396	$0.379 + 0.009 \cdot \text{SL}$	$0.386 + 0.007 \cdot \text{SL}$	$0.395 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.386	$0.367 + 0.009 \cdot \text{SL}$	$0.375 + 0.007 \cdot \text{SL}$	$0.388 + 0.006 \cdot \text{SL}$
D3 to QN	t_R	0.095	$0.070 + 0.013 \cdot \text{SL}$	$0.069 + 0.013 \cdot \text{SL}$	$0.056 + 0.014 \cdot \text{SL}$
	t_F	0.084	$0.061 + 0.011 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.430	$0.412 + 0.009 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$	$0.429 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.434	$0.415 + 0.009 \cdot \text{SL}$	$0.423 + 0.007 \cdot \text{SL}$	$0.437 + 0.006 \cdot \text{SL}$
G1 to QN	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.062 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.056 + 0.012 \cdot \text{SL}$	$0.053 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.332	$0.315 + 0.009 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.331 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.339	$0.321 + 0.009 \cdot \text{SL}$	$0.329 + 0.007 \cdot \text{SL}$	$0.342 + 0.006 \cdot \text{SL}$

OAK_LDI3/OAK_LDI3D2

D Latch with 3 Input, 3 Active High, 1X/2X Drive

Switching Characteristics (Cont.)(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

OAK_LDI3D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
G2 to QN	t_R	0.087	$0.060 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.080	$0.056 + 0.012 \cdot \text{SL}$	$0.058 + 0.011 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.351	$0.334 + 0.009 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$	$0.349 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.384	$0.365 + 0.009 \cdot \text{SL}$	$0.373 + 0.007 \cdot \text{SL}$	$0.386 + 0.006 \cdot \text{SL}$
G3 to QN	t_R	0.088	$0.062 + 0.013 \cdot \text{SL}$	$0.060 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$
	t_F	0.082	$0.058 + 0.012 \cdot \text{SL}$	$0.061 + 0.011 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.364	$0.347 + 0.009 \cdot \text{SL}$	$0.354 + 0.007 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.428	$0.409 + 0.009 \cdot \text{SL}$	$0.418 + 0.007 \cdot \text{SL}$	$0.431 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LS0/LS0D2

SR Latch with 1X/2X Drive

Logic Symbol



Truth Table


RN	SN	Q (n+1)	QN (n+1)
0	0	*	*
1	0	1	0
0	1	0	1
1	1	Q (n)	QN (n)

* Both Q and QN outputs will remain high during RN and SN are low. However, if RN and SN go high simultaneously, the output states are unpredictable.

Cell Data

Input Load (SL)				Gate Count	
LS0		LS0D2		LS0	LS0D2
RN	SN	RN	SN		
1.0	1.0	1.9	1.9	1.67	2.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LS0	LS0D2
Pulse Width Low (SN)	t _{PWL}	0.238	0.207
Removal Time (SN to RN)	t _{RM}	0.044	0.074
Recovery Time (SN to RN)	t _{RC}	0.176	0.146
Pulse Width Low (RN)	t _{PWL}	0.238	0.206

Switching Characteristics

(Typical process, 25°C, 2.5 V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LS0

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN to Q	t_R	0.169	$0.123 + 0.023 \cdot \text{SL}$	$0.125 + 0.022 \cdot \text{SL}$	$0.118 + 0.023 \cdot \text{SL}$
	t_F	0.175	$0.117 + 0.029 \cdot \text{SL}$	$0.110 + 0.031 \cdot \text{SL}$	$0.093 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.109	$0.076 + 0.016 \cdot \text{SL}$	$0.081 + 0.015 \cdot \text{SL}$	$0.081 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.103	$0.069 + 0.017 \cdot \text{SL}$	$0.074 + 0.016 \cdot \text{SL}$	$0.073 + 0.016 \cdot \text{SL}$
RN to Q	t_F	0.152	$0.088 + 0.032 \cdot \text{SL}$	$0.085 + 0.033 \cdot \text{SL}$	$0.080 + 0.033 \cdot \text{SL}$
	t_{PHL}	0.165	$0.131 + 0.017 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$	$0.135 + 0.016 \cdot \text{SL}$
SN to QN	t_F	0.152	$0.087 + 0.032 \cdot \text{SL}$	$0.085 + 0.033 \cdot \text{SL}$	$0.080 + 0.033 \cdot \text{SL}$
	t_{PHL}	0.165	$0.131 + 0.017 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$	$0.135 + 0.016 \cdot \text{SL}$
RN to QN	t_R	0.169	$0.123 + 0.023 \cdot \text{SL}$	$0.125 + 0.022 \cdot \text{SL}$	$0.118 + 0.023 \cdot \text{SL}$
	t_F	0.175	$0.117 + 0.029 \cdot \text{SL}$	$0.110 + 0.031 \cdot \text{SL}$	$0.093 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.109	$0.076 + 0.016 \cdot \text{SL}$	$0.081 + 0.015 \cdot \text{SL}$	$0.081 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.103	$0.069 + 0.017 \cdot \text{SL}$	$0.074 + 0.016 \cdot \text{SL}$	$0.073 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

LS0D2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN to Q	t_R	0.144	$0.120 + 0.012 \cdot \text{SL}$	$0.122 + 0.011 \cdot \text{SL}$	$0.117 + 0.012 \cdot \text{SL}$
	t_F	0.146	$0.117 + 0.014 \cdot \text{SL}$	$0.112 + 0.016 \cdot \text{SL}$	$0.095 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.090	$0.072 + 0.009 \cdot \text{SL}$	$0.078 + 0.008 \cdot \text{SL}$	$0.079 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.086	$0.066 + 0.010 \cdot \text{SL}$	$0.072 + 0.008 \cdot \text{SL}$	$0.073 + 0.008 \cdot \text{SL}$
RN to Q	t_F	0.119	$0.087 + 0.016 \cdot \text{SL}$	$0.084 + 0.017 \cdot \text{SL}$	$0.079 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.145	$0.127 + 0.009 \cdot \text{SL}$	$0.130 + 0.008 \cdot \text{SL}$	$0.132 + 0.008 \cdot \text{SL}$
SN to QN	t_F	0.119	$0.088 + 0.016 \cdot \text{SL}$	$0.084 + 0.017 \cdot \text{SL}$	$0.079 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.145	$0.127 + 0.009 \cdot \text{SL}$	$0.130 + 0.008 \cdot \text{SL}$	$0.132 + 0.008 \cdot \text{SL}$
RN to QN	t_R	0.144	$0.121 + 0.012 \cdot \text{SL}$	$0.122 + 0.011 \cdot \text{SL}$	$0.117 + 0.012 \cdot \text{SL}$
	t_F	0.146	$0.118 + 0.014 \cdot \text{SL}$	$0.113 + 0.016 \cdot \text{SL}$	$0.095 + 0.017 \cdot \text{SL}$
	t_{PLH}	0.090	$0.072 + 0.009 \cdot \text{SL}$	$0.078 + 0.008 \cdot \text{SL}$	$0.079 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.086	$0.066 + 0.010 \cdot \text{SL}$	$0.072 + 0.008 \cdot \text{SL}$	$0.073 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

LS1/LS1D2

SR Latch with Separate Inputs, 1X/2X Drive

Logic Symbol



Truth Table

RN	SN	RN*	SN*	Q (n+1)	QN (n+1)
0	0	x	x	*	*
x	0	0	x	*	*
x	x	0	0	*	*
0	x	x	0	*	*
1	0	1	x	1	0
0	1	x	1	0	1
1	x	1	0	1	0
x	1	0	1	0	1
1	1	1	1	Q (n)	QN (n)


$RN^* = RN1 + RN2, SN^* = SN1 + SN2$

* Both Q and QN output will remain high during RN (RN*) and SN (SN*) are low, if RN (RN*) and SN (SN*) go high simultaneously, the output states are unpredictable

Cell Data

Input Load (SL)												Gate Count	
LS1						LS1D2						LS1	LS1D2
SN1	SN2	SN	RN1	RN2	RN	SN1	SN2	SN	RN1	RN2	RN		
1.0	1.1	0.9	1.0	1.1	0.9	1.0	1.1	0.9	1.0	1.1	0.9	2.67	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LS1	LS1D2
Pulse Width Low (SN1)	t_{PWL}	0.356	0.302
Removal Time (SN1 to RN1)	t_{RM}	0.024	0.104
Recovery Time (SN1 to RN1)	t_{RC}	0.194	0.115
Removal Time (SN1 to RN2)	t_{RM}	0.046	0.123
Recovery Time (SN1 to RN2)	t_{RC}	0.173	0.097
Removal Time (SN1 to RN)	t_{RM}	0.033	0.110
Recovery Time (SN1 to RN)	t_{RC}	0.187	0.110
Pulse Width Low (SN2)	t_{PWL}	0.360	0.304
Removal Time (SN2 to RN1)	t_{RM}	0.010	0.085
Recovery Time (SN2 to RN1)	t_{RC}	0.211	0.135
Removal Time (SN2 to RN2)	t_{RM}	0.028	0.105
Recovery Time (SN2 to RN2)	t_{RC}	0.191	0.115
Removal Time (SN2 to RN)	t_{RM}	0.016	0.091
Recovery Time (SN2 to RN)	t_{RC}	0.204	0.129
Pulse Width Low (SN)	t_{PWL}	0.318	0.278
Removal Time (SN to RN1)	t_{RM}	0.022	0.100
Recovery Time (SN to RN1)	t_{RC}	0.200	0.122
Removal Time (SN to RN2)	t_{RM}	0.042	0.118
Recovery Time (SN to RN2)	t_{RC}	0.178	0.104
Removal Time (SN to RN)	t_{RM}	0.028	0.105
Recovery Time (SN to RN)	t_{RC}	0.192	0.117
Pulse Width Low (RN1)	t_{PWL}	0.355	0.295
Pulse Width Low (RN2)	t_{PWL}	0.360	0.297
Pulse Width Low (RN)	t_{PWL}	0.318	0.275

LS1/LS1D2

SR Latch with Separate Inputs, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LS1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN1 to Q	t_R	0.269	$0.198 + 0.035 \cdot \text{SL}$	$0.201 + 0.035 \cdot \text{SL}$	$0.201 + 0.035 \cdot \text{SL}$
	t_F	0.270	$0.177 + 0.047 \cdot \text{SL}$	$0.169 + 0.049 \cdot \text{SL}$	$0.157 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.158	$0.109 + 0.024 \cdot \text{SL}$	$0.109 + 0.024 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.150	$0.104 + 0.023 \cdot \text{SL}$	$0.104 + 0.023 \cdot \text{SL}$	$0.104 + 0.023 \cdot \text{SL}$
SN2 to Q	t_R	0.274	$0.197 + 0.039 \cdot \text{SL}$	$0.207 + 0.036 \cdot \text{SL}$	$0.217 + 0.035 \cdot \text{SL}$
	t_F	0.305	$0.213 + 0.046 \cdot \text{SL}$	$0.205 + 0.048 \cdot \text{SL}$	$0.191 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.158	$0.109 + 0.024 \cdot \text{SL}$	$0.109 + 0.024 \cdot \text{SL}$	$0.111 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.169	$0.124 + 0.023 \cdot \text{SL}$	$0.123 + 0.023 \cdot \text{SL}$	$0.123 + 0.023 \cdot \text{SL}$
SN to Q	t_R	0.232	$0.178 + 0.027 \cdot \text{SL}$	$0.181 + 0.026 \cdot \text{SL}$	$0.180 + 0.027 \cdot \text{SL}$
	t_F	0.268	$0.173 + 0.047 \cdot \text{SL}$	$0.167 + 0.049 \cdot \text{SL}$	$0.160 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.144	$0.110 + 0.017 \cdot \text{SL}$	$0.110 + 0.017 \cdot \text{SL}$	$0.110 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.154	$0.108 + 0.023 \cdot \text{SL}$	$0.108 + 0.023 \cdot \text{SL}$	$0.109 + 0.023 \cdot \text{SL}$
RN1 to Q	t_F	0.266	$0.170 + 0.048 \cdot \text{SL}$	$0.166 + 0.049 \cdot \text{SL}$	$0.162 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.264	$0.216 + 0.024 \cdot \text{SL}$	$0.219 + 0.023 \cdot \text{SL}$	$0.222 + 0.023 \cdot \text{SL}$
RN2 to Q	t_F	0.298	$0.201 + 0.048 \cdot \text{SL}$	$0.199 + 0.049 \cdot \text{SL}$	$0.195 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.290	$0.243 + 0.024 \cdot \text{SL}$	$0.245 + 0.023 \cdot \text{SL}$	$0.248 + 0.023 \cdot \text{SL}$
RN to Q	t_F	0.262	$0.165 + 0.049 \cdot \text{SL}$	$0.162 + 0.049 \cdot \text{SL}$	$0.158 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.262	$0.215 + 0.024 \cdot \text{SL}$	$0.217 + 0.023 \cdot \text{SL}$	$0.218 + 0.023 \cdot \text{SL}$
SN1 to QN	t_F	0.263	$0.167 + 0.048 \cdot \text{SL}$	$0.163 + 0.049 \cdot \text{SL}$	$0.159 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.265	$0.216 + 0.024 \cdot \text{SL}$	$0.219 + 0.023 \cdot \text{SL}$	$0.223 + 0.023 \cdot \text{SL}$
SN2 to QN	t_F	0.296	$0.199 + 0.048 \cdot \text{SL}$	$0.197 + 0.049 \cdot \text{SL}$	$0.193 + 0.049 \cdot \text{SL}$
	t_{PHL}	0.291	$0.243 + 0.024 \cdot \text{SL}$	$0.246 + 0.023 \cdot \text{SL}$	$0.249 + 0.023 \cdot \text{SL}$
SN to QN	t_F	0.259	$0.162 + 0.048 \cdot \text{SL}$	$0.159 + 0.049 \cdot \text{SL}$	$0.155 + 0.050 \cdot \text{SL}$
	t_{PHL}	0.262	$0.214 + 0.024 \cdot \text{SL}$	$0.216 + 0.023 \cdot \text{SL}$	$0.218 + 0.023 \cdot \text{SL}$
RN1 to QN	t_R	0.267	$0.196 + 0.035 \cdot \text{SL}$	$0.198 + 0.035 \cdot \text{SL}$	$0.199 + 0.035 \cdot \text{SL}$
	t_F	0.267	$0.174 + 0.047 \cdot \text{SL}$	$0.167 + 0.048 \cdot \text{SL}$	$0.154 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.156	$0.108 + 0.024 \cdot \text{SL}$	$0.108 + 0.024 \cdot \text{SL}$	$0.108 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.148	$0.103 + 0.023 \cdot \text{SL}$	$0.102 + 0.023 \cdot \text{SL}$	$0.102 + 0.023 \cdot \text{SL}$
RN2 to QN	t_R	0.272	$0.194 + 0.039 \cdot \text{SL}$	$0.204 + 0.036 \cdot \text{SL}$	$0.215 + 0.035 \cdot \text{SL}$
	t_F	0.303	$0.212 + 0.045 \cdot \text{SL}$	$0.203 + 0.048 \cdot \text{SL}$	$0.189 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.157	$0.108 + 0.024 \cdot \text{SL}$	$0.109 + 0.024 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.168	$0.123 + 0.023 \cdot \text{SL}$	$0.122 + 0.023 \cdot \text{SL}$	$0.122 + 0.023 \cdot \text{SL}$
RN to QN	t_R	0.231	$0.176 + 0.027 \cdot \text{SL}$	$0.179 + 0.027 \cdot \text{SL}$	$0.179 + 0.027 \cdot \text{SL}$
	t_F	0.265	$0.170 + 0.047 \cdot \text{SL}$	$0.164 + 0.049 \cdot \text{SL}$	$0.157 + 0.050 \cdot \text{SL}$
	t_{PLH}	0.143	$0.109 + 0.017 \cdot \text{SL}$	$0.109 + 0.017 \cdot \text{SL}$	$0.109 + 0.017 \cdot \text{SL}$
	t_{PHL}	0.153	$0.107 + 0.023 \cdot \text{SL}$	$0.107 + 0.023 \cdot \text{SL}$	$0.107 + 0.023 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

SR Latch with Separate Inputs, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

LS1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN1 to Q	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.074	$0.051 + 0.011 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.279	$0.262 + 0.008 \cdot \text{SL}$	$0.268 + 0.007 \cdot \text{SL}$	$0.274 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.265	$0.248 + 0.009 \cdot \text{SL}$	$0.255 + 0.007 \cdot \text{SL}$	$0.266 + 0.006 \cdot \text{SL}$
SN2 to Q	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.053 + 0.011 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.279	$0.263 + 0.008 \cdot \text{SL}$	$0.269 + 0.007 \cdot \text{SL}$	$0.275 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.290	$0.272 + 0.009 \cdot \text{SL}$	$0.280 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
SN to Q	t_R	0.078	$0.052 + 0.013 \cdot \text{SL}$	$0.050 + 0.014 \cdot \text{SL}$	$0.040 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.048 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.261	$0.245 + 0.008 \cdot \text{SL}$	$0.251 + 0.007 \cdot \text{SL}$	$0.256 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.270	$0.252 + 0.009 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$	$0.270 + 0.006 \cdot \text{SL}$
RN1 to Q	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.395	$0.377 + 0.009 \cdot \text{SL}$	$0.385 + 0.007 \cdot \text{SL}$	$0.395 + 0.006 \cdot \text{SL}$
RN2 to Q	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.054 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.424	$0.406 + 0.009 \cdot \text{SL}$	$0.414 + 0.007 \cdot \text{SL}$	$0.425 + 0.006 \cdot \text{SL}$
RN to Q	t_F	0.074	$0.050 + 0.012 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.386	$0.369 + 0.009 \cdot \text{SL}$	$0.376 + 0.007 \cdot \text{SL}$	$0.387 + 0.006 \cdot \text{SL}$
SN1 to QN	t_F	0.077	$0.052 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.406	$0.387 + 0.009 \cdot \text{SL}$	$0.395 + 0.007 \cdot \text{SL}$	$0.406 + 0.006 \cdot \text{SL}$
SN2 to QN	t_F	0.078	$0.054 + 0.012 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.438	$0.419 + 0.009 \cdot \text{SL}$	$0.427 + 0.007 \cdot \text{SL}$	$0.438 + 0.006 \cdot \text{SL}$
SN to QN	t_F	0.075	$0.050 + 0.013 \cdot \text{SL}$	$0.055 + 0.012 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.394	$0.375 + 0.009 \cdot \text{SL}$	$0.383 + 0.007 \cdot \text{SL}$	$0.395 + 0.006 \cdot \text{SL}$
RN1 to QN	t_R	0.081	$0.054 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.053 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.046 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.268	$0.252 + 0.008 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.264 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.265	$0.247 + 0.009 \cdot \text{SL}$	$0.254 + 0.007 \cdot \text{SL}$	$0.265 + 0.006 \cdot \text{SL}$
RN2 to QN	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.054 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.268	$0.252 + 0.008 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.264 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.290	$0.271 + 0.009 \cdot \text{SL}$	$0.279 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
RN to QN	t_R	0.079	$0.052 + 0.013 \cdot \text{SL}$	$0.051 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.054 + 0.012 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.255	$0.239 + 0.008 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.270	$0.252 + 0.009 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$	$0.270 + 0.006 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

BUSHOLDER

Cell List

Cell Name	Function Description
BUSHOLDER	Bus Holder

Logic Symbol



Cell Data


Input Load (SL)	Gate Count
Y	1.33
8.1	

INTERNAL CLOCK DRIVERS

Cell List

Cell Name	Function Description
CK2	Internal Clock Driver CMOS 2mA
CK4	Internal Clock Driver CMOS 4mA
CK6	Internal Clock Driver CMOS 6mA
CK8	Internal Clock Driver CMOS 8mA

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Standard Load (SL)				I/O Slot			
CK2	CK4	CK6	CK8	CK2	CK4	CK6	CK8
A	A	A	A				
17.524	17.551	25.277	25.271	1.0	1.0	1.0	1.0

CK2/CK4/CK6/CK8

Internal Clock Driver CMOS 2/4/6/8mA

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

CK2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.059	$0.053 + 0.003 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$	$0.052 + 0.003 \cdot \text{SL}$
	t_F	0.055	$0.047 + 0.004 \cdot \text{SL}$	$0.046 + 0.004 \cdot \text{SL}$	$0.045 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.119	$0.116 + 0.001 \cdot \text{SL}$	$0.116 + 0.001 \cdot \text{SL}$	$0.116 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.158	$0.154 + 0.002 \cdot \text{SL}$	$0.155 + 0.002 \cdot \text{SL}$	$0.155 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 482$, *Group2 : $482 \leq \text{SL} \leq 722$, *Group3 : $722 < \text{SL}$

CK4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.059	$0.056 + 0.002 \cdot \text{SL}$	$0.054 + 0.002 \cdot \text{SL}$	$0.054 + 0.002 \cdot \text{SL}$
	t_F	0.056	$0.052 + 0.002 \cdot \text{SL}$	$0.049 + 0.002 \cdot \text{SL}$	$0.048 + 0.002 \cdot \text{SL}$
	t_{PLH}	0.145	$0.143 + 0.001 \cdot \text{SL}$	$0.144 + 0.001 \cdot \text{SL}$	$0.144 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.191	$0.189 + 0.001 \cdot \text{SL}$	$0.190 + 0.001 \cdot \text{SL}$	$0.190 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 962$, *Group2 : $962 \leq \text{SL} \leq 1443$, *Group3 : $1443 < \text{SL}$

CK6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.060	$0.057 + 0.001 \cdot \text{SL}$	$0.055 + 0.001 \cdot \text{SL}$	$0.054 + 0.001 \cdot \text{SL}$
	t_F	0.055	$0.052 + 0.001 \cdot \text{SL}$	$0.049 + 0.001 \cdot \text{SL}$	$0.048 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.154	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$	$0.153 + 0.000 \cdot \text{SL}$
	t_{PHL}	0.189	$0.188 + 0.001 \cdot \text{SL}$	$0.189 + 0.001 \cdot \text{SL}$	$0.189 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 1443$, *Group2 : $1443 \leq \text{SL} \leq 2165$, *Group3 : $2165 < \text{SL}$

CK8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.062	$0.061 + 0.001 \cdot \text{SL}$	$0.057 + 0.001 \cdot \text{SL}$	$0.056 + 0.001 \cdot \text{SL}$
	t_F	0.058	$0.056 + 0.001 \cdot \text{SL}$	$0.051 + 0.001 \cdot \text{SL}$	$0.050 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.173	$0.172 + 0.000 \cdot \text{SL}$	$0.173 + 0.000 \cdot \text{SL}$	$0.173 + 0.000 \cdot \text{SL}$
	t_{PHL}	0.212	$0.211 + 0.000 \cdot \text{SL}$	$0.212 + 0.000 \cdot \text{SL}$	$0.212 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 1923$, *Group2 : $1923 \leq \text{SL} \leq 2887$, *Group3 : $2887 < \text{SL}$


Cell List

Cell Name	Function Description
DC4	2 > 4 Non-Inverting Decoder
DC4I	2 > 4 Inverting Decoder
DC8I	3 > 8 Inverting Decoder

DC4

2 > 4 Non-Inverting Decoder

Logic Symbol




Truth Table

S1	S0	Y0	Y1	Y2	Y3
0	0	1	0	0	0
0	1	0	1	0	0
1	0	0	0	1	0
1	1	0	0	0	1

Cell Data

Input Load (SL)		Gate Count
S0	S1	
2.5	2.4	6.00

Schematic Diagram



2 > 4 Non-Inverting Decoder

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DC4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to Y0	t_R	0.113	$0.065 + 0.024 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.045 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.050 + 0.023 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$	$0.041 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.202	$0.171 + 0.015 \cdot \text{SL}$	$0.180 + 0.013 \cdot \text{SL}$	$0.184 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.205	$0.175 + 0.015 \cdot \text{SL}$	$0.183 + 0.013 \cdot \text{SL}$	$0.187 + 0.013 \cdot \text{SL}$
S1 to Y0	t_R	0.111	$0.058 + 0.026 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.052 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.204	$0.174 + 0.015 \cdot \text{SL}$	$0.182 + 0.013 \cdot \text{SL}$	$0.186 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.222	$0.191 + 0.015 \cdot \text{SL}$	$0.199 + 0.013 \cdot \text{SL}$	$0.204 + 0.013 \cdot \text{SL}$
S0 to Y1	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.047 + 0.024 \cdot \text{SL}$	$0.043 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.142	$0.113 + 0.014 \cdot \text{SL}$	$0.119 + 0.013 \cdot \text{SL}$	$0.123 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.158	$0.128 + 0.015 \cdot \text{SL}$	$0.135 + 0.013 \cdot \text{SL}$	$0.140 + 0.013 \cdot \text{SL}$
S1 to Y1	t_R	0.108	$0.054 + 0.027 \cdot \text{SL}$	$0.051 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.053 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.203	$0.174 + 0.014 \cdot \text{SL}$	$0.181 + 0.013 \cdot \text{SL}$	$0.184 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.220	$0.190 + 0.015 \cdot \text{SL}$	$0.197 + 0.013 \cdot \text{SL}$	$0.202 + 0.013 \cdot \text{SL}$
S0 to Y2	t_R	0.109	$0.056 + 0.027 \cdot \text{SL}$	$0.052 + 0.028 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.096	$0.048 + 0.024 \cdot \text{SL}$	$0.049 + 0.024 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.203	$0.174 + 0.015 \cdot \text{SL}$	$0.181 + 0.013 \cdot \text{SL}$	$0.185 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.206	$0.175 + 0.015 \cdot \text{SL}$	$0.183 + 0.013 \cdot \text{SL}$	$0.188 + 0.013 \cdot \text{SL}$
S1 to Y2	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.054 + 0.027 \cdot \text{SL}$	$0.046 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.053 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.137	$0.107 + 0.015 \cdot \text{SL}$	$0.115 + 0.013 \cdot \text{SL}$	$0.118 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.173	$0.142 + 0.015 \cdot \text{SL}$	$0.150 + 0.013 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$
S0 to Y3	t_R	0.111	$0.056 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.048 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.050 + 0.022 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.143	$0.114 + 0.014 \cdot \text{SL}$	$0.120 + 0.013 \cdot \text{SL}$	$0.124 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.157	$0.127 + 0.015 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$	$0.139 + 0.012 \cdot \text{SL}$
S1 to Y3	t_R	0.110	$0.056 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.097	$0.051 + 0.023 \cdot \text{SL}$	$0.052 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.135	$0.106 + 0.015 \cdot \text{SL}$	$0.113 + 0.013 \cdot \text{SL}$	$0.116 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.168	$0.138 + 0.015 \cdot \text{SL}$	$0.145 + 0.013 \cdot \text{SL}$	$0.150 + 0.012 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

DC4I

2 > 4 Inverting Decoder

Logic Symbol




Truth Table

S1	S0	YN0	YN1	YN2	YN3
0	0	0	1	1	1
0	1	1	0	1	1
1	0	1	1	0	1
1	1	1	1	1	0

Cell Data

Input Load (SL)		Gate Count
S0	S1	
2.9	3.1	
		4.00

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DC4I


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to YN0	t_R	0.123	$0.057 + 0.033 \cdot \text{SL}$	$0.053 + 0.034 \cdot \text{SL}$	$0.047 + 0.035 \cdot \text{SL}$
	t_F	0.127	$0.062 + 0.032 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$	$0.053 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.155	$0.122 + 0.016 \cdot \text{SL}$	$0.127 + 0.015 \cdot \text{SL}$	$0.128 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.162	$0.126 + 0.018 \cdot \text{SL}$	$0.132 + 0.016 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$
S1 to YN0	t_R	0.141	$0.077 + 0.032 \cdot \text{SL}$	$0.069 + 0.034 \cdot \text{SL}$	$0.063 + 0.035 \cdot \text{SL}$
	t_F	0.124	$0.061 + 0.032 \cdot \text{SL}$	$0.054 + 0.034 \cdot \text{SL}$	$0.051 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.168	$0.136 + 0.016 \cdot \text{SL}$	$0.138 + 0.015 \cdot \text{SL}$	$0.139 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.163	$0.127 + 0.018 \cdot \text{SL}$	$0.131 + 0.017 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$
S0 to YN1	t_R	0.146	$0.086 + 0.030 \cdot \text{SL}$	$0.077 + 0.032 \cdot \text{SL}$	$0.059 + 0.034 \cdot \text{SL}$
	t_F	0.145	$0.087 + 0.029 \cdot \text{SL}$	$0.077 + 0.032 \cdot \text{SL}$	$0.060 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.090	$0.055 + 0.018 \cdot \text{SL}$	$0.065 + 0.015 \cdot \text{SL}$	$0.065 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.085	$0.047 + 0.019 \cdot \text{SL}$	$0.059 + 0.016 \cdot \text{SL}$	$0.057 + 0.016 \cdot \text{SL}$
S1 to YN1	t_R	0.144	$0.084 + 0.030 \cdot \text{SL}$	$0.069 + 0.034 \cdot \text{SL}$	$0.063 + 0.035 \cdot \text{SL}$
	t_F	0.124	$0.060 + 0.032 \cdot \text{SL}$	$0.054 + 0.033 \cdot \text{SL}$	$0.049 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.168	$0.137 + 0.016 \cdot \text{SL}$	$0.139 + 0.015 \cdot \text{SL}$	$0.140 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.163	$0.128 + 0.018 \cdot \text{SL}$	$0.132 + 0.016 \cdot \text{SL}$	$0.134 + 0.016 \cdot \text{SL}$
S0 to YN2	t_R	0.125	$0.060 + 0.032 \cdot \text{SL}$	$0.054 + 0.034 \cdot \text{SL}$	$0.048 + 0.035 \cdot \text{SL}$
	t_F	0.128	$0.063 + 0.032 \cdot \text{SL}$	$0.059 + 0.033 \cdot \text{SL}$	$0.053 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.156	$0.123 + 0.016 \cdot \text{SL}$	$0.127 + 0.015 \cdot \text{SL}$	$0.129 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.163	$0.127 + 0.018 \cdot \text{SL}$	$0.133 + 0.016 \cdot \text{SL}$	$0.135 + 0.016 \cdot \text{SL}$
S1 to YN2	t_R	0.161	$0.102 + 0.029 \cdot \text{SL}$	$0.090 + 0.032 \cdot \text{SL}$	$0.074 + 0.034 \cdot \text{SL}$
	t_F	0.137	$0.080 + 0.029 \cdot \text{SL}$	$0.067 + 0.032 \cdot \text{SL}$	$0.052 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.102	$0.068 + 0.017 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.080	$0.044 + 0.018 \cdot \text{SL}$	$0.054 + 0.016 \cdot \text{SL}$	$0.049 + 0.016 \cdot \text{SL}$
S0 to YN3	t_R	0.146	$0.086 + 0.030 \cdot \text{SL}$	$0.077 + 0.032 \cdot \text{SL}$	$0.059 + 0.034 \cdot \text{SL}$
	t_F	0.146	$0.088 + 0.029 \cdot \text{SL}$	$0.078 + 0.032 \cdot \text{SL}$	$0.060 + 0.033 \cdot \text{SL}$
	t_{PLH}	0.093	$0.057 + 0.018 \cdot \text{SL}$	$0.067 + 0.015 \cdot \text{SL}$	$0.067 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.088	$0.050 + 0.019 \cdot \text{SL}$	$0.061 + 0.016 \cdot \text{SL}$	$0.060 + 0.016 \cdot \text{SL}$
S1 to YN3	t_R	0.161	$0.102 + 0.029 \cdot \text{SL}$	$0.090 + 0.033 \cdot \text{SL}$	$0.075 + 0.034 \cdot \text{SL}$
	t_F	0.138	$0.080 + 0.029 \cdot \text{SL}$	$0.068 + 0.032 \cdot \text{SL}$	$0.055 + 0.034 \cdot \text{SL}$
	t_{PLH}	0.102	$0.069 + 0.016 \cdot \text{SL}$	$0.075 + 0.015 \cdot \text{SL}$	$0.074 + 0.015 \cdot \text{SL}$
	t_{PHL}	0.080	$0.044 + 0.018 \cdot \text{SL}$	$0.051 + 0.016 \cdot \text{SL}$	$0.051 + 0.016 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

DC8I

3 > 8 Inverting Decoder

Logic Symbol




Truth Table

S2	S1	S0	YN0	YN1	YN2	YN3	YN4	YN5	YN6	YN7
0	0	0	0	1	1	1	1	1	1	1
0	0	1	1	0	1	1	1	1	1	1
0	1	0	1	1	0	1	1	1	1	1
0	1	1	1	1	1	0	1	1	1	1
1	0	0	1	1	1	1	0	1	1	1
1	0	1	1	1	1	1	1	0	1	1
1	1	0	1	1	1	1	1	1	0	1
1	1	1	1	1	1	1	1	1	1	0

Cell Data

Input Load (SL)			Gate Count
S0	S1	S2	
5.0	5.0	5.1	10.33

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DC8I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to YN0	t_R	0.169	$0.080 + 0.044 \cdot \text{SL}$	$0.076 + 0.045 \cdot \text{SL}$	$0.069 + 0.046 \cdot \text{SL}$
	t_F	0.186	$0.095 + 0.045 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.082 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.188	$0.146 + 0.021 \cdot \text{SL}$	$0.150 + 0.020 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.196	$0.150 + 0.023 \cdot \text{SL}$	$0.154 + 0.022 \cdot \text{SL}$	$0.153 + 0.022 \cdot \text{SL}$
S1 to YN0	t_R	0.191	$0.103 + 0.044 \cdot \text{SL}$	$0.099 + 0.045 \cdot \text{SL}$	$0.091 + 0.046 \cdot \text{SL}$
	t_F	0.187	$0.095 + 0.046 \cdot \text{SL}$	$0.091 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.215	$0.173 + 0.021 \cdot \text{SL}$	$0.176 + 0.020 \cdot \text{SL}$	$0.177 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.207	$0.160 + 0.023 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$
S2 to YN0	t_R	0.213	$0.127 + 0.043 \cdot \text{SL}$	$0.120 + 0.045 \cdot \text{SL}$	$0.112 + 0.046 \cdot \text{SL}$
	t_F	0.183	$0.091 + 0.046 \cdot \text{SL}$	$0.087 + 0.047 \cdot \text{SL}$	$0.083 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.225	$0.184 + 0.021 \cdot \text{SL}$	$0.186 + 0.020 \cdot \text{SL}$	$0.188 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.207	$0.162 + 0.023 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$
S0 to YN1	t_R	0.182	$0.100 + 0.041 \cdot \text{SL}$	$0.089 + 0.044 \cdot \text{SL}$	$0.074 + 0.045 \cdot \text{SL}$
	t_F	0.201	$0.117 + 0.042 \cdot \text{SL}$	$0.104 + 0.045 \cdot \text{SL}$	$0.087 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.114	$0.073 + 0.021 \cdot \text{SL}$	$0.077 + 0.020 \cdot \text{SL}$	$0.076 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.063 + 0.023 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$
S1 to YN1	t_R	0.190	$0.104 + 0.043 \cdot \text{SL}$	$0.099 + 0.044 \cdot \text{SL}$	$0.093 + 0.045 \cdot \text{SL}$
	t_F	0.188	$0.097 + 0.046 \cdot \text{SL}$	$0.093 + 0.047 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.214	$0.173 + 0.020 \cdot \text{SL}$	$0.176 + 0.020 \cdot \text{SL}$	$0.177 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.208	$0.162 + 0.023 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
S2 to YN1	t_R	0.215	$0.128 + 0.044 \cdot \text{SL}$	$0.122 + 0.045 \cdot \text{SL}$	$0.114 + 0.046 \cdot \text{SL}$
	t_F	0.184	$0.092 + 0.046 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.226	$0.185 + 0.021 \cdot \text{SL}$	$0.188 + 0.020 \cdot \text{SL}$	$0.188 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.209	$0.163 + 0.023 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
S0 to YN2	t_R	0.170	$0.082 + 0.044 \cdot \text{SL}$	$0.078 + 0.045 \cdot \text{SL}$	$0.071 + 0.046 \cdot \text{SL}$
	t_F	0.189	$0.099 + 0.045 \cdot \text{SL}$	$0.093 + 0.047 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.189	$0.147 + 0.021 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$	$0.152 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.197	$0.151 + 0.023 \cdot \text{SL}$	$0.155 + 0.022 \cdot \text{SL}$	$0.156 + 0.022 \cdot \text{SL}$
S1 to YN2	t_R	0.205	$0.123 + 0.041 \cdot \text{SL}$	$0.110 + 0.044 \cdot \text{SL}$	$0.095 + 0.046 \cdot \text{SL}$
	t_F	0.198	$0.113 + 0.042 \cdot \text{SL}$	$0.100 + 0.046 \cdot \text{SL}$	$0.087 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.130	$0.090 + 0.020 \cdot \text{SL}$	$0.092 + 0.020 \cdot \text{SL}$	$0.091 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.112	$0.066 + 0.023 \cdot \text{SL}$	$0.072 + 0.021 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$
S2 to YN2	t_R	0.216	$0.129 + 0.043 \cdot \text{SL}$	$0.123 + 0.045 \cdot \text{SL}$	$0.114 + 0.046 \cdot \text{SL}$
	t_F	0.185	$0.093 + 0.046 \cdot \text{SL}$	$0.089 + 0.047 \cdot \text{SL}$	$0.085 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.227	$0.185 + 0.021 \cdot \text{SL}$	$0.188 + 0.020 \cdot \text{SL}$	$0.189 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.209	$0.163 + 0.023 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
S0 to YN3	t_R	0.181	$0.098 + 0.041 \cdot \text{SL}$	$0.088 + 0.044 \cdot \text{SL}$	$0.072 + 0.046 \cdot \text{SL}$
	t_F	0.201	$0.116 + 0.042 \cdot \text{SL}$	$0.104 + 0.045 \cdot \text{SL}$	$0.087 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.114	$0.072 + 0.021 \cdot \text{SL}$	$0.077 + 0.020 \cdot \text{SL}$	$0.076 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.062 + 0.023 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$

DC8I

3 > 8 Inverting Decoder

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

DC8I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S1 to YN3	t_R	0.203	$0.121 + 0.041 \cdot \text{SL}$	$0.108 + 0.044 \cdot \text{SL}$	$0.093 + 0.046 \cdot \text{SL}$
	t_F	0.194	$0.108 + 0.043 \cdot \text{SL}$	$0.097 + 0.046 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.129	$0.089 + 0.020 \cdot \text{SL}$	$0.090 + 0.020 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.110	$0.064 + 0.023 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$
S2 to YN3	t_R	0.214	$0.127 + 0.043 \cdot \text{SL}$	$0.121 + 0.045 \cdot \text{SL}$	$0.112 + 0.046 \cdot \text{SL}$
	t_F	0.183	$0.091 + 0.046 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$	$0.083 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.227	$0.186 + 0.021 \cdot \text{SL}$	$0.188 + 0.020 \cdot \text{SL}$	$0.189 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.209	$0.163 + 0.023 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
S0 to YN4	t_R	0.169	$0.081 + 0.044 \cdot \text{SL}$	$0.077 + 0.045 \cdot \text{SL}$	$0.070 + 0.046 \cdot \text{SL}$
	t_F	0.187	$0.097 + 0.045 \cdot \text{SL}$	$0.090 + 0.047 \cdot \text{SL}$	$0.083 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.188	$0.146 + 0.021 \cdot \text{SL}$	$0.150 + 0.020 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.196	$0.150 + 0.023 \cdot \text{SL}$	$0.154 + 0.022 \cdot \text{SL}$	$0.153 + 0.022 \cdot \text{SL}$
S1 to YN4	t_R	0.191	$0.104 + 0.043 \cdot \text{SL}$	$0.099 + 0.045 \cdot \text{SL}$	$0.092 + 0.046 \cdot \text{SL}$
	t_F	0.187	$0.096 + 0.046 \cdot \text{SL}$	$0.092 + 0.047 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.214	$0.173 + 0.021 \cdot \text{SL}$	$0.176 + 0.020 \cdot \text{SL}$	$0.177 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.207	$0.161 + 0.023 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$	$0.167 + 0.022 \cdot \text{SL}$
S2 to YN4	t_R	0.227	$0.145 + 0.041 \cdot \text{SL}$	$0.132 + 0.044 \cdot \text{SL}$	$0.115 + 0.046 \cdot \text{SL}$
	t_F	0.190	$0.103 + 0.043 \cdot \text{SL}$	$0.091 + 0.046 \cdot \text{SL}$	$0.081 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.140	$0.100 + 0.020 \cdot \text{SL}$	$0.101 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.109	$0.063 + 0.023 \cdot \text{SL}$	$0.069 + 0.021 \cdot \text{SL}$	$0.064 + 0.022 \cdot \text{SL}$
S0 to YN5	t_R	0.181	$0.099 + 0.041 \cdot \text{SL}$	$0.088 + 0.044 \cdot \text{SL}$	$0.072 + 0.046 \cdot \text{SL}$
	t_F	0.200	$0.116 + 0.042 \cdot \text{SL}$	$0.103 + 0.046 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.115	$0.073 + 0.021 \cdot \text{SL}$	$0.077 + 0.020 \cdot \text{SL}$	$0.077 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.063 + 0.023 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$
S1 to YN5	t_R	0.190	$0.104 + 0.043 \cdot \text{SL}$	$0.098 + 0.044 \cdot \text{SL}$	$0.092 + 0.045 \cdot \text{SL}$
	t_F	0.187	$0.096 + 0.046 \cdot \text{SL}$	$0.092 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.213	$0.172 + 0.020 \cdot \text{SL}$	$0.175 + 0.020 \cdot \text{SL}$	$0.176 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.207	$0.160 + 0.023 \cdot \text{SL}$	$0.165 + 0.022 \cdot \text{SL}$	$0.166 + 0.022 \cdot \text{SL}$
S2 to YN5	t_R	0.225	$0.145 + 0.040 \cdot \text{SL}$	$0.132 + 0.044 \cdot \text{SL}$	$0.115 + 0.045 \cdot \text{SL}$
	t_F	0.190	$0.102 + 0.044 \cdot \text{SL}$	$0.092 + 0.047 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.139	$0.099 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$	$0.099 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.062 + 0.023 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$	$0.065 + 0.022 \cdot \text{SL}$
S0 to YN6	t_R	0.170	$0.081 + 0.045 \cdot \text{SL}$	$0.077 + 0.046 \cdot \text{SL}$	$0.070 + 0.046 \cdot \text{SL}$
	t_F	0.188	$0.097 + 0.045 \cdot \text{SL}$	$0.091 + 0.047 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.189	$0.147 + 0.021 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$	$0.151 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.196	$0.150 + 0.023 \cdot \text{SL}$	$0.154 + 0.022 \cdot \text{SL}$	$0.154 + 0.022 \cdot \text{SL}$
S1 to YN6	t_R	0.203	$0.122 + 0.041 \cdot \text{SL}$	$0.109 + 0.044 \cdot \text{SL}$	$0.094 + 0.046 \cdot \text{SL}$
	t_F	0.196	$0.111 + 0.043 \cdot \text{SL}$	$0.098 + 0.046 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.130	$0.089 + 0.020 \cdot \text{SL}$	$0.091 + 0.020 \cdot \text{SL}$	$0.090 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.111	$0.065 + 0.023 \cdot \text{SL}$	$0.071 + 0.021 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**DC8I**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S2 to YN6	t_R	0.225	$0.143 + 0.041 \cdot \text{SL}$	$0.131 + 0.044 \cdot \text{SL}$	$0.115 + 0.046 \cdot \text{SL}$
	t_F	0.189	$0.102 + 0.044 \cdot \text{SL}$	$0.091 + 0.046 \cdot \text{SL}$	$0.081 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.139	$0.099 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.062 + 0.023 \cdot \text{SL}$	$0.068 + 0.021 \cdot \text{SL}$	$0.064 + 0.022 \cdot \text{SL}$
S0 to YN7	t_R	0.180	$0.099 + 0.041 \cdot \text{SL}$	$0.089 + 0.043 \cdot \text{SL}$	$0.072 + 0.045 \cdot \text{SL}$
	t_F	0.202	$0.117 + 0.042 \cdot \text{SL}$	$0.105 + 0.045 \cdot \text{SL}$	$0.088 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.113	$0.072 + 0.021 \cdot \text{SL}$	$0.077 + 0.019 \cdot \text{SL}$	$0.076 + 0.019 \cdot \text{SL}$
	t_{PHL}	0.109	$0.063 + 0.023 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$
S1 to YN7	t_R	0.201	$0.120 + 0.040 \cdot \text{SL}$	$0.107 + 0.044 \cdot \text{SL}$	$0.092 + 0.045 \cdot \text{SL}$
	t_F	0.194	$0.107 + 0.044 \cdot \text{SL}$	$0.097 + 0.046 \cdot \text{SL}$	$0.086 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.128	$0.089 + 0.020 \cdot \text{SL}$	$0.089 + 0.020 \cdot \text{SL}$	$0.088 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.110	$0.064 + 0.023 \cdot \text{SL}$	$0.068 + 0.022 \cdot \text{SL}$	$0.067 + 0.022 \cdot \text{SL}$
S2 to YN7	t_R	0.226	$0.144 + 0.041 \cdot \text{SL}$	$0.132 + 0.044 \cdot \text{SL}$	$0.116 + 0.046 \cdot \text{SL}$
	t_F	0.190	$0.101 + 0.044 \cdot \text{SL}$	$0.092 + 0.047 \cdot \text{SL}$	$0.085 + 0.047 \cdot \text{SL}$
	t_{PLH}	0.140	$0.100 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$	$0.100 + 0.020 \cdot \text{SL}$
	t_{PHL}	0.108	$0.063 + 0.023 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$	$0.066 + 0.022 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

ADDERS


Cell List

Cell Name	Function Description
FADH	Full Adder with 0.5X Drive
FA	Full Adder with 1X Drive
FAD2	Full Adder with 2X Drive
HADH	Half Adder with 0.5x Drive
HA	Half Adder with 1x Drive
HAD2	Half Adder with 2X Drive
SCG23	Full Adder with one inverted input, 1X Drive
SCG23D2	Full Adder with one inverted input, 2X Drive

FADH/FA/FAD2

Full Adder with 0.5X/1X/2X Drive

Logic Symbol



Truth Table

CI	A	B	S	CO
0	0	0	0	0
1	0	0	1	0
0	0	1	1	0
1	0	1	0	1
0	1	0	1	0
1	1	0	0	1
0	1	1	0	1
1	1	1	1	1

Cell Data

Input Load (SL)									Gate Count		
FADH			FA			FAD2			FADH	FA	FAD2
CI	A	B	CI	A	B	CI	A	B			
0.4	0.6	0.5	0.8	1.0	1.0	0.8	1.0	1.0	5.00	6.00	6.00

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FADH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.195	$0.083 + 0.056 \cdot \text{SL}$	$0.077 + 0.058 \cdot \text{SL}$	$0.064 + 0.059 \cdot \text{SL}$
	t_F	0.177	$0.081 + 0.048 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$	$0.074 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.415	$0.356 + 0.029 \cdot \text{SL}$	$0.368 + 0.026 \cdot \text{SL}$	$0.372 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.434	$0.371 + 0.032 \cdot \text{SL}$	$0.388 + 0.027 \cdot \text{SL}$	$0.401 + 0.026 \cdot \text{SL}$
B to S	t_R	0.194	$0.084 + 0.055 \cdot \text{SL}$	$0.075 + 0.058 \cdot \text{SL}$	$0.060 + 0.059 \cdot \text{SL}$
	t_F	0.177	$0.082 + 0.048 \cdot \text{SL}$	$0.084 + 0.047 \cdot \text{SL}$	$0.072 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.466	$0.408 + 0.029 \cdot \text{SL}$	$0.419 + 0.026 \cdot \text{SL}$	$0.423 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.492	$0.428 + 0.032 \cdot \text{SL}$	$0.446 + 0.027 \cdot \text{SL}$	$0.459 + 0.026 \cdot \text{SL}$
CI to S	t_R	0.193	$0.081 + 0.056 \cdot \text{SL}$	$0.075 + 0.058 \cdot \text{SL}$	$0.060 + 0.059 \cdot \text{SL}$
	t_F	0.188	$0.093 + 0.047 \cdot \text{SL}$	$0.096 + 0.046 \cdot \text{SL}$	$0.081 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.382	$0.322 + 0.030 \cdot \text{SL}$	$0.335 + 0.026 \cdot \text{SL}$	$0.340 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.370	$0.305 + 0.032 \cdot \text{SL}$	$0.325 + 0.027 \cdot \text{SL}$	$0.339 + 0.026 \cdot \text{SL}$
A to CO	t_R	0.201	$0.088 + 0.056 \cdot \text{SL}$	$0.080 + 0.058 \cdot \text{SL}$	$0.068 + 0.060 \cdot \text{SL}$
	t_F	0.183	$0.085 + 0.049 \cdot \text{SL}$	$0.091 + 0.047 \cdot \text{SL}$	$0.081 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.414	$0.355 + 0.030 \cdot \text{SL}$	$0.367 + 0.027 \cdot \text{SL}$	$0.371 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.433	$0.370 + 0.032 \cdot \text{SL}$	$0.387 + 0.027 \cdot \text{SL}$	$0.400 + 0.026 \cdot \text{SL}$
B to CO	t_R	0.239	$0.137 + 0.051 \cdot \text{SL}$	$0.120 + 0.055 \cdot \text{SL}$	$0.086 + 0.059 \cdot \text{SL}$
	t_F	0.207	$0.120 + 0.043 \cdot \text{SL}$	$0.112 + 0.046 \cdot \text{SL}$	$0.091 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.465	$0.406 + 0.030 \cdot \text{SL}$	$0.418 + 0.026 \cdot \text{SL}$	$0.422 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.498	$0.434 + 0.032 \cdot \text{SL}$	$0.452 + 0.027 \cdot \text{SL}$	$0.465 + 0.026 \cdot \text{SL}$
CI to CO	t_R	0.200	$0.086 + 0.057 \cdot \text{SL}$	$0.081 + 0.058 \cdot \text{SL}$	$0.068 + 0.060 \cdot \text{SL}$
	t_F	0.193	$0.095 + 0.049 \cdot \text{SL}$	$0.103 + 0.047 \cdot \text{SL}$	$0.092 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.272	$0.211 + 0.030 \cdot \text{SL}$	$0.225 + 0.027 \cdot \text{SL}$	$0.231 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.292	$0.224 + 0.034 \cdot \text{SL}$	$0.247 + 0.028 \cdot \text{SL}$	$0.266 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

FADH/FA/FAD2

Full Adder with 0.5X/1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.124	$0.073 + 0.026 \cdot \text{SL}$	$0.069 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.068 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.336	$0.305 + 0.015 \cdot \text{SL}$	$0.313 + 0.013 \cdot \text{SL}$	$0.321 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.344	$0.310 + 0.017 \cdot \text{SL}$	$0.320 + 0.014 \cdot \text{SL}$	$0.333 + 0.013 \cdot \text{SL}$
B to S	t_R	0.125	$0.073 + 0.026 \cdot \text{SL}$	$0.071 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.067 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.382	$0.351 + 0.015 \cdot \text{SL}$	$0.359 + 0.013 \cdot \text{SL}$	$0.367 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.402	$0.368 + 0.017 \cdot \text{SL}$	$0.379 + 0.014 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$
CI to S	t_R	0.126	$0.072 + 0.027 \cdot \text{SL}$	$0.073 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.124	$0.076 + 0.024 \cdot \text{SL}$	$0.083 + 0.022 \cdot \text{SL}$	$0.079 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.304	$0.273 + 0.016 \cdot \text{SL}$	$0.282 + 0.013 \cdot \text{SL}$	$0.289 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.299	$0.264 + 0.017 \cdot \text{SL}$	$0.277 + 0.014 \cdot \text{SL}$	$0.290 + 0.013 \cdot \text{SL}$
A to CO	t_R	0.122	$0.069 + 0.027 \cdot \text{SL}$	$0.067 + 0.027 \cdot \text{SL}$	$0.061 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.025 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.329	$0.299 + 0.015 \cdot \text{SL}$	$0.306 + 0.013 \cdot \text{SL}$	$0.313 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.338	$0.304 + 0.017 \cdot \text{SL}$	$0.315 + 0.014 \cdot \text{SL}$	$0.327 + 0.013 \cdot \text{SL}$
B to CO	t_R	0.168	$0.123 + 0.022 \cdot \text{SL}$	$0.117 + 0.024 \cdot \text{SL}$	$0.090 + 0.027 \cdot \text{SL}$
	t_F	0.163	$0.122 + 0.021 \cdot \text{SL}$	$0.123 + 0.020 \cdot \text{SL}$	$0.107 + 0.022 \cdot \text{SL}$
	t_{PLH}	0.376	$0.345 + 0.015 \cdot \text{SL}$	$0.353 + 0.013 \cdot \text{SL}$	$0.360 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.403	$0.369 + 0.017 \cdot \text{SL}$	$0.380 + 0.014 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$
CI to CO	t_R	0.127	$0.072 + 0.027 \cdot \text{SL}$	$0.074 + 0.027 \cdot \text{SL}$	$0.066 + 0.028 \cdot \text{SL}$
	t_F	0.126	$0.077 + 0.024 \cdot \text{SL}$	$0.085 + 0.023 \cdot \text{SL}$	$0.082 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.220	$0.189 + 0.016 \cdot \text{SL}$	$0.198 + 0.013 \cdot \text{SL}$	$0.207 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.225	$0.189 + 0.018 \cdot \text{SL}$	$0.202 + 0.015 \cdot \text{SL}$	$0.218 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

FAD2


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.106	$0.079 + 0.013 \cdot \text{SL}$	$0.079 + 0.013 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.086 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.094 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.346	$0.326 + 0.010 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.351 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.355	$0.333 + 0.011 \cdot \text{SL}$	$0.344 + 0.008 \cdot \text{SL}$	$0.365 + 0.007 \cdot \text{SL}$
B to S	t_R	0.107	$0.079 + 0.014 \cdot \text{SL}$	$0.080 + 0.013 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.110	$0.084 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.091 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.393	$0.373 + 0.010 \cdot \text{SL}$	$0.383 + 0.007 \cdot \text{SL}$	$0.399 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.408	$0.385 + 0.011 \cdot \text{SL}$	$0.397 + 0.008 \cdot \text{SL}$	$0.420 + 0.007 \cdot \text{SL}$
CI to S	t_R	0.106	$0.079 + 0.014 \cdot \text{SL}$	$0.080 + 0.013 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.085 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.094 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.333	$0.313 + 0.010 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.340 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.326	$0.303 + 0.012 \cdot \text{SL}$	$0.315 + 0.008 \cdot \text{SL}$	$0.339 + 0.007 \cdot \text{SL}$
A to CO	t_R	0.103	$0.076 + 0.013 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$
	t_F	0.105	$0.079 + 0.013 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.086 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.338	$0.319 + 0.009 \cdot \text{SL}$	$0.327 + 0.007 \cdot \text{SL}$	$0.342 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.347	$0.325 + 0.011 \cdot \text{SL}$	$0.335 + 0.008 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$
B to CO	t_R	0.152	$0.133 + 0.010 \cdot \text{SL}$	$0.124 + 0.012 \cdot \text{SL}$	$0.102 + 0.013 \cdot \text{SL}$
	t_F	0.164	$0.145 + 0.010 \cdot \text{SL}$	$0.144 + 0.010 \cdot \text{SL}$	$0.126 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.381	$0.361 + 0.010 \cdot \text{SL}$	$0.370 + 0.007 \cdot \text{SL}$	$0.385 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.404	$0.383 + 0.011 \cdot \text{SL}$	$0.393 + 0.008 \cdot \text{SL}$	$0.414 + 0.007 \cdot \text{SL}$
CI to CO	t_R	0.106	$0.079 + 0.013 \cdot \text{SL}$	$0.078 + 0.014 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.085 + 0.014 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$	$0.096 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.226	$0.205 + 0.010 \cdot \text{SL}$	$0.215 + 0.007 \cdot \text{SL}$	$0.232 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.230	$0.206 + 0.012 \cdot \text{SL}$	$0.219 + 0.009 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

HADH/HA/HAD2

Half Adder with 0.5X/1X/2X Drive

Logic Symbol




Truth Table

A	B	S	CO
0	0	0	0
0	1	1	0
1	0	1	0
1	1	0	1

Cell Data

Input Load (SL)						Gate Count		
HADH		HA		HAD2		HADH	HA	HAD2
A	B	A	B	A	B			
0.8	1.1	1.4	2.0	1.5	2.3	3.00	3.67	4.00

Schematic Diagram



HADH/HA/HAD2

Half Adder with 0.5X/1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

HADH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.193	$0.081 + 0.056 \cdot \text{SL}$	$0.075 + 0.058 \cdot \text{SL}$	$0.061 + 0.059 \cdot \text{SL}$
	t_F	0.185	$0.090 + 0.048 \cdot \text{SL}$	$0.094 + 0.047 \cdot \text{SL}$	$0.079 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.311	$0.252 + 0.029 \cdot \text{SL}$	$0.264 + 0.026 \cdot \text{SL}$	$0.268 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.312	$0.247 + 0.032 \cdot \text{SL}$	$0.267 + 0.027 \cdot \text{SL}$	$0.279 + 0.026 \cdot \text{SL}$
B to S	t_R	0.187	$0.074 + 0.057 \cdot \text{SL}$	$0.069 + 0.058 \cdot \text{SL}$	$0.058 + 0.059 \cdot \text{SL}$
	t_F	0.175	$0.079 + 0.048 \cdot \text{SL}$	$0.081 + 0.047 \cdot \text{SL}$	$0.069 + 0.048 \cdot \text{SL}$
	t_{PLH}	0.238	$0.178 + 0.030 \cdot \text{SL}$	$0.191 + 0.026 \cdot \text{SL}$	$0.196 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.250	$0.186 + 0.032 \cdot \text{SL}$	$0.205 + 0.027 \cdot \text{SL}$	$0.218 + 0.026 \cdot \text{SL}$
A to CO	t_R	0.181	$0.065 + 0.058 \cdot \text{SL}$	$0.058 + 0.060 \cdot \text{SL}$	$0.048 + 0.061 \cdot \text{SL}$
	t_F	0.154	$0.060 + 0.047 \cdot \text{SL}$	$0.056 + 0.048 \cdot \text{SL}$	$0.044 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.182	$0.126 + 0.028 \cdot \text{SL}$	$0.133 + 0.026 \cdot \text{SL}$	$0.134 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.213	$0.156 + 0.028 \cdot \text{SL}$	$0.166 + 0.026 \cdot \text{SL}$	$0.169 + 0.026 \cdot \text{SL}$
B to CO	t_R	0.180	$0.064 + 0.058 \cdot \text{SL}$	$0.057 + 0.060 \cdot \text{SL}$	$0.048 + 0.061 \cdot \text{SL}$
	t_F	0.151	$0.057 + 0.047 \cdot \text{SL}$	$0.051 + 0.048 \cdot \text{SL}$	$0.042 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.187	$0.131 + 0.028 \cdot \text{SL}$	$0.137 + 0.026 \cdot \text{SL}$	$0.139 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.198	$0.142 + 0.028 \cdot \text{SL}$	$0.151 + 0.026 \cdot \text{SL}$	$0.153 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

HA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.125	$0.071 + 0.027 \cdot \text{SL}$	$0.070 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.125	$0.077 + 0.024 \cdot \text{SL}$	$0.082 + 0.023 \cdot \text{SL}$	$0.076 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.244	$0.213 + 0.016 \cdot \text{SL}$	$0.222 + 0.013 \cdot \text{SL}$	$0.229 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.244	$0.209 + 0.018 \cdot \text{SL}$	$0.221 + 0.014 \cdot \text{SL}$	$0.234 + 0.013 \cdot \text{SL}$
B to S	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.113	$0.063 + 0.025 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.185	$0.154 + 0.016 \cdot \text{SL}$	$0.163 + 0.013 \cdot \text{SL}$	$0.170 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.195	$0.160 + 0.017 \cdot \text{SL}$	$0.172 + 0.014 \cdot \text{SL}$	$0.185 + 0.013 \cdot \text{SL}$
A to CO	t_R	0.111	$0.057 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.099	$0.054 + 0.023 \cdot \text{SL}$	$0.051 + 0.023 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.134	$0.105 + 0.014 \cdot \text{SL}$	$0.112 + 0.013 \cdot \text{SL}$	$0.115 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.168	$0.137 + 0.015 \cdot \text{SL}$	$0.145 + 0.013 \cdot \text{SL}$	$0.149 + 0.013 \cdot \text{SL}$
B to CO	t_R	0.110	$0.055 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$	$0.047 + 0.028 \cdot \text{SL}$
	t_F	0.098	$0.047 + 0.025 \cdot \text{SL}$	$0.057 + 0.023 \cdot \text{SL}$	$0.042 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.139	$0.110 + 0.014 \cdot \text{SL}$	$0.116 + 0.013 \cdot \text{SL}$	$0.120 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.153	$0.123 + 0.015 \cdot \text{SL}$	$0.130 + 0.013 \cdot \text{SL}$	$0.134 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

HADH/HA/HAD2

Half Adder with 0.5X/1X/2X Drive

Switching Characteristics


(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

HAD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.109	$0.082 + 0.014 \cdot \text{SL}$	$0.084 + 0.013 \cdot \text{SL}$	$0.078 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.086 + 0.013 \cdot \text{SL}$	$0.090 + 0.012 \cdot \text{SL}$	$0.094 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.246	$0.227 + 0.010 \cdot \text{SL}$	$0.236 + 0.007 \cdot \text{SL}$	$0.252 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.250	$0.227 + 0.011 \cdot \text{SL}$	$0.239 + 0.008 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$
B to S	t_R	0.101	$0.074 + 0.014 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$	$0.072 + 0.014 \cdot \text{SL}$
	t_F	0.101	$0.076 + 0.013 \cdot \text{SL}$	$0.079 + 0.012 \cdot \text{SL}$	$0.085 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.192	$0.172 + 0.010 \cdot \text{SL}$	$0.181 + 0.007 \cdot \text{SL}$	$0.198 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.200	$0.178 + 0.011 \cdot \text{SL}$	$0.189 + 0.008 \cdot \text{SL}$	$0.212 + 0.007 \cdot \text{SL}$
A to CO	t_R	0.087	$0.061 + 0.013 \cdot \text{SL}$	$0.058 + 0.014 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.075	$0.052 + 0.012 \cdot \text{SL}$	$0.053 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.146	$0.128 + 0.009 \cdot \text{SL}$	$0.136 + 0.007 \cdot \text{SL}$	$0.147 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.161	$0.143 + 0.009 \cdot \text{SL}$	$0.151 + 0.007 \cdot \text{SL}$	$0.163 + 0.006 \cdot \text{SL}$
B to CO	t_R	0.085	$0.057 + 0.014 \cdot \text{SL}$	$0.059 + 0.014 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$
	t_F	0.073	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.045 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.157	$0.139 + 0.009 \cdot \text{SL}$	$0.146 + 0.007 \cdot \text{SL}$	$0.157 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.153	$0.135 + 0.009 \cdot \text{SL}$	$0.143 + 0.007 \cdot \text{SL}$	$0.154 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Logic Symbol



Truth Table

AN	B	CI	S	CO
0	0	0	1	0
0	0	1	0	1
0	1	0	0	1
0	1	1	1	1
1	0	0	0	0
1	0	1	1	0
1	1	0	1	0
1	1	1	0	1

Cell Data

Input Load (SL)						Gate Count	
SCG23			SCG23D2			SCG23	SCG23D2
CI	AN	B	CI	AN	B		
0.8	0.7	1.0	0.8	0.6	1.0	6.33	6.33

SCG23/SCG23D2

Full Adder with one inverted input, 1X/2X Drive

Switching Characteristics SCG23

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
AN to S	t_R	0.124	$0.071 + 0.027 \cdot \text{SL}$	$0.069 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.067 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.398	$0.367 + 0.015 \cdot \text{SL}$	$0.376 + 0.013 \cdot \text{SL}$	$0.383 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.395	$0.361 + 0.017 \cdot \text{SL}$	$0.372 + 0.014 \cdot \text{SL}$	$0.385 + 0.013 \cdot \text{SL}$
B to S	t_R	0.126	$0.073 + 0.026 \cdot \text{SL}$	$0.071 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.067 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.382	$0.351 + 0.016 \cdot \text{SL}$	$0.360 + 0.013 \cdot \text{SL}$	$0.367 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.402	$0.368 + 0.017 \cdot \text{SL}$	$0.379 + 0.014 \cdot \text{SL}$	$0.392 + 0.013 \cdot \text{SL}$
CI to S	t_R	0.127	$0.073 + 0.027 \cdot \text{SL}$	$0.072 + 0.027 \cdot \text{SL}$	$0.064 + 0.028 \cdot \text{SL}$
	t_F	0.124	$0.076 + 0.024 \cdot \text{SL}$	$0.083 + 0.022 \cdot \text{SL}$	$0.079 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.304	$0.273 + 0.016 \cdot \text{SL}$	$0.282 + 0.013 \cdot \text{SL}$	$0.289 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.300	$0.266 + 0.017 \cdot \text{SL}$	$0.278 + 0.014 \cdot \text{SL}$	$0.292 + 0.013 \cdot \text{SL}$
AN to CO	t_R	0.123	$0.070 + 0.026 \cdot \text{SL}$	$0.067 + 0.027 \cdot \text{SL}$	$0.062 + 0.028 \cdot \text{SL}$
	t_F	0.117	$0.067 + 0.025 \cdot \text{SL}$	$0.070 + 0.024 \cdot \text{SL}$	$0.072 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.392	$0.362 + 0.015 \cdot \text{SL}$	$0.369 + 0.013 \cdot \text{SL}$	$0.376 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.393	$0.359 + 0.017 \cdot \text{SL}$	$0.369 + 0.014 \cdot \text{SL}$	$0.381 + 0.013 \cdot \text{SL}$
B to CO	t_R	0.169	$0.124 + 0.022 \cdot \text{SL}$	$0.118 + 0.024 \cdot \text{SL}$	$0.091 + 0.027 \cdot \text{SL}$
	t_F	0.165	$0.122 + 0.021 \cdot \text{SL}$	$0.124 + 0.021 \cdot \text{SL}$	$0.106 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.377	$0.346 + 0.015 \cdot \text{SL}$	$0.354 + 0.013 \cdot \text{SL}$	$0.361 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.405	$0.371 + 0.017 \cdot \text{SL}$	$0.381 + 0.014 \cdot \text{SL}$	$0.394 + 0.013 \cdot \text{SL}$
CI to CO	t_R	0.127	$0.073 + 0.027 \cdot \text{SL}$	$0.075 + 0.027 \cdot \text{SL}$	$0.067 + 0.028 \cdot \text{SL}$
	t_F	0.128	$0.078 + 0.025 \cdot \text{SL}$	$0.084 + 0.023 \cdot \text{SL}$	$0.084 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.221	$0.189 + 0.016 \cdot \text{SL}$	$0.199 + 0.013 \cdot \text{SL}$	$0.208 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.228	$0.191 + 0.018 \cdot \text{SL}$	$0.205 + 0.015 \cdot \text{SL}$	$0.221 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

Full Adder with one inverted input, 1X/2X Drive

Switching Characteristics
SCG23D2(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
AN to S	t_R	0.106	$0.079 + 0.014 \cdot \text{SL}$	$0.080 + 0.013 \cdot \text{SL}$	$0.073 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.087 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.095 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.420	$0.401 + 0.010 \cdot \text{SL}$	$0.410 + 0.007 \cdot \text{SL}$	$0.426 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.422	$0.400 + 0.011 \cdot \text{SL}$	$0.411 + 0.008 \cdot \text{SL}$	$0.433 + 0.007 \cdot \text{SL}$
B to S	t_R	0.107	$0.080 + 0.014 \cdot \text{SL}$	$0.081 + 0.013 \cdot \text{SL}$	$0.075 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.086 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.091 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.396	$0.376 + 0.010 \cdot \text{SL}$	$0.386 + 0.007 \cdot \text{SL}$	$0.403 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.411	$0.388 + 0.011 \cdot \text{SL}$	$0.400 + 0.008 \cdot \text{SL}$	$0.423 + 0.007 \cdot \text{SL}$
CI to S	t_R	0.107	$0.079 + 0.014 \cdot \text{SL}$	$0.081 + 0.013 \cdot \text{SL}$	$0.074 + 0.014 \cdot \text{SL}$
	t_F	0.111	$0.085 + 0.013 \cdot \text{SL}$	$0.089 + 0.012 \cdot \text{SL}$	$0.094 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.335	$0.315 + 0.010 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.342 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.328	$0.305 + 0.012 \cdot \text{SL}$	$0.317 + 0.008 \cdot \text{SL}$	$0.341 + 0.007 \cdot \text{SL}$
AN to CO	t_R	0.104	$0.077 + 0.013 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$	$0.072 + 0.014 \cdot \text{SL}$
	t_F	0.105	$0.079 + 0.013 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$	$0.087 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.414	$0.395 + 0.009 \cdot \text{SL}$	$0.403 + 0.007 \cdot \text{SL}$	$0.417 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.412	$0.391 + 0.011 \cdot \text{SL}$	$0.401 + 0.008 \cdot \text{SL}$	$0.421 + 0.007 \cdot \text{SL}$
B to CO	t_R	0.152	$0.133 + 0.010 \cdot \text{SL}$	$0.124 + 0.012 \cdot \text{SL}$	$0.103 + 0.013 \cdot \text{SL}$
	t_F	0.166	$0.146 + 0.010 \cdot \text{SL}$	$0.146 + 0.010 \cdot \text{SL}$	$0.129 + 0.011 \cdot \text{SL}$
	t_{PLH}	0.384	$0.364 + 0.010 \cdot \text{SL}$	$0.373 + 0.007 \cdot \text{SL}$	$0.388 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.406	$0.384 + 0.011 \cdot \text{SL}$	$0.394 + 0.008 \cdot \text{SL}$	$0.416 + 0.007 \cdot \text{SL}$
CI to CO	t_R	0.107	$0.080 + 0.013 \cdot \text{SL}$	$0.079 + 0.014 \cdot \text{SL}$	$0.076 + 0.014 \cdot \text{SL}$
	t_F	0.112	$0.085 + 0.013 \cdot \text{SL}$	$0.091 + 0.012 \cdot \text{SL}$	$0.097 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.227	$0.206 + 0.010 \cdot \text{SL}$	$0.216 + 0.007 \cdot \text{SL}$	$0.233 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.230	$0.207 + 0.012 \cdot \text{SL}$	$0.219 + 0.008 \cdot \text{SL}$	$0.245 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

MULTIPLEXERS


Cell List

Cell Name	Function Description
MX2DH	2 > 1 Non-Inverting Mux with 0.5X Drive
MX2	2 > 1 Non-Inverting Mux
MX2D2	2 > 1 Non-Inverting Mux with 2X Drive
MX2D4	2 > 1 Non-Inverting Mux with 4X Drive
MX2X4	4-Bit 2 > 1 Non-Inverting Mux
MX2IDH	2 > 1 Inverting Mux with 0.5X Drive
MX2I	2 > 1 Inverting Mux
MX2ID2	2 > 1 Inverting Mux with 2X Drive
MX2ID4	2 > 1 Inverting Mux with 4X Drive
MX2IDHA	2 > 1 Inverting Mux with Separate S and SN Inputs, 0.5X Drive
MX2IA	2 > 1 Inverting Mux with Separate S and SN Inputs
MX2ID2A	2 > 1 Inverting Mux with Separate S and SN Inputs, 2X Drive
MX2ID4A	2 > 1 Inverting Mux with Separate S and SN Inputs, 4X Drive
MX2IX4	4-Bit 2 > 1 Inverting Mux
MX3I	3 > 1 Inverting Mux
MX3ID2	3 > 1 Inverting Mux with 2X Drive
MX3ID4	3 > 1 Inverting Mux with 4X Drive
MX4	4 > 1 Non-Inverting Mux
MX4D2	4 > 1 Non-Inverting Mux with 2X Drive
MX4D4	4 > 1 Non-Inverting Mux with 4X Drive
MX8	8 > 1 Non-Inverting Mux
MX8D2	8 > 1 Non-Inverting Mux with 2X Drive
MX8D4	8 > 1 Non-inverting Mux with 4X Drive

MX2DH/MX2/MX2D2/MX2D4

2 > 1 Non-Inverting MUX with 0.5X/1X/2X/4X Drive

Logic Symbol




Truth Table

D0	D1	S	Y
0	x	0	0
1	x	0	1
x	0	1	0
x	1	1	1

Cell Data

Input Load (SL)											
MX2DH			MX2			MX2D2			MX2D4		
D0	D1	S	D0	D1	S	D0	D1	S	D0	D1	S
0.4	0.4	0.7	0.8	0.8	1.2	0.8	0.8	1.2	0.8	0.8	1.2
Gate Count											
MX2DH			MX2			MX2D2			MX2D4		
2.67			2.33			2.67			3.33		

Schematic Diagram



MX2DH/MX2/MX2D2/MX2D4

2 > 1 Non-Inverting MUX with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.187	$0.075 + 0.056 \cdot \text{SL}$	$0.066 + 0.058 \cdot \text{SL}$	$0.054 + 0.059 \cdot \text{SL}$
	t_F	0.174	$0.079 + 0.047 \cdot \text{SL}$	$0.079 + 0.047 \cdot \text{SL}$	$0.067 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.225	$0.167 + 0.029 \cdot \text{SL}$	$0.178 + 0.026 \cdot \text{SL}$	$0.180 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.239	$0.176 + 0.032 \cdot \text{SL}$	$0.194 + 0.027 \cdot \text{SL}$	$0.205 + 0.026 \cdot \text{SL}$
D1 to Y	t_R	0.187	$0.075 + 0.056 \cdot \text{SL}$	$0.067 + 0.058 \cdot \text{SL}$	$0.054 + 0.059 \cdot \text{SL}$
	t_F	0.174	$0.080 + 0.047 \cdot \text{SL}$	$0.080 + 0.047 \cdot \text{SL}$	$0.067 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.229	$0.171 + 0.029 \cdot \text{SL}$	$0.182 + 0.026 \cdot \text{SL}$	$0.185 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.243	$0.180 + 0.032 \cdot \text{SL}$	$0.198 + 0.027 \cdot \text{SL}$	$0.209 + 0.026 \cdot \text{SL}$
S to Y	t_R	0.186	$0.073 + 0.056 \cdot \text{SL}$	$0.067 + 0.058 \cdot \text{SL}$	$0.055 + 0.059 \cdot \text{SL}$
	t_F	0.171	$0.075 + 0.048 \cdot \text{SL}$	$0.078 + 0.047 \cdot \text{SL}$	$0.066 + 0.049 \cdot \text{SL}$
	t_{PLH}	0.236	$0.178 + 0.029 \cdot \text{SL}$	$0.188 + 0.026 \cdot \text{SL}$	$0.191 + 0.026 \cdot \text{SL}$
	t_{PHL}	0.243	$0.180 + 0.032 \cdot \text{SL}$	$0.198 + 0.027 \cdot \text{SL}$	$0.209 + 0.026 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.116	$0.062 + 0.027 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.065 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.176	$0.146 + 0.015 \cdot \text{SL}$	$0.154 + 0.013 \cdot \text{SL}$	$0.160 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.186	$0.152 + 0.017 \cdot \text{SL}$	$0.163 + 0.014 \cdot \text{SL}$	$0.175 + 0.013 \cdot \text{SL}$
D1 to Y	t_R	0.117	$0.064 + 0.027 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.179	$0.149 + 0.015 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$	$0.163 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.187	$0.153 + 0.017 \cdot \text{SL}$	$0.164 + 0.014 \cdot \text{SL}$	$0.176 + 0.013 \cdot \text{SL}$
S to Y	t_R	0.116	$0.061 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.053 + 0.028 \cdot \text{SL}$
	t_F	0.111	$0.061 + 0.025 \cdot \text{SL}$	$0.066 + 0.023 \cdot \text{SL}$	$0.063 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.180	$0.150 + 0.015 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.190	$0.156 + 0.017 \cdot \text{SL}$	$0.167 + 0.014 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2DH/MX2/MX2D2/MX2D4**2 > 1 Non-Inverting MUX with 0.5X/1X/2X/4X Drive****Switching Characteristics**(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**MX2D2**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.099	$0.072 + 0.014 \cdot \text{SL}$	$0.073 + 0.013 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.101	$0.074 + 0.013 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$	$0.083 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.186	$0.167 + 0.010 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$	$0.190 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.195	$0.173 + 0.011 \cdot \text{SL}$	$0.184 + 0.008 \cdot \text{SL}$	$0.206 + 0.007 \cdot \text{SL}$
D1 to Y	t_R	0.099	$0.072 + 0.014 \cdot \text{SL}$	$0.072 + 0.014 \cdot \text{SL}$	$0.067 + 0.014 \cdot \text{SL}$
	t_F	0.102	$0.075 + 0.013 \cdot \text{SL}$	$0.080 + 0.012 \cdot \text{SL}$	$0.082 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.189	$0.170 + 0.010 \cdot \text{SL}$	$0.178 + 0.007 \cdot \text{SL}$	$0.193 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.196	$0.174 + 0.011 \cdot \text{SL}$	$0.185 + 0.008 \cdot \text{SL}$	$0.207 + 0.007 \cdot \text{SL}$
S to Y	t_R	0.099	$0.073 + 0.013 \cdot \text{SL}$	$0.071 + 0.014 \cdot \text{SL}$	$0.065 + 0.014 \cdot \text{SL}$
	t_F	0.098	$0.070 + 0.014 \cdot \text{SL}$	$0.077 + 0.012 \cdot \text{SL}$	$0.081 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.186	$0.167 + 0.010 \cdot \text{SL}$	$0.176 + 0.007 \cdot \text{SL}$	$0.191 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.196	$0.174 + 0.011 \cdot \text{SL}$	$0.185 + 0.008 \cdot \text{SL}$	$0.208 + 0.007 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$ **MX2D4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.116	$0.102 + 0.007 \cdot \text{SL}$	$0.103 + 0.007 \cdot \text{SL}$	$0.101 + 0.007 \cdot \text{SL}$
	t_F	0.123	$0.107 + 0.008 \cdot \text{SL}$	$0.113 + 0.006 \cdot \text{SL}$	$0.124 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.228	$0.215 + 0.006 \cdot \text{SL}$	$0.223 + 0.004 \cdot \text{SL}$	$0.249 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.242	$0.228 + 0.007 \cdot \text{SL}$	$0.237 + 0.005 \cdot \text{SL}$	$0.269 + 0.004 \cdot \text{SL}$
D1 to Y	t_R	0.117	$0.103 + 0.007 \cdot \text{SL}$	$0.103 + 0.007 \cdot \text{SL}$	$0.102 + 0.007 \cdot \text{SL}$
	t_F	0.123	$0.107 + 0.008 \cdot \text{SL}$	$0.114 + 0.006 \cdot \text{SL}$	$0.124 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.231	$0.219 + 0.006 \cdot \text{SL}$	$0.227 + 0.004 \cdot \text{SL}$	$0.252 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.243	$0.228 + 0.007 \cdot \text{SL}$	$0.237 + 0.005 \cdot \text{SL}$	$0.270 + 0.004 \cdot \text{SL}$
S to Y	t_R	0.116	$0.102 + 0.007 \cdot \text{SL}$	$0.103 + 0.007 \cdot \text{SL}$	$0.101 + 0.007 \cdot \text{SL}$
	t_F	0.122	$0.105 + 0.008 \cdot \text{SL}$	$0.113 + 0.006 \cdot \text{SL}$	$0.123 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.223	$0.211 + 0.006 \cdot \text{SL}$	$0.219 + 0.004 \cdot \text{SL}$	$0.244 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.239	$0.224 + 0.007 \cdot \text{SL}$	$0.233 + 0.005 \cdot \text{SL}$	$0.266 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

MX2X4

4-Bit 2 > 1 Non-Inverting MUX

Logic Symbol



Truth Table

S	Y0	Y1	Y2	Y3
0	D00	D01	D02	D03
1	D10	D11	D12	D13

Cell Data

Input Load (SL)									Gate Count
D00	D10	D01	D11	D02	D12	D03	D13	S	8.00
0.8	0.8	0.9	0.8	0.8	0.8	0.8	0.8	3.4	

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2X4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D00 to Y0	t_R	0.119	$0.066 + 0.027 \cdot \text{SL}$	$0.063 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.066 + 0.024 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.067 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.181	$0.150 + 0.015 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.187	$0.153 + 0.017 \cdot \text{SL}$	$0.164 + 0.014 \cdot \text{SL}$	$0.176 + 0.013 \cdot \text{SL}$
D10 to Y0	t_R	0.119	$0.065 + 0.027 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.116	$0.066 + 0.025 \cdot \text{SL}$	$0.073 + 0.023 \cdot \text{SL}$	$0.068 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.181	$0.150 + 0.015 \cdot \text{SL}$	$0.159 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.191	$0.156 + 0.017 \cdot \text{SL}$	$0.168 + 0.014 \cdot \text{SL}$	$0.180 + 0.013 \cdot \text{SL}$
S to Y0	t_R	0.122	$0.069 + 0.027 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.065 + 0.025 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.201	$0.171 + 0.015 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.185 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.213	$0.178 + 0.017 \cdot \text{SL}$	$0.189 + 0.014 \cdot \text{SL}$	$0.201 + 0.013 \cdot \text{SL}$
D01 to Y1	t_R	0.118	$0.064 + 0.027 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.055 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.065 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.179	$0.148 + 0.015 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$	$0.162 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.186	$0.151 + 0.017 \cdot \text{SL}$	$0.163 + 0.014 \cdot \text{SL}$	$0.174 + 0.013 \cdot \text{SL}$
D11 to Y1	t_R	0.116	$0.062 + 0.027 \cdot \text{SL}$	$0.061 + 0.027 \cdot \text{SL}$	$0.054 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.065 + 0.024 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.064 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.178	$0.147 + 0.015 \cdot \text{SL}$	$0.156 + 0.013 \cdot \text{SL}$	$0.161 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.185	$0.151 + 0.017 \cdot \text{SL}$	$0.162 + 0.014 \cdot \text{SL}$	$0.174 + 0.013 \cdot \text{SL}$
S to Y1	t_R	0.121	$0.067 + 0.027 \cdot \text{SL}$	$0.065 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.112	$0.063 + 0.025 \cdot \text{SL}$	$0.069 + 0.023 \cdot \text{SL}$	$0.064 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.201	$0.170 + 0.015 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.185 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.209	$0.175 + 0.017 \cdot \text{SL}$	$0.186 + 0.014 \cdot \text{SL}$	$0.198 + 0.013 \cdot \text{SL}$
D02 to Y2	t_R	0.117	$0.065 + 0.026 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.065 + 0.025 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.182	$0.151 + 0.015 \cdot \text{SL}$	$0.160 + 0.013 \cdot \text{SL}$	$0.166 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.188	$0.154 + 0.017 \cdot \text{SL}$	$0.165 + 0.014 \cdot \text{SL}$	$0.177 + 0.013 \cdot \text{SL}$
D12 to Y2	t_R	0.117	$0.064 + 0.026 \cdot \text{SL}$	$0.062 + 0.027 \cdot \text{SL}$	$0.056 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.066 + 0.024 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.066 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.179	$0.149 + 0.015 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$	$0.163 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.187	$0.153 + 0.017 \cdot \text{SL}$	$0.164 + 0.014 \cdot \text{SL}$	$0.176 + 0.013 \cdot \text{SL}$
S to Y2	t_R	0.120	$0.068 + 0.026 \cdot \text{SL}$	$0.066 + 0.027 \cdot \text{SL}$	$0.057 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.064 + 0.025 \cdot \text{SL}$	$0.070 + 0.023 \cdot \text{SL}$	$0.065 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.200	$0.170 + 0.015 \cdot \text{SL}$	$0.179 + 0.013 \cdot \text{SL}$	$0.185 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.211	$0.177 + 0.017 \cdot \text{SL}$	$0.188 + 0.014 \cdot \text{SL}$	$0.200 + 0.013 \cdot \text{SL}$
D03 to Y3	t_R	0.121	$0.068 + 0.027 \cdot \text{SL}$	$0.065 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.067 + 0.024 \cdot \text{SL}$	$0.073 + 0.023 \cdot \text{SL}$	$0.068 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.180	$0.150 + 0.015 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.189	$0.156 + 0.017 \cdot \text{SL}$	$0.167 + 0.014 \cdot \text{SL}$	$0.178 + 0.013 \cdot \text{SL}$

MX2X4

4-Bit 2 > 1 Non-Inverting MUX

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2X4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D13 to Y3	t_R	0.121	$0.067 + 0.027 \cdot \text{SL}$	$0.064 + 0.027 \cdot \text{SL}$	$0.058 + 0.028 \cdot \text{SL}$
	t_F	0.115	$0.068 + 0.024 \cdot \text{SL}$	$0.072 + 0.023 \cdot \text{SL}$	$0.067 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.180	$0.150 + 0.015 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$	$0.164 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.188	$0.154 + 0.017 \cdot \text{SL}$	$0.165 + 0.014 \cdot \text{SL}$	$0.176 + 0.013 \cdot \text{SL}$
S to Y3	t_R	0.124	$0.071 + 0.026 \cdot \text{SL}$	$0.068 + 0.027 \cdot \text{SL}$	$0.060 + 0.028 \cdot \text{SL}$
	t_F	0.114	$0.066 + 0.024 \cdot \text{SL}$	$0.071 + 0.023 \cdot \text{SL}$	$0.067 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.203	$0.172 + 0.015 \cdot \text{SL}$	$0.181 + 0.013 \cdot \text{SL}$	$0.186 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.212	$0.178 + 0.017 \cdot \text{SL}$	$0.189 + 0.014 \cdot \text{SL}$	$0.200 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2IDH/MX2I/MX2ID2/MX2ID4

2 > 1 Inverting MUX with 0.5X/1X/2X/4X Drive

Logic Symbol




Truth Table

D0	D1	S	YN
0	x	0	1
1	x	0	0
x	0	1	1
x	1	1	0

Cell Data

Input Load (SL)											
MX2IDH			MX2I			MX2ID2			MX2ID4		
D0	D1	S	D0	D1	S	D0	D1	S	D0	D1	S
0.5	0.6	0.8	1.0	1.1	1.7	1.1	1.2	1.7	1.1	1.2	1.7
Gate Count											
MX2IDH			MX2I			MX2ID2			MX2ID4		
2.00			2.00			3.00			3.33		

Schematic Diagram



MX2IDH/MX2I/MX2ID2/MX2ID4

2 > 1 Inverting MUX with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2IDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.385	$0.156 + 0.114 \cdot \text{SL}$	$0.141 + 0.118 \cdot \text{SL}$	$0.137 + 0.119 \cdot \text{SL}$
	t_F	0.253	$0.115 + 0.069 \cdot \text{SL}$	$0.098 + 0.074 \cdot \text{SL}$	$0.082 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.195	$0.094 + 0.051 \cdot \text{SL}$	$0.093 + 0.051 \cdot \text{SL}$	$0.093 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.145	$0.073 + 0.036 \cdot \text{SL}$	$0.074 + 0.036 \cdot \text{SL}$	$0.075 + 0.036 \cdot \text{SL}$
D1 to YN	t_R	0.386	$0.155 + 0.116 \cdot \text{SL}$	$0.145 + 0.118 \cdot \text{SL}$	$0.140 + 0.119 \cdot \text{SL}$
	t_F	0.311	$0.174 + 0.069 \cdot \text{SL}$	$0.156 + 0.073 \cdot \text{SL}$	$0.139 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.225	$0.122 + 0.052 \cdot \text{SL}$	$0.124 + 0.051 \cdot \text{SL}$	$0.126 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.184	$0.110 + 0.037 \cdot \text{SL}$	$0.113 + 0.036 \cdot \text{SL}$	$0.114 + 0.036 \cdot \text{SL}$
S to YN	t_R	0.379	$0.144 + 0.118 \cdot \text{SL}$	$0.140 + 0.119 \cdot \text{SL}$	$0.140 + 0.119 \cdot \text{SL}$
	t_F	0.276	$0.134 + 0.071 \cdot \text{SL}$	$0.120 + 0.075 \cdot \text{SL}$	$0.111 + 0.076 \cdot \text{SL}$
	t_{PLH}	0.256	$0.154 + 0.051 \cdot \text{SL}$	$0.155 + 0.051 \cdot \text{SL}$	$0.155 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.220	$0.147 + 0.037 \cdot \text{SL}$	$0.150 + 0.036 \cdot \text{SL}$	$0.150 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.255	$0.151 + 0.052 \cdot \text{SL}$	$0.144 + 0.054 \cdot \text{SL}$	$0.129 + 0.055 \cdot \text{SL}$
	t_F	0.179	$0.117 + 0.031 \cdot \text{SL}$	$0.106 + 0.034 \cdot \text{SL}$	$0.091 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.137	$0.090 + 0.023 \cdot \text{SL}$	$0.089 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.105	$0.067 + 0.019 \cdot \text{SL}$	$0.073 + 0.017 \cdot \text{SL}$	$0.073 + 0.017 \cdot \text{SL}$
D1 to YN	t_R	0.253	$0.147 + 0.053 \cdot \text{SL}$	$0.141 + 0.055 \cdot \text{SL}$	$0.133 + 0.055 \cdot \text{SL}$
	t_F	0.233	$0.170 + 0.031 \cdot \text{SL}$	$0.161 + 0.034 \cdot \text{SL}$	$0.144 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.161	$0.111 + 0.025 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$	$0.115 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.141	$0.106 + 0.018 \cdot \text{SL}$	$0.107 + 0.017 \cdot \text{SL}$	$0.108 + 0.017 \cdot \text{SL}$
S to YN	t_R	0.248	$0.142 + 0.053 \cdot \text{SL}$	$0.136 + 0.055 \cdot \text{SL}$	$0.130 + 0.055 \cdot \text{SL}$
	t_F	0.198	$0.133 + 0.032 \cdot \text{SL}$	$0.124 + 0.035 \cdot \text{SL}$	$0.110 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.187	$0.139 + 0.024 \cdot \text{SL}$	$0.140 + 0.024 \cdot \text{SL}$	$0.140 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.164	$0.128 + 0.018 \cdot \text{SL}$	$0.131 + 0.017 \cdot \text{SL}$	$0.132 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2IDH/MX2I/MX2ID2/MX2ID4

2 > 1 Inverting MUX with 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2ID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.013 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.245	$0.229 + 0.008 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.211	$0.193 + 0.009 \cdot \text{SL}$	$0.200 + 0.007 \cdot \text{SL}$	$0.210 + 0.006 \cdot \text{SL}$
D1 to YN	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.051 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.049 + 0.012 \cdot \text{SL}$	$0.051 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.267	$0.251 + 0.008 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.251	$0.234 + 0.009 \cdot \text{SL}$	$0.241 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
S to YN	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.041 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.048 + 0.012 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.296	$0.280 + 0.008 \cdot \text{SL}$	$0.286 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.264	$0.247 + 0.009 \cdot \text{SL}$	$0.254 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

MX2ID4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.263	$0.254 + 0.005 \cdot \text{SL}$	$0.258 + 0.004 \cdot \text{SL}$	$0.269 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.223	$0.213 + 0.005 \cdot \text{SL}$	$0.218 + 0.004 \cdot \text{SL}$	$0.233 + 0.003 \cdot \text{SL}$
D1 to YN	t_R	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.056 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.285	$0.275 + 0.005 \cdot \text{SL}$	$0.280 + 0.003 \cdot \text{SL}$	$0.290 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.261	$0.251 + 0.005 \cdot \text{SL}$	$0.256 + 0.004 \cdot \text{SL}$	$0.272 + 0.003 \cdot \text{SL}$
S to YN	t_R	0.074	$0.061 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.315	$0.305 + 0.005 \cdot \text{SL}$	$0.310 + 0.003 \cdot \text{SL}$	$0.321 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.278	$0.268 + 0.005 \cdot \text{SL}$	$0.273 + 0.004 \cdot \text{SL}$	$0.289 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

MX2IDHA/MX2IA/MX2ID2A/MX2ID4A

2 > 1 Inverting MUX with Separate S and SN Inputs, 0.5X/1X/2X/4X Drive

Logic Symbol




Truth Table

D0	D1	S	SN	YN
0	x	0	1	1
1	x	0	1	0
x	0	1	0	1
x	1	1	0	0

Cell Data

Input Load (SL)															
MX2IDHA				MX2IA				MX2ID2A				MX2ID4A			
D0	D1	S	SN	D0	D1	S	SN	D0	D1	S	SN	D0	D1	S	SN
0.5	0.5	0.5	0.5	1.0	1.0	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
Gate Count															
MX2IDHA				MX2IA				MX2ID2A				MX2ID4A			
1.67				1.67				2.67				3.00			

Schematic Diagram



MX2IDHA/MX2IA/MX2ID2A/MX2ID4A

2 > 1 Inverting MUX with Separate S and SN Inputs, 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2IDHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.394	$0.164 + 0.115 \cdot \text{SL}$	$0.149 + 0.119 \cdot \text{SL}$	$0.144 + 0.119 \cdot \text{SL}$
	t_F	0.254	$0.116 + 0.069 \cdot \text{SL}$	$0.099 + 0.074 \cdot \text{SL}$	$0.083 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.195	$0.094 + 0.051 \cdot \text{SL}$	$0.093 + 0.051 \cdot \text{SL}$	$0.092 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.147	$0.075 + 0.036 \cdot \text{SL}$	$0.076 + 0.036 \cdot \text{SL}$	$0.076 + 0.036 \cdot \text{SL}$
D1 to YN	t_R	0.393	$0.161 + 0.116 \cdot \text{SL}$	$0.151 + 0.119 \cdot \text{SL}$	$0.146 + 0.119 \cdot \text{SL}$
	t_F	0.301	$0.161 + 0.070 \cdot \text{SL}$	$0.147 + 0.074 \cdot \text{SL}$	$0.133 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.230	$0.126 + 0.052 \cdot \text{SL}$	$0.128 + 0.051 \cdot \text{SL}$	$0.130 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.189	$0.115 + 0.037 \cdot \text{SL}$	$0.118 + 0.036 \cdot \text{SL}$	$0.120 + 0.036 \cdot \text{SL}$
S to YN	t_R	0.417	$0.184 + 0.116 \cdot \text{SL}$	$0.175 + 0.119 \cdot \text{SL}$	$0.171 + 0.119 \cdot \text{SL}$
	t_F	0.297	$0.154 + 0.071 \cdot \text{SL}$	$0.143 + 0.074 \cdot \text{SL}$	$0.134 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.245	$0.142 + 0.051 \cdot \text{SL}$	$0.143 + 0.051 \cdot \text{SL}$	$0.144 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.183	$0.109 + 0.037 \cdot \text{SL}$	$0.112 + 0.036 \cdot \text{SL}$	$0.114 + 0.036 \cdot \text{SL}$
SN to YN	t_R	0.418	$0.188 + 0.115 \cdot \text{SL}$	$0.173 + 0.119 \cdot \text{SL}$	$0.169 + 0.119 \cdot \text{SL}$
	t_F	0.248	$0.106 + 0.071 \cdot \text{SL}$	$0.094 + 0.074 \cdot \text{SL}$	$0.083 + 0.075 \cdot \text{SL}$
	t_{PLH}	0.210	$0.109 + 0.050 \cdot \text{SL}$	$0.107 + 0.051 \cdot \text{SL}$	$0.106 + 0.051 \cdot \text{SL}$
	t_{PHL}	0.141	$0.068 + 0.037 \cdot \text{SL}$	$0.070 + 0.036 \cdot \text{SL}$	$0.071 + 0.036 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2IA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.260	$0.154 + 0.053 \cdot \text{SL}$	$0.147 + 0.055 \cdot \text{SL}$	$0.133 + 0.056 \cdot \text{SL}$
	t_F	0.179	$0.117 + 0.031 \cdot \text{SL}$	$0.105 + 0.034 \cdot \text{SL}$	$0.090 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.137	$0.090 + 0.024 \cdot \text{SL}$	$0.089 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.105	$0.067 + 0.019 \cdot \text{SL}$	$0.073 + 0.017 \cdot \text{SL}$	$0.073 + 0.017 \cdot \text{SL}$
D1 to YN	t_R	0.256	$0.149 + 0.053 \cdot \text{SL}$	$0.143 + 0.055 \cdot \text{SL}$	$0.134 + 0.056 \cdot \text{SL}$
	t_F	0.218	$0.153 + 0.032 \cdot \text{SL}$	$0.147 + 0.034 \cdot \text{SL}$	$0.133 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.164	$0.114 + 0.025 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$	$0.117 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.144	$0.109 + 0.018 \cdot \text{SL}$	$0.110 + 0.017 \cdot \text{SL}$	$0.111 + 0.017 \cdot \text{SL}$
S to YN	t_R	0.278	$0.170 + 0.054 \cdot \text{SL}$	$0.165 + 0.055 \cdot \text{SL}$	$0.158 + 0.056 \cdot \text{SL}$
	t_F	0.212	$0.145 + 0.034 \cdot \text{SL}$	$0.140 + 0.035 \cdot \text{SL}$	$0.131 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.178	$0.129 + 0.024 \cdot \text{SL}$	$0.130 + 0.024 \cdot \text{SL}$	$0.131 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.138	$0.101 + 0.018 \cdot \text{SL}$	$0.103 + 0.018 \cdot \text{SL}$	$0.105 + 0.017 \cdot \text{SL}$
SN to YN	t_R	0.283	$0.179 + 0.052 \cdot \text{SL}$	$0.170 + 0.055 \cdot \text{SL}$	$0.156 + 0.056 \cdot \text{SL}$
	t_F	0.172	$0.108 + 0.032 \cdot \text{SL}$	$0.097 + 0.035 \cdot \text{SL}$	$0.086 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.152	$0.105 + 0.023 \cdot \text{SL}$	$0.103 + 0.024 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.098	$0.061 + 0.019 \cdot \text{SL}$	$0.066 + 0.017 \cdot \text{SL}$	$0.067 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX2IDHA/MX2IA/MX2ID2A/MX2ID4A

2 > 1 Inverting MUX with Separate S and SN Inputs, 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2ID2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.053 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.070	$0.045 + 0.013 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.042 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.248	$0.232 + 0.008 \cdot \text{SL}$	$0.238 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.213	$0.195 + 0.009 \cdot \text{SL}$	$0.203 + 0.007 \cdot \text{SL}$	$0.212 + 0.006 \cdot \text{SL}$
D1 to YN	t_R	0.080	$0.054 + 0.013 \cdot \text{SL}$	$0.052 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.049 + 0.011 \cdot \text{SL}$	$0.049 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.268	$0.252 + 0.008 \cdot \text{SL}$	$0.257 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.251	$0.234 + 0.009 \cdot \text{SL}$	$0.241 + 0.007 \cdot \text{SL}$	$0.251 + 0.006 \cdot \text{SL}$
S to YN	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.046 + 0.012 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.288	$0.272 + 0.008 \cdot \text{SL}$	$0.278 + 0.007 \cdot \text{SL}$	$0.283 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.245	$0.227 + 0.009 \cdot \text{SL}$	$0.235 + 0.007 \cdot \text{SL}$	$0.244 + 0.006 \cdot \text{SL}$
SN to YN	t_R	0.079	$0.053 + 0.013 \cdot \text{SL}$	$0.052 + 0.014 \cdot \text{SL}$	$0.042 + 0.014 \cdot \text{SL}$
	t_F	0.071	$0.047 + 0.012 \cdot \text{SL}$	$0.050 + 0.011 \cdot \text{SL}$	$0.043 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.268	$0.252 + 0.008 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.264 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.207	$0.190 + 0.009 \cdot \text{SL}$	$0.197 + 0.007 \cdot \text{SL}$	$0.207 + 0.006 \cdot \text{SL}$


*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

MX2ID4A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.060 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.055 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.269	$0.259 + 0.005 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$	$0.275 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.229	$0.218 + 0.005 \cdot \text{SL}$	$0.224 + 0.004 \cdot \text{SL}$	$0.239 + 0.003 \cdot \text{SL}$
D1 to YN	t_R	0.074	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$	$0.049 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.052 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.282 + 0.003 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.266	$0.255 + 0.005 \cdot \text{SL}$	$0.261 + 0.004 \cdot \text{SL}$	$0.276 + 0.003 \cdot \text{SL}$
S to YN	t_R	0.074	$0.061 + 0.007 \cdot \text{SL}$	$0.062 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.054 + 0.006 \cdot \text{SL}$	$0.055 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.307	$0.297 + 0.005 \cdot \text{SL}$	$0.302 + 0.003 \cdot \text{SL}$	$0.313 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.259	$0.249 + 0.005 \cdot \text{SL}$	$0.254 + 0.004 \cdot \text{SL}$	$0.269 + 0.003 \cdot \text{SL}$
SN to YN	t_R	0.075	$0.062 + 0.006 \cdot \text{SL}$	$0.061 + 0.007 \cdot \text{SL}$	$0.050 + 0.007 \cdot \text{SL}$
	t_F	0.066	$0.053 + 0.007 \cdot \text{SL}$	$0.056 + 0.006 \cdot \text{SL}$	$0.051 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.289	$0.279 + 0.005 \cdot \text{SL}$	$0.284 + 0.003 \cdot \text{SL}$	$0.295 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.223	$0.212 + 0.005 \cdot \text{SL}$	$0.218 + 0.004 \cdot \text{SL}$	$0.233 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

Logic Symbol



Truth Table

S	YN0	YN1	YN2	YN3
0	$\overline{D00}$	$\overline{D01}$	$\overline{D02}$	$\overline{D03}$
1	$\overline{D10}$	$\overline{D11}$	$\overline{D12}$	$\overline{D13}$

Cell Data

Input Load (SL)									Gate Count
D00	D10	D01	D11	D02	D12	D03	D13	S	6.33
1.0	1.1	1.0	1.1	1.1	1.1	1.0	1.1	5.5	

MX2IX4

4-Bit 2 > 1 Inverting MUX

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX2IX4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D00 to YN0	t_R	0.250	$0.145 + 0.052 \cdot \text{SL}$	$0.138 + 0.054 \cdot \text{SL}$	$0.124 + 0.056 \cdot \text{SL}$
	t_F	0.177	$0.116 + 0.031 \cdot \text{SL}$	$0.103 + 0.034 \cdot \text{SL}$	$0.088 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.135	$0.088 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$	$0.087 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.102	$0.064 + 0.019 \cdot \text{SL}$	$0.071 + 0.017 \cdot \text{SL}$	$0.071 + 0.017 \cdot \text{SL}$
D10 to YN0	t_R	0.247	$0.140 + 0.053 \cdot \text{SL}$	$0.135 + 0.055 \cdot \text{SL}$	$0.126 + 0.056 \cdot \text{SL}$
	t_F	0.232	$0.169 + 0.031 \cdot \text{SL}$	$0.159 + 0.034 \cdot \text{SL}$	$0.142 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.157	$0.108 + 0.025 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$	$0.112 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.140	$0.104 + 0.018 \cdot \text{SL}$	$0.105 + 0.018 \cdot \text{SL}$	$0.106 + 0.017 \cdot \text{SL}$
S to YN0	t_R	0.242	$0.136 + 0.053 \cdot \text{SL}$	$0.129 + 0.055 \cdot \text{SL}$	$0.122 + 0.056 \cdot \text{SL}$
	t_F	0.194	$0.127 + 0.034 \cdot \text{SL}$	$0.122 + 0.035 \cdot \text{SL}$	$0.108 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.226	$0.179 + 0.024 \cdot \text{SL}$	$0.179 + 0.024 \cdot \text{SL}$	$0.177 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.178	$0.141 + 0.019 \cdot \text{SL}$	$0.145 + 0.018 \cdot \text{SL}$	$0.148 + 0.017 \cdot \text{SL}$
D01 to YN1	t_R	0.252	$0.147 + 0.053 \cdot \text{SL}$	$0.141 + 0.054 \cdot \text{SL}$	$0.126 + 0.056 \cdot \text{SL}$
	t_F	0.178	$0.117 + 0.031 \cdot \text{SL}$	$0.104 + 0.034 \cdot \text{SL}$	$0.089 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.136	$0.089 + 0.024 \cdot \text{SL}$	$0.088 + 0.024 \cdot \text{SL}$	$0.087 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.102	$0.064 + 0.019 \cdot \text{SL}$	$0.071 + 0.017 \cdot \text{SL}$	$0.071 + 0.017 \cdot \text{SL}$
D11 to YN1	t_R	0.248	$0.142 + 0.053 \cdot \text{SL}$	$0.136 + 0.055 \cdot \text{SL}$	$0.128 + 0.056 \cdot \text{SL}$
	t_F	0.234	$0.172 + 0.031 \cdot \text{SL}$	$0.162 + 0.034 \cdot \text{SL}$	$0.144 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.160	$0.110 + 0.025 \cdot \text{SL}$	$0.113 + 0.024 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.140	$0.105 + 0.018 \cdot \text{SL}$	$0.106 + 0.017 \cdot \text{SL}$	$0.107 + 0.017 \cdot \text{SL}$
S to YN1	t_R	0.245	$0.138 + 0.054 \cdot \text{SL}$	$0.132 + 0.055 \cdot \text{SL}$	$0.125 + 0.056 \cdot \text{SL}$
	t_F	0.195	$0.128 + 0.033 \cdot \text{SL}$	$0.124 + 0.035 \cdot \text{SL}$	$0.110 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.226	$0.178 + 0.024 \cdot \text{SL}$	$0.178 + 0.024 \cdot \text{SL}$	$0.177 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.178	$0.141 + 0.019 \cdot \text{SL}$	$0.146 + 0.018 \cdot \text{SL}$	$0.148 + 0.017 \cdot \text{SL}$
D02 to YN2	t_R	0.258	$0.153 + 0.053 \cdot \text{SL}$	$0.146 + 0.054 \cdot \text{SL}$	$0.131 + 0.056 \cdot \text{SL}$
	t_F	0.182	$0.119 + 0.031 \cdot \text{SL}$	$0.109 + 0.034 \cdot \text{SL}$	$0.093 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.138	$0.091 + 0.024 \cdot \text{SL}$	$0.090 + 0.024 \cdot \text{SL}$	$0.090 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.103	$0.065 + 0.019 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$	$0.072 + 0.017 \cdot \text{SL}$
D12 to YN2	t_R	0.251	$0.145 + 0.053 \cdot \text{SL}$	$0.139 + 0.055 \cdot \text{SL}$	$0.131 + 0.055 \cdot \text{SL}$
	t_F	0.236	$0.174 + 0.031 \cdot \text{SL}$	$0.164 + 0.034 \cdot \text{SL}$	$0.148 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.161	$0.112 + 0.025 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$	$0.116 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.142	$0.106 + 0.018 \cdot \text{SL}$	$0.107 + 0.017 \cdot \text{SL}$	$0.109 + 0.017 \cdot \text{SL}$
S to YN2	t_R	0.251	$0.143 + 0.054 \cdot \text{SL}$	$0.138 + 0.055 \cdot \text{SL}$	$0.130 + 0.056 \cdot \text{SL}$
	t_F	0.197	$0.131 + 0.033 \cdot \text{SL}$	$0.126 + 0.035 \cdot \text{SL}$	$0.113 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.226	$0.179 + 0.024 \cdot \text{SL}$	$0.179 + 0.024 \cdot \text{SL}$	$0.177 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.179	$0.142 + 0.019 \cdot \text{SL}$	$0.147 + 0.018 \cdot \text{SL}$	$0.149 + 0.017 \cdot \text{SL}$
D03 to YN3	t_R	0.259	$0.155 + 0.052 \cdot \text{SL}$	$0.148 + 0.054 \cdot \text{SL}$	$0.133 + 0.055 \cdot \text{SL}$
	t_F	0.181	$0.118 + 0.031 \cdot \text{SL}$	$0.109 + 0.034 \cdot \text{SL}$	$0.094 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.139	$0.092 + 0.023 \cdot \text{SL}$	$0.091 + 0.024 \cdot \text{SL}$	$0.090 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.106	$0.069 + 0.019 \cdot \text{SL}$	$0.075 + 0.017 \cdot \text{SL}$	$0.075 + 0.017 \cdot \text{SL}$

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)**MX2IX4**


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D13 to YN3	t_R	0.257	$0.151 + 0.053 \cdot \text{SL}$	$0.144 + 0.055 \cdot \text{SL}$	$0.137 + 0.056 \cdot \text{SL}$
	t_F	0.234	$0.171 + 0.031 \cdot \text{SL}$	$0.161 + 0.034 \cdot \text{SL}$	$0.145 + 0.035 \cdot \text{SL}$
	t_{PLH}	0.161	$0.112 + 0.025 \cdot \text{SL}$	$0.114 + 0.024 \cdot \text{SL}$	$0.115 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.142	$0.107 + 0.018 \cdot \text{SL}$	$0.108 + 0.017 \cdot \text{SL}$	$0.109 + 0.017 \cdot \text{SL}$
S to YN3	t_R	0.251	$0.144 + 0.053 \cdot \text{SL}$	$0.137 + 0.055 \cdot \text{SL}$	$0.131 + 0.056 \cdot \text{SL}$
	t_F	0.196	$0.129 + 0.033 \cdot \text{SL}$	$0.124 + 0.035 \cdot \text{SL}$	$0.112 + 0.036 \cdot \text{SL}$
	t_{PLH}	0.230	$0.183 + 0.024 \cdot \text{SL}$	$0.183 + 0.024 \cdot \text{SL}$	$0.181 + 0.024 \cdot \text{SL}$
	t_{PHL}	0.183	$0.145 + 0.019 \cdot \text{SL}$	$0.150 + 0.018 \cdot \text{SL}$	$0.152 + 0.017 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX3I/MX3ID2/MX3ID4

3 > 1 Inverting MUX with 1X/2X/4X Drive

Logic Symbol




Truth Table

S0	S1	YN
0	0	D0
1	0	D1
x	1	D2

Cell Data

Input Load (SL)															
MX3I					MX3ID2					MX3ID4					
D0	D1	D2	S0	S1	D0	D1	D2	S0	S1	D0	D1	D2	S0	S1	
0.8	0.9	0.8	1.2	1.2	0.8	0.9	0.8	1.2	1.2	0.8	0.9	0.8	1.2	1.2	
Gate Count															
MX3I					MX3ID2					MX3ID4					
4.67					4.67					5.33					

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX3I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.110	$0.059 + 0.025 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.050 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.317	$0.289 + 0.014 \cdot \text{SL}$	$0.295 + 0.012 \cdot \text{SL}$	$0.296 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.307	$0.277 + 0.015 \cdot \text{SL}$	$0.284 + 0.013 \cdot \text{SL}$	$0.287 + 0.013 \cdot \text{SL}$
D1 to YN	t_R	0.110	$0.059 + 0.026 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.050 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.319	$0.291 + 0.014 \cdot \text{SL}$	$0.297 + 0.012 \cdot \text{SL}$	$0.298 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.306	$0.276 + 0.015 \cdot \text{SL}$	$0.283 + 0.013 \cdot \text{SL}$	$0.286 + 0.013 \cdot \text{SL}$
D2 to YN	t_R	0.103	$0.050 + 0.026 \cdot \text{SL}$	$0.046 + 0.027 \cdot \text{SL}$	$0.039 + 0.028 \cdot \text{SL}$
	t_F	0.091	$0.043 + 0.024 \cdot \text{SL}$	$0.045 + 0.023 \cdot \text{SL}$	$0.036 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.233	$0.206 + 0.014 \cdot \text{SL}$	$0.210 + 0.012 \cdot \text{SL}$	$0.211 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.224	$0.195 + 0.015 \cdot \text{SL}$	$0.201 + 0.013 \cdot \text{SL}$	$0.204 + 0.013 \cdot \text{SL}$
S0 to YN	t_R	0.110	$0.059 + 0.025 \cdot \text{SL}$	$0.053 + 0.027 \cdot \text{SL}$	$0.043 + 0.028 \cdot \text{SL}$
	t_F	0.095	$0.049 + 0.023 \cdot \text{SL}$	$0.048 + 0.023 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.317	$0.289 + 0.014 \cdot \text{SL}$	$0.294 + 0.012 \cdot \text{SL}$	$0.296 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.307	$0.278 + 0.015 \cdot \text{SL}$	$0.285 + 0.013 \cdot \text{SL}$	$0.288 + 0.013 \cdot \text{SL}$
S1 to YN	t_R	0.107	$0.056 + 0.026 \cdot \text{SL}$	$0.049 + 0.027 \cdot \text{SL}$	$0.042 + 0.028 \cdot \text{SL}$
	t_F	0.094	$0.049 + 0.022 \cdot \text{SL}$	$0.044 + 0.024 \cdot \text{SL}$	$0.039 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.238	$0.210 + 0.014 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$	$0.217 + 0.012 \cdot \text{SL}$
	t_{PHL}	0.249	$0.220 + 0.015 \cdot \text{SL}$	$0.227 + 0.013 \cdot \text{SL}$	$0.230 + 0.013 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX3I/MX3ID2/MX3ID4

3 > 1 Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX3ID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.089	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.012 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.333	$0.317 + 0.008 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.322	$0.304 + 0.009 \cdot \text{SL}$	$0.311 + 0.007 \cdot \text{SL}$	$0.322 + 0.006 \cdot \text{SL}$
D1 to YN	t_R	0.090	$0.064 + 0.013 \cdot \text{SL}$	$0.063 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.013 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.335	$0.319 + 0.008 \cdot \text{SL}$	$0.325 + 0.007 \cdot \text{SL}$	$0.332 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.320	$0.302 + 0.009 \cdot \text{SL}$	$0.310 + 0.007 \cdot \text{SL}$	$0.320 + 0.006 \cdot \text{SL}$
D2 to YN	t_R	0.081	$0.055 + 0.013 \cdot \text{SL}$	$0.054 + 0.013 \cdot \text{SL}$	$0.043 + 0.014 \cdot \text{SL}$
	t_F	0.072	$0.047 + 0.013 \cdot \text{SL}$	$0.052 + 0.011 \cdot \text{SL}$	$0.044 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.245	$0.229 + 0.008 \cdot \text{SL}$	$0.234 + 0.007 \cdot \text{SL}$	$0.240 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.235	$0.217 + 0.009 \cdot \text{SL}$	$0.224 + 0.007 \cdot \text{SL}$	$0.234 + 0.006 \cdot \text{SL}$
S0 to YN	t_R	0.089	$0.063 + 0.013 \cdot \text{SL}$	$0.064 + 0.013 \cdot \text{SL}$	$0.049 + 0.014 \cdot \text{SL}$
	t_F	0.077	$0.052 + 0.013 \cdot \text{SL}$	$0.056 + 0.011 \cdot \text{SL}$	$0.048 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.333	$0.317 + 0.008 \cdot \text{SL}$	$0.323 + 0.007 \cdot \text{SL}$	$0.330 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.322	$0.304 + 0.009 \cdot \text{SL}$	$0.312 + 0.007 \cdot \text{SL}$	$0.322 + 0.006 \cdot \text{SL}$
S1 to YN	t_R	0.086	$0.060 + 0.013 \cdot \text{SL}$	$0.059 + 0.013 \cdot \text{SL}$	$0.047 + 0.014 \cdot \text{SL}$
	t_F	0.076	$0.051 + 0.012 \cdot \text{SL}$	$0.055 + 0.011 \cdot \text{SL}$	$0.047 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.254	$0.238 + 0.008 \cdot \text{SL}$	$0.244 + 0.007 \cdot \text{SL}$	$0.250 + 0.006 \cdot \text{SL}$
	t_{PHL}	0.263	$0.245 + 0.009 \cdot \text{SL}$	$0.253 + 0.007 \cdot \text{SL}$	$0.263 + 0.006 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX3ID4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.365	$0.355 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.373 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.346	$0.336 + 0.005 \cdot \text{SL}$	$0.341 + 0.004 \cdot \text{SL}$	$0.357 + 0.003 \cdot \text{SL}$
D1 to YN	t_R	0.086	$0.073 + 0.007 \cdot \text{SL}$	$0.074 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.074	$0.062 + 0.006 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.059 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.367	$0.357 + 0.005 \cdot \text{SL}$	$0.362 + 0.004 \cdot \text{SL}$	$0.375 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.345	$0.334 + 0.005 \cdot \text{SL}$	$0.339 + 0.004 \cdot \text{SL}$	$0.356 + 0.003 \cdot \text{SL}$
D2 to YN	t_R	0.076	$0.062 + 0.007 \cdot \text{SL}$	$0.063 + 0.007 \cdot \text{SL}$	$0.051 + 0.007 \cdot \text{SL}$
	t_F	0.067	$0.053 + 0.007 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$	$0.052 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.269	$0.259 + 0.005 \cdot \text{SL}$	$0.264 + 0.003 \cdot \text{SL}$	$0.275 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.253	$0.242 + 0.005 \cdot \text{SL}$	$0.248 + 0.004 \cdot \text{SL}$	$0.263 + 0.003 \cdot \text{SL}$
S0 to YN	t_R	0.087	$0.075 + 0.006 \cdot \text{SL}$	$0.073 + 0.006 \cdot \text{SL}$	$0.059 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.060 + 0.007 \cdot \text{SL}$	$0.063 + 0.006 \cdot \text{SL}$	$0.057 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.364	$0.354 + 0.005 \cdot \text{SL}$	$0.360 + 0.004 \cdot \text{SL}$	$0.372 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.346	$0.335 + 0.005 \cdot \text{SL}$	$0.341 + 0.004 \cdot \text{SL}$	$0.357 + 0.003 \cdot \text{SL}$
S1 to YN	t_R	0.084	$0.072 + 0.006 \cdot \text{SL}$	$0.071 + 0.006 \cdot \text{SL}$	$0.058 + 0.007 \cdot \text{SL}$
	t_F	0.073	$0.061 + 0.006 \cdot \text{SL}$	$0.061 + 0.006 \cdot \text{SL}$	$0.058 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.286	$0.276 + 0.005 \cdot \text{SL}$	$0.281 + 0.004 \cdot \text{SL}$	$0.293 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.287	$0.277 + 0.005 \cdot \text{SL}$	$0.283 + 0.004 \cdot \text{SL}$	$0.298 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

MX4/MX4D2/MX4D4

4 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Logic Symbol




Truth Table

S0	S1	Y
0	0	D0
1	0	D1
0	1	D2
1	1	D3

Cell Data

Input Load (SL)																	
MX4						MX4D2						MX4D4					
D0	D1	D2	D3	S0	S1	D0	D1	D2	D3	S0	S1	D0	D1	D2	D3	S0	S1
0.8	0.9	0.8	0.8	1.9	1.2	0.8	0.8	0.8	0.8	1.9	1.2	0.8	0.8	0.8	0.8	1.9	1.2
Gate Count																	
MX4						MX4D2						MX4D4					
5.33						5.33						6.00					

Schematic Diagram



4 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.146	$0.091 + 0.027 \cdot \text{SL}$	$0.093 + 0.027 \cdot \text{SL}$	$0.088 + 0.028 \cdot \text{SL}$
	t_F	0.154	$0.102 + 0.026 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$	$0.116 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.263	$0.228 + 0.018 \cdot \text{SL}$	$0.240 + 0.014 \cdot \text{SL}$	$0.255 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.270	$0.228 + 0.021 \cdot \text{SL}$	$0.246 + 0.016 \cdot \text{SL}$	$0.269 + 0.014 \cdot \text{SL}$
D1 to Y	t_R	0.146	$0.091 + 0.027 \cdot \text{SL}$	$0.092 + 0.027 \cdot \text{SL}$	$0.087 + 0.028 \cdot \text{SL}$
	t_F	0.154	$0.102 + 0.026 \cdot \text{SL}$	$0.111 + 0.024 \cdot \text{SL}$	$0.116 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.264	$0.229 + 0.018 \cdot \text{SL}$	$0.241 + 0.014 \cdot \text{SL}$	$0.256 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.273	$0.230 + 0.021 \cdot \text{SL}$	$0.248 + 0.016 \cdot \text{SL}$	$0.271 + 0.014 \cdot \text{SL}$
D2 to Y	t_R	0.145	$0.090 + 0.028 \cdot \text{SL}$	$0.092 + 0.027 \cdot \text{SL}$	$0.086 + 0.028 \cdot \text{SL}$
	t_F	0.153	$0.102 + 0.026 \cdot \text{SL}$	$0.108 + 0.024 \cdot \text{SL}$	$0.114 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.260	$0.225 + 0.018 \cdot \text{SL}$	$0.238 + 0.014 \cdot \text{SL}$	$0.252 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.269	$0.227 + 0.021 \cdot \text{SL}$	$0.244 + 0.016 \cdot \text{SL}$	$0.267 + 0.014 \cdot \text{SL}$
D3 to Y	t_R	0.144	$0.089 + 0.028 \cdot \text{SL}$	$0.092 + 0.027 \cdot \text{SL}$	$0.086 + 0.028 \cdot \text{SL}$
	t_F	0.154	$0.102 + 0.026 \cdot \text{SL}$	$0.109 + 0.024 \cdot \text{SL}$	$0.115 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.258	$0.222 + 0.018 \cdot \text{SL}$	$0.235 + 0.014 \cdot \text{SL}$	$0.250 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.270	$0.228 + 0.021 \cdot \text{SL}$	$0.246 + 0.016 \cdot \text{SL}$	$0.268 + 0.014 \cdot \text{SL}$
S0 to Y	t_R	0.146	$0.090 + 0.028 \cdot \text{SL}$	$0.093 + 0.027 \cdot \text{SL}$	$0.089 + 0.028 \cdot \text{SL}$
	t_F	0.154	$0.103 + 0.026 \cdot \text{SL}$	$0.110 + 0.024 \cdot \text{SL}$	$0.115 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.273	$0.237 + 0.018 \cdot \text{SL}$	$0.250 + 0.014 \cdot \text{SL}$	$0.265 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.285	$0.242 + 0.021 \cdot \text{SL}$	$0.260 + 0.016 \cdot \text{SL}$	$0.283 + 0.014 \cdot \text{SL}$
S1 to Y	t_R	0.135	$0.076 + 0.029 \cdot \text{SL}$	$0.083 + 0.027 \cdot \text{SL}$	$0.080 + 0.028 \cdot \text{SL}$
	t_F	0.137	$0.083 + 0.027 \cdot \text{SL}$	$0.093 + 0.025 \cdot \text{SL}$	$0.102 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.199	$0.164 + 0.018 \cdot \text{SL}$	$0.176 + 0.014 \cdot \text{SL}$	$0.191 + 0.013 \cdot \text{SL}$
	t_{PHL}	0.213	$0.171 + 0.021 \cdot \text{SL}$	$0.188 + 0.016 \cdot \text{SL}$	$0.210 + 0.014 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX4/MX4D2/MX4D4

4 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.135	$0.108 + 0.013 \cdot \text{SL}$	$0.107 + 0.014 \cdot \text{SL}$	$0.109 + 0.014 \cdot \text{SL}$
	t_F	0.151	$0.121 + 0.015 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$	$0.141 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.281	$0.257 + 0.012 \cdot \text{SL}$	$0.271 + 0.008 \cdot \text{SL}$	$0.295 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.290	$0.262 + 0.014 \cdot \text{SL}$	$0.277 + 0.010 \cdot \text{SL}$	$0.311 + 0.008 \cdot \text{SL}$
D1 to Y	t_R	0.134	$0.108 + 0.013 \cdot \text{SL}$	$0.107 + 0.014 \cdot \text{SL}$	$0.109 + 0.014 \cdot \text{SL}$
	t_F	0.150	$0.120 + 0.015 \cdot \text{SL}$	$0.130 + 0.013 \cdot \text{SL}$	$0.142 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.280	$0.257 + 0.012 \cdot \text{SL}$	$0.270 + 0.008 \cdot \text{SL}$	$0.294 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.291	$0.263 + 0.014 \cdot \text{SL}$	$0.278 + 0.010 \cdot \text{SL}$	$0.312 + 0.008 \cdot \text{SL}$
D2 to Y	t_R	0.133	$0.107 + 0.013 \cdot \text{SL}$	$0.105 + 0.014 \cdot \text{SL}$	$0.107 + 0.014 \cdot \text{SL}$
	t_F	0.150	$0.121 + 0.015 \cdot \text{SL}$	$0.129 + 0.013 \cdot \text{SL}$	$0.141 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.276	$0.253 + 0.012 \cdot \text{SL}$	$0.266 + 0.008 \cdot \text{SL}$	$0.290 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.287	$0.260 + 0.014 \cdot \text{SL}$	$0.275 + 0.010 \cdot \text{SL}$	$0.308 + 0.008 \cdot \text{SL}$
D3 to Y	t_R	0.134	$0.107 + 0.013 \cdot \text{SL}$	$0.105 + 0.014 \cdot \text{SL}$	$0.107 + 0.014 \cdot \text{SL}$
	t_F	0.150	$0.121 + 0.015 \cdot \text{SL}$	$0.130 + 0.012 \cdot \text{SL}$	$0.141 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.278	$0.255 + 0.012 \cdot \text{SL}$	$0.268 + 0.008 \cdot \text{SL}$	$0.292 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.291	$0.263 + 0.014 \cdot \text{SL}$	$0.278 + 0.010 \cdot \text{SL}$	$0.312 + 0.008 \cdot \text{SL}$
S0 to Y	t_R	0.134	$0.106 + 0.014 \cdot \text{SL}$	$0.108 + 0.014 \cdot \text{SL}$	$0.110 + 0.014 \cdot \text{SL}$
	t_F	0.151	$0.121 + 0.015 \cdot \text{SL}$	$0.129 + 0.013 \cdot \text{SL}$	$0.142 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.287	$0.264 + 0.012 \cdot \text{SL}$	$0.277 + 0.008 \cdot \text{SL}$	$0.301 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.301	$0.273 + 0.014 \cdot \text{SL}$	$0.289 + 0.010 \cdot \text{SL}$	$0.323 + 0.008 \cdot \text{SL}$
S1 to Y	t_R	0.127	$0.098 + 0.014 \cdot \text{SL}$	$0.099 + 0.014 \cdot \text{SL}$	$0.104 + 0.014 \cdot \text{SL}$
	t_F	0.141	$0.111 + 0.015 \cdot \text{SL}$	$0.120 + 0.013 \cdot \text{SL}$	$0.133 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.213	$0.189 + 0.012 \cdot \text{SL}$	$0.202 + 0.008 \cdot \text{SL}$	$0.226 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.231	$0.203 + 0.014 \cdot \text{SL}$	$0.218 + 0.010 \cdot \text{SL}$	$0.252 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

4 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX4D4


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.169	$0.156 + 0.006 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$	$0.154 + 0.007 \cdot \text{SL}$
	t_F	0.191	$0.176 + 0.007 \cdot \text{SL}$	$0.179 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.345	$0.330 + 0.008 \cdot \text{SL}$	$0.340 + 0.005 \cdot \text{SL}$	$0.376 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.358	$0.341 + 0.009 \cdot \text{SL}$	$0.352 + 0.006 \cdot \text{SL}$	$0.397 + 0.004 \cdot \text{SL}$
D1 to Y	t_R	0.169	$0.156 + 0.006 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$
	t_F	0.192	$0.176 + 0.008 \cdot \text{SL}$	$0.181 + 0.007 \cdot \text{SL}$	$0.200 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.344	$0.329 + 0.008 \cdot \text{SL}$	$0.339 + 0.005 \cdot \text{SL}$	$0.375 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.359	$0.342 + 0.009 \cdot \text{SL}$	$0.352 + 0.006 \cdot \text{SL}$	$0.398 + 0.004 \cdot \text{SL}$
D2 to Y	t_R	0.167	$0.154 + 0.007 \cdot \text{SL}$	$0.153 + 0.007 \cdot \text{SL}$	$0.154 + 0.007 \cdot \text{SL}$
	t_F	0.191	$0.176 + 0.007 \cdot \text{SL}$	$0.180 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.341	$0.326 + 0.008 \cdot \text{SL}$	$0.336 + 0.005 \cdot \text{SL}$	$0.371 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.356	$0.339 + 0.009 \cdot \text{SL}$	$0.350 + 0.006 \cdot \text{SL}$	$0.394 + 0.004 \cdot \text{SL}$
D3 to Y	t_R	0.168	$0.156 + 0.006 \cdot \text{SL}$	$0.154 + 0.007 \cdot \text{SL}$	$0.153 + 0.007 \cdot \text{SL}$
	t_F	0.191	$0.176 + 0.008 \cdot \text{SL}$	$0.179 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.342	$0.327 + 0.008 \cdot \text{SL}$	$0.337 + 0.005 \cdot \text{SL}$	$0.372 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.359	$0.342 + 0.009 \cdot \text{SL}$	$0.353 + 0.006 \cdot \text{SL}$	$0.398 + 0.004 \cdot \text{SL}$
S0 to Y	t_R	0.169	$0.156 + 0.006 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$	$0.155 + 0.007 \cdot \text{SL}$
	t_F	0.192	$0.176 + 0.008 \cdot \text{SL}$	$0.181 + 0.007 \cdot \text{SL}$	$0.200 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.350	$0.335 + 0.008 \cdot \text{SL}$	$0.345 + 0.005 \cdot \text{SL}$	$0.381 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.369	$0.352 + 0.009 \cdot \text{SL}$	$0.362 + 0.006 \cdot \text{SL}$	$0.407 + 0.004 \cdot \text{SL}$
S1 to Y	t_R	0.167	$0.154 + 0.006 \cdot \text{SL}$	$0.153 + 0.007 \cdot \text{SL}$	$0.152 + 0.007 \cdot \text{SL}$
	t_F	0.188	$0.174 + 0.007 \cdot \text{SL}$	$0.177 + 0.007 \cdot \text{SL}$	$0.196 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.273	$0.257 + 0.008 \cdot \text{SL}$	$0.267 + 0.005 \cdot \text{SL}$	$0.303 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.298	$0.281 + 0.009 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$	$0.337 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

MX8/MX8D2/MX8D4

8 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Logic Symbol




Truth Table

S0	S1	S2	Y
0	0	0	D0
1	0	0	D1
0	1	0	D2
1	1	0	D3
0	0	1	D4
1	0	1	D5
0	1	1	D6
1	1	1	D7

Cell Data

Input Load (SL)											Gate Count
MX8											MX8
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.7	0.7	0.8	0.7	0.7	0.8	0.7	0.8	1.0	1.8	1.2	10.00
MX8D2											MX8D2
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.7	0.7	0.7	0.7	0.7	0.8	0.7	0.8	1.0	1.8	1.2	10.33
MX8D4											MX8D4
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.7	0.7	0.8	0.7	0.7	0.8	0.7	0.8	1.0	1.8	1.2	11.00

Schematic Diagram



MX8/MX8D2/MX8D4

8 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.187	$0.131 + 0.028 \cdot \text{SL}$	$0.133 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.216	$0.161 + 0.027 \cdot \text{SL}$	$0.172 + 0.024 \cdot \text{SL}$	$0.184 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.391	$0.350 + 0.021 \cdot \text{SL}$	$0.368 + 0.016 \cdot \text{SL}$	$0.389 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.417	$0.367 + 0.025 \cdot \text{SL}$	$0.390 + 0.019 \cdot \text{SL}$	$0.422 + 0.015 \cdot \text{SL}$
D1 to Y	t_R	0.186	$0.131 + 0.028 \cdot \text{SL}$	$0.133 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.216	$0.161 + 0.027 \cdot \text{SL}$	$0.172 + 0.024 \cdot \text{SL}$	$0.184 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.391	$0.350 + 0.021 \cdot \text{SL}$	$0.368 + 0.016 \cdot \text{SL}$	$0.389 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.417	$0.367 + 0.025 \cdot \text{SL}$	$0.391 + 0.019 \cdot \text{SL}$	$0.423 + 0.015 \cdot \text{SL}$
D2 to Y	t_R	0.187	$0.132 + 0.027 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.217	$0.162 + 0.027 \cdot \text{SL}$	$0.174 + 0.024 \cdot \text{SL}$	$0.185 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.393	$0.351 + 0.021 \cdot \text{SL}$	$0.369 + 0.016 \cdot \text{SL}$	$0.391 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.420	$0.370 + 0.025 \cdot \text{SL}$	$0.394 + 0.019 \cdot \text{SL}$	$0.426 + 0.015 \cdot \text{SL}$
D3 to Y	t_R	0.187	$0.132 + 0.027 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.217	$0.162 + 0.027 \cdot \text{SL}$	$0.174 + 0.024 \cdot \text{SL}$	$0.185 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.393	$0.351 + 0.021 \cdot \text{SL}$	$0.370 + 0.016 \cdot \text{SL}$	$0.391 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.420	$0.370 + 0.025 \cdot \text{SL}$	$0.394 + 0.019 \cdot \text{SL}$	$0.426 + 0.015 \cdot \text{SL}$
D4 to Y	t_R	0.187	$0.132 + 0.028 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.216	$0.161 + 0.027 \cdot \text{SL}$	$0.172 + 0.024 \cdot \text{SL}$	$0.184 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.390	$0.349 + 0.021 \cdot \text{SL}$	$0.367 + 0.016 \cdot \text{SL}$	$0.388 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.417	$0.367 + 0.025 \cdot \text{SL}$	$0.391 + 0.019 \cdot \text{SL}$	$0.422 + 0.015 \cdot \text{SL}$
D5 to Y	t_R	0.187	$0.132 + 0.028 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.136 + 0.027 \cdot \text{SL}$
	t_F	0.216	$0.161 + 0.027 \cdot \text{SL}$	$0.172 + 0.024 \cdot \text{SL}$	$0.184 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.390	$0.349 + 0.021 \cdot \text{SL}$	$0.367 + 0.016 \cdot \text{SL}$	$0.388 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.417	$0.367 + 0.025 \cdot \text{SL}$	$0.391 + 0.019 \cdot \text{SL}$	$0.423 + 0.015 \cdot \text{SL}$
D6 to Y	t_R	0.187	$0.133 + 0.027 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.137 + 0.027 \cdot \text{SL}$
	t_F	0.217	$0.162 + 0.028 \cdot \text{SL}$	$0.174 + 0.024 \cdot \text{SL}$	$0.186 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.392	$0.351 + 0.021 \cdot \text{SL}$	$0.369 + 0.016 \cdot \text{SL}$	$0.391 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.421	$0.371 + 0.025 \cdot \text{SL}$	$0.395 + 0.019 \cdot \text{SL}$	$0.427 + 0.015 \cdot \text{SL}$
D7 to Y	t_R	0.187	$0.133 + 0.027 \cdot \text{SL}$	$0.134 + 0.027 \cdot \text{SL}$	$0.137 + 0.027 \cdot \text{SL}$
	t_F	0.217	$0.162 + 0.028 \cdot \text{SL}$	$0.174 + 0.024 \cdot \text{SL}$	$0.186 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.393	$0.351 + 0.021 \cdot \text{SL}$	$0.370 + 0.016 \cdot \text{SL}$	$0.391 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.421	$0.371 + 0.025 \cdot \text{SL}$	$0.395 + 0.019 \cdot \text{SL}$	$0.427 + 0.015 \cdot \text{SL}$
S0 to Y	t_R	0.188	$0.133 + 0.028 \cdot \text{SL}$	$0.135 + 0.027 \cdot \text{SL}$	$0.138 + 0.027 \cdot \text{SL}$
	t_F	0.217	$0.161 + 0.028 \cdot \text{SL}$	$0.175 + 0.024 \cdot \text{SL}$	$0.185 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.556	$0.514 + 0.021 \cdot \text{SL}$	$0.533 + 0.016 \cdot \text{SL}$	$0.554 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.578	$0.528 + 0.025 \cdot \text{SL}$	$0.552 + 0.019 \cdot \text{SL}$	$0.584 + 0.015 \cdot \text{SL}$
S1 to Y	t_R	0.180	$0.124 + 0.028 \cdot \text{SL}$	$0.127 + 0.027 \cdot \text{SL}$	$0.130 + 0.027 \cdot \text{SL}$
	t_F	0.203	$0.147 + 0.028 \cdot \text{SL}$	$0.160 + 0.025 \cdot \text{SL}$	$0.173 + 0.023 \cdot \text{SL}$
	t_{PLH}	0.310	$0.269 + 0.021 \cdot \text{SL}$	$0.287 + 0.016 \cdot \text{SL}$	$0.308 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.327	$0.277 + 0.025 \cdot \text{SL}$	$0.301 + 0.019 \cdot \text{SL}$	$0.333 + 0.015 \cdot \text{SL}$

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)
MX8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S2 to Y	t_R	0.157	$0.097 + 0.030 \cdot \text{SL}$	$0.103 + 0.028 \cdot \text{SL}$	$0.110 + 0.027 \cdot \text{SL}$
	t_F	0.163	$0.102 + 0.030 \cdot \text{SL}$	$0.117 + 0.026 \cdot \text{SL}$	$0.138 + 0.024 \cdot \text{SL}$
	t_{PLH}	0.219	$0.179 + 0.020 \cdot \text{SL}$	$0.195 + 0.016 \cdot \text{SL}$	$0.215 + 0.014 \cdot \text{SL}$
	t_{PHL}	0.234	$0.186 + 0.024 \cdot \text{SL}$	$0.207 + 0.018 \cdot \text{SL}$	$0.235 + 0.015 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 10$, *Group3 : $10 < \text{SL}$

MX8/MX8D2/MX8D4

8 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.180	$0.151 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$
	t_F	0.215	$0.183 + 0.016 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$	$0.214 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.417	$0.390 + 0.014 \cdot \text{SL}$	$0.406 + 0.009 \cdot \text{SL}$	$0.439 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.443	$0.411 + 0.016 \cdot \text{SL}$	$0.429 + 0.011 \cdot \text{SL}$	$0.475 + 0.008 \cdot \text{SL}$
D1 to Y	t_R	0.180	$0.152 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$
	t_F	0.215	$0.183 + 0.016 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$	$0.214 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.417	$0.390 + 0.014 \cdot \text{SL}$	$0.407 + 0.009 \cdot \text{SL}$	$0.439 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.443	$0.411 + 0.016 \cdot \text{SL}$	$0.430 + 0.011 \cdot \text{SL}$	$0.475 + 0.008 \cdot \text{SL}$
D2 to Y	t_R	0.180	$0.152 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
	t_F	0.216	$0.183 + 0.017 \cdot \text{SL}$	$0.197 + 0.013 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.419	$0.391 + 0.014 \cdot \text{SL}$	$0.408 + 0.009 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.447	$0.415 + 0.016 \cdot \text{SL}$	$0.433 + 0.011 \cdot \text{SL}$	$0.478 + 0.008 \cdot \text{SL}$
D3 to Y	t_R	0.180	$0.152 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
	t_F	0.216	$0.183 + 0.017 \cdot \text{SL}$	$0.197 + 0.013 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.419	$0.391 + 0.014 \cdot \text{SL}$	$0.408 + 0.009 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.447	$0.415 + 0.016 \cdot \text{SL}$	$0.433 + 0.011 \cdot \text{SL}$	$0.478 + 0.008 \cdot \text{SL}$
D4 to Y	t_R	0.180	$0.151 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$
	t_F	0.215	$0.183 + 0.016 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$	$0.213 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.416	$0.389 + 0.014 \cdot \text{SL}$	$0.405 + 0.009 \cdot \text{SL}$	$0.438 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.443	$0.411 + 0.016 \cdot \text{SL}$	$0.430 + 0.011 \cdot \text{SL}$	$0.475 + 0.008 \cdot \text{SL}$
D5 to Y	t_R	0.180	$0.151 + 0.014 \cdot \text{SL}$	$0.153 + 0.014 \cdot \text{SL}$	$0.157 + 0.013 \cdot \text{SL}$
	t_F	0.215	$0.183 + 0.016 \cdot \text{SL}$	$0.196 + 0.013 \cdot \text{SL}$	$0.213 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.416	$0.389 + 0.014 \cdot \text{SL}$	$0.405 + 0.009 \cdot \text{SL}$	$0.438 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.443	$0.412 + 0.016 \cdot \text{SL}$	$0.430 + 0.011 \cdot \text{SL}$	$0.475 + 0.008 \cdot \text{SL}$
D6 to Y	t_R	0.181	$0.152 + 0.014 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
	t_F	0.217	$0.183 + 0.017 \cdot \text{SL}$	$0.198 + 0.013 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.418	$0.391 + 0.014 \cdot \text{SL}$	$0.408 + 0.009 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.447	$0.415 + 0.016 \cdot \text{SL}$	$0.434 + 0.011 \cdot \text{SL}$	$0.479 + 0.008 \cdot \text{SL}$
D7 to Y	t_R	0.181	$0.152 + 0.014 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
	t_F	0.216	$0.183 + 0.017 \cdot \text{SL}$	$0.198 + 0.013 \cdot \text{SL}$	$0.215 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.419	$0.391 + 0.014 \cdot \text{SL}$	$0.408 + 0.009 \cdot \text{SL}$	$0.440 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.447	$0.416 + 0.016 \cdot \text{SL}$	$0.434 + 0.011 \cdot \text{SL}$	$0.479 + 0.008 \cdot \text{SL}$
S0 to Y	t_R	0.181	$0.152 + 0.014 \cdot \text{SL}$	$0.154 + 0.014 \cdot \text{SL}$	$0.158 + 0.013 \cdot \text{SL}$
	t_F	0.216	$0.183 + 0.017 \cdot \text{SL}$	$0.198 + 0.013 \cdot \text{SL}$	$0.214 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.582	$0.554 + 0.014 \cdot \text{SL}$	$0.571 + 0.009 \cdot \text{SL}$	$0.603 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.604	$0.572 + 0.016 \cdot \text{SL}$	$0.590 + 0.011 \cdot \text{SL}$	$0.636 + 0.008 \cdot \text{SL}$
S1 to Y	t_R	0.175	$0.146 + 0.014 \cdot \text{SL}$	$0.149 + 0.014 \cdot \text{SL}$	$0.152 + 0.014 \cdot \text{SL}$
	t_F	0.207	$0.174 + 0.016 \cdot \text{SL}$	$0.187 + 0.013 \cdot \text{SL}$	$0.206 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.334	$0.307 + 0.014 \cdot \text{SL}$	$0.323 + 0.009 \cdot \text{SL}$	$0.356 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.351	$0.319 + 0.016 \cdot \text{SL}$	$0.337 + 0.011 \cdot \text{SL}$	$0.383 + 0.008 \cdot \text{SL}$

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)
MX8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S2 to Y	t_R	0.158	$0.128 + 0.015 \cdot \text{SL}$	$0.131 + 0.014 \cdot \text{SL}$	$0.138 + 0.014 \cdot \text{SL}$
	t_F	0.172	$0.136 + 0.018 \cdot \text{SL}$	$0.152 + 0.014 \cdot \text{SL}$	$0.176 + 0.012 \cdot \text{SL}$
	t_{PLH}	0.239	$0.212 + 0.014 \cdot \text{SL}$	$0.228 + 0.009 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$
	t_{PHL}	0.250	$0.218 + 0.016 \cdot \text{SL}$	$0.236 + 0.011 \cdot \text{SL}$	$0.281 + 0.008 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 16$, *Group3 : $16 < \text{SL}$

MX8/MX8D2/MX8D4

8 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)

MX8D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.228	$0.217 + 0.005 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_F	0.276	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.504	$0.486 + 0.009 \cdot \text{SL}$	$0.499 + 0.006 \cdot \text{SL}$	$0.544 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.547	$0.527 + 0.010 \cdot \text{SL}$	$0.539 + 0.007 \cdot \text{SL}$	$0.594 + 0.005 \cdot \text{SL}$
D1 to Y	t_R	0.227	$0.216 + 0.005 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_F	0.276	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.504	$0.486 + 0.009 \cdot \text{SL}$	$0.498 + 0.006 \cdot \text{SL}$	$0.544 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.547	$0.527 + 0.010 \cdot \text{SL}$	$0.539 + 0.007 \cdot \text{SL}$	$0.594 + 0.005 \cdot \text{SL}$
D2 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.214 + 0.007 \cdot \text{SL}$
	t_F	0.276	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.292 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.503	$0.485 + 0.009 \cdot \text{SL}$	$0.497 + 0.006 \cdot \text{SL}$	$0.543 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.548	$0.528 + 0.010 \cdot \text{SL}$	$0.540 + 0.007 \cdot \text{SL}$	$0.595 + 0.005 \cdot \text{SL}$
D3 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_F	0.276	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.292 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.503	$0.485 + 0.009 \cdot \text{SL}$	$0.497 + 0.006 \cdot \text{SL}$	$0.543 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.548	$0.528 + 0.010 \cdot \text{SL}$	$0.540 + 0.007 \cdot \text{SL}$	$0.595 + 0.005 \cdot \text{SL}$
D4 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_F	0.274	$0.259 + 0.007 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.499	$0.481 + 0.009 \cdot \text{SL}$	$0.494 + 0.006 \cdot \text{SL}$	$0.539 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.543	$0.524 + 0.010 \cdot \text{SL}$	$0.536 + 0.007 \cdot \text{SL}$	$0.590 + 0.005 \cdot \text{SL}$
D5 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.213 + 0.007 \cdot \text{SL}$
	t_F	0.274	$0.259 + 0.007 \cdot \text{SL}$	$0.260 + 0.007 \cdot \text{SL}$	$0.290 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.499	$0.482 + 0.009 \cdot \text{SL}$	$0.494 + 0.006 \cdot \text{SL}$	$0.540 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.543	$0.524 + 0.010 \cdot \text{SL}$	$0.536 + 0.007 \cdot \text{SL}$	$0.591 + 0.005 \cdot \text{SL}$
D6 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.214 + 0.007 \cdot \text{SL}$
	t_F	0.275	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.502	$0.484 + 0.009 \cdot \text{SL}$	$0.496 + 0.006 \cdot \text{SL}$	$0.542 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.547	$0.528 + 0.010 \cdot \text{SL}$	$0.540 + 0.007 \cdot \text{SL}$	$0.595 + 0.005 \cdot \text{SL}$
D7 to Y	t_R	0.227	$0.216 + 0.006 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$	$0.214 + 0.007 \cdot \text{SL}$
	t_F	0.276	$0.261 + 0.007 \cdot \text{SL}$	$0.262 + 0.007 \cdot \text{SL}$	$0.291 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.502	$0.484 + 0.009 \cdot \text{SL}$	$0.496 + 0.006 \cdot \text{SL}$	$0.542 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.548	$0.528 + 0.010 \cdot \text{SL}$	$0.540 + 0.007 \cdot \text{SL}$	$0.595 + 0.005 \cdot \text{SL}$
S0 to Y	t_R	0.228	$0.217 + 0.006 \cdot \text{SL}$	$0.212 + 0.007 \cdot \text{SL}$	$0.214 + 0.007 \cdot \text{SL}$
	t_F	0.275	$0.261 + 0.007 \cdot \text{SL}$	$0.261 + 0.007 \cdot \text{SL}$	$0.292 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.666	$0.648 + 0.009 \cdot \text{SL}$	$0.660 + 0.006 \cdot \text{SL}$	$0.706 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.705	$0.685 + 0.010 \cdot \text{SL}$	$0.698 + 0.007 \cdot \text{SL}$	$0.753 + 0.005 \cdot \text{SL}$
S1 to Y	t_R	0.225	$0.214 + 0.006 \cdot \text{SL}$	$0.209 + 0.007 \cdot \text{SL}$	$0.211 + 0.007 \cdot \text{SL}$
	t_F	0.272	$0.257 + 0.007 \cdot \text{SL}$	$0.258 + 0.007 \cdot \text{SL}$	$0.288 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.415	$0.398 + 0.009 \cdot \text{SL}$	$0.410 + 0.006 \cdot \text{SL}$	$0.455 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.450	$0.430 + 0.010 \cdot \text{SL}$	$0.442 + 0.007 \cdot \text{SL}$	$0.497 + 0.005 \cdot \text{SL}$

Switching Characteristics (Cont.) (Typical process, 25°C, 2.5V, $t_R/t_F = 0.20\text{ns}$, SL: Standard Load)
MX8D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S2 to Y	t_R	0.220	$0.209 + 0.005 \cdot \text{SL}$	$0.203 + 0.007 \cdot \text{SL}$	$0.205 + 0.007 \cdot \text{SL}$
	t_F	0.254	$0.239 + 0.007 \cdot \text{SL}$	$0.240 + 0.007 \cdot \text{SL}$	$0.270 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.318	$0.300 + 0.009 \cdot \text{SL}$	$0.312 + 0.006 \cdot \text{SL}$	$0.358 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.342	$0.323 + 0.010 \cdot \text{SL}$	$0.335 + 0.007 \cdot \text{SL}$	$0.391 + 0.005 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 27$, *Group3 : $27 < \text{SL}$

Input/Output Cells

4

Contents

Overview	4-1
Summary Tables	4-2
Input Buffers	4-7
Output Buffers.....	4-19
Bi-Directional Buffers	4-58
Input Clock Drivers	4-60
Oscillators	4-69
PCI Buffers	4-87
USB (Universal Serial Bus) I/O Buffers	4-92
Power Pads.....	4-103
Analog Interface.....	4-104
Slot Cells	4-111

OVERVIEW

The fourth chapter describes various kinds of Input/Output cells only (2.5V/ 3.3V/ 5V-tolerant) in STD111 library.

The switching characteristics of each cell are attached to its basic cell information. The AC characteristics of bi-directional buffers are not included in this data sheet. However, they can be derived from different combinations of input and output buffers.

There are so many possible combinations of input/output cells, therefore, the naming conventions are adopted to help you memorize and use this cell library efficiently. You can refer to the naming conventions contained in “Summary Tables” section.

The “Summary Tables” section shows the list of 2.5V, 3.3V and 5V-tolerant I/O cells separated by the category (input, output, bi-directional, etc.), and the more detailed description tables can be found on the leading part of each category.

All 2.5V, 3.3V-interface and 5V-tolerant buffers use 1 I/O slot. The default pitch of a regular I/O buffer is 52 μm (in case of no limitation of bonding equipments). All 2.5V, 3.3V-interface and 5V-tolerant buffers use this regular I/O slot if the data sheet do not state differently.




Figure 4-1.

NOTES:

1. As to analog IO cells in the library, the voltage level of the input/output signal is the same as the IO power supply voltage level, no level shifter inside.
2. When both A and B driving signals do not exist, SEC tolerant IO's pad voltage goes high state. However, those 5V tolerant input and bi-directional cells with 100k Ω pull-up resistor have NMOS pass transistor like Figure 4.1. Therefore, pad voltage of 5V tolerant IO for 3.3V interface could be 1.7V instead of VDD.

SUMMARY TABLES

Input Buffers

Cell Type	Cell Name	Page
CMOS Level	PIC/PICD/PICU	4-8
	PHIC/PHICD/PHICU	
	PTIC/PTICD/PTICU	
CMOS Schmitt Trigger Level	PIS/PISD/PISU	4-12
	PHIS/PHISD/PHISU	
	PTIS/PTISD/PTISU	
LVTTL Level	PHIT/PHITD/PHITU	4-16
	PTIT/PTITD/PTITU	

<Naming Convention of Input Buffers>

Pvlab					
v		a		b	
None	Normal operation	C	CMOS level	None	No resistor
H	3.3V interface	S	Schmitt trigger level	D	Pull-down resistor
T	5V-tolerant	T	LVTTL level	U	Pull-up resistor

Output Buffers

Cell Type	Cell Name	Current Drive (mA)	Page
Normal	POBy	1/2/4/6/8/10/12	4-20
	POBySM	4/6/8/10/12	
	POBySH	10/12	
	PHOBy	1/2/4/6/8/10/12	
	PHOBySM	4/6/8/10/12	
	PHOBySH	10/12	
Open Drain	PODy	1/2/4/6/8/10/12	4-29
	PODySM	4/6/8/10/12	
	PODySH	10/12	
	PHODy	1/2/4/6/8/10/12	
	PHODySM	4/6/8/10/12	
	PHODySH	10/12	
	PTODy	1/2/3	

Cell Type	Cell Name	Current Drive (mA)	Page
Tri-State	POTy	1/2/4/6/8/10/12	4-39
	POTySM	4/6/8/10/12	
	POTySH	10/12	
	PHOTy	1/2/4/6/8/10/12	
	PHOTySM	4/6/8/10/12	
	PHOTySH	10/12	
	PTOTy	1/2/3	

<Naming Convention of Output Buffers>

P wO x y z			
w		y	
None	Normal operation	1	1 mA drive
H	3.3V interface	2	2mA drive
x		4	4mA drive
B	Normal buffer	6	6mA drive
D	Open drain buffer	8	8mA drive
T	Tri-state buffer	10	10mA drive
z		12	12mA drive
None	No slew-rate control		
SM	Medium slew-rate control		
SH	High slew-rate control		
P T O x y			
x		y	
D	Open drain buffer	1	1 mA drive
T	Tri-state buffer	2	2mA drive
		3	3mA drive

Bi-Directional Buffers

Cell Type	Cell Name	Page
Open Drain	PBaDyz/PBaUDyz	4-59
	PHBaDyz/PHBaUDyz	
	PTBaDyz/PTBaUDyz	
Tri-State	PBaTyz/PBaDTyz/PBaUTyz	
	PHBaTy/PHBaDTy/PHBaUTy	
	PTBaTy/PTBaDTy/PTBaUTy	

<Naming Convention of Bi-Directional Buffers>

Pw B a b x y z			
w		y	
None	Normal	1	1 mA drive
H	3.3V interface	2	2mA drive
a		4	4mA drive
C	LVC MOS level	6	6mA drive
S	LVC MOS Schmitt trigger level	8	8mA drive
T	LVTTL level	10	10mA drive
b		12	12mA drive
None	No resistor	z	
D	Pull-down resistor	None	No slew-rate control
U	Pull-up resistor	SM	Medium slew -rate control
x		SH	High slew-rate control
B	Normal buffer		
D	Open drain buffer		
T	Tri-state buffer		
P T B a b x y			
a		x	
C	LVC MOS level	D	Open drain buffer
S	LVC MOS Schmitt trigger level	T	Tri-state buffer
T	LVTTL level	y	
b		1	1 mA drive
None	No resistor	2	2mA drive
D	Pull-down resistor	3	3mA drive
U	Pull-up resistor		

Input Clock Drivers with PAD

Cell Type	Cell Name	Current Drive (mA)	Page
LVC MOS Level	PSCKDCaby	2/4/6/8	4-61
LVC MOS Schmitt Trigger Level	PSCKDSaby	2/4/6/8	4-65

<Naming Convention of Input Clock Drivers>

PSCKD a b y			
a		y	
C	LVC MOS Level	2	2mA drive
S	LVC MOS Schmitt Trigger Level	4	4mA drive
b		6	6mA drive
None	No Resistor	8	8mA drive
D	Pull-Down Resistor		
U	Pull-Up Resistor		

Oscillators

Cell Type	Cell Name	Page
Oscillator	PHSOSCK1/K2/M1/M2/M3	4-70
	PHSOSCK17/K27/M16/M26/M36	4-76
	PSOSCK1/K2/M1/M2	4-82

PCI Buffers

Cell Type	Cell Name	Page
5V-tolerant PCI Input	PTIPCI	4-89
5V-tolerant PCI Input	PTOPCI	4-90
5V-tolerant PCI Bi-Directional	PTBPCI	4-91

USB (Universal Serial Bus) I/O Buffers (Under Development)

Cell Type	Cell Name	Page
Bidirectional USB Buffer	PBUSB/PBUSB1	4-94
	PBUSB_LS	4-95
	PBUSB_FS	4-96

Power Pads

Cell Type	Cell Name	Page
2.5V VDD	VDD2(I/P/O/IP/OP/T)	4-103
3.3V VDD	VDD3(P/O/OP)	
VSS	VSS2(I/P/O/IP/OP/T)	
	VSS3(P/O/OP)	
Analog VDD Power Pad	VDD2I_ABB/VDD2OP_ABB/VDD2T_ABB	4-103
Analog VSS Power Pads	VSS2I_ABB/VSS2OP_ABB/VSS2T_ABB	
	VBB_ABB/VSSBB_ABB	

Analog Interface

Cell Type	Cell Name	Page
Analog Input with Separated Bulk-Bias	PNC_ABB PIA_ABB/PIAR10_ABB/PIAR50_ABB PIC_ABB/PICC_ABB/PICEN_ABB	4-104
Analog Output with Separated Bulk-Bias	POA_ABB/POAR10_ABB/POAR50_ABB POT(1/2/4/8)_ABB	
Analog Bi-Directional with Separated Bulk-Bias	PBCT(1/2/4/8)_ABB	

NOTE: As to analog IO cells in the library, the voltage level of the input/output signal is the same as the IO power supply voltage level, no level shifter inside.

Slot Cells

Cell Type	Cell Name	Page
ESD Slot Cells	EV2I/EV2P/EV2O/EV2IP/EV2OP/EV2T	4-111
	EV3P/EV3O/EV3OP	
	EV2I_ABB/EV2OP_ABB/EV2T/ABB	
Common Slot Cells	EC0C0/EC0C0D	4-112
	EC0CA0/EC0CA0D	
	EC0C0_BB/EC0C0D_BB/ EC0C0_VBB/EC0C0D_VBB	

INPUT BUFFERS

Cell List

Cell Name	Function Description
PIC/PICD/PICU	2.5V LVCMOS Level Input Buffers
PHIC/PHICD/PHICU	3.3V LVCMOS Level Input Buffers
PTIC/PTICD/PTICU	5V-tolerant LVCMOS Level Input Buffers
PIS/PISD/PISU	2.5V LVCMOS Schmitt Trigger Level Input Buffers
PHIS/PHISD/PHISU	3.3V LVCMOS Schmitt Trigger Level Input Buffers
PTIS/PTISD/PTISU	5V-tolerant LVCMOS Schmitt Trigger Level Input Buffers
PHIT/PHITD/PHITU	3.3V LVTTL Level Input Buffers
PTIT/PTITD/PTITU	5V-tolerant LVTTL Level Input Buffers


PvIC/PvICD/PvICU

LVC MOS Level Input Buffers

Cell Availability

2.5V Only	3.3V Interface	5V Tolerant
PIC/PICD/PICU	PHIC/PHICD/PHICU	PTIC/PTICD/PTICU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIC/PICD/PICU	2.897
PHIC/PHICD/PHICU	2.897
PTIC/PTICD/PTICU	2.897

PvIC/PvICD/PvICU

LVC MOS Level Input Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.204	$0.186 + 0.009 \cdot \text{SL}$	$0.184 + 0.010 \cdot \text{SL}$	$0.165 + 0.010 \cdot \text{SL}$
	t_F	0.151	$0.138 + 0.006 \cdot \text{SL}$	$0.141 + 0.006 \cdot \text{SL}$	$0.128 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.629	$0.615 + 0.007 \cdot \text{SL}$	$0.621 + 0.005 \cdot \text{SL}$	$0.637 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.547	$0.535 + 0.006 \cdot \text{SL}$	$0.542 + 0.004 \cdot \text{SL}$	$0.571 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.204	$0.186 + 0.009 \cdot \text{SL}$	$0.183 + 0.010 \cdot \text{SL}$	$0.165 + 0.010 \cdot \text{SL}$
	t_F	0.153	$0.141 + 0.006 \cdot \text{SL}$	$0.143 + 0.006 \cdot \text{SL}$	$0.131 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.684	$0.669 + 0.007 \cdot \text{SL}$	$0.675 + 0.005 \cdot \text{SL}$	$0.692 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.518	$0.506 + 0.006 \cdot \text{SL}$	$0.512 + 0.004 \cdot \text{SL}$	$0.542 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.206	$0.188 + 0.009 \cdot \text{SL}$	$0.186 + 0.010 \cdot \text{SL}$	$0.166 + 0.010 \cdot \text{SL}$
	t_F	0.151	$0.139 + 0.006 \cdot \text{SL}$	$0.140 + 0.006 \cdot \text{SL}$	$0.128 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.588	$0.574 + 0.007 \cdot \text{SL}$	$0.580 + 0.005 \cdot \text{SL}$	$0.597 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.603	$0.591 + 0.006 \cdot \text{SL}$	$0.598 + 0.004 \cdot \text{SL}$	$0.627 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

NOTE: The delay measure point of LVC MOS input buffer is from PAD(VDD/2) to Y(VDD/2).

PvIC/PvICD/PvICU

LVCMOS Level Input Buffers

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PHIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.124 + 0.005 \cdot \text{SL}$	$0.124 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.770	$0.763 + 0.003 \cdot \text{SL}$	$0.765 + 0.003 \cdot \text{SL}$	$0.775 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.893	$0.885 + 0.004 \cdot \text{SL}$	$0.888 + 0.003 \cdot \text{SL}$	$0.913 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.004 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.847	$0.840 + 0.003 \cdot \text{SL}$	$0.842 + 0.003 \cdot \text{SL}$	$0.853 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.856	$0.849 + 0.004 \cdot \text{SL}$	$0.852 + 0.003 \cdot \text{SL}$	$0.877 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.124 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.714	$0.708 + 0.003 \cdot \text{SL}$	$0.710 + 0.003 \cdot \text{SL}$	$0.720 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.968	$0.960 + 0.004 \cdot \text{SL}$	$0.964 + 0.003 \cdot \text{SL}$	$0.989 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

NOTE: The delay measure point of LVCMOS input buffer is from PAD(VDD/2) to Y(VDD/2).

PvIC/PvICD/PvICU

LVC MOS Level Input Buffers

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PTIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.134	$0.124 + 0.005 \cdot \text{SL}$	$0.124 + 0.005 \cdot \text{SL}$	$0.118 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.920	$0.913 + 0.003 \cdot \text{SL}$	$0.916 + 0.003 \cdot \text{SL}$	$0.926 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.274	$1.266 + 0.004 \cdot \text{SL}$	$1.270 + 0.003 \cdot \text{SL}$	$1.294 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PTICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.134	$0.124 + 0.005 \cdot \text{SL}$	$0.124 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.002	$0.995 + 0.003 \cdot \text{SL}$	$0.997 + 0.003 \cdot \text{SL}$	$1.008 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.239	$1.231 + 0.004 \cdot \text{SL}$	$1.234 + 0.003 \cdot \text{SL}$	$1.259 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PTICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.134	$0.124 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.118 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.004 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.136 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.767	$0.760 + 0.003 \cdot \text{SL}$	$0.762 + 0.003 \cdot \text{SL}$	$0.772 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.469	$1.461 + 0.004 \cdot \text{SL}$	$1.464 + 0.003 \cdot \text{SL}$	$1.489 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

NOTE: The delay measure point of LVC MOS input buffer is from PAD(VDD/2) to Y(VDD/2).


PvIS/PvISD/PvISU

LVC MOS Schmitt Trigger Level Input Buffers

Cell Availability

2.5V Only	3.3V Interface	5V Tolerant
PIS/PISD/PISU	PHIS/PHISD/PHISU	PTIS/PTISD/PTISU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIS/PISD/PISU	2.897
PHIS/PHISD/PHISU	2.897
PTIS/PTISD/PTISU	2.897

LVCMOS Schmitt Trigger Level Input Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PIS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.225	$0.203 + 0.011 \cdot \text{SL}$	$0.206 + 0.010 \cdot \text{SL}$	$0.199 + 0.010 \cdot \text{SL}$
	t_F	0.165	$0.150 + 0.008 \cdot \text{SL}$	$0.155 + 0.006 \cdot \text{SL}$	$0.173 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.992	$0.976 + 0.008 \cdot \text{SL}$	$0.983 + 0.006 \cdot \text{SL}$	$1.019 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.935	$0.921 + 0.007 \cdot \text{SL}$	$0.928 + 0.005 \cdot \text{SL}$	$0.973 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PISD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.224	$0.203 + 0.011 \cdot \text{SL}$	$0.206 + 0.010 \cdot \text{SL}$	$0.198 + 0.010 \cdot \text{SL}$
	t_F	0.167	$0.152 + 0.007 \cdot \text{SL}$	$0.156 + 0.006 \cdot \text{SL}$	$0.174 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.045	$1.029 + 0.008 \cdot \text{SL}$	$1.036 + 0.006 \cdot \text{SL}$	$1.072 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.921	$0.908 + 0.007 \cdot \text{SL}$	$0.914 + 0.005 \cdot \text{SL}$	$0.960 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PISU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.226	$0.205 + 0.011 \cdot \text{SL}$	$0.208 + 0.010 \cdot \text{SL}$	$0.201 + 0.010 \cdot \text{SL}$
	t_F	0.165	$0.150 + 0.008 \cdot \text{SL}$	$0.155 + 0.006 \cdot \text{SL}$	$0.173 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.961	$0.944 + 0.008 \cdot \text{SL}$	$0.952 + 0.006 \cdot \text{SL}$	$0.989 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.991	$0.978 + 0.007 \cdot \text{SL}$	$0.985 + 0.005 \cdot \text{SL}$	$1.029 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PvIS/PvISD/PvISU

LVCMOS Schmitt Trigger Level Input Buffers

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PHIS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.998	$0.992 + 0.003 \cdot \text{SL}$	$0.994 + 0.003 \cdot \text{SL}$	$1.004 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.339	$1.331 + 0.004 \cdot \text{SL}$	$1.334 + 0.003 \cdot \text{SL}$	$1.359 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHISD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.004 \cdot \text{SL}$	$0.131 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.076	$1.069 + 0.003 \cdot \text{SL}$	$1.071 + 0.003 \cdot \text{SL}$	$1.081 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.337	$1.329 + 0.004 \cdot \text{SL}$	$1.332 + 0.003 \cdot \text{SL}$	$1.357 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHISU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.136 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.944	$0.937 + 0.003 \cdot \text{SL}$	$0.939 + 0.003 \cdot \text{SL}$	$0.949 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.416	$1.408 + 0.004 \cdot \text{SL}$	$1.412 + 0.003 \cdot \text{SL}$	$1.437 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

LVCMOS Schmitt Trigger Level Input Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)**PTIS**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.136	$0.126 + 0.005 \cdot \text{SL}$	$0.126 + 0.005 \cdot \text{SL}$	$0.119 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.004 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.164	$1.158 + 0.003 \cdot \text{SL}$	$1.160 + 0.003 \cdot \text{SL}$	$1.170 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.387	$1.379 + 0.004 \cdot \text{SL}$	$1.382 + 0.003 \cdot \text{SL}$	$1.407 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$ **PTISD**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.136	$0.127 + 0.005 \cdot \text{SL}$	$0.126 + 0.005 \cdot \text{SL}$	$0.119 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.248	$1.241 + 0.003 \cdot \text{SL}$	$1.243 + 0.003 \cdot \text{SL}$	$1.253 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.374	$1.366 + 0.004 \cdot \text{SL}$	$1.370 + 0.003 \cdot \text{SL}$	$1.394 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$ **PTISU**

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.136	$0.126 + 0.005 \cdot \text{SL}$	$0.126 + 0.005 \cdot \text{SL}$	$0.119 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.017	$1.010 + 0.003 \cdot \text{SL}$	$1.013 + 0.003 \cdot \text{SL}$	$1.023 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.536	$1.528 + 0.004 \cdot \text{SL}$	$1.532 + 0.003 \cdot \text{SL}$	$1.557 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$ **NOTE:** The delay measure point of LVCMOS input buffer is from PAD(VDD/2) to Y(VDD/2).


PvIT/PvITD/PvITU

LVTTL Level Input Buffers

Cell Availability

3.3V Interface	5V Tolerant
PHIT/PHITD/PHITU	PTIT/PTITD/PTITU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PHIT/PHITD/PHITU	2.897
PTIT/PTITD/PTITU	2.897

PvIT/PvITD/PvITU

LVTTL Level Input Buffers

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PHIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.665	$0.658 + 0.003 \cdot \text{SL}$	$0.660 + 0.003 \cdot \text{SL}$	$0.670 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.930	$0.922 + 0.004 \cdot \text{SL}$	$0.925 + 0.003 \cdot \text{SL}$	$0.950 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHITD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.124 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.004 \cdot \text{SL}$	$0.131 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.750	$0.743 + 0.003 \cdot \text{SL}$	$0.746 + 0.003 \cdot \text{SL}$	$0.756 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.905	$0.897 + 0.004 \cdot \text{SL}$	$0.900 + 0.003 \cdot \text{SL}$	$0.925 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHITU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.601	$0.594 + 0.003 \cdot \text{SL}$	$0.596 + 0.003 \cdot \text{SL}$	$0.606 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.006	$0.998 + 0.004 \cdot \text{SL}$	$1.001 + 0.003 \cdot \text{SL}$	$1.026 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

NOTE: The delay measure point of LVTTL input buffer is from PAD(1.4) to Y(VDD/2).

PvIT/PvITD/PvITU

LVTTL Level Input Buffers

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PTIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.751	$0.744 + 0.003 \cdot \text{SL}$	$0.746 + 0.003 \cdot \text{SL}$	$0.757 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.194	$1.186 + 0.004 \cdot \text{SL}$	$1.190 + 0.003 \cdot \text{SL}$	$1.215 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PTITD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.123 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.129 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.899	$0.892 + 0.003 \cdot \text{SL}$	$0.895 + 0.003 \cdot \text{SL}$	$0.905 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.194	$1.186 + 0.004 \cdot \text{SL}$	$1.189 + 0.003 \cdot \text{SL}$	$1.214 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PTITU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.133	$0.124 + 0.005 \cdot \text{SL}$	$0.123 + 0.005 \cdot \text{SL}$	$0.117 + 0.005 \cdot \text{SL}$
	t_F	0.139	$0.130 + 0.005 \cdot \text{SL}$	$0.132 + 0.004 \cdot \text{SL}$	$0.137 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.653	$0.646 + 0.003 \cdot \text{SL}$	$0.648 + 0.003 \cdot \text{SL}$	$0.658 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.438	$1.430 + 0.004 \cdot \text{SL}$	$1.433 + 0.003 \cdot \text{SL}$	$1.458 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

OUTPUT BUFFERS

Cell List

Cell Name	Function Description
POB(1/2/4/6/8/10/12)	2.5V LVCMOS Normal Output Buffers
POB(4/6/8/10/12)SM	2.5V LVCMOS Normal Output Buffers with Medium Slew-Rate
POB(10/12)SH	2.5V LVCMOS Normal Output Buffers with High Slew-Rate
PHOB(1/2/4/6/8/10/12)	3.3V LVCMOS Normal Output Buffers
PHOB(4/6/8/10/12)SM	3.3V LVCMOS Normal Output Buffers with Medium Slew-Rate
PHOB(10/12)SH	3.3V LVCMOS Normal Output Buffers with High Slew-Rate
POD(1/2/4/6/8/10/12)	2.5V LVCMOS Open Drain Output Buffers
POD(4/6/8/10/12)SM	2.5V LVCMOS Open Drain Output Buffers with Medium Slew-Rate
POD(10/12)SH	2.5V LVCMOS Open Drain Output Buffers with High Slew-Rate
PHOD(1/2/4/6/8/10/12)	3.3V LVCMOS Open Drain Output Buffers
PHOD(4/6/8/10/12)SM	3.3V LVCMOS Open Drain Output Buffers with Medium Slew-Rate
PHOD(10/12)SH	3.3V LVCMOS Open Drain Output Buffers with High Slew-Rate
PTOD(1/2/3)	5V Tolerant Open Drain Output Buffers
POT(1/2/4/6/8/10/12)	2.5V LVCMOS Tri-State Output Buffers
POT(4/6/8/10/12)SM	2.5V LVCMOS Tri-State Output Buffers with Medium Slew-Rate
POT(10/12)SH	2.5V LVCMOS Tri-State Output Buffers with High Slew-Rate
PHOT(1/2/4/6/8/10/12)	3.3V LVCMOS Tri-State Output Buffers
PHOT(4/6/8/10/12)SM	3.3V LVCMOS Tri-State Output Buffers with Medium Slew-Rate
PHOT(10/12)SH	3.3V LVCMOS Tri-State Output Buffers with High Slew-Rate
PTOT(1/2/3)	5V Tolerant Tri-State Output Buffers


PvOByz

Normal Output Buffers

Cell Availability

Only 2.5V	3.3V Interface
POB(1/2/4/6/8/10/12) POB(4/6/8/10/12)SM POB(10/12)SH	PHOB(1/2/4/6/8/10/12) PHOB(4/6/8/10/12)SM PHOB(10/12)SH

Logic Symbol



Truth Table

A	PAD
0	0
1	1

Standard Load (SL)

Cell Name	A
POB(1/2/4/6/8)	9.801
POB(8/10/12)SM	16.532
POB(10/12)	19.614
POB(10/12)SH	25.576
PHOB(1/2/4/6/8/10/12)	5.444
PHOB(4/6/8/10/12)SM	5.444
PHOB(10/12)SH	5.444

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POB1**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	31.508	$1.210 + 0.606 \cdot \text{CL}$	$1.212 + 0.606 \cdot \text{CL}$	$1.209 + 0.606 \cdot \text{CL}$
	t_F	33.275	$1.275 + 0.640 \cdot \text{CL}$	$1.279 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	t_{PLH}	15.295	$0.789 + 0.290 \cdot \text{CL}$	$0.787 + 0.290 \cdot \text{CL}$	$0.790 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.054	$0.944 + 0.322 \cdot \text{CL}$	$0.946 + 0.322 \cdot \text{CL}$	$0.946 + 0.322 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB2**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	15.772	$0.624 + 0.303 \cdot \text{CL}$	$0.622 + 0.303 \cdot \text{CL}$	$0.625 + 0.303 \cdot \text{CL}$
	t_F	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	t_{PLH}	7.843	$0.590 + 0.145 \cdot \text{CL}$	$0.590 + 0.145 \cdot \text{CL}$	$0.589 + 0.145 \cdot \text{CL}$
	t_{PHL}	9.699	$0.580 + 0.182 \cdot \text{CL}$	$0.580 + 0.182 \cdot \text{CL}$	$0.578 + 0.182 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB4**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.917	$0.348 + 0.151 \cdot \text{CL}$	$0.342 + 0.151 \cdot \text{CL}$	$0.343 + 0.151 \cdot \text{CL}$
	t_F	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.271	$0.643 + 0.073 \cdot \text{CL}$	$0.644 + 0.073 \cdot \text{CL}$	$0.644 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.026	$0.468 + 0.091 \cdot \text{CL}$	$0.467 + 0.091 \cdot \text{CL}$	$0.466 + 0.091 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB6**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.317	$0.308 + 0.100 \cdot \text{CL}$	$0.280 + 0.101 \cdot \text{CL}$	$0.265 + 0.101 \cdot \text{CL}$
	t_F	6.097	$0.261 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	t_{PLH}	3.204	$0.785 + 0.048 \cdot \text{CL}$	$0.786 + 0.048 \cdot \text{CL}$	$0.786 + 0.048 \cdot \text{CL}$
	t_{PHL}	3.520	$0.487 + 0.061 \cdot \text{CL}$	$0.483 + 0.061 \cdot \text{CL}$	$0.481 + 0.061 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOByz

Normal Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POB8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.293	$0.230 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$
	t_F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t_{PLH}	3.470	$1.129 + 0.047 \cdot \text{CL}$	$1.128 + 0.047 \cdot \text{CL}$	$1.127 + 0.047 \cdot \text{CL}$
	t_{PHL}	3.069	$0.845 + 0.044 \cdot \text{CL}$	$0.845 + 0.044 \cdot \text{CL}$	$0.845 + 0.044 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POB10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.217	$0.236 + 0.060 \cdot \text{CL}$	$0.207 + 0.060 \cdot \text{CL}$	$0.189 + 0.060 \cdot \text{CL}$
	t_F	3.668	$0.174 + 0.070 \cdot \text{CL}$	$0.166 + 0.070 \cdot \text{CL}$	$0.163 + 0.070 \cdot \text{CL}$
	t_{PLH}	2.107	$0.654 + 0.029 \cdot \text{CL}$	$0.656 + 0.029 \cdot \text{CL}$	$0.656 + 0.029 \cdot \text{CL}$
	t_{PHL}	2.218	$0.401 + 0.036 \cdot \text{CL}$	$0.397 + 0.036 \cdot \text{CL}$	$0.395 + 0.036 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POB12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	2.719	$0.264 + 0.049 \cdot \text{CL}$	$0.229 + 0.050 \cdot \text{CL}$	$0.202 + 0.050 \cdot \text{CL}$
	t_F	3.069	$0.166 + 0.058 \cdot \text{CL}$	$0.154 + 0.058 \cdot \text{CL}$	$0.148 + 0.058 \cdot \text{CL}$
	t_{PLH}	1.950	$0.734 + 0.024 \cdot \text{CL}$	$0.739 + 0.024 \cdot \text{CL}$	$0.740 + 0.024 \cdot \text{CL}$
	t_{PHL}	1.942	$0.433 + 0.030 \cdot \text{CL}$	$0.427 + 0.030 \cdot \text{CL}$	$0.424 + 0.030 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POB4SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.135	$0.752 + 0.148 \cdot \text{CL}$	$0.660 + 0.149 \cdot \text{CL}$	$0.586 + 0.150 \cdot \text{CL}$
	t_F	9.483	$1.001 + 0.170 \cdot \text{CL}$	$0.889 + 0.172 \cdot \text{CL}$	$0.787 + 0.173 \cdot \text{CL}$
	t_{PLH}	5.457	$1.802 + 0.073 \cdot \text{CL}$	$1.823 + 0.073 \cdot \text{CL}$	$1.829 + 0.073 \cdot \text{CL}$
	t_{PHL}	6.998	$2.362 + 0.093 \cdot \text{CL}$	$2.422 + 0.092 \cdot \text{CL}$	$2.439 + 0.091 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB6SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.045	$1.305 + 0.095 \cdot \text{CL}$	$1.245 + 0.096 \cdot \text{CL}$	$1.147 + 0.097 \cdot \text{CL}$
	t_F	6.980	$1.447 + 0.111 \cdot \text{CL}$	$1.410 + 0.111 \cdot \text{CL}$	$1.318 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.100	$2.394 + 0.054 \cdot \text{CL}$	$2.575 + 0.051 \cdot \text{CL}$	$2.676 + 0.049 \cdot \text{CL}$
	t_{PHL}	6.308	$2.898 + 0.068 \cdot \text{CL}$	$3.119 + 0.064 \cdot \text{CL}$	$3.254 + 0.062 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB8SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.152	$1.648 + 0.070 \cdot \text{CL}$	$1.663 + 0.070 \cdot \text{CL}$	$1.594 + 0.071 \cdot \text{CL}$
	t_F	5.708	$1.557 + 0.083 \cdot \text{CL}$	$1.595 + 0.082 \cdot \text{CL}$	$1.543 + 0.083 \cdot \text{CL}$
	t_{PLH}	4.762	$2.427 + 0.047 \cdot \text{CL}$	$2.708 + 0.041 \cdot \text{CL}$	$2.900 + 0.039 \cdot \text{CL}$
	t_{PHL}	5.616	$2.839 + 0.056 \cdot \text{CL}$	$3.103 + 0.050 \cdot \text{CL}$	$3.289 + 0.048 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POB10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.204	$1.322 + 0.058 \cdot \text{CL}$	$1.361 + 0.057 \cdot \text{CL}$	$1.342 + 0.057 \cdot \text{CL}$
	t_F	4.729	$1.356 + 0.067 \cdot \text{CL}$	$1.416 + 0.066 \cdot \text{CL}$	$1.403 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.405	$2.495 + 0.038 \cdot \text{CL}$	$2.718 + 0.034 \cdot \text{CL}$	$2.886 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.175	$2.861 + 0.046 \cdot \text{CL}$	$3.101 + 0.041 \cdot \text{CL}$	$3.281 + 0.039 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOByz

Normal Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POB12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.190	$1.629 + 0.051 \cdot \text{CL}$	$1.774 + 0.048 \cdot \text{CL}$	$1.847 + 0.047 \cdot \text{CL}$
	t_F	4.546	$1.542 + 0.060 \cdot \text{CL}$	$1.723 + 0.056 \cdot \text{CL}$	$1.811 + 0.055 \cdot \text{CL}$
	t_{PLH}	4.640	$2.688 + 0.039 \cdot \text{CL}$	$2.990 + 0.033 \cdot \text{CL}$	$3.244 + 0.030 \cdot \text{CL}$
	t_{PHL}	5.372	$3.145 + 0.045 \cdot \text{CL}$	$3.432 + 0.039 \cdot \text{CL}$	$3.677 + 0.036 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POB10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.202	$2.922 + 0.066 \cdot \text{CL}$	$3.205 + 0.060 \cdot \text{CL}$	$3.394 + 0.057 \cdot \text{CL}$
	t_F	6.442	$2.722 + 0.074 \cdot \text{CL}$	$2.995 + 0.069 \cdot \text{CL}$	$3.168 + 0.067 \cdot \text{CL}$
	t_{PLH}	7.316	$4.395 + 0.058 \cdot \text{CL}$	$4.943 + 0.047 \cdot \text{CL}$	$5.408 + 0.041 \cdot \text{CL}$
	t_{PHL}	7.953	$4.743 + 0.064 \cdot \text{CL}$	$5.265 + 0.054 \cdot \text{CL}$	$5.711 + 0.048 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POB12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.575	$3.532 + 0.061 \cdot \text{CL}$	$3.914 + 0.053 \cdot \text{CL}$	$4.189 + 0.050 \cdot \text{CL}$
	t_F	6.532	$3.087 + 0.069 \cdot \text{CL}$	$3.482 + 0.061 \cdot \text{CL}$	$3.754 + 0.057 \cdot \text{CL}$
	t_{PLH}	7.825	$4.698 + 0.063 \cdot \text{CL}$	$5.373 + 0.049 \cdot \text{CL}$	$5.946 + 0.041 \cdot \text{CL}$
	t_{PHL}	8.410	$5.170 + 0.065 \cdot \text{CL}$	$5.765 + 0.053 \cdot \text{CL}$	$6.283 + 0.046 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOB1**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	42.148	$1.623 + 0.811 \cdot \text{CL}$	$1.624 + 0.810 \cdot \text{CL}$	$1.621 + 0.811 \cdot \text{CL}$
	t_F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t_{PLH}	20.150	$1.403 + 0.375 \cdot \text{CL}$	$1.404 + 0.375 \cdot \text{CL}$	$1.401 + 0.375 \cdot \text{CL}$
	t_{PHL}	16.887	$1.325 + 0.311 \cdot \text{CL}$	$1.321 + 0.311 \cdot \text{CL}$	$1.324 + 0.311 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB2**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	21.098	$0.836 + 0.405 \cdot \text{CL}$	$0.836 + 0.405 \cdot \text{CL}$	$0.833 + 0.405 \cdot \text{CL}$
	t_F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t_{PLH}	10.450	$1.078 + 0.187 \cdot \text{CL}$	$1.076 + 0.187 \cdot \text{CL}$	$1.076 + 0.187 \cdot \text{CL}$
	t_{PHL}	9.844	$0.948 + 0.178 \cdot \text{CL}$	$0.949 + 0.178 \cdot \text{CL}$	$0.947 + 0.178 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB4**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.563	$0.433 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$
	t_F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t_{PLH}	5.676	$0.991 + 0.094 \cdot \text{CL}$	$0.990 + 0.094 \cdot \text{CL}$	$0.990 + 0.094 \cdot \text{CL}$
	t_{PHL}	5.280	$0.832 + 0.089 \cdot \text{CL}$	$0.832 + 0.089 \cdot \text{CL}$	$0.833 + 0.089 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB6**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.047	$0.294 + 0.135 \cdot \text{CL}$	$0.294 + 0.135 \cdot \text{CL}$	$0.293 + 0.135 \cdot \text{CL}$
	t_F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t_{PLH}	4.232	$1.109 + 0.062 \cdot \text{CL}$	$1.108 + 0.062 \cdot \text{CL}$	$1.108 + 0.062 \cdot \text{CL}$
	t_{PHL}	3.804	$0.839 + 0.059 \cdot \text{CL}$	$0.839 + 0.059 \cdot \text{CL}$	$0.840 + 0.059 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOB8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.293	$0.230 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$
	t_F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t_{PLH}	3.470	$1.129 + 0.047 \cdot \text{CL}$	$1.128 + 0.047 \cdot \text{CL}$	$1.127 + 0.047 \cdot \text{CL}$
	t_{PHL}	3.069	$0.845 + 0.044 \cdot \text{CL}$	$0.845 + 0.044 \cdot \text{CL}$	$0.845 + 0.044 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOB10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.243	$0.197 + 0.081 \cdot \text{CL}$	$0.191 + 0.081 \cdot \text{CL}$	$0.190 + 0.081 \cdot \text{CL}$
	t_F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.174 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t_{PLH}	3.030	$1.160 + 0.037 \cdot \text{CL}$	$1.157 + 0.037 \cdot \text{CL}$	$1.156 + 0.037 \cdot \text{CL}$
	t_{PHL}	2.643	$0.863 + 0.036 \cdot \text{CL}$	$0.863 + 0.036 \cdot \text{CL}$	$0.863 + 0.036 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOB12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.544	$0.181 + 0.067 \cdot \text{CL}$	$0.170 + 0.067 \cdot \text{CL}$	$0.167 + 0.068 \cdot \text{CL}$
	t_F	3.070	$0.176 + 0.058 \cdot \text{CL}$	$0.162 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.751	$1.197 + 0.031 \cdot \text{CL}$	$1.193 + 0.031 \cdot \text{CL}$	$1.190 + 0.031 \cdot \text{CL}$
	t_{PHL}	2.370	$0.887 + 0.030 \cdot \text{CL}$	$0.887 + 0.030 \cdot \text{CL}$	$0.887 + 0.030 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics (Typical process, 25°C, 2.5V/3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOB4SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.608	$0.517 + 0.202 \cdot \text{CL}$	$0.486 + 0.202 \cdot \text{CL}$	$0.477 + 0.203 \cdot \text{CL}$
	t_F	9.435	$0.947 + 0.170 \cdot \text{CL}$	$0.842 + 0.172 \cdot \text{CL}$	$0.750 + 0.173 \cdot \text{CL}$
	t_{PLH}	6.404	$1.715 + 0.094 \cdot \text{CL}$	$1.716 + 0.094 \cdot \text{CL}$	$1.718 + 0.094 \cdot \text{CL}$
	t_{PHL}	7.039	$2.530 + 0.090 \cdot \text{CL}$	$2.579 + 0.089 \cdot \text{CL}$	$2.594 + 0.089 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB6SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.211	$0.618 + 0.132 \cdot \text{CL}$	$0.540 + 0.133 \cdot \text{CL}$	$0.478 + 0.134 \cdot \text{CL}$
	t_F	6.910	$1.355 + 0.111 \cdot \text{CL}$	$1.328 + 0.112 \cdot \text{CL}$	$1.248 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.165	$2.022 + 0.063 \cdot \text{CL}$	$2.037 + 0.063 \cdot \text{CL}$	$2.041 + 0.063 \cdot \text{CL}$
	t_{PHL}	6.311	$3.000 + 0.066 \cdot \text{CL}$	$3.208 + 0.062 \cdot \text{CL}$	$3.333 + 0.060 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB8SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.691	$0.888 + 0.096 \cdot \text{CL}$	$0.802 + 0.098 \cdot \text{CL}$	$0.711 + 0.099 \cdot \text{CL}$
	t_F	6.059	$1.788 + 0.085 \cdot \text{CL}$	$1.905 + 0.083 \cdot \text{CL}$	$1.926 + 0.083 \cdot \text{CL}$
	t_{PLH}	4.807	$2.352 + 0.049 \cdot \text{CL}$	$2.434 + 0.047 \cdot \text{CL}$	$2.466 + 0.047 \cdot \text{CL}$
	t_{PHL}	6.336	$3.367 + 0.059 \cdot \text{CL}$	$3.714 + 0.052 \cdot \text{CL}$	$3.984 + 0.049 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOB10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.501	$0.614 + 0.078 \cdot \text{CL}$	$0.553 + 0.079 \cdot \text{CL}$	$0.502 + 0.080 \cdot \text{CL}$
	t_F	5.283	$1.821 + 0.069 \cdot \text{CL}$	$1.971 + 0.066 \cdot \text{CL}$	$2.023 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.008	$2.093 + 0.038 \cdot \text{CL}$	$2.129 + 0.038 \cdot \text{CL}$	$2.140 + 0.037 \cdot \text{CL}$
	t_{PHL}	5.781	$3.176 + 0.052 \cdot \text{CL}$	$3.541 + 0.045 \cdot \text{CL}$	$3.833 + 0.041 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOB12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.002	$0.794 + 0.064 \cdot \text{CL}$	$0.770 + 0.065 \cdot \text{CL}$	$0.723 + 0.065 \cdot \text{CL}$
	t_F	4.483	$1.509 + 0.059 \cdot \text{CL}$	$1.656 + 0.057 \cdot \text{CL}$	$1.734 + 0.056 \cdot \text{CL}$
	t_{PLH}	3.970	$2.249 + 0.034 \cdot \text{CL}$	$2.350 + 0.032 \cdot \text{CL}$	$2.408 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.356	$3.141 + 0.044 \cdot \text{CL}$	$3.442 + 0.038 \cdot \text{CL}$	$3.692 + 0.035 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOB10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.281	$1.455 + 0.077 \cdot \text{CL}$	$1.475 + 0.076 \cdot \text{CL}$	$1.424 + 0.077 \cdot \text{CL}$
	t_F	6.213	$2.435 + 0.076 \cdot \text{CL}$	$2.714 + 0.070 \cdot \text{CL}$	$2.902 + 0.067 \cdot \text{CL}$
	t_{PLH}	5.749	$3.412 + 0.047 \cdot \text{CL}$	$3.654 + 0.042 \cdot \text{CL}$	$3.825 + 0.040 \cdot \text{CL}$
	t_{PHL}	7.639	$4.521 + 0.062 \cdot \text{CL}$	$5.020 + 0.052 \cdot \text{CL}$	$5.446 + 0.047 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOB12SH


Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.972	$1.688 + 0.066 \cdot \text{CL}$	$1.804 + 0.063 \cdot \text{CL}$	$1.821 + 0.063 \cdot \text{CL}$
	t_F	6.233	$2.772 + 0.069 \cdot \text{CL}$	$3.130 + 0.062 \cdot \text{CL}$	$3.403 + 0.058 \cdot \text{CL}$
	t_{PLH}	5.899	$3.670 + 0.045 \cdot \text{CL}$	$3.971 + 0.039 \cdot \text{CL}$	$4.210 + 0.035 \cdot \text{CL}$
	t_{PHL}	7.963	$4.796 + 0.063 \cdot \text{CL}$	$5.374 + 0.052 \cdot \text{CL}$	$5.877 + 0.045 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Cell Availability

2.5V Only	3.3V Interface	5V Tolerant
POD(1/2/4/6/8/10/12) POD(4/6/8/10/12)SM POD(10/12)SH	PHOD(1/2/4/6/8/10/12) PHOD(4/6/8/10/12)SM PHOD(10/12)SH	PTOD(1/2/3)

Logic Symbol



Truth Table

TN	EN	PAD
1	0	0
0	x	Hi-Z
x	1	Hi-Z

Standard Load (SL)

Cell Name	TN	EN
POD(1/2/4/6/8/10/12)	2.897	2.916
POD(4/6/8/10/12)SM	2.897	2.916
POD(10/12)SH	2.897	2.916
PHOD(1/2/4/6/8/10/12)	2.897	2.916
PHOD(4/6/8/10/12)SM	2.897	2.916
PHOD(10/12)SH	2.897	2.916
PTOD(1/2/3)	2.897	2.916

PvODyz

Open Drain Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	33.275	$1.275 + 0.640 \cdot \text{CL}$	$1.279 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	tPHL	24.790	$1.900 + 0.458 \cdot \text{CL}$	$1.764 + 0.461 \cdot \text{CL}$	$1.764 + 0.461 \cdot \text{CL}$
	tPLZ	0.875	$0.874 + 0.000 \cdot \text{CL}$	$0.875 + 0.000 \cdot \text{CL}$	$0.875 + 0.000 \cdot \text{CL}$
EN to PAD	tF	33.275	$1.275 + 0.640 \cdot \text{CL}$	$1.279 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	tPHL	24.888	$1.998 + 0.458 \cdot \text{CL}$	$1.862 + 0.461 \cdot \text{CL}$	$1.862 + 0.461 \cdot \text{CL}$
	tPLZ	0.917	$0.917 + 0.000 \cdot \text{CL}$	$0.917 + 0.000 \cdot \text{CL}$	$0.917 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	tPHL	14.231	$1.304 + 0.259 \cdot \text{CL}$	$1.229 + 0.260 \cdot \text{CL}$	$1.229 + 0.260 \cdot \text{CL}$
	tPLZ	0.728	$0.728 + 0.000 \cdot \text{CL}$	$0.728 + 0.000 \cdot \text{CL}$	$0.728 + 0.000 \cdot \text{CL}$
EN to PAD	tF	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	tPHL	14.329	$1.403 + 0.259 \cdot \text{CL}$	$1.327 + 0.260 \cdot \text{CL}$	$1.324 + 0.260 \cdot \text{CL}$
	tPLZ	0.772	$0.772 + 0.000 \cdot \text{CL}$	$0.771 + 0.000 \cdot \text{CL}$	$0.772 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POD4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	tPHL	7.510	$1.047 + 0.129 \cdot \text{CL}$	$1.008 + 0.130 \cdot \text{CL}$	$1.011 + 0.130 \cdot \text{CL}$
	tPLZ	0.857	$0.857 + 0.000 \cdot \text{CL}$	$0.857 + 0.000 \cdot \text{CL}$	$0.857 + 0.000 \cdot \text{CL}$
EN to PAD	tF	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	tPHL	7.609	$1.146 + 0.129 \cdot \text{CL}$	$1.106 + 0.130 \cdot \text{CL}$	$1.110 + 0.130 \cdot \text{CL}$
	tPLZ	0.900	$0.900 + 0.000 \cdot \text{CL}$	$0.900 + 0.000 \cdot \text{CL}$	$0.900 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POD6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	6.097	$0.255 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	tPHL	5.319	$1.010 + 0.086 \cdot \text{CL}$	$0.984 + 0.087 \cdot \text{CL}$	$0.984 + 0.087 \cdot \text{CL}$
	tPLZ	0.984	$0.984 + 0.000 \cdot \text{CL}$	$0.984 + 0.000 \cdot \text{CL}$	$0.984 + 0.000 \cdot \text{CL}$
EN to PAD	tF	6.097	$0.255 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	tPHL	5.418	$1.108 + 0.086 \cdot \text{CL}$	$1.083 + 0.087 \cdot \text{CL}$	$1.083 + 0.087 \cdot \text{CL}$
	tPLZ	1.026	$1.026 + 0.000 \cdot \text{CL}$	$1.026 + 0.000 \cdot \text{CL}$	$1.026 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POD8**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	4.588	$0.206 + 0.088 \cdot \text{CL}$	$0.207 + 0.088 \cdot \text{CL}$	$0.207 + 0.088 \cdot \text{CL}$
	t _{PHL}	4.260	$1.028 + 0.065 \cdot \text{CL}$	$1.009 + 0.065 \cdot \text{CL}$	$1.009 + 0.065 \cdot \text{CL}$
	t _{PLZ}	1.111	$1.111 + 0.000 \cdot \text{CL}$	$1.111 + 0.000 \cdot \text{CL}$	$1.111 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	4.588	$0.206 + 0.088 \cdot \text{CL}$	$0.207 + 0.088 \cdot \text{CL}$	$0.207 + 0.088 \cdot \text{CL}$
	t _{PHL}	4.358	$1.126 + 0.065 \cdot \text{CL}$	$1.107 + 0.065 \cdot \text{CL}$	$1.108 + 0.065 \cdot \text{CL}$
	t _{PLZ}	1.153	$1.153 + 0.000 \cdot \text{CL}$	$1.153 + 0.000 \cdot \text{CL}$	$1.153 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POD10**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	3.667	$0.161 + 0.070 \cdot \text{CL}$	$0.162 + 0.070 \cdot \text{CL}$	$0.162 + 0.070 \cdot \text{CL}$
	t _{PHL}	3.524	$0.938 + 0.052 \cdot \text{CL}$	$0.923 + 0.052 \cdot \text{CL}$	$0.923 + 0.052 \cdot \text{CL}$
	t _{PLZ}	0.968	$0.968 + 0.000 \cdot \text{CL}$	$0.968 + 0.000 \cdot \text{CL}$	$0.968 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	3.667	$0.161 + 0.070 \cdot \text{CL}$	$0.162 + 0.070 \cdot \text{CL}$	$0.162 + 0.070 \cdot \text{CL}$
	t _{PHL}	3.623	$1.037 + 0.052 \cdot \text{CL}$	$1.022 + 0.052 \cdot \text{CL}$	$1.022 + 0.052 \cdot \text{CL}$
	t _{PLZ}	1.011	$1.011 + 0.000 \cdot \text{CL}$	$1.011 + 0.000 \cdot \text{CL}$	$1.011 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POD12**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	3.064	$0.143 + 0.058 \cdot \text{CL}$	$0.143 + 0.058 \cdot \text{CL}$	$0.144 + 0.058 \cdot \text{CL}$
	t _{PHL}	3.108	$0.953 + 0.043 \cdot \text{CL}$	$0.941 + 0.043 \cdot \text{CL}$	$0.941 + 0.043 \cdot \text{CL}$
	t _{PLZ}	1.032	$1.031 + 0.000 \cdot \text{CL}$	$1.032 + 0.000 \cdot \text{CL}$	$1.032 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	3.064	$0.143 + 0.058 \cdot \text{CL}$	$0.143 + 0.058 \cdot \text{CL}$	$0.144 + 0.058 \cdot \text{CL}$
	t _{PHL}	3.207	$1.052 + 0.043 \cdot \text{CL}$	$1.039 + 0.043 \cdot \text{CL}$	$1.040 + 0.043 \cdot \text{CL}$
	t _{PLZ}	1.075	$1.075 + 0.000 \cdot \text{CL}$	$1.075 + 0.000 \cdot \text{CL}$	$1.075 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvODyz

Open Drain Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POD4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	9.279	$0.637 + 0.173 \cdot \text{CL}$	$0.549 + 0.175 \cdot \text{CL}$	$0.510 + 0.175 \cdot \text{CL}$
	t _{PHL}	9.580	$3.085 + 0.130 \cdot \text{CL}$	$3.073 + 0.130 \cdot \text{CL}$	$3.078 + 0.130 \cdot \text{CL}$
	t _{PLZ}	1.000	$0.999 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	9.279	$0.637 + 0.173 \cdot \text{CL}$	$0.549 + 0.175 \cdot \text{CL}$	$0.510 + 0.175 \cdot \text{CL}$
	t _{PHL}	9.679	$3.183 + 0.130 \cdot \text{CL}$	$3.172 + 0.130 \cdot \text{CL}$	$3.177 + 0.130 \cdot \text{CL}$
	t _{PLZ}	1.043	$1.042 + 0.000 \cdot \text{CL}$	$1.043 + 0.000 \cdot \text{CL}$	$1.043 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POD6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	6.521	$0.979 + 0.111 \cdot \text{CL}$	$0.863 + 0.113 \cdot \text{CL}$	$0.735 + 0.115 \cdot \text{CL}$
	t _{PHL}	8.285	$3.720 + 0.091 \cdot \text{CL}$	$3.870 + 0.088 \cdot \text{CL}$	$3.952 + 0.087 \cdot \text{CL}$
	t _{PLZ}	1.275	$1.275 + 0.000 \cdot \text{CL}$	$1.275 + 0.000 \cdot \text{CL}$	$1.275 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	6.521	$0.979 + 0.111 \cdot \text{CL}$	$0.863 + 0.113 \cdot \text{CL}$	$0.735 + 0.115 \cdot \text{CL}$
	t _{PHL}	8.383	$3.819 + 0.091 \cdot \text{CL}$	$3.968 + 0.088 \cdot \text{CL}$	$4.054 + 0.087 \cdot \text{CL}$
	t _{PLZ}	1.317	$1.317 + 0.000 \cdot \text{CL}$	$1.317 + 0.000 \cdot \text{CL}$	$1.317 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POD8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	5.166	$1.112 + 0.081 \cdot \text{CL}$	$1.028 + 0.083 \cdot \text{CL}$	$0.893 + 0.085 \cdot \text{CL}$
	t _{PHL}	7.288	$3.655 + 0.073 \cdot \text{CL}$	$3.883 + 0.068 \cdot \text{CL}$	$4.028 + 0.066 \cdot \text{CL}$
	t _{PLZ}	1.883	$1.882 + 0.000 \cdot \text{CL}$	$1.883 + 0.000 \cdot \text{CL}$	$1.883 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	5.166	$1.112 + 0.081 \cdot \text{CL}$	$1.028 + 0.083 \cdot \text{CL}$	$0.893 + 0.085 \cdot \text{CL}$
	t _{PHL}	7.387	$3.754 + 0.073 \cdot \text{CL}$	$3.981 + 0.068 \cdot \text{CL}$	$4.126 + 0.066 \cdot \text{CL}$
	t _{PLZ}	1.926	$1.924 + 0.000 \cdot \text{CL}$	$1.925 + 0.000 \cdot \text{CL}$	$1.925 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POD10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	4.261	$0.986 + 0.066 \cdot \text{CL}$	$0.954 + 0.066 \cdot \text{CL}$	$0.867 + 0.067 \cdot \text{CL}$
	t _{PHL}	6.653	$3.655 + 0.060 \cdot \text{CL}$	$3.871 + 0.056 \cdot \text{CL}$	$4.025 + 0.054 \cdot \text{CL}$
	t _{PLZ}	1.883	$1.882 + 0.000 \cdot \text{CL}$	$1.883 + 0.000 \cdot \text{CL}$	$1.883 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	4.261	$0.985 + 0.066 \cdot \text{CL}$	$0.955 + 0.066 \cdot \text{CL}$	$0.867 + 0.067 \cdot \text{CL}$
	t _{PHL}	6.752	$3.754 + 0.060 \cdot \text{CL}$	$3.970 + 0.056 \cdot \text{CL}$	$4.123 + 0.054 \cdot \text{CL}$
	t _{PLZ}	1.926	$1.924 + 0.000 \cdot \text{CL}$	$1.925 + 0.000 \cdot \text{CL}$	$1.925 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POD12SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	3.987	$1.230 + 0.055 \cdot \text{CL}$	$1.278 + 0.054 \cdot \text{CL}$	$1.248 + 0.055 \cdot \text{CL}$
	t _{PHL}	6.787	$3.941 + 0.057 \cdot \text{CL}$	$4.253 + 0.051 \cdot \text{CL}$	$4.507 + 0.047 \cdot \text{CL}$
	t _{PLZ}	2.251	$2.250 + 0.000 \cdot \text{CL}$	$2.251 + 0.000 \cdot \text{CL}$	$2.251 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	3.987	$1.230 + 0.055 \cdot \text{CL}$	$1.278 + 0.054 \cdot \text{CL}$	$1.248 + 0.055 \cdot \text{CL}$
	t _{PHL}	6.886	$4.040 + 0.057 \cdot \text{CL}$	$4.351 + 0.051 \cdot \text{CL}$	$4.606 + 0.047 \cdot \text{CL}$
	t _{PLZ}	2.294	$2.292 + 0.000 \cdot \text{CL}$	$2.293 + 0.000 \cdot \text{CL}$	$2.293 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POD10SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	5.431	$2.047 + 0.068 \cdot \text{CL}$	$2.179 + 0.065 \cdot \text{CL}$	$2.213 + 0.065 \cdot \text{CL}$
	t _{PHL}	9.785	$5.852 + 0.079 \cdot \text{CL}$	$6.395 + 0.068 \cdot \text{CL}$	$6.860 + 0.062 \cdot \text{CL}$
	t _{PLZ}	2.322	$2.321 + 0.000 \cdot \text{CL}$	$2.322 + 0.000 \cdot \text{CL}$	$2.322 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	5.431	$2.047 + 0.068 \cdot \text{CL}$	$2.179 + 0.065 \cdot \text{CL}$	$2.213 + 0.065 \cdot \text{CL}$
	t _{PHL}	9.884	$5.950 + 0.079 \cdot \text{CL}$	$6.494 + 0.068 \cdot \text{CL}$	$6.959 + 0.062 \cdot \text{CL}$
	t _{PLZ}	2.365	$2.363 + 0.000 \cdot \text{CL}$	$2.364 + 0.000 \cdot \text{CL}$	$2.365 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POD12SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	5.378	$2.451 + 0.059 \cdot \text{CL}$	$2.627 + 0.055 \cdot \text{CL}$	$2.722 + 0.054 \cdot \text{CL}$
	t _{PHL}	10.235	$6.317 + 0.078 \cdot \text{CL}$	$6.969 + 0.065 \cdot \text{CL}$	$7.539 + 0.058 \cdot \text{CL}$
	t _{PLZ}	2.690	$2.688 + 0.000 \cdot \text{CL}$	$2.689 + 0.000 \cdot \text{CL}$	$2.690 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	5.378	$2.451 + 0.059 \cdot \text{CL}$	$2.627 + 0.055 \cdot \text{CL}$	$2.722 + 0.054 \cdot \text{CL}$
	t _{PHL}	10.334	$6.416 + 0.078 \cdot \text{CL}$	$7.068 + 0.065 \cdot \text{CL}$	$7.638 + 0.058 \cdot \text{CL}$
	t _{PLZ}	2.733	$2.730 + 0.000 \cdot \text{CL}$	$2.732 + 0.000 \cdot \text{CL}$	$2.733 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t _{PHL}	17.228	$1.663 + 0.311 \cdot \text{CL}$	$1.664 + 0.311 \cdot \text{CL}$	$1.664 + 0.311 \cdot \text{CL}$
	t _{PLZ}	1.199	$1.198 + 0.000 \cdot \text{CL}$	$1.199 + 0.000 \cdot \text{CL}$	$1.199 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t _{PHL}	17.327	$1.762 + 0.311 \cdot \text{CL}$	$1.763 + 0.311 \cdot \text{CL}$	$1.763 + 0.311 \cdot \text{CL}$
	t _{PLZ}	1.242	$1.242 + 0.000 \cdot \text{CL}$	$1.242 + 0.000 \cdot \text{CL}$	$1.242 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t _{PHL}	10.187	$1.292 + 0.178 \cdot \text{CL}$	$1.291 + 0.178 \cdot \text{CL}$	$1.294 + 0.178 \cdot \text{CL}$
	t _{PLZ}	1.056	$1.056 + 0.000 \cdot \text{CL}$	$1.056 + 0.000 \cdot \text{CL}$	$1.056 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t _{PHL}	10.286	$1.391 + 0.178 \cdot \text{CL}$	$1.390 + 0.178 \cdot \text{CL}$	$1.393 + 0.178 \cdot \text{CL}$
	t _{PLZ}	1.100	$1.100 + 0.000 \cdot \text{CL}$	$1.100 + 0.000 \cdot \text{CL}$	$1.100 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t _{PHL}	5.622	$1.175 + 0.089 \cdot \text{CL}$	$1.175 + 0.089 \cdot \text{CL}$	$1.175 + 0.089 \cdot \text{CL}$
	t _{PLZ}	1.206	$1.206 + 0.000 \cdot \text{CL}$	$1.206 + 0.000 \cdot \text{CL}$	$1.206 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t _{PHL}	5.721	$1.273 + 0.089 \cdot \text{CL}$	$1.274 + 0.089 \cdot \text{CL}$	$1.274 + 0.089 \cdot \text{CL}$
	t _{PLZ}	1.249	$1.249 + 0.000 \cdot \text{CL}$	$1.249 + 0.000 \cdot \text{CL}$	$1.249 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t _{PHL}	4.080	$1.115 + 0.059 \cdot \text{CL}$	$1.115 + 0.059 \cdot \text{CL}$	$1.115 + 0.059 \cdot \text{CL}$
	t _{PLZ}	1.166	$1.166 + 0.000 \cdot \text{CL}$	$1.166 + 0.000 \cdot \text{CL}$	$1.166 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t _{PHL}	4.179	$1.214 + 0.059 \cdot \text{CL}$	$1.214 + 0.059 \cdot \text{CL}$	$1.214 + 0.059 \cdot \text{CL}$
	t _{PLZ}	1.209	$1.209 + 0.000 \cdot \text{CL}$	$1.209 + 0.000 \cdot \text{CL}$	$1.209 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOD8**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t _{PHL}	3.344	$1.120 + 0.044 \cdot \text{CL}$	$1.120 + 0.044 \cdot \text{CL}$	$1.120 + 0.044 \cdot \text{CL}$
	t _{PLZ}	1.240	$1.240 + 0.000 \cdot \text{CL}$	$1.240 + 0.000 \cdot \text{CL}$	$1.240 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t _{PHL}	3.443	$1.219 + 0.044 \cdot \text{CL}$	$1.219 + 0.044 \cdot \text{CL}$	$1.219 + 0.044 \cdot \text{CL}$
	t _{PLZ}	1.284	$1.284 + 0.000 \cdot \text{CL}$	$1.284 + 0.000 \cdot \text{CL}$	$1.284 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.175 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t _{PHL}	2.917	$1.137 + 0.036 \cdot \text{CL}$	$1.138 + 0.036 \cdot \text{CL}$	$1.137 + 0.036 \cdot \text{CL}$
	t _{PLZ}	1.315	$1.315 + 0.000 \cdot \text{CL}$	$1.315 + 0.000 \cdot \text{CL}$	$1.315 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.175 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t _{PHL}	3.016	$1.236 + 0.036 \cdot \text{CL}$	$1.236 + 0.036 \cdot \text{CL}$	$1.237 + 0.036 \cdot \text{CL}$
	t _{PLZ}	1.359	$1.359 + 0.000 \cdot \text{CL}$	$1.359 + 0.000 \cdot \text{CL}$	$1.359 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t _F	3.071	$0.177 + 0.058 \cdot \text{CL}$	$0.163 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t _{PHL}	2.644	$1.161 + 0.030 \cdot \text{CL}$	$1.161 + 0.030 \cdot \text{CL}$	$1.161 + 0.030 \cdot \text{CL}$
	t _{PLZ}	1.390	$1.390 + 0.000 \cdot \text{CL}$	$1.390 + 0.000 \cdot \text{CL}$	$1.390 + 0.000 \cdot \text{CL}$
EN to PAD	t _F	3.071	$0.177 + 0.058 \cdot \text{CL}$	$0.163 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t _{PHL}	2.743	$1.260 + 0.030 \cdot \text{CL}$	$1.260 + 0.030 \cdot \text{CL}$	$1.260 + 0.030 \cdot \text{CL}$
	t _{PLZ}	1.433	$1.433 + 0.000 \cdot \text{CL}$	$1.433 + 0.000 \cdot \text{CL}$	$1.433 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvODyz

Open Drain Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOD4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	9.439	$0.956 + 0.170 \cdot \text{CL}$	$0.850 + 0.172 \cdot \text{CL}$	$0.752 + 0.173 \cdot \text{CL}$
	tPHL	7.343	$2.833 + 0.090 \cdot \text{CL}$	$2.883 + 0.089 \cdot \text{CL}$	$2.896 + 0.089 \cdot \text{CL}$
	tPLZ	1.304	$1.305 + 0.000 \cdot \text{CL}$	$1.303 + 0.000 \cdot \text{CL}$	$1.305 + 0.000 \cdot \text{CL}$
EN to PAD	tF	9.439	$0.956 + 0.170 \cdot \text{CL}$	$0.850 + 0.172 \cdot \text{CL}$	$0.752 + 0.173 \cdot \text{CL}$
	tPHL	7.441	$2.932 + 0.090 \cdot \text{CL}$	$2.981 + 0.089 \cdot \text{CL}$	$2.995 + 0.089 \cdot \text{CL}$
	tPLZ	1.349	$1.348 + 0.000 \cdot \text{CL}$	$1.349 + 0.000 \cdot \text{CL}$	$1.349 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	6.922	$1.379 + 0.111 \cdot \text{CL}$	$1.347 + 0.111 \cdot \text{CL}$	$1.264 + 0.113 \cdot \text{CL}$
	tPHL	6.621	$3.306 + 0.066 \cdot \text{CL}$	$3.516 + 0.062 \cdot \text{CL}$	$3.643 + 0.060 \cdot \text{CL}$
	tPLZ	1.609	$1.609 + 0.000 \cdot \text{CL}$	$1.609 + 0.000 \cdot \text{CL}$	$1.609 + 0.000 \cdot \text{CL}$
EN to PAD	tF	6.922	$1.379 + 0.111 \cdot \text{CL}$	$1.347 + 0.111 \cdot \text{CL}$	$1.264 + 0.113 \cdot \text{CL}$
	tPHL	6.720	$3.405 + 0.066 \cdot \text{CL}$	$3.615 + 0.062 \cdot \text{CL}$	$3.742 + 0.060 \cdot \text{CL}$
	tPLZ	1.653	$1.653 + 0.000 \cdot \text{CL}$	$1.653 + 0.000 \cdot \text{CL}$	$1.653 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOD8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	tF	6.080	$1.825 + 0.085 \cdot \text{CL}$	$1.936 + 0.083 \cdot \text{CL}$	$1.953 + 0.083 \cdot \text{CL}$
	tPHL	6.644	$3.669 + 0.059 \cdot \text{CL}$	$4.019 + 0.052 \cdot \text{CL}$	$4.291 + 0.049 \cdot \text{CL}$
	tPLZ	1.913	$1.913 + 0.000 \cdot \text{CL}$	$1.913 + 0.000 \cdot \text{CL}$	$1.913 + 0.000 \cdot \text{CL}$
EN to PAD	tF	6.080	$1.825 + 0.085 \cdot \text{CL}$	$1.936 + 0.083 \cdot \text{CL}$	$1.953 + 0.083 \cdot \text{CL}$
	tPHL	6.743	$3.768 + 0.059 \cdot \text{CL}$	$4.118 + 0.053 \cdot \text{CL}$	$4.390 + 0.049 \cdot \text{CL}$
	tPLZ	1.957	$1.957 + 0.000 \cdot \text{CL}$	$1.956 + 0.000 \cdot \text{CL}$	$1.957 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOD10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	5.308	$1.865 + 0.069 \cdot \text{CL}$	$2.008 + 0.066 \cdot \text{CL}$	$2.054 + 0.065 \cdot \text{CL}$
	t_{PHL}	6.099	$3.486 + 0.052 \cdot \text{CL}$	$3.855 + 0.045 \cdot \text{CL}$	$4.150 + 0.041 \cdot \text{CL}$
	t_{PLZ}	2.661	$2.661 + 0.000 \cdot \text{CL}$	$2.661 + 0.000 \cdot \text{CL}$	$2.661 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	5.308	$1.865 + 0.069 \cdot \text{CL}$	$2.008 + 0.066 \cdot \text{CL}$	$2.054 + 0.065 \cdot \text{CL}$
	t_{PHL}	6.198	$3.585 + 0.052 \cdot \text{CL}$	$3.955 + 0.045 \cdot \text{CL}$	$4.249 + 0.041 \cdot \text{CL}$
	t_{PLZ}	2.705	$2.705 + 0.000 \cdot \text{CL}$	$2.705 + 0.000 \cdot \text{CL}$	$2.704 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOD12SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.505	$1.544 + 0.059 \cdot \text{CL}$	$1.686 + 0.056 \cdot \text{CL}$	$1.760 + 0.055 \cdot \text{CL}$
	t_{PHL}	5.672	$3.452 + 0.044 \cdot \text{CL}$	$3.756 + 0.038 \cdot \text{CL}$	$4.008 + 0.035 \cdot \text{CL}$
	t_{PLZ}	2.661	$2.661 + 0.000 \cdot \text{CL}$	$2.661 + 0.000 \cdot \text{CL}$	$2.661 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	4.505	$1.544 + 0.059 \cdot \text{CL}$	$1.686 + 0.056 \cdot \text{CL}$	$1.760 + 0.055 \cdot \text{CL}$
	t_{PHL}	5.771	$3.551 + 0.044 \cdot \text{CL}$	$3.855 + 0.038 \cdot \text{CL}$	$4.107 + 0.035 \cdot \text{CL}$
	t_{PLZ}	2.705	$2.705 + 0.000 \cdot \text{CL}$	$2.705 + 0.000 \cdot \text{CL}$	$2.705 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOD10SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.249	$2.489 + 0.075 \cdot \text{CL}$	$2.762 + 0.070 \cdot \text{CL}$	$2.945 + 0.067 \cdot \text{CL}$
	t_{PHL}	7.897	$4.768 + 0.063 \cdot \text{CL}$	$5.272 + 0.052 \cdot \text{CL}$	$5.704 + 0.047 \cdot \text{CL}$
	t_{PLZ}	2.715	$2.715 + 0.000 \cdot \text{CL}$	$2.715 + 0.000 \cdot \text{CL}$	$2.715 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	6.249	$2.489 + 0.075 \cdot \text{CL}$	$2.762 + 0.070 \cdot \text{CL}$	$2.945 + 0.067 \cdot \text{CL}$
	t_{PHL}	7.996	$4.867 + 0.063 \cdot \text{CL}$	$5.371 + 0.052 \cdot \text{CL}$	$5.803 + 0.047 \cdot \text{CL}$
	t_{PLZ}	2.757	$2.757 + 0.000 \cdot \text{CL}$	$2.757 + 0.000 \cdot \text{CL}$	$2.757 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOD12SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.277	$2.841 + 0.069 \cdot \text{CL}$	$3.190 + 0.062 \cdot \text{CL}$	$3.455 + 0.058 \cdot \text{CL}$
	t_{PHL}	8.214	$5.033 + 0.064 \cdot \text{CL}$	$5.618 + 0.052 \cdot \text{CL}$	$6.126 + 0.045 \cdot \text{CL}$
	t_{PLZ}	3.120	$3.119 + 0.000 \cdot \text{CL}$	$3.120 + 0.000 \cdot \text{CL}$	$3.120 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	6.277	$2.841 + 0.069 \cdot \text{CL}$	$3.190 + 0.062 \cdot \text{CL}$	$3.455 + 0.058 \cdot \text{CL}$
	t_{PHL}	8.313	$5.132 + 0.064 \cdot \text{CL}$	$5.717 + 0.052 \cdot \text{CL}$	$6.226 + 0.045 \cdot \text{CL}$
	t_{PLZ}	3.162	$3.161 + 0.000 \cdot \text{CL}$	$3.162 + 0.000 \cdot \text{CL}$	$3.162 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PTOD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	33.498	$2.496 + 0.620 \cdot \text{CL}$	$2.456 + 0.621 \cdot \text{CL}$	$2.426 + 0.621 \cdot \text{CL}$
	t_{PHL}	16.998	$1.635 + 0.307 \cdot \text{CL}$	$1.632 + 0.307 \cdot \text{CL}$	$1.641 + 0.307 \cdot \text{CL}$
	t_{PLZ}	1.028	$1.028 + 0.000 \cdot \text{CL}$	$1.028 + 0.000 \cdot \text{CL}$	$1.028 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	33.498	$2.496 + 0.620 \cdot \text{CL}$	$2.456 + 0.621 \cdot \text{CL}$	$2.426 + 0.621 \cdot \text{CL}$
	t_{PHL}	17.097	$1.734 + 0.307 \cdot \text{CL}$	$1.733 + 0.307 \cdot \text{CL}$	$1.736 + 0.307 \cdot \text{CL}$
	t_{PLZ}	1.072	$1.072 + 0.000 \cdot \text{CL}$	$1.072 + 0.000 \cdot \text{CL}$	$1.072 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PTOD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	16.748	$1.240 + 0.310 \cdot \text{CL}$	$1.234 + 0.310 \cdot \text{CL}$	$1.222 + 0.310 \cdot \text{CL}$
	t_{PHL}	8.985	$1.312 + 0.153 \cdot \text{CL}$	$1.315 + 0.153 \cdot \text{CL}$	$1.312 + 0.153 \cdot \text{CL}$
	t_{PLZ}	1.151	$1.151 + 0.000 \cdot \text{CL}$	$1.151 + 0.000 \cdot \text{CL}$	$1.151 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	16.748	$1.240 + 0.310 \cdot \text{CL}$	$1.234 + 0.310 \cdot \text{CL}$	$1.222 + 0.310 \cdot \text{CL}$
	t_{PHL}	9.084	$1.411 + 0.153 \cdot \text{CL}$	$1.414 + 0.153 \cdot \text{CL}$	$1.411 + 0.153 \cdot \text{CL}$
	t_{PLZ}	1.195	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$


PTOD3

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	11.158	$0.810 + 0.207 \cdot \text{CL}$	$0.812 + 0.207 \cdot \text{CL}$	$0.809 + 0.207 \cdot \text{CL}$
	t_{PHL}	6.351	$1.235 + 0.102 \cdot \text{CL}$	$1.238 + 0.102 \cdot \text{CL}$	$1.239 + 0.102 \cdot \text{CL}$
	t_{PLZ}	1.272	$1.272 + 0.000 \cdot \text{CL}$	$1.272 + 0.000 \cdot \text{CL}$	$1.272 + 0.000 \cdot \text{CL}$
EN to PAD	t_F	11.158	$0.810 + 0.207 \cdot \text{CL}$	$0.812 + 0.207 \cdot \text{CL}$	$0.809 + 0.207 \cdot \text{CL}$
	t_{PHL}	6.450	$1.334 + 0.102 \cdot \text{CL}$	$1.337 + 0.102 \cdot \text{CL}$	$1.338 + 0.102 \cdot \text{CL}$
	t_{PLZ}	1.316	$1.316 + 0.000 \cdot \text{CL}$	$1.316 + 0.000 \cdot \text{CL}$	$1.316 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Cell Availability

2.5V Only	3.3V Interface	5V Tolerant
POT(1/2/4/6/8/10/12) POT(4/6/8/10/12)SM POT(10/12)SH	PHOT(1/2/4/6/8/10/12) PHOT(4/6/8/10/12)SM PHOT(10/12)SH	PTOT(1/2/3)

Logic Symbol**Truth Table**

TN	EN	A	PAD
1	0	0	0
1	0	1	1
x	1	x	Hi-Z
0	x	x	Hi-Z

Standard Load (SL)

Cell Name	TN	EN	A
POT(1/2/4/6/8/10/12)	2.898	2.916	3.023
POT(4/6/8/10/12)SM	2.898	2.916	3.023
POT(10/12)SH	2.898	2.916	3.023
PHOT(1/2/4/6/8/10/12)	2.898	2.916	5.444
PHOT(4/6/8/10/12)SM	2.898	2.916	5.444
PHOT(10/12)SH	2.898	2.916	5.444
PTOT(1/2/3)	2.898	2.916	5.444

PvOTyz

Tri-State Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	31.508	$1.210 + 0.606 \cdot \text{CL}$	$1.212 + 0.606 \cdot \text{CL}$	$1.209 + 0.606 \cdot \text{CL}$
	t_F	33.275	$1.275 + 0.640 \cdot \text{CL}$	$1.279 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	t_{PLH}	15.732	$1.226 + 0.290 \cdot \text{CL}$	$1.224 + 0.290 \cdot \text{CL}$	$1.224 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.556	$1.448 + 0.322 \cdot \text{CL}$	$1.448 + 0.322 \cdot \text{CL}$	$1.445 + 0.322 \cdot \text{CL}$
TN to PAD	t_R	31.508	$1.210 + 0.606 \cdot \text{CL}$	$1.212 + 0.606 \cdot \text{CL}$	$1.209 + 0.606 \cdot \text{CL}$
	t_F	33.275	$1.275 + 0.640 \cdot \text{CL}$	$1.279 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	t_{PLH}	15.780	$1.271 + 0.290 \cdot \text{CL}$	$1.272 + 0.290 \cdot \text{CL}$	$1.275 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.679	$1.572 + 0.322 \cdot \text{CL}$	$1.569 + 0.322 \cdot \text{CL}$	$1.572 + 0.322 \cdot \text{CL}$
	t_{PLZ}	0.958	$0.958 + 0.000 \cdot \text{CL}$	$0.958 + 0.000 \cdot \text{CL}$	$0.958 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.662	$0.662 + 0.000 \cdot \text{CL}$	$0.662 + 0.000 \cdot \text{CL}$	$0.662 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	31.508	$1.210 + 0.606 \cdot \text{CL}$	$1.212 + 0.606 \cdot \text{CL}$	$1.209 + 0.606 \cdot \text{CL}$
	t_F	33.274	$1.277 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$	$1.276 + 0.640 \cdot \text{CL}$
	t_{PLH}	15.882	$1.375 + 0.290 \cdot \text{CL}$	$1.374 + 0.290 \cdot \text{CL}$	$1.377 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.782	$1.675 + 0.322 \cdot \text{CL}$	$1.674 + 0.322 \cdot \text{CL}$	$1.671 + 0.322 \cdot \text{CL}$
	t_{PLZ}	1.000	$1.000 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.705	$0.705 + 0.000 \cdot \text{CL}$	$0.705 + 0.000 \cdot \text{CL}$	$0.705 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	15.772	$0.624 + 0.303 \cdot \text{CL}$	$0.622 + 0.303 \cdot \text{CL}$	$0.625 + 0.303 \cdot \text{CL}$
	t_F	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.290	$1.036 + 0.145 \cdot \text{CL}$	$1.037 + 0.145 \cdot \text{CL}$	$1.035 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.194	$1.074 + 0.182 \cdot \text{CL}$	$1.076 + 0.182 \cdot \text{CL}$	$1.073 + 0.182 \cdot \text{CL}$
TN to PAD	t_R	15.772	$0.624 + 0.303 \cdot \text{CL}$	$0.622 + 0.303 \cdot \text{CL}$	$0.625 + 0.303 \cdot \text{CL}$
	t_F	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.337	$1.083 + 0.145 \cdot \text{CL}$	$1.083 + 0.145 \cdot \text{CL}$	$1.083 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.317	$1.197 + 0.182 \cdot \text{CL}$	$1.197 + 0.182 \cdot \text{CL}$	$1.200 + 0.182 \cdot \text{CL}$
	t_{PLZ}	0.808	$0.808 + 0.000 \cdot \text{CL}$	$0.808 + 0.000 \cdot \text{CL}$	$0.808 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.768	$0.768 + 0.000 \cdot \text{CL}$	$0.768 + 0.000 \cdot \text{CL}$	$0.768 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	15.772	$0.624 + 0.303 \cdot \text{CL}$	$0.622 + 0.303 \cdot \text{CL}$	$0.625 + 0.303 \cdot \text{CL}$
	t_F	18.210	$0.685 + 0.351 \cdot \text{CL}$	$0.688 + 0.350 \cdot \text{CL}$	$0.685 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.440	$1.186 + 0.145 \cdot \text{CL}$	$1.187 + 0.145 \cdot \text{CL}$	$1.185 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.420	$1.300 + 0.182 \cdot \text{CL}$	$1.302 + 0.182 \cdot \text{CL}$	$1.299 + 0.182 \cdot \text{CL}$
	t_{PLZ}	0.851	$0.851 + 0.000 \cdot \text{CL}$	$0.851 + 0.000 \cdot \text{CL}$	$0.851 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.810	$0.810 + 0.000 \cdot \text{CL}$	$0.810 + 0.000 \cdot \text{CL}$	$0.810 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POT4**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.917	$0.348 + 0.151 \cdot \text{CL}$	$0.342 + 0.151 \cdot \text{CL}$	$0.343 + 0.151 \cdot \text{CL}$
	t_F	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.724	$1.097 + 0.073 \cdot \text{CL}$	$1.097 + 0.073 \cdot \text{CL}$	$1.097 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.527	$0.969 + 0.091 \cdot \text{CL}$	$0.968 + 0.091 \cdot \text{CL}$	$0.969 + 0.091 \cdot \text{CL}$
TN to PAD	t_R	7.917	$0.348 + 0.151 \cdot \text{CL}$	$0.342 + 0.151 \cdot \text{CL}$	$0.343 + 0.151 \cdot \text{CL}$
	t_F	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.772	$1.144 + 0.073 \cdot \text{CL}$	$1.144 + 0.073 \cdot \text{CL}$	$1.145 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.649	$1.088 + 0.091 \cdot \text{CL}$	$1.089 + 0.091 \cdot \text{CL}$	$1.090 + 0.091 \cdot \text{CL}$
	t_{PLZ}	0.940	$0.940 + 0.000 \cdot \text{CL}$	$0.940 + 0.000 \cdot \text{CL}$	$0.940 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.978	$0.978 + 0.000 \cdot \text{CL}$	$0.978 + 0.000 \cdot \text{CL}$	$0.978 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	7.917	$0.348 + 0.151 \cdot \text{CL}$	$0.342 + 0.151 \cdot \text{CL}$	$0.343 + 0.151 \cdot \text{CL}$
	t_F	9.121	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$	$0.359 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.874	$1.247 + 0.073 \cdot \text{CL}$	$1.247 + 0.073 \cdot \text{CL}$	$1.247 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.752	$1.192 + 0.091 \cdot \text{CL}$	$1.192 + 0.091 \cdot \text{CL}$	$1.191 + 0.091 \cdot \text{CL}$
	t_{PLZ}	0.982	$0.982 + 0.000 \cdot \text{CL}$	$0.982 + 0.000 \cdot \text{CL}$	$0.982 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.020	$1.020 + 0.000 \cdot \text{CL}$	$1.020 + 0.000 \cdot \text{CL}$	$1.020 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POT6**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.317	$0.309 + 0.100 \cdot \text{CL}$	$0.280 + 0.101 \cdot \text{CL}$	$0.265 + 0.101 \cdot \text{CL}$
	t_F	6.097	$0.261 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	t_{PLH}	3.660	$1.240 + 0.048 \cdot \text{CL}$	$1.241 + 0.048 \cdot \text{CL}$	$1.242 + 0.048 \cdot \text{CL}$
	t_{PHL}	4.024	$0.989 + 0.061 \cdot \text{CL}$	$0.986 + 0.061 \cdot \text{CL}$	$0.985 + 0.061 \cdot \text{CL}$
TN to PAD	t_R	5.317	$0.309 + 0.100 \cdot \text{CL}$	$0.280 + 0.101 \cdot \text{CL}$	$0.265 + 0.101 \cdot \text{CL}$
	t_F	6.097	$0.260 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	t_{PLH}	3.708	$1.288 + 0.048 \cdot \text{CL}$	$1.289 + 0.048 \cdot \text{CL}$	$1.289 + 0.048 \cdot \text{CL}$
	t_{PHL}	4.142	$1.099 + 0.061 \cdot \text{CL}$	$1.101 + 0.061 \cdot \text{CL}$	$1.102 + 0.061 \cdot \text{CL}$
	t_{PLZ}	1.067	$1.067 + 0.000 \cdot \text{CL}$	$1.067 + 0.000 \cdot \text{CL}$	$1.067 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.188	$1.187 + 0.000 \cdot \text{CL}$	$1.188 + 0.000 \cdot \text{CL}$	$1.188 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	5.317	$0.309 + 0.100 \cdot \text{CL}$	$0.280 + 0.101 \cdot \text{CL}$	$0.265 + 0.101 \cdot \text{CL}$
	t_F	6.097	$0.260 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$	$0.256 + 0.117 \cdot \text{CL}$
	t_{PLH}	3.810	$1.391 + 0.048 \cdot \text{CL}$	$1.392 + 0.048 \cdot \text{CL}$	$1.392 + 0.048 \cdot \text{CL}$
	t_{PHL}	4.245	$1.203 + 0.061 \cdot \text{CL}$	$1.204 + 0.061 \cdot \text{CL}$	$1.205 + 0.061 \cdot \text{CL}$
	t_{PLZ}	1.111	$1.111 + 0.000 \cdot \text{CL}$	$1.111 + 0.000 \cdot \text{CL}$	$1.111 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.230	$1.230 + 0.000 \cdot \text{CL}$	$1.230 + 0.000 \cdot \text{CL}$	$1.230 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POT8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.049	$0.351 + 0.074 \cdot \text{CL}$	$0.303 + 0.075 \cdot \text{CL}$	$0.269 + 0.075 \cdot \text{CL}$
	t_F	4.592	$0.229 + 0.087 \cdot \text{CL}$	$0.216 + 0.088 \cdot \text{CL}$	$0.210 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.220	$1.401 + 0.036 \cdot \text{CL}$	$1.406 + 0.036 \cdot \text{CL}$	$1.407 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.313	$1.044 + 0.045 \cdot \text{CL}$	$1.038 + 0.045 \cdot \text{CL}$	$1.035 + 0.046 \cdot \text{CL}$
TN to PAD	t_R	4.049	$0.351 + 0.074 \cdot \text{CL}$	$0.303 + 0.075 \cdot \text{CL}$	$0.269 + 0.075 \cdot \text{CL}$
	t_F	4.591	$0.227 + 0.087 \cdot \text{CL}$	$0.214 + 0.088 \cdot \text{CL}$	$0.209 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.268	$1.448 + 0.036 \cdot \text{CL}$	$1.453 + 0.036 \cdot \text{CL}$	$1.454 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.424	$1.140 + 0.046 \cdot \text{CL}$	$1.143 + 0.046 \cdot \text{CL}$	$1.144 + 0.046 \cdot \text{CL}$
	t_{PLZ}	1.195	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.397	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.049	$0.351 + 0.074 \cdot \text{CL}$	$0.303 + 0.075 \cdot \text{CL}$	$0.269 + 0.075 \cdot \text{CL}$
	t_F	4.591	$0.227 + 0.087 \cdot \text{CL}$	$0.214 + 0.088 \cdot \text{CL}$	$0.209 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.371	$1.552 + 0.036 \cdot \text{CL}$	$1.556 + 0.036 \cdot \text{CL}$	$1.557 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.527	$1.243 + 0.046 \cdot \text{CL}$	$1.245 + 0.046 \cdot \text{CL}$	$1.247 + 0.046 \cdot \text{CL}$
	t_{PLZ}	1.238	$1.238 + 0.000 \cdot \text{CL}$	$1.238 + 0.000 \cdot \text{CL}$	$1.238 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.439	$1.439 + 0.000 \cdot \text{CL}$	$1.439 + 0.000 \cdot \text{CL}$	$1.439 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POT10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.219	$0.240 + 0.060 \cdot \text{CL}$	$0.210 + 0.060 \cdot \text{CL}$	$0.190 + 0.060 \cdot \text{CL}$
	t_F	3.669	$0.176 + 0.070 \cdot \text{CL}$	$0.166 + 0.070 \cdot \text{CL}$	$0.164 + 0.070 \cdot \text{CL}$
	t_{PLH}	2.653	$1.200 + 0.029 \cdot \text{CL}$	$1.201 + 0.029 \cdot \text{CL}$	$1.202 + 0.029 \cdot \text{CL}$
	t_{PHL}	2.807	$0.985 + 0.036 \cdot \text{CL}$	$0.984 + 0.036 \cdot \text{CL}$	$0.983 + 0.036 \cdot \text{CL}$
TN to PAD	t_R	3.218	$0.240 + 0.060 \cdot \text{CL}$	$0.209 + 0.060 \cdot \text{CL}$	$0.191 + 0.060 \cdot \text{CL}$
	t_F	3.668	$0.174 + 0.070 \cdot \text{CL}$	$0.166 + 0.070 \cdot \text{CL}$	$0.163 + 0.070 \cdot \text{CL}$
	t_{PLH}	2.704	$1.250 + 0.029 \cdot \text{CL}$	$1.253 + 0.029 \cdot \text{CL}$	$1.253 + 0.029 \cdot \text{CL}$
	t_{PHL}	2.925	$1.097 + 0.037 \cdot \text{CL}$	$1.099 + 0.037 \cdot \text{CL}$	$1.100 + 0.036 \cdot \text{CL}$
	t_{PLZ}	1.095	$1.095 + 0.000 \cdot \text{CL}$	$1.095 + 0.000 \cdot \text{CL}$	$1.095 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.144	$1.144 + 0.000 \cdot \text{CL}$	$1.143 + 0.000 \cdot \text{CL}$	$1.144 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	3.218	$0.240 + 0.060 \cdot \text{CL}$	$0.209 + 0.060 \cdot \text{CL}$	$0.191 + 0.060 \cdot \text{CL}$
	t_F	3.668	$0.174 + 0.070 \cdot \text{CL}$	$0.166 + 0.070 \cdot \text{CL}$	$0.163 + 0.070 \cdot \text{CL}$
	t_{PLH}	2.807	$1.354 + 0.029 \cdot \text{CL}$	$1.355 + 0.029 \cdot \text{CL}$	$1.356 + 0.029 \cdot \text{CL}$
	t_{PHL}	3.027	$1.201 + 0.037 \cdot \text{CL}$	$1.202 + 0.036 \cdot \text{CL}$	$1.203 + 0.036 \cdot \text{CL}$
	t_{PLZ}	1.138	$1.138 + 0.000 \cdot \text{CL}$	$1.138 + 0.000 \cdot \text{CL}$	$1.138 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.186	$1.185 + 0.000 \cdot \text{CL}$	$1.186 + 0.000 \cdot \text{CL}$	$1.186 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POT12**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	2.721	$0.269 + 0.049 \cdot \text{CL}$	$0.232 + 0.050 \cdot \text{CL}$	$0.204 + 0.050 \cdot \text{CL}$
	t_F	3.069	$0.169 + 0.058 \cdot \text{CL}$	$0.155 + 0.058 \cdot \text{CL}$	$0.148 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.497	$1.281 + 0.024 \cdot \text{CL}$	$1.286 + 0.024 \cdot \text{CL}$	$1.287 + 0.024 \cdot \text{CL}$
	t_{PHL}	2.531	$1.016 + 0.030 \cdot \text{CL}$	$1.014 + 0.030 \cdot \text{CL}$	$1.012 + 0.030 \cdot \text{CL}$
TN to PAD	t_R	2.721	$0.269 + 0.049 \cdot \text{CL}$	$0.232 + 0.050 \cdot \text{CL}$	$0.204 + 0.050 \cdot \text{CL}$
	t_F	3.069	$0.167 + 0.058 \cdot \text{CL}$	$0.154 + 0.058 \cdot \text{CL}$	$0.147 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.548	$1.332 + 0.024 \cdot \text{CL}$	$1.338 + 0.024 \cdot \text{CL}$	$1.339 + 0.024 \cdot \text{CL}$
	t_{PHL}	2.646	$1.122 + 0.030 \cdot \text{CL}$	$1.125 + 0.030 \cdot \text{CL}$	$1.126 + 0.030 \cdot \text{CL}$
	t_{PLZ}	1.160	$1.160 + 0.000 \cdot \text{CL}$	$1.160 + 0.000 \cdot \text{CL}$	$1.160 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.248	$1.248 + 0.000 \cdot \text{CL}$	$1.248 + 0.000 \cdot \text{CL}$	$1.248 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	2.721	$0.269 + 0.049 \cdot \text{CL}$	$0.232 + 0.050 \cdot \text{CL}$	$0.204 + 0.050 \cdot \text{CL}$
	t_F	3.069	$0.167 + 0.058 \cdot \text{CL}$	$0.154 + 0.058 \cdot \text{CL}$	$0.147 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.651	$1.435 + 0.024 \cdot \text{CL}$	$1.440 + 0.024 \cdot \text{CL}$	$1.442 + 0.024 \cdot \text{CL}$
	t_{PHL}	2.749	$1.225 + 0.030 \cdot \text{CL}$	$1.228 + 0.030 \cdot \text{CL}$	$1.229 + 0.030 \cdot \text{CL}$
	t_{PLZ}	1.203	$1.203 + 0.000 \cdot \text{CL}$	$1.203 + 0.000 \cdot \text{CL}$	$1.203 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.290	$1.290 + 0.000 \cdot \text{CL}$	$1.290 + 0.000 \cdot \text{CL}$	$1.290 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POT4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.136	$0.756 + 0.148 \cdot \text{CL}$	$0.663 + 0.149 \cdot \text{CL}$	$0.590 + 0.150 \cdot \text{CL}$
	t_F	9.485	$1.005 + 0.170 \cdot \text{CL}$	$0.893 + 0.172 \cdot \text{CL}$	$0.791 + 0.173 \cdot \text{CL}$
	t_{PLH}	5.943	$2.288 + 0.073 \cdot \text{CL}$	$2.310 + 0.073 \cdot \text{CL}$	$2.315 + 0.073 \cdot \text{CL}$
	t_{PHL}	7.625	$2.988 + 0.093 \cdot \text{CL}$	$3.050 + 0.092 \cdot \text{CL}$	$3.069 + 0.091 \cdot \text{CL}$
TN to PAD	t_R	8.136	$0.756 + 0.148 \cdot \text{CL}$	$0.663 + 0.149 \cdot \text{CL}$	$0.590 + 0.150 \cdot \text{CL}$
	t_F	9.485	$1.005 + 0.170 \cdot \text{CL}$	$0.893 + 0.172 \cdot \text{CL}$	$0.791 + 0.173 \cdot \text{CL}$
	t_{PLH}	5.992	$2.336 + 0.073 \cdot \text{CL}$	$2.358 + 0.073 \cdot \text{CL}$	$2.364 + 0.073 \cdot \text{CL}$
	t_{PHL}	7.747	$3.110 + 0.093 \cdot \text{CL}$	$3.171 + 0.092 \cdot \text{CL}$	$3.189 + 0.091 \cdot \text{CL}$
	t_{PLZ}	1.169	$1.169 + 0.000 \cdot \text{CL}$	$1.169 + 0.000 \cdot \text{CL}$	$1.169 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.521	$1.521 + 0.000 \cdot \text{CL}$	$1.521 + 0.000 \cdot \text{CL}$	$1.521 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	8.136	$0.756 + 0.148 \cdot \text{CL}$	$0.663 + 0.149 \cdot \text{CL}$	$0.590 + 0.150 \cdot \text{CL}$
	t_F	9.485	$1.005 + 0.170 \cdot \text{CL}$	$0.893 + 0.172 \cdot \text{CL}$	$0.791 + 0.173 \cdot \text{CL}$
	t_{PLH}	6.094	$2.439 + 0.073 \cdot \text{CL}$	$2.461 + 0.073 \cdot \text{CL}$	$2.466 + 0.073 \cdot \text{CL}$
	t_{PHL}	7.850	$3.213 + 0.093 \cdot \text{CL}$	$3.275 + 0.091 \cdot \text{CL}$	$3.291 + 0.091 \cdot \text{CL}$
	t_{PLZ}	1.212	$1.212 + 0.000 \cdot \text{CL}$	$1.212 + 0.000 \cdot \text{CL}$	$1.212 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.563	$1.563 + 0.000 \cdot \text{CL}$	$1.563 + 0.000 \cdot \text{CL}$	$1.563 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POT6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.049	$1.312 + 0.095 \cdot \text{CL}$	$1.251 + 0.096 \cdot \text{CL}$	$1.155 + 0.097 \cdot \text{CL}$
	t_F	6.982	$1.450 + 0.111 \cdot \text{CL}$	$1.413 + 0.111 \cdot \text{CL}$	$1.321 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.589	$2.881 + 0.054 \cdot \text{CL}$	$3.063 + 0.051 \cdot \text{CL}$	$3.165 + 0.049 \cdot \text{CL}$
	t_{PHL}	6.936	$3.524 + 0.068 \cdot \text{CL}$	$3.747 + 0.064 \cdot \text{CL}$	$3.882 + 0.062 \cdot \text{CL}$
TN to PAD	t_R	6.049	$1.312 + 0.095 \cdot \text{CL}$	$1.252 + 0.096 \cdot \text{CL}$	$1.155 + 0.097 \cdot \text{CL}$
	t_F	6.982	$1.451 + 0.111 \cdot \text{CL}$	$1.414 + 0.111 \cdot \text{CL}$	$1.322 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.638	$2.930 + 0.054 \cdot \text{CL}$	$3.112 + 0.051 \cdot \text{CL}$	$3.214 + 0.049 \cdot \text{CL}$
	t_{PHL}	7.057	$3.645 + 0.068 \cdot \text{CL}$	$3.868 + 0.064 \cdot \text{CL}$	$4.002 + 0.062 \cdot \text{CL}$
	t_{PLZ}	1.448	$1.448 + 0.000 \cdot \text{CL}$	$1.448 + 0.000 \cdot \text{CL}$	$1.448 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.401	$2.401 + 0.000 \cdot \text{CL}$	$2.401 + 0.000 \cdot \text{CL}$	$2.400 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	6.049	$1.312 + 0.095 \cdot \text{CL}$	$1.252 + 0.096 \cdot \text{CL}$	$1.155 + 0.097 \cdot \text{CL}$
	t_F	6.982	$1.451 + 0.111 \cdot \text{CL}$	$1.414 + 0.111 \cdot \text{CL}$	$1.322 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.740	$3.034 + 0.054 \cdot \text{CL}$	$3.215 + 0.051 \cdot \text{CL}$	$3.316 + 0.049 \cdot \text{CL}$
	t_{PHL}	7.160	$3.748 + 0.068 \cdot \text{CL}$	$3.971 + 0.064 \cdot \text{CL}$	$4.106 + 0.062 \cdot \text{CL}$
	t_{PLZ}	1.491	$1.491 + 0.000 \cdot \text{CL}$	$1.491 + 0.000 \cdot \text{CL}$	$1.491 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.443	$2.442 + 0.000 \cdot \text{CL}$	$2.443 + 0.000 \cdot \text{CL}$	$2.443 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POT8SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.157	$1.658 + 0.070 \cdot \text{CL}$	$1.671 + 0.070 \cdot \text{CL}$	$1.601 + 0.071 \cdot \text{CL}$
	t_F	5.712	$1.575 + 0.083 \cdot \text{CL}$	$1.605 + 0.082 \cdot \text{CL}$	$1.549 + 0.083 \cdot \text{CL}$
	t_{PLH}	5.234	$2.895 + 0.047 \cdot \text{CL}$	$3.178 + 0.041 \cdot \text{CL}$	$3.371 + 0.039 \cdot \text{CL}$
	t_{PHL}	6.241	$3.455 + 0.056 \cdot \text{CL}$	$3.724 + 0.050 \cdot \text{CL}$	$3.913 + 0.048 \cdot \text{CL}$
TN to PAD	t_R	5.158	$1.661 + 0.070 \cdot \text{CL}$	$1.673 + 0.070 \cdot \text{CL}$	$1.602 + 0.071 \cdot \text{CL}$
	t_F	5.723	$1.615 + 0.082 \cdot \text{CL}$	$1.625 + 0.082 \cdot \text{CL}$	$1.561 + 0.083 \cdot \text{CL}$
	t_{PLH}	5.282	$2.942 + 0.047 \cdot \text{CL}$	$3.226 + 0.041 \cdot \text{CL}$	$3.419 + 0.039 \cdot \text{CL}$
	t_{PHL}	6.351	$3.546 + 0.056 \cdot \text{CL}$	$3.827 + 0.050 \cdot \text{CL}$	$4.021 + 0.048 \cdot \text{CL}$
	t_{PLZ}	2.053	$2.053 + 0.000 \cdot \text{CL}$	$2.053 + 0.000 \cdot \text{CL}$	$2.053 + 0.000 \cdot \text{CL}$
	t_{PHZ}	3.255	$3.255 + 0.000 \cdot \text{CL}$	$3.255 + 0.000 \cdot \text{CL}$	$3.255 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	5.158	$1.661 + 0.070 \cdot \text{CL}$	$1.673 + 0.070 \cdot \text{CL}$	$1.602 + 0.071 \cdot \text{CL}$
	t_F	5.723	$1.615 + 0.082 \cdot \text{CL}$	$1.625 + 0.082 \cdot \text{CL}$	$1.561 + 0.083 \cdot \text{CL}$
	t_{PLH}	5.385	$3.046 + 0.047 \cdot \text{CL}$	$3.329 + 0.041 \cdot \text{CL}$	$3.522 + 0.039 \cdot \text{CL}$
	t_{PHL}	6.454	$3.649 + 0.056 \cdot \text{CL}$	$3.930 + 0.050 \cdot \text{CL}$	$4.125 + 0.048 \cdot \text{CL}$
	t_{PLZ}	2.096	$2.096 + 0.000 \cdot \text{CL}$	$2.096 + 0.000 \cdot \text{CL}$	$2.096 + 0.000 \cdot \text{CL}$
	t_{PHZ}	3.297	$3.297 + 0.000 \cdot \text{CL}$	$3.297 + 0.000 \cdot \text{CL}$	$3.297 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POT10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.208	$1.327 + 0.058 \cdot \text{CL}$	$1.366 + 0.057 \cdot \text{CL}$	$1.346 + 0.057 \cdot \text{CL}$
	t_F	4.733	$1.366 + 0.067 \cdot \text{CL}$	$1.422 + 0.066 \cdot \text{CL}$	$1.407 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.875	$2.962 + 0.038 \cdot \text{CL}$	$3.187 + 0.034 \cdot \text{CL}$	$3.355 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.800	$3.480 + 0.046 \cdot \text{CL}$	$3.724 + 0.042 \cdot \text{CL}$	$3.905 + 0.039 \cdot \text{CL}$
TN to PAD	t_R	4.208	$1.327 + 0.058 \cdot \text{CL}$	$1.366 + 0.057 \cdot \text{CL}$	$1.346 + 0.057 \cdot \text{CL}$
	t_F	4.736	$1.381 + 0.067 \cdot \text{CL}$	$1.430 + 0.066 \cdot \text{CL}$	$1.412 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.924	$3.012 + 0.038 \cdot \text{CL}$	$3.236 + 0.034 \cdot \text{CL}$	$3.404 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.917	$3.591 + 0.047 \cdot \text{CL}$	$3.839 + 0.042 \cdot \text{CL}$	$4.023 + 0.039 \cdot \text{CL}$
	t_{PLZ}	2.053	$2.053 + 0.000 \cdot \text{CL}$	$2.053 + 0.000 \cdot \text{CL}$	$2.053 + 0.000 \cdot \text{CL}$
	t_{PHZ}	3.255	$3.254 + 0.000 \cdot \text{CL}$	$3.255 + 0.000 \cdot \text{CL}$	$3.255 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.208	$1.327 + 0.058 \cdot \text{CL}$	$1.366 + 0.057 \cdot \text{CL}$	$1.346 + 0.057 \cdot \text{CL}$
	t_F	4.736	$1.381 + 0.067 \cdot \text{CL}$	$1.430 + 0.066 \cdot \text{CL}$	$1.412 + 0.066 \cdot \text{CL}$
	t_{PLH}	5.027	$3.115 + 0.038 \cdot \text{CL}$	$3.339 + 0.034 \cdot \text{CL}$	$3.507 + 0.032 \cdot \text{CL}$
	t_{PHL}	6.020	$3.694 + 0.047 \cdot \text{CL}$	$3.942 + 0.042 \cdot \text{CL}$	$4.126 + 0.039 \cdot \text{CL}$
	t_{PLZ}	2.095	$2.096 + 0.000 \cdot \text{CL}$	$2.095 + 0.000 \cdot \text{CL}$	$2.095 + 0.000 \cdot \text{CL}$
	t_{PHZ}	3.297	$3.297 + 0.000 \cdot \text{CL}$	$3.297 + 0.000 \cdot \text{CL}$	$3.297 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

POT12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.196	$1.635 + 0.051 \cdot \text{CL}$	$1.781 + 0.048 \cdot \text{CL}$	$1.853 + 0.047 \cdot \text{CL}$
	t_F	4.558	$1.568 + 0.060 \cdot \text{CL}$	$1.742 + 0.056 \cdot \text{CL}$	$1.824 + 0.055 \cdot \text{CL}$
	t_{PLH}	5.110	$3.154 + 0.039 \cdot \text{CL}$	$3.458 + 0.033 \cdot \text{CL}$	$3.713 + 0.030 \cdot \text{CL}$
	t_{PHL}	5.995	$3.754 + 0.045 \cdot \text{CL}$	$4.049 + 0.039 \cdot \text{CL}$	$4.298 + 0.036 \cdot \text{CL}$
TN to PAD	t_R	4.196	$1.637 + 0.051 \cdot \text{CL}$	$1.781 + 0.048 \cdot \text{CL}$	$1.854 + 0.047 \cdot \text{CL}$
	t_F	4.583	$1.655 + 0.059 \cdot \text{CL}$	$1.791 + 0.056 \cdot \text{CL}$	$1.853 + 0.055 \cdot \text{CL}$
	t_{PLH}	5.159	$3.203 + 0.039 \cdot \text{CL}$	$3.507 + 0.033 \cdot \text{CL}$	$3.763 + 0.030 \cdot \text{CL}$
	t_{PHL}	6.095	$3.815 + 0.046 \cdot \text{CL}$	$4.134 + 0.039 \cdot \text{CL}$	$4.395 + 0.036 \cdot \text{CL}$
	t_{PLZ}	2.421	$2.421 + 0.000 \cdot \text{CL}$	$2.421 + 0.000 \cdot \text{CL}$	$2.421 + 0.000 \cdot \text{CL}$
	t_{PHZ}	4.133	$4.133 + 0.000 \cdot \text{CL}$	$4.133 + 0.000 \cdot \text{CL}$	$4.133 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.196	$1.637 + 0.051 \cdot \text{CL}$	$1.782 + 0.048 \cdot \text{CL}$	$1.854 + 0.047 \cdot \text{CL}$
	t_F	4.583	$1.655 + 0.059 \cdot \text{CL}$	$1.790 + 0.056 \cdot \text{CL}$	$1.854 + 0.055 \cdot \text{CL}$
	t_{PLH}	5.261	$3.307 + 0.039 \cdot \text{CL}$	$3.610 + 0.033 \cdot \text{CL}$	$3.865 + 0.030 \cdot \text{CL}$
	t_{PHL}	6.197	$3.918 + 0.046 \cdot \text{CL}$	$4.236 + 0.039 \cdot \text{CL}$	$4.498 + 0.036 \cdot \text{CL}$
	t_{PLZ}	2.464	$2.464 + 0.000 \cdot \text{CL}$	$2.464 + 0.000 \cdot \text{CL}$	$2.464 + 0.000 \cdot \text{CL}$
	t_{PHZ}	4.175	$4.175 + 0.000 \cdot \text{CL}$	$4.175 + 0.000 \cdot \text{CL}$	$4.175 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**POT10SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.218	$2.940 + 0.066 \cdot \text{CL}$	$3.224 + 0.060 \cdot \text{CL}$	$3.412 + 0.057 \cdot \text{CL}$
	t_F	6.448	$2.737 + 0.074 \cdot \text{CL}$	$3.005 + 0.069 \cdot \text{CL}$	$3.175 + 0.067 \cdot \text{CL}$
	t_{PLH}	7.876	$4.948 + 0.059 \cdot \text{CL}$	$5.499 + 0.048 \cdot \text{CL}$	$5.966 + 0.041 \cdot \text{CL}$
	t_{PHL}	8.633	$5.417 + 0.064 \cdot \text{CL}$	$5.943 + 0.054 \cdot \text{CL}$	$6.389 + 0.048 \cdot \text{CL}$
TN to PAD	t_R	6.219	$2.942 + 0.066 \cdot \text{CL}$	$3.225 + 0.060 \cdot \text{CL}$	$3.414 + 0.057 \cdot \text{CL}$
	t_F	6.460	$2.782 + 0.074 \cdot \text{CL}$	$3.029 + 0.069 \cdot \text{CL}$	$3.189 + 0.066 \cdot \text{CL}$
	t_{PLH}	7.929	$5.001 + 0.059 \cdot \text{CL}$	$5.553 + 0.048 \cdot \text{CL}$	$6.019 + 0.041 \cdot \text{CL}$
	t_{PHL}	8.748	$5.516 + 0.065 \cdot \text{CL}$	$6.051 + 0.054 \cdot \text{CL}$	$6.505 + 0.048 \cdot \text{CL}$
	t_{PLZ}	2.532	$2.532 + 0.000 \cdot \text{CL}$	$2.532 + 0.000 \cdot \text{CL}$	$2.532 + 0.000 \cdot \text{CL}$
	t_{PHZ}	4.231	$4.230 + 0.000 \cdot \text{CL}$	$4.231 + 0.000 \cdot \text{CL}$	$4.231 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	6.219	$2.942 + 0.066 \cdot \text{CL}$	$3.226 + 0.060 \cdot \text{CL}$	$3.413 + 0.057 \cdot \text{CL}$
	t_F	6.460	$2.782 + 0.074 \cdot \text{CL}$	$3.029 + 0.069 \cdot \text{CL}$	$3.189 + 0.066 \cdot \text{CL}$
	t_{PLH}	8.031	$5.105 + 0.059 \cdot \text{CL}$	$5.655 + 0.048 \cdot \text{CL}$	$6.122 + 0.041 \cdot \text{CL}$
	t_{PHL}	8.850	$5.620 + 0.065 \cdot \text{CL}$	$6.155 + 0.054 \cdot \text{CL}$	$6.607 + 0.048 \cdot \text{CL}$
	t_{PLZ}	2.575	$2.575 + 0.000 \cdot \text{CL}$	$2.575 + 0.000 \cdot \text{CL}$	$2.575 + 0.000 \cdot \text{CL}$
	t_{PHZ}	4.273	$4.272 + 0.000 \cdot \text{CL}$	$4.273 + 0.000 \cdot \text{CL}$	$4.273 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **POT12SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.593	$3.555 + 0.061 \cdot \text{CL}$	$3.937 + 0.053 \cdot \text{CL}$	$4.211 + 0.049 \cdot \text{CL}$
	t_F	6.548	$3.126 + 0.068 \cdot \text{CL}$	$3.509 + 0.061 \cdot \text{CL}$	$3.773 + 0.057 \cdot \text{CL}$
	t_{PLH}	8.385	$5.248 + 0.063 \cdot \text{CL}$	$5.928 + 0.049 \cdot \text{CL}$	$6.505 + 0.041 \cdot \text{CL}$
	t_{PHL}	9.094	$5.840 + 0.065 \cdot \text{CL}$	$6.443 + 0.053 \cdot \text{CL}$	$6.966 + 0.046 \cdot \text{CL}$
TN to PAD	t_R	6.596	$3.560 + 0.061 \cdot \text{CL}$	$3.941 + 0.053 \cdot \text{CL}$	$4.213 + 0.049 \cdot \text{CL}$
	t_F	6.599	$3.299 + 0.066 \cdot \text{CL}$	$3.606 + 0.060 \cdot \text{CL}$	$3.832 + 0.057 \cdot \text{CL}$
	t_{PLH}	8.439	$5.302 + 0.063 \cdot \text{CL}$	$5.982 + 0.049 \cdot \text{CL}$	$6.558 + 0.041 \cdot \text{CL}$
	t_{PHL}	9.189	$5.880 + 0.066 \cdot \text{CL}$	$6.518 + 0.053 \cdot \text{CL}$	$7.056 + 0.046 \cdot \text{CL}$
	t_{PLZ}	2.900	$2.900 + 0.000 \cdot \text{CL}$	$2.900 + 0.000 \cdot \text{CL}$	$2.900 + 0.000 \cdot \text{CL}$
	t_{PHZ}	5.109	$5.108 + 0.000 \cdot \text{CL}$	$5.109 + 0.000 \cdot \text{CL}$	$5.109 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	6.596	$3.560 + 0.061 \cdot \text{CL}$	$3.941 + 0.053 \cdot \text{CL}$	$4.214 + 0.049 \cdot \text{CL}$
	t_F	6.599	$3.299 + 0.066 \cdot \text{CL}$	$3.606 + 0.060 \cdot \text{CL}$	$3.832 + 0.057 \cdot \text{CL}$
	t_{PLH}	8.541	$5.405 + 0.063 \cdot \text{CL}$	$6.085 + 0.049 \cdot \text{CL}$	$6.661 + 0.041 \cdot \text{CL}$
	t_{PHL}	9.291	$5.983 + 0.066 \cdot \text{CL}$	$6.620 + 0.053 \cdot \text{CL}$	$7.159 + 0.046 \cdot \text{CL}$
	t_{PLZ}	2.943	$2.943 + 0.000 \cdot \text{CL}$	$2.943 + 0.000 \cdot \text{CL}$	$2.943 + 0.000 \cdot \text{CL}$
	t_{PHZ}	5.151	$5.150 + 0.000 \cdot \text{CL}$	$5.150 + 0.000 \cdot \text{CL}$	$5.151 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	42.148	$1.623 + 0.811 \cdot \text{CL}$	$1.624 + 0.810 \cdot \text{CL}$	$1.621 + 0.811 \cdot \text{CL}$
	t_F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t_{PLH}	20.296	$1.549 + 0.375 \cdot \text{CL}$	$1.548 + 0.375 \cdot \text{CL}$	$1.548 + 0.375 \cdot \text{CL}$
	t_{PHL}	17.148	$1.586 + 0.311 \cdot \text{CL}$	$1.584 + 0.311 \cdot \text{CL}$	$1.581 + 0.311 \cdot \text{CL}$
TN to PAD	t_R	42.146	$1.623 + 0.810 \cdot \text{CL}$	$1.620 + 0.811 \cdot \text{CL}$	$1.623 + 0.810 \cdot \text{CL}$
	t_F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t_{PLH}	20.383	$1.633 + 0.375 \cdot \text{CL}$	$1.635 + 0.375 \cdot \text{CL}$	$1.635 + 0.375 \cdot \text{CL}$
	t_{PHL}	17.350	$1.785 + 0.311 \cdot \text{CL}$	$1.786 + 0.311 \cdot \text{CL}$	$1.783 + 0.311 \cdot \text{CL}$
	t_{PLZ}	1.249	$1.249 + 0.000 \cdot \text{CL}$	$1.249 + 0.000 \cdot \text{CL}$	$1.249 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.951	$0.951 + 0.000 \cdot \text{CL}$	$0.951 + 0.000 \cdot \text{CL}$	$0.951 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	42.146	$1.623 + 0.810 \cdot \text{CL}$	$1.620 + 0.811 \cdot \text{CL}$	$1.623 + 0.810 \cdot \text{CL}$
	t_F	33.014	$1.269 + 0.635 \cdot \text{CL}$	$1.270 + 0.635 \cdot \text{CL}$	$1.267 + 0.635 \cdot \text{CL}$
	t_{PLH}	20.485	$1.738 + 0.375 \cdot \text{CL}$	$1.737 + 0.375 \cdot \text{CL}$	$1.737 + 0.375 \cdot \text{CL}$
	t_{PHL}	17.453	$1.888 + 0.311 \cdot \text{CL}$	$1.889 + 0.311 \cdot \text{CL}$	$1.889 + 0.311 \cdot \text{CL}$
	t_{PLZ}	1.292	$1.292 + 0.000 \cdot \text{CL}$	$1.292 + 0.000 \cdot \text{CL}$	$1.292 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.995	$0.995 + 0.000 \cdot \text{CL}$	$0.995 + 0.000 \cdot \text{CL}$	$0.995 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	21.098	$0.836 + 0.405 \cdot \text{CL}$	$0.836 + 0.405 \cdot \text{CL}$	$0.833 + 0.405 \cdot \text{CL}$
	t_F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t_{PLH}	10.592	$1.218 + 0.187 \cdot \text{CL}$	$1.218 + 0.187 \cdot \text{CL}$	$1.218 + 0.187 \cdot \text{CL}$
	t_{PHL}	10.105	$1.209 + 0.178 \cdot \text{CL}$	$1.211 + 0.178 \cdot \text{CL}$	$1.208 + 0.178 \cdot \text{CL}$
TN to PAD	t_R	21.098	$0.836 + 0.405 \cdot \text{CL}$	$0.836 + 0.405 \cdot \text{CL}$	$0.833 + 0.405 \cdot \text{CL}$
	t_F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t_{PLH}	10.678	$1.304 + 0.187 \cdot \text{CL}$	$1.304 + 0.187 \cdot \text{CL}$	$1.304 + 0.187 \cdot \text{CL}$
	t_{PHL}	10.306	$1.411 + 0.178 \cdot \text{CL}$	$1.410 + 0.178 \cdot \text{CL}$	$1.410 + 0.178 \cdot \text{CL}$
	t_{PLZ}	1.104	$1.104 + 0.000 \cdot \text{CL}$	$1.104 + 0.000 \cdot \text{CL}$	$1.104 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.998	$0.998 + 0.000 \cdot \text{CL}$	$0.998 + 0.000 \cdot \text{CL}$	$0.998 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	21.098	$0.836 + 0.405 \cdot \text{CL}$	$0.836 + 0.405 \cdot \text{CL}$	$0.833 + 0.405 \cdot \text{CL}$
	t_F	18.188	$0.706 + 0.350 \cdot \text{CL}$	$0.702 + 0.350 \cdot \text{CL}$	$0.705 + 0.350 \cdot \text{CL}$
	t_{PLH}	10.781	$1.406 + 0.187 \cdot \text{CL}$	$1.407 + 0.187 \cdot \text{CL}$	$1.410 + 0.187 \cdot \text{CL}$
	t_{PHL}	10.409	$1.513 + 0.178 \cdot \text{CL}$	$1.513 + 0.178 \cdot \text{CL}$	$1.516 + 0.178 \cdot \text{CL}$
	t_{PLZ}	1.149	$1.149 + 0.000 \cdot \text{CL}$	$1.149 + 0.000 \cdot \text{CL}$	$1.149 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.042	$1.042 + 0.000 \cdot \text{CL}$	$1.042 + 0.000 \cdot \text{CL}$	$1.042 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOT4**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.563	$0.433 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$
	t_F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t_{PLH}	5.815	$1.128 + 0.094 \cdot \text{CL}$	$1.128 + 0.094 \cdot \text{CL}$	$1.128 + 0.094 \cdot \text{CL}$
	t_{PHL}	5.544	$1.096 + 0.089 \cdot \text{CL}$	$1.096 + 0.089 \cdot \text{CL}$	$1.096 + 0.089 \cdot \text{CL}$
TN to PAD	t_R	10.563	$0.433 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$
	t_F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t_{PLH}	5.901	$1.213 + 0.094 \cdot \text{CL}$	$1.214 + 0.094 \cdot \text{CL}$	$1.215 + 0.094 \cdot \text{CL}$
	t_{PHL}	5.746	$1.297 + 0.089 \cdot \text{CL}$	$1.297 + 0.089 \cdot \text{CL}$	$1.298 + 0.089 \cdot \text{CL}$
	t_{PLZ}	1.255	$1.256 + 0.000 \cdot \text{CL}$	$1.255 + 0.000 \cdot \text{CL}$	$1.255 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.091	$1.091 + 0.000 \cdot \text{CL}$	$1.091 + 0.000 \cdot \text{CL}$	$1.091 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	10.563	$0.433 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$	$0.431 + 0.203 \cdot \text{CL}$
	t_F	9.114	$0.371 + 0.175 \cdot \text{CL}$	$0.371 + 0.175 \cdot \text{CL}$	$0.372 + 0.175 \cdot \text{CL}$
	t_{PLH}	6.003	$1.316 + 0.094 \cdot \text{CL}$	$1.317 + 0.094 \cdot \text{CL}$	$1.318 + 0.094 \cdot \text{CL}$
	t_{PHL}	5.848	$1.400 + 0.089 \cdot \text{CL}$	$1.401 + 0.089 \cdot \text{CL}$	$1.401 + 0.089 \cdot \text{CL}$
	t_{PLZ}	1.300	$1.300 + 0.000 \cdot \text{CL}$	$1.300 + 0.000 \cdot \text{CL}$	$1.300 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.135	$1.135 + 0.000 \cdot \text{CL}$	$1.135 + 0.000 \cdot \text{CL}$	$1.135 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOT6**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.047	$0.293 + 0.135 \cdot \text{CL}$	$0.294 + 0.135 \cdot \text{CL}$	$0.293 + 0.135 \cdot \text{CL}$
	t_F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t_{PLH}	4.212	$1.087 + 0.063 \cdot \text{CL}$	$1.087 + 0.062 \cdot \text{CL}$	$1.087 + 0.062 \cdot \text{CL}$
	t_{PHL}	4.022	$1.057 + 0.059 \cdot \text{CL}$	$1.057 + 0.059 \cdot \text{CL}$	$1.057 + 0.059 \cdot \text{CL}$
TN to PAD	t_R	7.047	$0.293 + 0.135 \cdot \text{CL}$	$0.294 + 0.135 \cdot \text{CL}$	$0.293 + 0.135 \cdot \text{CL}$
	t_F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t_{PLH}	4.298	$1.172 + 0.063 \cdot \text{CL}$	$1.173 + 0.063 \cdot \text{CL}$	$1.173 + 0.063 \cdot \text{CL}$
	t_{PHL}	4.223	$1.256 + 0.059 \cdot \text{CL}$	$1.257 + 0.059 \cdot \text{CL}$	$1.257 + 0.059 \cdot \text{CL}$
	t_{PLZ}	1.246	$1.246 + 0.000 \cdot \text{CL}$	$1.246 + 0.000 \cdot \text{CL}$	$1.246 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.094	$1.094 + 0.000 \cdot \text{CL}$	$1.094 + 0.000 \cdot \text{CL}$	$1.094 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	7.047	$0.293 + 0.135 \cdot \text{CL}$	$0.294 + 0.135 \cdot \text{CL}$	$0.293 + 0.135 \cdot \text{CL}$
	t_F	6.082	$0.254 + 0.117 \cdot \text{CL}$	$0.254 + 0.117 \cdot \text{CL}$	$0.255 + 0.117 \cdot \text{CL}$
	t_{PLH}	4.400	$1.275 + 0.063 \cdot \text{CL}$	$1.276 + 0.062 \cdot \text{CL}$	$1.276 + 0.062 \cdot \text{CL}$
	t_{PHL}	4.325	$1.359 + 0.059 \cdot \text{CL}$	$1.360 + 0.059 \cdot \text{CL}$	$1.359 + 0.059 \cdot \text{CL}$
	t_{PLZ}	1.289	$1.290 + 0.000 \cdot \text{CL}$	$1.289 + 0.000 \cdot \text{CL}$	$1.289 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.137	$1.137 + 0.000 \cdot \text{CL}$	$1.137 + 0.000 \cdot \text{CL}$	$1.137 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOT8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.293	$0.229 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$	$0.227 + 0.101 \cdot \text{CL}$
	t_F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t_{PLH}	3.444	$1.100 + 0.047 \cdot \text{CL}$	$1.101 + 0.047 \cdot \text{CL}$	$1.101 + 0.047 \cdot \text{CL}$
	t_{PHL}	3.289	$1.064 + 0.044 \cdot \text{CL}$	$1.065 + 0.044 \cdot \text{CL}$	$1.065 + 0.044 \cdot \text{CL}$
TN to PAD	t_R	5.293	$0.229 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$	$0.227 + 0.101 \cdot \text{CL}$
	t_F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t_{PLH}	3.530	$1.185 + 0.047 \cdot \text{CL}$	$1.186 + 0.047 \cdot \text{CL}$	$1.186 + 0.047 \cdot \text{CL}$
	t_{PHL}	3.489	$1.263 + 0.045 \cdot \text{CL}$	$1.264 + 0.044 \cdot \text{CL}$	$1.265 + 0.044 \cdot \text{CL}$
	t_{PLZ}	1.322	$1.322 + 0.000 \cdot \text{CL}$	$1.322 + 0.000 \cdot \text{CL}$	$1.322 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.140	$1.140 + 0.000 \cdot \text{CL}$	$1.140 + 0.000 \cdot \text{CL}$	$1.140 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	5.293	$0.229 + 0.101 \cdot \text{CL}$	$0.228 + 0.101 \cdot \text{CL}$	$0.227 + 0.101 \cdot \text{CL}$
	t_F	4.572	$0.205 + 0.087 \cdot \text{CL}$	$0.202 + 0.087 \cdot \text{CL}$	$0.201 + 0.087 \cdot \text{CL}$
	t_{PLH}	3.632	$1.288 + 0.047 \cdot \text{CL}$	$1.288 + 0.047 \cdot \text{CL}$	$1.289 + 0.047 \cdot \text{CL}$
	t_{PHL}	3.591	$1.367 + 0.044 \cdot \text{CL}$	$1.367 + 0.044 \cdot \text{CL}$	$1.367 + 0.044 \cdot \text{CL}$
	t_{PLZ}	1.366	$1.366 + 0.000 \cdot \text{CL}$	$1.366 + 0.000 \cdot \text{CL}$	$1.366 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.184	$1.184 + 0.000 \cdot \text{CL}$	$1.184 + 0.000 \cdot \text{CL}$	$1.184 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOT10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.242	$0.194 + 0.081 \cdot \text{CL}$	$0.191 + 0.081 \cdot \text{CL}$	$0.190 + 0.081 \cdot \text{CL}$
	t_F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.175 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t_{PLH}	3.000	$1.124 + 0.038 \cdot \text{CL}$	$1.125 + 0.037 \cdot \text{CL}$	$1.125 + 0.037 \cdot \text{CL}$
	t_{PHL}	2.863	$1.083 + 0.036 \cdot \text{CL}$	$1.084 + 0.036 \cdot \text{CL}$	$1.084 + 0.036 \cdot \text{CL}$
TN to PAD	t_R	4.242	$0.194 + 0.081 \cdot \text{CL}$	$0.191 + 0.081 \cdot \text{CL}$	$0.190 + 0.081 \cdot \text{CL}$
	t_F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.175 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t_{PLH}	3.085	$1.208 + 0.038 \cdot \text{CL}$	$1.209 + 0.038 \cdot \text{CL}$	$1.210 + 0.038 \cdot \text{CL}$
	t_{PHL}	3.063	$1.282 + 0.036 \cdot \text{CL}$	$1.283 + 0.036 \cdot \text{CL}$	$1.284 + 0.036 \cdot \text{CL}$
	t_{PLZ}	1.397	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.186	$1.186 + 0.000 \cdot \text{CL}$	$1.186 + 0.000 \cdot \text{CL}$	$1.186 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.242	$0.195 + 0.081 \cdot \text{CL}$	$0.190 + 0.081 \cdot \text{CL}$	$0.190 + 0.081 \cdot \text{CL}$
	t_F	3.669	$0.183 + 0.070 \cdot \text{CL}$	$0.175 + 0.070 \cdot \text{CL}$	$0.172 + 0.070 \cdot \text{CL}$
	t_{PLH}	3.188	$1.311 + 0.038 \cdot \text{CL}$	$1.312 + 0.038 \cdot \text{CL}$	$1.313 + 0.037 \cdot \text{CL}$
	t_{PHL}	3.166	$1.386 + 0.036 \cdot \text{CL}$	$1.386 + 0.036 \cdot \text{CL}$	$1.387 + 0.036 \cdot \text{CL}$
	t_{PLZ}	1.441	$1.441 + 0.000 \cdot \text{CL}$	$1.441 + 0.000 \cdot \text{CL}$	$1.441 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.230	$1.230 + 0.000 \cdot \text{CL}$	$1.230 + 0.000 \cdot \text{CL}$	$1.230 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOT12**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.544	$0.178 + 0.067 \cdot \text{CL}$	$0.169 + 0.067 \cdot \text{CL}$	$0.166 + 0.068 \cdot \text{CL}$
	t_F	3.071	$0.176 + 0.058 \cdot \text{CL}$	$0.163 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.717	$1.154 + 0.031 \cdot \text{CL}$	$1.154 + 0.031 \cdot \text{CL}$	$1.154 + 0.031 \cdot \text{CL}$
	t_{PHL}	2.592	$1.108 + 0.030 \cdot \text{CL}$	$1.109 + 0.030 \cdot \text{CL}$	$1.109 + 0.030 \cdot \text{CL}$
TN to PAD	t_R	3.544	$0.178 + 0.067 \cdot \text{CL}$	$0.169 + 0.067 \cdot \text{CL}$	$0.166 + 0.068 \cdot \text{CL}$
	t_F	3.071	$0.176 + 0.058 \cdot \text{CL}$	$0.163 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.802	$1.236 + 0.031 \cdot \text{CL}$	$1.238 + 0.031 \cdot \text{CL}$	$1.239 + 0.031 \cdot \text{CL}$
	t_{PHL}	2.792	$1.307 + 0.030 \cdot \text{CL}$	$1.308 + 0.030 \cdot \text{CL}$	$1.309 + 0.030 \cdot \text{CL}$
	t_{PLZ}	1.471	$1.472 + 0.000 \cdot \text{CL}$	$1.471 + 0.000 \cdot \text{CL}$	$1.471 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.232	$1.232 + 0.000 \cdot \text{CL}$	$1.232 + 0.000 \cdot \text{CL}$	$1.232 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	3.544	$0.178 + 0.067 \cdot \text{CL}$	$0.169 + 0.067 \cdot \text{CL}$	$0.166 + 0.068 \cdot \text{CL}$
	t_F	3.071	$0.176 + 0.058 \cdot \text{CL}$	$0.163 + 0.058 \cdot \text{CL}$	$0.156 + 0.058 \cdot \text{CL}$
	t_{PLH}	2.904	$1.340 + 0.031 \cdot \text{CL}$	$1.341 + 0.031 \cdot \text{CL}$	$1.341 + 0.031 \cdot \text{CL}$
	t_{PHL}	2.894	$1.410 + 0.030 \cdot \text{CL}$	$1.411 + 0.030 \cdot \text{CL}$	$1.411 + 0.030 \cdot \text{CL}$
	t_{PLZ}	1.515	$1.516 + 0.000 \cdot \text{CL}$	$1.515 + 0.000 \cdot \text{CL}$	$1.515 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.276	$1.276 + 0.000 \cdot \text{CL}$	$1.276 + 0.000 \cdot \text{CL}$	$1.276 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOT4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.608	$0.513 + 0.202 \cdot \text{CL}$	$0.486 + 0.202 \cdot \text{CL}$	$0.477 + 0.203 \cdot \text{CL}$
	t_F	9.436	$0.949 + 0.170 \cdot \text{CL}$	$0.845 + 0.172 \cdot \text{CL}$	$0.747 + 0.173 \cdot \text{CL}$
	t_{PLH}	6.340	$1.651 + 0.094 \cdot \text{CL}$	$1.652 + 0.094 \cdot \text{CL}$	$1.653 + 0.094 \cdot \text{CL}$
	t_{PHL}	7.303	$2.794 + 0.090 \cdot \text{CL}$	$2.843 + 0.089 \cdot \text{CL}$	$2.855 + 0.089 \cdot \text{CL}$
TN to PAD	t_R	10.608	$0.513 + 0.202 \cdot \text{CL}$	$0.486 + 0.202 \cdot \text{CL}$	$0.477 + 0.203 \cdot \text{CL}$
	t_F	9.436	$0.949 + 0.170 \cdot \text{CL}$	$0.845 + 0.172 \cdot \text{CL}$	$0.747 + 0.173 \cdot \text{CL}$
	t_{PLH}	6.426	$1.736 + 0.094 \cdot \text{CL}$	$1.738 + 0.094 \cdot \text{CL}$	$1.739 + 0.094 \cdot \text{CL}$
	t_{PHL}	7.503	$2.993 + 0.090 \cdot \text{CL}$	$3.043 + 0.089 \cdot \text{CL}$	$3.057 + 0.089 \cdot \text{CL}$
	t_{PLZ}	1.417	$1.417 + 0.000 \cdot \text{CL}$	$1.417 + 0.000 \cdot \text{CL}$	$1.417 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.355	$1.355 + 0.000 \cdot \text{CL}$	$1.355 + 0.000 \cdot \text{CL}$	$1.355 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	10.608	$0.513 + 0.202 \cdot \text{CL}$	$0.486 + 0.202 \cdot \text{CL}$	$0.477 + 0.203 \cdot \text{CL}$
	t_F	9.436	$0.949 + 0.170 \cdot \text{CL}$	$0.845 + 0.172 \cdot \text{CL}$	$0.747 + 0.173 \cdot \text{CL}$
	t_{PLH}	6.529	$1.840 + 0.094 \cdot \text{CL}$	$1.841 + 0.094 \cdot \text{CL}$	$1.842 + 0.094 \cdot \text{CL}$
	t_{PHL}	7.606	$3.097 + 0.090 \cdot \text{CL}$	$3.146 + 0.089 \cdot \text{CL}$	$3.160 + 0.089 \cdot \text{CL}$
	t_{PLZ}	1.461	$1.461 + 0.000 \cdot \text{CL}$	$1.461 + 0.000 \cdot \text{CL}$	$1.460 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.399	$1.399 + 0.000 \cdot \text{CL}$	$1.399 + 0.000 \cdot \text{CL}$	$1.399 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PHOT6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.208	$0.611 + 0.132 \cdot \text{CL}$	$0.535 + 0.133 \cdot \text{CL}$	$0.477 + 0.134 \cdot \text{CL}$
	t_F	6.913	$1.361 + 0.111 \cdot \text{CL}$	$1.333 + 0.112 \cdot \text{CL}$	$1.254 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.098	$1.955 + 0.063 \cdot \text{CL}$	$1.969 + 0.063 \cdot \text{CL}$	$1.973 + 0.063 \cdot \text{CL}$
	t_{PHL}	6.581	$3.267 + 0.066 \cdot \text{CL}$	$3.476 + 0.062 \cdot \text{CL}$	$3.603 + 0.060 \cdot \text{CL}$
TN to PAD	t_R	7.208	$0.611 + 0.132 \cdot \text{CL}$	$0.535 + 0.133 \cdot \text{CL}$	$0.477 + 0.134 \cdot \text{CL}$
	t_F	6.914	$1.361 + 0.111 \cdot \text{CL}$	$1.334 + 0.112 \cdot \text{CL}$	$1.251 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.184	$2.040 + 0.063 \cdot \text{CL}$	$2.056 + 0.063 \cdot \text{CL}$	$2.059 + 0.063 \cdot \text{CL}$
	t_{PHL}	6.781	$3.468 + 0.066 \cdot \text{CL}$	$3.677 + 0.062 \cdot \text{CL}$	$3.803 + 0.060 \cdot \text{CL}$
	t_{PLZ}	1.724	$1.724 + 0.000 \cdot \text{CL}$	$1.724 + 0.000 \cdot \text{CL}$	$1.724 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.742	$1.742 + 0.000 \cdot \text{CL}$	$1.742 + 0.000 \cdot \text{CL}$	$1.742 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	7.208	$0.611 + 0.132 \cdot \text{CL}$	$0.535 + 0.133 \cdot \text{CL}$	$0.477 + 0.134 \cdot \text{CL}$
	t_F	6.914	$1.361 + 0.111 \cdot \text{CL}$	$1.334 + 0.112 \cdot \text{CL}$	$1.251 + 0.113 \cdot \text{CL}$
	t_{PLH}	5.287	$2.144 + 0.063 \cdot \text{CL}$	$2.158 + 0.063 \cdot \text{CL}$	$2.162 + 0.063 \cdot \text{CL}$
	t_{PHL}	6.884	$3.571 + 0.066 \cdot \text{CL}$	$3.779 + 0.062 \cdot \text{CL}$	$3.906 + 0.060 \cdot \text{CL}$
	t_{PLZ}	1.768	$1.768 + 0.000 \cdot \text{CL}$	$1.768 + 0.000 \cdot \text{CL}$	$1.768 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.786	$1.786 + 0.000 \cdot \text{CL}$	$1.786 + 0.000 \cdot \text{CL}$	$1.786 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOT8SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.686	$0.878 + 0.096 \cdot \text{CL}$	$0.794 + 0.098 \cdot \text{CL}$	$0.705 + 0.099 \cdot \text{CL}$
	t_F	6.065	$1.797 + 0.085 \cdot \text{CL}$	$1.914 + 0.083 \cdot \text{CL}$	$1.934 + 0.083 \cdot \text{CL}$
	t_{PLH}	4.736	$2.280 + 0.049 \cdot \text{CL}$	$2.363 + 0.047 \cdot \text{CL}$	$2.395 + 0.047 \cdot \text{CL}$
	t_{PHL}	6.607	$3.635 + 0.059 \cdot \text{CL}$	$3.984 + 0.052 \cdot \text{CL}$	$4.255 + 0.049 \cdot \text{CL}$
TN to PAD	t_R	5.687	$0.884 + 0.096 \cdot \text{CL}$	$0.796 + 0.098 \cdot \text{CL}$	$0.707 + 0.099 \cdot \text{CL}$
	t_F	6.065	$1.798 + 0.085 \cdot \text{CL}$	$1.915 + 0.083 \cdot \text{CL}$	$1.935 + 0.083 \cdot \text{CL}$
	t_{PLH}	4.821	$2.363 + 0.049 \cdot \text{CL}$	$2.447 + 0.047 \cdot \text{CL}$	$2.480 + 0.047 \cdot \text{CL}$
	t_{PHL}	6.807	$3.835 + 0.059 \cdot \text{CL}$	$4.184 + 0.052 \cdot \text{CL}$	$4.454 + 0.049 \cdot \text{CL}$
	t_{PLZ}	2.028	$2.029 + 0.000 \cdot \text{CL}$	$2.028 + 0.000 \cdot \text{CL}$	$2.028 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.128	$2.128 + 0.000 \cdot \text{CL}$	$2.128 + 0.000 \cdot \text{CL}$	$2.128 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	5.687	$0.884 + 0.096 \cdot \text{CL}$	$0.797 + 0.098 \cdot \text{CL}$	$0.707 + 0.099 \cdot \text{CL}$
	t_F	6.065	$1.798 + 0.085 \cdot \text{CL}$	$1.915 + 0.083 \cdot \text{CL}$	$1.935 + 0.083 \cdot \text{CL}$
	t_{PLH}	4.924	$2.466 + 0.049 \cdot \text{CL}$	$2.550 + 0.047 \cdot \text{CL}$	$2.582 + 0.047 \cdot \text{CL}$
	t_{PHL}	6.910	$3.939 + 0.059 \cdot \text{CL}$	$4.287 + 0.052 \cdot \text{CL}$	$4.557 + 0.049 \cdot \text{CL}$
	t_{PLZ}	2.072	$2.072 + 0.000 \cdot \text{CL}$	$2.072 + 0.000 \cdot \text{CL}$	$2.072 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.172	$2.172 + 0.000 \cdot \text{CL}$	$2.172 + 0.000 \cdot \text{CL}$	$2.172 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOT10SM**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.499	$0.605 + 0.078 \cdot \text{CL}$	$0.551 + 0.079 \cdot \text{CL}$	$0.500 + 0.080 \cdot \text{CL}$
	t_F	5.289	$1.831 + 0.069 \cdot \text{CL}$	$1.980 + 0.066 \cdot \text{CL}$	$2.030 + 0.066 \cdot \text{CL}$
	t_{PLH}	3.975	$2.054 + 0.038 \cdot \text{CL}$	$2.093 + 0.038 \cdot \text{CL}$	$2.105 + 0.037 \cdot \text{CL}$
	t_{PHL}	6.063	$3.455 + 0.052 \cdot \text{CL}$	$3.822 + 0.045 \cdot \text{CL}$	$4.115 + 0.041 \cdot \text{CL}$
TN to PAD	t_R	4.509	$0.633 + 0.078 \cdot \text{CL}$	$0.572 + 0.079 \cdot \text{CL}$	$0.511 + 0.080 \cdot \text{CL}$
	t_F	5.290	$1.834 + 0.069 \cdot \text{CL}$	$1.981 + 0.066 \cdot \text{CL}$	$2.031 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.038	$2.086 + 0.039 \cdot \text{CL}$	$2.142 + 0.038 \cdot \text{CL}$	$2.163 + 0.038 \cdot \text{CL}$
	t_{PHL}	6.264	$3.655 + 0.052 \cdot \text{CL}$	$4.022 + 0.045 \cdot \text{CL}$	$4.315 + 0.041 \cdot \text{CL}$
	t_{PLZ}	2.773	$2.774 + 0.000 \cdot \text{CL}$	$2.773 + 0.000 \cdot \text{CL}$	$2.773 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.109	$2.110 + 0.000 \cdot \text{CL}$	$2.109 + 0.000 \cdot \text{CL}$	$2.109 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.509	$0.633 + 0.078 \cdot \text{CL}$	$0.572 + 0.079 \cdot \text{CL}$	$0.511 + 0.080 \cdot \text{CL}$
	t_F	5.290	$1.834 + 0.069 \cdot \text{CL}$	$1.981 + 0.066 \cdot \text{CL}$	$2.031 + 0.066 \cdot \text{CL}$
	t_{PLH}	4.140	$2.189 + 0.039 \cdot \text{CL}$	$2.245 + 0.038 \cdot \text{CL}$	$2.266 + 0.038 \cdot \text{CL}$
	t_{PHL}	6.366	$3.758 + 0.052 \cdot \text{CL}$	$4.125 + 0.045 \cdot \text{CL}$	$4.418 + 0.041 \cdot \text{CL}$
	t_{PLZ}	2.817	$2.817 + 0.000 \cdot \text{CL}$	$2.817 + 0.000 \cdot \text{CL}$	$2.817 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.153	$2.153 + 0.000 \cdot \text{CL}$	$2.153 + 0.000 \cdot \text{CL}$	$2.153 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PHOT12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.998	$0.788 + 0.064 \cdot \text{CL}$	$0.767 + 0.065 \cdot \text{CL}$	$0.718 + 0.065 \cdot \text{CL}$
	t_F	4.487	$1.515 + 0.059 \cdot \text{CL}$	$1.662 + 0.057 \cdot \text{CL}$	$1.739 + 0.055 \cdot \text{CL}$
	t_{PLH}	3.937	$2.211 + 0.035 \cdot \text{CL}$	$2.314 + 0.032 \cdot \text{CL}$	$2.373 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.635	$3.418 + 0.044 \cdot \text{CL}$	$3.720 + 0.038 \cdot \text{CL}$	$3.971 + 0.035 \cdot \text{CL}$
TN to PAD	t_R	4.011	$0.830 + 0.064 \cdot \text{CL}$	$0.793 + 0.064 \cdot \text{CL}$	$0.733 + 0.065 \cdot \text{CL}$
	t_F	4.489	$1.518 + 0.059 \cdot \text{CL}$	$1.664 + 0.056 \cdot \text{CL}$	$1.740 + 0.055 \cdot \text{CL}$
	t_{PLH}	4.005	$2.253 + 0.035 \cdot \text{CL}$	$2.372 + 0.033 \cdot \text{CL}$	$2.438 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.835	$3.617 + 0.044 \cdot \text{CL}$	$3.920 + 0.038 \cdot \text{CL}$	$4.170 + 0.035 \cdot \text{CL}$
	t_{PLZ}	2.773	$2.774 + 0.000 \cdot \text{CL}$	$2.773 + 0.000 \cdot \text{CL}$	$2.773 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.495	$2.495 + 0.000 \cdot \text{CL}$	$2.495 + 0.000 \cdot \text{CL}$	$2.495 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.011	$0.830 + 0.064 \cdot \text{CL}$	$0.793 + 0.064 \cdot \text{CL}$	$0.733 + 0.065 \cdot \text{CL}$
	t_F	4.489	$1.518 + 0.059 \cdot \text{CL}$	$1.664 + 0.056 \cdot \text{CL}$	$1.740 + 0.055 \cdot \text{CL}$
	t_{PLH}	4.108	$2.356 + 0.035 \cdot \text{CL}$	$2.475 + 0.033 \cdot \text{CL}$	$2.542 + 0.032 \cdot \text{CL}$
	t_{PHL}	5.938	$3.720 + 0.044 \cdot \text{CL}$	$4.023 + 0.038 \cdot \text{CL}$	$4.274 + 0.035 \cdot \text{CL}$
	t_{PLZ}	2.817	$2.818 + 0.000 \cdot \text{CL}$	$2.817 + 0.000 \cdot \text{CL}$	$2.817 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.538	$2.539 + 0.000 \cdot \text{CL}$	$2.538 + 0.000 \cdot \text{CL}$	$2.538 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PHOT10SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.273	$1.448 + 0.077 \cdot \text{CL}$	$1.465 + 0.076 \cdot \text{CL}$	$1.414 + 0.077 \cdot \text{CL}$
	t_F	6.224	$2.449 + 0.075 \cdot \text{CL}$	$2.727 + 0.070 \cdot \text{CL}$	$2.915 + 0.067 \cdot \text{CL}$
	t_{PLH}	5.546	$3.210 + 0.047 \cdot \text{CL}$	$3.452 + 0.042 \cdot \text{CL}$	$3.622 + 0.040 \cdot \text{CL}$
	t_{PHL}	7.875	$4.751 + 0.062 \cdot \text{CL}$	$5.253 + 0.052 \cdot \text{CL}$	$5.682 + 0.047 \cdot \text{CL}$
TN to PAD	t_R	5.279	$1.469 + 0.076 \cdot \text{CL}$	$1.475 + 0.076 \cdot \text{CL}$	$1.420 + 0.077 \cdot \text{CL}$
	t_F	6.225	$2.451 + 0.075 \cdot \text{CL}$	$2.728 + 0.070 \cdot \text{CL}$	$2.916 + 0.067 \cdot \text{CL}$
	t_{PLH}	5.629	$3.285 + 0.047 \cdot \text{CL}$	$3.532 + 0.042 \cdot \text{CL}$	$3.704 + 0.040 \cdot \text{CL}$
	t_{PHL}	8.076	$4.952 + 0.062 \cdot \text{CL}$	$5.454 + 0.052 \cdot \text{CL}$	$5.882 + 0.047 \cdot \text{CL}$
	t_{PLZ}	2.857	$2.857 + 0.000 \cdot \text{CL}$	$2.857 + 0.000 \cdot \text{CL}$	$2.856 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.572	$2.572 + 0.000 \cdot \text{CL}$	$2.572 + 0.000 \cdot \text{CL}$	$2.571 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	5.279	$1.469 + 0.076 \cdot \text{CL}$	$1.475 + 0.076 \cdot \text{CL}$	$1.419 + 0.077 \cdot \text{CL}$
	t_F	6.225	$2.451 + 0.075 \cdot \text{CL}$	$2.728 + 0.070 \cdot \text{CL}$	$2.916 + 0.067 \cdot \text{CL}$
	t_{PLH}	5.732	$3.388 + 0.047 \cdot \text{CL}$	$3.635 + 0.042 \cdot \text{CL}$	$3.807 + 0.040 \cdot \text{CL}$
	t_{PHL}	8.178	$5.056 + 0.062 \cdot \text{CL}$	$5.557 + 0.052 \cdot \text{CL}$	$5.985 + 0.047 \cdot \text{CL}$
	t_{PLZ}	2.900	$2.901 + 0.000 \cdot \text{CL}$	$2.900 + 0.000 \cdot \text{CL}$	$2.900 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.615	$2.616 + 0.000 \cdot \text{CL}$	$2.615 + 0.000 \cdot \text{CL}$	$2.615 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ **PHOT12SH**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.965	$1.691 + 0.065 \cdot \text{CL}$	$1.798 + 0.063 \cdot \text{CL}$	$1.812 + 0.063 \cdot \text{CL}$
	t_F	6.246	$2.790 + 0.069 \cdot \text{CL}$	$3.146 + 0.062 \cdot \text{CL}$	$3.418 + 0.058 \cdot \text{CL}$
	t_{PLH}	5.693	$3.462 + 0.045 \cdot \text{CL}$	$3.765 + 0.039 \cdot \text{CL}$	$4.004 + 0.035 \cdot \text{CL}$
	t_{PHL}	8.197	$5.024 + 0.063 \cdot \text{CL}$	$5.605 + 0.052 \cdot \text{CL}$	$6.112 + 0.045 \cdot \text{CL}$
TN to PAD	t_R	4.983	$1.756 + 0.065 \cdot \text{CL}$	$1.833 + 0.063 \cdot \text{CL}$	$1.833 + 0.063 \cdot \text{CL}$
	t_F	6.248	$2.799 + 0.069 \cdot \text{CL}$	$3.151 + 0.062 \cdot \text{CL}$	$3.421 + 0.058 \cdot \text{CL}$
	t_{PLH}	5.769	$3.514 + 0.045 \cdot \text{CL}$	$3.832 + 0.039 \cdot \text{CL}$	$4.077 + 0.035 \cdot \text{CL}$
	t_{PHL}	8.397	$5.221 + 0.064 \cdot \text{CL}$	$5.805 + 0.052 \cdot \text{CL}$	$6.310 + 0.045 \cdot \text{CL}$
	t_{PLZ}	3.262	$3.262 + 0.000 \cdot \text{CL}$	$3.262 + 0.000 \cdot \text{CL}$	$3.261 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.957	$2.957 + 0.000 \cdot \text{CL}$	$2.957 + 0.000 \cdot \text{CL}$	$2.957 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.983	$1.756 + 0.065 \cdot \text{CL}$	$1.833 + 0.063 \cdot \text{CL}$	$1.833 + 0.063 \cdot \text{CL}$
	t_F	6.248	$2.799 + 0.069 \cdot \text{CL}$	$3.151 + 0.062 \cdot \text{CL}$	$3.421 + 0.058 \cdot \text{CL}$
	t_{PLH}	5.871	$3.618 + 0.045 \cdot \text{CL}$	$3.935 + 0.039 \cdot \text{CL}$	$4.180 + 0.035 \cdot \text{CL}$
	t_{PHL}	8.500	$5.325 + 0.063 \cdot \text{CL}$	$5.908 + 0.052 \cdot \text{CL}$	$6.413 + 0.045 \cdot \text{CL}$
	t_{PLZ}	3.306	$3.306 + 0.000 \cdot \text{CL}$	$3.306 + 0.000 \cdot \text{CL}$	$3.305 + 0.000 \cdot \text{CL}$
	t_{PHZ}	3.001	$3.001 + 0.000 \cdot \text{CL}$	$3.001 + 0.000 \cdot \text{CL}$	$3.001 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])

PTOT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	44.026	$2.843 + 0.824 \cdot \text{CL}$	$2.992 + 0.821 \cdot \text{CL}$	$3.100 + 0.819 \cdot \text{CL}$
	t_F	33.890	$2.747 + 0.623 \cdot \text{CL}$	$2.704 + 0.624 \cdot \text{CL}$	$2.677 + 0.624 \cdot \text{CL}$
	t_{PLH}	21.514	$2.654 + 0.377 \cdot \text{CL}$	$2.712 + 0.376 \cdot \text{CL}$	$2.748 + 0.376 \cdot \text{CL}$
	t_{PHL}	17.371	$1.761 + 0.312 \cdot \text{CL}$	$1.781 + 0.312 \cdot \text{CL}$	$1.799 + 0.312 \cdot \text{CL}$
TN to PAD	t_R	44.026	$2.843 + 0.824 \cdot \text{CL}$	$2.992 + 0.821 \cdot \text{CL}$	$3.100 + 0.819 \cdot \text{CL}$
	t_F	33.854	$2.744 + 0.622 \cdot \text{CL}$	$2.692 + 0.623 \cdot \text{CL}$	$2.662 + 0.624 \cdot \text{CL}$
	t_{PLH}	21.600	$2.740 + 0.377 \cdot \text{CL}$	$2.798 + 0.376 \cdot \text{CL}$	$2.834 + 0.376 \cdot \text{CL}$
	t_{PHL}	17.491	$1.944 + 0.311 \cdot \text{CL}$	$1.951 + 0.311 \cdot \text{CL}$	$1.963 + 0.311 \cdot \text{CL}$
	t_{PLZ}	1.075	$1.075 + 0.000 \cdot \text{CL}$	$1.075 + 0.000 \cdot \text{CL}$	$1.075 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.801	$1.800 + 0.000 \cdot \text{CL}$	$1.800 + 0.000 \cdot \text{CL}$	$1.801 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	44.026	$2.843 + 0.824 \cdot \text{CL}$	$2.992 + 0.821 \cdot \text{CL}$	$3.100 + 0.819 \cdot \text{CL}$
	t_F	33.854	$2.744 + 0.622 \cdot \text{CL}$	$2.692 + 0.623 \cdot \text{CL}$	$2.662 + 0.624 \cdot \text{CL}$
	t_{PLH}	21.702	$2.845 + 0.377 \cdot \text{CL}$	$2.900 + 0.376 \cdot \text{CL}$	$2.936 + 0.376 \cdot \text{CL}$
	t_{PHL}	17.593	$2.048 + 0.311 \cdot \text{CL}$	$2.051 + 0.311 \cdot \text{CL}$	$2.069 + 0.311 \cdot \text{CL}$
	t_{PLZ}	1.120	$1.120 + 0.000 \cdot \text{CL}$	$1.120 + 0.000 \cdot \text{CL}$	$1.120 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.844	$1.844 + 0.000 \cdot \text{CL}$	$1.844 + 0.000 \cdot \text{CL}$	$1.844 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

PTOT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	22.250	$1.485 + 0.415 \cdot \text{CL}$	$1.620 + 0.413 \cdot \text{CL}$	$1.725 + 0.411 \cdot \text{CL}$
	t_F	17.034	$1.379 + 0.313 \cdot \text{CL}$	$1.416 + 0.312 \cdot \text{CL}$	$1.419 + 0.312 \cdot \text{CL}$
	t_{PLH}	11.348	$1.857 + 0.190 \cdot \text{CL}$	$1.908 + 0.189 \cdot \text{CL}$	$1.947 + 0.188 \cdot \text{CL}$
	t_{PHL}	9.224	$1.372 + 0.157 \cdot \text{CL}$	$1.399 + 0.157 \cdot \text{CL}$	$1.422 + 0.156 \cdot \text{CL}$
TN to PAD	t_R	22.250	$1.485 + 0.415 \cdot \text{CL}$	$1.620 + 0.413 \cdot \text{CL}$	$1.725 + 0.411 \cdot \text{CL}$
	t_F	16.992	$1.367 + 0.312 \cdot \text{CL}$	$1.396 + 0.312 \cdot \text{CL}$	$1.402 + 0.312 \cdot \text{CL}$
	t_{PLH}	11.434	$1.944 + 0.190 \cdot \text{CL}$	$1.994 + 0.189 \cdot \text{CL}$	$2.030 + 0.188 \cdot \text{CL}$
	t_{PHL}	9.348	$1.545 + 0.156 \cdot \text{CL}$	$1.563 + 0.156 \cdot \text{CL}$	$1.579 + 0.155 \cdot \text{CL}$
	t_{PLZ}	1.201	$1.201 + 0.000 \cdot \text{CL}$	$1.201 + 0.000 \cdot \text{CL}$	$1.201 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.304	$2.304 + 0.000 \cdot \text{CL}$	$2.304 + 0.000 \cdot \text{CL}$	$2.303 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	22.250	$1.485 + 0.415 \cdot \text{CL}$	$1.620 + 0.413 \cdot \text{CL}$	$1.725 + 0.411 \cdot \text{CL}$
	t_F	16.992	$1.367 + 0.312 \cdot \text{CL}$	$1.396 + 0.312 \cdot \text{CL}$	$1.402 + 0.312 \cdot \text{CL}$
	t_{PLH}	11.537	$2.046 + 0.190 \cdot \text{CL}$	$2.097 + 0.189 \cdot \text{CL}$	$2.136 + 0.188 \cdot \text{CL}$
	t_{PHL}	9.450	$1.648 + 0.156 \cdot \text{CL}$	$1.664 + 0.156 \cdot \text{CL}$	$1.685 + 0.155 \cdot \text{CL}$
	t_{PLZ}	1.245	$1.245 + 0.000 \cdot \text{CL}$	$1.245 + 0.000 \cdot \text{CL}$	$1.245 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.347	$2.347 + 0.000 \cdot \text{CL}$	$2.347 + 0.000 \cdot \text{CL}$	$2.347 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load[pf])**PTOT3**

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	14.950	$1.003 + 0.279 \cdot \text{CL}$	$1.124 + 0.277 \cdot \text{CL}$	$1.223 + 0.275 \cdot \text{CL}$
	t_F	11.398	$0.929 + 0.209 \cdot \text{CL}$	$0.952 + 0.209 \cdot \text{CL}$	$0.976 + 0.209 \cdot \text{CL}$
	t_{PLH}	7.984	$1.628 + 0.127 \cdot \text{CL}$	$1.665 + 0.126 \cdot \text{CL}$	$1.702 + 0.126 \cdot \text{CL}$
	t_{PHL}	6.545	$1.288 + 0.105 \cdot \text{CL}$	$1.308 + 0.105 \cdot \text{CL}$	$1.327 + 0.104 \cdot \text{CL}$
TN to PAD	t_R	14.950	$1.005 + 0.279 \cdot \text{CL}$	$1.122 + 0.277 \cdot \text{CL}$	$1.227 + 0.275 \cdot \text{CL}$
	t_F	11.350	$0.906 + 0.209 \cdot \text{CL}$	$0.926 + 0.208 \cdot \text{CL}$	$0.947 + 0.208 \cdot \text{CL}$
	t_{PLH}	8.070	$1.714 + 0.127 \cdot \text{CL}$	$1.751 + 0.126 \cdot \text{CL}$	$1.789 + 0.126 \cdot \text{CL}$
	t_{PHL}	6.666	$1.450 + 0.104 \cdot \text{CL}$	$1.462 + 0.104 \cdot \text{CL}$	$1.481 + 0.104 \cdot \text{CL}$
	t_{PLZ}	1.323	$1.323 + 0.000 \cdot \text{CL}$	$1.323 + 0.000 \cdot \text{CL}$	$1.323 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.808	$2.809 + 0.000 \cdot \text{CL}$	$2.808 + 0.000 \cdot \text{CL}$	$2.808 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	14.950	$1.005 + 0.279 \cdot \text{CL}$	$1.122 + 0.277 \cdot \text{CL}$	$1.227 + 0.275 \cdot \text{CL}$
	t_F	11.350	$0.906 + 0.209 \cdot \text{CL}$	$0.926 + 0.208 \cdot \text{CL}$	$0.947 + 0.208 \cdot \text{CL}$
	t_{PLH}	8.173	$1.817 + 0.127 \cdot \text{CL}$	$1.855 + 0.126 \cdot \text{CL}$	$1.891 + 0.126 \cdot \text{CL}$
	t_{PHL}	6.768	$1.553 + 0.104 \cdot \text{CL}$	$1.565 + 0.104 \cdot \text{CL}$	$1.584 + 0.104 \cdot \text{CL}$
	t_{PLZ}	1.367	$1.367 + 0.000 \cdot \text{CL}$	$1.367 + 0.000 \cdot \text{CL}$	$1.367 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.852	$2.853 + 0.000 \cdot \text{CL}$	$2.852 + 0.000 \cdot \text{CL}$	$2.851 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

BI-DIRECTIONAL BUFFERS


Cell List

Cell Name	Function Description
PBaDyz	2.5V Open-Drain Bi-Directional Buffers
PBaUDyz	2.5V Open-Drain Bi-Directional Buffers with Pull-Up
PHBaDyz	3.3V Interface Open-Drain Bi-Directional Buffers with Pull-Down
PHBaUDyz	3.3V Interface Open-Drain Bi-Directional Buffers with Pull-Up
PTBaDy	5V - Tolerant Open-Drain Bi-Directional Buffers
PTBaUDy	5V - Tolerant Open-Drain Bi-Directional Buffers with Pull-Up
PBaTyz	2.5V Tri-State Bi-Directional Buffers
PBaDTyz	2.5V Tri-State Bi-Directional Buffers with Pull-Down
PBaUTyz	2.5V Tri-State Bi-Directional Buffers with Pull-Up
PHBaTyz	3.3V Interface Tri-State Bi-Directional Buffers
PHBaDTyz	3.3V Interface Tri-State Bi-Directional Buffers with Pull-Down
PHBaUTyz	3.3V Interface Tri-State Bi-Directional Buffers with Pull-Up
PTBaTy	5V - Tolerant Tri-State Bi-Directional Buffers
PTBaDTy	5V - Tolerant Tri-State Bi-Directional Buffers with Pull-Down
PTBaUTy	5V - Tolerant Tri-State Bi-Directional Buffers with Pull-Up

BI-DIRECTIONAL BUFFERS


Open Drain Bi-Directional Buffers

PvBaDyz




Tri-State Bi-Directional Buffers


PvBaTyz




PvBaUDyz



PvBaDTyz



PvBaUTyz




INPUT CLOCK DRIVERS

Cell List

Cell Name	Function Description
PSCKDC(2/4/6/8)	2.5V LVCMOS Level Input Clock Driver
PSCKDCD(2/4/6/8)	2.5V LVCMOS Level Input Clock Driver with Pull-Down
PSCKDCU(2/4/6/8)	2.5V LVCMOS Level Input Clock Driver with Pull-Up
PSCKDS(2/4/6/8)	2.5V LVCMOS-Schmitt Trigger Level Input Clock Driver
PSCKDSD(2/4/6/8)	2.5V LVCMOS-Schmitt Trigger Level Input Clock Driver with Pull-Down
PSCKDSU(2/4/6/8)	2.5V LVCMOS-Schmitt Trigger Level Input Clock Driver with Pull-Up

Logic Symbol



Cell Availability

Only 2.5V
PSCKDC/PSCKDCD/PSCKDCU (2/4/6/8)

Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PSCKDC/PSCKDCD/PSCKDCU (2/4/6/8)	4.193

PSCKDCby

LVC MOS Level Input Clock Drivers

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00ns$, SL: Standard Load)

PSCKDC2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.175	$0.169 + 0.003*SL$	$0.124 + 0.003*SL$	$0.100 + 0.003*SL$
	t_F	0.142	$0.134 + 0.004*SL$	$0.101 + 0.004*SL$	$0.086 + 0.004*SL$
	t_{PLH}	0.813	$0.811 + 0.001*SL$	$0.807 + 0.001*SL$	$0.806 + 0.001*SL$
	t_{PHL}	0.795	$0.791 + 0.002*SL$	$0.788 + 0.002*SL$	$0.789 + 0.002*SL$

*Group1 : $SL < 482$, *Group2 : $482 \leq SL \leq 722$, *Group3 : $722 < SL$

PSCKDC4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.235	$0.232 + 0.002*SL$	$0.175 + 0.002*SL$	$0.136 + 0.002*SL$
	t_F	0.182	$0.178 + 0.002*SL$	$0.126 + 0.002*SL$	$0.099 + 0.002*SL$
	t_{PLH}	1.051	$1.049 + 0.001*SL$	$1.050 + 0.001*SL$	$1.048 + 0.001*SL$
	t_{PHL}	1.036	$1.034 + 0.001*SL$	$1.031 + 0.001*SL$	$1.028 + 0.001*SL$

*Group1 : $SL < 962$, *Group2 : $962 \leq SL \leq 1443$, *Group3 : $1443 < SL$

PSCKDC6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.291	$0.289 + 0.001*SL$	$0.226 + 0.001*SL$	$0.181 + 0.001*SL$
	t_F	0.224	$0.222 + 0.001*SL$	$0.160 + 0.001*SL$	$0.122 + 0.001*SL$
	t_{PLH}	1.246	$1.245 + 0.000*SL$	$1.254 + 0.000*SL$	$1.251 + 0.000*SL$
	t_{PHL}	1.237	$1.235 + 0.001*SL$	$1.232 + 0.001*SL$	$1.227 + 0.001*SL$

*Group1 : $SL < 1443$, *Group2 : $1443 \leq SL \leq 2165$, *Group3 : $2165 < SL$

PSCKDC8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.341	$0.340 + 0.001*SL$	$0.273 + 0.001*SL$	$0.224 + 0.001*SL$
	t_F	0.263	$0.262 + 0.001*SL$	$0.196 + 0.001*SL$	$0.149 + 0.001*SL$
	t_{PLH}	1.415	$1.414 + 0.000*SL$	$1.431 + 0.000*SL$	$1.429 + 0.000*SL$
	t_{PHL}	1.410	$1.409 + 0.000*SL$	$1.407 + 0.000*SL$	$1.402 + 0.000*SL$

*Group1 : $SL < 1923$, *Group2 : $1923 \leq SL \leq 2887$, *Group3 : $2887 < SL$

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PSCKDCD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.172	$0.165 + 0.003 \cdot \text{SL}$	$0.122 + 0.003 \cdot \text{SL}$	$0.099 + 0.003 \cdot \text{SL}$
	t_F	0.146	$0.139 + 0.004 \cdot \text{SL}$	$0.104 + 0.004 \cdot \text{SL}$	$0.087 + 0.004 \cdot \text{SL}$
	t_{PLH}	0.903	$0.900 + 0.001 \cdot \text{SL}$	$0.897 + 0.001 \cdot \text{SL}$	$0.896 + 0.001 \cdot \text{SL}$
	t_{PHL}	0.796	$0.792 + 0.002 \cdot \text{SL}$	$0.789 + 0.002 \cdot \text{SL}$	$0.790 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 482$, *Group2 : $482 \leq \text{SL} \leq 722$, *Group3 : $722 < \text{SL}$
PSCKDCD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.231	$0.228 + 0.002 \cdot \text{SL}$	$0.171 + 0.002 \cdot \text{SL}$	$0.135 + 0.002 \cdot \text{SL}$
	t_F	0.189	$0.185 + 0.002 \cdot \text{SL}$	$0.130 + 0.002 \cdot \text{SL}$	$0.102 + 0.002 \cdot \text{SL}$
	t_{PLH}	1.137	$1.135 + 0.001 \cdot \text{SL}$	$1.136 + 0.001 \cdot \text{SL}$	$1.133 + 0.001 \cdot \text{SL}$
	t_{PHL}	1.048	$1.046 + 0.001 \cdot \text{SL}$	$1.042 + 0.001 \cdot \text{SL}$	$1.039 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 962$, *Group2 : $962 \leq \text{SL} \leq 1443$, *Group3 : $1443 < \text{SL}$
PSCKDCD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.287	$0.285 + 0.001 \cdot \text{SL}$	$0.222 + 0.001 \cdot \text{SL}$	$0.178 + 0.001 \cdot \text{SL}$
	t_F	0.234	$0.231 + 0.001 \cdot \text{SL}$	$0.167 + 0.001 \cdot \text{SL}$	$0.127 + 0.001 \cdot \text{SL}$
	t_{PLH}	1.330	$1.329 + 0.000 \cdot \text{SL}$	$1.338 + 0.000 \cdot \text{SL}$	$1.334 + 0.000 \cdot \text{SL}$
	t_{PHL}	1.256	$1.255 + 0.001 \cdot \text{SL}$	$1.252 + 0.001 \cdot \text{SL}$	$1.246 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 1443$, *Group2 : $1443 \leq \text{SL} \leq 2165$, *Group3 : $2165 < \text{SL}$
PSCKDCD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.337	$0.335 + 0.001 \cdot \text{SL}$	$0.270 + 0.001 \cdot \text{SL}$	$0.222 + 0.001 \cdot \text{SL}$
	t_F	0.274	$0.273 + 0.001 \cdot \text{SL}$	$0.205 + 0.001 \cdot \text{SL}$	$0.156 + 0.001 \cdot \text{SL}$
	t_{PLH}	1.497	$1.496 + 0.000 \cdot \text{SL}$	$1.513 + 0.000 \cdot \text{SL}$	$1.511 + 0.000 \cdot \text{SL}$
	t_{PHL}	1.436	$1.435 + 0.000 \cdot \text{SL}$	$1.434 + 0.000 \cdot \text{SL}$	$1.427 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 1923$, *Group2 : $1923 \leq \text{SL} \leq 2887$, *Group3 : $2887 < \text{SL}$

PSCKDCby

LVC MOS Level Input Clock Drivers

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00ns$, SL: Standard Load)

PSCKDCU2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.181	$0.174 + 0.003*SL$	$0.128 + 0.003*SL$	$0.102 + 0.003*SL$
	t_F	0.140	$0.133 + 0.004*SL$	$0.100 + 0.004*SL$	$0.086 + 0.004*SL$
	t_{PLH}	0.810	$0.807 + 0.001*SL$	$0.804 + 0.001*SL$	$0.802 + 0.001*SL$
	t_{PHL}	0.879	$0.875 + 0.002*SL$	$0.873 + 0.002*SL$	$0.873 + 0.002*SL$

*Group1 : $SL < 482$, *Group2 : $482 \leq SL \leq 722$, *Group3 : $722 < SL$

PSCKDCU4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.243	$0.240 + 0.002*SL$	$0.181 + 0.002*SL$	$0.141 + 0.002*SL$
	t_F	0.179	$0.175 + 0.002*SL$	$0.124 + 0.002*SL$	$0.098 + 0.002*SL$
	t_{PLH}	1.055	$1.053 + 0.001*SL$	$1.054 + 0.001*SL$	$1.052 + 0.001*SL$
	t_{PHL}	1.117	$1.115 + 0.001*SL$	$1.112 + 0.001*SL$	$1.108 + 0.001*SL$

*Group1 : $SL < 962$, *Group2 : $962 \leq SL \leq 1443$, *Group3 : $1443 < SL$

PSCKDCU6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.301	$0.299 + 0.001*SL$	$0.233 + 0.001*SL$	$0.187 + 0.001*SL$
	t_F	0.221	$0.219 + 0.001*SL$	$0.158 + 0.001*SL$	$0.121 + 0.001*SL$
	t_{PLH}	1.255	$1.254 + 0.000*SL$	$1.264 + 0.000*SL$	$1.261 + 0.000*SL$
	t_{PHL}	1.315	$1.314 + 0.001*SL$	$1.311 + 0.001*SL$	$1.306 + 0.001*SL$


*Group1 : $SL < 1443$, *Group2 : $1443 \leq SL \leq 2165$, *Group3 : $2165 < SL$

PSCKDCU8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.352	$0.350 + 0.001*SL$	$0.282 + 0.001*SL$	$0.231 + 0.001*SL$
	t_F	0.260	$0.258 + 0.001*SL$	$0.194 + 0.001*SL$	$0.148 + 0.001*SL$
	t_{PLH}	1.428	$1.427 + 0.000*SL$	$1.446 + 0.000*SL$	$1.444 + 0.000*SL$
	t_{PHL}	1.487	$1.486 + 0.000*SL$	$1.484 + 0.000*SL$	$1.479 + 0.000*SL$

*Group1 : $SL < 1923$, *Group2 : $1923 \leq SL \leq 2887$, *Group3 : $2887 < SL$

Logic Symbol



Cell Availability

Only 2.5V
PSCKDS/PSCKDSD/PSCKDSU(2/4/6/8)

Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

	PI
PSCKDS/PSCKDSD/PSCKDSU (2/4/6/8)	4.193

PSCKDSby

LVCMOS Schmitt Trigger Level Input Clock Drivers

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00ns$, SL: Standard Load)

PSCKDS2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.201	$0.195 + 0.003*SL$	$0.157 + 0.003*SL$	$0.130 + 0.003*SL$
	t_F	0.194	$0.187 + 0.004*SL$	$0.149 + 0.004*SL$	$0.124 + 0.004*SL$
	t_{PLH}	1.142	$1.139 + 0.001*SL$	$1.142 + 0.001*SL$	$1.142 + 0.001*SL$
	t_{PHL}	1.195	$1.191 + 0.002*SL$	$1.197 + 0.002*SL$	$1.196 + 0.002*SL$

*Group1 : $SL < 482$, *Group2 : $482 \leq SL \leq 722$, *Group3 : $722 < SL$

PSCKDS4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.270	$0.267 + 0.002*SL$	$0.219 + 0.002*SL$	$0.182 + 0.002*SL$
	t_F	0.264	$0.260 + 0.002*SL$	$0.215 + 0.002*SL$	$0.178 + 0.002*SL$
	t_{PLH}	1.401	$1.399 + 0.001*SL$	$1.415 + 0.001*SL$	$1.418 + 0.001*SL$
	t_{PHL}	1.484	$1.482 + 0.001*SL$	$1.500 + 0.001*SL$	$1.501 + 0.001*SL$

*Group1 : $SL < 962$, *Group2 : $962 \leq SL \leq 1443$, *Group3 : $1443 < SL$

PSCKDS6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.331	$0.329 + 0.001*SL$	$0.278 + 0.001*SL$	$0.239 + 0.001*SL$
	t_F	0.356	$0.354 + 0.001*SL$	$0.307 + 0.001*SL$	$0.261 + 0.001*SL$
	t_{PLH}	1.610	$1.609 + 0.001*SL$	$1.639 + 0.000*SL$	$1.645 + 0.000*SL$
	t_{PHL}	1.743	$1.742 + 0.001*SL$	$1.775 + 0.001*SL$	$1.783 + 0.001*SL$

*Group1 : $SL < 1443$, *Group2 : $1443 \leq SL \leq 2165$, *Group3 : $2165 < SL$

PSCKDS8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.384	$0.383 + 0.001*SL$	$0.334 + 0.001*SL$	$0.293 + 0.001*SL$
	t_F	0.456	$0.454 + 0.001*SL$	$0.406 + 0.001*SL$	$0.359 + 0.001*SL$
	t_{PLH}	1.788	$1.788 + 0.000*SL$	$1.829 + 0.000*SL$	$1.841 + 0.000*SL$
	t_{PHL}	1.990	$1.989 + 0.001*SL$	$2.039 + 0.000*SL$	$2.055 + 0.000*SL$

*Group1 : $SL < 1923$, *Group2 : $1923 \leq SL \leq 2887$, *Group3 : $2887 < SL$

LVC MOS Schmitt Trigger Level Input Clock Drivers
Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PSCKDSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.199	$0.193 + 0.003 \cdot \text{SL}$	$0.155 + 0.003 \cdot \text{SL}$	$0.129 + 0.003 \cdot \text{SL}$
	t_F	0.198	$0.191 + 0.004 \cdot \text{SL}$	$0.153 + 0.004 \cdot \text{SL}$	$0.127 + 0.004 \cdot \text{SL}$
	t_{PLH}	1.208	$1.205 + 0.001 \cdot \text{SL}$	$1.208 + 0.001 \cdot \text{SL}$	$1.209 + 0.001 \cdot \text{SL}$
	t_{PHL}	1.243	$1.239 + 0.002 \cdot \text{SL}$	$1.246 + 0.002 \cdot \text{SL}$	$1.245 + 0.002 \cdot \text{SL}$

*Group1 : $\text{SL} < 482$, *Group2 : $482 \leq \text{SL} \leq 722$, *Group3 : $722 < \text{SL}$
PSCKDSD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.267	$0.264 + 0.002 \cdot \text{SL}$	$0.217 + 0.002 \cdot \text{SL}$	$0.181 + 0.002 \cdot \text{SL}$
	t_F	0.269	$0.266 + 0.002 \cdot \text{SL}$	$0.220 + 0.002 \cdot \text{SL}$	$0.182 + 0.002 \cdot \text{SL}$
	t_{PLH}	1.464	$1.463 + 0.001 \cdot \text{SL}$	$1.478 + 0.001 \cdot \text{SL}$	$1.481 + 0.001 \cdot \text{SL}$
	t_{PHL}	1.547	$1.545 + 0.001 \cdot \text{SL}$	$1.562 + 0.001 \cdot \text{SL}$	$1.564 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 962$, *Group2 : $962 \leq \text{SL} \leq 1443$, *Group3 : $1443 < \text{SL}$
PSCKDSD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.328	$0.326 + 0.001 \cdot \text{SL}$	$0.276 + 0.001 \cdot \text{SL}$	$0.237 + 0.001 \cdot \text{SL}$
	t_F	0.361	$0.358 + 0.001 \cdot \text{SL}$	$0.310 + 0.001 \cdot \text{SL}$	$0.264 + 0.001 \cdot \text{SL}$
	t_{PLH}	1.671	$1.670 + 0.001 \cdot \text{SL}$	$1.700 + 0.000 \cdot \text{SL}$	$1.706 + 0.000 \cdot \text{SL}$
	t_{PHL}	1.815	$1.813 + 0.001 \cdot \text{SL}$	$1.846 + 0.001 \cdot \text{SL}$	$1.853 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 1443$, *Group2 : $1443 \leq \text{SL} \leq 2165$, *Group3 : $2165 < \text{SL}$
PSCKDSD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.382	$0.381 + 0.001 \cdot \text{SL}$	$0.332 + 0.001 \cdot \text{SL}$	$0.291 + 0.001 \cdot \text{SL}$
	t_F	0.458	$0.457 + 0.001 \cdot \text{SL}$	$0.408 + 0.001 \cdot \text{SL}$	$0.360 + 0.001 \cdot \text{SL}$
	t_{PLH}	1.849	$1.848 + 0.000 \cdot \text{SL}$	$1.889 + 0.000 \cdot \text{SL}$	$1.901 + 0.000 \cdot \text{SL}$
	t_{PHL}	2.066	$2.065 + 0.001 \cdot \text{SL}$	$2.115 + 0.000 \cdot \text{SL}$	$2.131 + 0.000 \cdot \text{SL}$

*Group1 : $\text{SL} < 1923$, *Group2 : $1923 \leq \text{SL} \leq 2887$, *Group3 : $2887 < \text{SL}$

PSCKDSby

LVCMOS Schmitt Trigger Level Input Clock Drivers

Switching Characteristics

(Typical process, 25 °C, 2.5V, $t_R/t_F = 3.00ns$, SL: Standard Load)

PSCKDSU2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.206	$0.200 + 0.003*SL$	$0.160 + 0.003*SL$	$0.133 + 0.003*SL$
	t_F	0.193	$0.186 + 0.004*SL$	$0.149 + 0.004*SL$	$0.124 + 0.004*SL$
	t_{PLH}	1.168	$1.165 + 0.001*SL$	$1.168 + 0.001*SL$	$1.168 + 0.001*SL$
	t_{PHL}	1.253	$1.249 + 0.002*SL$	$1.256 + 0.002*SL$	$1.255 + 0.002*SL$

*Group1 : $SL < 482$, *Group2 : $482 \leq SL \leq 722$, *Group3 : $722 < SL$

PSCKDSU4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.276	$0.273 + 0.002*SL$	$0.225 + 0.002*SL$	$0.187 + 0.002*SL$
	t_F	0.268	$0.264 + 0.002*SL$	$0.220 + 0.002*SL$	$0.182 + 0.002*SL$
	t_{PLH}	1.435	$1.434 + 0.001*SL$	$1.451 + 0.001*SL$	$1.453 + 0.001*SL$
	t_{PHL}	1.545	$1.543 + 0.001*SL$	$1.562 + 0.001*SL$	$1.564 + 0.001*SL$

*Group1 : $SL < 962$, *Group2 : $962 \leq SL \leq 1443$, *Group3 : $1443 < SL$

PSCKDSU6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.339	$0.337 + 0.001*SL$	$0.285 + 0.001*SL$	$0.245 + 0.001*SL$
	t_F	0.365	$0.362 + 0.001*SL$	$0.315 + 0.001*SL$	$0.269 + 0.001*SL$
	t_{PLH}	1.651	$1.650 + 0.001*SL$	$1.681 + 0.000*SL$	$1.688 + 0.000*SL$
	t_{PHL}	1.811	$1.810 + 0.001*SL$	$1.845 + 0.001*SL$	$1.853 + 0.001*SL$

*Group1 : $SL < 1443$, *Group2 : $1443 \leq SL \leq 2165$, *Group3 : $2165 < SL$

PSCKDSU8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.394	$0.392 + 0.001*SL$	$0.342 + 0.001*SL$	$0.300 + 0.001*SL$
	t_F	0.469	$0.467 + 0.001*SL$	$0.418 + 0.001*SL$	$0.370 + 0.001*SL$
	t_{PLH}	1.835	$1.834 + 0.000*SL$	$1.877 + 0.000*SL$	$1.890 + 0.000*SL$
	t_{PHL}	2.066	$2.065 + 0.001*SL$	$2.117 + 0.000*SL$	$2.134 + 0.000*SL$

*Group1 : $SL < 1923$, *Group2 : $1923 \leq SL \leq 2887$, *Group3 : $2887 < SL$

OSCILLATORS

Cell List

Cell Name	Function Description
PHSOSCK1	Oscillator Cell with Enable (~ 100kHz)
PHSOSCK2	Oscillator Cell with Enable (100K ~ 1MHz)
PHSOSCK17	Oscillator Cell with Enable and Feedback Resistor 10M Ω (~ 100kHz)
PHSOSCK27	Oscillator Cell with Enable and Feedback Resistor 10M Ω (100K ~ 1MHz)
PHSOSCM1	Oscillator Cell with Enable (1M ~ 10MHz)
PHSOSCM2	Oscillator Cell with Enable (10M ~ 40MHz)
PHSOSCM3	Oscillator Cell with Enable (40M ~ 100MHz)
PHSOSCM16	Oscillator Cell with Enable and Feedback Resistor 1M Ω (1M ~ 10MHz)
PHSOSCM26	Oscillator Cell with Enable and Feedback Resistor 1M Ω (10M ~ 40MHz)
PHSOSCM36	Oscillator Cell with Enable and Feedback Resistor 1M Ω (40M ~ 100MHz)

NOTE: Use I/O 3.3V and Core 2.5V

Cell Name	Function Description
PSOSCK1	Oscillator Cell with Enable (~ 100kHz)
PSOSCK2	Oscillator Cell with Enable (100K ~ 1MHz)
PSOSCM1	Oscillator Cell with Enable (1M ~ 10MHz)
PSOSCM2	Oscillator Cell with Enable (10M ~ 40MHz)

NOTE: Use I/O 2.5V and Core 2.5V

Oscillator Cell with Enable

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Input Load (SL)		I/O Sizes	
<i>PHSOSCK1/K2</i>	<i>PHSOSCM1/M2/M3</i>	<i>PHSOSCK1/K2</i>	<i>PHSOSCM1/M2/M3</i>
E	E		
3.55	3.55	2 I/O Slots	2 I/O Slots

Switching Characteristics

PHSOSCK1

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2030.800	$40.550 + 39.805 \cdot \text{CL}$	$40.800 + 39.800 \cdot \text{CL}$	$40.500 + 39.804 \cdot \text{CL}$
	t_F	1973.700	$39.450 + 38.685 \cdot \text{CL}$	$39.300 + 38.688 \cdot \text{CL}$	$39.600 + 38.684 \cdot \text{CL}$
	t_{PLH}	909.370	$19.320 + 17.801 \cdot \text{CL}$	$19.310 + 17.801 \cdot \text{CL}$	$19.400 + 17.800 \cdot \text{CL}$
	t_{PHL}	957.810	$20.335 + 18.749 \cdot \text{CL}$	$20.430 + 18.748 \cdot \text{CL}$	$20.100 + 18.752 \cdot \text{CL}$
E to PADY	t_R	2030.800	$40.550 + 39.805 \cdot \text{CL}$	$40.800 + 39.800 \cdot \text{CL}$	$40.500 + 39.804 \cdot \text{CL}$
	t_F	1973.700	$39.450 + 38.685 \cdot \text{CL}$	$39.300 + 38.688 \cdot \text{CL}$	$39.600 + 38.684 \cdot \text{CL}$
	t_{PLH}	909.250	$19.200 + 17.801 \cdot \text{CL}$	$19.150 + 17.802 \cdot \text{CL}$	$19.300 + 17.800 \cdot \text{CL}$
	t_{PHL}	957.470	$20.020 + 18.749 \cdot \text{CL}$	$20.010 + 18.749 \cdot \text{CL}$	$20.100 + 18.748 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.203	$0.187 + 0.008 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_F	0.201	$0.186 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$	$0.200 + 0.006 \cdot \text{SL}$
	t_{PLH}	10.400	$10.389 + 0.006 \cdot \text{SL}$	$10.394 + 0.004 \cdot \text{SL}$	$10.426 + 0.003 \cdot \text{SL}$
	t_{PHL}	12.561	$12.550 + 0.006 \cdot \text{SL}$	$12.555 + 0.004 \cdot \text{SL}$	$12.592 + 0.004 \cdot \text{SL}$
E to YN	t_R	0.203	$0.187 + 0.008 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_F	0.201	$0.186 + 0.008 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	9.676	$9.665 + 0.006 \cdot \text{SL}$	$9.669 + 0.004 \cdot \text{SL}$	$9.702 + 0.003 \cdot \text{SL}$
	t_{PHL}	12.364	$12.353 + 0.006 \cdot \text{SL}$	$12.357 + 0.004 \cdot \text{SL}$	$12.396 + 0.004 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK1/K2/M1/M2/M3

Oscillator Cell with Enable

Switching Characteristics

PHSOSCK2

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	261.510	$5.285 + 5.124 \cdot \text{CL}$	$5.270 + 5.125 \cdot \text{CL}$	$5.270 + 5.125 \cdot \text{CL}$
	t_F	246.440	$4.965 + 4.830 \cdot \text{CL}$	$4.940 + 4.830 \cdot \text{CL}$	$4.940 + 4.830 \cdot \text{CL}$
	t_{PLH}	96.965	$2.873 + 1.882 \cdot \text{CL}$	$2.875 + 1.882 \cdot \text{CL}$	$2.860 + 1.882 \cdot \text{CL}$
	t_{PHL}	97.991	$2.901 + 1.902 \cdot \text{CL}$	$2.893 + 1.902 \cdot \text{CL}$	$2.920 + 1.902 \cdot \text{CL}$
E to PADY	t_R	261.510	$5.285 + 5.124 \cdot \text{CL}$	$5.270 + 5.125 \cdot \text{CL}$	$5.270 + 5.125 \cdot \text{CL}$
	t_F	246.440	$4.965 + 4.830 \cdot \text{CL}$	$4.940 + 4.830 \cdot \text{CL}$	$4.970 + 4.830 \cdot \text{CL}$
	t_{PLH}	96.810	$2.720 + 1.882 \cdot \text{CL}$	$2.710 + 1.882 \cdot \text{CL}$	$2.710 + 1.882 \cdot \text{CL}$
	t_{PHL}	97.596	$2.503 + 1.902 \cdot \text{CL}$	$2.508 + 1.902 \cdot \text{CL}$	$2.490 + 1.902 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.187	$0.170 + 0.008 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$
	t_F	0.177	$0.162 + 0.008 \cdot \text{SL}$	$0.166 + 0.007 \cdot \text{SL}$	$0.172 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.286	$2.276 + 0.005 \cdot \text{SL}$	$2.280 + 0.004 \cdot \text{SL}$	$2.306 + 0.003 \cdot \text{SL}$
	t_{PHL}	2.131	$2.119 + 0.006 \cdot \text{SL}$	$2.124 + 0.004 \cdot \text{SL}$	$2.157 + 0.004 \cdot \text{SL}$
E to YN	t_R	0.186	$0.170 + 0.008 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$
	t_F	0.177	$0.162 + 0.008 \cdot \text{SL}$	$0.166 + 0.007 \cdot \text{SL}$	$0.172 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.149	$2.138 + 0.005 \cdot \text{SL}$	$2.143 + 0.004 \cdot \text{SL}$	$2.169 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.687	$1.676 + 0.006 \cdot \text{SL}$	$1.681 + 0.004 \cdot \text{SL}$	$1.714 + 0.004 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

Switching Characteristics

PHSOSCM1

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	16.399	$0.541 + 0.317 \cdot \text{CL}$	$0.289 + 0.322 \cdot \text{CL}$	$0.310 + 0.322 \cdot \text{CL}$
	t_F	17.023	$0.453 + 0.331 \cdot \text{CL}$	$0.571 + 0.329 \cdot \text{CL}$	$0.331 + 0.332 \cdot \text{CL}$
	t_{PLH}	8.556	$1.164 + 0.148 \cdot \text{CL}$	$1.131 + 0.149 \cdot \text{CL}$	$1.139 + 0.148 \cdot \text{CL}$
	t_{PHL}	9.600	$1.162 + 0.169 \cdot \text{CL}$	$1.138 + 0.169 \cdot \text{CL}$	$1.147 + 0.169 \cdot \text{CL}$
E to PADY	t_R	16.474	$0.549 + 0.319 \cdot \text{CL}$	$0.448 + 0.321 \cdot \text{CL}$	$0.454 + 0.320 \cdot \text{CL}$
	t_F	17.028	$0.513 + 0.330 \cdot \text{CL}$	$0.532 + 0.330 \cdot \text{CL}$	$0.484 + 0.331 \cdot \text{CL}$
	t_{PLH}	8.505	$1.045 + 0.149 \cdot \text{CL}$	$1.110 + 0.148 \cdot \text{CL}$	$1.073 + 0.148 \cdot \text{CL}$
	t_{PHL}	9.491	$1.019 + 0.169 \cdot \text{CL}$	$1.036 + 0.169 \cdot \text{CL}$	$1.026 + 0.169 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.140	$0.125 + 0.007 \cdot \text{SL}$	$0.126 + 0.007 \cdot \text{SL}$	$0.121 + 0.007 \cdot \text{SL}$
	t_F	0.128	$0.113 + 0.007 \cdot \text{SL}$	$0.116 + 0.007 \cdot \text{SL}$	$0.114 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.378	$1.369 + 0.004 \cdot \text{SL}$	$1.372 + 0.004 \cdot \text{SL}$	$1.384 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.140	$1.131 + 0.005 \cdot \text{SL}$	$1.134 + 0.004 \cdot \text{SL}$	$1.149 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.139	$0.123 + 0.008 \cdot \text{SL}$	$0.126 + 0.007 \cdot \text{SL}$	$0.121 + 0.007 \cdot \text{SL}$
	t_F	0.128	$0.114 + 0.007 \cdot \text{SL}$	$0.116 + 0.007 \cdot \text{SL}$	$0.115 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.558	$1.549 + 0.004 \cdot \text{SL}$	$1.552 + 0.004 \cdot \text{SL}$	$1.565 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.243	$1.234 + 0.005 \cdot \text{SL}$	$1.237 + 0.004 \cdot \text{SL}$	$1.251 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK1/K2/M1/M2/M3

Oscillator Cell with Enable

Switching Characteristics

PHSOSCM2

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	4.378	$0.613 + 0.075 \cdot \text{CL}$	$0.480 + 0.078 \cdot \text{CL}$	$0.361 + 0.080 \cdot \text{CL}$
	t_F	4.588	$0.819 + 0.075 \cdot \text{CL}$	$0.650 + 0.079 \cdot \text{CL}$	$0.499 + 0.081 \cdot \text{CL}$
	t_{PLH}	3.414	$1.536 + 0.038 \cdot \text{CL}$	$1.548 + 0.037 \cdot \text{CL}$	$1.546 + 0.037 \cdot \text{CL}$
	t_{PHL}	3.720	$1.579 + 0.043 \cdot \text{CL}$	$1.610 + 0.042 \cdot \text{CL}$	$1.612 + 0.042 \cdot \text{CL}$
E to PADY	t_R	4.294	$0.370 + 0.078 \cdot \text{CL}$	$0.310 + 0.080 \cdot \text{CL}$	$0.263 + 0.080 \cdot \text{CL}$
	t_F	4.466	$0.504 + 0.079 \cdot \text{CL}$	$0.423 + 0.081 \cdot \text{CL}$	$0.358 + 0.082 \cdot \text{CL}$
	t_{PLH}	3.458	$1.565 + 0.038 \cdot \text{CL}$	$1.580 + 0.038 \cdot \text{CL}$	$1.584 + 0.038 \cdot \text{CL}$
	t_{PHL}	3.971	$1.827 + 0.043 \cdot \text{CL}$	$1.851 + 0.042 \cdot \text{CL}$	$1.856 + 0.042 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.109	$0.096 + 0.006 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.094 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.082 + 0.007 \cdot \text{SL}$	$0.082 + 0.007 \cdot \text{SL}$	$0.081 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.719	$1.711 + 0.004 \cdot \text{SL}$	$1.713 + 0.003 \cdot \text{SL}$	$1.718 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.436	$1.428 + 0.004 \cdot \text{SL}$	$1.430 + 0.004 \cdot \text{SL}$	$1.437 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.109	$0.096 + 0.006 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.094 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.082 + 0.006 \cdot \text{SL}$	$0.082 + 0.007 \cdot \text{SL}$	$0.081 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.862	$1.855 + 0.004 \cdot \text{SL}$	$1.857 + 0.003 \cdot \text{SL}$	$1.862 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.827	$1.819 + 0.004 \cdot \text{SL}$	$1.821 + 0.004 \cdot \text{SL}$	$1.827 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

Switching Characteristics

PHSOSCM3

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2.653	$0.973 + 0.034 \cdot \text{CL}$	$1.264 + 0.028 \cdot \text{CL}$	$1.165 + 0.029 \cdot \text{CL}$
	t_F	2.830	$1.187 + 0.033 \cdot \text{CL}$	$1.297 + 0.031 \cdot \text{CL}$	$1.220 + 0.032 \cdot \text{CL}$
	t_{PLH}	3.235	$2.217 + 0.020 \cdot \text{CL}$	$2.343 + 0.018 \cdot \text{CL}$	$2.425 + 0.017 \cdot \text{CL}$
	t_{PHL}	3.349	$2.145 + 0.024 \cdot \text{CL}$	$2.286 + 0.021 \cdot \text{CL}$	$2.416 + 0.020 \cdot \text{CL}$
E to PADY	t_R	2.570	$1.026 + 0.031 \cdot \text{CL}$	$1.207 + 0.027 \cdot \text{CL}$	$0.867 + 0.032 \cdot \text{CL}$
	t_F	2.801	$1.194 + 0.032 \cdot \text{CL}$	$1.223 + 0.032 \cdot \text{CL}$	$1.346 + 0.030 \cdot \text{CL}$
	t_{PLH}	3.433	$2.410 + 0.020 \cdot \text{CL}$	$2.530 + 0.018 \cdot \text{CL}$	$2.625 + 0.017 \cdot \text{CL}$
	t_{PHL}	4.374	$3.161 + 0.024 \cdot \text{CL}$	$3.311 + 0.021 \cdot \text{CL}$	$3.446 + 0.019 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$ (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.093	$0.086 + 0.003 \cdot \text{SL}$	$0.086 + 0.003 \cdot \text{SL}$	$0.084 + 0.004 \cdot \text{SL}$
	t_F	0.074	$0.067 + 0.003 \cdot \text{SL}$	$0.067 + 0.003 \cdot \text{SL}$	$0.067 + 0.004 \cdot \text{SL}$
	t_{PLH}	2.577	$2.573 + 0.002 \cdot \text{SL}$	$2.574 + 0.002 \cdot \text{SL}$	$2.582 + 0.002 \cdot \text{SL}$
	t_{PHL}	2.203	$2.198 + 0.002 \cdot \text{SL}$	$2.199 + 0.002 \cdot \text{SL}$	$2.207 + 0.002 \cdot \text{SL}$
E to YN	t_R	0.093	$0.087 + 0.003 \cdot \text{SL}$	$0.085 + 0.003 \cdot \text{SL}$	$0.084 + 0.004 \cdot \text{SL}$
	t_F	0.074	$0.067 + 0.004 \cdot \text{SL}$	$0.067 + 0.003 \cdot \text{SL}$	$0.067 + 0.004 \cdot \text{SL}$
	t_{PLH}	2.759	$2.755 + 0.002 \cdot \text{SL}$	$2.756 + 0.002 \cdot \text{SL}$	$2.763 + 0.002 \cdot \text{SL}$
	t_{PHL}	3.209	$3.205 + 0.002 \cdot \text{SL}$	$3.206 + 0.002 \cdot \text{SL}$	$3.213 + 0.002 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and Feedback Resistor

Logic Symbol



Truth Table

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Cell Data

Input Load (SL)		I/O Sizes	
PHSOSCK17/K27	PHSOSCM16/M26/M36	PHSOSCK17/K27	PHSOSCM16/M26/M36
E	E		
3.55	3.55	2 I/O Slots	2 I/O Slots

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and 10Mohm Resistor

Switching Characteristics

PHSOSCK17

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2042.700	$42.700 + 40.000 \cdot \text{CL}$	$43.100 + 39.992 \cdot \text{CL}$	$42.800 + 39.996 \cdot \text{CL}$
	t_F	1997.600	$40.850 + 39.135 \cdot \text{CL}$	$41.000 + 39.132 \cdot \text{CL}$	$41.000 + 39.132 \cdot \text{CL}$
	t_{PLH}	905.240	$19.065 + 17.724 \cdot \text{CL}$	$19.120 + 17.722 \cdot \text{CL}$	$19.000 + 17.724 \cdot \text{CL}$
	t_{PHL}	959.380	$21.530 + 18.757 \cdot \text{CL}$	$21.540 + 18.757 \cdot \text{CL}$	$21.600 + 18.756 \cdot \text{CL}$
E to PADY	t_R	2043.000	$43.500 + 39.990 \cdot \text{CL}$	$43.400 + 39.992 \cdot \text{CL}$	$43.400 + 39.992 \cdot \text{CL}$
	t_F	1973.800	$39.550 + 38.685 \cdot \text{CL}$	$39.600 + 38.684 \cdot \text{CL}$	$39.300 + 38.688 \cdot \text{CL}$
	t_{PLH}	909.710	$19.560 + 17.803 \cdot \text{CL}$	$19.530 + 17.804 \cdot \text{CL}$	$19.800 + 17.800 \cdot \text{CL}$
	t_{PHL}	953.620	$21.120 + 18.650 \cdot \text{CL}$	$21.060 + 18.651 \cdot \text{CL}$	$21.300 + 18.648 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.202	$0.186 + 0.008 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_F	0.201	$0.185 + 0.008 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	10.406	$10.396 + 0.005 \cdot \text{SL}$	$10.400 + 0.004 \cdot \text{SL}$	$10.432 + 0.003 \cdot \text{SL}$
	t_{PHL}	12.617	$12.606 + 0.006 \cdot \text{SL}$	$12.611 + 0.004 \cdot \text{SL}$	$12.648 + 0.004 \cdot \text{SL}$
E to YN	t_R	0.202	$0.187 + 0.008 \cdot \text{SL}$	$0.190 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$
	t_F	0.201	$0.186 + 0.007 \cdot \text{SL}$	$0.189 + 0.007 \cdot \text{SL}$	$0.199 + 0.006 \cdot \text{SL}$
	t_{PLH}	9.695	$9.684 + 0.006 \cdot \text{SL}$	$9.688 + 0.004 \cdot \text{SL}$	$9.720 + 0.003 \cdot \text{SL}$
	t_{PHL}	12.361	$12.350 + 0.006 \cdot \text{SL}$	$12.355 + 0.004 \cdot \text{SL}$	$12.392 + 0.004 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and Feedback Resistor

Switching Characteristics

PHSOSCK27

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	261.840	$5.415 + 5.128 \cdot \text{CL}$	$5.400 + 5.129 \cdot \text{CL}$	$5.400 + 5.129 \cdot \text{CL}$
	t_F	246.770	$4.995 + 4.836 \cdot \text{CL}$	$4.990 + 4.836 \cdot \text{CL}$	$4.960 + 4.836 \cdot \text{CL}$
	t_{PLH}	96.999	$2.934 + 1.881 \cdot \text{CL}$	$2.917 + 1.882 \cdot \text{CL}$	$2.950 + 1.881 \cdot \text{CL}$
	t_{PHL}	98.217	$3.074 + 1.903 \cdot \text{CL}$	$3.071 + 1.903 \cdot \text{CL}$	$3.080 + 1.903 \cdot \text{CL}$
E to PADY	t_R	261.890	$5.465 + 5.128 \cdot \text{CL}$	$5.470 + 5.128 \cdot \text{CL}$	$5.470 + 5.128 \cdot \text{CL}$
	t_F	246.440	$4.965 + 4.830 \cdot \text{CL}$	$4.940 + 4.830 \cdot \text{CL}$	$4.940 + 4.830 \cdot \text{CL}$
	t_{PLH}	96.895	$2.798 + 1.882 \cdot \text{CL}$	$2.785 + 1.882 \cdot \text{CL}$	$2.800 + 1.882 \cdot \text{CL}$
	t_{PHL}	97.654	$2.607 + 1.901 \cdot \text{CL}$	$2.602 + 1.901 \cdot \text{CL}$	$2.590 + 1.901 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.187	$0.171 + 0.008 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$
	t_F	0.177	$0.162 + 0.008 \cdot \text{SL}$	$0.166 + 0.007 \cdot \text{SL}$	$0.172 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.302	$2.292 + 0.005 \cdot \text{SL}$	$2.296 + 0.004 \cdot \text{SL}$	$2.323 + 0.003 \cdot \text{SL}$
	t_{PHL}	2.183	$2.172 + 0.006 \cdot \text{SL}$	$2.177 + 0.004 \cdot \text{SL}$	$2.209 + 0.004 \cdot \text{SL}$
E to YN	t_R	0.187	$0.171 + 0.008 \cdot \text{SL}$	$0.175 + 0.007 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$
	t_F	0.177	$0.163 + 0.007 \cdot \text{SL}$	$0.165 + 0.007 \cdot \text{SL}$	$0.172 + 0.006 \cdot \text{SL}$
	t_{PLH}	2.161	$2.150 + 0.005 \cdot \text{SL}$	$2.154 + 0.004 \cdot \text{SL}$	$2.181 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.685	$1.674 + 0.006 \cdot \text{SL}$	$1.679 + 0.004 \cdot \text{SL}$	$1.712 + 0.004 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and Feedback Resistor

Switching Characteristics

PHSOSCM16

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	16.421	$0.399 + 0.320 \cdot \text{CL}$	$0.367 + 0.321 \cdot \text{CL}$	$0.250 + 0.323 \cdot \text{CL}$
	t_F	17.016	$0.619 + 0.328 \cdot \text{CL}$	$0.498 + 0.330 \cdot \text{CL}$	$0.309 + 0.333 \cdot \text{CL}$
	t_{PLH}	8.557	$1.168 + 0.148 \cdot \text{CL}$	$1.122 + 0.149 \cdot \text{CL}$	$1.154 + 0.148 \cdot \text{CL}$
	t_{PHL}	9.628	$1.153 + 0.169 \cdot \text{CL}$	$1.179 + 0.169 \cdot \text{CL}$	$1.166 + 0.169 \cdot \text{CL}$
E to PADY	t_R	16.450	$0.607 + 0.317 \cdot \text{CL}$	$0.360 + 0.322 \cdot \text{CL}$	$0.420 + 0.321 \cdot \text{CL}$
	t_F	17.030	$0.557 + 0.329 \cdot \text{CL}$	$0.522 + 0.330 \cdot \text{CL}$	$0.543 + 0.330 \cdot \text{CL}$
	t_{PLH}	8.503	$1.070 + 0.149 \cdot \text{CL}$	$1.110 + 0.148 \cdot \text{CL}$	$1.034 + 0.149 \cdot \text{CL}$
	t_{PHL}	9.492	$1.021 + 0.169 \cdot \text{CL}$	$1.037 + 0.169 \cdot \text{CL}$	$1.029 + 0.169 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.139	$0.125 + 0.007 \cdot \text{SL}$	$0.125 + 0.007 \cdot \text{SL}$	$0.121 + 0.007 \cdot \text{SL}$
	t_F	0.129	$0.116 + 0.007 \cdot \text{SL}$	$0.116 + 0.007 \cdot \text{SL}$	$0.114 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.386	$1.378 + 0.004 \cdot \text{SL}$	$1.380 + 0.004 \cdot \text{SL}$	$1.392 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.146	$1.137 + 0.005 \cdot \text{SL}$	$1.140 + 0.004 \cdot \text{SL}$	$1.155 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.139	$0.123 + 0.008 \cdot \text{SL}$	$0.126 + 0.007 \cdot \text{SL}$	$0.121 + 0.007 \cdot \text{SL}$
	t_F	0.128	$0.114 + 0.007 \cdot \text{SL}$	$0.116 + 0.007 \cdot \text{SL}$	$0.115 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.562	$1.553 + 0.004 \cdot \text{SL}$	$1.556 + 0.004 \cdot \text{SL}$	$1.568 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.242	$1.232 + 0.005 \cdot \text{SL}$	$1.236 + 0.004 \cdot \text{SL}$	$1.250 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and Feedback Resistor

Switching Characteristics

PHSOSCM26

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	4.379	$0.612 + 0.075 \cdot \text{CL}$	$0.479 + 0.078 \cdot \text{CL}$	$0.361 + 0.080 \cdot \text{CL}$
	t_F	4.598	$0.829 + 0.075 \cdot \text{CL}$	$0.659 + 0.079 \cdot \text{CL}$	$0.508 + 0.081 \cdot \text{CL}$
	t_{PLH}	3.419	$1.540 + 0.038 \cdot \text{CL}$	$1.553 + 0.037 \cdot \text{CL}$	$1.550 + 0.037 \cdot \text{CL}$
	t_{PHL}	3.732	$1.588 + 0.043 \cdot \text{CL}$	$1.620 + 0.042 \cdot \text{CL}$	$1.623 + 0.042 \cdot \text{CL}$
E to PADY	t_R	4.297	$0.372 + 0.078 \cdot \text{CL}$	$0.312 + 0.080 \cdot \text{CL}$	$0.265 + 0.080 \cdot \text{CL}$
	t_F	4.466	$0.504 + 0.079 \cdot \text{CL}$	$0.423 + 0.081 \cdot \text{CL}$	$0.358 + 0.082 \cdot \text{CL}$
	t_{PLH}	3.463	$1.570 + 0.038 \cdot \text{CL}$	$1.585 + 0.038 \cdot \text{CL}$	$1.589 + 0.038 \cdot \text{CL}$
	t_{PHL}	3.970	$1.826 + 0.043 \cdot \text{CL}$	$1.851 + 0.042 \cdot \text{CL}$	$1.856 + 0.042 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.109	$0.096 + 0.006 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.093 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.082 + 0.007 \cdot \text{SL}$	$0.082 + 0.007 \cdot \text{SL}$	$0.081 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.725	$1.718 + 0.004 \cdot \text{SL}$	$1.719 + 0.003 \cdot \text{SL}$	$1.724 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.440	$1.432 + 0.004 \cdot \text{SL}$	$1.434 + 0.004 \cdot \text{SL}$	$1.440 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.109	$0.096 + 0.006 \cdot \text{SL}$	$0.095 + 0.007 \cdot \text{SL}$	$0.094 + 0.007 \cdot \text{SL}$
	t_F	0.095	$0.081 + 0.007 \cdot \text{SL}$	$0.082 + 0.007 \cdot \text{SL}$	$0.081 + 0.007 \cdot \text{SL}$
	t_{PLH}	1.867	$1.860 + 0.004 \cdot \text{SL}$	$1.861 + 0.003 \cdot \text{SL}$	$1.866 + 0.003 \cdot \text{SL}$
	t_{PHL}	1.826	$1.818 + 0.004 \cdot \text{SL}$	$1.820 + 0.004 \cdot \text{SL}$	$1.826 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PHSOSCK17/K27/M16/M26/M36

Oscillator Cell with Enable and Feedback Resistor

Switching Characteristics

PHSOSCM36

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2.542	$0.991 + 0.031 \cdot \text{CL}$	$0.980 + 0.031 \cdot \text{CL}$	$1.262 + 0.027 \cdot \text{CL}$
	t_F	2.837	$1.210 + 0.033 \cdot \text{CL}$	$1.305 + 0.031 \cdot \text{CL}$	$1.221 + 0.032 \cdot \text{CL}$
	t_{PLH}	3.238	$2.222 + 0.020 \cdot \text{CL}$	$2.339 + 0.018 \cdot \text{CL}$	$2.440 + 0.017 \cdot \text{CL}$
	t_{PHL}	3.357	$2.147 + 0.024 \cdot \text{CL}$	$2.296 + 0.021 \cdot \text{CL}$	$2.419 + 0.020 \cdot \text{CL}$
E to PADY	t_R	2.482	$1.095 + 0.028 \cdot \text{CL}$	$0.589 + 0.038 \cdot \text{CL}$	$1.624 + 0.024 \cdot \text{CL}$
	t_F	2.797	$1.165 + 0.033 \cdot \text{CL}$	$1.216 + 0.032 \cdot \text{CL}$	$1.349 + 0.030 \cdot \text{CL}$
	t_{PLH}	3.437	$2.415 + 0.020 \cdot \text{CL}$	$2.533 + 0.018 \cdot \text{CL}$	$2.633 + 0.017 \cdot \text{CL}$
	t_{PHL}	4.373	$3.160 + 0.024 \cdot \text{CL}$	$3.310 + 0.021 \cdot \text{CL}$	$3.443 + 0.019 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.093	$0.086 + 0.003 \cdot \text{SL}$	$0.086 + 0.003 \cdot \text{SL}$	$0.084 + 0.004 \cdot \text{SL}$
	t_F	0.074	$0.067 + 0.003 \cdot \text{SL}$	$0.067 + 0.003 \cdot \text{SL}$	$0.066 + 0.004 \cdot \text{SL}$
	t_{PLH}	2.582	$2.577 + 0.002 \cdot \text{SL}$	$2.579 + 0.002 \cdot \text{SL}$	$2.586 + 0.002 \cdot \text{SL}$
	t_{PHL}	2.207	$2.202 + 0.002 \cdot \text{SL}$	$2.204 + 0.002 \cdot \text{SL}$	$2.211 + 0.002 \cdot \text{SL}$
E to YN	t_R	0.093	$0.087 + 0.003 \cdot \text{SL}$	$0.085 + 0.003 \cdot \text{SL}$	$0.084 + 0.004 \cdot \text{SL}$
	t_F	0.074	$0.067 + 0.003 \cdot \text{SL}$	$0.066 + 0.004 \cdot \text{SL}$	$0.066 + 0.004 \cdot \text{SL}$
	t_{PLH}	2.764	$2.760 + 0.002 \cdot \text{SL}$	$2.761 + 0.002 \cdot \text{SL}$	$2.769 + 0.002 \cdot \text{SL}$
	t_{PHL}	3.207	$3.202 + 0.002 \cdot \text{SL}$	$3.204 + 0.002 \cdot \text{SL}$	$3.211 + 0.002 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PSOSCK1/K2/M1/M2

Oscillator Cell with Enable

Logic Symbol



Truth Table

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Cell Data

Input Load (SL)		I/O Sizes	
PSOSCK1/K2	PSOSCM1/M2	PSOSCK1/K2	PSOSCM1/M2
E	E		
3.49	3.49	2 I/O Slots	2 I/O Slots

PSOSCK1/K2/M1/M2

Oscillator Cell with Enable

Switching Characteristics

PSOSCK1

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2059.600	$79.600 + 39.600 \cdot \text{CL}$	$79.400 + 39.604 \cdot \text{CL}$	$79.400 + 39.604 \cdot \text{CL}$
	t_F	1941.400	$72.400 + 37.380 \cdot \text{CL}$	$72.400 + 37.380 \cdot \text{CL}$	$72.100 + 37.384 \cdot \text{CL}$
	t_{PLH}	885.410	$33.110 + 17.046 \cdot \text{CL}$	$33.030 + 17.048 \cdot \text{CL}$	$33.300 + 17.044 \cdot \text{CL}$
	t_{PHL}	872.610	$36.035 + 16.732 \cdot \text{CL}$	$36.030 + 16.732 \cdot \text{CL}$	$36.000 + 16.732 \cdot \text{CL}$
E to PADY	t_R	2059.600	$79.600 + 39.600 \cdot \text{CL}$	$79.400 + 39.604 \cdot \text{CL}$	$79.400 + 39.604 \cdot \text{CL}$
	t_F	1941.400	$72.400 + 37.380 \cdot \text{CL}$	$72.400 + 37.380 \cdot \text{CL}$	$72.100 + 37.384 \cdot \text{CL}$
	t_{PLH}	884.940	$32.615 + 17.047 \cdot \text{CL}$	$32.620 + 17.046 \cdot \text{CL}$	$32.800 + 17.044 \cdot \text{CL}$
	t_{PHL}	872.030	$35.455 + 16.732 \cdot \text{CL}$	$35.490 + 16.731 \cdot \text{CL}$	$35.400 + 16.732 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.179	$0.164 + 0.008 \cdot \text{SL}$	$0.167 + 0.007 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$
	t_F	0.169	$0.153 + 0.008 \cdot \text{SL}$	$0.158 + 0.006 \cdot \text{SL}$	$0.160 + 0.006 \cdot \text{SL}$
	t_{PLH}	9.684	$9.674 + 0.005 \cdot \text{SL}$	$9.678 + 0.004 \cdot \text{SL}$	$9.702 + 0.003 \cdot \text{SL}$
	t_{PHL}	9.212	$9.201 + 0.005 \cdot \text{SL}$	$9.205 + 0.004 \cdot \text{SL}$	$9.234 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.179	$0.162 + 0.009 \cdot \text{SL}$	$0.168 + 0.007 \cdot \text{SL}$	$0.162 + 0.007 \cdot \text{SL}$
	t_F	0.169	$0.153 + 0.008 \cdot \text{SL}$	$0.158 + 0.006 \cdot \text{SL}$	$0.160 + 0.006 \cdot \text{SL}$
	t_{PLH}	8.619	$8.609 + 0.005 \cdot \text{SL}$	$8.613 + 0.004 \cdot \text{SL}$	$8.637 + 0.003 \cdot \text{SL}$
	t_{PHL}	8.790	$8.779 + 0.005 \cdot \text{SL}$	$8.783 + 0.004 \cdot \text{SL}$	$8.812 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PSOSCK1/K2/M1/M2

Oscillator Cell with Enable

Switching Characteristics

PSOSCK2

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	312.740	$12.140 + 6.012 \cdot \text{CL}$	$12.160 + 6.012 \cdot \text{CL}$	$12.160 + 6.012 \cdot \text{CL}$
	t_F	302.800	$11.250 + 5.831 \cdot \text{CL}$	$11.260 + 5.831 \cdot \text{CL}$	$11.230 + 5.831 \cdot \text{CL}$
	t_{PLH}	113.550	$4.822 + 2.175 \cdot \text{CL}$	$4.830 + 2.174 \cdot \text{CL}$	$4.830 + 2.174 \cdot \text{CL}$
	t_{PHL}	126.860	$5.765 + 2.422 \cdot \text{CL}$	$5.760 + 2.422 \cdot \text{CL}$	$5.760 + 2.422 \cdot \text{CL}$
E to PADY	t_R	312.730	$12.155 + 6.012 \cdot \text{CL}$	$12.130 + 6.012 \cdot \text{CL}$	$12.160 + 6.012 \cdot \text{CL}$
	t_F	302.800	$11.250 + 5.831 \cdot \text{CL}$	$11.260 + 5.831 \cdot \text{CL}$	$11.230 + 5.831 \cdot \text{CL}$
	t_{PLH}	113.090	$4.375 + 2.174 \cdot \text{CL}$	$4.350 + 2.175 \cdot \text{CL}$	$4.380 + 2.174 \cdot \text{CL}$
	t_{PHL}	126.470	$5.363 + 2.422 \cdot \text{CL}$	$5.370 + 2.422 \cdot \text{CL}$	$5.370 + 2.422 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.183	$0.168 + 0.008 \cdot \text{SL}$	$0.171 + 0.007 \cdot \text{SL}$	$0.165 + 0.007 \cdot \text{SL}$
	t_F	0.174	$0.159 + 0.007 \cdot \text{SL}$	$0.163 + 0.006 \cdot \text{SL}$	$0.165 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.034	$1.024 + 0.005 \cdot \text{SL}$	$1.028 + 0.004 \cdot \text{SL}$	$1.052 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.984	$0.973 + 0.005 \cdot \text{SL}$	$0.977 + 0.004 \cdot \text{SL}$	$1.006 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.173	$0.156 + 0.008 \cdot \text{SL}$	$0.161 + 0.007 \cdot \text{SL}$	$0.156 + 0.007 \cdot \text{SL}$
	t_F	0.162	$0.147 + 0.008 \cdot \text{SL}$	$0.151 + 0.006 \cdot \text{SL}$	$0.154 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.760	$0.750 + 0.005 \cdot \text{SL}$	$0.754 + 0.004 \cdot \text{SL}$	$0.777 + 0.003 \cdot \text{SL}$
	t_{PHL}	0.737	$0.726 + 0.005 \cdot \text{SL}$	$0.731 + 0.004 \cdot \text{SL}$	$0.758 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PSOSCK1/K2/M1/M2

Oscillator Cell with Enable

Switching Characteristics

PSOSCM1

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	17.123	$0.623 + 0.330 \cdot \text{CL}$	$0.771 + 0.327 \cdot \text{CL}$	$0.726 + 0.328 \cdot \text{CL}$
	t_F	14.433	$0.838 + 0.272 \cdot \text{CL}$	$0.601 + 0.277 \cdot \text{CL}$	$0.520 + 0.278 \cdot \text{CL}$
	t_{PLH}	8.392	$1.252 + 0.143 \cdot \text{CL}$	$1.187 + 0.144 \cdot \text{CL}$	$1.210 + 0.144 \cdot \text{CL}$
	t_{PHL}	7.916	$1.254 + 0.133 \cdot \text{CL}$	$1.215 + 0.134 \cdot \text{CL}$	$1.264 + 0.133 \cdot \text{CL}$
E to PADY	t_R	17.057	$0.557 + 0.330 \cdot \text{CL}$	$0.597 + 0.329 \cdot \text{CL}$	$0.738 + 0.327 \cdot \text{CL}$
	t_F	14.461	$0.695 + 0.275 \cdot \text{CL}$	$0.651 + 0.276 \cdot \text{CL}$	$0.576 + 0.277 \cdot \text{CL}$
	t_{PLH}	8.003	$0.780 + 0.144 \cdot \text{CL}$	$0.823 + 0.144 \cdot \text{CL}$	$0.826 + 0.144 \cdot \text{CL}$
	t_{PHL}	7.640	$0.925 + 0.134 \cdot \text{CL}$	$0.937 + 0.134 \cdot \text{CL}$	$0.986 + 0.133 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.259	$0.229 + 0.015 \cdot \text{SL}$	$0.224 + 0.016 \cdot \text{SL}$	$0.192 + 0.017 \cdot \text{SL}$
	t_F	0.235	$0.198 + 0.018 \cdot \text{SL}$	$0.200 + 0.018 \cdot \text{SL}$	$0.179 + 0.018 \cdot \text{SL}$
	t_{PLH}	1.022	$1.003 + 0.009 \cdot \text{SL}$	$1.008 + 0.008 \cdot \text{SL}$	$1.021 + 0.008 \cdot \text{SL}$
	t_{PHL}	1.065	$1.043 + 0.011 \cdot \text{SL}$	$1.048 + 0.010 \cdot \text{SL}$	$1.065 + 0.009 \cdot \text{SL}$
E to YN	t_R	0.252	$0.222 + 0.015 \cdot \text{SL}$	$0.217 + 0.017 \cdot \text{SL}$	$0.188 + 0.017 \cdot \text{SL}$
	t_F	0.228	$0.192 + 0.018 \cdot \text{SL}$	$0.192 + 0.018 \cdot \text{SL}$	$0.174 + 0.018 \cdot \text{SL}$
	t_{PLH}	0.825	$0.807 + 0.009 \cdot \text{SL}$	$0.811 + 0.008 \cdot \text{SL}$	$0.823 + 0.008 \cdot \text{SL}$
	t_{PHL}	0.989	$0.966 + 0.011 \cdot \text{SL}$	$0.971 + 0.010 \cdot \text{SL}$	$0.986 + 0.009 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PSOSCK1/K2/M1/M2

Oscillator Cell with Enable

Switching Characteristics

PSOSCM2

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	4.764	$0.945 + 0.076 \cdot \text{CL}$	$1.199 + 0.071 \cdot \text{CL}$	$0.774 + 0.077 \cdot \text{CL}$
	t_F	4.163	$1.162 + 0.060 \cdot \text{CL}$	$0.909 + 0.065 \cdot \text{CL}$	$0.914 + 0.065 \cdot \text{CL}$
	t_{PLH}	3.306	$1.509 + 0.036 \cdot \text{CL}$	$1.509 + 0.036 \cdot \text{CL}$	$1.556 + 0.035 \cdot \text{CL}$
	t_{PHL}	3.235	$1.479 + 0.035 \cdot \text{CL}$	$1.541 + 0.034 \cdot \text{CL}$	$1.581 + 0.033 \cdot \text{CL}$
E to PADY	t_R	4.631	$0.496 + 0.083 \cdot \text{CL}$	$0.768 + 0.077 \cdot \text{CL}$	$0.667 + 0.079 \cdot \text{CL}$
	t_F	3.953	$0.486 + 0.069 \cdot \text{CL}$	$0.520 + 0.069 \cdot \text{CL}$	$0.462 + 0.069 \cdot \text{CL}$
	t_{PLH}	2.971	$1.152 + 0.036 \cdot \text{CL}$	$1.177 + 0.036 \cdot \text{CL}$	$1.139 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.245	$1.505 + 0.035 \cdot \text{CL}$	$1.565 + 0.034 \cdot \text{CL}$	$1.577 + 0.033 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.094	$0.083 + 0.005 \cdot \text{SL}$	$0.083 + 0.005 \cdot \text{SL}$	$0.078 + 0.005 \cdot \text{SL}$
	t_F	0.097	$0.087 + 0.005 \cdot \text{SL}$	$0.085 + 0.005 \cdot \text{SL}$	$0.079 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.123	$1.117 + 0.003 \cdot \text{SL}$	$1.118 + 0.003 \cdot \text{SL}$	$1.122 + 0.002 \cdot \text{SL}$
	t_{PHL}	1.082	$1.074 + 0.004 \cdot \text{SL}$	$1.076 + 0.003 \cdot \text{SL}$	$1.083 + 0.003 \cdot \text{SL}$
E to YN	t_R	0.086	$0.075 + 0.005 \cdot \text{SL}$	$0.075 + 0.005 \cdot \text{SL}$	$0.074 + 0.005 \cdot \text{SL}$
	t_F	0.088	$0.077 + 0.006 \cdot \text{SL}$	$0.077 + 0.006 \cdot \text{SL}$	$0.072 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.928	$0.922 + 0.003 \cdot \text{SL}$	$0.923 + 0.003 \cdot \text{SL}$	$0.926 + 0.002 \cdot \text{SL}$
	t_{PHL}	1.263	$1.255 + 0.004 \cdot \text{SL}$	$1.257 + 0.003 \cdot \text{SL}$	$1.262 + 0.003 \cdot \text{SL}$

*Group1 : SL < 3, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

Overview

PCI buffers are designed for PCI local bus application which is intended for high-performance 32-bit or 64-bit bus architecture.

SEC supports PCI input, output and bi-directional buffers for 3.3V and 5V signaling environment.

Features

- 0.24μm, low-power, high performance CMOS technology
- Input, output, and bi-directional PCI buffers
- PCI local bus specification rev2.1 compliant
- Operating at up to 66MHz, including 33MHz
- Electrically compliant interface in 3.3V and 5V bus environments

Description

These PCI buffers are designed for 3.3V and 5V environments. These buffers are compliant with the PCI local bus specification rev2.1. The PCI buffers for 66MHz can be available in 33MHz interface, but require more power pads due to their fast and noisy characteristics. The 5V tolerant PCI buffers can be used for 33MHz, 5V environment. These tolerant PCI buffers require 5V power for bulk of PMOS driver for 5V bus environment or 3.3V power for 3.3V environment. The 5V tolerant PCI drivers support 5V environment while EN5V is low. Although tolerant PCI buffers support 5V environment, they do not drive 5V.

NOTE: If you want to use PCI buffers, please contact SEC.

Cell List

Cell Name	Description	Operating Frequency	Operating Voltage
PTBPCI	Bi-direction	Up to 33MHz at 5V signaling ^(note1) Up to 66MHz at 3.3V signaling	3.3V
PTOPCI	Driver	Up to 33MHz at 5V signaling Up to 66MHz at 3.3V signaling	
PTIPCI	Receiver	Up to 33MHz at 5V signaling Up to 66MHz at 3.3V signaling	

NOTE1: 3.3V signaling conditions: EN5V=high, VIO=3.3V, 5V tolerant is not supported.
5V signaling conditions: EN5V=low, VIO=5V, and 5V tolerant is supported.

Power Cell Name	Description
VDD2I_PCI	2.5V Power cell for internal core and PCI I/Os
VDD3OP_PCI	3.3V Power cell for PCI I/Os
VDD5O_PCI	VIO(3.3V or 5V) Power cell for PCI I/Os ^(note2)
VSSI_PCI	Gnd Power cell for internal core; not used for PCI I/Os
VSSOP_PCI	Gnd Power cell for PCI I/Os

NOTE2: In 3.3V signaling, VIO is 3.3V, which is provided through the VDD5O_PCI power cell.
In 5V signaling, VIO is 5V, which is provided through the VDD5O_PCI power cell.

PCI BUFFERS

Option ^(note3)

Cell Name	Description
VDET_111PCI	3.3V or 5V voltage detector

NOTE3: Voltage detector circuit will automatically set the EN5V pin either high or low according to VIO voltage level.

Electrical Characteristics


DC Characteristics

Symbol	Parameter	3.3V Signaling			5V Signaling			Unit
		Condition	Min	Max	Condition	Min	Max	
V _{CC}	Supply Voltage		3.0	3.6		3.0	3.6	V
V _{IO}	Vdd5o Voltage		V _{CC}			4.75	5.25	V
V _{ih}	Input high voltage		0.47V _{CC}	V _{CC} +0.5		1.9	V _{IO} +0.5	V
V _{il}	Input low voltage		− 0.5	0.33V _{CC}		− 0.5	0.9	V
I _i	Input leakage current	0 < V _{IN} < V _{CC}	−10	10	0 < V _{IN} < V _{IO}	−70	70	μA
V _{oh}	Output high voltage	I _{OUT} = −500 μA	0.9V _{CC}	−	I _{OUT} = −2mA	2.4	−	V
V _{ol}	Output low voltage	I _{OUT} = 1500 μA	−	0.1V _{CC}	I _{OUT} = 6mA	−	0.55	V

AC Characteristics

Symbol	Parameter	3.3V Signaling			5V Signaling			Unit
		Condition	Min	Max	Condition	Min	Max	
I _{oh} (AC)	Switching current high	V _{OUT} = 0.3V _{CC}	-12V _{CC}		V _{OUT} = 1.4V	-44		mA
		V _{OUT} = 0.7V _{CC}		-32V _{CC}	V _{OUT} = 2.4V	-2.33		
		V _{OUT} = 0.9V _{CC}	-1.71V _{CC}		V _{OUT} = 3.0V		-142	
I _{ol} (AC)	Switching current low	V _{OUT} = 0.6V _{CC}	16V _{CC}		V _{OUT} = 2.2V	95		mA
		V _{OUT} = 0.1V _{CC}	2.67V _{CC}		V _{OUT} = 0.55V	23.9		
		V _{OUT} = 0.18V _{CC}		38V _{CC}	V _{OUT} = 0.71V		206	
I _{cl}	Low clamp current	-3 < V _{IN} ≤ -1	-25 + (V _{IN} + 1) / 0.015		-5 < V _{IN} ≤ -1	-25 + (V _{IN} + 1) / 0.015		mA
I _{ch}	High clamp current	V _{CC} +1 ≤ V _{IN} < V _{CC} +4	25 + (V _{IN} - V _{CC} -1) / 0.015					mA
T _r	Output rise time	0.3V _{CC} to 0.6V _{CC}	1.0	4.0	0.4V to 2.4V	1.0	5.0	V/ns
T _f	Output fall time	0.6V _{CC} to 0.3V _{CC}	1.0	4.0	2.4V to 0.4V	1.0	5.0	V/ns

Logic Symbol



Truth Table

Input Truth Table			
PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PTIPCI


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.271	$0.261 + 0.005 \cdot \text{SL}$	$0.261 + 0.005 \cdot \text{SL}$	$0.265 + 0.005 \cdot \text{SL}$
	t_F	0.135	$0.131 + 0.002 \cdot \text{SL}$	$0.132 + 0.002 \cdot \text{SL}$	$0.143 + 0.001 \cdot \text{SL}$
	t_{PLH}	0.322	$0.318 + 0.002 \cdot \text{SL}$	$0.319 + 0.002 \cdot \text{SL}$	$0.326 + 0.002 \cdot \text{SL}$
	t_{PHL}	0.798	$0.793 + 0.002 \cdot \text{SL}$	$0.795 + 0.002 \cdot \text{SL}$	$0.818 + 0.001 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PTOPCI

5V-tolerant PCI Output Buffers

Logic Symbol



Truth Table

Output Truth Table			
A	EN	TN	PAD
0	0	1	0
1	0	1	1
x	1	x	Hi-Z
x	x	0	Hi-Z


Switching Characteristics (Typical process, 25°C, 2.5V, 3.3V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

PTOPCI

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	2.110	$0.782 + 0.026 \cdot \text{CL}$	$0.764 + 0.027 \cdot \text{CL}$	$0.706 + 0.028 \cdot \text{CL}$
	t_F	2.513	$0.718 + 0.035 \cdot \text{CL}$	$0.675 + 0.037 \cdot \text{CL}$	$0.611 + 0.038 \cdot \text{CL}$
	t_{PLH}	2.452	$1.374 + 0.024 \cdot \text{CL}$	$1.557 + 0.018 \cdot \text{CL}$	$1.663 + 0.016 \cdot \text{CL}$
	t_{PHL}	2.087	$0.994 + 0.022 \cdot \text{CL}$	$1.039 + 0.021 \cdot \text{CL}$	$1.069 + 0.020 \cdot \text{CL}$
TN to PAD	t_R	2.111	$0.792 + 0.026 \cdot \text{CL}$	$0.767 + 0.027 \cdot \text{CL}$	$0.707 + 0.028 \cdot \text{CL}$
	t_F	2.289	$0.355 + 0.039 \cdot \text{CL}$	$0.349 + 0.039 \cdot \text{CL}$	$0.337 + 0.039 \cdot \text{CL}$
	t_{PLH}	2.635	$1.554 + 0.024 \cdot \text{CL}$	$1.739 + 0.018 \cdot \text{CL}$	$1.845 + 0.016 \cdot \text{CL}$
	t_{PHL}	2.081	$0.981 + 0.023 \cdot \text{CL}$	$1.035 + 0.021 \cdot \text{CL}$	$1.060 + 0.020 \cdot \text{CL}$
	t_{PLZ}	0.727	$0.727 + 0.000 \cdot \text{CL}$	$0.727 + 0.000 \cdot \text{CL}$	$0.727 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.274	$1.274 + 0.000 \cdot \text{CL}$	$1.273 + 0.000 \cdot \text{CL}$	$1.273 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	2.111	$0.792 + 0.026 \cdot \text{CL}$	$0.768 + 0.027 \cdot \text{CL}$	$0.707 + 0.028 \cdot \text{CL}$
	t_F	2.289	$0.354 + 0.039 \cdot \text{CL}$	$0.349 + 0.039 \cdot \text{CL}$	$0.337 + 0.039 \cdot \text{CL}$
	t_{PLH}	2.693	$1.612 + 0.024 \cdot \text{CL}$	$1.798 + 0.018 \cdot \text{CL}$	$1.904 + 0.016 \cdot \text{CL}$
	t_{PHL}	2.139	$1.039 + 0.023 \cdot \text{CL}$	$1.094 + 0.021 \cdot \text{CL}$	$1.118 + 0.020 \cdot \text{CL}$
	t_{PLZ}	0.742	$0.742 + 0.000 \cdot \text{CL}$	$0.742 + 0.000 \cdot \text{CL}$	$0.742 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.289	$1.289 + 0.000 \cdot \text{CL}$	$1.288 + 0.000 \cdot \text{CL}$	$1.288 + 0.000 \cdot \text{CL}$

*Group1 : CL < 30, *Group2 : $30 \leq \text{CL} \leq 50$, *Group3 : $50 < \text{CL}$

Logic Symbol



Truth Table

Input Truth Table


PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Output Truth Table

A	EN	TN	PAD
0	0	1	0
1	0	1	1
x	1	x	Hi-Z
x	x	0	Hi-Z

Option:

Logic Symbol



Truth Table

Input		Output
A	PD	Y
3.3V		1
5V		0
X	0	Last Y
X	1	Last Y

Cell Data

Cell Name	Detecting Voltage
vdet_110pci	3.3V, 5V

USB (Universal Serial Bus) I/O Buffers *(Under Development)*

Overview

USB I/O buffer consists of a differential input receiver, a differential output driver, two single-ended receivers, and two pads. The differential input receiver has the 0.8V ~ 2.5V common mode input voltage range and both of the two single-ended receivers have 0.8V and 2.0V as their low and high input threshold voltages, V_{IL} , V_{IH} , respectively.

For low power consumption in a stand-by mode, the suspend pin (SUSPND) of the receiver and the driver should be in the high state. The differential output drivers have a Low/Full speed control pin (SPEED) to select the operation speed and have Output Enable Negative pin (OEN) to achieve a bi-directional half duplex operation.

Features

- Complies with universal serial bus specification 1.0
- Supports 12Mbps “Full speed” and 1.5Mbps “Low speed” serial data transmission
- Supports both “Full speed” and “Low speed” Design Kits
- Supports both “Full speed only” and “Low speed only” cells to reduce silicon area

Electrical Specifications

DC Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2)	Min	Max	Unit
Supply Current					
Suspend Device	I _{CCS}			10	μA
Leakage Current					
Hi-Z State Input Leakage	I _{LO}	0V < V _{IN} < 3.3V	−10	10	μA
Input Levels					
Differential Input Sensitivity	V _{DI}	I (D+) – (D-) I	0.2		V
Differential Common Mode Range	V _{CM}	Includes V _{DI} range	0.8	2.5	
Single Ended Receiver Threshold	V _{SE}		0.8	2.0	
Output Levels					
Static Output Low	V _{OL}	RL of 1.5KΩ to 3.6V		0.3	V
Static Output High	V _{OH}	RL of 15KΩ to GND	2.8	3.6	
Capacitance					
Transceiver Capacitance	C _{IN}	Pin to GND		20	pF

Full Speed Output Buffer Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2, 3)	Min	Max	Unit
Driver Characteristics					
Transition Time		Notes 5 and Figure 1			ns
Rise Time	T_R	CL = 50pF	4.0	20.0	
Fall Time	T_F	CL = 50pF	4.0	20.0	
Rise/Fall Time Matching	T_{RFM}	(T_R/T_F)	90	110	%
Output Signal Crossover Voltage	V_{CRS}		1.3	2.0	V
Drive Output Resistance	Z_{DRV}	Steady state drive	28	43	Ω

USB (Universal Serial Bus) I/O Buffers *(Under Development)*


Low Speed Output Buffer Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2, 4)	Min	Max	Unit
Driver Characteristics					
Transition Time Rise Time	T_R	Notes 5 and Figure 1 $C_L = 50\text{pF}$ $C_L = 350\text{pF}$	75	300	ns
Fall Time	T_F	$C_L = 50\text{pF}$ $C_L = 350\text{pF}$	75	300	
Rise/Fall Time Matching	T_{RFM}	(T_R/T_F)	80	120	%
Output Signal Crossover Voltage	V_{CRS}		1.3	2.0	V

NOTES:

1. All voltages are measured from the local ground potential, unless otherwise specified.
2. All timings use a capacitive load (C_L) to ground of 50pF, unless otherwise specified.
3. Full speed timings have a 1.5K Ω pull-up to 2.8V on the DP data line.
4. Low speed timings have a 1.5K Ω pull-up to 2.8V on the DN data line.
5. Measured from 10% to 90% of the data signal.

FIGURE 1: Data Signal Rise and Fall Time



Cell List


Cell Name	Function Description
PBUSB/PBUSB1	Low/Full speed USB Buffer (1.5 MHz/12 MHz select)
PBUSB_LS	Low speed only USB Buffer (1.5 MHz only, reduced cell size)
PBUSB_FS	Full speed only USB Buffer (12 MHz only, reduced cell size)

PBUSB/PBUSB1/PBUSB_LS/PBUSB_FS (Under Development)

Universal Serial Bus I/O Buffer

PBUSB/PBUSB1

Symbol



Pin Connection

Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

Cell Structure


PBUSB = PISER + PICDR + POTLS + POTFS
PBUSB1 = PISER + PICDR + POTLS + POTFS

There only exists PBUSB not PBUSB1 in the physical DB. The division of cell name (PBUSB/PBUSB1) is caused to notify their different working-mode. PBUSB selects POTLS (SPEED=0) to work on the Low Speed Mode. PBUSB1 selects POTFS (SPEED=1) to work on the Full Speed Mode. In case that the physical area is critical, Low speed only (PBUSB_LS) or Full speed only (PBUSB_FS) USB IO cell would be provided at the request of the customer, i.e.

PBUSB_LS = PISER + PICDR + POTLS
PBUSB_FS = PISER + PICDR + POTFS

PBUSB_LS

Symbol



Pin Connection


Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

PBUSB/PBUSB1/PBUSB_LS/PBUSB_FS (Under Development)

Universal Serial Bus I/O Buffer

PBUSB_FS

Symbol




Pin Connection

Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

PISER

Single-Ended Receiver

Symbol



Pin Connection

Input	Output
DP	RXDP
DN	RXDN

Truth Table

DP	DN	RXDP	RXDN
0	0	0	0
0	1	0	1
1	0	1	0
1	1	1	1

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.80\text{ns}$, SL: Standard Load)

PISER

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
DP to RXDP	t_R	0.109	$0.094 + 0.008 \cdot \text{SL}$	$0.092 + 0.008 \cdot \text{SL}$	$0.080 + 0.008 \cdot \text{SL}$
	t_F	0.103	$0.086 + 0.008 \cdot \text{SL}$	$0.087 + 0.008 \cdot \text{SL}$	$0.076 + 0.008 \cdot \text{SL}$
	t_{PLH}	0.598	$0.587 + 0.005 \cdot \text{SL}$	$0.591 + 0.004 \cdot \text{SL}$	$0.599 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.585	$0.573 + 0.006 \cdot \text{SL}$	$0.579 + 0.005 \cdot \text{SL}$	$0.595 + 0.004 \cdot \text{SL}$
DN to RXDN	t_R	0.109	$0.094 + 0.008 \cdot \text{SL}$	$0.092 + 0.008 \cdot \text{SL}$	$0.080 + 0.008 \cdot \text{SL}$
	t_F	0.103	$0.086 + 0.008 \cdot \text{SL}$	$0.087 + 0.008 \cdot \text{SL}$	$0.076 + 0.008 \cdot \text{SL}$
	t_{PLH}	0.598	$0.587 + 0.005 \cdot \text{SL}$	$0.591 + 0.004 \cdot \text{SL}$	$0.599 + 0.004 \cdot \text{SL}$
	t_{PHL}	0.585	$0.573 + 0.006 \cdot \text{SL}$	$0.579 + 0.005 \cdot \text{SL}$	$0.595 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 60$, *Group3 : $60 < \text{SL}$


PBUSB/PBUSB1/PBUSB_LS/PBUSB_FS (Under Development)

Universal Serial Bus I/O Buffer

PICDR

Differential Receiver

Symbol



Pin Connection

Input	Output
DP DN SUSPND	RXD

Truth Table

DP	DN	SUSPND	RXD
0	0	0	0
0	1	0	0
1	0	0	1
1	1	0	x
x	x	1	0

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.80\text{ns}$, SL: Standard Load)

PICDR


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
DP to RXD	t_R	0.198	$0.179 + 0.010 \cdot \text{SL}$	$0.186 + 0.008 \cdot \text{SL}$	$0.168 + 0.008 \cdot \text{SL}$
	t_F	0.188	$0.167 + 0.010 \cdot \text{SL}$	$0.187 + 0.006 \cdot \text{SL}$	$0.252 + 0.005 \cdot \text{SL}$
	t_{PLH}	9.606	$9.588 + 0.009 \cdot \text{SL}$	$9.604 + 0.005 \cdot \text{SL}$	$9.656 + 0.004 \cdot \text{SL}$
	t_{PHL}	8.896	$8.876 + 0.010 \cdot \text{SL}$	$8.897 + 0.005 \cdot \text{SL}$	$9.013 + 0.003 \cdot \text{SL}$
DN to RXD	t_R	0.213	$0.192 + 0.010 \cdot \text{SL}$	$0.203 + 0.008 \cdot \text{SL}$	$0.190 + 0.008 \cdot \text{SL}$
	t_F	0.219	$0.195 + 0.012 \cdot \text{SL}$	$0.219 + 0.006 \cdot \text{SL}$	$0.303 + 0.005 \cdot \text{SL}$
	t_{PLH}	3.600	$3.578 + 0.011 \cdot \text{SL}$	$3.602 + 0.006 \cdot \text{SL}$	$3.677 + 0.004 \cdot \text{SL}$
	t_{PHL}	4.510	$4.487 + 0.011 \cdot \text{SL}$	$4.510 + 0.006 \cdot \text{SL}$	$4.647 + 0.004 \cdot \text{SL}$
SUSPND to RXD	t_R	0.168	$0.150 + 0.009 \cdot \text{SL}$	$0.154 + 0.008 \cdot \text{SL}$	$0.133 + 0.008 \cdot \text{SL}$
	t_F	0.226	$0.200 + 0.013 \cdot \text{SL}$	$0.226 + 0.007 \cdot \text{SL}$	$0.337 + 0.005 \cdot \text{SL}$
	t_{PLH}	1.360	$1.344 + 0.008 \cdot \text{SL}$	$1.358 + 0.005 \cdot \text{SL}$	$1.404 + 0.004 \cdot \text{SL}$
	t_{PHL}	1.628	$1.604 + 0.012 \cdot \text{SL}$	$1.628 + 0.007 \cdot \text{SL}$	$1.779 + 0.004 \cdot \text{SL}$

*Group1 : $\text{SL} < 4$, *Group2 : $4 \leq \text{SL} \leq 60$, *Group3 : $60 < \text{SL}$

POTLS

Tri-State Output Buffer with Low Speed

Symbol



Pin Connection

Input	Output
TXDP	DP
TXDN	DN
SPEED	
SUSPND	
OEN	

Truth Table

TXDP	TXDN	SUSPND	OEN	SPEED	DP	DN
0	0	0	0	0	0	0
0	1	0	0	0	0	1
1	0	0	0	0	1	0
1	1	0	0	0	1	1
x	x	1	x	x	Hi-Z	Hi-Z
x	x	x	1	x	Hi-Z	Hi-Z
x	x	x	x	1	Hi-Z	Hi-Z

NOTE: SUSPND is the Suspend Mode control signal for the output driver. SUSPND=1 or OEN=1, both Low speed driver and Full speed driver are suspended. SPEED is the Low/Full speed output mode selecting signal, SPEED=0, SUSPND=0, OEN=0 Low speed mode transmitting.

PBUSB/PBUSB1/PBUSB_LS/PBUSB_FS (Under Development)

Universal Serial Bus I/O Buffer

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.80\text{ns}$, CL: Capacitive Load)

POTLS


Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TXDP to DP	t_R	116.330	$115.030 + 0.026 \cdot \text{CL}$	$120.870 + 0.000 \cdot \text{CL}$	$122.130 + 0.000 \cdot \text{CL}$
	t_F	135.200	$135.200 + 0.000 \cdot \text{CL}$	$122.110 + 0.053 \cdot \text{CL}$	$135.790 + 0.000 \cdot \text{CL}$
	t_{PLH}	111.850	$111.850 + 0.000 \cdot \text{CL}$	$105.020 + 0.078 \cdot \text{CL}$	$104.630 + 0.083 \cdot \text{CL}$
	t_{PHL}	112.920	$108.320 + 0.092 \cdot \text{CL}$	$119.180 + 0.000 \cdot \text{CL}$	$109.490 + 0.004 \cdot \text{CL}$
OEN to DP	t_R	114.230	$114.230 + 0.000 \cdot \text{CL}$	$113.240 + 0.009 \cdot \text{CL}$	$113.210 + 0.009 \cdot \text{CL}$
	t_F	129.430	$129.430 + 0.000 \cdot \text{CL}$	$131.350 + 0.000 \cdot \text{CL}$	$127.390 + 0.000 \cdot \text{CL}$
	t_{PLH}	79.258	$79.258 + 0.000 \cdot \text{CL}$	$77.803 + 0.028 \cdot \text{CL}$	$73.459 + 0.086 \cdot \text{CL}$
	t_{PHL}	113.000	$108.925 + 0.081 \cdot \text{CL}$	$110.840 + 0.043 \cdot \text{CL}$	$119.360 + 0.000 \cdot \text{CL}$
	t_{PLZ}	2.272	$2.272 + 0.000 \cdot \text{CL}$	$2.272 + 0.000 \cdot \text{CL}$	$2.272 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.474	$2.474 + 0.000 \cdot \text{CL}$	$2.473 + 0.000 \cdot \text{CL}$	$2.474 + 0.000 \cdot \text{CL}$
SPEED to DP	t_R	114.230	$114.230 + 0.000 \cdot \text{CL}$	$113.220 + 0.009 \cdot \text{CL}$	$113.190 + 0.010 \cdot \text{CL}$
	t_F	129.355	$129.355 + 0.000 \cdot \text{CL}$	$131.370 + 0.000 \cdot \text{CL}$	$127.380 + 0.000 \cdot \text{CL}$
	t_{PLH}	79.233	$79.233 + 0.000 \cdot \text{CL}$	$77.772 + 0.028 \cdot \text{CL}$	$73.473 + 0.086 \cdot \text{CL}$
	t_{PHL}	113.010	$108.910 + 0.082 \cdot \text{CL}$	$110.990 + 0.040 \cdot \text{CL}$	$119.270 + 0.000 \cdot \text{CL}$
	t_{PLZ}	2.261	$2.261 + 0.000 \cdot \text{CL}$	$2.261 + 0.000 \cdot \text{CL}$	$2.261 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.455	$2.455 + 0.000 \cdot \text{CL}$	$2.458 + 0.000 \cdot \text{CL}$	$2.454 + 0.000 \cdot \text{CL}$
SUSPND to DP	t_R	114.230	$114.230 + 0.000 \cdot \text{CL}$	$113.220 + 0.009 \cdot \text{CL}$	$113.190 + 0.010 \cdot \text{CL}$
	t_F	129.395	$129.395 + 0.000 \cdot \text{CL}$	$131.340 + 0.000 \cdot \text{CL}$	$127.380 + 0.000 \cdot \text{CL}$
	t_{PLH}	79.047	$79.047 + 0.000 \cdot \text{CL}$	$77.598 + 0.028 \cdot \text{CL}$	$73.290 + 0.086 \cdot \text{CL}$
	t_{PHL}	112.830	$108.730 + 0.082 \cdot \text{CL}$	$110.830 + 0.040 \cdot \text{CL}$	$119.050 + 0.000 \cdot \text{CL}$
	t_{PLZ}	2.084	$2.084 + 0.000 \cdot \text{CL}$	$2.084 + 0.000 \cdot \text{CL}$	$2.084 + 0.000 \cdot \text{CL}$
	t_{PHZ}	2.284	$2.283 + 0.000 \cdot \text{CL}$	$2.285 + 0.000 \cdot \text{CL}$	$2.284 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POTFS

Tri-State Output Buffer with Full Speed

Symbol



Pin Connection

Input	Output
TXDP	DP
TXDN	DN
SPEED	
SUSPND	
OEN	

Truth Table

TXDP	TXDN	SUSPND	OEN	SPEED	DP	DN
0	0	0	0	1	0	0
0	1	0	0	1	0	1
1	0	0	0	1	1	0
1	1	0	0	1	1	1
x	x	1	x	x	Hi-z	Hi-z
x	x	x	1	x	Hi-z	Hi-z
x	x	x	x	0	Hi-z	Hi-z

NOTE: SUSPND is the Suspend Mode control signal for the output driver. SUSPND=1 or OEN=1, both Low speed driver and Full speed driver are suspended. SPEED is the Low/Full speed output mode selecting signal, SPEED=1, SUSPND=0, OEN=0 Low speed mode transmitting.

PBUSB/PBUSB1/PBUSB_LS/PBUSB_FS (Under Development)

Universal Serial Bus I/O Buffer

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

POTFS

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TXDP to DP	t_R	7.537	$4.664 + 0.057 \cdot \text{CL}$	$5.798 + 0.035 \cdot \text{CL}$	$5.770 + 0.035 \cdot \text{CL}$
	t_F	7.794	$4.733 + 0.061 \cdot \text{CL}$	$5.879 + 0.038 \cdot \text{CL}$	$5.900 + 0.038 \cdot \text{CL}$
	t_{PLH}	7.961	$5.205 + 0.055 \cdot \text{CL}$	$6.073 + 0.038 \cdot \text{CL}$	$5.998 + 0.039 \cdot \text{CL}$
	t_{PHL}	7.565	$5.466 + 0.042 \cdot \text{CL}$	$5.457 + 0.042 \cdot \text{CL}$	$6.008 + 0.035 \cdot \text{CL}$
OEN to DP	t_R	7.878	$5.429 + 0.049 \cdot \text{CL}$	$5.129 + 0.055 \cdot \text{CL}$	$5.407 + 0.051 \cdot \text{CL}$
	t_F	7.602	$4.896 + 0.054 \cdot \text{CL}$	$4.948 + 0.053 \cdot \text{CL}$	$5.180 + 0.050 \cdot \text{CL}$
	t_{PLH}	7.628	$5.244 + 0.048 \cdot \text{CL}$	$4.558 + 0.061 \cdot \text{CL}$	$5.973 + 0.043 \cdot \text{CL}$
	t_{PHL}	7.809	$5.049 + 0.055 \cdot \text{CL}$	$5.525 + 0.046 \cdot \text{CL}$	$4.734 + 0.056 \cdot \text{CL}$
	t_{PLZ}	1.251	$1.251 + 0.000 \cdot \text{CL}$	$1.251 + 0.000 \cdot \text{CL}$	$1.248 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.851	$1.850 + 0.000 \cdot \text{CL}$	$1.851 + 0.000 \cdot \text{CL}$	$1.851 + 0.000 \cdot \text{CL}$
SPEED to DP	t_R	7.678	$3.979 + 0.074 \cdot \text{CL}$	$5.169 + 0.050 \cdot \text{CL}$	$5.687 + 0.043 \cdot \text{CL}$
	t_F	7.842	$3.786 + 0.081 \cdot \text{CL}$	$5.228 + 0.052 \cdot \text{CL}$	$5.699 + 0.046 \cdot \text{CL}$
	t_{PLH}	7.969	$5.082 + 0.058 \cdot \text{CL}$	$5.499 + 0.049 \cdot \text{CL}$	$5.714 + 0.047 \cdot \text{CL}$
	t_{PHL}	7.830	$5.117 + 0.054 \cdot \text{CL}$	$5.686 + 0.043 \cdot \text{CL}$	$5.014 + 0.052 \cdot \text{CL}$
SUSPND to DP	t_R	7.578	$5.329 + 0.045 \cdot \text{CL}$	$5.629 + 0.039 \cdot \text{CL}$	$5.906 + 0.035 \cdot \text{CL}$
	t_F	7.882	$5.476 + 0.048 \cdot \text{CL}$	$5.788 + 0.042 \cdot \text{CL}$	$6.080 + 0.038 \cdot \text{CL}$
	t_{PLH}	7.940	$5.053 + 0.058 \cdot \text{CL}$	$5.470 + 0.049 \cdot \text{CL}$	$5.985 + 0.043 \cdot \text{CL}$
	t_{PHL}	7.621	$4.605 + 0.060 \cdot \text{CL}$	$5.257 + 0.047 \cdot \text{CL}$	$5.309 + 0.047 \cdot \text{CL}$
	t_{PLZ}	1.046	$1.046 + 0.000 \cdot \text{CL}$	$1.045 + 0.000 \cdot \text{CL}$	$1.046 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.646	$1.646 + 0.000 \cdot \text{CL}$	$1.646 + 0.000 \cdot \text{CL}$	$1.646 + 0.000 \cdot \text{CL}$


*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POWER PADS

Cell List


Cell Name		Function Description
VDD Power Pads	VSS Power Pads	
VDD2I	VSS2I	2.5V Internal
VDD2P	VSS2P	2.5V Pre-Driver
VDD2O	VSS2O	2.5V Output-Driver
VDD2IP	VSS2IP	2.5V Internal and Pre-Driver
VDD2OP	VSS2OP	2.5V Output-Driver and Pre-Driver
VDD2T	VSS2T	2.5V Total
VDD3P	VSS3P	3.3V Pre-Driver
VDD3O	VSS3O	3.3V Output-Driver
VDD3OP	VSS3OP	3.3V Output-Driver and Pre-Driver

Logic Symbol



Cell Name		Function Description
VDD Power Pads	VSS Power Pads	
VDD2I_ABB	VSS2I_ABB	2.5V Internal with Separate Bulk Bias
VDD2OP_ABB	VSS2OP_ABB	2.5V Pre-Driver and Output-Driver with Separate Bulk Bias
VDD2T_ABB	VSS2T_ABB	2.5V Total with Separate Bulk Bias
	VBB_ABB	Bulk Bias Power Pad
	VSSBB_ABB	Bulk Bias and VSS Power Pad

Logic Symbol



ANALOG INTERFACE

Analog Input


Cell Name	Function Description
PIC_ABB	Analog CMOS Level Input Buffer Separate Bulk-Bias
PICC_ABB	Analog CMOS Level Input Buffer Separate Bulk-Bias and without Nand-Tree
PICEN_ABB	Analog CMOS Level Input Buffer with Enable Port and Separate Bulk-Bias

Analog Output

Cell Name	Function Description
POT1_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 1mA Drive
POT2_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 2mA Drive
POT4_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 4mA Drive
POT8_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 8mA Drive

Analog CMOS Level Input Buffers with Separate Bulk-Bias

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIC_ABB	3.620

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PIC_ABB


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.205	$0.186 + 0.010 \cdot \text{SL}$	$0.186 + 0.010 \cdot \text{SL}$	$0.166 + 0.010 \cdot \text{SL}$
	t_F	0.149	$0.136 + 0.006 \cdot \text{SL}$	$0.138 + 0.006 \cdot \text{SL}$	$0.125 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.051	$1.036 + 0.007 \cdot \text{SL}$	$1.042 + 0.005 \cdot \text{SL}$	$1.059 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.991	$0.979 + 0.006 \cdot \text{SL}$	$0.986 + 0.004 \cdot \text{SL}$	$1.014 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

PICC_ABB

Analog CMOS Level Input Buffers with Separate Bulk-Bias

Logic Symbol



Truth Table

PAD	Y
0	0
1	1

Switching Characteristics

(Typical process, 25 °C, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)


PICC_ABB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t _R	0.176	0.157 + 0.010*SL	0.157 + 0.009*SL	0.126 + 0.010*SL
	t _F	0.127	0.112 + 0.007*SL	0.119 + 0.006*SL	0.106 + 0.006*SL
	t _{PLH}	1.027	1.010 + 0.008*SL	1.019 + 0.006*SL	1.044 + 0.005*SL
	t _{PHL}	0.973	0.960 + 0.007*SL	0.969 + 0.004*SL	1.003 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≤ SL ≤ 45, *Group3 : 45 < SL

Analog CMOS Level Input Buffers with Enable Port and Separate Bulk-Bias

Logic Symbol



Truth Table

PAD	PI	EN	Y	PO
1	1	1	1	0
0	x	1	0	1
1	0	1	1	1
x	x	0	0	1

Standard Load (SL)

Cell Name	PI	EN
PICEN_ABB	2.897	2.897

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 3.00\text{ns}$, SL: Standard Load)

PICEN_ABB


Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.231	$0.211 + 0.010 \cdot \text{SL}$	$0.212 + 0.010 \cdot \text{SL}$	$0.198 + 0.010 \cdot \text{SL}$
	t_F	0.177	$0.164 + 0.007 \cdot \text{SL}$	$0.167 + 0.006 \cdot \text{SL}$	$0.166 + 0.006 \cdot \text{SL}$
	t_{PLH}	1.104	$1.088 + 0.008 \cdot \text{SL}$	$1.096 + 0.006 \cdot \text{SL}$	$1.128 + 0.005 \cdot \text{SL}$
	t_{PHL}	1.174	$1.160 + 0.007 \cdot \text{SL}$	$1.169 + 0.004 \cdot \text{SL}$	$1.212 + 0.003 \cdot \text{SL}$
EN to Y	t_R	0.176	$0.155 + 0.011 \cdot \text{SL}$	$0.156 + 0.010 \cdot \text{SL}$	$0.152 + 0.010 \cdot \text{SL}$
	t_F	0.131	$0.117 + 0.007 \cdot \text{SL}$	$0.120 + 0.006 \cdot \text{SL}$	$0.121 + 0.006 \cdot \text{SL}$
	t_{PLH}	0.315	$0.301 + 0.007 \cdot \text{SL}$	$0.306 + 0.005 \cdot \text{SL}$	$0.323 + 0.005 \cdot \text{SL}$
	t_{PHL}	0.329	$0.318 + 0.006 \cdot \text{SL}$	$0.323 + 0.004 \cdot \text{SL}$	$0.352 + 0.003 \cdot \text{SL}$

*Group1 : $\text{SL} < 3$, *Group2 : $3 \leq \text{SL} \leq 45$, *Group3 : $45 < \text{SL}$

POT1/2/4/8_ABB

Analog Tri-state Output Buffers with Enable Port and Separate Bulk-Bias

Logic Symbol



Truth Table

TN	EN	A	PAD
1	0	0	0
1	0	1	1
x	1	x	Hi - z
0	x	x	Hi - z

Standard Load (SL)

Cell Name	TN	EN	A
POT1_ABB	2.898	2.916	3.023
POT2_ABB	2.898	2.916	3.023
POT4_ABB	2.898	2.916	3.023
POT8_ABB	2.898	2.916	3.023

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

POT1_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	32.056	$1.759 + 0.606 \cdot \text{CL}$	$1.758 + 0.606 \cdot \text{CL}$	$1.761 + 0.606 \cdot \text{CL}$
	t_F	33.870	$1.873 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$
	t_{PLH}	16.015	$1.507 + 0.290 \cdot \text{CL}$	$1.507 + 0.290 \cdot \text{CL}$	$1.507 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.839	$1.729 + 0.322 \cdot \text{CL}$	$1.731 + 0.322 \cdot \text{CL}$	$1.731 + 0.322 \cdot \text{CL}$
TN to PAD	t_R	32.056	$1.759 + 0.606 \cdot \text{CL}$	$1.758 + 0.606 \cdot \text{CL}$	$1.761 + 0.606 \cdot \text{CL}$
	t_F	33.870	$1.873 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$
	t_{PLH}	16.063	$1.553 + 0.290 \cdot \text{CL}$	$1.557 + 0.290 \cdot \text{CL}$	$1.554 + 0.290 \cdot \text{CL}$
	t_{PHL}	17.962	$1.852 + 0.322 \cdot \text{CL}$	$1.854 + 0.322 \cdot \text{CL}$	$1.851 + 0.322 \cdot \text{CL}$
	t_{PLZ}	0.958	$0.958 + 0.000 \cdot \text{CL}$	$0.958 + 0.000 \cdot \text{CL}$	$0.958 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.662	$0.662 + 0.000 \cdot \text{CL}$	$0.662 + 0.000 \cdot \text{CL}$	$0.662 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	32.056	$1.759 + 0.606 \cdot \text{CL}$	$1.758 + 0.606 \cdot \text{CL}$	$1.761 + 0.606 \cdot \text{CL}$
	t_F	33.870	$1.873 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$	$1.872 + 0.640 \cdot \text{CL}$
	t_{PLH}	16.165	$1.658 + 0.290 \cdot \text{CL}$	$1.657 + 0.290 \cdot \text{CL}$	$1.660 + 0.290 \cdot \text{CL}$
	t_{PHL}	18.064	$1.957 + 0.322 \cdot \text{CL}$	$1.954 + 0.322 \cdot \text{CL}$	$1.957 + 0.322 \cdot \text{CL}$
	t_{PLZ}	1.000	$1.000 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$	$1.000 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.705	$0.705 + 0.000 \cdot \text{CL}$	$0.705 + 0.000 \cdot \text{CL}$	$0.705 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Analog Tri-state Output Buffers with Enable Port and Separate Bulk-Bias

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

POT2_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	16.047	$0.897 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$
	t_F	18.535	$1.010 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.431	$1.177 + 0.145 \cdot \text{CL}$	$1.177 + 0.145 \cdot \text{CL}$	$1.177 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.353	$1.235 + 0.182 \cdot \text{CL}$	$1.233 + 0.182 \cdot \text{CL}$	$1.236 + 0.182 \cdot \text{CL}$
TN to PAD	t_R	16.047	$0.897 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$
	t_F	18.535	$1.010 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.479	$1.224 + 0.145 \cdot \text{CL}$	$1.224 + 0.145 \cdot \text{CL}$	$1.228 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.477	$1.357 + 0.182 \cdot \text{CL}$	$1.357 + 0.182 \cdot \text{CL}$	$1.360 + 0.182 \cdot \text{CL}$
	t_{PLZ}	0.808	$0.808 + 0.000 \cdot \text{CL}$	$0.808 + 0.000 \cdot \text{CL}$	$0.808 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.768	$0.768 + 0.000 \cdot \text{CL}$	$0.768 + 0.000 \cdot \text{CL}$	$0.768 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	16.047	$0.897 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$	$0.899 + 0.303 \cdot \text{CL}$
	t_F	18.535	$1.010 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$	$1.011 + 0.350 \cdot \text{CL}$
	t_{PLH}	8.581	$1.327 + 0.145 \cdot \text{CL}$	$1.327 + 0.145 \cdot \text{CL}$	$1.327 + 0.145 \cdot \text{CL}$
	t_{PHL}	10.580	$1.460 + 0.182 \cdot \text{CL}$	$1.462 + 0.182 \cdot \text{CL}$	$1.462 + 0.182 \cdot \text{CL}$
	t_{PLZ}	0.851	$0.851 + 0.000 \cdot \text{CL}$	$0.851 + 0.000 \cdot \text{CL}$	$0.851 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.810	$0.810 + 0.000 \cdot \text{CL}$	$0.810 + 0.000 \cdot \text{CL}$	$0.810 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

POT4_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.054	$0.484 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$
	t_F	9.284	$0.522 + 0.175 \cdot \text{CL}$	$0.521 + 0.175 \cdot \text{CL}$	$0.522 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.795	$1.167 + 0.073 \cdot \text{CL}$	$1.168 + 0.073 \cdot \text{CL}$	$1.168 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.607	$1.048 + 0.091 \cdot \text{CL}$	$1.048 + 0.091 \cdot \text{CL}$	$1.048 + 0.091 \cdot \text{CL}$
TN to PAD	t_R	8.054	$0.484 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$
	t_F	9.284	$0.522 + 0.175 \cdot \text{CL}$	$0.521 + 0.175 \cdot \text{CL}$	$0.522 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.842	$1.214 + 0.073 \cdot \text{CL}$	$1.215 + 0.073 \cdot \text{CL}$	$1.216 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.729	$1.168 + 0.091 \cdot \text{CL}$	$1.169 + 0.091 \cdot \text{CL}$	$1.170 + 0.091 \cdot \text{CL}$
	t_{PLZ}	0.940	$0.940 + 0.000 \cdot \text{CL}$	$0.940 + 0.000 \cdot \text{CL}$	$0.940 + 0.000 \cdot \text{CL}$
	t_{PHZ}	0.978	$0.978 + 0.000 \cdot \text{CL}$	$0.978 + 0.000 \cdot \text{CL}$	$0.978 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	8.054	$0.484 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$	$0.480 + 0.151 \cdot \text{CL}$
	t_F	9.284	$0.522 + 0.175 \cdot \text{CL}$	$0.521 + 0.175 \cdot \text{CL}$	$0.522 + 0.175 \cdot \text{CL}$
	t_{PLH}	4.945	$1.318 + 0.073 \cdot \text{CL}$	$1.318 + 0.073 \cdot \text{CL}$	$1.318 + 0.073 \cdot \text{CL}$
	t_{PHL}	5.832	$1.271 + 0.091 \cdot \text{CL}$	$1.272 + 0.091 \cdot \text{CL}$	$1.274 + 0.091 \cdot \text{CL}$
	t_{PLZ}	0.982	$0.982 + 0.000 \cdot \text{CL}$	$0.982 + 0.000 \cdot \text{CL}$	$0.982 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.020	$1.020 + 0.000 \cdot \text{CL}$	$1.020 + 0.000 \cdot \text{CL}$	$1.020 + 0.000 \cdot \text{CL}$

*Group1 : CL < 50, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

POT1/2/4/8_ABB

Analog Tri-state Output Buffers with Enable Port and Separate Bulk-Bias

Switching Characteristics

(Typical process, 25°C, 2.5V, $t_R/t_F = 0.17\text{ns}$, CL: Capacitive Load)

POT8_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.117	$0.414 + 0.074 \cdot \text{CL}$	$0.368 + 0.075 \cdot \text{CL}$	$0.336 + 0.075 \cdot \text{CL}$
	t_F	4.673	$0.309 + 0.087 \cdot \text{CL}$	$0.297 + 0.088 \cdot \text{CL}$	$0.292 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.256	$1.437 + 0.036 \cdot \text{CL}$	$1.441 + 0.036 \cdot \text{CL}$	$1.442 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.352	$1.084 + 0.045 \cdot \text{CL}$	$1.078 + 0.045 \cdot \text{CL}$	$1.074 + 0.046 \cdot \text{CL}$
TN to PAD	t_R	4.117	$0.414 + 0.074 \cdot \text{CL}$	$0.368 + 0.075 \cdot \text{CL}$	$0.336 + 0.075 \cdot \text{CL}$
	t_F	4.672	$0.307 + 0.087 \cdot \text{CL}$	$0.295 + 0.088 \cdot \text{CL}$	$0.290 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.304	$1.484 + 0.036 \cdot \text{CL}$	$1.489 + 0.036 \cdot \text{CL}$	$1.490 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.464	$1.180 + 0.046 \cdot \text{CL}$	$1.183 + 0.046 \cdot \text{CL}$	$1.184 + 0.046 \cdot \text{CL}$
	t_{PLZ}	1.195	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$	$1.195 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.397	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$	$1.397 + 0.000 \cdot \text{CL}$
EN to PAD	t_R	4.117	$0.414 + 0.074 \cdot \text{CL}$	$0.369 + 0.075 \cdot \text{CL}$	$0.336 + 0.075 \cdot \text{CL}$
	t_F	4.672	$0.307 + 0.087 \cdot \text{CL}$	$0.295 + 0.088 \cdot \text{CL}$	$0.291 + 0.088 \cdot \text{CL}$
	t_{PLH}	3.406	$1.588 + 0.036 \cdot \text{CL}$	$1.592 + 0.036 \cdot \text{CL}$	$1.592 + 0.036 \cdot \text{CL}$
	t_{PHL}	3.567	$1.284 + 0.046 \cdot \text{CL}$	$1.285 + 0.046 \cdot \text{CL}$	$1.287 + 0.046 \cdot \text{CL}$
	t_{PLZ}	1.238	$1.238 + 0.000 \cdot \text{CL}$	$1.238 + 0.000 \cdot \text{CL}$	$1.238 + 0.000 \cdot \text{CL}$
	t_{PHZ}	1.439	$1.439 + 0.000 \cdot \text{CL}$	$1.439 + 0.000 \cdot \text{CL}$	$1.439 + 0.000 \cdot \text{CL}$

*Group1 : $\text{CL} < 50$, *Group2 : $50 \leq \text{CL} \leq 75$, *Group3 : $75 < \text{CL}$

Cell List

Cell Name	Function Description
EV2I	2.5V Internal ESD Protection
EV2P	2.5V Pre-Driver ESD Protection
EV2O	2.5V Output-Driver ESD Protection
EV2IP	2.5V Internal and Pre-Driver ESD Protection
EV2OP	2.5V Output-Driver and Pre-Driver ESD Protection
EV2T	2.5V Total ESD Protection
EV3P	3.3V Pre-Driver ESD Protection
EV3O	3.3V Output-Driver ESD Protection
EV3OP	3.3V Output-Driver and Pre-Driver ESD Protection
EV2I_ABB	2.5V Internal ESD Protection with Separated Bulk-Bias
EV2OP_ABB	2.5V Output-Driver and Pre-Driver ESD Protection with Separated Bulk-Bias
EV2T_ABB	2.5V Total ESD Protection with Separated Bulk-Bias

NOTE: All of Slot Cells have no Pad and can be added automatically by using SEC utility CubicPlan.

Common Slot Cells

Cell List

Cell Name	Function Description
EC0C0	Metal Ring Separator between Different Digital Blocks
EC0C0D ¹	Metal Ring Separator between Different Digital Blocks for Noise Critical Design
EC0CA0	Metal Ring Separator between Digital to Analog
EC0CA0D ¹	Metal Ring Separator between Digital to Analog for Noise Critical Design
EC0C0_BB	Metal Ring Separator between Different Analog Blocks with VBB Ring Separated
EC0C0D_BB ¹	Metal Ring Separator between Different Analog Blocks for Noise Critical Design with VBB Ring Separated
EC0C0_VBB ²	Metal Ring Separator between Different Analog Blocks with VBB Ring Connected
EC0C0D_VBB ^{1,2}	Metal Ring Separator between Different Analog Blocks for Noise Critical Design with VBB Ring Connected

NOTES:

1. If CDL ring connected with bi-directional diode, ESD protection level can be dropped.
2. If analog blocks have only one VBB power pad, metal connected VBB ring type should be used.
3. All of Slot Cells can be added automatically by using SEC utility CubicPlan, or by Manual.

Compiled Macrocells

5

Contents

Overview to Compiled Memory	5-1
Compiled Memory Naming Convention.....	5-1
Characteristics for Timing and Power	5-2
Built-In Self Test for Compiled Memory	5-3
Selection Guide for Compiled Memory	5-4
High-Density Compiled Memory	
SPSRAM_HD High-Density Single-Port Synchronous SRAM	5-7
SPSRAMBW_HD High-Density Single-Port Synchronous SRAM with Bit-Write.....	5-17
DPSRAM_HD High-Density Dual-Port Synchronous SRAM.....	5-27
SPARAM_HD High-Density Single-Port Asynchronous SRAM	5-37
DROM_HD High-Density Synchronous Diffusion Programmable ROM	5-48
MROM_HD High-Density Synchronous Metal Programmable ROM.....	5-56
ARFRAM_HD High-Density Multi-port Asynchronous Register File.....	5-64
FIFO_HD High-Density Synchronous First-In First-Out Memory.....	5-83
Low-Power Compiled Memory	
SPSRAM_LP Low Power Single-Port Synchronous SRAM	5-95
DPSRAM_LP Low Power Dual-Port Synchronous SRAM.....	5-105
SPARAM_LP Low Power Single-Port Asynchronous SRAM	5-115
DROM_LP Low Power Synchronous Diffusion Programmable ROM	5-125
MROM_LP Low Power Synchronous Metal Programmable ROM.....	5-133
Overview to Compiled Datapath	5-141
Compiled Macrocell Selection Guide	5-142
ADDER Adder/Subtractor.....	5-143
BS Barrel Shifter.....	5-148
MPY Modified Booth Multiplier	5-153

OVERVIEW TO COMPILED MEMORY

This section contains the overview of STD111 compiled memory. In STD111 compiled memory, we provide application-specific memory solution - high-density and low-power application. That is, two different library set of compiled memory are available in STD111 cell library. One is the high-density compiled memory, called STD111-HD compiled memory and the other is the low-power compiled memory, called STD111-LP compiled memory. The high-density compiled memories are suitable for high integration application with high-performance whereas the low-power compiled memories are suitable for portable applications. These are complete memories that are customized to satisfy the requirements of the circuit at hand. Depending on the function to be generated, the final memory will be implemented as a stand-alone, pitch-matched and customized leafcells. In addition, to implement optimized memory, we apply the state-of-the-art design architecture techniques. In STD111 cell library, the compiled memory is fully generated by a user-configurable compiler, called memory compiler. It allows you to configure a memory through memory-related specification such as word depth, bit per word, column mux type and so on. The compiler allows you to select and customize any of memory to satisfy the specific circuit requirements. When the required specifications have been fully given, you may get any or all of the following items:

- Area-optimized and speed-optimized layout blocks
- Schematic netlist for simulation and verification
- Phantom cell to use in chip-level layout
- Tabular model for timing and power characteristics
- Automatic datasheet for a specific instance

For more detailed information regarding to memory compiler, contact your local representative or headquarters.

COMPILED MEMORY NAMING CONVENTION

The naming convention of compiled memory in this section will be shown as Figure 5-1. The memory name consists of the following convention.

[memory_code]_[appl_code]_[opt_code]_[config_code]

Figure 5-1. Compiled Memory Naming Convention

The first string, 'memory_code', means the name of memory type. In STD111 compiled memory, the available memory types are as follows:

- SPSRAM : Single-Port Synchronous SRAM
- SPSRAMBW : Single-Port Synchronous SRAM with Bit-Write
- DPSRAM : Dual-Port Synchronous SRAM
- SPARAM : Single-Port Asynchronous SRAM
- DROM : Synchronous Diffusion-Programmable ROM
- MROM : Synchronous Metal-Programmable ROM
- ARFRAM : Multi-Port Asynchronous Register File
- FIFO : Synchronous First-In First-Out Memory

The second string, 'appl_code', means the specific application to suitably support the compiled memory and the application code is one of HD (High-Density), LP (Low-Power) and HS (High-Speed). In STD111 compiled memory, the high-speed compiled memory is not supported as another library set. Instead, the high-density compiled memory can be applied for the high-performance application.

The third string, 'opt_code', represents the number of read and write ports for multi-port memory and the option code is composed of the following convention:

$$\text{opt_code} = \langle n \rangle r \langle m \rangle w$$

Currently this field is only used for ARFRAM, where n is the total number of read ports (1~2) and m is the total number of write ports (1~2). The last string, 'config_code', represents the configuration of the memory to be specified. This configuration code is composed of the following convention:

$$\langle \text{WORD} \rangle \text{ x } \langle \text{BPW} \rangle \text{ m } \langle \text{YMUX} \rangle \text{ b } \langle \text{BANK} \rangle$$

Here, WORD is the word depth, BPW is bit per word, YMUX is the available column mux type and BANK is the number of bank to be used. For example, 'spsram_hd_1024x32m16b2' refers to a High-Density single-port synchronous SRAM with 1024 words, 32 bits, 16 column mux and 2 bank. Second, 'arfram_hd_1r2w_32x32m2' refers to a High-Density three-port (1 read/2 write) asynchronous register file with 32 word, 32 bits and 2 column mux and 'spsram_lp_1024x32m16b2' refers to a Low-Power single-port synchronous SRAM with 1024 words, 32 bits, 16 column mux and 2 bank.

CHARACTERISTICS FOR TIMING AND POWER

STD111-HD compiled memory is only supported at 2.5V supply voltage whereas STD111-LP compiled memory is supported at both 2.5V supply voltage and 1.8V supply voltage. Compiled memory in this section has been characterized using typical-case at 25 degree and 2.5V supply. The values of worst-case or best-case can be derived by using derating factors provided in Chapter 1.

For the timing characteristics, 2-dimensional table look-up model has been adopted to yield more accuracy. Based on the combination of input slopes and output loads, the propagation delay is measured from the input crossing 50% VDD to the output crossing 50% VDD. The timing values reported in the tables are also taken from the same voltage level as the switching characteristics with 0.2ns for input slope and 10SL(Standard Load) for output load.

For the power characteristics, the average power consumption is measured on the condition that input slope is 0.2ns and output load is 10SL. Also, the power consumption depends on input switching activity. The power values reported in the tables are also taken from 50% input switching activity. For compiled memory macrocells, average read power consumption, average write power consumption and average standby power consumption are available, except that the standby power consumption is not available in ARFRAM and FIFO. Average standby power consumption is measured on the condition that CSN (Chip Select Negative) is in disable mode and other signals are in normal operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while disabling CSN signal, if possible. In dual-port memory, the average power consumption is measured on the condition that only one port is in active mode and the other port is isolated.

BUILT-IN SELF TEST FOR COMPILED MEMORY

SEC provides engineering design services to support Built-In Self-Test (BIST) for the compiled memory macrocell. BIST circuits are designed to detect a set of fault types, such as stuck-at faults, transition faults, coupling faults and address decoder faults that adversely impact the functionality of the memory block. As shown in Figure 5-2, SEC adopts BIST architecture which is called SOA (Single Ordered Addressing) algorithm.




Figure 5-2. Memory BIST Architecture

From Figure 5-2, although several memory macrocells of the same types or the different types exist together in a circuit, SEC supports it as single BIST architecture. For more detailed information regarding to the BIST for compiled memory macrocells, please contact your local representative or headquarters.

SELECTION GUIDE FOR COMPILED MEMORY

STD111-HD (High-Density) Compiled Memory


Application	Memory Type	Description
High-Density with High-Performance	SPSRAM_HD	<ul style="list-style-type: none"> - High-Density Single-port Synchronous Static RAM - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	SPSRAMBW_HD	<ul style="list-style-type: none"> - High-Density Single-port Synchronous Static RAM with Bit-Write - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	DPSRAM_HD	<ul style="list-style-type: none"> - High-Density Dual-port Synchronous Static RAM - Positive-edge clock operation - Flexible aspect ratio (Ymux = 2, 4, 8, 16)
	SPARAM_HD	<ul style="list-style-type: none"> - High-Density Single-port Asynchronous Static RAM - Synchronous write operation / Asynchronous read operation - Dual bank available - Flexible aspect ratio (Ymux = 2, 4, 8, 16, 32)
	DROM_HD	<ul style="list-style-type: none"> - High-Density Synchronous Diffusion programmable ROM - Diffusion programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)
	MROM_HD	<ul style="list-style-type: none"> - High-Density Synchronous Metal programmable ROM - Metal-2 programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)
	ARFRAM_HD	<ul style="list-style-type: none"> - High-Density Multi-port Asynchronous Register File - Synchronous write operation / Asynchronous read operation - 1-to-2 write ports / 1-to-2 read ports - Flexible aspect ratio (Ymux = 2,4,8)
	FIFO_HD	<ul style="list-style-type: none"> - High-Density Synchronous First-In First-Out Memory - Positive-edge clock operation - Reset and re-transmit operation available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)

STD111-LP (Low-Power) Compiled Memory

Application	Memory Type	Description
Low-Power	SPSRAM_LP	<ul style="list-style-type: none"> - Low-Power Single-port Synchronous Static RAM - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	DPSRAM_LP	<ul style="list-style-type: none"> - Low-Power Dual-port Synchronous Static RAM - Positive-edge clock operation - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	SPARAM_LP	<ul style="list-style-type: none"> - Low-Power Single-port Asynchronous Static RAM - Synchronous write operation / Asynchronous read operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	DROM_LP	<ul style="list-style-type: none"> - Low-Power Synchronous Diffusion programmable ROM - Diffusion programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)
	MROM_LP	<ul style="list-style-type: none"> - Low-Power Synchronous Metal programmable ROM - Metal-2 programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)

NOTE

Logic Symbol



Features

- Suitable for high-density application
- Separated data I/O
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tri-state output control
- Latched inputs and outputs
- Automatic power-down
- Zero standby current
- Low noise output optimization
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

SPSRAM_HD is a single-port synchronous static RAM which is provided as a compiler. SPSRAM_HD is intended for use in high-density applications. On the rising edge of CK, the write cycle is initiated when WEN is low and CSN is low. The data on DI[] is written into the memory location specified on A[]. During the write cycle, DOUT[] remains stable. On the rising edge of CK, the read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

CK	CSN	WEN	OEN	A	DI	DOUT	COMMENT
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read cycle

Parameter Description

SPSRAM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b), Column mux(y) and Number of banks(ba).

SPSRAM_HD

High Density Single-Port Synchronous Static RAM

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	1	1	1	1
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If CSN is low and WEN is high on the rising edge of CK, the RAM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are presented at DOUT.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI []	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.

Pin Capacitance


Unit: [SL]

	CK	CSN	WEN	OEN	A	DI	DOUT
ba = 1	9.08	7.03	6.95	4.73	7.14	4.26	8.79
ba = 2	9.08	7.03	6.95	4.73	7.14	4.26	8.79

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPSRAM_HD has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from SPSRAM_HD compiler. In dual bank, the bank selected by the address is only activated while the other bank is in idle mode.



Application Notes

1. Permitting over-the-cell routing.
In chip-level layout, over-the-cell routing in SPSRAM_HD is permitted only for Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPSRAM_HD.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

SPSRAM_HD

High Density Single-Port Synchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ckh}	Clock pulse width high
t _{ckl}	Clock pulse width low	t _{as}	Address setup time
t _{ah}	Address hold time	t _{cs}	CSN setup time
t _{ch}	CSN hold time	t _{ds}	Data-In setup time
t _{dh}	Data-In hold time	t _{ws}	WEN setup time
t _{wh}	WEN hold time	t _{acc}	Data access time
t _{da}	De-access time	t _{dz}	DOUT drive to high-Z time
t _{zd}	DOUT high-Z to drive time	t _{od}	OEN to valid output time
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

High Density Single-Port Synchronous Static RAM

Reference Table

* For Ymux=4

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	256	512	512	1024	768	1536	1024	2048
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.67	2.75	2.90	3.01	3.04	3.19	3.11	3.30
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.45	0.48	0.50	0.51	0.53	0.58	0.54	0.68
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.35	0.35	0.30	0.30	0.27	0.26	0.26	0.25
t _{dh}	0.16	0.16	0.24	0.25	0.34	0.34	0.44	0.44
t _{ws}	0.55	0.56	0.50	0.51	0.48	0.50	0.50	0.53
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{acc}	2.14	2.21	2.34	2.45	2.48	2.61	2.54	2.70
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.68	1.73
t _{dz}	0.20	0.20	0.23	0.23	0.24	0.24	0.24	0.26
t _{zd}	0.23	0.23	0.26	0.26	0.28	0.28	0.28	0.28
t _{od}	0.72	0.72	0.81	0.81	0.92	0.92	1.03	1.03
Power (μW/MHz)								
Power_read	241.57	268.41	442.37	488.18	644.43	713.65	847.72	944.82
Power_write	291.60	322.60	584.59	641.00	921.25	1009.78	1301.57	1428.97
Power_standby	57.06	73.89	106.31	141.11	155.35	216.27	204.19	299.40
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAM_HD

High Density Single-Port Synchronous Static RAM

Reference Table

* For Ymux=8

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.67	2.75	2.90	3.02	3.05	3.20	3.11	3.30
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.43	0.47	0.46	0.50	0.48	0.53	0.47	0.56
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.36	0.33	0.33	0.31	0.30	0.30	0.29
t _{dh}	0.14	0.14	0.20	0.20	0.26	0.26	0.33	0.33
t _{ws}	0.55	0.56	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{acc}	2.14	2.21	2.35	2.45	2.48	2.62	2.54	2.71
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.69	1.73
t _{dz}	0.19	0.19	0.21	0.21	0.22	0.22	0.23	0.23
t _{zd}	0.22	0.22	0.24	0.24	0.26	0.26	0.26	0.26
t _{od}	0.70	0.70	0.77	0.77	0.84	0.84	0.92	0.92
Power (μW/MHz)								
Power_read	207.03	229.54	369.82	404.52	533.06	581.99	696.75	761.96
Power_write	244.00	270.27	464.85	508.31	707.23	771.09	971.11	1058.63
Power_standby	31.58	45.74	54.37	79.95	76.86	118.01	99.04	159.92
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

High Density Single-Port Synchronous Static RAM

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.70	2.81	2.93	3.07	3.08	3.26	3.15	3.36
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.57	0.61	0.60	0.65	0.63	0.68	0.66	0.72
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.37	0.34	0.35	0.32	0.35	0.31	0.35
t _{dh}	0.13	0.13	0.17	0.17	0.23	0.23	0.28	0.28
t _{ws}	0.55	0.56	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{acc}	2.17	2.26	2.38	2.50	2.51	2.67	2.57	2.76
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.69	1.73
t _{dz}	0.18	0.18	0.20	0.20	0.21	0.21	0.22	0.22
t _{zd}	0.21	0.21	0.23	0.23	0.24	0.24	0.25	0.25
t _{od}	0.69	0.69	0.75	0.75	0.80	0.80	0.86	0.86
Power (μW/MHz)								
Power_read	189.69	211.57	335.71	368.00	481.75	525.63	627.82	684.07
Power_write	220.81	245.81	408.49	447.98	606.72	662.40	815.51	889.07
Power_standby	26.07	43.74	41.79	70.58	57.20	99.25	72.30	129.73
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAM_HD

High Density Single-Port Synchronous Static RAM

Reference Table


* For Ymux=32 (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	4	4	8	8	12	12	16	16
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.75	2.91	2.99	3.18	3.15	3.37	3.22	3.47
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.56	0.59	0.57	0.61	0.57	0.63	0.58	0.64
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.60	0.35	0.60	0.33	0.62	0.32	0.64
t _{dh}	0.12	0.12	0.17	0.17	0.21	0.21	0.25	0.25
t _{ws}	0.56	0.57	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{acc}	2.21	2.35	2.43	2.60	2.57	2.77	2.63	2.86
t _{da}	1.38	1.40	1.56	1.59	1.66	1.70	1.68	1.73
t _{dz}	0.18	0.18	0.20	0.20	0.21	0.21	0.21	0.21
t _{zd}	0.21	0.21	0.22	0.22	0.24	0.24	0.24	0.24
t _{od}	0.69	0.69	0.74	0.74	0.78	0.78	0.83	0.83
Power (μW/MHz)								
Power_read	180.53	201.95	318.87	350.17	456.78	498.53	594.26	647.71
Power_write	207.22	231.24	378.35	415.74	554.34	605.89	735.19	801.71
Power_standby	19.88	35.95	29.68	55.03	39.17	74.90	48.36	95.57
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04


NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

High Density Single-Port Synchronous Static RAM

Read Cycle




Write Cycle




SPSRAM_HD

High Density Single-Port Synchronous Static RAM

Read Cycle with CSN Controlled




OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



Features

- Suitable for high-density application
- Bit-Write capability
- Separated data I/O
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tristate output
- Latched inputs and outputs
- Automatic power-down
- Zero standby current
- Low noise output optimization
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPSRAMBW_HD is a single-port synchronous static RAM with bit-write capability which is provided as a compiler. SPSRAMBW_HD is intended for use in high-density applications. Basically, its functionality is exactly same as SPSRAM_HD except a bit-write operation which is controlled by BWEN[], named bit-write enable signal bus. Each bit of BWEN[] enables or disables the write operation of its corresponding bit in DI[]. On the rising edge of CK, the write cycle is initiated when WEN is low and CSN is low. The data bits in DI[], which their corresponding bit(s) in BWEN[] are low, are written into the memory location specified on A[]. When all bits of BWEN[] are high, any data in DI[] are not written into the memory location specified on A[]. When all bits of BWEN[] are low, the data in DI[] are written into the memory location specified on A[], which is exactly same as the write operation in SPSRAM_HD. During the write cycle, DOUT[] remains stable. On the rising edge of CK, the read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

SPSRAMBW_HD Function Table

CK	CSN	WEN	OEN	A	BWEN	DI	DOUT	Comment
X	X	X	H	X	X	X	Z	OEN makes tri-state output
X	H	X	L	X	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	all L	Valid	DOUT(t-1)	Word-write cycle
↑	L	L	L	Valid	L	Valid	DOUT(t-1)	Bit-write cycle
↑	L	L	L	Valid	all H	Valid	DOUT(t-1)	No operation
↑	L	H	L	Valid	X	X	MEM(A)	Read Cycle

SPSRAMBW_HD

High Density Single-Port Synchronous SRAM with Bit-write

Parameter Description

SPSRAMBW_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b), Column mux(y) and Number of banks(ba)

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	2	2	2	2
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If CSN is low and WEN is high on the rising edge of CK, the RAM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are presented at DOUT.
BWEN[]	Bit-Write Enable	Bit-write enable input bus. The bit-write enable is latched into the RAM on the rising edge of CK. Each bit of BWEN[] enables/disables the write operation of corresponding data bit. BWEN[i] corresponds to DI[i] in bit-write. If WEN and BWEN[0] are low and BWEN[1] is high, DI[0] is written into the memory location specified on A[], but DI[1] is not written.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A[]	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI[]	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT[]	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.

High Density Single-Port Synchronous SRAM with Bit-write

Pin Capacitance


Unit: [SL]

	CK	CSN	WEN	BWEN	OEN	A	DI	DOUT
ba =1	9.08	7.03	6.95	4.26	4.73	7.14	4.26	8.79
ba = 2	9.08	7.03	6.95	4.26	4.73	7.14	4.26	8.79

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPSRAMBW_HD has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from SPSRAMBW_HD compiler. In dual bank, the bank selected by the address is only activated while the other bank is in idle mode.



Application Notes

1. Permitting Over-the-cell routing
In chip-level layout, over-the-cell routing in SPSRAMBW_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPSRAMBW_HD.
4. A byte-write or word-write operation will be supported with SPSRAMBW_HD.
Please refer to the function table. In byte-write operation, the number of BWEN[] signal bus should be divided by a byte (8) and eight BWEN signals should be tied to a connection wire. In this case, DI[] bus is controlled by a byte-wired BWEN signal instead of each BWEN bit. In word-write operation, the functionality is exactly same as SPSRAM_HD. If all of BWEN[] signal is tied to low state, DI[] bus is only controlled by WEN.
5. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

SPSRAMBW_HD

High Density Single-Port Synchronous SRAM with Bit-write

Characteristics

Definition for AC Timing (ns)			
Symbol		Description	
t _{cyc}		Clock cycle time	
t _{ckl}		Clock pulse width low	
t _{ah}		Address hold time	
t _{ch}		CSN hold time	
t _{dh}		Data-In hold time	
t _{wh}		WEN hold time	
t _{bwh}		BWEN hold time	
t _{da}		De-access time	
t _{zd}		DOUT high-Z to drive time	
Definition for Power Consumption (μW/MHz)			
Power_read		The dynamic average power consumption while in a read cycle	
Power_write		The dynamic average power consumption while in a write cycle	
Power_standby		The standby power consumption while CSN is high	
Definition for Area (μm)			
Width		The physical width in X-direction	
Height		The physical height in Y-direction	

High Density Single-Port Synchronous SRAM with Bit-write

Reference Table

* For Ymux=4

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	256	512	512	1024	768	1536	1024	2048
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.67	2.75	2.90	3.01	3.04	3.19	3.11	3.30
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.45	0.48	0.50	0.51	0.53	0.58	0.54	0.68
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.35	0.35	0.30	0.30	0.27	0.26	0.26	0.25
t _{dh}	0.16	0.16	0.24	0.25	0.34	0.34	0.44	0.44
t _{ws}	0.55	0.56	0.50	0.51	0.48	0.50	0.50	0.53
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{bws}	0.42	0.45	0.38	0.44	0.35	0.44	0.33	0.45
t _{bwh}	0.14	0.14	0.22	0.22	0.31	0.31	0.41	0.41
t _{acc}	2.14	2.21	2.34	2.45	2.48	2.61	2.54	2.70
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.68	1.73
t _{dz}	0.20	0.20	0.23	0.23	0.24	0.24	0.24	0.24
t _{zd}	0.23	0.23	0.26	0.26	0.28	0.28	0.28	0.28
t _{od}	0.72	0.72	0.81	0.81	0.92	0.92	1.03	1.03
Power (μW/MHz)								
Power_read	255.46	287.55	470.50	534.89	686.77	796.08	904.26	1071.12
Power_write	304.34	337.62	610.64	671.87	960.30	1056.66	1353.31	1492.00
Power_standby	69.94	89.11	132.72	172.39	195.27	263.75	257.60	363.18
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAMBW_HD

High Density Single-Port Synchronous SRAM with Bit-write

Reference Table

* For Ymux=8

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.67	2.75	2.90	3.02	3.05	3.20	3.11	3.30
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.43	0.47	0.46	0.50	0.48	0.53	0.47	0.56
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.36	0.33	0.33	0.31	0.30	0.30	0.29
t _{dh}	0.14	0.14	0.20	0.20	0.26	0.26	0.33	0.33
t _{ws}	0.55	0.56	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{bws}	0.42	0.45	0.38	0.45	0.35	0.44	0.33	0.44
t _{bwh}	0.12	0.12	0.18	0.18	0.24	0.24	0.31	0.31
t _{acc}	2.14	2.21	2.35	2.45	2.48	2.62	2.54	2.71
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.69	1.73
t _{dz}	0.19	0.19	0.21	0.21	0.22	0.22	0.23	0.23
t _{zd}	0.22	0.22	0.24	0.24	0.26	0.26	0.26	0.26
t _{od}	0.70	0.70	0.77	0.77	0.84	0.84	0.92	0.92
Power (μW/MHz)								
Power_read	214.55	239.49	385.13	428.85	556.10	624.86	727.48	827.51
Power_write	250.40	279.24	478.61	526.86	728.29	799.36	999.45	1096.73
Power_standby	38.12	54.83	68.24	98.86	98.06	146.85	127.56	198.79
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

High Density Single-Port Synchronous SRAM with Bit-write

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.70	2.81	2.93	3.07	3.08	3.26	3.15	3.36
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.57	0.61	0.60	0.65	0.63	0.68	0.66	0.72
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.37	0.34	0.35	0.32	0.35	0.31	0.35
t _{dh}	0.13	0.13	0.17	0.17	0.23	0.23	0.28	0.28
t _{ws}	0.55	0.56	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{bws}	0.43	0.48	0.39	0.47	0.37	0.47	0.35	0.47
t _{bwh}	0.11	0.11	0.16	0.16	0.21	0.21	0.26	0.26
t _{acc}	2.17	2.26	2.38	2.50	2.51	2.67	2.57	2.76
t _{da}	1.39	1.41	1.56	1.59	1.66	1.70	1.69	1.73
t _{dz}	0.18	0.18	1.20	0.20	0.21	0.21	0.22	0.22
t _{zd}	0.21	0.21	0.23	0.23	0.24	0.24	0.25	0.25
t _{od}	0.69	0.69	0.75	0.75	0.80	0.80	0.86	0.86
Power (μW/MHz)								
Power_read	194.40	217.74	345.29	382.79	496.26	551.18	647.29	722.90
Power_write	224.02	251.54	415.78	460.27	618.19	681.30	831.26	914.62
Power_standby	29.41	49.55	49.30	83.11	68.88	118.58	88.15	155.97
Area (μm)								
Width	1145.58	1145.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAMBW_HD

High Density Single-Port Synchronous SRAM with Bit-write

Reference Table

* For Ymux=32


(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	4	4	8	8	12	12	16	16
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	2.75	2.91	2.99	3.18	3.15	3.37	3.22	3.47
t _{ckl}	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
t _{ckh}	0.48	0.48	0.48	0.48	0.48	0.48	0.48	0.48
t _{as}	0.56	0.59	0.57	0.61	0.57	0.63	0.58	0.64
t _{ah}	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
t _{cs}	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
t _{ch}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ds}	0.37	0.60	0.35	0.60	0.33	0.62	0.32	0.64
t _{dh}	0.12	0.12	0.17	0.17	0.21	0.21	0.25	0.25
t _{ws}	0.56	0.57	0.50	0.52	0.48	0.50	0.50	0.52
t _{wh}	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
t _{bws}	0.46	0.52	0.42	0.52	0.39	0.53	0.37	0.54
t _{bwh}	0.10	0.10	0.15	0.15	0.19	0.19	0.23	0.23
t _{acc}	2.21	2.35	2.43	2.60	2.57	2.77	2.63	2.86
t _{da}	1.38	1.40	1.56	1.59	1.66	1.70	1.68	1.73
t _{dz}	0.18	0.18	0.20	0.20	0.21	0.21	0.21	0.21
t _{zd}	0.21	0.21	0.22	0.22	0.24	0.24	0.24	0.24
t _{od}	0.69	0.69	0.74	0.74	0.78	0.78	0.83	0.83
Power (μW/MHz)								
Power_read	183.69	206.04	325.65	360.13	467.36	515.57	608.81	672.35
Power_write	208.66	234.93	382.40	424.64	561.15	620.17	744.92	821.51
Power_standby	21.53	39.89	33.97	64.20	46.10	89.42	57.93	115.55
Area (μm)								
Width	1145.58	1144.58	2087.66	2087.66	3029.74	3029.74	3971.82	3971.82
Height	247.02	444.94	375.54	701.97	504.05	959.01	632.57	1216.04


NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

High Density Single-Port Synchronous SRAM with Bit-write

Read Cycle




Write Cycle




SPSRAMBW_HD

High Density Single-Port Synchronous SRAM with Bit-write

Read Cycle with CSN Controlled




OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



Features

- Suitable for high-density application
- Separated data I/O
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tri-state output control
- Latched inputs and outputs
- Automatic power-down
- Zero standby current
- Low noise output optimization
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 128Kbits capacity
- Up to 8K number of words
- Up to 128 number of bits per word

Function Description

DPSRAM_HD is a dual-port synchronous static RAM which is provided as a compiler. DPSRAM_HD is intended for use in high-density applications. Each port is fully independent. On the rising edge of CK1(CK2), the write cycle is initiated when WEN1 (WEN2) is low and CSN1 (CSN2) is low. The data on DI1[] (DI2[]) is written into the memory location specified on A1[] (A2[]). During the write cycle, DOUT1[] (DOUT2[]) remains stable. On the rising edge of CK1(CK2), the read cycle is initiated when WEN1 (WEN2) is high and CSN1(CSN2) is low. The data at DOUT1[] (DOUT2[]) become valid after a delay. While in standby mode that CSN1(CSN2) is high, DI1[] (DI2[]) are disabled, data stored in the memory is retained and DOUT1[] (DOUT2[]) remains stable. When OEN1 (OEN2) is high, DOUT1[] (DOUT2[]) is placed in a high-impedance state.

DPSRAM_HD Function Table

CK1 CK2	CSN1 CSN2	WEN1 WEN2	OEN1 OEN2	A1 A2	DI1 DI2	DOUT1 DOUT2	Comment
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read cycle

DPSRAM_HD

High-Density Dual-Port Synchronous Static RAM

Parameter Description

DPSRAM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and Column mux(y).

Parameters		Ymux = 2	Ymux = 4	Ymux = 8	Ymux = 16
Words (w)	Min	16	32	64	128
	Max	1024	2048	4096	8192
	Step	8	16	32	64
Bpw (b)	Min	1	1	1	1
	Max	128	64	32	16
	Step	1	1	1	1

Pin Descriptions

Name	Type	Description
CK1 CK2	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If WEN is high on the rising edge of CK, the RAM is in read mode.
CSN1 CSN2	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN1 WEN2	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are presented at DOUT.
OEN1 OEN2	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A1 [] A2 []	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI1 [] DI2 []	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT1 [] DOUT2 []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.


Pin Capacitance

(Unit = SL)

CK	CSN	WEN	OEN	A	DI	DOUT
28.53	8.37	7.68	5.66	8.23	4.60	9.13

NOTE: Each pin's capacitance is exactly same regardless of available mux types.

Block Diagram



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in DPSRAM_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of DPSRAM_HD.
4. Contention mode in same address access
In DPSRAM_HD, simultaneous operation by both ports on the same memory address, as write/write, write/read or read/write operation, causes a contention problem. Simultaneous operation is defined as a state in which both ports are enabled, both address buses are equal at the rising edge of CK. DPSRAM_HD has no scheme preventing the contention. Due to simultaneous operation, silicon will behave unpredictably. A write operation cannot end and data appearing at outputs may not be valid. Please refer to the timing diagrams if you want to avoid the contention mode between both ports. In write/write operation, the data stored at the current address will be unpredictable. In write/read or read/write operation, the read port is invalid while the write port is still valid. If you want to avoid the contention mode, you have to give the value greater than tcc (clock-to-clock setup time). However, simultaneous read/read is allowable without any restrictions.
5. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

DPSRAM_HD

High-Density Dual-Port Synchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol		Description	
t _{cyc}		Clock cycle time	
t _{ckh}		Clock pulse width high	
t _{as}		Address setup time	
t _{cs}		CSN setup time	
t _{ds}		Data-In setup time	
t _{ws}		WEN setup time	
t _{acc}		Data access time	
t _{dz}		DOUT drive to high-Z time	
t _{od}		OEN to valid output time	
Definition for Power Consumption (μW/MHz)			
Power_read		The dynamic average power consumption while in a read cycle	
Power_write		The dynamic average power consumption while in a write cycle	
Power_standby		The standby power consumption while CSN is high	
Definition for Area (μm)			
Width		The physical width in X-direction	
Height		The physical height in Y-direction	

Reference Table

* For Ymux=2 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	256	512	768	1024
bpw	32	64	96	128
Timing (ns)				
t _{cyc}	3.43	3.94	4.36	4.70
t _{ckl}	0.88	0.86	0.86	0.86
t _{ckh}	0.59	0.63	0.69	0.78
t _{cc}	1.74	2.25	2.46	2.92
t _{as}	0.41	0.40	0.40	0.39
t _{ah}	0.27	0.27	0.27	0.27
t _{cs}	0.36	0.35	0.36	0.36
t _{ch}	0.27	0.27	0.27	0.27
t _{ds}	0.26	0.26	0.26	0.26
t _{dh}	0.56	0.64	0.70	0.77
t _{ws}	0.38	0.38	0.38	0.38
t _{wh}	0.27	0.27	0.27	0.27
t _{acc}	2.81	3.29	3.64	3.88
t _{da}	1.88	2.24	2.50	2.68
t _{dz}	0.52	0.59	0.67	0.75
t _{zd}	0.63	0.70	0.77	0.84
t _{od}	0.73	0.80	0.87	0.96
Power (μW/MHz)				
Power_read	252.60	467.66	715.73	996.83
Power_write	330.45	661.87	1066.43	1544.15
Power_standby	42.46	49.53	56.46	63.27
Area (μm)				
Width	954.08	1645.28	2336.48	3027.68
Height	541.34	839.85	1138.35	1436.86

NOTES:

1. In power consumption of DPSRAM_HD, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_HD

High-Density Dual-Port Synchronous Static RAM

Reference Table

* For Ymux=4 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	512	1024	1536	2048
bpw	16	32	48	64
Timing (ns)				
t _{cyc}	3.19	3.66	4.13	4.60
t _{ckl}	0.88	0.86	0.85	0.86
t _{ckh}	0.59	0.59	0.61	0.63
t _{cc}	1.74	2.25	2.64	2.92
t _{as}	0.41	0.40	0.40	0.39
t _{ah}	0.27	0.27	0.27	0.27
t _{cs}	0.35	0.35	0.35	0.35
t _{ch}	0.27	0.27	0.27	0.27
t _{ds}	0.10	0.10	0.10	0.10
t _{dh}	0.48	0.52	0.57	0.62
t _{ws}	0.38	0.38	0.38	0.38
t _{wh}	0.27	0.27	0.27	0.27
t _{acc}	2.78	3.25	3.60	3.84
t _{da}	1.85	2.21	2.47	2.64
t _{dz}	0.50	0.54	0.59	0.64
t _{zd}	0.60	0.65	0.70	0.74
t _{od}	0.70	0.75	0.80	0.85
Power (μW/MHz)				
Power_read	225.40	417.84	643.21	901.51
Power_write	272.29	524.02	823.22	1169.90
Power_standby	35.66	41.21	46.81	52.46
Area (μm)				
Width	954.08	1645.28	2336.48	3027.68
Height	541.34	839.85	1138.35	1436.86

NOTES:

1. In power consumption of DPSRAM_HD, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	1024	2048	3072	4096
bpw	8	16	24	32
Timing (ns)				
t _{cyc}	3.23	3.69	4.14	4.59
t _{ckl}	0.91	0.91	0.92	0.94
t _{ckh}	0.59	0.59	0.59	0.59
t _{cc}	1.74	2.25	2.64	2.92
t _{as}	0.53	0.54	0.55	0.57
t _{ah}	0.27	0.27	0.27	0.27
t _{cs}	0.36	0.35	0.36	0.36
t _{ch}	0.27	0.27	0.27	0.27
t _{ds}	0.10	0.10	0.10	0.10
t _{dh}	0.47	0.50	0.53	0.57
t _{ws}	0.38	0.38	0.38	0.38
t _{wh}	0.27	0.27	0.27	0.27
t _{acc}	2.81	3.28	3.63	3.87
t _{da}	1.88	2.23	2.49	2.67
t _{dz}	0.49	0.52	0.55	0.59
t _{zd}	0.59	0.62	0.66	0.69
t _{od}	0.69	0.72	0.76	0.80
Power (μW/MHz)				
Power_read	217.93	400.88	616.43	864.59
Power_write	236.82	438.10	674.19	945.08
Power_standby	36.77	43.19	49.68	56.24
Area (μm)				
Width	954.08	1645.28	2336.48	3027.68
Height	541.34	839.85	1138.35	1436.86

NOTES:

1. In power consumption of DPSRAM_HD, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_HD

High-Density Dual-Port Synchronous Static RAM

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)


Parameters				
words	2048	4096	6144	8192
bpw	4	8	12	16
Timing (ns)				
t _{cyc}	3.26	3.72	4.17	4.63
t _{ckl}	0.90	0.90	0.91	0.93
t _{ckh}	0.59	0.59	0.59	0.59
t _{cc}	1.75	2.25	2.64	2.92
t _{as}	0.53	0.53	0.53	0.55
t _{ah}	0.27	0.27	0.27	0.27
t _{cs}	0.36	0.35	0.36	0.36
t _{ch}	0.27	0.27	0.27	0.27
t _{ds}	0.10	0.10	0.10	0.10
t _{dh}	0.46	0.48	0.51	0.54
t _{ws}	0.38	0.38	0.38	0.38
t _{wh}	0.27	0.27	0.27	0.27
t _{acc}	2.85	3.31	3.67	3.91
t _{da}	1.91	2.26	2.53	2.70
t _{dz}	0.48	0.50	0.53	0.56
t _{zd}	0.58	0.61	0.63	0.66
t _{od}	0.69	0.71	0.74	0.77
Power (μW/MHz)				
Power_read	215.68	391.61	599.53	839.42
Power_write	220.61	395.55	598.37	829.10
Power_standby	36.67	42.75	48.88	55.05
Area (μm)				
Width	954.08	1645.28	2336.48	3027.68
Height	541.34	839.85	1138.35	1436.86

NOTES:


1. In power consumption of DPSRAM_HD, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle



Write Cycle



High-Density Dual-Port Synchronous Static RAM


(OEN = low, WEN = high, DI = don't care)

(CK, A, WEN, DI, CSN = don't care)

The diagram shows two clock signals, CK1 and CK2, over time. CK1 is a square wave. CK2 is a square wave that is phase-shifted relative to CK1. The phase shift is labeled t_{cc} with a double-headed arrow. The condition $(A1 = A2)$ is noted at the bottom right.

STD111

Logic Symbol



Features

- Suitable for high-density application
- Standby (power down) mode available
- Separated data I/O
- Asynchronous operation
- Asynchronous tri-state output
- Address transition detector
- Write-enable transition detector
- Chip-select transition detector
- Bank-select transition detector
- Automatic power-down
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPARAM_HD is a single-port asynchronous static RAM which is provided as a compiler. SPARAM_HD is intended for use in high-density applications. At the falling edge of WEN, the write cycle is initiated. At the rising edge of WEN, the write cycle is ended. During the write cycle, the data on DI[] is written into the memory location specified on A[]. The read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay whenever A[] transition is detected. While in standby mode that CSN is high, A[] and DI[] are disabled, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

SPARAM_HD Function Table

CSN	WEN	OEN	A	DI	DOUT	Comment
X	X	H	X	X	Z	Unconditional tri-state output
H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
L	↓	L	Valid	Valid	DOUT(t-1)	Write cycle starts
L	↑	L	Valid	Valid	MEM(A)	Write cycle ends and Read Cycle starts
L	L	L	Stable	Valid	DOUT(t-1)	Write Cycle
L	H	L	Toggle	X	MEM(A)	Read Cycle

SPARAM_HD

High-Density Single-Port Asynchronous Static RAM

Parameter Description

SPARAM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 2	Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words(w)	ba = 1	Min	16	32	64	128	256
		Max	512	1024	2048	4096	8192
		Step	8	16	32	64	128
	ba = 2	Min	32	64	128	256	512
		Max	1024	2048	4096	8192	16384
		Step	16	32	64	128	256
Bpw(b)		Min	1	1	1	1	
		Max	256	128	64	32	16
		Step	1	1	1	1	1

Pin Descriptions

Name	I/O	Description
CSN	Chip Enable	Chip select input. The chip select signal acts as the memory enable signal for selections of multiple blocks. When CSN is high, the memory goes to stand-by (power down) mode and no access to the memory can occur. Conversely, if low, a read or write access can occur. When CSN falls, an access is initiated.
WEN	Read/Write Enable	Write enable input. The write enable signal selects the type of memory access. The high state for a read access and the low state for a write access. Upon the rising edge of WEN, a write access completed and a read access initiated.
OEN	Data Output Enable	Output enable input. The output enable signal controls the output drivers from driven to tri-state condition unconditionally.
A []	Address	Address input bus. A[] should be stable when WEN is low. The address selects the location to be accessed. When the address changes, the transition is detected and the internal clock pulse is generated.
DI []	Data Input	Data input bus. The data input is written to the accessed location when WEN is low.
DOUT []	Data Output	Data output bus. The data output is data stored in the accessed location during a read access. Data output driver has tri-state logic. When OEN is low, the driver drives a certain value. Otherwise, data output keeps Hi-Z state. During a write access, data on DOUT is predictable.

Pin Capacitance


Unit: [SL]

	CSN	WEN	OEN	A	DI	DOUT
ba = 1	1.87	1.87	1.87	3.91	1.87	7.12
ba = 2	1.87	1.87	1.87	3.91	1.87	7.12

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPARAM_HD has 2 different physical architectures due to the word depth. Optionally, one of these architectures is generated from SPARAM_HD compiler. In dual-bank, the bank selected by the address is only activated while the other bank is in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in SPARAM_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPARAM_HD.
4. Avoiding short transition on the address bus
In SPARAM_HD, rather than the write operation which is synchronously performed by WEN signal, the read operation is asynchronously performed whenever the address transition is occurred. In this case, if the short transition on the address, called a skew, is happened, since SPARAM_HD recognizes the short address transition as the stable address transition and do perform a read operation. At that time, while in the read operation, the data stored in the memory may be corrupted due to the short transition. To prevent such fail, the stable address cycle time (tcyc) is required. The essential requirement to recognize valid address transition is that at least minimum address period should be equal or greater than tacc (access time).
5. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

SPARAM_HD

High-Density Single-Port Asynchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol		Description	
t _{cyc}		Address cycle time	
t _{cas}		Address setup time for CSN rise	
t _{wh}		WEN hold time	
t _{ch}		CSN hold time	
t _{dh}		Data-In hold time	
t _{acc}		Data access time for read cycle	
t _{da}		De-access time	
t _{zd}		DOUT high-Z to drive time	
t _{od}		OEN to valid output time	
Definition for Power Consumption (μW/MHz)			
Power_read		The dynamic average power consumption while in a read cycle	
Power_write		The dynamic average power consumption while in a write cycle	
Power_standby		The standby power consumption while CSN is high	
Definition for Area (μm)			
Width		The physical width in X-direction	
Height		The physical height in Y-direction	

High-Density Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=2

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	128	256	256	512	384	768	512	1024
bpw	64	64	128	128	192	192	256	256
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	3.54	3.62	3.80	3.92	4.06	4.21	4.32	4.51
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	3.76	3.85	4.02	4.14	4.28	4.44	4.54	4.73
t _{ah}	0.49	0.51	0.72	0.75	1.01	1.04	1.36	1.39
t _{wh}	3.76	3.85	4.02	4.14	4.28	4.44	4.54	4.73
t _{ds}	0.14	0.16	0.14	0.17	0.14	0.16	0.14	0.15
t _{dh}	0.76	0.75	0.84	0.84	0.94	0.93	1.04	1.03
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.61	1.72	1.70	1.84	1.79	1.97	1.89	2.11
t _{wen}	2.43	2.47	2.66	2.70	2.88	2.93	3.10	3.17
t _{acc}	3.54	3.62	3.80	3.92	4.06	4.21	4.32	4.51
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.39	1.49	1.47	1.62	1.57	1.74	1.67	1.88
t _{dz}	0.51	0.51	0.55	0.55	0.58	0.58	0.61	0.61
t _{zd}	0.33	0.33	0.36	0.36	0.40	0.40	0.43	0.43
t _{od}	0.55	0.55	0.58	0.58	0.62	0.62	0.65	0.66
Power (μW/MHz)								
Power_read	296.01	315.80	565.87	618.94	850.87	951.64	1151.00	1313.90
Power_write	397.43	427.42	890.37	972.44	1513.74	1670.46	2267.53	2521.46
Power_standby	31.21	75.63	56.71	147.15	82.31	227.53	107.99	316.78
Area (μm)								
Width	1207.22	1207.22	2157.05	2157.05	3106.87	3106.87	4056.69	4056.69
Height	342.44	646.60	471.08	903.88	599.72	1161.16	728.36	1418.44

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

SPARAM_HD

High-Density Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=4 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	256	512	512	1024	768	1536	1024	2048
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	3.51	3.59	3.74	3.86	3.97	4.13	4.20	4.40
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	3.74	3.82	3.97	4.09	4.20	4.35	4.43	4.62
t _{ah}	0.52	0.54	0.75	0.78	1.04	1.07	1.39	1.43
t _{wh}	3.74	3.82	3.97	4.09	4.20	4.35	4.43	4.62
t _{ds}	0.15	0.16	0.15	0.16	0.15	0.16	0.15	0.14
t _{dh}	0.74	0.73	0.80	0.78	0.86	0.84	0.91	0.91
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.59	1.69	1.65	1.79	1.71	1.88	1.77	1.98
t _{wen}	2.45	2.49	2.67	2.72	2.90	2.95	3.12	3.18
t _{acc}	3.51	3.59	3.74	3.86	3.97	4.13	4.20	4.40
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.36	1.47	1.42	1.56	1.48	1.66	1.54	1.75
t _{dz}	0.51	0.51	0.55	0.55	0.58	0.58	0.61	0.61
t _{zd}	0.33	0.33	0.36	0.36	0.40	0.40	0.43	0.43
t _{od}	0.55	0.55	0.59	0.58	0.62	0.62	0.66	0.65
Power (μW/MHz)								
Power_read	237.40	247.96	447.05	474.50	669.40	721.00	904.45	987.49
Power_write	294.56	309.83	627.93	669.30	1030.91	1109.77	1503.48	1631.23
Power_standby	20.26	48.08	34.13	86.35	48.14	129.20	62.27	176.64
Area (μm)								
Width	1207.22	1207.22	2157.05	2157.05	3106.87	3106.87	4056.69	4056.69
Height	342.44	646.60	471.08	903.88	599.72	1161.16	728.36	1418.44

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

High-Density Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=8

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	3.53	3.62	3.76	3.89	3.99	4.16	4.23	4.43
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	3.75	3.85	3.99	4.12	4.22	4.38	4.45	4.65
t _{ah}	0.52	0.54	0.75	0.78	1.04	1.07	1.39	1.43
t _{wh}	3.75	3.85	3.99	4.12	4.22	4.38	4.45	4.65
t _{ds}	0.15	0.16	0.15	0.17	0.15	0.16	0.15	0.14
t _{dh}	0.70	0.67	0.76	0.72	0.83	0.78	0.89	0.85
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.61	1.72	1.67	1.82	1.73	1.91	1.79	2.01
t _{wen}	2.44	2.47	2.67	2.70	2.89	2.93	3.11	3.17
t _{acc}	3.53	3.62	3.76	3.89	3.99	4.16	4.23	4.43
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.38	1.50	1.44	1.59	1.50	1.69	1.56	1.78
t _{dz}	0.51	0.51	0.55	0.54	0.58	0.58	0.61	0.61
t _{zd}	0.33	0.33	0.36	0.36	0.40	0.40	0.43	0.43
t _{od}	0.55	0.55	0.58	0.58	0.62	0.62	0.65	0.65
Power (μW/MHz)								
Power_read	211.43	219.32	399.31	417.73	600.08	632.62	813.75	863.97
Power_write	232.50	247.38	483.89	512.41	773.59	824.42	1104.59	1183.43
Power_standby	17.12	41.09	27.84	69.75	38.67	100.88	49.61	134.50
Area (μm)								
Width	1207.22	1207.22	2157.05	2175.05	3106.87	3106.87	4056.69	4056.69
Height	342.44	646.60	471.08	903.88	599.72	1161.16	728.36	1418.44

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

SPARAM_HD

High-Density Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	3.56	3.68	3.80	3.95	4.03	4.21	4.27	4.48
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	3.78	3.91	4.02	4.18	4.25	4.45	4.49	4.72
t _{ah}	0.52	0.54	0.75	0.78	1.04	1.07	1.39	1.43
t _{wh}	3.78	3.91	4.02	4.18	4.25	4.45	4.49	4.72
t _{ds}	0.16	0.16	0.17	0.19	0.16	0.20	0.14	0.17
t _{dh}	0.65	0.56	0.71	0.62	0.77	0.68	0.84	0.75
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.64	1.79	1.70	1.88	1.76	1.98	1.82	2.07
t _{wen}	2.43	2.44	2.65	2.67	2.87	2.90	3.10	3.13
t _{acc}	3.56	3.68	3.80	3.95	4.03	4.21	4.27	4.48
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.41	1.55	1.48	1.65	1.54	1.74	1.60	1.84
t _{dz}	0.51	0.51	0.54	0.54	0.58	0.58	0.61	0.61
t _{zd}	0.33	0.33	0.36	0.36	0.40	0.40	0.43	0.43
t _{od}	0.55	0.55	0.58	0.58	0.62	0.62	0.65	0.65
Power (μW/MHz)								
Power_read	194.95	201.50	373.63	387.64	565.45	588.69	770.41	804.65
Power_write	203.19	215.26	410.81	434.92	645.75	684.69	908.00	964.57
Power_standby	15.82	39.97	25.12	64.23	34.53	89.89	44.06	116.95
Area (μm)								
Width	1207.22	1207.22	2157.05	2157.05	3106.87	3106.87	4056.69	4056.69
Height	342.44	646.60	471.08	903.88	599.72	1161.16	728.36	1418.44

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

High-Density Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=32

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	4	4	8	8	12	12	16	16
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	3.61	3.77	3.85	4.05	4.09	4.32	4.33	4.60
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	3.84	4.03	4.08	4.31	4.32	4.58	4.56	4.86
t _{ah}	0.52	0.54	0.75	0.78	1.04	1.08	1.39	1.43
t _{wh}	3.84	4.03	4.08	4.31	4.32	4.58	4.56	4.86
t _{ds}	0.15	0.23	0.18	0.31	0.19	0.36	0.16	0.39
t _{dh}	0.54	0.36	0.60	0.42	0.66	0.47	0.72	0.52
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.70	1.92	1.76	2.01	1.82	2.11	1.88	2.20
t _{wen}	2.40	2.38	2.62	2.61	2.84	2.83	3.06	3.06
t _{acc}	3.61	3.77	3.85	4.05	4.09	4.32	4.33	4.60
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.47	1.66	1.53	1.75	1.59	1.85	1.66	1.94
t _{dz}	0.51	0.51	0.54	0.54	0.58	0.58	0.61	0.61
t _{zd}	0.33	0.33	0.36	0.36	0.40	0.40	0.43	0.43
t _{od}	0.55	0.55	0.58	0.58	0.62	0.62	0.65	0.66
Power (μW/MHz)								
Power_read	179.77	185.70	356.81	368.61	547.31	565.88	751.28	777.49
Power_write	182.59	202.06	372.72	402.17	583.36	624.20	814.52	868.18
Power_standby	16.11	48.56	24.84	71.16	33.67	94.59	42.61	118.85
Area (μm)								
Width	1207.22	1207.22	2157.05	2157.05	3106.87	3106.87	4056.69	4056.69
Height	342.44	646.60	471.08	903.88	599.72	1161.16	728.36	1418.44


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

SPARAM_HD


High-Density Single-Port Asynchronous Static RAM

Timing Diagrams


Read Cycle



Read Cycle with CSN-Controlled




Basic Write Cycle




High-Density Single-Port Asynchronous Static RAM

Write Cycle with CSN Controlled




Read-Modified-Write Cycle



NOTES:

1. When the wen hold time after the last address bit transition is satisfied, D+ will toggle in response to a successful read of the initial contents of address A1. When the wen hold time after the last address bit transition is not satisfied, D+ will go to unknown state.
2. Address bits are not allowed to change while WEN is low. If they do change, then the data for one or more addresses in the memory array may be corrupted.

OEN Controlled Output Enable




NOTE: "don't care" means the condition that these pins are in normal operation mode.

DROM_HD

High-Density Synchronous Diffusion Programmable ROM

Logic Symbol



Features

- Suitable for high-density applications
- Diffusion-programmable code available
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tri-state output
- Latched inputs and outputs
- Automatic power-down
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

DROM_HD is a synchronous diffusion programmable ROM which is provided as a compiler. DROM_HD is intended for use in high-density applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

DROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

Parameter Description

DROM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and Column mux(y) and Number of banks(ba).

High-Density Synchronous Diffusion Programmable ROM

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance

(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	8.74	6.626	3.724	7.248	9.408
ba = 2	5.336	4.904	3.736	4.880	9.436


NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

DROM_HD

High-Density Synchronous Diffusion Programmable ROM

Block Diagrams

DROM_HD has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from DROM_HD compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in DROM_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of DROM_HD.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ch}	CSN hold time from CK rise
t _{ckl}	Clock pulse width low	t _{acc}	Data access time
t _{ckh}	Clock pulse width high	t _{da}	De-access time
t _{as}	Address setup time	t _{dz}	DOUT drive to high-Z time
t _{ah}	Address hold time	t _{zd}	DOUT high-Z to drive time
t _{cs}	CSN setup time	t _{od}	OEN to valid output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

DROM_HD

High-Density Synchronous Diffusion Programmable ROM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.05	4.29	4.46	4.72	4.86	5.15	5.26	5.58
t _{ckl}	0.44	0.68	0.44	0.72	0.44	0.75	0.45	0.78
t _{ckh}	1.12	1.35	1.12	1.38	1.12	1.41	1.12	1.44
t _{as}	0.16	0.84	0.18	0.90	0.22	0.98	0.26	1.06
t _{ah}	0.61	0.86	0.61	0.90	0.61	0.93	0.61	0.97
t _{cs}	0.44	0.68	0.44	0.72	0.44	0.75	0.44	0.78
t _{ch}	0.52	0.78	0.52	0.81	0.52	0.85	0.52	0.88
t _{acc}	2.94	3.25	3.06	3.41	3.25	3.64	3.51	3.94
t _{da}	2.49	2.74	2.71	2.99	2.93	3.25	3.16	3.51
t _{dz}	0.75	0.75	0.89	0.88	1.03	1.03	1.19	1.19
t _{zd}	0.87	0.87	1.00	1.00	1.13	1.13	1.28	1.27
t _{od}	0.96	0.96	1.09	1.09	1.22	1.22	1.37	1.37
Power (μW/MHz)								
Power_read	284.25	287.74	601.59	605.65	1003.35	1007.62	1489.53	1493.63
Power_standby	32.63	79.37	52.54	121.27	72.61	163.47	92.83	205.98
Area (μm)								
Width	611.11	611.11	983.51	983.51	1355.64	1355.64	1727.51	1727.51
Height	222.56	427.50	303.20	588.78	383.84	750.06	464.48	911.34

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

High-Density Synchronous Diffusion Programmable ROM

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.05	4.29	4.46	4.72	4.86	5.15	5.26	5.58
t _{ckl}	0.44	0.68	0.44	0.72	0.44	0.75	0.44	0.78
t _{ckh}	1.12	1.35	1.12	1.38	1.12	1.41	1.12	1.44
t _{as}	0.16	0.84	0.18	0.90	0.22	0.98	0.26	1.06
t _{ah}	0.61	0.86	0.61	0.90	0.61	0.93	0.61	0.97
t _{cs}	0.45	0.68	0.45	0.72	0.45	0.75	0.44	0.78
t _{ch}	0.52	0.78	0.52	0.81	0.52	0.85	0.52	0.88
t _{acc}	2.98	3.25	3.10	3.41	3.29	3.64	3.54	3.94
t _{da}	2.50	2.75	2.72	3.01	2.94	3.26	3.17	3.52
t _{dz}	0.72	0.71	0.80	0.80	0.88	0.88	0.96	0.96
t _{zd}	0.84	0.84	0.92	0.91	0.99	0.99	1.07	1.07
t _{od}	0.92	0.92	1.00	1.00	1.08	1.08	1.16	1.16
Power (μW/MHz)								
Power_read	283.62	286.97	601.73	605.51	1003.47	1007.47	1488.83	1492.86
Power_standby	32.61	79.35	52.51	121.20	72.57	163.36	92.79	205.83
Area (μm)								
Width	610.82	610.82	983.44	983.44	1355.64	1355.64	1727.44	1727.44
Height	222.56	427.50	303.20	588.78	383.84	750.06	464.48	911.34

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode

DROM_HD

High-Density Synchronous Diffusion Programmable ROM

Reference Table


* For Ymux=32 (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.05	4.29	4.46	4.72	4.86	5.15	5.26	5.58
t _{ckl}	0.44	0.68	0.44	0.72	0.45	0.75	0.45	0.78
t _{ckh}	1.12	1.35	1.12	1.38	1.12	1.41	1.12	1.44
t _{as}	0.17	0.84	0.19	0.90	0.22	0.98	0.26	1.06
t _{ah}	0.61	0.86	0.61	0.90	0.61	0.93	0.61	0.96
t _{cs}	0.45	0.68	0.45	0.72	0.45	0.75	0.45	0.78
t _{ch}	0.52	0.78	0.52	0.81	0.52	0.84	0.52	0.88
t _{acc}	3.06	3.46	3.17	3.62	3.36	3.84	3.61	4.14
t _{da}	2.51	2.77	2.74	3.03	2.96	3.29	3.19	3.54
t _{dz}	0.70	0.69	0.75	0.75	0.81	0.81	0.87	0.87
t _{zd}	0.82	0.82	0.87	0.87	0.93	0.93	0.99	0.99
t _{od}	0.91	0.90	0.96	0.96	1.02	1.02	1.08	1.08
Power (μW/MHz)								
Power_read	281.73	284.99	601.01	604.96	1003.42	1007.94	1488.97	1493.94
Power_standby	32.61	79.35	52.49	121.20	72.54	163.40	92.77	205.95
Area (μm)								
Width	610.23	610.23	983.27	983.27	1355.64	1355.64	1727.34	1727.34
Height	222.56	427.50	303.20	588.78	383.84	750.06	464.48	911.34


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode

Timing Diagrams


Read Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable




NOTE: "don't care" means the condition that these pins are in normal operation mode.

MROM_HD

High-Density Synchronous Metal Programmable ROM

Logic Symbol



Features

- Suitable for high-density applications
- Metal-2 programmable code available
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tri-state output control
- Latched inputs and outputs
- Automatic power-down
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

MROM_HD is a synchronous metal-2 programmable ROM which is provided as a compiler. MROM_HD is intended for use in high-density applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

MROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

Parameter Description

MROM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance

(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	13.386	4.88	4.20	5.74	8.86
ba = 2	14.436	5.16	3.84	5.44	8.86


NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

MROM_HD

High-Density Synchronous Metal Programmable ROM

Block Diagrams

MROM_HD has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from MROM_HD compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in MROM_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of MROM_HD.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ch}	CSN hold time from CK rise
t _{ckl}	Clock pulse width low	t _{acc}	Data access time
t _{ckh}	Clock pulse width high	t _{da}	De-access time
t _{as}	Address setup time	t _{dz}	DOUT drive to high-Z time
t _{ah}	Address hold time	t _{zd}	DOUT high-Z to drive time
t _{cs}	CSN setup time	t _{od}	OEN to valid output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

MROM_HD

High-Density Synchronous Metal Programmable ROM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.17	4.44	4.77	5.09	5.34	5.71	5.90	6.31
t _{ckl}	0.60	0.85	0.60	0.91	0.60	0.97	0.60	1.03
t _{ckh}	1.18	1.45	1.18	1.50	1.18	1.55	1.18	1.60
t _{as}	0.10	0.97	0.13	1.02	0.24	1.17	0.44	1.40
t _{ah}	0.69	1.00	0.69	1.07	0.69	1.13	0.69	1.19
t _{cs}	0.60	0.85	0.60	0.91	0.60	0.97	0.60	1.03
t _{ch}	0.61	0.92	0.61	0.99	0.61	1.05	0.61	1.11
t _{acc}	2.95	3.25	3.29	3.65	3.68	4.10	4.12	4.60
t _{da}	2.52	2.81	2.93	3.28	3.33	3.73	3.72	4.17
t _{dz}	0.64	0.64	0.74	0.73	0.83	0.83	0.92	0.92
t _{zd}	0.76	0.75	0.85	0.84	0.93	0.93	1.02	1.01
t _{od}	0.83	0.83	0.95	0.92	1.01	1.01	1.09	1.09
Power (μW/MHz)								
Power_read	368.42	371.97	847.64	852.19	1498.81	1504.22	2321.92	2328.06
Power_standby	38.49	88.04	61.32	137.55	85.20	188.99	110.04	242.36
Area (μm)								
Width	567.93	567.93	997.77	997.77	1426.75	1426.75	1854.86	1854.86
Height	285.40	555.34	428.76	842.06	572.12	1128.78	715.48	1415.50

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

High-Density Synchronous Metal Programmable ROM

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.18	4.45	4.77	5.08	5.34	5.70	5.90	6.32
t _{ckl}	0.60	0.85	0.60	0.91	0.60	0.97	0.60	1.03
t _{ckh}	1.18	1.45	1.18	1.50	1.18	1.55	1.18	1.60
t _{as}	0.10	0.97	0.13	1.03	0.24	1.17	0.44	1.40
t _{ah}	0.69	1.00	0.69	1.07	0.69	1.13	0.69	1.19
t _{cs}	0.60	0.85	0.60	0.91	0.60	0.97	0.60	1.03
t _{ch}	0.61	0.92	0.61	0.99	0.61	1.05	0.61	1.11
t _{acc}	2.95	3.32	3.29	3.72	3.68	4.17	4.12	4.67
t _{da}	2.53	2.82	2.94	3.29	3.34	3.75	3.74	4.19
t _{dz}	0.60	0.60	0.66	0.66	0.72	0.72	0.78	0.78
t _{zd}	0.72	0.72	0.78	0.78	0.84	0.83	0.89	0.88
t _{od}	0.80	0.79	0.85	0.85	0.91	0.91	0.96	0.96
Power (μW/MHz)								
Power_read	367.69	371.16	847.48	852.11	1498.70	1504.41	2321.34	2328.06
Power_standby	38.39	89.04	61.30	138.50	85.15	189.87	109.95	243.15
Area (μm)								
Width	567.62	567.62	997.69	997.69	1426.75	1426.75	1854.80	1854.80
Height	285.40	555.34	428.76	842.06	572.12	1128.78	715.48	1415.50

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode

MROM_HD

High-Density Synchronous Metal Programmable ROM

Reference Table


* For Ymux=32 (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.18	4.44	4.77	5.08	5.34	5.70	5.90	6.30
t _{ckl}	0.60	0.85	0.60	0.91	0.60	0.97	0.60	1.02
t _{ckh}	1.18	1.45	1.18	1.50	1.18	1.55	1.18	1.60
t _{as}	0.10	0.97	0.13	1.03	0.24	1.17	0.44	1.40
t _{ah}	0.69	1.00	0.69	1.07	0.69	1.13	0.69	1.19
t _{cs}	0.60	0.85	0.60	0.91	0.60	0.96	0.60	1.02
t _{ch}	0.61	0.92	0.61	0.99	0.61	1.05	0.61	1.11
t _{acc}	3.03	3.47	3.36	3.72	3.75	4.29	4.19	4.78
t _{da}	2.55	2.85	2.96	3.29	3.36	3.76	3.76	4.19
t _{dz}	0.59	0.58	0.63	0.66	0.67	0.67	0.71	0.71
t _{zd}	0.70	0.70	0.74	0.78	0.78	0.78	0.82	0.82
t _{od}	0.78	0.77	0.82	0.85	0.86	0.85	0.90	0.89
Power (μW/MHz)								
Power_read	365.71	369.21	846.96	852.11	1498.49	1504.40	2320.31	2327.77
Power_standby	38.41	89.10	61.30	138.50	85.13	189.88	109.89	243.14
Area (μm)								
Width	566.98	566.98	997.51	997.69	1426.75	1426.75	1854.71	1854.71
Height	285.40	555.34	428.76	842.06	572.12	1128.78	715.48	1415.50


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode

Timing Diagrams


Read Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable




NOTE: "don't care" means the condition that these pins are in normal operation mode.

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Logic Symbol

arfram_hd_<nr>r<nw>w_<w>xm<y>



NOTES:

1. Words (w) is the number of words in ARFRAM_HD.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. Writes (nw) is the number of write ports (1-to-2).
5. Reads (nr) is the number of read ports (1-to-2).
6. $m = \lceil \log_2 w \rceil$

Features

- Suitable for high-density applications
- Separated data I/O
- Fully independent ports
- Synchronous write operation
- Asynchronous read operation
- Latched inputs and outputs
- Asynchronous tri-state output control
- Configurable 1-to-2 read ports
- Configurable 1-to-2 write ports
- Flexible aspect ratio
- Up to 16Kbits capacity
- Up to 1024 number of words
- Up to 64 number of bits per word

Function Description

ARFRAM_HD is a multi-port asynchronous register file which is provided as a compiler. ARFRAM_HD is intended for use in high-density applications. It allows maximum 4 ports with configurable 1-to-2 read ports and 1-to-2 write ports. All read and write ports are fully independent. At the falling edge of WEN, the write cycle is initiated. While WEN is low, the data at DI[] is written into the memory location specified on WA[]. At the rising edge of WEN, the write cycle ends. Regardless of WEN signal, the read cycle is always enabled. The data stored in the memory location specified on RA[] becomes valid through DOUT[] after a delay. When OEN is high, DOUT[] is placed in a high-impedance state.

ARFRAM_HD Write Function Table

WEN	WA	DI	Comment
H	X	X	Write disable mode
↓	Valid	X	Write cycle starts
↑	X	Valid	Write cycle ends

ARFRAM_HD Read Function Table

RA	OEN	DOUT	Comment
Valid	L	MEM (RA)	Read cycle
X	H	Z	Unconditional tri-state output

Parameter Description

ARFRAM_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y), Number of read ports(nr) and Number of write ports(nw).

Parameters		Ymux = 2	Ymux = 4	Ymux = 8
Words (w)	Min	4	8	16
	Max	256	512	1024
	Step	2	4	8
Bpw (b)	Min	1	1	1
	Max	64	32	16
	Step	1	1	1
Write ports (nw)		1, 2		
Read ports (nr)		1, 2		

Pin Descriptions

Name	I/O	Description
WEN<nw-1>	Write Enable	Write enable input on each write port. While it is high, it prevents a write-operation. The write-operation starts when it becomes low. At the rising edge of WEN, write-operation completed at the memory location.
WA<nw-1>[]	Write Address	Write address bus on each write port. It specifies the location that the data will be written in the write-operation. WA[] is latched at the falling edge of WEN.
DI<nw-1>[]	Data Input	Data input bus on each write port. It contains data values to be written into the memory during the write-cycle. DI[] is latched at the rising edge of WEN.
OEN<nr-1>	Data Output Enable	Output enable input on each read port. The output enable signal controls the output drivers from driven to tri-state condition unconditionally.
RA<nr-1>[]	Read Address	Read address bus on each read port. It specifies the location to be read in the read-operation.
DOUT<nr-1>[]	Data Output	Data output bus on each read port. It presents the data word stored in the location specified by RA[] address bus. Data output is in the high-impedance state when OEN is high.

Pin Capacitance

Unit: [SL]


WEN	OEN	WA	RA	DI	DOUT
1	0.4	0.36	1.66	0.2	1.19

NOTE: Each pin's capacitance is exactly same regardless of available mux types.

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Block Diagrams



Application Notes

1. Permitting over-the-cell routing
In ARFRAM_HD, the over-the-cell routing is permitted. While doing layout on the chip-level, any signals to be routed can be crossed over the area of register file generated by ARFRAM_HD compiler.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of ARFRAM_HD.
4. Contention mode under same addresses (RA[]=WA[]).
In ARFRAM_HD, simultaneous operations by both ports on the same address (RA[]=WA[]) as read/write, write/read, write/write operation, cause a contention problem. Simultaneous operation is defined as a state in which both ports are enabled, both address buses are equal. ARFRAM_HD has no scheme preventing the contention. Due to simultaneous operation, silicon will behave unpredictably. A write operation cannot complete and data appearing at outputs may not be valid. Please refer to the timing diagrams if you want to avoid the contention mode between both ports.

Characteristics

Definition for AC Timing (ns)	
Symbol	Description
t_{cyc}	Minimum address cycle time for read cycle
t_{as}	Address setup time from WA[] to WEN fall
t_{ah}	Address hold time from WEN fall to WA[]
t_{ds}	Data-in setup time from DI[] to WEN rise
t_{dh}	Data-in hold time from WEN rise to DI[]
t_{wen}	Minimum WEN pulse width low to guarantee write cycle
t_{wenh}	Minimum WEN pulse width high to guarantee write cycle
t_{wwc}	Write-write contention time from one WA[] to the other WA[]
t_{da}	De-access time from RA to DOUT
t_{acc}	Data access time for read cycle
t_{wda}	De-access time from WEN fall to DOUT
t_{wacc}	Data access time for WEN rise
t_{zd}	DOUT high-Z to drive time
t_{dz}	DOUT drive to high-Z time
t_{od}	OEN to valid output time
Definition for Power Consumption (μ W/MHz)	
Power_read	The dynamic average power consumption while in a read cycle
Power_write	The dynamic average power consumption while in a write cycle
Definition for Area (μ m)	
Width	The physical width in X-direction
Height	The physical height in Y-direction

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=2 (nr=1, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	32	64	128	256
bpw	8	16	32	64
Timing (ns)				
t _{cyc}	1.47	1.71	2.15	2.81
t _{as}	0.45	0.57	0.79	1.20
t _{ah}	0.58	0.65	0.79	1.08
t _{ds}	0.50	0.49	0.47	0.43
t _{dh}	0.12	0.13	0.15	0.19
t _{wen}	1.15	1.25	1.45	1.85
t _{wenh}	0.58	0.63	0.72	0.93
t _{acc}	1.47	1.71	2.15	2.81
t _{da}	0.30	0.30	0.30	0.30
t _{wacc}	1.69	1.95	2.41	3.12
t _{wda}	0.45	0.45	0.45	0.45
t _{dz}	0.18	0.20	0.24	0.33
t _{zd}	0.56	0.59	0.66	0.80
t _{od}	1.36	1.39	1.45	1.59
Power (μW/MHz)				
Power_read	15.17	32.57	75.86	196.42
Power_write	53.36	121.72	316.18	936.13
Area (μm)				
Width	215.33	315.42	515.58	915.91
Height	228.40	342.57	570.91	1027.60

Reference Table

* For Ymux=4 (nr=1, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	64	128	256	512
bpw	4	8	16	32
Timing (ns)				
t _{cyc}	1.53	1.77	2.20	2.91
t _{as}	0.38	0.45	0.59	0.81
t _{ah}	0.57	0.63	0.76	1.01
t _{ds}	0.48	0.50	0.54	0.61
t _{dh}	0.11	0.12	0.12	0.14
t _{wen}	1.16	1.27	1.47	1.89
t _{wenh}	0.58	0.63	0.74	0.95
t _{acc}	1.53	1.77	2.20	2.91
t _{da}	0.30	0.30	0.30	0.30
t _{wacc}	1.75	1.98	2.42	3.14
t _{wda}	0.45	0.45	0.45	0.45
t _{dz}	0.18	0.20	0.25	0.34
t _{zd}	0.56	0.60	0.67	0.82
t _{od}	1.44	1.47	1.54	1.68
Power (μW/MHz)				
Power_read	15.38	33.05	76.42	195.34
Power_write	42.72	108.88	285.62	856.81
Area (μm)				
Width	216.53	316.54	516.57	916.61
Height	212.88	327.08	555.48	1012.30

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=8 (nr=1, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	128	256	512	1024
bpw	2	4	8	16
Timing (ns)				
t _{cyc}	1.70	1.95	2.40	3.07
t _{as}	0.36	0.40	0.49	0.61
t _{ah}	0.57	0.63	0.74	0.98
t _{ds}	0.56	0.61	0.71	0.91
t _{dh}	0.11	0.11	0.12	0.13
t _{wen}	1.26	1.38	1.62	2.12
t _{wenh}	0.63	0.69	0.81	1.06
t _{acc}	1.70	1.95	2.40	3.07
t _{da}	0.30	0.30	0.30	0.30
t _{wacc}	1.90	2.15	2.60	3.26
t _{wda}	0.45	0.45	0.45	0.45
t _{dz}	0.18	0.20	0.25	0.34
t _{zd}	0.56	0.59	0.66	0.81
t _{od}	1.60	1.63	1.70	1.83
Power (μW/MHz)				
Power_read	16.36	34.81	78.97	196.35
Power_write	46.03	103.92	273.24	826.00
Area (μm)				
Width	216.94	316.62	515.99	914.72
Height	212.06	326.29	554.75	1011.67

Reference Table

* For Ymux=2 (nr=1, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	32	64	128	256
bpw	8	16	32	64
Timing (ns)				
t _{cyc}	1.56	1.81	2.23	2.78
t _{as}	0.99	1.14	1.43	2.02
t _{ah}	0.58	0.65	0.80	1.10
t _{ds}	0.51	0.49	0.47	0.40
t _{dh}	0.14	0.15	0.18	0.24
t _{wen}	1.19	1.30	1.52	1.97
t _{wenh}	0.60	0.65	0.76	0.99
t _{acc}	1.56	1.81	2.23	2.78
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	1.83	2.11	2.61	3.32
t _{wda}	0.46	0.46	0.46	0.46
t _{dz}	0.20	0.25	0.35	0.56
t _{zd}	0.60	0.67	0.83	1.15
t _{od}	1.22	1.28	1.40	1.69
t _{wwc}	1.19	1.30	1.52	1.97
Power (μW/MHz)				
Power_read	20.58	43.05	96.84	239.84
Power_write	57.96	132.63	348.16	1043.89
Area (μm)				
Width	271.86	395.38	642.41	1136.49
Height	276.38	399.91	646.98	1141.12

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=4 (nr=1, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	64	128	256	512
bpw	4	8	16	32
Timing (ns)				
t _{cyc}	1.77	1.99	2.39	3.04
t _{as}	0.42	0.51	0.69	1.01
t _{ah}	0.57	0.64	0.77	1.05
t _{ds}	0.50	0.51	0.53	0.58
t _{dh}	0.12	0.13	0.14	0.17
t _{wen}	1.20	1.32	1.54	2.00
t _{wenh}	0.60	0.66	0.77	1.00
t _{acc}	1.77	1.99	2.39	3.04
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	2.03	2.28	2.75	3.49
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.18	0.22	0.28	0.42
t _{zd}	0.57	0.62	0.72	0.93
t _{od}	1.31	1.35	1.43	1.58
t _{wwc}	1.20	1.32	1.54	2.00
Power (μW/MHz)				
Power_read	19.18	40.01	89.66	220.93
Power_write	51.85	119.44	317.63	966.11
Area (μm)				
Width	273.54	396.96	643.80	1137.47
Height	276.70	400.23	647.43	1141.73

Reference Table

* For Ymux=8 (nr=1, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	128	256	512	1024
bpw	2	4	8	16
Timing (ns)				
t _{cyc}	1.78	2.03	2.46	3.02
t _{as}	0.41	0.47	0.58	0.76
t _{ah}	0.57	0.63	0.75	1.01
t _{ds}	0.75	0.81	0.91	1.10
t _{dh}	0.12	0.12	0.12	0.13
t _{wen}	1.52	1.65	1.91	2.45
t _{wenh}	0.76	0.82	0.95	1.23
t _{acc}	1.78	2.03	2.46	3.02
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	2.03	2.30	2.78	3.42
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.18	0.20	0.25	0.34
t _{zd}	0.56	0.59	0.67	0.83
t _{od}	1.41	1.44	1.49	1.60
t _{wwc}	1.52	1.65	1.91	2.45
Power (μW/MHz)				
Power_read	19.29	39.70	88.26	216.35
Power_write	52.86	119.27	315.12	959.01
Area (μm)				
Width	274.12	397.07	642.99	1134.81
Height	275.60	399.21	646.44	1140.89

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=2 (nr=2, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	32	64	128	256
bpw	8	16	32	64
Timing (ns)				
t _{cyc}	1.60	1.88	2.35	2.87
t _{as}	0.78	0.92	1.20	1.76
t _{ah}	0.57	0.64	0.77	1.05
t _{ds}	0.50	0.49	0.46	0.44
t _{dh}	0.12	0.13	0.15	0.19
t _{wen}	1.17	1.27	1.47	1.90
t _{wenh}	0.58	0.63	0.74	0.95
t _{acc}	1.60	1.88	2.35	2.87
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	1.84	2.16	2.69	3.35
t _{wda}	0.45	0.45	0.45	0.46
t _{dz}	0.19	0.21	0.26	0.36
t _{zd}	0.49	0.53	0.61	0.78
t _{od}	1.18	1.21	1.28	1.41
Power (μW/MHz)				
Power_read	18.94	40.44	92.85	235.25
Power_write	56.79	130.16	341.79	1024.63
Area (μm)				
Width	289.55	417.32	672.85	1183.92
Height	255.39	380.63	631.11	1132.06

Reference Table

* For Ymux=4 (nr=2, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	64	128	256	512
bpw	4	8	16	32
Timing (ns)				
t _{cyc}	1.87	2.12	2.57	3.20
t _{as}	0.42	0.52	0.69	1.02
t _{ah}	0.57	0.62	0.74	1.00
t _{ds}	0.50	0.52	0.56	0.64
t _{dh}	0.11	0.12	0.12	0.14
t _{wen}	1.19	1.30	1.52	1.98
t _{wenh}	0.59	0.65	0.76	0.99
t _{acc}	1.87	2.12	2.57	3.20
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	2.11	2.38	2.88	3.62
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.18	0.21	0.26	0.35
t _{zd}	0.49	0.53	0.61	0.76
t _{od}	1.29	1.32	1.38	1.49
Power (μW/MHz)				
Power_read	17.80	37.84	86.62	218.91
Power_write	51.35	117.91	313.81	956.66
Area (μm)				
Width	291.46	419.11	674.42	1185.03
Height	255.79	381.09	631.67	1132.84

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=8 (nr=2, nw=1) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	128	256	512	1024
bpw	2	4	8	16
Timing (ns)				
t _{cyc}	1.96	2.25	2.72	3.24
t _{as}	0.36	0.42	0.53	0.70
t _{ah}	0.57	0.62	0.74	0.97
t _{ds}	0.76	0.82	0.94	1.18
t _{dh}	0.11	0.11	0.12	0.13
t _{wen}	1.47	1.60	1.87	2.44
t _{wenh}	0.74	0.80	0.94	1.22
t _{acc}	1.96	2.25	2.72	3.24
t _{da}	0.32	0.32	0.32	0.32
t _{wacc}	2.19	2.50	3.01	3.62
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.18	0.21	0.25	0.35
t _{zd}	0.49	0.53	0.60	0.76
t _{od}	1.53	1.56	1.61	1.72
Power (μW/MHz)				
Power_read	18.49	39.36	89.50	223.34
Power_write	51.94	117.44	309.85	940.41
Area (μm)				
Width	292.10	419.23	673.50	1182.02
Height	254.40	379.74	630.42	1131.77

Reference Table

* For Ymux=2 (nr=2, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	32	64	128	256
bpw	8	16	32	64
Timing (ns)				
t _{cyc}	1.57	1.82	2.24	2.77
t _{as}	0.63	0.79	1.10	1.71
t _{ah}	0.58	0.65	0.80	1.12
t _{ds}	0.45	0.44	0.42	0.34
t _{dh}	0.09	0.09	0.11	0.23
t _{wen}	1.18	1.29	1.51	1.96
t _{wenh}	0.59	0.65	0.76	0.98
t _{acc}	1.57	1.82	2.24	2.77
t _{da}	0.31	0.31	0.31	0.31
t _{wacc}	1.83	2.12	2.61	3.29
t _{wda}	0.45	0.45	0.45	0.45
t _{dz}	0.20	0.24	0.34	0.55
t _{zd}	0.59	0.67	0.82	1.14
t _{od}	1.22	1.27	1.39	1.68
t _{wwc}	1.18	1.29	1.51	1.96
Power (μW/MHz)				
Power_read	20.09	43.55	100.05	251.39
Power_write	58.58	137.61	371.51	1142.60
Area (μm)				
Width	354.11	513.31	831.72	1468.54
Height	263.96	387.98	636.02	1132.10

ARFRAM_HD

High-Density Multi-port Asynchronous Register File

Reference Table

* For Ymux=4 (nr=2, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)

Parameters				
words	64	128	256	512
bpw	4	8	16	32
Timing (ns)				
t _{cyc}	1.92	2.15	2.55	3.18
t _{as}	0.39	0.48	0.66	1.00
t _{ah}	0.57	0.64	0.77	1.05
t _{ds}	0.49	0.50	0.52	0.57
t _{dh}	0.10	0.10	0.10	0.14
t _{wen}	1.20	1.31	1.53	1.98
t _{wenh}	0.60	0.65	0.77	0.99
t _{acc}	1.92	2.15	2.55	3.18
t _{da}	0.31	0.31	0.31	0.31
t _{wacc}	2.12	2.37	2.83	3.55
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.18	0.21	0.27	0.41
t _{zd}	0.57	0.62	0.72	0.93
t _{od}	1.31	1.35	1.43	1.58
t _{wwc}	1.20	1.31	1.53	1.98
Power (μW/MHz)				
Power_read	19.28	41.23	93.76	233.36
Power_write	52.93	124.67	341.57	1069.11
Area (μm)				
Width	356.51	515.57	833.69	1469.94
Height	264.31	388.38	636.51	1132.77

Reference Table

* For Ymux=8 (nr=2, nw=2) (Typical process, 2.5V, 25°C, Output load=10SL, Input slope=0.2 ns, SA=0.5)


Parameters				
words	128	256	512	1024
bpw	2	4	8	16
Timing (ns)				
t _{cyc}	1.78	2.03	2.46	3.02
t _{as}	0.36	0.41	0.52	0.74
t _{ah}	0.57	0.63	0.75	1.01
t _{ds}	0.75	0.81	0.92	1.12
t _{dh}	0.10	0.10	0.10	0.10
t _{wen}	1.52	1.63	1.87	2.42
t _{wenh}	0.76	0.82	0.94	1.21
t _{acc}	1.78	2.03	2.46	3.02
t _{da}	0.31	0.31	0.31	0.31
t _{wacc}	2.03	2.30	2.77	3.40
t _{wda}	0.47	0.47	0.47	0.47
t _{dz}	0.17	0.20	0.24	0.34
t _{zd}	0.55	0.59	0.66	0.82
t _{od}	1.41	1.43	1.48	1.60
t _{wwc}	1.52	1.63	1.87	2.42
Power (μW/MHz)				
Power_read	20.24	43.27	98.07	242.66
Power_write	53.78	125.16	340.83	1063.80
Area (μm)				
Width	357.32	515.72	832.53	1466.16
Height	263.10	387.20	635.42	1131.84

ARFRAM_HD


High-Density Multi-port Asynchronous Register File

Timing Diagrams


Read Cycle



Write Cycle




OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.


High-Density Multi-port Asynchronous Register File

Read-Write Contention



NOTE: If WEN[] falls while WA[] is same as RA[], it is a read-write contention. While WEN[] is low, DOUT[] is UNKNOWN and write data is valid. After t_{wacc} from the rising edge of WEN, the read data (D1) is valid.

Write-Read Contention




NOTE: While WEN is low, if read access begins by RA<>[] which is same as WA<>[] latched at the falling edge of WEN, it is Write-read contention. The read data is invalid whereas the write is still valid. After transition of RA[], DOUT[] is UNKNOWN and write is valid. After t_{wacc} from the rising edge of WEN, DOUT[] is valid.

ARFRAM_HD

High-Density Multi-port Asynchronous Register File


Write-Write Contention



NOTE: If address latched at the falling edge of write ports are same and t_1 is smaller than or equal to $twwc$, it is write-write contention. The data stored at current address will be unpredictable.

High-Density Synchronous First-In First-Out Memory

Logic Symbol



Features

- Suitable for high-density applications
- Over-read and over-write protection capability
- Retransmit capability
- Synchronous operation
- Duty-free clock cycle
- Asynchronous tri-state output control
- Latched full and empty status flag output
- Automatic power-down
- Flexible aspect ratio
- Up to 32Kbits capacity
- Up to 4K number of words
- Up to 64 number of bits per word

Function Description

FIFO_HD is a synchronous first-in first-out buffer memory which is provided as a compiler. FIFO_HD is intended for use in high-density applications. After valid reset, on the rising of WCK, the write cycle is initiated when WEN is low, RST is high and FF is low. The data on DI[] is written into the memory location specified by the write pointer. During normal write operation, the rising edge of WCK will reset EF if it is set. At the last available memory location, write operation will set FF. DI[] and WEN must satisfy the setup and hold requirements with respect to the rising edge of WCK.

On the rising edge of RCK, the read cycle is initiated when REN is low, RST is high, RTM is high and EF is low. The data located in the memory specified by the read pointer comes in DOUT[] after some delay. During normal read operation, the rising edge of RCK will reset FF if it is set. At the last available memory location with available data, read operation will set EF. A valid DOUT[] will be possibly in some specified time after the rising edge of RCK, under that OEN is low. And the output data will remain unchanged until the next read, reset, or retransmit mode come in. REN must satisfy the setup and hold requirements with respect to the rising edge of RCK. When OEN is high, DOUT[] is placed in a high-impedance state.

In reset mode, a reset is globally initiated at the falling edge of RST. The reset operation will set EF and reset FF and make the data output zero. The reset operation will initiate the read pointer and the write pointer as 0. After reset operation, the status of EF will make RCK inoperable. The valid write input signal will become operable as RST is high. The read input signal will remain inoperable until EF is reset by the first read input signal valid write.

In retransmit mode, a retransmit is initiated at the falling edge of RTM only if the total number of writes after a reset operation is less than the word size of the memory in FIFO_HD and more than 0 ($0 < \text{total number of write} < W$). The retransmit operation will initiate the read pointer as 0 to allow the retransmission of data, make DOUT[] zero and make EF reset if it is set. The valid read input signal will become operable as RTM is high.

FIFO_HD

High-Density Synchronous First-In First-Out Memory

FIFO_HD Function Table

RST	WEN	WCK	REN	RCK	RTM	OEN	EF	FF	DI	DOUT	COMMENT
↓	X	X	X	X	X	X	↑	↓	X	L	Reset mode
H	X	X	X	X	↓	X	↓	X	X	L	Retransmit mode
H	X	X	L	↑	H	L	L	↓	X	DOUT(t)	Read mode
H	L	↑	X	X	X	X	↓	L	valid	DOUT(t-1)	Write mode
H	X	X	L	↑	H	L	↑	L	X	DOUT(t)	Read and Empty mode
H	L	↑	X	X	X	X	L	↑	valid	DOUT(t-1)	Write and Full mode
H	X	X	H	↑	H	L	X	X	X	DOUT(t-1)	Note 1
H	X	X	L	↑	H	L	H	X	X	DOUT(t-1)	Note 2
X	X	X	X	X	X	H	X	X	X	Hi-Z	Note 3
H	H	↑	X	X	X	X	X	X	valid	DOUT(t-1)	Note 4
H	L	↑	X	X	X	X	X	H	valid	DOUT(t-1)	Note 5

NOTES:

1. Read is blocked when REN is high and the read port is in disable mode.
2. Read is blocked when EF is high (overhead protection).
3. Under that OEN is high, DOUT[] goes to tri-state output mode.
4. Write is blocked when WEN is high and the write port is in disable mode.
5. Write is blocked when FF is high (overwrite protection).

Parameter Description

FIFO_HD is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b) and Column mux(y).

Parameters		Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	Min	32	64	128	256
	Max	512	1024	2048	4096
	Step	32	64	128	256
Bpw (b)	Min	2	2	2	2
	Max	64	32	16	8
	Step	1	1	1	1

High-Density Synchronous First-In First-Out Memory

Pin Descriptions

Name	I/O	Description
RCK	Read Clock	Read clock input. Upon the rising edge of RCK, it begins a read operation when REN is low, RST is high, RTM is high and EF is low.
REN	Read Enable	Read enable input. When REN is low, the read access occurs properly. Conversely when REN is high, no read access can occur and the read port of the FIFO_HD goes to power down mode. REN is latched at the rising edge of RCK.
OEN	Data Output Enable	Output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
RST	Reset	Reset input. Upon the falling edge of RST, the reset mode is initiated. RST resets the read and write pointer to their initial position. RST sets EF and resets FF. RST makes DOUT[] zero.
RTM	Retransmit	Retransmit input. Upon the falling edge of RTM, the retransmit mode is initiated, provided that RST is high. RTM resets the read pointer to its initial position. RTM makes DOUT[] zero.
WCK	Write Clock	Write clock input. Upon the rising edge of WCK, it begins a write operation when WE is low, RST is high and FF is low.
WEN	Write Enable	Write enable input. When WEN is low, a write access occurs properly. Conversely when WEN is high, no write access can occur and the write port of the FIFO_HD goes to power down mode. WEN is latched at the rising edge of WCK.
DI	Date In	Data input bus. DI[] is latched on the rising edge of WCK. Data input is written into the addressed location in write mode.
EF	Empty Flag	Empty flag. If the memory has no data to be read, EF goes high. Valid reset makes EF high and valid retransmit makes it low.
FF	Full Flag	Full flag. If the memory has no vacancy to write data, FF goes high. Valid reset makes FF low.
DOUT	Data Out	Data output bus. Data output is valid after the rising edge of RCK while the FIFO_HD is in read mode when OEN is low. Conversely when OEN is high, DOUT[] goes to high-impedance state. By reset or retransmit operation. DOUT[] goes to 0.

Pin Capacitance

Unit: [SL]


RST	RTM	WCK	RCK	OEN	WEN	REN	DI	DOUT
7.3	4.3	7.7	4.8	3.5	2.2	1.3	1.2	6.2

NOTE: Each pin's capacitance is exactly same regardless of available mux types.

FIFO_HD

High-Density Synchronous First-In First-Out Memory

Block Diagrams



Application Notes

1. Permitting over-the-cell routing.
In chip-level layout, over-the-cell routing in FIFO_HD is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of FIFO_HD.
4. FIFO_HD must be reset before any operation performed.
The reset operation initiates the read pointer and the write pointer as 0.
5. FIFO_HD should be reset again before resuming normal operation if abnormal operation is performed.
Abnormal operations are invalid retransmit operation, and read/write operation causing timing requirement violations.
6. The retransmit operation initiates the read pointer as 0.
7. The retransmit is useful only when the total number of writes after a reset is less than the total word capacity of the FIFO_HD and more than 0.
8. Outputs are not changed until the first valid read after a reset or retransmit.

Characteristics

Definition for AC Timing (ns)	
Symbol	Description
t_{rst}	Min RST pulse width low
t_{rtm}	Min RTM pulse width low
t_{rcyc}	Read clock cycle time
t_{rckh}	Read clock pulse width high
t_{rckl}	Read clock pulse width low
t_{wcyc}	Write clock cycle time
t_{wckh}	Write clock pulse width high
t_{wckl}	Write clock pulse width low
t_{rs}	REN setup to RCK rising
t_{rh}	REN hold from RCK rising
t_{ws}	WEN setup to WCK rising
t_{wh}	WEN hold from WCK rising
t_{wrsc}	WCK setup to RCK rising
t_{rwcs}	RCK setup to WCK rising
t_{ds}	DI setup to WCK rising
t_{dh}	DI hold from WCK rising
t_{rstw}	RST setup to WCK rising
t_{rtmr}	RTM setup to RCK rising
t_{rste}	Delay from RST falling to EF rising
t_{rstf}	Delay from RST falling to FF falling
t_{rstd}	Delay from RST falling to DOUT zero
t_{rstda}	Output hold time from RST falling to DOUT
t_{rtme}	Delay from RTM falling to EF falling
t_{rtmd}	Delay from RTM falling to DOUT zero
t_{rtmda}	Output hold time from RTM falling to DOUT
t_{we}	Delay from WCK rising to EF falling
t_{wf}	Delay from WCK rising to FF rising
t_{rf}	Delay from RCK rising to FF falling
t_{re}	Delay from RCK rising to EF rising
t_{acc}	Data access time (Delay from RCK rising to DOUT[] transition)
t_{da}	De-access time (Output hold time from RCK rising to DOUT[])
t_{dz}	DOUT drive to high-Z time
t_{zd}	DOUT high-Z to drive time
t_{od}	OEN to valid output time
Definition for Power Consumption (μ W/MHz)	
Power_read	The dynamic average power consumption while in a read cycle
Power_write	The dynamic average power consumption while in a write cycle
Definition for Area (μ m)	
Width	The physical width in X-direction
Height	The physical height in Y-direction

FIFO_HD

High-Density Synchronous First-In First-Out Memory

Reference Table

* For Ymux=4 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA = 0.5)

Parameters				
words	128	256	384	512
bpw	16	32	48	64
Timing (ns)				
t _{rst}	2.73	2.98	3.22	3.47
t _{rtm}	3.32	3.54	3.81	4.14
t _{rcyc}	2.65	2.96	3.26	3.56
t _{rckl}	0.76	0.76	0.76	0.76
t _{rckh}	0.54	0.54	0.54	0.54
t _{wcyc}	2.60	2.90	3.21	3.51
t _{wckl}	1.09	1.13	1.17	1.21
t _{wckh}	0.65	0.68	0.72	0.76
t _{rs}	0.45	0.45	0.45	0.45
t _{rh}	0.11	0.11	0.11	0.11
t _{ws}	0.48	0.48	0.48	0.48
t _{wh}	0.11	0.11	0.11	0.11
t _{ds}	0.08	0.06	0.04	0.02
t _{dh}	0.49	0.52	0.56	0.60
t _{rstw}	0.60	0.60	0.60	0.60
t _{rtmr}	0.70	0.70	0.70	0.70
t _{wrcs}	1.22	1.22	1.22	1.22
t _{rwcs}	1.26	1.32	1.42	1.55
t _{rstd}	2.71	2.98	3.26	3.55
t _{rstda}	0.32	0.32	0.32	0.32
t _{rste}	2.72	2.96	3.21	3.45
t _{rstf}	2.72	2.96	3.21	3.45
t _{rtmd}	2.70	2.97	3.25	3.55
t _{rtmda}	0.31	0.31	0.31	0.31
t _{rtme}	3.35	3.57	3.85	4.17
t _{we}	0.68	0.68	0.68	0.68
t _{wf}	2.23	2.42	2.62	2.82
t _{re}	2.08	2.27	2.46	2.67
t _{rf}	0.69	0.69	0.70	0.70
t _{acc}	2.15	2.37	2.61	2.85
t _{da}	1.73	1.94	2.15	2.38
t _{dz}	0.39	0.47	0.54	0.61
t _{zd}	0.45	0.47	0.50	0.52
t _{od}	0.70	0.75	0.80	0.85
Power (μW/MHz)				
Power_read	173.60	303.03	440.99	587.45
Power_write	169.14	299.42	439.63	589.78
Area (μm)				
Width	577.92	969.60	1361.28	1752.96
Height	367.20	541.92	716.64	891.36

High-Density Synchronous First-In First-Out Memory

Reference Table

* For Ymux=8

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA = 0.5)

Parameters				
words	256	512	768	1024
bpw	8	16	24	32
Timing (ns)				
t _{rst}	2.74	2.99	3.23	3.48
t _{rtm}	3.33	3.55	3.82	4.15
t _{rcyc}	2.67	2.98	3.28	3.57
t _{rckl}	0.76	0.76	0.77	0.77
t _{rckh}	0.54	0.54	0.54	0.54
t _{wcyc}	2.61	2.91	3.21	3.52
t _{wckl}	1.09	1.12	1.15	1.18
t _{wckh}	0.66	0.69	0.72	0.75
t _{rs}	0.45	0.45	0.45	0.45
t _{rh}	0.11	0.11	0.11	0.11
t _{ws}	0.48	0.48	0.48	0.48
t _{wh}	0.11	0.11	0.11	0.11
t _{ds}	0.09	0.07	0.05	0.04
t _{dh}	0.48	0.51	0.54	0.58
t _{rstw}	0.60	0.60	0.60	0.60
t _{rtmr}	0.56	0.56	0.56	0.56
t _{wrcs}	1.22	1.22	1.22	1.22
t _{rwcs}	1.26	1.32	1.41	1.55
t _{rstd}	2.80	3.07	3.35	3.64
t _{rstda}	0.32	0.32	0.32	0.32
t _{rste}	2.72	2.96	3.21	3.47
t _{rstf}	2.72	2.96	3.21	3.47
t _{rtmd}	2.79	3.06	3.34	3.63
t _{rtmda}	0.31	0.31	0.30	0.30
t _{rtme}	3.37	3.59	3.86	4.19
t _{we}	0.68	0.68	0.68	0.68
t _{wf}	2.23	2.41	2.61	2.81
t _{re}	2.09	2.27	2.47	2.67
t _{rf}	0.69	0.69	0.69	0.69
t _{acc}	2.17	2.40	2.63	2.87
t _{da}	1.71	1.92	2.14	2.37
t _{dz}	0.38	0.43	0.49	0.55
t _{zd}	0.45	0.47	0.49	0.51
t _{od}	0.69	0.72	0.75	0.77
Power (μW/MHz)				
Power_read	150.94	256.35	369.00	488.88
Power_write	131.96	220.73	315.77	417.07
Area (μm)				
Width	577.92	969.60	1361.28	1752.96
Height	384.18	558.90	733.62	908.34

FIFO_HD

High-Density Synchronous First-In First-Out Memory

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	512	1024	1536	2048
bpw	4	8	12	16
Timing (ns)				
t _{rst}	2.74	2.99	3.23	3.48
t _{rtm}	3.33	3.55	3.83	4.15
t _{rcyc}	2.73	3.00	3.28	3.56
t _{rckl}	0.76	0.76	0.77	0.77
t _{rckh}	0.54	0.54	0.54	0.54
t _{wcyc}	2.61	2.91	3.22	3.52
t _{wckl}	1.08	1.11	1.14	1.17
t _{wckh}	0.68	0.71	0.74	0.77
t _{rs}	0.45	0.45	0.45	0.45
t _{rh}	0.11	0.11	0.11	0.11
t _{ws}	0.48	0.48	0.48	0.48
t _{wh}	0.11	0.11	0.11	0.11
t _{ds}	0.09	0.07	0.06	0.04
t _{dh}	0.48	0.51	0.53	0.56
t _{rstw}	0.60	0.60	0.60	0.60
t _{rtmr}	0.56	0.56	0.56	0.56
t _{wrcs}	1.22	1.22	1.22	1.22
t _{rwcs}	1.26	1.32	1.41	1.55
t _{rstd}	2.97	3.24	3.52	3.81
t _{rstda}	0.32	0.32	0.32	0.32
t _{rste}	2.71	2.95	3.20	3.46
t _{rstf}	2.71	2.95	3.20	3.46
t _{rtmd}	2.96	3.23	3.51	3.80
t _{rtmda}	0.31	0.31	0.30	0.30
t _{rtme}	3.37	3.59	3.86	4.19
t _{we}	0.68	0.68	0.68	0.68
t _{wf}	2.23	2.42	2.61	2.81
t _{re}	2.08	2.27	2.47	2.67
t _{rf}	0.69	0.69	0.69	0.69
t _{acc}	2.22	2.45	2.68	2.92
t _{da}	1.68	1.89	2.11	2.34
t _{dz}	0.37	0.42	0.47	0.52
t _{zd}	0.45	0.46	0.48	0.50
t _{od}	0.69	0.71	0.74	0.76
Power (μW/MHz)				
Power_read	135.27	226.91	326.22	433.20
Power_write	110.48	178.15	250.39	327.19
Area (μm)				
Width	577.92	969.60	1361.28	1752.96
Height	388.10	562.82	737.54	912.26

High-Density Synchronous First-In First-Out Memory

Reference Table

* For Ymux=32


(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	1024	2048	3072	4096
bpw	2	4	6	8
Timing (ns)				
t _{rst}	2.74	2.99	3.24	3.49
t _{rtm}	3.34	3.56	3.84	4.17
t _{rcyc}	2.79	3.06	3.33	3.59
t _{rckl}	0.76	0.76	0.77	0.77
t _{rckh}	0.54	0.54	0.54	0.54
t _{wcyc}	2.61	2.92	3.22	3.53
t _{wckl}	1.08	1.11	1.14	1.16
t _{wckh}	0.74	0.76	0.79	0.81
t _{rs}	0.45	0.45	0.45	0.45
t _{rh}	0.11	0.11	0.11	0.11
t _{ws}	0.48	0.48	0.48	0.48
t _{wh}	0.11	0.11	0.11	0.11
t _{ds}	0.10	0.08	0.06	0.05
t _{dh}	0.48	0.50	0.53	0.56
t _{rstw}	0.60	0.60	0.60	0.60
t _{rtmr}	0.56	0.56	0.56	0.56
t _{wrcs}	1.22	1.22	1.22	1.22
t _{rwcs}	1.26	1.32	1.41	1.55
t _{rstd}	3.29	3.57	3.85	4.13
t _{rstda}	0.32	0.32	0.32	0.32
t _{rste}	2.71	2.96	3.21	3.47
t _{rstf}	2.71	2.96	3.21	3.47
t _{rtmd}	3.28	3.56	3.84	4.12
t _{rtmda}	0.31	0.31	0.31	0.31
t _{rtme}	3.37	3.60	3.87	4.21
t _{we}	0.68	0.68	0.68	0.68
t _{wf}	2.23	2.42	2.62	2.81
t _{re}	2.08	2.27	2.46	2.66
t _{rf}	0.69	0.69	0.69	0.69
t _{acc}	2.30	2.53	2.76	3.00
t _{da}	1.62	1.83	2.05	2.26
t _{dz}	0.37	0.41	0.45	0.50
t _{zd}	0.45	0.46	0.48	0.49
t _{od}	0.69	0.71	0.73	0.75
Power (μW/MHz)				
Power_read	126.21	208.85	299.06	396.82
Power_write	97.58	154.68	215.62	280.39
Area (μm)				
Width	577.92	969.60	1361.28	1752.96
Height	405.36	580.08	754.80	929.52

High-Density Synchronous First-In First-Out Memory

Timing Diagrams

Read Cycle




NOTES:

1. Read cycle is blocked during empty state (over-read protected)
2. twrcs is the timing related between first write on empty state and first subsequent read. If it is not satisfied, DOUT[i] will be unpredictable.
3. tre is the timing related to the read and empty mode.

High-Density Synchronous First-In First-Out Memory


Write Cycle



NOTES:

1. Write cycle is blocked during full state (over-write protected)
2. t_{wcs} is the timing related between first read on full state and first subsequent write.
If it is not satisfied, $DOUT[i]$ (not shown) will be unpredictable.
3. t_{wf} is the timing related to the write and full mode.

Reset Cycle




NOTE: Read cycle and write cycle are blocked when RST is low.

FIFO_HD


High-Density Synchronous First-In First-Out Memory

Retransmit Cycle




NOTE: Read cycle is blocked when RTM is low.

OEN Controlled Output Enable



Logic Symbol



Features

- Suitable for low-power application
- Separated data I/O
- Synchronous operation
- Asynchronous tristate output
- Latched inputs and outputs
- Automatic power-down mode available
- Self-controlled circuit available
- Zero standby current
- Low noise output optimization
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPSRAM_LP is a single-port synchronous static RAM which is provided as a compiler. SPSRAM_LP is intended for use in low-power applications. On the rising edge of CK, the write cycle is initiated when WEN is low and CSN is low. The data on DI[] is written into the memory location specified on A[]. During the write cycle, DOUT[] remains stable. On the rising edge of CK, the read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] and DI[] are disabled, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

CK	CSN	WEN	OEN	A	DI	DOUT	COMMENT
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read cycle

Parameter Description

SPSRAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y) and Number of banks(ba).

SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	1	1	1	1
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If WEN is high on the rising edge of CK, the RAM is in read mode. Upon the falling edge of CK, the RAM is in a precharge state.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are present at DOUT.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other input. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI []	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.

Pin Capacitance


Unit: [SL]

	CK	CSN	WEN	OEN	A	DI	DOUT
ba = 1	8.15	14.34	7.73	5.75	9.02	3.07	9.44
ba = 2	8.15	14.34	7.73	5.75	9.02	3.07	9.44

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPSRAM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from SPSRAM_LP compiler. Power is only consumed by the bank that is selected by the address and the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing.
In chip-level layout, over-the-cell routing in SPSRAM_LP is permitted only for Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPSRAM_LP.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ckh}	Clock pulse width high
t _{ckl}	Clock pulse width low	t _{as}	Address setup time
t _{ah}	Address hold time	t _{cs}	CSN setup time
t _{ch}	CSN hold time	t _{ds}	Data-In setup time
t _{dh}	Data-In hold time	t _{ws}	WEN setup time
t _{wh}	WEN hold time	t _{acc}	Data access time
t _{da}	De-access time	t _{dz}	DOUT drive to high-Z time
t _{zd}	DOUT high-Z to drive time	t _{od}	OEN to valid output time
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

* For Ymux=4

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	256	512	512	1024	768	1536	1024	2048
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.92	5.67	5.92	6.79	6.95	7.86	8.02	8.90
t _{ckl}	1.48	1.84	1.59	2.03	1.71	2.21	1.84	2.38
t _{ckh}	2.45	2.69	2.99	3.30	3.49	3.88	3.96	4.43
t _{as}	0.61	0.87	0.64	0.94	0.74	1.02	0.90	1.09
t _{ah}	0.81	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{cs}	1.21	1.69	1.34	1.91	1.46	2.11	1.58	2.30
t _{ch}	0.39	0.63	0.39	0.71	0.39	0.79	0.39	0.87
t _{ds}	0.52	0.66	0.52	0.75	0.52	0.84	0.52	0.93
t _{dh}	0.93	1.34	1.02	1.51	1.10	1.67	1.16	1.81
t _{ws}	0.86	1.10	0.92	1.20	0.96	1.28	0.96	1.34
t _{wh}	0.81	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{acc}	3.31	3.63	3.98	4.42	4.62	5.18	5.23	5.92
t _{da}	2.92	3.18	3.58	3.94	4.22	4.66	4.83	5.35
t _{dz}	0.72	0.71	0.82	0.82	0.90	0.90	0.97	0.97
t _{zd}	0.85	0.84	0.96	0.94	1.05	1.04	1.13	1.14
t _{od}	0.99	0.99	1.10	1.10	1.19	1.19	1.27	1.27
Power (μW/MHz)								
Power_read	143.46	163.94	281.99	335.50	432.10	537.16	593.77	768.90
Power_write	172.57	186.29	376.58	406.40	629.80	684.41	932.24	1020.33
Power_standby	0.99	4.15	1.12	5.11	1.14	5.95	1.04	6.65
Area (μm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.92	5.66	5.91	6.76	6.94	7.82	8.02	8.83
t _{ckl}	1.48	1.84	1.55	2.03	1.62	2.21	1.69	2.39
t _{ckh}	2.46	2.69	2.99	3.30	3.49	3.88	3.96	4.43
t _{as}	0.62	0.87	0.62	0.94	0.67	1.02	0.76	1.09
t _{ah}	0.81	1.00	0.84	1.09	0.86	1.18	0.87	1.28
t _{cs}	1.20	1.68	1.28	1.88	1.35	2.07	1.39	2.25
t _{ch}	0.39	0.63	0.39	0.71	0.39	0.79	0.39	0.87
t _{ds}	0.52	0.66	0.52	0.75	0.52	0.84	0.52	0.93
t _{dh}	0.92	1.31	0.99	1.46	1.05	1.62	1.10	1.76
t _{ws}	0.86	1.10	0.92	1.18	0.96	1.27	0.96	1.35
t _{wh}	0.81	1.00	0.84	1.09	0.86	1.18	0.87	1.28
t _{acc}	3.35	3.68	4.02	4.47	4.65	5.23	5.26	5.96
t _{da}	2.93	3.21	3.60	3.96	4.24	4.68	4.84	5.36
t _{dz}	0.69	0.69	0.77	0.77	0.86	0.83	0.88	0.88
t _{zd}	0.82	0.82	0.91	0.91	0.98	0.98	1.03	1.03
t _{od}	0.96	0.96	1.05	1.05	1.12	1.12	1.17	1.17
Power (μW/MHz)								
Power_read	101.97	118.37	188.68	225.33	281.29	347.48	379.81	484.83
Power_write	119.22	130.03	243.99	264.23	395.25	429.37	573.01	625.45
Power_standby	1.06	4.16	1.18	5.08	1.28	6.03	1.35	7.02
Area (μm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.92	5.65	5.90	6.75	6.94	7.80	8.03	8.80
t _{ckl}	1.48	1.84	1.54	2.04	1.59	2.22	1.63	2.39
t _{ckh}	2.46	2.70	2.99	3.30	3.49	3.88	3.96	4.42
t _{as}	0.62	0.87	0.65	0.94	0.66	1.02	0.66	1.09
t _{ah}	0.81	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{cs}	1.20	1.68	1.26	1.87	1.31	2.05	1.34	2.22
t _{ch}	0.39	0.63	0.39	0.71	0.39	0.79	0.39	0.87
t _{ds}	0.52	0.66	0.52	0.75	0.52	0.84	0.52	0.93
t _{dh}	0.91	1.31	0.98	1.46	1.03	1.60	1.07	1.71
t _{ws}	0.86	1.10	0.92	1.20	0.96	1.28	0.97	1.34
t _{wh}	0.81	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{acc}	3.39	3.74	4.06	4.53	4.70	5.29	5.31	6.02
t _{da}	2.96	3.23	3.61	3.98	4.25	4.69	4.86	5.37
t _{dz}	0.68	0.68	0.74	0.74	0.80	0.80	0.83	0.84
t _{zd}	0.81	0.80	0.88	0.87	0.94	0.93	0.98	0.99
t _{od}	0.95	0.95	1.02	1.02	1.08	1.08	1.12	1.12
Power (μW/MHz)								
Power_read	79.66	92.67	139.36	164.69	202.03	244.30	267.66	331.51
Power_write	92.55	101.98	178.34	193.64	279.29	302.67	395.39	429.07
Power_standby	1.03	4.20	1.13	5.18	1.20	6.13	1.24	7.04
Area (μm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Reference Table


* For Ymux=32 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	4	4	8	8	12	12	16	16
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.97	5.73	5.97	6.82	7.03	7.87	8.14	8.87
t _{ckl}	1.45	1.84	1.51	2.04	1.57	2.22	1.61	2.39
t _{ckh}	2.54	2.78	3.06	3.38	3.56	3.95	4.02	4.49
t _{as}	0.62	0.87	0.64	0.94	0.64	1.02	0.63	1.09
t _{ah}	0.80	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{cs}	1.18	1.68	1.24	1.87	1.29	2.05	1.31	2.22
t _{ch}	0.39	0.63	0.39	0.71	0.39	0.79	0.39	0.87
t _{ds}	0.52	0.66	0.52	0.75	0.52	0.84	0.52	0.93
t _{dh}	0.92	1.31	0.99	1.47	1.04	1.60	1.07	1.71
t _{ws}	0.84	1.10	0.91	1.20	0.95	1.28	0.97	1.33
t _{wh}	0.80	1.00	0.84	1.10	0.86	1.19	0.87	1.26
t _{acc}	3.57	3.94	4.24	4.74	4.89	5.50	5.50	6.24
t _{da}	3.09	3.37	3.75	4.12	4.39	4.83	4.99	5.51
t _{dz}	0.68	0.68	0.75	0.75	0.79	0.79	0.82	0.82
t _{zd}	0.81	0.81	0.88	0.88	0.94	0.94	0.97	0.97
t _{od}	0.95	0.95	1.02	1.03	1.08	1.08	1.11	1.11
Power (μW/MHz)								
Power_read	69.74	80.33	118.40	137.56	168.63	198.70	220.43	263.75
Power_write	80.77	88.55	149.52	161.64	227.80	245.38	315.63	339.75
Power_standby	1.03	4.17	1.12	5.12	1.21	6.06	1.29	7.00
Area (μm)								
Width	686.34	686.34	1295.06	1295.06	1903.78	1903.78	2512.50	2512.50
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18


NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

Low-Power Single-Port Synchronous Static RAM

Read Cycle




Write Cycle




SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Read Cycle with CSN Controlled




OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



Features

- Suitable for low-power applications
- Synchronous operation
- Automatic power-down mode available
- Self-controlled circuit available
- Asynchronous tristate output
- Low noise output optimization
- Separated data I/O
- Flexible aspect ratio
- Zero standby current
- Latched inputs and outputs
- Up to 128Kbits capacity
- Up to 8K number of words
- Up to 128 number of bit per word

Function Description

DPSRAM_LP is a dual-port synchronous static RAM which is provided as a compiler. DPSRAM_LP is intended for use in low-power applications. Each port is fully independent. On the rising edge of CK1 (CK), the write cycle is initiated when WEN1 (WEN2) is low and CSN1 (CSN2) is low. The data on DI1[] (DI2[]) is written into the memory location specified on A1[] (A2[]). During the write cycle, DOUT1[] (DOUT2[]) remains stable. On the rising edge of CK1 (CK2), the read cycle is initiated when WEN1 (WEN2) is high and CSN1 (CSN2) is low. The data at DOUT1[] (DOUT2[]) become valid after a delay. While in standby mode that CSN1 (CSN2) is high, A1[] (A2[]) and DI1[] (DI2[]) are disabled, data stored in the memory is retained and DOUT1[] (DOUT2[]) remains stable. When OEN1 (OEN2) is high, DOUT1[] (DOUT2[]) is placed in a high-impedance state.

DPSRAM_LP Function Table

CK1 CK2	CSN1 CSN2	WEN1 WEN2	OEN1 OEN2	A1 A2	DI1 DI2	DOUT1 DOUT2	Comment
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read Cycle

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Parameter Description

DPSRAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and column mux(y).

Parameters		Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	Min	32	64	128	256
	Max	1024	2048	4096	8192
	Step	16	32	64	128
Bpw (b)	Min	1	1	1	1
	Max	128	64	32	16
	Step	1	1	1	1

Pin Descriptions

Name	Type	Description
CK1 CK2	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If WEN is high on the rising edge of CK, the RAM is in read mode. Upon the falling edge of CK, the RAM is in a precharge state.
CSN1 CSN2	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN1 WEN2	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are present at DOUT.
OEN1 OEN2	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A1 [] A2 []	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI1 [] DI2 []	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT1 [] DOUT2 []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.


Pin Capacitance

(Unit = SL)

CK	CSN	WEN	OEN	A	DI	DOUT
5.04	12.00	7.25	4.51	8.02	4.94	9.13

NOTE: Each pin's capacitance is exactly same regardless of available mux types.

Block Diagram



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in DPSRAM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of DPSRAM_LP.
4. Contention mode in same address access
In DPSRAM_LP, simultaneous operation by both ports on the same memory address, as write/write, write/read or read/write operation, causes a contention problem. Simultaneous operation is defined as a state in which both ports are enabled, both address buses are equal at the rising edge of CK. DPSRAM_LP has no scheme preventing the contention. Due to simultaneous operation, silicon will behave unpredictably. A write operation cannot end and data appearing at outputs may not be valid. Please refer to the timing diagrams if you want to avoid the contention mode between both ports. In write/write operation, the data stored at the current address will be unpredictable. In write/read or read/write operation, the read port is invalid while the write port is still valid. If you want to avoid the contention mode, you have to give the value greater than tcc (clock-to-clock setup time). However, simultaneous read/read is allowable without any restrictions. Power reduction during standby mode.
5. Power reduction during standby mode
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol		Description	
t _{cyc}	Clock cycle time	t _{ckl}	Clock pulse width low
t _{ckh}	Clock pulse width high	t _{cc}	Clock to Clock Setup time
t _{as}	Address setup time	t _{ah}	Address hold time
t _{cs}	CSN setup time	t _{ch}	CSN hold time
t _{ds}	Data-In setup time	t _{dh}	Data-In hold time
t _{ws}	WEN setup time	t _{wh}	WEN hold time
t _{acc}	Data access time	t _{da}	De-access time
t _{dz}	DOUT drive to high-Z time	t _{zd}	DOUT high-Z to drive time
t _{od}	OEN to valid output time		
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

* For Ymux=4

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	256	512	768	1024
bpw	32	64	96	128
Timing (ns)				
t _{cyc}	5.16	6.79	8.59	10.58
t _{ckl}	1.43	1.65	1.97	2.39
t _{ckh}	2.43	3.29	4.25	5.32
t _{cc}	2.17	3.02	3.96	4.99
t _{as}	0.60	0.79	1.01	1.26
t _{ah}	0.67	0.70	0.71	0.71
t _{cs}	1.32	1.65	2.06	2.56
t _{ch}	0.35	0.36	0.36	0.36
t _{ds}	0.24	0.24	0.24	0.24
t _{dh}	0.92	1.14	1.38	1.65
t _{ws}	0.85	0.89	0.91	0.90
t _{wh}	0.67	0.70	0.71	0.71
t _{acc}	3.27	4.32	5.51	6.84
t _{da}	2.87	3.93	5.12	6.45
t _{dz}	0.80	1.02	1.27	1.54
t _{zd}	0.93	1.16	1.41	1.67
t _{od}	1.06	1.29	1.54	1.80
Power (μW/MHz)				
Power_read	201.94	407.65	633.31	878.92
Power_write	239.50	537.32	915.91	1375.29
Power_standby	1.25	1.53	1.95	2.52
Area (μm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	512	1024	1536	2048
bpw	16	32	48	64
Timing (ns)				
t _{cyc}	5.13	6.76	8.59	10.64
t _{ckl}	1.41	1.64	2.00	2.49
t _{ckh}	2.43	3.29	4.25	5.32
t _{cc}	2.17	3.02	3.96	4.99
t _{as}	0.64	0.88	1.15	1.44
t _{ah}	0.67	0.70	0.71	0.71
t _{cs}	1.27	1.59	2.04	2.63
t _{ch}	0.36	0.36	0.36	0.36
t _{ds}	0.24	0.24	0.24	0.24
t _{dh}	0.89	1.06	1.25	1.46
t _{ws}	0.85	0.89	0.91	0.90
t _{wh}	0.67	0.70	0.71	0.71
t _{acc}	3.32	4.38	5.58	6.90
t _{da}	2.90	3.95	5.15	6.47
t _{dz}	0.76	0.94	1.13	1.34
t _{zd}	0.89	1.07	1.26	1.46
t _{od}	1.02	1.20	1.40	1.60
Power (μW/MHz)				
Power_read	143.73	276.51	419.61	573.02
Power_write	166.62	353.80	584.54	858.84
Power_standby	1.27	1.39	1.51	1.63
Area (μm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	1024	2048	3072	4096
bpw	8	16	24	32
Timing (ns)				
t _{cyc}	5.18	6.92	8.74	10.62
t _{ckl}	1.42	1.61	1.89	2.24
t _{ckh}	2.44	3.29	4.25	5.32
t _{cc}	2.17	3.02	3.96	5.00
t _{as}	0.60	0.80	1.02	1.27
t _{ah}	0.67	0.70	0.71	0.71
t _{cs}	1.26	1.53	1.89	2.36
t _{ch}	0.36	0.36	0.36	0.36
t _{ds}	0.24	0.24	0.24	0.24
t _{dh}	0.87	1.02	1.19	1.37
t _{ws}	0.85	0.89	0.91	0.90
t _{wh}	0.67	0.70	0.71	0.71
t _{acc}	3.36	4.43	5.62	6.94
t _{da}	2.91	3.97	5.16	6.94
t _{dz}	0.74	0.89	1.06	1.24
t _{zd}	0.87	1.03	1.20	1.36
t _{od}	1.00	1.16	1.33	1.51
Power (μW/MHz)				
Power_read	102.73	197.93	298.62	404.79
Power_write	120.48	254.06	412.66	596.28
Power_standby	1.28	1.37	1.49	1.62
Area (μm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Reference Table

* For Ymux=32 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)


Parameters				
words	2048	4096	6144	8192
bpw	4	8	12	16
Timing (ns)				
t _{cyc}	5.16	6.91	8.74	10.65
t _{ckl}	1.43	1.67	1.93	2.19
t _{ckh}	2.44	3.29	4.25	5.32
t _{cc}	2.17	3.02	3.96	5.00
t _{as}	0.59	0.79	1.01	1.26
t _{ah}	0.67	0.70	0.71	0.71
t _{cs}	1.27	1.59	1.93	2.28
t _{ch}	0.36	0.36	0.36	0.36
t _{ds}	0.24	0.24	0.24	0.24
t _{dh}	0.86	1.00	1.16	1.33
t _{ws}	0.85	0.89	0.91	0.91
t _{wh}	0.67	0.70	0.71	0.71
t _{acc}	3.43	4.52	5.71	7.03
t _{da}	2.94	3.99	5.19	6.51
t _{dz}	0.73	0.87	1.03	1.19
t _{zd}	0.86	1.01	1.16	1.32
t _{od}	0.99	1.14	1.29	1.46
Power (μW/MHz)				
Power_read	88.33	165.78	246.32	329.93
Power_write	103.72	212.70	337.55	478.29
Power_standby	1.28	1.36	1.47	1.60
Area (μm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:


1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle




Write Cycle




DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM


Read Cycle with CSN Controlled



OEN Controlled Output Enable




Contention Mode



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



NOTES:

1. Words (w) is the number of words in SPARAM_LP.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. Banks(ba) is the number of banks.
5. $m = \lceil \log_2 w \rceil$

Features

- Suitable for low-power applications
- Standby (power down) mode available
- Separated data I/O
- Asynchronous operation
- Asynchronous tri-state output
- Address transition detectors
- Write enable transition detector
- Chip select transition detector
- Bank select transition detector
- Automatic power-down mode
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPARAM_LP is a single-port asynchronous static RAM which is provided as a compiler. SPARAM_LP is intended for use in low-power applications. At the falling edge of WEN, the write cycle is initiated. At the rising edge of WEN, the write cycle is ended. During the write cycle, the data on DI[] is written into the memory location specified on A[]. The read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay whenever A[] transition is detected. While in standby mode that CSN is high, A[] and DI[] are disabled, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

SPARAM_LP Function Table

CSN	WEN	OEN	A	DI	DOUT	Comment
X	X	H	X	X	Z	Unconditional tri-state output
H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
L	↓	L	Valid	Valid	DOUT(t-1)	Write cycle starts
L	↑	L	Valid	Valid	MEM(A)	Write cycle ends and read cycle starts
L	L	L	Stable	Valid	DOUT(t-1)	Write cycle
L	H	L	Toggle	X	MEM(A)	Read cycle

SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Parameter Description

SPARAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	1	1	1	1
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CSN	Chip Enable	Chip select input. The chip select signal acts as the memory enable signal for selections of multiple blocks. When CSN is high, the memory goes to stand-by (power down) mode and no access to the memory can occur. Conversely, if low, a read or write access can occur. When CSN falls, an access is initiated.
WEN	Read/Write Enable	Write enable input. The write enable signal selects the type of memory access. The high state for a read access and the low state for a write access. Upon the rising edge of WEN, a write access completed and a read access initiated.
OEN	Data Output Enable	Output enable input. The output enable signal controls the output drivers from driven to tri-state condition unconditionally.
A []	Address	Address input bus. A[] should be stable when WEN is low. The address selects the location to be accessed. When the address changes, the transition is detected and the internal clock pulse is generated.
DI []	Data Input	Data input bus. The data input is written to the accessed location when WEN is low.
DOUT []	Data Output	Data output bus. The data output is data stored in the accessed location during a read access. Data output driver has tri-state logic. When OEN is low, the driver drives a certain value. Otherwise, data output keeps Hi-Z state. During a write access, data on DOUT is predictable.

Pin Capacitance


Unit: [SL]

	CSN	WEN	OEN	A	DI	DOUT
ba = 1	1.87	1.87	1.87	3.91	1.87	7.12
ba = 2	1.87	1.87	1.87	3.91	1.87	7.12

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPARAM_LP has 2 different physical architectures due to the word depth. Optionally, one of these architectures is generated from SPARAM_LP compiler. In dual-bank, the bank selected by the address is only activated while the other bank is in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in SPARAM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPARAM_LP.
4. Avoiding short transition on the address bus
In SPARAM_LP, rather than the write operation which is synchronously performed by WEN signal, the read operation is asynchronously performed whenever the address transition is occurred. In this case, if the short transition on the address, called a skew, is happened, since SPARAM_LP recognizes the short address transition as the stable address transition and do perform a read operation. At that time, while in the read operation, the data stored in the memory may be corrupted due to the short transition. To prevent such fail, the stable address cycle time (tcyc) is required. The essential requirement to recognize valid address transition is that at least minimum address period should be equal or greater than tacc (access time).
5. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Address cycle time	t _{as}	Address setup time
t _{cas}	Address setup time for CSN rise	t _{ah}	Address hold time
t _{wh}	WEN hold time	t _{cs}	CSN setup time
t _{ch}	CSN hold time	t _{ds}	Data-In setup time
t _{dh}	Data-In hold time	t _{wen}	WEN pulse width low
t _{acc}	Data access time for read cycle	t _{wacc}	Data access time for WEN rise
t _{da}	De-access time	t _{wda}	De-access time for WEN rise
t _{zd}	DOUT high-Z to drive time	t _{dz}	DOUT drive to high-Z time
t _{od}	OEN to valid output time		
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Low-Power Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=4

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	256	512	512	1024	768	1536	1024	2048
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.24	4.35	4.68	4.83	5.11	5.32	5.55	5.81
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	4.19	4.29	4.62	4.78	5.06	5.27	5.49	5.75
t _{ah}	1.78	1.79	2.19	2.21	2.61	2.63	3.03	3.05
t _{wh}	4.19	4.29	4.62	4.78	5.06	5.27	5.49	5.75
t _{ds}	0.10	0.09	0.12	0.17	0.11	0.20	0.07	0.17
t _{dh}	0.66	0.63	0.73	0.69	0.85	0.74	0.94	0.80
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.19	1.31	1.28	1.46	1.38	1.60	1.47	1.75
t _{wen}	2.93	3.10	3.30	3.55	3.67	4.01	4.04	4.47
t _{acc}	4.24	4.35	4.68	4.83	5.11	5.32	5.55	5.81
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.24	1.36	1.33	1.51	1.43	1.65	1.52	1.80
t _{dz}	0.34	0.35	0.42	0.42	0.49	0.49	0.56	0.56
t _{zd}	0.29	0.29	0.37	0.36	0.44	0.44	0.52	0.52
t _{od}	0.45	0.45	0.53	0.53	0.61	0.61	0.69	0.69
Power (μW/MHz)								
Power_read	127.68	155.00	237.46	301.07	352.92	469.66	474.07	660.77
Power_write	205.47	230.05	440.97	513.60	751.22	898.01	1136.22	1383.27
Power_standby	17.01	27.91	31.03	53.82	45.17	84.92	59.44	121.20
Area (μm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.26	4.37	4.70	4.86	5.13	5.35	5.56	5.83
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	4.21	4.32	4.64	4.81	5.08	5.29	5.51	5.78
t _{ah}	1.78	1.79	2.19	2.21	2.61	2.63	3.03	3.05
t _{wh}	4.21	4.32	4.64	4.81	5.08	5.29	5.51	5.78
t _{ds}	0.10	0.18	0.13	0.27	0.12	0.30	0.07	0.28
t _{dh}	0.64	0.58	0.73	0.63	0.83	0.69	0.92	0.75
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.21	1.34	1.30	1.49	1.40	1.64	1.49	1.79
t _{wen}	2.96	3.16	3.33	3.62	3.70	4.07	4.07	4.53
t _{acc}	4.26	4.37	4.70	4.86	5.13	5.35	5.56	5.83
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.26	1.39	1.35	1.54	1.45	1.69	1.54	1.83
t _{dz}	0.32	0.32	0.37	0.37	0.42	0.42	0.47	0.47
t _{zd}	0.26	0.26	0.31	0.31	0.37	0.37	0.42	0.42
t _{od}	0.42	0.42	0.48	0.48	0.53	0.53	0.58	0.58
Power (μW/MHz)								
Power_read	89.72	112.08	154.81	200.04	222.74	299.30	293.53	409.88
Power_write	136.41	153.87	261.39	306.79	423.69	510.31	623.29	764.42
Power_standby	13.54	23.41	23.38	41.44	33.28	62.12	43.24	85.43
Area (μm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Low-Power Single-Port Asynchronous Static RAM

Reference Table

* For Ymux=16

(Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.30	4.43	4.73	4.92	5.16	5.40	5.60	5.89
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	4.24	4.38	4.68	4.86	5.11	5.35	5.55	5.83
t _{ah}	1.78	1.79	2.20	2.21	2.61	2.63	3.03	3.05
t _{wh}	4.24	4.38	4.68	4.86	5.11	5.35	5.55	5.83
t _{ds}	0.09	0.12	0.14	0.24	0.14	0.30	0.10	0.30
t _{dh}	0.59	0.48	0.68	0.53	0.77	0.59	0.87	0.64
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.25	1.40	1.34	1.55	1.43	1.69	1.53	1.84
t _{wen}	3.02	3.28	3.40	3.74	3.77	4.19	4.14	4.65
t _{acc}	4.30	4.43	4.73	4.92	5.16	5.40	5.60	5.89
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.30	1.45	1.39	1.60	1.48	1.74	1.58	1.89
t _{dz}	0.31	0.31	0.35	0.35	0.38	0.38	0.42	0.42
t _{zd}	0.25	0.25	0.29	0.29	0.32	0.32	0.36	0.36
t _{od}	0.40	0.40	0.44	0.44	0.48	0.48	0.52	0.52
Power (μW/MHz)								
Power_read	69.37	89.23	112.69	148.76	157.46	213.99	203.68	284.91
Power_write	101.53	117.46	171.73	205.67	260.59	319.18	368.11	457.99
Power_standby	11.60	21.92	19.60	36.39	27.63	52.22	35.70	69.41
Area (μm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Reference Table


* For Ymux=32 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	4	4	8	8	12	12	16	16
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.39	4.58	4.81	5.06	5.23	5.53	5.65	6.01
t _{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{cas}	4.34	4.52	4.76	5.00	5.18	5.47	5.60	5.95
t _{ah}	1.77	1.78	2.19	2.21	2.61	2.63	3.03	3.06
t _{wh}	4.34	4.52	4.76	5.00	5.18	5.47	5.60	5.95
t _{ds}	0.11	0.26	0.18	0.38	0.19	0.48	0.15	0.55
t _{dh}	0.49	0.29	0.58	0.34	0.67	0.38	0.77	0.43
t _{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{ch}	1.31	1.51	1.40	1.66	1.49	1.81	1.58	4.96
t _{wen}	3.16	3.53	3.53	3.98	3.89	4.42	4.25	4.87
t _{acc}	4.39	4.58	4.81	5.06	5.23	5.53	5.65	6.01
t _{da}	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
t _{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t _{wacc}	1.36	1.57	1.45	1.72	1.54	1.87	1.63	2.01
t _{dz}	0.29	0.29	0.34	0.34	0.38	0.38	0.40	0.40
t _{zd}	0.23	0.23	0.27	0.27	0.60	0.30	0.34	0.34
t _{od}	0.38	0.38	0.44	0.44	0.48	0.48	0.51	0.51
Power (μW/MHz)								
Power_read	57.70	75.79	90.74	121.92	124.49	170.91	158.97	222.74
Power_write	84.02	106.24	127.80	163.74	180.92	233.92	243.37	316.77
Power_standby	11.90	25.70	18.92	38.73	25.95	52.52	32.99	67.00
Area (μm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams


Read Cycle



Read Cycle with CSN-Controlled




Basic Write Cycle




SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Write Cycle with CSN Controlled




Read-Modified-Write Cycle



NOTES:


1. When the wen hold time after the last address bit transition is satisfied, D+ will toggle in response to a successful read of the initial contents of address A1. When the wen hold time after the last address bit transition is not satisfied, D+ will go to unknown state.
2. Address bits are not allowed to change while WEN is low. If they do change, then the data for one or more addresses in the memory array may be corrupted.

OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



Features

- Suitable for low-power applications
- Diffusion-programmable code available
- Synchronous operation
- Asynchronous tri-state output
- Latched inputs and outputs
- Automatic power-down mode available
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

DROM_LP is a synchronous diffusion programmable ROM which is provided as a compiler. DROM_LP is intended for use in low-power applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] is disabled and DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

DROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

Parameter Description

DROM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and Column mux(y) and Number of banks(ba).

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance


(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	4.581	5.336	3.799	5.623	8.015
ba = 2	4.392	4.322	3.050	4.512	8.189

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

DROM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from DROM_LP compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in DROM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of DROM_LP.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ch}	CSN hold time from CK rise
t _{ckl}	Clock pulse width low	t _{acc}	Data access time
t _{ckh}	Clock pulse width high	t _{da}	De-access time
t _{as}	Address setup time	t _{dz}	DOUT drive to high-Z time
t _{ah}	Address hold time	t _{zd}	DOUT high-Z to drive time
t _{cs}	CSN setup time	t _{od}	OEN to Valid Output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Low-Power Synchronous Diffusion Programmable ROM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.79	4.98	6.17	6.39	7.78	8.03	9.64	9.91
t _{ckl}	2.02	2.02	2.44	2.44	2.86	2.86	3.26	3.26
t _{ckh}	2.11	2.30	2.56	2.78	3.04	3.29	3.54	3.82
t _{as}	0.10	1.33	0.10	1.37	0.10	1.41	0.10	1.45
t _{ah}	0.69	0.88	0.69	0.91	0.69	0.94	0.69	0.97
t _{cs}	0.87	1.23	0.87	1.27	0.87	1.31	0.87	1.35
t _{ch}	0.61	0.81	0.61	0.84	0.61	0.87	0.61	0.90
t _{acc}	3.37	3.64	3.86	4.17	4.44	4.80	5.11	5.51
t _{da}	2.89	3.09	3.47	3.72	4.10	4.37	4.76	5.07
t _{dz}	0.67	0.65	0.75	0.74	0.84	0.83	0.92	0.92
t _{zd}	0.77	0.76	0.85	0.84	0.93	0.92	1.01	0.99
t _{od}	0.90	0.88	0.98	0.97	1.06	1.05	1.14	1.12
Power (μW/MHz)								
Power_read	169.22	179.53	377.62	399.51	641.30	678.26	960.25	1015.80
Power_standby	0.96	4.90	1.07	5.78	1.17	6.64	1.25	7.49
Area (μm)								
Width	511.53	511.53	883.93	883.93	1256.06	1256.06	1627.93	1627.93
Height	214.62	405.22	295.26	566.50	375.90	727.78	456.54	889.06

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.80	4.99	6.17	6.39	7.78	8.03	9.63	9.91
t _{ckl}	2.02	2.02	2.44	2.44	2.86	2.86	3.26	3.26
t _{ckh}	2.11	2.31	2.56	2.78	3.04	3.29	3.54	3.82
t _{as}	0.10	1.33	0.10	1.37	0.10	1.41	0.10	1.45
t _{ah}	0.69	0.88	0.69	0.91	0.69	0.94	0.69	0.97
t _{cs}	0.87	1.23	0.87	1.27	0.87	1.31	0.87	1.35
t _{ch}	0.61	0.81	0.61	0.84	0.61	0.87	0.61	0.90
t _{acc}	3.42	3.71	3.91	4.25	4.48	4.87	5.15	5.58
t _{da}	2.90	3.11	3.48	3.73	4.11	4.39	4.77	5.08
t _{dz}	0.63	0.63	0.70	0.69	0.76	0.75	0.82	0.81
t _{zd}	0.74	0.73	0.80	0.79	0.86	0.84	0.91	0.90
t _{od}	0.87	0.86	0.93	0.92	0.99	0.97	1.04	1.03
Power (μW/MHz)								
Power_read	121.24	130.01	156.66	273.76	421.02	438.26	614.32	653.51
Power_standby	0.96	4.89	1.05	5.75	1.14	6.61	1.21	7.46
Area (μm)								
Width	511.24	511.24	883.86	883.86	1256.06	1256.06	1627.86	1627.86
Height	214.62	405.22	295.26	566.50	375.90	727.78	456.54	889.06

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Low-Power Synchronous Diffusion Programmable ROM

Reference Table

* For Ymux=32 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	4.80	4.99	6.17	6.39	7.78	8.03	9.64	9.92
t _{ckl}	2.02	2.02	2.44	2.44	2.86	2.86	3.26	3.26
t _{ckh}	2.12	2.31	2.56	2.78	3.04	3.29	3.55	3.82
t _{as}	0.10	1.33	0.10	1.37	0.10	1.41	0.10	1.45
t _{ah}	0.68	0.88	0.68	0.91	0.68	0.94	0.68	0.97
t _{cs}	0.87	1.23	0.87	1.27	0.87	1.31	0.87	1.35
t _{ch}	0.61	0.81	0.61	0.84	0.61	0.87	0.61	0.90
t _{acc}	3.49	3.85	3.98	4.39	4.55	5.01	5.22	5.72
t _{da}	2.91	3.13	3.50	3.75	4.12	4.41	4.78	5.10
t _{dz}	0.62	0.61	0.67	0.66	0.72	0.71	0.76	0.75
t _{zd}	0.73	0.72	0.77	0.76	0.82	0.81	0.86	0.85
t _{od}	0.85	0.84	0.90	0.86	0.95	0.93	0.99	0.98
Power (μW/MHz)								
Power_read	97.93	105.95	197.49	212.21	312.62	334.97	443.33	474.24
Power_standby	0.95	4.89	1.04	5.76	1.12	6.63	1.19	7.50
Area (μm)								
Width	510.65	510.65	883.69	883.69	1256.06	1256.06	1627.76	1627.76
Height	214.61	405.22	295.26	566.50	375.90	727.78	456.54	889.06


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DROM_LP


Low-Power Synchronous Diffusion Programmable ROM

Timing Diagrams


Read Cycle



Read Cycle with CSN Controlled




OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



Features

- Suitable for low-power applications
- Metal-2 programmable code available
- Synchronous operation
- Asynchronous tri-state output
- Latched inputs and outputs
- Automatic power-down mode
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

MROM_LP is a synchronous diffusion programmable ROM which is provided as a compiler. MROM_LP is intended for use in low-power applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] is disabled and DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

MROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

MROM_LP

Low-Power Synchronous Metal Programmable ROM

Parameter Description

MROM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A []	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT []	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance


(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	4.346	4.741	3.257	7.865	8.308
ba = 2	5.190	5.288	3.405	4.614	8.463

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

MROM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from MROM_LP compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in MROM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of MROM_LP.
4. Power reduction during standby mode.
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

MROM_LP

Low-Power Synchronous Metal Programmable ROM

Characteristics

Definition for AC Timing (ns)			
Symbol	Description	Symbol	Description
t _{cyc}	Clock cycle time	t _{ch}	CSN hold time from CK rise
t _{ckl}	Clock pulse width low	t _{acc}	Data access time
t _{ckh}	Clock pulse width high	t _{da}	De-access time
t _{as}	Address setup time	t _{dz}	DOUT drive to high-Z time
t _{ah}	Address hold time	t _{zd}	DOUT high-Z to drive time
t _{cs}	CSN setup time	t _{od}	OEN to valid output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Low-Power Synchronous Metal Programmable ROM

Reference Table

* For Ymux=8 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	512	1024	1024	2048	1536	3072	2048	4096
bpw	32	32	64	64	96	96	128	128
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	5.73	5.95	8.43	8.71	11.31	11.64	14.36	14.74
t _{ckl}	2.15	2.15	2.72	2.72	3.24	3.24	3.72	3.72
t _{ckh}	2.27	2.49	2.87	3.15	3.53	3.86	4.23	4.62
t _{as}	0.10	1.34	0.10	1.41	0.10	1.48	0.10	1.55
t _{ah}	0.65	0.87	0.65	0.92	0.65	0.98	0.65	1.03
t _{cs}	0.84	1.24	0.84	1.31	0.84	1.38	0.84	1.45
t _{ch}	0.58	0.80	0.58	0.86	0.58	0.91	0.58	0.97
t _{acc}	3.55	3.84	4.28	4.64	5.12	5.55	6.07	6.57
t _{da}	3.11	3.34	3.93	4.22	4.80	5.16	5.73	6.14
t _{dz}	0.63	0.63	0.72	0.72	0.81	0.81	0.89	0.90
t _{zd}	0.74	0.74	0.82	0.83	0.90	0.91	0.98	0.99
t _{od}	0.86	0.87	0.95	0.96	1.03	1.04	1.11	1.12
Power (μW/MHz)								
Power_read	198.36	207.26	475.39	496.65	848.69	885.97	1318.24	1375.22
Power_standby	0.97	5.58	1.07	7.17	1.17	8.77	1.25	10.36
Area (μm)								
Width	484.49	484.49	876.09	876.09	1267.42	1267.42	1658.49	1658.49
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

MROM_LP

Low-Power Synchronous Metal Programmable ROM

Reference Table

* For Ymux=16 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	1024	2048	2048	4096	3072	6144	4096	8192
bpw	16	16	32	32	48	48	64	64
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	5.74	5.96	8.43	8.71	11.31	11.64	14.36	14.75
t _{ckl}	2.15	2.15	2.72	2.72	3.24	3.24	3.72	3.72
t _{ckh}	2.27	2.49	2.87	3.15	3.53	3.86	4.23	4.62
t _{as}	0.10	1.34	0.10	1.41	0.10	1.48	0.10	1.55
t _{ah}	0.65	0.87	0.65	0.92	0.65	0.98	0.65	1.03
t _{cs}	0.85	1.24	0.85	1.31	0.85	1.38	0.85	1.45
t _{ch}	0.58	0.80	0.58	0.86	0.58	0.91	0.58	0.97
t _{acc}	3.59	3.91	4.32	4.72	5.16	5.62	6.11	6.64
t _{da}	3.12	3.36	3.94	4.24	4.81	5.17	5.74	6.16
t _{dz}	0.60	0.60	0.66	0.67	0.72	0.73	0.78	0.79
t _{zd}	0.71	0.71	0.77	0.77	0.82	0.83	0.88	0.89
t _{od}	0.84	0.84	0.90	0.90	0.95	0.96	1.01	1.01
Power (μW/MHz)								
Power_read	135.73	145.00	307.50	325.72	529.17	558.24	800.72	842.55
Power_standby	0.96	5.57	1.05	7.15	1.13	8.73	1.20	10.30
Area (μm)								
Width	484.20	484.20	876.02	876.02	1267.42	1267.42	1658.42	1658.42
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Low-Power Synchronous Metal Programmable ROM

Reference Table

* For Ymux=32 (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	2048	4096	4096	8192	6144	12288	8192	16384
bpw	8	8	16	16	24	24	32	32
ba	1	2	1	2	1	2	1	2
Timing (ns)								
t _{cyc}	5.74	5.96	8.43	8.70	11.30	11.63	14.36	14.74
t _{ckl}	2.15	2.15	2.72	2.71	3.24	3.23	3.72	3.71
t _{ckh}	2.27	2.49	2.87	3.15	3.53	3.86	4.23	4.62
t _{as}	0.10	1.34	0.10	1.41	0.10	1.48	0.10	1.55
t _{ah}	0.65	0.87	0.65	0.92	0.65	0.98	0.65	1.04
t _{cs}	0.85	1.24	0.85	1.31	0.85	1.38	0.85	1.45
t _{ch}	0.58	0.80	0.58	0.86	0.58	0.91	0.58	0.97
t _{acc}	3.67	4.05	4.40	4.85	5.24	5.76	6.18	6.77
t _{da}	3.13	3.38	3.95	4.26	4.83	5.19	5.76	6.18
t _{dz}	0.59	0.59	0.63	0.64	0.68	0.68	0.72	0.73
t _{zd}	0.70	0.70	0.74	0.74	0.78	0.79	0.83	0.83
t _{od}	0.82	0.83	0.87	0.87	0.91	0.92	0.95	0.96
Power (μW/MHz)								
Power_read	106.53	115.07	226.29	242.14	372.56	396.68	545.33	578.71
Power_standby	0.95	5.57	1.04	7.16	1.12	8.76	1.18	10.37
Area (μm)								
Width	483.61	483.61	875.85	875.85	1267.42	1267.42	1658.32	1658.32
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62


NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

MROM_LP


Low-Power Synchronous Metal Programmable ROM

Timing Diagrams


Read Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode

COMPILED DATAPATH MACROCELLS

Datapath macro cell is a set of n-bit data operators that enables more efficient datapath module design and implementation. Compiled datapath macro cell creates area-, speed- and power-optimized adders, subtractors, barrel shifters, and multipliers based on the user specified parameters. It creates a function model, a timing information for simulation, and a verified hard macro layout.

The followings are the summary of main features of compiled datapath macro cells:

ADVANCED DESIGN TECHNIQUE

All of STD111 compiled datapath macro cells adopt very advanced design techniques to get optimized performances on the given parameters. Some of those design techniques are as follows:

- Hierarchical double carry select scheme to reduce carry-chain delay
- Transmission gate multiplexing for data shifting
- Allowing pipeline insertion in multiplication
- Primitive standard cell compatible leaf cell layout
- Allowing over-the-cell routing
- Dense datapath module layout generation with topological regularity.

FLEXIBLE DATAPATH MACROCELL DESIGN FLOW

The implementation of datapath module is one of the most critical and important elements in the design of high performance systems; DSPs, multimedia, graphics, microprocessors and so on. In these systems, the datapath modules are used much more than other designs and at the same time, datapath module affects the overall design performances.

The macrocell generation flow is tightly integrated into Apollo, Avant! which is used as a main tool at a full chip layout step. By supporting an easy-to-use ASIC environment, achieving full custom-like density, performance, ASIC designers can expect improving productivity. In the design of datapath macro cell, the optimal module placement of leafcell is a key point to take advantage of inherent regularity in datapaths. An optimal datapath module placement can maximize density, minimize speed, bus line skew, power consumption and turn-around time in ASIC design.

The design environment has been developed to support datapath macro cells as shown in below. This flow is tightly integrated from Verilog, Cadence, to Apollo, Avant!. With the pre-defined leafcell information and given parameters, the schematic generator gives a Verilog structural netlist of datapath cell and the placement information of used leafcell instances. It enables the mapping of regularity from a logic design into a standard cell place-and-rout tool. You can get area- and performance-optimized layouts of datapath macro cells.





Figure 5-3 Datapath Instance Generation Flow

COMPILED MACROCELL SELECTION GUIDE

Type	Macrocell	Description
Datapath	ADDER	Low-power/high-speed 4-to-64 bits addition/subtraction - Double-carry select algorithm - 2's complement overflow
	BS	Low-power/high-speed 4-to-64 bits barrel shifter - Bi-directional shift and rotation - Logical or arithmetic shift - External filler data is available
	MPY	Low-power/high-speed 6-to-64 bits modified Booth Multiplier - 2's complement multiplication - 1-stage pipeline insertion is available

Logic Symbol



Features

- Asynchronous operation
- 4 to 64 bit adder/subtractor
- High-speed/low-power operation
- 2's complement or unsigned-magnitude operation
- 2's complement overflow flag available
- Sophisticated carry-select and group-bypass scheme
- Two output drive strength available

Function Description

The ADDER is an n -bit carry-select adder and subtractor which is provided as a compiler. The ADDER is intended to use in high-speed and low-power applications. It essentially adopts the double carry-select scheme which has hierarchically doubled carry-select groups of bits to allow the high-speed of addition/subtraction operation. And in addition, the inside of each group is designed by a partial group-bypass scheme so as to acquire more high-speed. It performs a 2's complement addition/subtraction or unsigned-magnitude addition. The overflow flag shows the occurrence of overflow while adding two positive or two negative numbers and it should be ignored while doing unsigned-magnitude operations.

Function Table

Output	Function
SOUT	AIN + BIN + CIN (addition)
	AIN + ~BIN + CIN (subtraction)
OVF	$(\sim \text{SOUT} [\text{bits}-1]) \cdot (\text{AIN} [\text{bits}-1] \cdot \text{BIN} [\text{bits}-1]) + (\text{SOUT} [\text{bits}-1]) \cdot (\sim \text{AIN} [\text{bits}-1]) \cdot (\sim \text{BIN} [\text{bits}-1])$

Parameter Description

ADDER is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	Description	Range
bits	Number of bits for the input data bus	4 to 64
sub	0: addition only; 1: addition/subtraction	0/1
ovf	Overflow flag for signed operation	0/1
drv	Output drive strength	1/2

ADDER

Adder/Subtractor


Pin Description

Name	Type	Description
AIN []	Input	Augend in addition, Minuend in subtraction
BIN []		Addend in addition, Subtrahend in subtraction
CIN		Carry-in in addition/subtraction It must be kept the 'HIGH' state in 2's complement subtraction.
SUB		Addition/subtraction flag (optional when the parameter sub = 1)
SOUT[]	output	The result of addition/subtraction
COUT		Carry-out in addition/subtraction
OVF		The overflow/underflow of addition/subtraction (optional when the parameter ovf = 1)


Pin Capacitance [Unit: pF]

Name	Case	Value
AIN[]	all	0.0200
BIN[]	sub=0 sub=1	0.0200 0.0150
CIN	all	0.0349
SUB	sub=1	0.0143 × bits

Block Diagram



Timing Diagram



Timing Type Definition

Timing Type	Definition
tPHLas/tPLHas	Propagation delay from AIN[] to SOUT[]
tPHLbs/tPLHbs	Propagation delay from BIN[] to SOUT[]
tPHLcs/tPLHcs	Propagation delay from CIN to SOUT[]
tPHLss/tPLHss	Propagation delay from SUB to SOUT[]
tPHLac/tPLHac	Propagation delay from AIN[] to COUT
tPHLbc/tPLHbc	Propagation delay from BIN[] to COUT
tPHLcc/tPLHcc	Propagation delay from CIN to COUT
tPHLsc/tPLHsc	Propagation delay from SUB to COUT
tPHLao/tPLHao	Propagation delay from AIN[] to OVF
tPHLbo/tPLHbo	Propagation delay from BIN[] to OVF
tPHLco/tPLHco	Propagation delay from CIN to OVF
tPHLso/tPLHso	Propagation delay from SUB to OVF
tPDAas	De-access time from AIN[] to SOUT[]
tPDAbs	De-access time from BIN[] to SOUT[]
tPDACS	De-access time from CIN to SOUT[]
tPDAss	De-access time from SUB to SOUT[]

ADDER

Adder/Subtractor

Characteristic Reference Table

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of bits	-	S	Input slope	ns
V _{DD}	Power supply voltage	V	SL	Standard load	-
C _L	Output load	SL	SA	Input switching activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Type	8		24		36		48		64	
Case: sub=0, ovf=1, drv=1										
tPHLac/tPLHac	0.98	0.90	1.44	1.47	1.72	1.80	1.93	2.06	2.12	2.27
tPHLbc/tPLHbc	0.95	0.90	1.42	1.47	1.69	1.80	1.91	2.05	2.09	2.27
tPHLcc/tPLHcc	0.67	0.77	1.13	1.33	1.41	1.66	1.62	1.92	1.81	2.13
tPHLao/tPLHao	1.08	1.38	1.74	1.96	2.15	2.33	2.49	2.64	2.84	2.97
tPHLbo/tPLHbo	1.09	1.36	1.74	1.94	2.15	2.30	2.49	2.61	2.85	2.94
tPHLco/tPLHco	0.95	1.07	1.60	1.65	2.01	2.02	2.36	2.33	2.71	2.66
tPHLas/tPLHas	1.14	1.29	1.73	1.80	2.09	2.12	2.38	2.37	2.66	2.63
tPHLbs/tPLHbs	1.14	1.26	1.73	1.77	2.09	2.09	2.38	2.35	2.65	2.60
tPHLcs/tPLHcs	1.00	0.98	1.59	1.49	1.95	1.80	2.24	2.06	2.52	2.32
tPDAas	0.35		0.35		0.35		0.35		0.35	
tPDAbs	0.35		0.35		0.35		0.35		0.35	
tPDACS	0.25		0.25		0.25		0.25		0.25	
Case: sub=1, ovf=1, drv=1										
tPHLac/tPLHac	0.98	0.90	1.45	1.48	1.73	1.82	1.73	1.82	2.14	2.30
tPHLbc/tPLHbc	1.27	1.09	1.74	1.66	2.02	2.00	2.02	2.00	2.44	2.48
tPHLcc/tPLHcc	0.67	0.76	1.14	1.34	1.42	1.68	1.42	1.68	1.83	2.16
tPHLsc/tPLHsc	1.01	1.19	1.07	1.89	1.11	2.30	1.11	2.30	1.13	2.88
tPHLao/tPLHao	1.08	1.37	1.78	1.99	2.19	2.37	2.19	2.37	2.80	2.94
tPHLbo/tPLHbo	1.27	1.67	1.96	2.29	2.37	2.66	2.37	2.66	2.98	3.24
tPHLco/tPLHco	0.96	1.06	1.64	1.69	2.05	2.06	2.05	2.06	2.66	2.63
tPHLso/tPLHso	1.54	1.53	1.60	2.35	1.64	2.84	1.64	2.84	1.75	3.58
tPHLas/tPLHas	1.14	1.29	1.76	1.83	2.14	2.16	2.14	2.16	2.69	2.67
tPHLbs/tPLHbs	1.33	1.58	1.95	2.12	2.32	2.45	2.32	2.45	2.88	2.96
tPHLcs/tPLHcs	1.00	0.98	1.63	1.52	2.00	1.85	2.00	1.85	2.56	2.36
tPHLss/tPLHss	1.41	1.32	2.15	2.06	2.59	2.50	2.59	2.50	3.27	3.17
tPDAas	0.35		0.35		0.35		0.35		0.35	
tPDAbs	0.62		0.62		0.62		0.62		0.62	
tPDACS	0.25		0.25		0.25		0.25		0.25	
tPDAss	0.59		0.59		0.59		0.59		0.59	

Characteristic Reference Table (Continued)

2) Power Characteristics [Unit: $\mu\text{W}/\text{MHz}$]

(Typical process, 25°C, $V_{DD}=2.5\text{V}$, $C_L=10$, $S=0.2$, $SA=0.5$)

Case			8	24	36	48	64
sub=0	ovf=0	drv=1	6.46	20.24	30.35	40.27	53.20
		drv=2	7.32	22.55	33.85	45.04	59.80
	ovf=1	drv=1	6.86	20.35	30.47	40.59	54.09
		drv=2	7.65	22.79	34.15	45.51	60.65
sub=1	ovf=0	drv=1	7.44	25.38	38.43	51.12	67.50
		drv=2	8.30	28.26	42.73	56.78	74.87
	ovf=1	drv=1	7.69	25.73	38.89	51.72	68.33
		drv=2	8.59	28.62	43.19	57.38	75.69


3) Size Characteristics [Unit: μm]

Type	Case	8	24	36	48	64
Width	sub=0 ovf=0	64.79	66.65	67.26	67.22	66.13
	sub=0 ovf=1	66.13	66.75	66.95	66.94	66.58
	sub=1 ovf=0	76.79	78.65	79.26	79.22	78.13
	sub=1 ovf=1	78.13	78.75	78.95	78.94	78.58
Height	all	90.00	266.00	398.00	530.00	706.00

BS

Barrel Shifter

Logic Symbol



Features

- Asynchronous operation
- 4 to 64 bit barrel shifter
- High speed, low power operation
- Transmission gate multiplexing scheme
- Bi-directional shift or rotation
- Fill with zero, MSB, or filler data
- Refresh flag
- Two output drive strength available

Function Description

The BS is an n-bit barrel shifter which is provided as a compiler. The BS is intended to use in high-speed and low-power applications. It performs a shifting or circular rotation operation and allows both arithmetic and logical shift operations. Also, it can shift and rotate input data in either direction and the direction of the shift can be chosen between MSB (LEFT) and LSB (RIGHT) of the bit string. Logical shifts fill vacant bits with zeros, and arithmetic shifts fill spaces with duplicates of the original MSB. The vacant bits also can be filled with filler data input(FIN). During a right shift, the FIN data fills the vacant bits with data from the LSB of the shift data bus. During a left shift, the shift data bus fills the vacant bits with data from the MSB of the shift data bus (essentially a circular shift).

Function Table

MSH	DIR	C1	C2	DOUT
0	0	0	0	Shift right and fill with zeros
0	0	0	1	Shift right and fill with MSB of DIN[]
0	0	1	0	Shift right and fill with FIN[] data
0	0	1	1	Rotate right
0	1	0	0	Shift left and fill with zeros
0	1	0	1	Shift left and fill with MSB
0	1	1	0	Shift left and fill with FIN[] data
0	1	1	1	Rotate left
1	X	0	0	All the bits are set to zero
1	X	0	1	All the bits are set to the MSB of DIN[]
1	X	1	0	FIN[]
1	X	1	1	DIN[]

NOTE: An 'X' indicates a "don't care" condition.

Parameter Description

BS is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	Description	Range
bits	Number of bits for the input data bus	4 to 64
type	Direction of shift	BOTH/LEFT/RIGHT
drv	Drive strength	1/2


Pin Description

Name	Type	Description
DIN[]	Input	Data input bus
FIN[]		Filler data input
DIR		Specify the direction of the shift or rotation (Left/Right) (optional when the parameter type = BOTH)
C1, C2		Specify the filler at the vacant bit (zero/MSB/FIN[])
SH[]		Shift amount (unsigned-magnitude binary)
MSH		Maximum shift flag. It refreshes all the bits of output data with filler according to C1 and C2.
DOUT[]	Output	Data output bus

Pin Capacitance [Unit: pF]


Name	Case	Value
C1	all	0.0155
C2	all	0.0196
FIN[]	all	0.0071
MSH	type = BOTH	0.0191
	type = LEFT/RIGHT	0.0263
DIN[]	type = BOTH	0.0171
	type = LEFT/RIGHT	0.0157
SH[]	type = BOTH	$-0.000003 \cdot \text{bits} \cdot \text{bits} + 0.000017 \cdot \text{bits} + 0.0580$
	type = LEFT/RIGHT	$-0.000002 \cdot \text{bits} \cdot \text{bits} + 0.000009 \cdot \text{bits} + 0.0288$
DIR	type = BOTH	0.0127

Block Diagram



BS Barrel Shifter

Timing Diagram



Timing Type Definition

Timing Type	Definition
tPHLdid/tPLHdid	Propagation delay from DIN[] to DOUT[]
tPHLfid/tPLHfid	Propagation delay from FIN[] to DOUT[]
tPHLshd/tPLHshd	Propagation delay from SH[] to DOUT[]
tPHLdrd/tPLHdrd	Propagation delay from DIR to DOUT[]
tPHLc1d/tPLHc1d	Propagation delay from C1 to DOUT[]
tPHLc2d/tPLHc2d	Propagation delay from C2 to DOUT[]
tPHLmsd/tPLHmsd	Propagation delay from MSH to DOUT[]
tPDA did	De-access time from DIN[] to DOUT[]
tPDA fid	De-access time from FIN[] to DOUT[]
tPDA shd	De-access time from SH[] to DOUT[]
tPDA drd	De-access time from DIR to DOUT[]
tPDA c1d	De-access time from C1 to DOUT[]
tPDA c2d	De-access time from C2 to DOUT[]
tPDA msd	De-access time from MSH to DOUT[]

Characteristic Reference Tables

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of bits	-	S	Input slope	ns
V _{DD}	Power supply voltage	V	SL	Standard load	-
C _L	Output load	SL	SA	Input switching activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Type	8		24		36		48		64	
Case: type=BOTH, drv= 1										
tPHLc1d/tPLHc1d	1.55	1.58	1.94	1.96	2.15	2.18	2.29	2.35	2.37	2.49
tPHLc2d/tPLHc2d	1.52	1.56	1.94	2.00	2.18	2.28	2.35	2.52	2.49	2.77
tPHLdid/tPLHdid	1.56	1.48	1.96	1.84	2.19	2.04	2.36	2.17	2.49	2.26
tPHLmsd/tPLHmsd	0.71	0.73	0.82	0.86	0.90	0.96	0.98	1.06	1.08	1.19
tPHLshd/tPLHshd	0.98	0.90	1.13	1.16	1.24	1.36	1.35	1.56	1.51	1.82
tPHLfid/tPLHfid	1.23	1.22	1.52	1.52	1.65	1.66	1.72	1.72	1.71	1.70
tPHLdrd/tPLHdrd	0.62	0.64	0.72	0.77	0.80	0.86	0.87	0.95	0.97	1.08
tPDAc1d	1.12		1.28		1.39		1.50		1.66	
tPDAc2d	1.05		1.14		1.21		1.30		1.43	
tPDAdid	1.05		1.14		1.22		1.32		1.46	
tPDAm sd	0.55		0.66		0.74		0.82		0.93	
tPDAs hd	0.76		0.75		0.74		0.73		0.73	
tPD Afid	0.52		0.61		0.68		0.75		0.85	
tPD A drd	0.74		0.88		0.98		1.08		1.21	
Case: type=LEFT, drv=1										
tPHLc1d/tPLHc1d	1.50	1.52	1.89	1.90	2.10	2.12	2.24	2.27	2.31	2.38
tPHLc2d/tPLHc2d	1.47	1.51	1.87	1.95	2.11	2.22	2.28	2.45	2.43	2.69
tPHLdid/tPLHdid	1.50	1.42	1.90	1.78	2.13	1.97	2.30	2.10	2.42	2.16
tPHLmsd/tPLHmsd	0.50	0.52	0.62	0.66	0.69	0.76	0.76	0.84	0.83	0.93
tPHLshd/tPLHshd	0.96	0.89	1.08	1.10	1.16	1.25	1.24	1.41	1.32	1.61
tPHLfid/tPLHfid	1.18	1.17	1.46	1.46	1.59	1.60	1.66	1.66	1.66	1.64
tPDAc1d	1.09		1.24		1.35		1.46		1.61	
tPDAc2d	1.01		1.10		1.17		1.25		1.37	
tPDAdid	1.01		1.10		1.18		1.27		1.40	
tPDAm sd	0.72		0.70		0.69		0.70		0.71	
tPDAs hd	0.43		0.52		0.58		0.63		0.70	
tPD Afid	0.71		0.91		1.02		1.11		1.18	

BS

Barrel Shifter

Characteristic Reference Table (Continued)

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, $V_{DD}=2.5V$, $C_L=10$, $S=0.2$, $SA=0.5$)

Type	8		24		36		48		64	
Case: type=RIGHT, drv=1										
tPHLc1d/tPLHc1d	1.50	1.53	1.87	1.86	2.07	2.08	2.22	2.28	2.32	2.49
tPHLc2d/tPLHc2d	1.46	1.51	1.83	1.92	2.07	2.20	2.30	2.46	2.56	2.76
tPHLdid/tPLHdid	1.50	1.43	1.89	1.77	2.12	1.96	2.29	2.09	2.45	2.19
tPHLmsd/tPLHmsd	0.49	0.52	0.61	0.66	0.69	0.76	0.75	0.84	0.82	0.92
tPHLshd/tPLHshd	0.96	0.89	1.09	1.10	1.17	1.25	1.23	1.41	1.30	1.62
tPHLfid/tPLHfid	1.19	1.17	1.45	1.46	1.58	1.60	1.65	1.66	1.65	1.64
tPDAc1d	1.09		1.19		1.29		1.43		1.66	
tPDAc2d	1.00		1.09		1.16		1.25		1.39	
tPDAdid	1.00		1.09		1.17		1.27		1.42	
tPDAm sd	0.71		0.69		0.69		0.70		0.73	
tPDAs hd	0.43		0.52		0.58		0.64		0.70	
tPD Afid	0.71		0.83		0.93		1.02		1.14	

2) Power Characteristics [Unit: $\mu W/MHz$]


(Typical process, 25°C, $V_{DD}=2.5V$, $C_L=10$, $S=0.2$, $SA=0.5$, $drv = 1$)

Case	8	24	36	48	64
type=BOTH	9.94	36.69	57.72	79.58	110.01
type=LEFT	6.82	23.31	36.57	50.57	70.42
type=RIGHT	6.80	23.64	36.76	50.30	69.01

3) Size Characteristics [Unit: μm]

Type	Case	8	24	36	48	64
Width	type=BOTH	114.83	178.33	218.13	251.21	284.88
	type=LEFT	76.37	109.57	131.44	150.71	172.38
	type=RIGHT	76.37	109.57	131.44	150.71	172.38
Height	all	112.00	288.00	420.00	552.00	728.00

Logic Symbol



Features

- Asynchronous/synchronous operation
- 6 to 64 bit multiplication
- High speed/low power operation
- 2's complement signed multiplication
- Modified booth algorithm
- 1-stage pipeline insertion available
- Two drive strength available.

Function Description

The MPY is an NxM multiplier which is provided as a compiler. The MPY is intended to use in high-speed and low-power applications. It adopts the modified booth's multiplication scheme to encode the multiplier bits by partitioning the bits into three bit groups, with one bit shared between groups and performs a signed multiplication operation between two integers. It allows from 6-bit to 64-bit with a configurable size of output buffer and 1-stage pipeline scheme is available to improve the frequency of design.

The partial products are summed up with two adders; the MSB adder and the LSB adder. The MSB adder is a fast group bypass adder. The LSB adder is programmable to insert 1-stage pipeline scheme and is, therefore, the ripple carry adder. The clock to the pipeline controls the internal data change, so that the data is always stable throughout the clock period and there is no hold problem.

PARAMETER DESCRIPTION

MPY is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	Description	Range
xbits	Multiplicand (XIN) bits	6 to 64 (even)
ybits	Multiplier (YIN) bits	6 to 64 (even)
pipes	Pipeline stage	0/1
drv	Output drive strength	1/2

NOTE: The xbits should be greater than or equal to the ybits ($x \geq y$).

MPY

Modified Booth Multiplier

Pin Description


Pin Name	Type	Description
XIN []	Input	Data input bus – Multiplicand
YIN []		Data input bus – Multiplier
MCKN		Clock input to the pipeline register. (optional when the parameter pipes = 1)
RSTN		Reset negative input to the pipeline register. (optional when the parameter pipes = 1).
POUT[]	output	Data output bus – Product result

Pin Capacitance [Unit: pF]


Name	Case	Value
XIN[]	all	0.0153
YIN[]	all	0.0293
MCKN	pipe=1	$0.000018 \times x_width + 0.001406 \times y_width - 0.000003 \times x_width \times y_width + 0.021955$
RSTN	pipe=1	$0.000041 \times x_width + 0.003235 \times y_width - 0.000006 \times x_width \times y_width + 0.021454$

Block Diagram

<pipes=0>




<pipes=1>



Timing Diagram

<pipes=0>



Timing Type Definition


Timing Type	Definition
tPHLxp/tPLHxp	Propagation delay from XIN[] to POUT[]
tPHLyp/tPLHyp	Propagation delay from YIN[] to POUT[]
tPDAXp	De-access time from XIN[] to POUT[]
tPDAYp	De-access time from YIN[] to POUT[]

MPY

Modified Booth Multiplier

Timing Diagram (Continued)

<pipes=1>



Timing Type Definition

Timing Type	Definition
SETUPxck	Setup time for input XIN[] to MCKN
SETUPyck	Setup time for input YIN[] to MCKN
SETUPPrck	Setup time for input RSTN to MCKN
HOLDxck	Hold time for input XIN[] to MCKN
HOLDyck	Hold time for input YIN[] to MCKN
HOLDrck	Hold time for input RSTN to MCKN
MINHpck	Minimum Clock Pulse width HIGH
MINLpck	Minimum Clock Pulse width LOW
MINLprn	Minimum Clock Pulse width RSTN
tPHLckp/tPLHckp	Propagation delay from MCKN to POUT[]
tPHLrnp/tPLHrnp	Propagation delay from RSTN to POUT[]
tPDAckp	De-access time from MCKN to POUT[]
tPDArnp	De-access time from RSTN to POUT[]

Characteristic Reference Table

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of bits	-	W	Number of YIN[] bits	-
V _{DD}	Power supply voltage	V	S	Input slope	ns
C _L	Output load	SL	SA	Input switching activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Type	8x8	24x24	36x36	48x48	64x64
<i>Case: pipes=0,drv=1</i>					
tPHLxp/tPLHxp	2.72 / 2.68	5.78 / 5.65	8.01 / 7.87	10.17 / 10.10	12.96 / 13.06
tPHLyp/tPLHyp	2.37 / 2.22	4.56 / 4.46	6.20 / 6.13	7.84 / 7.81	10.02 / 10.05
tPDAXp	1.02	1.23	1.43	1.66	2.00
tPDAYp	1.97	2.24	2.43	2.63	2.90
<i>Case: pipes=1,drv=1</i>					
HOLDrck	0.00	0.00	0.00	0.00	0.00
HOLDxck	0.00	0.00	0.00	0.00	0.00
HOLDyck	0.00	0.00	0.00	0.00	0.00
MINHpc	0.57	0.71	0.81	0.90	1.04
MINLpc	0.23	0.30	0.35	0.40	0.47
MINLprn	0.67	1.09	1.47	1.91	2.59
SETUPrck	0.67	1.09	1.47	1.91	2.59
SETUPxck	1.66	3.04	4.09	5.13	6.52
SETUPyck	1.88	2.90	3.67	4.43	5.45
tPHLckp	1.83	3.44	4.55	5.58	6.81
tPHLrnp	1.72	2.07	2.32	2.58	2.92
tPLHckp	1.47	3.06	4.19	5.28	6.65
tPLHrnp	0.00	0.00	0.00	0.00	0.00
tPDACKp	0.52	0.57	0.61	0.66	0.71
tPDARnp	0.61	0.69	0.75	0.81	0.89

MPY

Modified Booth Multiplier

Characteristic Reference Table (Continued)

2) Power Characteristics [Unit: $\mu\text{W}/\text{MHz}$]

(Typical process, 25°C, $V_{DD}=2.5\text{V}$, $C_L=10$, $S=0.2$, $SA=0.5$)

Case	8x8	24x24	36x36	48x48	64x64
pipes=0, drv=1	62.32	385.23	1209.05	2531.42	5070.11
pipes=1, drv=1	85.17	328.68	964.13	1987.71	3956.24

3) Size Characteristics [Unit: μm]

Type	Case	8x8	24x24	36x36	48x48	64x64
Width	pipes=0, drv=1	222.06	475.21	668.62	865.07	1131.74
	pipes=1, drv=1	276.30	531.49	723.89	917.16	1176.21
Height	pipes=0, drv=1	112.00	288.00	420.00	552.00	728.00
	pipes=1, drv=1	123.00	299.00	431.00	563.00	739.00

PLL

6

Contents

PLL2013X 6-1

General Description

The PLL2013X is a Phase-Locked Loop (PLL) Frequency Synthesizer constructed in CMOS on single monolithic structure. The PLL macrofunctions provide frequency multiplication capabilities. The output clock frequency F_{out} is related to the input clock frequency F_{in} (XTALIN) by the following equation:

$$F_{out} = (m \times F_{in}) / (p \times s).$$


Where, F_{out} is the output clock frequency. F_{in} is the input clock frequency. m , p and s are the values for programmable dividers. PLL2013X consists of a Phase/Frequency Detector (PFD), a Charge Pump, an External Loop Filter, a Voltage Controlled Oscillator (VCO), a 6-bit Pre-divider, an 8-bit Main divider and a 2-bit Post Scaler as shown in Figure 6-1.

Features

- 0.25μm CMOS device technology
- 2.5V single power supply
- Output frequency range: 20-170MHz
- Jitter: ±150 ps at 170MHz
- Duty ratio: 45% to 55% (All tuned range)
- Frequency changed by programmable dividers
- Provision for 14.318MHz crystal oscillator buffer (option)
- Lock detector (option)
- Power down mode

Block Diagram

Figure 6-1 Phase Locked Loop Block Diagram




NOTE: X-tal oscillator and Lock detector are optional block. If customer concerns about this block - Xtal buffer or lock detector, refer to Optional Block Users Guide (page 6-6).

Pin Description

Name	I/O Type	I/O Pad	Pin Description
VDD25A2	Digital Power	vdd2t_abb	Digital power supply
VSS25A2	Digital Ground	vss2t_abb	Digital ground
VDD25A1	Analog Power	vdd2t_abb	Analog power supply
VSS25A1	Analog Ground	vss2t_abb	Analog ground
VBBA	Analog sub bias /Digital sub bias	vbb_abb	Analog/Digital sub bias
FIN	Digital Input	picc_abb	Reference frequency input
FILTER	Analog Output	poar50_abb	Pump out is connected to filter. A capacitor is connected between the pin and analog ground.
FOUT	Digital Output	pot8_abb	20MHz~170MHz clock output
PWRDN	Digital Input	picc_abb	FSPLL clock power down. - When PWRDN is High, PLL do not operate. - If PWRDN is not used, it should be tied to VSS.
P[5:0]	Digital Input	picc_abb	The values for 6bit programmable pre-divider.
M[7:0]	Digital Input	picc_abb	The values for 8bit programmable main divider.
S[1:0]	Digital Input	picc_abb	The values for 2bit programmable post scaler.

Figure 6-2 Core Configuration



Recommended Operating Conditions

Characteristics	Symbol	Min	Typ	Max	Unit
Supply voltage	VDD25A2 - VDD25A1	-0.1		+0.1	V
Oscillator frequency	Fosc		14.318		MHz
External loop filter capacitance	LF		820		pF
Operating temperature	Topr	0		70	°C

NOTE: It is strongly recommended that all the supply pins (VDD25A2, VDD25A1) be powered from the same operating supply voltage to avoid power latch-up.

DC Electrical Characteristics

Characteristics	Symbol	Min	Typ	Max	Unit
Operating voltage	VDD25A2/VDD25A1	2.375	2.5	2.625	V
Digital input voltage high	V _{IH}	1.9			V
Digital input voltage low	V _{IL}			0.5	V
Dynamic current	I _{dd}			3	mA
Power down current	I _{pd}			50	μA

AC Electrical Characteristics

Characteristics	Symbol	Min	Typ	Max	Unit
Crystal frequency	F _{XTAL}		14.318		MHz
Input frequency	F _{IN}	2		40	MHz
Output clock frequency	F _{OUT}	20		170	MHz
Input clock duty cycle	T _{ID}	40		60	%
Output clock duty cycle (at 170MHz)	T _{OD}	45		55	%
Input glitch pulse width	T _{IGP}	1			ns
Locking time	T _{LT}			150	μs
Jitter, cycle to cycle	T _{JCC}	-150		+150	ps

NOTE: It is strongly recommended that input signal is not generated glitch, but if customer cannot help generating glitch, customer must carefully considerate the specification.

Functional Description

A PLL is the circuit synchronizing an output signal (generated by an VCO) with a reference or input signal in frequency as well as in phase.

In this application, it includes the following basic blocks.

- The voltage-controlled oscillator to generate the output frequency
- The divider P divides the input frequency by p
- The divider M divides the VCO output frequency by m
- The divider S divides the VCO output frequency by s
- The phase frequency detector detects the phase difference between the reference frequency and the output frequency (after division) and controls the charge pump voltage.
- The loop filter removes the high frequency components in charge pump voltage and gives smooth and clean control to VCO

The m, p, s values can be programmed by 16bit digital data from the external source. So the PLL can be locked in the desired frequency.

$$F_{out} = (m \times F_{in}) / (p \times s)$$

where

$$F_{in} = 14.318\text{MHz}, m = M + 8, p = P + 2, s = 2^S$$

Table 6-1 Digital Data Format

Main Divider	Pre Divider	Post Scaler
M7, M6, M5, M4, M3, M2, M1, M0	P5, P4, P3, P2, P1, P0	S1, S0

NOTES:

1. S[1]-S[0]: Output frequency scaler
2. M[7]-M[0]: VCO frequency divider
3. P[5]-P[0]: Input frequency divider

OUTPUT FREQUENCY EQUATION & TABLE

$$\text{Frequency equation: } F_{OUT} = \frac{(M + 8)}{(P + 2) \times 2^S} \times F_{IN}$$

Table 6-2 Example of Divider Ratio


M7	M6	M5	M4	M3	M2	M1	M0	M	m(M+8)	S1	S0	2 ^S
0	1	0	1	0	1	0	1	85	93	0	0	1
P5	P4	P3	P2	P1	P0	P	p(P+2)					
1	0	1	0	1	0	42	44					

CORE EVALUATION GUIDE

For the embedded PLL, we must consider the test circuits for the embedded PLL core in multiple applications. Hence the following requirements should be satisfied.

- The FILTER and FOUT pins must be bypassed for external test.
- For PLL test (below 2 examples), it is needed to control the dividers - M[7:0], P[5:0] and S[1:0] - that generate multiple clocks.
 - #1. Registers can be used for easy control of divider values.
 - #2. N sample bits of 16-bit divider pins can be bypassed for test using mux.

Figure 6-3 PLL Functional Block Diagram



Core Layout Guide

The digital power (VDD25A2, VSS25A2) and the analog power (VDD25A1, VSS25A1) must be dedicated to PLL only and separated. If the dedicated VDD25A2 and VSS25A2 is not allowed that of the least power consuming block is shared with the PLL.

The poar50_abb pad is used as a FILTER pad that contains only ESD production diodes with 500ohm resistors.

The FOUT and FILTER pins must be placed far from the internal signals in order to avoid overlapping signal lines.

The blocks having a large digital switching current must be located away from the PLL core.

For the FOUT pad, you can use a custom drive buffer or pot8_abb buffer considering the drive current.

Optional Block Users Guide

— There are crystal driver cell options for the PLL2013X core


1. If the crystal component not used, an external clock source is applied to the FIN

- If the crystal component not used, an external clock I/O buffer offered from samsung's STD111 library is recommended for use
- When implementing an embedded PLL block, the following pins must be bypassed externally for testing the PLL locking function:
 - Without Xtal-driver: FIN, FILTER, FOUT, VDD25A1, VSS25A1, VDD25A2 and VSS25A2, VBBA.

2. If the crystal componet and the lock detector used, please contact SEC application engineer


- When implementing an embedded PLL block, the following pins must be bypassed externally for testing the PLL locking function:
 - With Xtal-driver: XTALIN, XTALOUT, LDOUT, FILTER, FOUT, VDD25A1, VSS25A1, VDD25A2 and VSS25A2, VBBA

Figure 6-4 The Example of PLL Block With Crystal Component and Lock Detector



XTAL Buffer Cell


Figure 6-5 XTAL PAD Symbol



- A XTAL Buffer cell for PLL is supported STD111 databook of Samsung.
- The XTAL must be located between PADA and PADB.
Enable pin (E) must be HIGH in normal operation.
- PI pin must be connected to vdd25a2 and the PO pin floated.

Lock Detector


Figure 6-6 Lock Detector Block




The built-in lock detector circuit will only work, when it is used in conjunction with PFD block output up/down signal. (refer to Figure 6-6)

We represent the output of lock detector in the timing diagram. (refer to Figure 6-7)

Figure 6-7 Lock Detector Timing Diagram



PACKAGE CONFIGURATION



PACKAGE PIN DESCRIPTION

Name	Pin No.	I/O Type	Pin Description
VDDD	35, 36	DP	Digital power supply
VSSD	33, 34	DG	Digital ground
VBB	19, 20	AB/DB	Analog / digital sub bias
PWRDN	18	DI	FSPLL clock power down. - When PWRDN is high, PLL do not operate. - If PWRDN is not used, it should be tied to VSS.
P[0]~P[5]	45~48, 1, 2	DI	Pre-divider input
VDDA	13, 14	AP	Analog power supply
VSSA	11, 12	AG	Analog ground
XTALIN	15	AI	Xtal external input Load Cap: 25pF If customer don't use the xtal, use this pin to input port.
XTALOUT	16	AO	Xtal external output Load Cap: 25pF If customer don't use the xtal, Float this pin.
FOUT	23	DO	20MHZ~170MHz clock output
LDOUT	10	DO	Lock detector output
FILTER	17	AO	Pump out is connected to the filter. A 820pF capacitor is connected between the filter pin and analog ground pin
S[0]~S[1]	32, 31	DI	Post scaler input
M[0]~M[7]	37~44	DI	8-bit main divider input
TST1, TST3	3, 5	DI	Test pin, apply to analog vdda
TST2, TST4, TST5	4, 29, 30	DI	Test pin, apply to ground
VDDO	28	PP	I/O pad power
VSSO	27	PG	I/O pad ground

NOTES:

1. I/O TYPE PP and PG denote PAD power and PAD ground respectively.
2. XTALIN, XTALOUT, LDOUT is test pin for PLL in Samsung.

Design Considerations

The following design considerations apply:

- Jitter is affected by the power noise, substrate noise, etc.
It increases when the noise level increases.
- A CMOS-level input reference clock is recommend for signal compatibility with the PLL circuit. Other levels such as TTL may degrade the tolerances.
- The used of two, or more PLLs requires special design considerations. Please consult your application engineer for more information.
- The following apply to the noise level, which can be minimized by using good analog power and ground isolation techniques in the system:
 - Use wide PCB traces for POWER (VDD25A2/VSS25A2, VDD25A1/VSS25A1, VBBA) connections to the PLL core. Separate the traces from the chip's VDD25A2/VSS25A2, VDD25A1/VSS25A1 supplies.
 - Use proper VDD25A2/VSS25A2, VDD25A1/VSS25A1 de-coupling.
 - Use good power and ground sources on the board.
 - Use power VBBA for minimize substrate noise.
- The PLL core should be placed as close as possible to the dedicated loop filter and analog power and ground pins.
- It is inadvisable to locate noise-generating signals, such as data buses and high-current outputs, near the PLL I/O cells.
- Other related I/O signals should be placed near the PLL I/O but do not have any pre-defined placement restriction.


PLL Specification

We appreciate your interest in our products. If you have further questions, please specify in the attached form. Thank you very much.

Parameter	Min	Typ	Max	Unit	Remarks
Supply voltage					
Output frequency range					
Input frequency range					
Cycle-to-cycle jitter					
Lock up time					
Dynamic current					
Standby current					
Output clock duty ratio					
Long term jitter					
Output slew rate					

- Do you need XTAL driver buffer in PLL core?
 - If you need it, what is the crystal frequency range?
 - If not, What is the input frequency range?
- Do you need the lock detector?
- Do you need the I/O cell of Samsung?
- Do you need the external pin for PLL test?
- What is the main frequency and frequency range?
- How many FSPLLs do you use in your system?
- What is output loading?
- Could you internal/external pin configurations as required?
- Specially requested function list:

DESIGN CENTERS



SSI

3655 North First Street San Jose CA, 95134,
U.S.A.

TEL (1)-408-544-4740
FAX (1)-408-544-4950

SWDC

3345 Michelson Drive, Suite 250, Irvine, CA
92612, U.S.A.

TEL (1)-408-544-4885
FAX (1)-408-544-4950

CDI

85 West Tasman Road San Jose, CA 95134

TEL (1)-408-544-4553
FAX (1)-408-544-4979

SSEL

Samsung Electronics Europe ASIC Design
Center Great West House, Great West Road,
Brentford, Middlesex TW8 9DQ

TEL (44)-20-8380-7101
FAX (44)-20-8380-7095

SoCTechnology

Samsung Electronics Germany ASIC/SOC
Design Center & Sales Representative Am
Kronberger Hang 4, D-65824

Schwalbach/Ts., Germany
TEL (49)-6196-66-7302
FAX (49)-6196-66-7366

SJC

Samsung Japan Co. ASIC Design Center
Samsung Tokyo Distribution Center 5F,
2-6-38 Shinonome, Koutou-ku, Tokyo,
135-0062

TEL (81)-3-5564-2100
FAX (81)-3-5564-2101

ComSOC

Samsung Electronics Singapore ASIC Design
Center 31 International Business Park,
#04-06 Creative Resource, Singapore
609921

TEL (65)-6425-2212
FAX (65)-6425-2022

CoAsia

Samsung Electronics Taiwan ASIC Center 9F,
No. 69, Chou Tze St., Nei hu, Taipei, Taiwan,
R.O.C.

TEL (886)-2-2658-2020
FAX (886)-2-8780-0101

Si-Plaza

Unit 2505, 25F, Cosco Tower, 183 Queen's
Road Central, HK

TEL (852)-2907-6388
FAX (852)-2907-7188

AlphaChips

San #24, Nongseo-Ri Giheung-Eup,
Yongin-City, Gyunggi-Do, Korea

TEL (82)-031-209-1800
FAX (82)-031-209-1819

**CUSTOMER
FEEDBACK**

We would appreciate your feedback on this document. Please copy the following page, add your comments, and fax it to us at the address on the following page.

If appropriate, please also fax copies of any marked-up pages from this document.

Important: Please include your name, phone number, fax number and company address so that we may contact you directly for clarification or additional information.

Thank you for your help in improving the quality of our documents.

Reader's Comments

Fax your comments to:
System LSI Business,
ASIC Infra P/J

Fax: (82)-031-209-4920

Please tell us how you rate this document. Please a check mark in the appropriate blank for each category.

	Excellent	Good	Average	Fair	Poor
<input type="checkbox"/> Completeness of information	_____	_____	_____	_____	_____
<input type="checkbox"/> Clarity of information	_____	_____	_____	_____	_____
<input type="checkbox"/> Ease of finding information	_____	_____	_____	_____	_____
<input type="checkbox"/> Technical content	_____	_____	_____	_____	_____
<input type="checkbox"/> Usefulness of examples and illustrations	_____	_____	_____	_____	_____
<input type="checkbox"/> Overall manual	_____	_____	_____	_____	_____

What could we do to improve this document?

If you found errors in this document, please specify the error and page number. If appropriate, please fax a marked-up copy of the page(s).

Please complete the information below so that we may contact you directly for clarification or additional information.

☐ Name _____ ☐ Date _____

☐ Telephone _____ ☐ Fax _____

☐ Title _____

☐ Department _____ ☐ Mail Stop _____

☐ Company Name _____

☐ Street _____

☐ City, State, Zip _____