

STDM110

0.25μm 2.5V CMOS Standard Cell Library for Pure Logic/MDL Products

STDM110
0.25μm 2.5V CMOS Standard Cell Library
for Pure Logic/MDL Products
Data Book

© 1999 Samsung Electronics Co., Ltd.
All rights reserved. No part of this document may be reproduced, in any form or by any means, without the prior written consent of the publisher. Samsung assumes no responsibility for any errors resulting from the use of the information contained herein, nor does it convey any license under the patent rights of Samsung or others. Samsung reserves the right to make changes in its products or product specification to improve function or design at any time, without notice.

SEC and STDM110 are trademarks of Samsung Electronics Co., Ltd. Verilog is a registered trademark of Cadence Design Systems, Inc. Viewlogic is a registered trademark of Viewlogic Systems, Inc. Mentor is a registered trademark or Mentor Graphics Co. Synopsys is a registered trademark of Synopsys, Inc.

Head Office

Samsung Electronics Co., Ltd
System LSI Business,
ASIC Division, ASIC Design Service Team
San #24, Nongseo-Ri,
Kiheung-Eup, Yongin-City,
Kyunggi-Do, Korea

TEL 82-2-760-6500, 6501 (Hot Line)
FAX 82-331-209-4920
http://www.intl.samsungsemi.com

Marketing Team

Samsung Electronics Co., Ltd
System LSI Business,
ASIC Division,
ASIC Marketing Team
15th Fl., Severance Bldg.
84-11, 5-Ka, Namdaemoon-Ro, Chung-Ku,
Seoul, Korea

TEL 82-2-259-4988
FAX 82-2-259-2494

Printed in the Republic of Korea

Introduction

This databook contains information about STDM110 0.25μm 2.5V standard cell library for pure Logic/MDL products developed by SEC (Samsung Electronics Corporation).

The “library” basically contains various kinds of internal and I/O cells and soft-macros which are used for developing ASIC (Application Specific Integrated Circuit). It also includes a design kit helping designers to work in a workstation platform, and all sorts of design environments needed for an automatic chip design.

There are six chapters in this databook:

Chapter 1	Introduction
Chapter 2	Electrical Characteristics
Chapter 3	Internal Macrocells
Chapter 4	Input/Output Cells
Chapter 5	Compiled Macrocells
Chapter 6	PLL

In this databook each cell is followed by its AC electrical characteristics, and these characteristic values are almost equal when the corresponding cell is operated in a real chip.

The purpose of this databook is to prevent any misuse or misapplication of STDM110 cell library by providing precise information about the cell list, electrical data, directions for use, and matters demanding special attention.

If you want to get more information about DRAMs, Digital cores and Analog cores that are not included in this databook, access the Samsung ASIC web site(http://www.intl.samsungsemi.com) or contact Head Office.

Contents

1 Introduction

1.1 Library Description 1-1
1.2 Features 1-2
1.3 EDA Support 1-4
1.4 Product Family 1-4
1.4.1 Analog Core Cell 1-4
1.4.2 Internal Macrocells 1-12
1.4.3 Compiled Macrocells 1-12
1.4.4 Input/Output Cells 1-14
1.5 Timings 1-16
1.6 Delay Model 1-22
1.7 Testability Design Methodology 1-24
1.8 Maximum Fanouts 1-27
1.9 Packages Capability by Lead Count 1-34
1.10 Power Dissipation 1-36
1.11 V_{DD}/V_{SS} Rules and Guidelines 1-39
1.12 Crystal Oscillator Considerations 1-45

2 Electrical Characteristics

DC Electrical Characteristics 2-1

3 Internal Macrocells

Overview 3-1
Summary Tables 3-2

Logic Cells

AD2DH/AD2/AD2D2/AD2D4 3-17
AD3DH/AD3/AD3D2/AD3D4 3-19
AD4DH/AD4/AD4D2/AD4D4 3-21
AD5/AD5D2/AD5D4 3-24
ND2DH/ND2/ND2D2/ND2D4 3-27
ND3DH/ND3/ND3D2/ND3D4 3-29
ND4DH/ND4/ND4D2/ND4D2B/ND4D4 3-32
ND5/ND5D2/ND5D4 3-35
ND6/ND6D2/ND6D4 3-38

ND8/ND8D2/ND8D4....3-42
NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A....3-46
NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A....3-49
NR4DH/NR4/NR4D2/NR4D2B/NR4D4....3-53
NR5/NR5D2/NR5D4....3-56
NR6/NR6D2/NR6D4....3-60
NR8/NR8D2/NR8D4....3-64
OR2DH/OR2/OR2D2/OR2D4....3-68
OR3DH/OR3/OR3D3/OR3D4....3-70
OR4DH/OR4/OR4D2/OR4D4....3-73
OR5/OR5D2/OR5D4....3-76
XN2/XN2D2/XN2D4....3-80
XN3/XN3D2/XN3D4....3-82
XO2/XO2D2/XO2D4....3-84
XO3/XO3D2/XO3D4....3-86
AO21DH/AO21/AO21D2/AO21D2B/AO21D4....3-88
AO211DH/AO211/AO211D2/AO211D2B/AO211D4....3-91
AO2M110/AO2M110D2....3-94
AO22DH/AO22/AO22D2/AO22D2B/AO22D4....3-97
AO22DHA/AO22A/AO22D2A/AO22D4A....3-100
AO221/AO221D2/AO221D4....3-103
AO222/AO222D2/AO222D2B/AO222D4....3-107
AO222A/AO222D2A/AO222D4A....3-112
AO2222/AO2222D2/AO2222D4....3-114
AO31DH/AO31/AO31D2/AO31D4....3-118
AO311/AO311D2/AO311D4....3-121
AO3M110/AO3M110D2....3-125
AO32/AO32D2/AO32D4....3-128
AO321/AO321D2/AO321D4....3-132
AO322/AO322D2/AO322D4....3-136
AO33/AO33D2/AO33D4....3-140
AO331/AO331D2/AO331D4....3-144
AO332/AO332D2/AO332D4....3-148
AO4M110/AO4M110D2....3-152
OA21DH/OA21/OA21D2/OA21D2B/OA21D4....3-155
OA211DH/OA211/OA211D2/OA211D2B/OA211D4....3-158
OA2M110/OA2M110D2....3-161
OA22DH/OA22/OA22D2/OA22D2B/OA22D4....3-164
OA22DHA/OA22AOA22D2A/OA22D4A....3-167
OA221/OA221D2/OA221D4....3-170
OA222/OA222D2/OA222D2B/OA222D4....3-174
OA2222/OA2222D2/OA2222D4....3-179
OA31/OA31D2/OA31D4....3-183

OA311/OA311D2/OA311D4 3-186
OA3M110/OA3M110D2 3-190
OA32/OA32D2/OA32D4 3-193
OA321/OA321D2/OA321D 3-197
OA322/OA322D2/OA322D4 3-201
OA33/OA33D2/OA33D4 3-205
OA331/OA331D2/OA331D4 3-209
OA332/OA332D2/OA332D4 3-213
OA4M110/OA4M110D2 3-217
SCG1/SCG1D2 3-220
SCG2//SCG2D2 3-223
SCG3/SCG3D2 3-225
SCG4/SCG4D2 3-228
SCG5/SCG5D2 3-231
SCG6/SCG6D2 3-234
SCG7/SCG7D2 3-236
SCG8/SCG8D2 3-239
SCG9/SCG9D2 3-241
SCG10/SCG10D2 3-243
SCG11/SCG11D2 3-245
SCG12/SCG12D2 3-248
SCG13/SCG13D2 3-250
SCG14/SCG14D2 3-252
SCG15/SCG15D2 3-254
SCG16/SCG16D2 3-256
SCG17/SCG17D2 3-258
SCG18/SCG18D2 3-160
SCG19/SCG19D2 3-263
SCG20/SCG20D2 3-265
SCG21/SCG21D2 3-267
SCG22/SCG22D2 3-269
DL1D2/DL1D4 3-271
DL2D2/DL2D4 3-272
DL3D2/DL3D4 3-273
DL4D2/DL4D4 3-274
DL5D2/DL5D4 3-275
DL10D2/DL10D4 3-276
IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16 3-277
IVCD(11/13)/IVCD(22/26)/IVCD44 3-280
IVT/IVTD2/IVTD4/IVTD8/IVTD16 3-282
IVTN/IVTND2/IVTND4/IVTND8/IVTND16 3-284
NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16 3-286
OAK_NID10P/OAK_NID 20P 3-289

NIT/NITD2/NITD4/NITD8/NITD16 3-290
OAK_DUCLK10/OAK_DUCLK16 3-296
CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/
CTSBD8/CTSBD16 3-298

Flip-Flops

FD1/FD1D2 3-304
FD1CS/FD1CSD2 3-306
FD1S/FD1SD2 3-308
FD1SQ/FD1SQD2 3-310
FD1Q/FD1QD2 3-312
FD2/FD2D2 3-314
FD2CS/FD2CSD2 3-316
FD2S/FD2SD2 3-320
FD2SQ/FD2SQD2 3-322
FD2Q/FD2QD2 3-324
FD3/FD3D2 3-326
FD3CS/FD3CSD2 3-328
FD3S/FD3SD2 3-332
FD3SQ/FD3SQD2 3-334
FD3Q/FD3QD2 3-336
FD4/FD4D2 3-338
FD4CS/FD4CSD2 3-341
FD4S/FD4SD2 3-345
FD4SQ/FD4SQD2 3-349
FD4Q/FD4QD2 3-352
FD5/FD5D2 3-354
FD5S/FD5SD2 3-356
FD6/FD6D2 3-358
FD6S/FD6SD2 3-360
FD7/FD7D2 3-362
FD7S/FD7SD2 3-364
FD8/FD8D2 3-366
FD8S/FD8SD2 3-369
FDS2/FDS2D2 3-373
FDS2CS/FDS2CSD2 3-375
FDS2S/FDS2SD2 3-377
FDS3/FDS3D2 3-379
FDS3CS/FDS3CSD2 3-381
FDS3S/FDS3SD2 3-383
FJ1/FJ1D2 3-385
FJ1S/FJ1SD2 3-387
FJ2/FJ2D2 3-389
FJ2S/FJ2SD2 3-391

FJ4/FJ4D2 3-393
FJ4S/FJ4SD2 3-396
FT2/FT2D2 3-399

Latches

LD1/LD1D2 3-402
LD1A/LD1D2A 3-404
LD1Q/LD1QD2 3-406
LD2/LD2D2 3-408
LD2Q/LD2QD2 3-411
LD3/LD3D2 3-413
LD4/LD4D2 3-416
LD5/LD5D2 3-419
LD5Q/LD5QD2 3-421
LD6/LD6D2 3-423
LD6Q/LD6QD2 3-426
LD7/LD7D2 3-428
LD8/LD8D2 3-431
LS0/LS0D2 3-434
LS1/LS1D2 3-436

Bus Holder

BUSHOLDER 3-437

Internal Clock Drivers

CK(2/4/6/8) 3-438

Decoders

DC4 3-441
DC4I 3-443
DC8I 3-445

Adders

FADH/FA/FAD2 3-450
HADH/HA/HAD2 3-453
SCG23/SCG23D2 3-456

Multiplexers

MX2DH/MX2/MX2D2/MX2D4 3-460
MX2X4 3-463
MX2IDH/MX2I/MX2ID2/MX2ID4 3-466
MX2IDHA/MX2IA/MX2ID2A/MX2ID4A 3-469
MX2IX4 3-472
MX3I/MX3ID2/MX3ID4 3-475
MX4/MX4D2/MX4D4 3-479

MX8/MX8D2/MX8D4 3-483

4 Input/Output Cells

Overview 4-1
Summary Tables 4-2

Input Buffers

PvIC/PvICD/PvICU 4-8
PvIS/PvISD/PvISU 4-12
PvIT/PvITD/PvITU 4-16

Output Buffers

PvOByz 4-20
PvODyz 4-29
PvOTyz 4-41

Bi-Directional Buffers

PvBaDyz/PvBaUDyz 4-59
PvBaTyz/PvBaDTyz/PvBaUTyz 4-59

Oscillators

PHSOSC(K1/K2/M1/M2) 4-61
PH2SOSC(K1/K2/M1/M2) 4-66
PSOSC(K1/K2/M1/M2) 4-71

PCI Buffers

PTIPCI 4-78
PTOPCI 4-79
PTBPCI 4-80

USB I/O Buffers

PBUSB/PBUSB1 4-83
PBUSBLS 4-84
PBUSB_FS 4-85

Power Pads

VDD2(I/P/O/IP/OP/T)/VDD3(P/O/OP) 4-92
VSS2(I/P/O/IP/OP/T)/VSS3(P/O/OP) 4-92

Analog Interface

VDD2I_ABB/VDD2OP_ABB/VDD2T_ABB 4-92
VSS2I_ABB/VSS2OP_ABB/VSS2T_ABB 4-92
VBB_ABB/VSSBB_ABB 4-92
PIC_ABB 4-94

PICC_ABB 4-95
PICEN_ABB 4-96
POT1/2/4/8/_ABB 4-97

ESD Slot Cells

EV1I/EV2P/EV2O/EV2OP/EV3P/EV3O/EV3OP 4-100
EV1I_ABB/EV2OP_ABB 4-100

Common Slot Cells

EC0C0/EC0C0D/EC0CA0/EC0CA0D/EC0C0_BB/EC0C0D_BB/EC0C0_VBB/EC0C0D_VBB 4-101

5 Compiled Macrocells

Overview 5-1
Compiled Memory Naming Convention 5-1
Characteristics for Timing and Power 5-2
Built-In Self Test and Built-In Redundancy-Analysis 5-4
Compiled Memory Selection Guide 5-5

Low-Power Compiled Memory

SPSRAM_LP 5-7
DPSRAM_LP 5-17
SPARAM_LP 5-27
DROM 5-37
MROM 5-45

Overview to Compiled Datapath

Overview to Compiled Datapath 5-53
Compiled Macrocell Selection Guide 5-54
ADDER 5-55
BS 5-66
MPY 5-78

6 PLL

PLL2013X 6-1

NOTE

Introduction 1

Table of Contents

1.1 Library Description 1-1
1.2 Features 1-2
1.3 EDA Support 1-4
1.4 Product Family 1-4
1.4.1 Analog Core Cells 1-4
1.4.2 Internal Macrocells 1-12
1.4.3 Compiled Macrocells 1-12
1.4.4 Input/Output Cells 1-14
1.5 Timings 1-16
1.6 Delay Model 1-22
1.7 Testability Design Methodology 1-24
1.8 Maximum Fanouts 1-27
1.9 Packages Capability by Lead Count 1-34
1.10 Power Dissipation 1-37
1.11 V_{DD}/V_{SS} Rules and Guidelines 1-40
1.12 Crystal Oscillator Considerations 1-46

1.1 Library Description

Samsung ASIC offers STDM110 as 0.25um CMOS standard cell library. Samsung's 0.25um cell-based logic process providing up to 5 layers of interconnect metal with various I/O pad-pitch options such as 70um pitch pad and 80um pitch pad.

STDM110 which reduced power dissipation and system cost by merging the logic and IPs as a whole and connecting internally from logic to memory data bus is ideal for high-performance products such as graphics controller, projector, portable CD and so on.

STDM110 can support up to eight million gate counts of logic providing 75% of usable gate. Logic density is 2.1 times greater than that of MDL90. The power consumption of compiled memory is 90% smaller than MDL90.

STDM110 also supports fully user-configurable compiled memory and datapath elements. Each element is provided as a compiler. Two different types of compiled memories in STDM110 are available to support memories suitable to high-density and low-power applications.

To support mixed voltage environments, 2.5V, 3.3V drive and 5V-tolerant IO cells are available. LVTTL, LVCMOS, PCI, OSC, AGP, PECL, HSTL, LVDS and USB buffers are supported. To better support a system-on-chip design style, various core cells are available including processor cores like ARM7TDMI/ARM9TDMI/ ARM920T/ARM940T from ARM, Teaklite from DSPG.

The STDM110 supports data transmission and communication core such as USB, IEEE1284 and UART.

The list of analog core cells includes ADC, DAC, CODEC, LVDS, RAMDAC and PLL with various bits and frequency ranges.

Samsung design methodology offers an comprehensive timing driven design flow including automated time budgeting, tight floorplan synthesis intergration, powerful timing analysis and timing driven layout. Its advanced characterization flow provides accurate timing data and robust delay models for a 0.25um very deep-submicron technology. Advanced verification methods like static timing analysis and formal verification provide an effective verification methodology with a variety of simulators and cycle based simulation. Samsung DFT methodology supports scan design, BIST and JTAG boundary scan. Samsung provides a full set of test-ready IPs with an efficient core test integration methodology.

1.2 Features

- 1.8V standard cell library including processor and analog cores
- 0.25um five layer metal(from four layer metal option) CMOS technology
  - Logic, processor and analog
- High basic cell usages
  - Up to 8 million gates
  - Maximum usage: 75% for five layer metal
- High speed
  - Typical 2-input NAND gate delay (ND2D4): 112ps (F/O=2 + WL (0.02pF))
- Operation temperature (T_A)
  - Commercial range: 0°C to +70°C
  - Industrial range: –40°C to +85°C
- Digital cores usages
  - Hard-macro: ARM7TDMI, ARM9TDMI, ARM920T, ARM940T, Teaklite
  - Soft-macro: AMBA, DMA Controller, SDRAM Controller, Interrupt Controller, IIC, WDT, RTC, USB, IrDA, UART(16C450, 16C550), Fast Ethernet MAC, P1394a LINK, RS Decoder, Viterbi Decoder
- Analog cores usages
  - Ultra low voltage analog core (2.5V and 1.8V) available
  - Analog core supply voltage:
    2.5V analog core: 2.5V ± 5%
    1.8V analog core: 1.8V ± 5%
  - ADC: 8bit (30M, 2.5V), 10bit ((30M, 100M, 2.5V), (250K, 20M, 1.8V)), 12bit (200K, 20M, 2.5V)
  - DAC: 8bit (2M, 2.5V), 10bit ((300M, 2.5V), (2M, 1.8V)), 12bit ((2M, 2.5V), (80M, 1.8V))
  - CODEC: 8bit (8K~11K), 16bit (44.1K)
  - PLL: 25M ~ 300M (FSPLL, 2.5V), 1G (PLL, 1.8V), 20M ~ 170M(FSPLL, 1.8V)
  - Others: 300M (RAMDAC+PLL)
- Fully user-configurable Static RAMs and ROMs
  - High-density and low-power memory available
  - Duty-free cycle in synchronous memory available
  - 2-bank architecture available
  - Flexible aspect ratio available
  - Up to 256K-bit single-port SRAM available.
  - Up to 128K-bit dual-port SRAM available.
  - Up to 512K-bit diffusion and metal-2 ROM available.
  - Up to 16K-bit multi-port register file available.
  - Up to 32K-bit FIFO available.
- Fully configurable datapath macrocells
  - 4 ~ 64 bit adder available
  - 4 ~ 64 bit barrel shifter available
  - 6 ~ 64 bit multiplier with 1-stage pipeline available
  - Various output driver strength available
  - A tightly integrate apollo, Avant!, design environment
- I/O cells
  - 2.5V/3.3V and 5V tolerant IO
  - 3-level (high, medium, no) slew rate control
  - 1/2/4/6/8/10/12mA available for 3.3V and 2.5V output buffers
  - 1/2/3mA available for 5V-tolerant output buffers

- IO IP available
  - PCI ((33MHz, 66MHz, 3.3V), (33MHz, 3.3/5V tolerant))
  - USB (full speed/low speed)
  - SSTL2 (DDR SDRAM interface, up to 200MHz)
  - AGP (AGP2.0 Compliant, 66MHz@1X,133MHz@2X, 266MHz@4X)
  - PECL (2.5V interface, up to 400MHz)
  - HSTL (class1, class2, 30MHz)
  - LVDS (3.3V(2.5V optional) interface, 300MHz)
- Various package options
  - QFP, thin QFP, power QFP, plastic BGA, super BGA, plastic leaded chip carrier, etc.
- Fully integrated CAD software and EDA support
  - Logic synthesis: Synopsys Design Compiler
  - Logic simulation: Cadence Verilog-XL, Cadence NC-Verilog, Viewlogic ViewSim, Mentor ModelSim-VHDL, Mentor ModelSim-Verilog, Synopsys VSS, Synopsys VCS
  - Scan insertion and ATPG: Synopsys TestGen, Synopsys Test Compiler, Mentor Fastscan
  - Static timing analysis: Synopsys PrimeTime, Synopsys MOTIVE
  - RC analysis: Avant! Star-RC
  - Power analysis: Synopsys DesignPower, CubicPower (In-House Tool)
  - Formal verification: Synopsys Formality, Chrysalis Design VERIFYer, Verplex Tuxedo-LEC
  - Fault simulation: Cadence Verifault, SuperTest (In-House Tool)
  - Delay calculator: CubicDelay (In-House Tool)

- STDM110 contains 12 user selectable clock tree cells(CTC). At the pre-layout design stage, these will be used as the cells which represent actual clock tree informatin of P&R. The key features of new Samsung ASIC CTS flow are as follows:
  - 12 user selectable clock tree cells(CTC) for STDM110
  - Good pre-layout and post-layout correlation
  - No customer netlist modification
  - Accurate post-layout back-annotation mechanism
  - Insertion delay, skew, transition time management
  - Clock tree information file generation
  - Cover 100 to 30,000 fanouts and up to 1M gate count for CTS spanning block (GCCSB)
  - Tightly coupled with Samsung in-house delay calculator, CubicDelay Gated CTS support
  - Hierarchical/Flatten verilog, edif interface for P&R

For more detail information for CTC flow, refer to “CTC flow guideline for CubicDelay” included in Samsung ASIC design kit.

1.3 EDA Support

Samsung ASIC provides an efficient solution for multi-million gate ASICs in very deep submicron (VDSM) technology. For large system-on-chip (SOC) type designs, static verification methodology (static timing analysis and formal verification) will shorten your design cycle time, which in turn will lessen today's ever-increasing time-to-market pressure. Our Design-for-Test (DFT) methodology and service take you through all phases of test insertion, test pattern generation and fault grading to get high test coverage.

STDM110 supports a rich collection of industry-standard EDA tools from Cadence, Synopsys, Mentor graphics, and Avant! on multiple design platforms such as Solaris and HP. Customers are allowed to choose among the industry-leading EDA tools from design capture, synthesis, simulation, and DFT to layout. Several powerful proprietary software tools are seamlessly integrated in our design kits to improve your product quality.

For high simulation accuracy, STDM110 uses a proprietary delay calculator. Cell delay is calculated based on a matrix of delay parameters for each macrocell, and signal interconnect delay is calculated based on the RC tree analysis.

1.4 Product Family

STDM110 library include the following design elements:

- Analog core cells
- Digital core cells
- Internal macrocells
- Compiled macrocells
- Input/Output cells.

1.4.1 ANALOG CORE CELLS

Introduction to Analog Cores

Samsung ASIC is one of the leading suppliers of cell based mixed analog and digital designs. As a leading supplier of mixed analog and digital designs, Samsung ASIC has more analog design experience than any other vendors. Analog has been and will continue to be a part of the strategic focus at Samsung ASIC. Analog design is a part of the total Samsung ASIC integrated design system. Workstation symbols are supplied for analog cells and are entered as part of the design by the customer or design center. Samsung ASIC uses basically the same automatic layout and verification tools for analog cells as for digital cells. Analog designs are processed on the same production line as digital designs.

Samsung's analog core family comprises ADC,DAC,PLL and sigma-delta ADC/DAC, and their brief functional descriptions are introduced below.
[data sheets for all analog cores available]

Analog-to-Digital Converters

Analog-to-digital converters provide the link between the analog world and digital systems. Due to their extensive use of analog and mixed analog-digital operations, A/D converters often appear as the bottleneck in data processing applications, limiting the overall speed or precision.

An A/D converter produces a digital output, D, as a function of the analog input, A:

$$D = f(A)$$

While the input can assume an infinite number of values, the output can be selected from only a finite set of codes given by the converter's output word length(i.e, resolution). Thus, the ADC must approximate each input level with one

of these codes, this process is so called 'quantization'.

In a digital system the amplitude is quantized into discrete steps, and at the same time the signal is sampled at discrete time intervals. This time interval is called sampling time or sampling frequency. After sampling and quantization process, the analog signal(A) becomes digital output (D).

Digital-to-Analog Converters

The D/A converters are the digital-to-analog conversion circuits, which are also called DACs. They can be considered as decoding devices that accept digitally coded signals and provide analog output in the form of currents or voltages. In this manner, they provide an interface between the digital signal of the computer systems and continuous signals of analog world. They are employed in a variety of applications, from CRT display systems and voice sythesizers to automatic test systems, digital controlled attenuators, and process control actuators. In addition, they are key components inside most A/D converters.

Figure 1 shows the functional block diagram of a basic D/A converter system. The input to the D/A converter is a digital word, made up a stream of binary bits comprised of 1's and 0's. The output analog quantity A, which can be a voltage or current, is related to the input as

$$A = KV_{REF}\left[\frac{b1}{2^1}+\frac{b2}{2^2}+\ldots+\frac{bn}{2^n}\right]$$

where K is a scale factor, V_{REF} is a reference voltage, n is the total number of bits, and b1,b2,...,bn are the bit coefficients, which are quntized to be a 1 or a 0.

As a function of the input binary word which determines the bit coefficients, the output exhibits 2^n discrete voltage level ranging from zero to a maximum value of

$$Vo(max) = V_{REF}\frac{2^n-1}{2^n}$$

with a minimum step change ΔVo given as $\Delta Vo = \frac{V_{REF}}{2^n}$ \

Figure 1-1. Functional Block Diagram of Basic D/A Converter



Sigma-Delta ADC/DAC

VLSI offers high speed and high density, but reduced accuracy for analog components and reduced signal range (reduced dynamic range). Hence, an exchange of digital complexity and of resolution in time for resolution in signal amplitude is needed. So good solution is over-sampling data converter. Oversampling sigma-delta converter is used in slow speed (audio band) application because of process limit. It's noise shaping (sigma-delta) feature make high resolution about max. SND=90~100dB

In ADC path, analog single input is converted to differential signal with anti-aliasing filtering through anti-aliasing filter block. And sigma-delta modulator converts the signal into oversampled noise-shaping 1bit PDM (Pulse Density Modulation). Following digital decimation filter reject the out of band noise and outputs 16bits high resolution digital data with down sampled to Fs rate. In DAC path, digital input data is oversampled by interpolation filter and it is converted to noise-shaped 1bit PDM through digital sigma-delta modulator. Analog SC-post-filter rejects the out of band noise. And anti-image filter rejects sampling images and outputs single analog signal with high resolution.

Phase Locked Loop

Samsung's PLL cores implemented as an analog function provide frequency multiplication capabilities and enable system designers to synchronize ASIC chip-level clock networks with a common reference signal.

In the past, designers wishing to incorporate a PLL into a digital design environment had only two options:

(1) A special mixed-signal process to incorporate analog functions onto the chip
(2) An all digital PLL that can be incorporated into a standard digital process.

However, a mixed-signal process is too expensive to be a feasible solution. On the other hand digital PLLs typically require huge silicon area and exhibits poor locking time despite their high accuracy.

Differing from the previous solutions, Samsung's PLL cores can be implemented on standard digital CMOS process while functioning as an analog PLL.

Samsung's PLL cores:
* Require only a few off-chip passive components for the whole function
* Remove the need for an expensive mixed-signal process
* Provide faster locking time than all digital PLLs
* Present low jitter characteristics

Glossary by Core Families

1. Digital-to-Analog Converter

1. Resolution - An n-bit binary converter should be able to provide 2^n distinct and different analog output values corresponding to the set of n-bit binary words. A converter that satisfies this criterion is said to have resolution of n bits. The smallest output change that can be resolved by a linear DAC is 2^{-n} of the full-scale span.

2. Accuracy - Error of a D/A converter is the difference between the actual analog output and the output that is expected when a given digital code is applied to the converter. Source of error include gain error, offset error, linearity errors and noise. Error is usually commensurate with resolution, less than $2^{-(n+1)}$, or 1/2 LSB of full scale.

Figure 1-2. Error of D/A Converter



3. LSB (Least-Significant Bit) - In a system in which a numerical magnitude is represented by a series of binary digits, the LSB is that bit that carries the smallest value or weight. It represents the smallest analog change that can be resolved by an n-bit converter.

$$\text{LSB (Analog Value)} = FSR/2^n$$

FSR = Full-Scale Range, n = number of bits

4. MSB (Most-Significant Bit) - The binary digit with the largest numerical weighting. Normally, the MSB of a digital word has a weighting of 1/2 the full range.

5. Compliance-Voltage Range - For a current output DAC, the maximum range of(output) terminal voltage for which the device will provide the specified current-output characteristics.

6. Glitch - A glitch is a switching transient appearing in the output during a code transition. Its value is expressed as a product of voltage (V*ns) or current (mA*ns) and time duration or charge transferred.

7. Harmonic Distortion (and Total Harmonic Distortion) - The DAC is driven by the digitized representation of sine wave. The ratio of the RMS sum of the harmonics of the DAC output to the fundamental value is the THD. Usually only the lower order harmonics are included, such as second through fifth.

$$THD = 20\log\frac{(V2^2+V3^2+V4^2+V5^2)^{1/2}}{V1}$$

V1: RMS amplitude of the fundamental

8. Signal-to-Noise Ratio (SNR) - This signal to noise ratio depends on the resolution of the converter and automatically includes specifications of linearity, distortion, sampling time uncertainty, glitches, noise, and settling time. Over half the sampling frequency, this signal to noise ratio must be specified and should ideally follows the theoretical formula;

$$S/N_{max} = 6.02N + 1.76dB$$

9. Slew Rate - Slew rate of a device or circuit is a limitation in the rate of change of output voltage, usually imposed by some basic circuit consideration such as limited current to charge of capacitor. Amplifiers with slew rate of a few V/μs are common and moderate in cost. Slew rates greater than about 75 V/μs are usually seen only in more sophisticated (and expensive) devices The output slewing speed of a voltage-output D/A converter is usually limited by the slew rate of the amplifier used at its output (if one is used).

10. Settling Time - The time required, following a prescribed data change from the 50% point of the login input change, for the output of a DAC to reach and to remain within a given fraction (usually ±1/2lsb) of the final value. Typical prescribed changes are full scale, 1MSB and 1LSB at a major carry. Settling time of current-output DACs is quite fast. The major share of settling time of a voltage-output DAC is usually contributed by the settling time of the output op-amp circuit.

Figure 1-3. Setting Time



11. Power-Supply Sensitivity -The sensitivity of a converter to changes in the power-supply voltages is normally expressed in terms of percent-of-full-scale change in analog output value (of fractions of 1LSB) for a 1% dc change in the power supply. Power supply sensitivity may also expressed in relation to a specified dc shift of supply voltage. A converter may be considered "good" if the change in reading at full scale does not exceed 1/2LSB for 3% change in power supply. Even better specs are necessary for converters designed for battery operation.

12. ILE (integral Linearity Error) - Linearity error of a converter, expressed in %, ppm of full-scale range or multiples of 1LSB, is a deviation of the analog values in a plot of the measured conversion relationship from a straight line. The straight line can be either a "best straight line" determined empirically by manipulation of the gain and/or offset to equalize maximum positive and negative deviation of the actual transfer characteristics from this straight line; or it can be a straight line passing through the endpoints of the transfer characteristic endpoints of the transfer characteristic after they have been calibrated (sometimes referred to as "endpoint" linearity). Endpoint linearity error is similar to relative accuracy error. For multiplying D/A converters, the analog linearity error, at a specified digital code, is defined in the same way as for multipliers, by deviation from a "best straight line" through the plot of the analog output-input response.

13. DLE (Differential Linearity Error) - Any two adjacent digital codes should result in measured output values that are exactly 1LSB apart (2-n of full scale for an n-bit converter). Any deviation of the measured "step" from the ideal difference is called differential linearity error expressed in multiplies of 1LSB. It is an important specification because a differential linearity error greater than 1LSB can lead to non-monotonic response in a D/A converter and missed codes in an A/D converter.

14. Monotonic - A DAC is said to be monotonic if the output either increases or remains constant as the digital input increases with the result that the output will always be a single-valued function of the input. The specification "monotonic"

(over a given temperature range) is sometimes substituted for a differential nonlinearity specification since differential nonlinearity less than 1LSB is a sufficient condition for monotonic behaviour.

2. Analog-to-Digital Converter

1. ILE (Integral Linearity Error: INL) - Integral nonlinearity refers to the deviation of each individual code from a line drawn from "zero" through "full scale". The point used as "zero" occurs 1/2LSB before the first code transition. "Full scale" is defined as a level 1 1/2LSB beyond the last code transition. The deviation is measured from the center of each particular code to the true straight line.

2. DLE (Differential Linearity Error: DNL) - An ideal ADC exhibits code transitions that are exactly 1LSB apart. DNL is the deviation from this ideal value. It is often specified in terms of the resolution for which no missing codes are guaranteed.

3. Offset Error - The first transition should occur at a level 1/2LSB above "zero". Offset is defined as the deviation of the actual first code transition from that point.

4. Gain Error - The first code transition should occur for an analog value 1/2LSB above nominal negative full scale. The last transition should occur for an analog value 1 1/2LSB below the nominal positive full scale. Gain error is the deviation of the actual difference between first and last code transitions and the ideal difference between the first and last code transitions.

5. Pipeline Delay (Latency) - The number of clock cycles between conversion initiation and the associated output data being made available. New output data is provided every clock cycle.

6. Effective Number of Bits (ENOB) - This is a measure of a device's dynamic performance and may be obtained from the SNDR or from a sine wave curve test fit according to the following expression:

ENOB = SNDR - 1.76/6.02

ENOB = N-log2[RMS error (actual) / RMS error (ideal)]

7. Analog Bandwidth - The analog input frequency at which the spectral power of the fundamental frequency, as determined by FFT analysis is reduced by 3dB.

8. Aperture Delay - The delay between the sampling clock and the instant the analog input signal is sampled.

9. Aperture Jitter - The sample to sample variation in aperture delay.

10. Bit Error Rate (BER) - The number of spurious code errors produced for any given input sine wave frequency at a given clock frequency. In this case it is the number of codes occurring outside the histogram cusp for a 1/2 FS sine wave.

11. Signal to Noise Ratio - This signal to noise ratio depends on the resolution of the converter and automatically includes specifications of linearity, distortion, sampling time uncertainty, glitches, noise, and settling time. Over half the sampling frequency, this signal to noise ratio must be specified and should ideally follow the theoretical formula;

$$S/N_{max} = 6.02N + 1.76dB$$

3. Phase Locked Loop

1. Lock Time - The time it takes the PLL to lock onto the system clock. Fast or slow lock time may be controlled by the loop filter characteristics. The loop filter characteristics are controlled by varying the R and C components. (Remember that R and C define the damping-factor as well)

2. Phase Error - The phase difference between the feedback clock signal and the system signal clock.

3. Clock Jitter - The deviations in a clock's output transitions from their ideal positions define the clock jitter. Jitter is sometimes specified as an absolute value in nanoseconds. All jitter measurement are made at a specified voltage.

1) Cycle-to-Cycle Jitter: The change in a clock's output transition from its corresponding position in the previous cycle. This kind of jitter is the most difficult to measure and usually requires a time-interval analyzer

Figure 1-4. Cycle-to-Cycle Jitter



: The maximum of such values over multiple cycles (J1,J2...) is the max. cycle-to-cycle jitter.

2) Period Jitter: Period jitter measures the maximum change in a clock's output transition from its ideal position. You can use period-jitter measurements to calculate timing margins in systems.

Figure 1-5. Period Jitter



3) Long-term Jitter: Long-term jitter measures the maximum change in a clock's output transition from its ideal position over many cycles. How many cycles depends on the application and the frequency. A classic example of system affected by long-term jitter is a graphics card driving a CRT

4) Power Down Mode: PLL state in which the quiescent current is lowered to a very low level to conserve power.

5) Synthesize clock: a system clock may run at a relatively low rate compared to system components. A CPU, for example, may require an internal clock that is several times faster than the system I/O bus clock. Designers can use PLL

technology to synthesize a higher frequency on-chip clock using the system clock as a reference.

6) Deskew clock: Multiple chips on a printed circuit board or cores of different sizes within a single system on a chip experience clock skew. By using PLL or DLL technology to shift the phase of the reference clock within each chip or core, designers can minimize skew tune a system to perform up its potential.

7) Duty Ratio: the percentage of the period that the output is in a high state.

8) Output frequency range: The maximum output frequency range minus the minimum output frequency that is produced with an input signal for which the cell specifications still apply.

Customer Service

Samsung provides a full custom support for our customers need of analog cores. Samsung's worldwide sales offices and representatives give our customers a first-hand support for analog cores. And if needed, Samsung engineers are prepared to provide a fully customized total solution to satisfy our customers.

Technical Support

If our customers want to develop mixed-signal products, Samsung provides all technical support to meet customers needs. Mixed-signal design is quite different from pure logic design in terms of circuit design, techniques, layout and test methodology. Thus Samsung provides a successful technical guide and firmly support for all development steps.

Definition of Analog Core Data Sheet Types

Each product developed by Samsung will be supported by technical literature where the data sheets progress through the following levels of refinement

1. Core Preview

Describes the main features and specifications for core that is under development. Some specifications such as exact pin-outs may not be finalized at time of publication.The purpose of this document is to provide customers with advance product planning information.

2. Preliminary Datasheet

This is the first document completely describing a new core. It contains an features, application, timing diagram, theory of operation, core pin information, test guide, layout guide and AC/DC electrical information. This data sheet are based on prototype silicon performance and on worst case simulation models.The purpose of this data sheet is to provide ASIC customer with technical information sufficiently detailed to guarantee that they can safely begin active development.

3.Final Data sheet

This is an updated version of preliminary data sheet reflecting actual performance of the final silicon. Updates include tighter specifications, more min. and max. values. The purpose of this data sheet is to communicate the confirmed performance of cores which have passed qualification, been fully characterized.

1.4.2 INTERNAL MACROCELLS

Internal Macrocells are the lowest level of logic functions such as NAND, NOR and flip-flop used for logic designs. There are about 471 different types of internal macrocells. They usually come in four levels of drive strength (0.5X, 1X, 2X and 4X).

These macrocells have many levels of representations—logic symbol, logic model, timing model, transistor schematic, HSPICE netlist, physical layout, and placement and routing model.

1.4.3 COMPILED MACROCELLS

Compiled macrocells of STDM110 consist of compiled memory and compiled datapath macrocells.

1.4.3.1 Compiled Memory Macrocells

Memories in STDM110 are fully user-configurable and are provided as a compiler. Two different types of memories are available in STDM110. One is suitable for high-density application with high-performance, called STDM110-HD compiled memory. The other is suitable for low-power application, called STDM110-LP compiled memory.

In STDM110-HD compiled memory, eight types of memories are available such as single-port synchronous/asynchronous static RAM, dual-port synchronous static RAM, synchronous diffusion/metal-programmable ROM, multi-port asynchronous register file and synchronous first-in first-out memory. Synchronous memories have a fully synchronous operation at the rising-edge of clock and the duty-free cycle is available. Also, the bit-write capability is available. Asynchronous memories have a synchronous operation for a write enable signal during write mode and have an asynchronous operation for address signal during read mode. Multi-port asynchronous register file supports four kinds of configurations such as 2 port(1-read/1-write), 3 port(1-read/2-write and 2-read/1-write) and 4 port (2-read/2-write). The first-in first-out memory which is widely used in communication buffering types of applications has also fully synchronous operation at the rising- edge of clock.

On the other hand, in STDM110-LP compiled memory, five types of memories are available such as single-port synchronous/asynchronous static RAM, dual-port synchronous static RAM and synchronous diffusion/metal-programmable ROM. Synchronous memories are almost same as that of STDM110-HD except that the duty-free cycle is not available. Asynchronous memory is same as that of STDM110-HD.

To dramatically reduce the power consumption in STDM110-LP, some of low-power techniques such as a partial activation architecture in cell array and a divided word-line structure was adopted, rather than STDM110-HD.

Basically in STDM110-HD and STDM110-LP, the power-down mode which significantly reduces the power dissipated during a read or write mode is provided. Also compiled memories have a standby mode except multi-port asynchronous register file and first-in first-out memory. While in standby mode, the data stored in the memory is retained, data outputs remain stable and the power is greatly reduced because memory operation is internally blocked while the memory contents and the data outputs are unaffected.

To improve the memory performance and to reduce the power consumption, 2-bank architecture is provided except some memories such as dual-port synchronous static RAM, multi- port asynchronous register file and first-in first-out memory. In 2-bank architecture, only one bank is activated and the other bank is in standby mode.

To support various memory shapes which are determined by the floorplan of a chip design, flexible memory aspect ratios are provided. For certain specific memory configuration, all types of timing, power and area values are provided by an automatic datasheet generator.

To easily do interface to layout, the physical abstract data for Silicon Ensemble and Apollo, called phantom cell or black box, is provided. BIST(Built-In Self-Test) circuitry is currently available for most of STDM110 compiled memories. BIST circuits are designed to detect a set of fault types that impact the functionality of memory and is generated by a softmacro-based BIST generator.

The softmacro-based BIST generator generates both an individual BIST netlist for each memory and a shared BIST netlist for all memories used in a design. However, when several memories of the same or the different type area used in the design, if you generate the individual BIST netlist for each memory, there are some redundant blocks because the individual BIST netlist has same function. In this case, it would better use the shared BIST netlist to eliminate such redundancy and reduce area.

1.4.3.2 Compiled Datapath Macrocells

Compiled datapath macro cells include Adder, Barrel Shifter and Multiplier. Adder performs the adding or adding/subtracting operation on the control of a mode selection signal. Barrel Shifter makes input data shift or rotate in the left/right direction. In the shift operation, the vacant bit can be padded with zero, MSB value, or external data. Multiplier performs the 2's compliment multiplication. One pipeline stage insertion is available to get a high operating frequency.

They have two output drive strengths, which are equal to the 1X and 2X-Drive in the primitive cell library. The hard macro cells are built through the Apollo, placement and routing tool from Avant!. All the leaf cells have the same physical configuration compatible with the primitive cell library. It allows that any primitive cell can be used as a bit slice cell in the datapath module design.

We provide two kinds of engineering design services. One is to support additional compiled datapath macrocells such as ALUs, Comparators, Priority encoders, Incrementers and Decrementers, and so on. Another is to make hardwired datapath module design which provides a regular structured layout.

1.4.4 INPUT/OUTPUT CELLS

There are about seven hundreds different I/O buffers. Each I/O cell is implemented solely on the basic I/O cell architecture which forms the periphery of a chip.

A test logic is provided to enable the efficient parametric (threshold voltage) testing on input buffers including LVCMOS and TTL level converters, Schmitt trigger input buffers, clock drivers and oscillator buffers. Pull-up and pull-down resistors are optional features.

Three basic types of output buffers (non-inverting, tri-state and open drain) are available in a range of driving capabilities from 1mA to 12mA for 2.5V, 3.3V drive and from 1mA to 3mA for 5.0V tolerant drive. One or two levels of slew rate controls are provided for each buffer type (except 1mA, 2mA and 3mA buffers) to reduce output power/ground noise and signal ringing, especially in simultaneous switching outputs.

Bi-directional buffers are combinations of input buffers and output buffers (tri-state and open drain) in a single unit. The I/O structure has been fully characterized for ESD protection and latch-up resistance.

For user's convenience, STDM110 library provides 100KΩ pull-down and pull-up resistance respectively.

1.4.4.1 I/O Applications

To support mixed voltage environments, LVTTL, LVCMOS and Schmitt trigger I/O cells are available at 2.5V, 3.3V interface and 5V tolerant interface. The I/O application diagram is as follows.

Figure 1-6. I/O Applications



1.4.4.2 I/O Cell Drives Options

To provide designers with the greater flexibility, each I/O buffer can be selected among various current levels (e.g., 1mA, 2mA,..., 12mA). The choice of current-level for I/O buffers affects their propagation delay and current noise.

The slew rate control helps decrease the system noise and output signal overshoot/undershoot caused by the switching of output buffers. The output edge rate can be slowed down by selecting the high slew rate control cells.

STDM110 provides three different sets of output slew rate controls. Only one I/O slot is required for any slew rate control options.

1.4.4.3 5V Tolerant I/O Buffers

STDM110 I/O library is based on a process which has the most optimum performance in 1.8V.

In this process, voltage more than 3.6V are not allowed at the gate oxide because of a reliability problem. And a special circuit is adopted in order to make pin voltage tolerable up to 5.25V and to offer TTL interface driving up to 3mA. Obviously, this circuit is constructed not to permit more than 3.6V at the gate oxide. The external circuit diagram is as follows.

The maximum external tolerance of this buffer is 5.25V. It can be used as a 3.3V normal buffer.

Figure 1-7. 5V Tolerant I/O Buffers



1.4.4.4 PCI Buffers

PCI buffers are designed for PCI local bus application which is an industry-standard, high-performance 32bit or 64bit bus architecture. Samsung ASIC offers input, output, bi-directional PCI buffers for 33MHz and 66MHz operation. These buffers are compliant with PCI local bus specification 2.1.

1.4.4.5 USB (Universal Serial Bus) Buffers

Various kinds of peripheral equipment such as mouse, joy stick, keyboard, modem, scanner and printer improve the power of a computer. However, it is not easy to connect and use them properly in the computer.

USB specification established late in 1995 is a good solution for this problem, providing facile method of an expansion. Samsung ASIC offers full speed and low speed USB buffers that complies with Universal Serial Bus specification 1.0, 1.1.

1.4.4.6 Other Buffers

Samsung ASIC can support various kinds of buffers such as HSTL, SSTL, AGP, PECL, LVDS, and so on. For more information please contact us.

1.5 Timings

1.5.1 WIRE LENGTH LOAD

Table 1-1. shows the equivalent standard load matrix for 4-layer and 5-layer metal interconnect. The equivalent standard load values are function of gate count and fanout. These values are based on capacitive loading and are used in wire length estimates which affect propagation delay.

Table 1-1. Equivalent Standard loads for 4-layer and 5-layer Metal Interconnect

Gates Count	Fanouts										
	1	2	3	4	5	6	7	8	16	32	64
4LM											
5000	1.159	2.242	3.822	5.113	5.965	7.020	7.859	10.94	28.672	45.642	79.821
10000	1.530	2.932	5.561	7.701	8.964	10.500	12.110	15.211	29.903	47.725	83.520
50000	4.192	8.247	12.439	16.494	16.801	17.980	21.026	22.806	35.536	48.347	84.605
100000	4.596	9.327	13.925	18.523	18.889	20.241	23.582	27.031	41.002	54.253	94.944
150000	12.843	17.125	21.406	22.684	23.600	24.296	26.001	29.730	39.828	63.672	127.344
200000	13.520	18.026	22.533	23.885	24.849	25.582	27.372	31.299	41.865	66.931	133.812
300000	14.871	19.830	24.786	26.588	27.596	28.363	30.317	34.634	46.268	73.871	147.587
400000	16.225	21.631	26.852	28.693	29.845	30.718	32.868	37.479	50.016	79.707	159.207
500000	18.099	24.132	30.166	32.177	33.435	34.390	36.777	42.032	53.235	84.861	169.459
600000	19.375	25.836	32.476	34.593	35.915	36.919	39.467	45.186	54.763	87.312	174.320
800000	22.324	29.767	37.739	40.113	41.593	42.719	45.642	52.399	59.180	94.390	188.385
1000000	25.078	33.439	42.657	45.272	46.898	48.140	51.408	59.135	63.283	100.964	201.447
1500000	32.631	43.509	56.047	59.341	61.381	62.946	67.174	77.514	75.639	120.743	240.788
2000000	39.706	52.941	68.596	72.524	74.956	76.821	81.946	94.736	87.196	139.244	277.587
2500000	46.327	61.770	80.342	84.864	87.657	89.807	95.771	110.853	97.994	156.527	311.959
3000000	52.517	70.023	91.321	96.399	99.532	101.946	108.693	125.919	108.065	172.646	344.022
4000000	60.251	80.335	104.770	110.594	114.189	116.958	124.701	144.463	123.979	198.073	394.685
5000000	67.558	90.078	117.479	124.008	128.041	131.146	139.827	161.985	139.017	222.099	442.560
6000000	75.754	101.005	131.728	139.052	143.573	147.053	156.788	181.634	155.879	249.038	496.241
5LM											
5000	1.101	2.131	3.631	4.856	5.667	6.669	7.466	10.397	27.238	43.360	75.830
10000	1.454	2.786	5.283	7.317	8.515	9.976	11.505	14.451	28.408	45.339	79.344
50000	3.982	7.834	11.818	15.670	15.961	17.081	19.976	21.666	33.760	45.929	80.374
100000	4.366	8.861	13.229	17.597	17.944	19.229	22.403	25.679	38.952	51.540	90.198
150000	12.201	16.268	20.336	21.549	22.420	23.081	24.701	28.244	37.837	60.488	120.977
200000	12.843	17.125	21.406	22.691	23.606	24.304	26.004	29.734	39.771	63.584	127.122
300000	14.128	18.839	23.546	25.259	26.216	26.944	28.801	32.903	43.955	70.178	140.207
400000	15.414	20.549	25.509	27.257	28.353	29.181	31.225	35.606	47.515	75.722	151.247
500000	17.195	22.925	28.658	30.567	31.763	32.670	34.938	39.931	50.573	80.618	160.986
600000	18.406	24.543	30.852	32.862	34.119	35.073	37.494	42.926	52.025	82.947	165.605
800000	21.208	28.278	35.852	38.107	39.514	40.584	43.360	49.779	56.220	89.670	178.967
1000000	23.825	31.767	40.524	43.008	44.554	45.733	48.837	56.178	60.119	95.916	191.374
1500000	31.000	41.333	53.245	56.374	58.312	59.798	63.815	73.637	71.856	114.706	228.749
2000000	37.721	50.295	65.166	68.898	71.208	72.980	77.849	90.000	82.837	132.281	263.707
2500000	44.011	58.682	76.324	80.621	83.274	85.317	90.983	105.311	93.093	148.700	296.362
3000000	49.891	66.523	86.755	91.579	94.555	96.849	103.257	119.622	102.661	164.014	326.821
4000000	57.239	76.318	99.532	105.065	108.479	111.110	118.466	137.239	117.779	188.169	374.950
5000000	64.180	85.575	111.606	117.807	121.639	124.588	132.836	153.885	132.067	210.995	420.432
6000000	71.965	95.955	125.141	132.099	136.394	139.700	148.949	172.552	148.084	236.587	471.429
7000000	78.436	104.582	136.393	143.976	148.655	152.259	162.339	188.067	161.397	257.858	513.812
8000000	87.950	117.266	152.935	161.439	166.687	170.727	182.031	210.877	180.976	289.134	576.135

1.5.2 TIMING PARAMETERS

This section discusses issues involving timing parameters.

1.5.2.1 Transition Time

Figure 1-8. shows the definition of rise transition time (t_R) and fall transition time (t_F). Transition time is defined as the delay between the time when the input (output) signal voltage level is 10% of supply voltage (V_{DD}) and the time of the input (output) signal voltage level is 90% of V_{DD}.

Figure 1-8. Rise and Fall Transition Time



1.5.2.2 Propagation Delay

Figure 1-9. shows the definition of propagation delays. Propagation delay is defined as the delay between the time when the input signal voltage level is 50% of supply voltage (V_{DD}) and the time when the output signal voltage level is 50% of V_{DD}.

Figure 1-9. Propagation Delay



1.5.2.3 Setup / Hold Time

Figure 1-10. shows the definition of setup time and hold time. The setup timing check is defined as the minimum interval which a data signal must remain stable before active transition of a clock. Any change to the data signal within this interval results in a timing violation.
The hold timing check is defined as the minimum interval which a data signal must remain stable after active transition of a clock. Any change to the data signal within this interval results in a timing violation.

Figure 1-10. Setup and Hold Time



1.5.2.4 Recovery Time

Figure 1-11. shows the definition of recovery time. A recovery timing check measures the time between the release of an asynchronous control signal from the active state to the next active clock edge.
For example, the time between RN and the CK of FD2 cell. If the active edge of the CK occurs too soon after the release of the RN, the state of the FD2 becomes uncertain. The state can be the value set by the RN or the value clocked into the FD2 from the data input.

Figure 1-11. Recovery Time



1.5.2.5 Removal Time

Figure 1-12. shows the definition of removal time. A removal timing check measures the time between the active clock edge and the release of an asynchronous control signal from the active state.
For example, the time between RN and the CK of FD2 cell. If the release of the RN occurs too soon after the active edge of the clock, the state of the FD2 becomes uncertain. The uncertainty can be caused by the value set by the RN or the value clocked into the FD2 from the data input.

Figure 1-12. Removal Time



1.5.2.6 Minimum Pulse Width

Figure 1-13. shows the definition of minimum pulse width. The minimum pulse width timing check is the minimum allowable time for the positive (high) or negative (low) phase of each cycle.

Figure 1-13. Minimum Pulse Width



1.5.2.7 Minimum Period

Figure 1-14. shows the definition of minimum period. The minimum period timing check is the minimum allowable time for one complete cycle of the signal.

Figure 1-14. Minimum Period



1.5.3 TEMPERATURE AND SUPPLY VOLTAGE

The next figure describes propagation delay derating factors (K_T, K_V) as a function of on-chip junction temperature (T_J) and supply voltage (V_{DD}). As a result of power dissipation, the junction temperature is generally higher than the ambient temperature.

The temperature of the die inside the package (junction temperature, T_J) is calculated using chip power dissipation and the thermal resistance to the ambient temperature (θ_{JA}) of the package. Information on package thermal performance can be obtained from Samsung application engineers.

Figure 1-15. Effect of Temperature and Supply Voltage on Propagation Delay



1.5.4 BEST AND WORST CASE CONDITIONS

A circuit should be designed to operate properly within a given specification level, either commercial or industrial. It is recommended that circuits be simulated for best case, normal case, and worst case conditions at each specification level.

The following expressions also allow for the effect of process variation on circuit performance.

Best case(Worst case):

T_{BC} (T_{WC}) = K_P x K_T x K_V x T_{NOM}

where

$\boldsymbol{T}_{BC}$ = Best case propagation delay

$\boldsymbol{T}_{WC}$ = Worst case propagation delay

T_{NOM} = Normal propagation delay

($\boldsymbol{T}_J$ = 25°C, $\boldsymbol{V}_{DD}$ = 1.85V and typical process)

$\boldsymbol{K}_P$, $\boldsymbol{K}_T$, $\boldsymbol{K}_V$ = Refer toTable 1-2., Table 1-3., and Table 1-4.

1.5.5 DERATING FACTORS OF STDM110

The multipliers can be applied to nominal delay data in order to estimate the effects of supply voltage, temperature and process. Nominal data are provided for conditions of V_{DD} = 1.8V, T_J = 25°C and typical process.

The derating factors of STDM110 is as follows.

Table 1-2. STDM110 Cell Process Derating Factor (K_P)

Process Factor (K_P)	Slow	Typ	Fast
	1.252	1.0	0.809

Table 1-3. STDM110 Cell Temperature Derating Factor (K_T)

Temp. (°C)	125	85	70	25	0	–40
K_T	1.129	1.079	1.060	1.000	0.966	0.909

Table 1-4. STDM110 Cell Voltage Derating Factor (K_V)

Voltage (V)	1.65	1.80	1.95
K_V	1.113	1.000	0.914

1.6 Delay Model

The ASIC timing characteristics consist of the following components:

- Cell propagation delay from input to output transitions based on input waveform slope, fanout loads and distributed interconnection wire resistance and capacitance.
- Interconnection wire delay across the metal lines.
- Timing requirement parameters such as setup time, hold time, recovery time, skew time, minimum pulse width, etc.
- Derating factors for junction temperature, power supply voltage, and process variations.

Timing model for STDM110 focuses on how to characterize cell propagation delay time accurately. To accomplish this goal, 2-dimensional table look-up delay model has been adopted. The index variables of this table are input waveform slope and output load capacitance. See the figure below. Samsung ASIC design automation system supports an n-dimensional table model even though we adopted 2-dimensional model for our 0.25μm cell-based products.

Figure 1-16. 2-Dimensional Table Delay Model



The Table 1-5. shows an example of this model for 2-input NAND cell. The data in this table are high-to-low transition delay times from one of the two input pins to output pin. The number of points and values of the index variables can differ for each cell.

Table 1-5. Table Delay Model Example

SLOP \ CAP	0.0060	0.0260	0.0480	0.0920	0.1590	0.2480
0.0260	0.05808	0.12103	0.18966	0.32676	0.53545	0.81256
0.2730	0.09949	0.17367	0.24202	0.37902	0.58771	0.86485
0.4780	0.11632	0.20817	0.28627	0.42265	0.63065	0.90741
0.8870	0.13823	0.25166	1.35082	0.51127	0.71886	0.99418
1.5000	0.15769	0.29517	1.41346	0.60959	0.85193	1.12790

Notice that 5-by-6 table is used. Delay values between grid points and beyond this table are determined by linear interpolation and extrapolation methods. This general table delay model provides great flexibility as well as high accuracy since extensive software revisions are not required when a cell library is updated. The other timing components such as interconnection wire delay, timing requirement parameters and derating factors are characterized in a commonly-accepted way in industry.

The figure below summarizes the features of Samsung ASIC's delay model.

① 2-dimensional table delay model for output loading and input waveform slope effects is used.The slopes (t_R, t_F) and delay times (t_{PLH}, t_{PHL}) of all cell instances are calculated recursively.

② The input waveform slope of each primary input pad and the loading capacitance of each primary output pad can be assigned individually or by default.

③ Pin to pin delays of cells and interconnection wires are supported.

④ The effect of distributed interconnection wire resistance and capacitance on cell delay is analysed using the effective capacitance concept.

Figure 1-17. Features of Delay Model



1.7 Testability Design Methodology

1.7.1 SCAN DESIGN

- Multiplexed scan flip-flop that minimizes the area or delay overhead needed to implement scan design.
- Automated design rules checking, scan insertion, and test pattern generation
- High fault coverage on synchronous designs

1.7.2 BOUNDARY-SCAN

- IEEE Std 1149.1
- JTAG boundary-scan registers with primitive cells
- Boundary-Scan Description Language (BSDL) description for board testing
- Combination with internal scan design and core testing

Boundary Scan Architecture

A boundary scan architecture contains TAP (Test Access Port), TAP controller, instruction register and a group of test data registers. The instruction and test data registers are separate shift-register-based paths connected in parallel with a common serial data input and a common serial data output which are connected to TAP, TDI and TDO signals. TAP controller selects the alternative instruction and test data register paths between TDI and TDO. The schematic view of the top level design of the test logic architecture is shown in the Figure 1-18.

Figure 1-18. JTAG Test Access Port (TAP) Block Diagram



Boundary Scan Functional Block Descriptions

TAP (Test Access Port)

TAP is a general-purpose port that can provide with an access to many test support functions built into a component, including the test logic. It includes three inputs (TCK; Test Clock Signal, TMS; Test Mode Signal and TDI; Test Data Input) and one output (TDO; Test Data Output) required by the test logic. An optional fourth input (TRSTN; Test Reset) is provided for the asynchronous initialization of the test logic. The values applied at TMS and TDI pins are sampled on the rising edge of TCK, and the value placed on TDO pin changes on the falling edge of TCK.

TAP Controller

TAP controller receives TCK, interprets the signals on TMS, and generates clock and control signals for both instruction and test data registers and for other parts of the test circuitries as required.

Instruction Register/Instruction Decoder

Test instructions are shifted into and held by the instruction register. Test instructions include a selection of tests to be performed or the test data register to be accessed. A basic 3-bit instruction register and its instruction decoder are provided as macrofunctions in the library.

Test Data Registers

Data registers include a bypass register, a boundary scan register, a device identification register and other design specific registers. Only the bypass- and boundary scan registers are mandatory; the rest are optional.

Bypass register: The bypass register provides a single-bit serial connection through the circuit when none of the other test data registers is selected. It can be used to allow test data to flow through a given device to the other components in a product without affecting a normal operation.

Boundary scan register: The boundary scan register detects typical production defects in board interconnects, such as opens, shorts, etc. It also allows an access to component inputs and outputs when you test their logic or sample flow-through signals. Special boundary scan register macrocells are provided for this purpose. These special registers is discussed in the next section of next pages.

Design-specific test data register: These optional registers may be provided to allow an access to design-specific test support features in the integrated circuit, such as self-test, scan test.

Device identification register: This is an optional test data register that allows the manufacturer part number and variant of a components to be identified. The 32-bit identification register is partitioned into four fields:

Device version identifier1st field	The first four bits beginning from MSB	
Device part number	2nd field	16 bits
Manufacturer's JEDEC number	3rd field	11 bits
LSB	4th field	1 bit —tied in High

The ASIC designer is free to fill the version and part number in any manner as long as the total twenty bits are used.

Samsung's JEDEC code: 78 decimal = 1001110
Continuation field (4 bits) = 0000

Contents of device identification register:

XXXX XXXXXXXXXXXXXXX 0000 1001110 1
Users can define these two fields.



1.7.3 BIST (BUILT-IN SELF-TEST)

- Efficient test solution for compiled memory macrocells
- At speed and parallel testing of multiple memories
- Less routing overhead and test pin requirements

1.8 Maximum Fanouts

1.8.1 INTERNAL MACROCELLS

The maximum fanouts for STDM110 primitive cells are as follows. Note that these fanout limitation values are calculated when the rise and fall times of the input signal is 0.273ns. Depending on the rise and fall times, the maximum fanout limitations can be varied case by case.

In the following table the maximum fanout values for all pins of STDM110 internal macrocells are listed.

Table 1-6. Maximum Fanouts of Internal Macrocells
(When input t_R/t_F = 0.273ns, one fanout (SL) = 0.006380pF)

Cell Name	Output Pin	Maximum Fanout
ad2	Y	37
ad2d2	Y	76
ad2d4	Y	149
ad2dh	Y	16
ad3	Y	37
ad3d2	Y	74
ad3d4	Y	146
ad3dh	Y	16
ad4	Y	37
ad4d2	Y	72
ad4d4	Y	142
ad4dh	Y	16
ad5	Y	17
ad5d2	Y	35
ad5d4	Y	150
ao21	Y	17
ao211	Y	10
ao2111	Y	6
ao2111d2	Y	77
ao211d2	Y	20
ao211d2b	Y	76
ao211d4	Y	154
ao211dh	Y	5
ao21d2	Y	34
ao21d2b	Y	75
ao21d4	Y	151
ao21dh	Y	8
ao22	Y	16
ao221	Y	9
ao221d2	Y	75
ao221d4	Y	151
ao222	Y	9
ao2222	Y	5
ao2222d2	Y	75
ao2222d4	Y	151
ao222a	Y	14
ao222d2	Y	18
ao222d2a	Y	75
ao222d2b	Y	75
ao222d4	Y	151
ao222d4a	Y	151
ao22a	Y	16
ao22d2	Y	32
ao22d2a	Y	32
ao22d2b	Y	76
ao22d4	Y	150
ao22d4a	Y	150
ao22dh	Y	7
ao22dha	Y	7
ao31	Y	15
ao311	Y	9
ao3111	Y	5
ao3111d2	Y	77
ao311d2	Y	76
ao311d4	Y	151
ao31d2	Y	32
ao31d4	Y	152
ao31dh	Y	6
ao32	Y	15
ao321	Y	8
ao321d2	Y	75
ao321d4	Y	151
ao322	Y	7
ao322d2	Y	75
ao322d4	Y	151
ao32d2	Y	76
ao32d4	Y	150
ao33	Y	14
ao331	Y	7
ao331d2	Y	75
ao331d4	Y	151
ao332	Y	7
ao332d2	Y	75
ao332d4	Y	151
ao33d2	Y	74
ao33d4	Y	150
ao4111	Y	5
ao4111d2	Y	75
busholder	Y	10000
dc4	Y0	37
	Y1	37
	Y2	37
	Y3	36
dc4i	YN0	33
	YN1	33
	YN2	33
	YN3	34
dc8i	YN0	23
	YN1	23
	YN2	23
	YN3	23
	YN4	23
	YN5	23
	YN6	23
	YN7	23
dl1d2	Y	76
dl1d4	Y	154
dl2d2	Y	76
dl2d4	Y	154
dl3d2	Y	76
dl3d4	Y	154
dl4d2	Y	76
dl4d4	Y	154
dl5d2	Y	76
dl5d4	Y	154
dl10d2	Y	76

Cell Name	Output Pin	Maximum Fanout
dl10d4	Y	154
oak_duclk10	CK	381
	CKB	381
oak_duclk16	CK	382
	CKB	382
fa	S	36
	CO	36
fad2	S	74
	CO	74
fadh	S	15
	CO	15
fd1	Q	37
	QN	37
fd1d2	Q	75
	QN	75
fd1cs	Q	37
	QN	36
fd1csd2	Q	75
	QN	74
fd1q	Q	37
fd1qd2	Q	75
fd1s	Q	37
	QN	37
fd1sd2	Q	76
	QN	75
fd1sq	Q	36
fd1sqd2	Q	75
fd2	Q	37
	QN	37
fd2d2	Q	74
	QN	74
fd2cs	Q	37
	QN	36
fd2csd2	Q	76
	QN	71
fd2q	Q	37
fd2qd2	Q	75
fd2s	Q	36
	QN	37
fd2sd2	Q	74
	QN	74
fd2sq	Q	37
fd2sqd2	Q	75
fd3	Q	37
	QN	37
fd3d2	Q	75
	QN	75
fd3cs	Q	37
	QN	37
fd3csd2	Q	75
	QN	73
fd3q	Q	37
fd3qd2	Q	75
fd3s	Q	37
	QN	37
fd3sd2	Q	75
	QN	74
fd3sq	Q	37
fd3sqd2	Q	75
fd4	Q	36
	QN	37
fd4d2	Q	74
	QN	73
fd4cs	Q	35
	QN	33

Cell Name	Output Pin	Maximum Fanout
fd4csd2	Q	75
	QN	68
fd4q	Q	37
fd4qd2	Q	74
fd4s	Q	37
	QN	36
fd4sd2	Q	74
	QN	72
fd4sq	Q	36
fd4sqd2	Q	74
fd5	Q	37
	QN	36
fd5d2	Q	75
	QN	75
fd5s	Q	37
	QN	36
fd5sd2	Q	76
	QN	75
fd6	Q	37
	QN	37
fd6d2	Q	74
	QN	74
fd6s	Q	36
	QN	37
fd6sd2	Q	74
	QN	74
fd7	Q	37
	QN	37
fd7d2	Q	75
	QN	74
fd7s	Q	37
	QN	37
fd7sd2	Q	75
	QN	74
fd8	Q	37
	QN	36
fd8d2	Q	74
	QN	73
fd8s	Q	37
	QN	37
fd8sd2	Q	74
	QN	72
fds2	Q	37
	QN	36
fds2d2	Q	75
	QN	75
fds2cs	Q	37
	QN	36
fds2csd2	Q	75
	QN	74
fds2s	Q	37
	QN	37
fds2sd2	Q	75
	QN	75
fds3	Q	37
	QN	37
fds3d2	Q	75
	QN	75
fds3cs	Q	37
	QN	37
fds3csd2	Q	75
	QN	75
fds3s	Q	36
	QN	37

Cell Name	Output Pin	Maximum Fanout
fds3sd2	Q	75
	QN	75
fj1	Q	36
	QN	37
fj1d2	Q	75
	QN	75
fj1s	Q	36
	QN	37
fj1sd2	Q	75
	QN	75
fj2	Q	36
	QN	37
fj2d2	Q	74
	QN	75
fj2s	Q	36
	QN	37
fj2sd2	Q	73
	QN	74
fj4	Q	36
	QN	36
fj4d2	Q	72
	QN	75
fj4s	Q	37
	QN	36
fj4sd2	Q	73
	QN	71
ft2	Q	37
	QN	37
ft2d2	Q	73
	QN	74
ha	S	37
	CO	37
had2	S	74
	CO	74
hadh	S	16
	CO	16
iv	Y	37
ivcd11	Y	36
	YN	37
ivcd13	Y	33
	YN	114
ivcd22	Y	74
	YN	76
ivcd26	Y	67
	YN	224
ivcd44	Y	150
	YN	154
ivd2	Y	76
ivd3	Y	114
ivd4	Y	154
ivd6	Y	223
ivd8	Y	301
ivd16	Y	624
ivdh	Y	16
ivt	Y	31
ivtd2	Y	69
ivtd4	Y	145
ivtd8	Y	292
ivtd16	Y	591
ivtn	Y	31
ivtnd2	Y	69
ivtnd4	Y	145
ivtnd8	Y	292
ivtnd16	Y	592

Cell Name	Output Pin	Maximum Fanout
ld1	Q	37
	QN	36
ld1d2	Q	75
	QN	75
ld1a	Q	26
ld1d2a	Q	59
ld1q	Q	36
ld1qd2	Q	75
ld2	Q	36
	QN	37
ld2d2	Q	74
	QN	75
ld2q	Q	37
ld2qd2	Q	75
ld3	Q	37
	QN	36
ld3d2	Q	75
	QN	74
ld4	Q	37
	QN	36
ld4d2	Q	76
	QN	75
ld5	Q	37
	QN	37
ld5d2	Q	75
	QN	75
ld5q	Q	36
ld5qd2	Q	75
ld6	Q	36
	QN	37
ld6d2	Q	74
	QN	75
ld6q	Q	37
ld6qd2	Q	74
ld7	Q	37
	QN	36
ld7d2	Q	75
	QN	74
ld8	Q	37
	QN	36
ld8d2	Q	76
	QN	75
oak_ldi2	Q	36
	QN	37
oak_ldi2d2	Q	75
	QN	75
oak_ldi3	Q	37
	QN	37
oak_ldi3d2	Q	75
	QN	75
ls0	Q	33
	QN	33
ls0d2	Q	67
	QN	67
ls1	Q	16
	QN	16
ls1d2	Q	75
	QN	75
mx2	Y	37
mx2d2	Y	74
mx2d4	Y	144
mx2dh	Y	16
mx2i	YN	16
mx2ia	YN	16
mx2id2	YN	75

Cell Name	Output Pin	Maximum Fanout
mx2id2a	YN	74
mx2id4	YN	151
mx2id4a	YN	150
mx2idh	YN	7
mx2idha	YN	7
mx2ix4	YN0	16
	YN1	16
	YN2	16
	YN3	16
mx2x4	Y0	37
	Y1	37
	Y2	37
	Y3	37
mx3i	YN	36
mx3id2	YN	74
mx3id4	YN	150
mx4	Y	36
mx4d2	Y	71
mx4d4	Y	131
mx8	Y	35
mx8d2	Y	68
mx8d4	Y	121
nd2	Y	35
nd2d2	Y	71
nd2d4	Y	141
nd2dh	Y	15
nd3	Y	23
nd3d2	Y	46
nd3d4	Y	93
nd3dh	Y	10
nd4	Y	17
nd4d2	Y	34
nd4d2b	Y	74
nd4d4	Y	150
nd4dh	Y	7
nd5	Y	36
nd5d2	Y	74
nd5d4	Y	152
nd6	Y	37
nd6d2	Y	75
nd6d4	Y	151
nd8	Y	36
nd8d2	Y	75
nd8d4	Y	151
nid	Y	37
oak_nid10p	Y	2607
nid16	Y	605
nid2	Y	76
oak_nid20p	Y	5185
nid3	Y	112
nid4	Y	151
nid6	Y	223
nid8	Y	297
nidh	Y	16
nit	Y	31
nitd16	Y	591
nitd2	Y	69
nitd4	Y	144
nitd8	Y	292
nitn	Y	31
nitnd16	Y	591
nitnd2	Y	69
nitnd4	Y	144
nitnd8	Y	292
nr2	Y	19

Cell Name	Output Pin	Maximum Fanout
nr2a	Y	36
nr2d2	Y	36
nr2d2b	Y	75
nr2d4	Y	153
nr2dh	Y	8
nr3	Y	11
nr3a	Y	22
nr3d2	Y	22
nr3d2b	Y	76
nr3d4	Y	153
nr3dh	Y	6
nr4	Y	37
nr4d2	Y	76
nr4d4	Y	153
nr4dh	Y	16
nr5	Y	37
nr5d2	Y	76
nr5d4	Y	153
nr6	Y	37
nr6d2	Y	76
nr6d4	Y	153
nr8	Y	37
nr8d2	Y	74
nr8d4	Y	147
oa21	Y	17
oa211	Y	16
oa2111	Y	15
oa2111d2	Y	74
oa211d2	Y	33
oa211d2b	Y	74
oa211d4	Y	151
oa211dh	Y	7
oa21d2	Y	35
oa21d2b	Y	74
oa21d4	Y	150
oa21dh	Y	7
oa22	Y	16
oa221	Y	13
oa221d2	Y	74
oa221d4	Y	150
oa222	Y	11
oa2222	Y	7
oa2222d2	Y	75
oa2222d4	Y	151
oa222d2	Y	22
oa222d2b	Y	75
oa222d4	Y	152
oa22a	Y	17
oa22d2	Y	32
oa22d2a	Y	35
oa22d2b	Y	76
oa22d4	Y	151
oa22d4a	Y	151
oa22dh	Y	8
oa22dha	Y	7
oa31	Y	10
oa311	Y	10
oa3111	Y	8
oa3111d2	Y	74
oa311d2	Y	74
oa311d4	Y	150
oa31d2	Y	20
oa31d4	Y	150
oa31dh	Y	5
oa32	Y	9

Cell Name	Output Pin	Maximum Fanout
oa321	Y	8
oa321d2	Y	75
oa321d4	Y	151
oa322	Y	6
oa322d2	Y	75
oa322d4	Y	151
oa32d2	Y	75
oa32d4	Y	151
oa33	Y	8
oa331	Y	7
oa331d2	Y	75
oa331d4	Y	150
oa332	Y	4
oa332d2	Y	75
oa332d4	Y	151
oa33d2	Y	75
oa33d4	Y	152
oa4111	Y	5
oa4111d2	Y	74
or2	Y	36
or2d2	Y	74
or2d4	Y	150
or2dh	Y	16
or3	Y	36
or3d2	Y	76
or3d4	Y	153
or3dh	Y	16
or4	Y	33
or4d2	Y	66
or4d4	Y	150
or4dh	Y	16
or5	Y	33
or5d2	Y	65
or5d4	Y	150
scg1	Y	22
scg1d2	Y	46
scg2	Y	36
scg2d2	Y	74
scg3	Y	23
scg3d2	Y	46
scg4	Y	34
scg4d2	Y	68
scg5	Y	36
scg5d2	Y	72
scg6	Y	36
scg6d2	Y	74
scg7	Y	33
scg7d2	Y	67
scg8	Y	36
scg8d2	Y	74
scg9	Y	37
scg9d2	Y	74
scg10	Y	36
scg10d2	Y	73
scg11	Y	11
scg11d2	Y	22
scg12	Y	17
scg12d2	Y	35
scg13	Y	33
scg13d2	Y	66
scg14	Y	33
scg14d2	Y	67
scg15	Y	23
scg15d2	Y	46
scg16	Y	17
scg16d2	Y	34
scg17	Y	34
scg17d2	Y	69
scg18	Y	22
scg18d2	Y	45
scg19	Y	17
scg19d2	Y	33
scg20	Y	18
scg20d2	Y	36
scg21	Y	11
scg21d2	Y	22
scg22	Y	16
scg22d2	Y	34
scg23	S	36
	CO	36
scg23d2	S	72
	CO	72
xn2	Y	37
xn2d2	Y	74
xn2d4	Y	146
xn3	Y	36
xn3d2	Y	71
xn3d4	Y	130
xo2	Y	37
xo2d2	Y	74
xo2d4	Y	146
xo3	Y	36
xo3d2	Y	71
xo3d4	Y	130

1.8.2 I/O CELLS

The maximum fanouts for I/O cells are as follows.

Table 1-7. Maximum Fanouts of I/O Cells
(t_R/t_F = 0.273ns, one fanout (SL) = 0.00638pF)

Cell Name	Output Pin	Maximum Fanout
phic	Y	162
phicd	Y	162
phicu	Y	162
phis	Y	162
phisd	Y	162
phisu	Y	162
phit	Y	162
phitd	Y	162
phitu	Y	162
phsosck1	YN	157
phsosck2	YN	121
phsoscm1	YN	121
phsoscm2	YN	121
ph2sosck1	YN	61
ph2sosck2	YN	142
ph2soscm1	YN	145
ph2soscm2	YN	257
pic	Y	161
pic_abb	Y	161
picc_abb	Y	164
picd	Y	161
picen_abb	Y	161
picu	Y	161
pis	Y	161
pisd	Y	161
pisu	Y	161
ptic	Y	162
pticd	Y	162
pticu	Y	162
ptis	Y	161
ptisd	Y	161
ptisu	Y	161
ptit	Y	162
ptitd	Y	162
ptitu	Y	162

1.8.3 CK CELL MAX FANOUT

STDM110 maximum fanout for CK cells

<Condition>

- VDD = 1.8V
- Fanout = 0.00338pF (= input cap for CK pin of FD1)
- Standard Load (SL) = 0.006380pF
- Input slope = 0.273ns
- Max output transition time (mott) =1.5ns
- Maximum frequency ≤ 200MHz
- Net length (μm/fanout): branch net length for each fanout except trunk

Table 1-8. Maximum Fanout for CK Cells

Trunk width (μm)	8				In case that interconnection is not considered
Net length (μm/fanout)	20		200		
Trunk length (μm)	5000	10000	5000	10000	
ck2	272	106	55	21	585
ck4	597	399	122	81	1060
ck6	890	640	181	130	1519
ck8	1247	904	254	184	2121

Table 1-9. Maximum Fanout for NID Cells

Trunk width (μm)	0.44		8		In case that interconnection is not considered
Net length (μm/fanout)	20		200		
Trunk length (μm)	5000	10000	5000	10000	
nid	–	–	–	–	37
nid2	–	–	–	–	76
nid3	–	–	–	–	112
nid4	15	–	–	–	151
nid6	47	–	3	–	223
nid8	72	–	14	–	297
nid16	132	–	56	22	605

For high fanout nets including clock net, Samsung strongly recommends using clock tree synthesis.

1.9 Package Capability By Lead Count

■ In-house ❑ Sub-contractor

LQFP												
Package	Pitch	Lead Inductance	Lead Count										
			32	48	64	80	100	128	144	160	176	208	256
0707 mm	0.8		■										
	0.5	< 3nH		■									
1010 mm	0.5	< 5nH			■								
1212 mm	0.5	< 5nH				■							
1420 mm	0.5	< 12nH						■					
1414 mm	0.8	< 6nH			■								
	0.5	< 6nH					■						
	0.4	v						■					
2020 mm	0.4								■				
2024 mm	0.5									■	■		
2828 mm	0.5	< 17nH										■	
	0.4	< 17nH											■
TQFP													
1212 mm	0.5	< 5nH				■							
1414 mm	0.5	< 5nH					■						
1420 mm	0.065	< 10nH					■						

PQFP (PQ2 Thermally Enhanced)									
Package	Pitch	Lead Count							
		100	120	128	144	160	208	240	304
1420 mm	0.65	❑							
	0.5			❑					
2828 mm	0.8		❑	❑					
	0.65				❑	❑			
	0.5						❑		
3232 mm	0.5							❑	
4040 mm	0.5								❑
QFP (with Heat Spreader)									
1420 mm	0.65	■							
	0.5								
2828 mm	0.8		❑	■					
	0.65				❑	❑			
	0.5						❑		
3232 mm	0.5							❑	
4040 mm	0.5								❑

■ In-house ❑ Sub-contractor

PLCC									
Package	**Pitch**	**Lead Inductance**	**Lead Count**						
			18	28	32	44	52	68	84
7.37 x 12.35 mm	1.27		■						
11.53 x 11.53 mm				■					
11.44 x 13.98 mm					■				
16.61 x 16.61 mm		< 5nH				■			
19.10 x 19.10 mm							■		
24.23 x 24.23 mm								■	
29.31 x 29.31 mm		< 13nH							■

SOP								
Package	**Pitch**	**Lead Count**						
		32	48	64(56)	68	69	100	256
8.34 x 20.30 mm	1.27	■						
TSOP1								
1014 mm	0.4		■					
PLCC								
24.33 x 24.23mm	1.27				■			
QFP								
1420 mm	0.65						■	
FBGA								
0909 mm	0.75			■				
0911 mm	0.8					■		
1717 mm	1.00							■

SBGA									
Package	**Pitch**	**Lead Inductance**		**Lead Count**					
		Lp/g	**Lsig**	256	304	352	540	648	696
2727 mm	1.27	< 3nH	< 7nH	❑					
3131 mm		< 3nH	< 8nH		❑				
3535 mm		< 3nH	< 8nH			❑			
42.5 x 47.5 mm		< 3nH	<9nH				❑		
4545 mm		< 3nH	<9nH					❑	
47.5 x 47.5 mm									❑

Package Parameter Guide for PBGAs and FBGAs

Lead Inductance							
Package Type	**Stack-Up (layer)**	**PCB Size (mm x mm)**	**L_p/g (nH)**	**L_wire (nH)**	**L_total (nH)**	**T (mm)**	**L_sig (nH)**
PBGA	2L	23 x 23	< 3.5	1.5	< 4.5	5	< 7
	2L	27 x 27	< 4	1.5	< 5.5	6	< 7.5
	2L	31 x 31	< 4.1	1.5	< 5.6	7	< 8.5
	2L	35 x 35	< 4.5	1.5	< 6	8	< 10
	4L	23 x 23	< 1.3	1.5	< 2.8	5	< 3.5
	4L	27 x 27	< 1.5	1.5	< 3	6	< 4
	4L	31 x 31	< 1.6	1.5	< 3.1	7	< 4.5
	4L	35 x 35	< 1.7	1.5	< 3.2	8	< 5.5
FBGA	2L	06 x 06	< 2	1.5	< 3.5	2	< 2.5
	2L	08 x 08	< 2	1.5	< 3.5	2	< 3.5
	2L	09 x 09	< 2	1.5	< 3.5	2	< 4.5
	2L	10 x 10	< 2	1.5	< 3.5	2	< 4.5
	2L	12 x 12	< 2	1.5	< 3.5	2	< 5
	2L	13 x 13	< 2	1.5	< 3.5	2	< 6
	2L	14 x 14	< 2	1.5	< 3.5	2	< 6
	2L	16 x 16	< 2	1.5	< 3.5	2	< 7
	2L	17 x 17	< 2	1.5	< 3.5	2	< 8
	2L	18 x 18	< 2	1.5	< 3.5	2	< 8

NOTES: Condition to use above package parameter guide;

1. Above data are estimated calculations with below assumptions.
2. Center balls are all ground balls for PBGA ball map design.
3. For a ball map design, the power/ground ball pair should be arranged next to each other and located on the center closed inside row and column.
4. Distance between power/ground bonding pad and ball must be less than listed above T[mm] column distance.
5. The bonding wire length between power/ground ball and PCB bonding pad should be less than 2mm.
6. L_total = L_p/g + L_wire; L_p/g: Total inductance of power/ground pad L_sig: Signal line inductance.
7. Contact IPT development P/T for ball map design request form in special case, other than above 1) ~ 6) notes. Special guide will be provided.

1.10 Power Dissipation

1.10.1 ESTIMATION OF POWER DISSIPATION IN CMOS CIRCUIT

CMOS circuits have been traditionally considered to consume low power since they draw very small amount of current in a steady state. However, the recent revolution in a CMOS technology that allows very high gate density has changed the way the power dissipation should be understood. The power dissipation in a CMOS circuit is affected by various factors such as the number of gates, the switching frequency, the loading on the output of a gate, and so on.

Power dissipation is important when designers decide the amount of necessary power supply current for the device to operate in safety. Propagation delays and reliability of the device also depend on power dissipation that determines the temperature at which the die operates. To obtain high speed and reliability, designers must estimate power dissipation of the device accurately and determine the appropriate environments including the package and system cooling methods.

This section describes the concepts of two types of power dissipation (static and dynamic) in a CMOS circuit, the method of calculating those in the SEC STD110 library.

1.10.2 STATIC (DC) POWER DISSIPATION

There are two types of static or DC current contributing to the total static power dissipation in CMOS circuits.

One is the leakage current of the gates resulted by a reverse bias between a well and a substrate region. There is no DC current path from power to ground in a CMOS because one of the transistor pair is always off, therefore, no static current except the leakage current flows through the internal gates of the device. The amount of this leakage current is, however, in the range of tens of nano amperes, which is negligible.

The other is DC current that flows through the input and output buffers when the circuit is interfaced with other devices, especially TTL. The current of pull-up/pull-down transistor in the input buffers is about 33μA (at 3.3V) and 25uA (at 2.5V) typically, which is also negligible. Therefore, only DC current that the output buffers source or sink has to be counted to estimate the total static power dissipation.

DC power dissipation of output and bi-directional buffers is determined by the following formula:

$$P_{DC_OUTPUT}\,[mW] = \left(\sum_{k=1}^{n} (V_{OL(k)} \times I_{OL(k)} \times t_{L(k)}) + \sum_{k=1}^{n} ((V_{DD} - V_{OH(k)}) \times I_{OH(k)} \times t_{H(k)}) \right) / T$$

$$P_{DC_BI}\,[mW] = \left(\sum_{k=1}^{n} (V_{OL(k)} \times I_{OL(k)} \times t_{L(k)}) + \sum_{k=1}^{n} ((V_{DD} - V_{OH(k)}) \times I_{OH(k)} \times t_{H(k)}) \right) \times S_{out} / T$$

where,

n = Number of output and bidirectional buffers

T = Total operation time in output mode

t_H = The sum of logic high state time

t_L = The sum of logic low state time

$t_L + t_H = T$ (Supposed that all output and bidirectional buffers have just logic high or low state)

Sout is the output mode ratio of bidirectional buffers (typically 0.5)

1.10.3 DYNAMIC (AC) POWER DISSIPATION

When a CMOS gate changes its state, it draws switching current as a result of charging or discharging a load capacitance, C_L. The energy associated with the switching current for a node capacitance, C_L, is

$$C_L \times V_{DD^2}$$

where V_{DD} is the power supply voltage.

In addition to the power dissipated by the load capacitance, CMOS circuits consume power due to the short-circuit current flowing through a temporary V_{DD}-to-ground path during switching.

The dynamic power dissipation for an entire chip is much more complicated to estimate since it depends on the degree of switching activity of the circuit. Samsung has found that the degree of switching activity is 10% on the average and recommends this number to be used in estimating the total dynamic power dissipation.

1.10.4 POWER DISSIPATION IN STDM110

This section describes the equations on how to estimate the power dissipation in STDM110. As explained in the previous section, the total power dissipation (P_{TOTAL}) consists of static power dissipation (P_{DC}) and dynamic power dissipation (P_{AC}).

$$P_{TOTAL} = P_{AC} + P_{DC}$$

P_{DC} is negligible in case of CMOS logic.

The dynamic power dissipation is caused by three components: input buffers (P_{AC_INPUT}), output buffers (P_{AC_OUTPUT}), bidirectional buffers (P_{AC_BI}), and internal cells ($P_{AC_INTERNAL}$).

$$P_{AC} = P_{AC_INPUT} + P_{AC_OUTPUT} + P_{AC_BI} + P_{AC_INTERNAL}$$

Each term mentioned above is characterized by the following equations:

$$P_{AC_INPUT}\,[mW] = 2.5\times \sum_{j}^{N_2.5V_input}\left(I_{j_eq_p}\times\frac{F_j}{100}\times S_j\right) + 3.3\times \sum_{k}^{N_3.3V_input}\left(I_{k_eq_p}\times\frac{F_k}{100}\times S_k\right) + 6.25\times \sum_{i}^{N_total_input}(0.001\times S_i\times F_i\times C_{i_inload})$$

$$P_{AC_OUTPUT}\,[mW] = 2.5\times \sum_{i}^{N_2.5V_output}\left(I_{i_eq_p}\times\frac{F_i}{100}\times S_i\right) + 3.3\times \sum_{j}^{N_3.3V_output}\left(I_{j_eq_p}\times\frac{F_j}{100}\times S_j\right) + 6.25\times \sum_{i}^{N_2.5V_output}(0.001\times S_i\times F_i\times C_{i_outload}) + 10.89\times \sum_{j}^{N_3.3V_output}(0.001\times S_j\times F_j\times C_{j_outload})$$

$$P_{AC_BI}\,[mW] = P_{AC_BI_INPUT}\times(1-S_{out}) + P_{AC_BI_OUTPUT}\times S_{out}$$

$$P_{AC_BI_INPUT}\,[mW] = 2.5\times \sum_{j}^{N_2.5V_bi}\left(I_{j_eq_p}\times\frac{F_j}{100}\times S_j\right) + 3.3\times \sum_{k}^{N_3.3V_bi}\left(I_{k_eq_p}\times\frac{F_k}{100}\times S_k\right) + 6.25\times \sum_{i}^{N_total_bi}(0.001\times S_i\times F_i\times C_{i_inload})$$

$$P_{AC_BI_OUTPUT}\,[mW] = 2.5\times \sum_{i}^{N_2.5V_bi}\left(I_{i_eq_p}\times\frac{F_i}{100}\times S_i\right) + 3.3\times \sum_{j}^{N_3.3V_bi}\left(I_{j_eq_p}\times\frac{F_j}{100}\times S_j\right) + 6.25\times \sum_{i}^{N_2.5V_bi}(0.001\times S_i\times F_i\times C_{i_outload}) + 10.89\times \sum_{j}^{N_3.3V_bi}(0.001\times S_i\times F_i\times C_{i_outload})$$

$$P_{AC_INTERNAL}\,[mW] = 0.001\times(0.1176\times S + 0.0093)\times G\times F + \sum_{j}^{N_macro}(0.001\times P_i\times F_i)$$

where,

N_2.5V_input is the number of 2.5V interface input buffers used
N_3.3V input is the number of 3.3V interface input buffers used,
N_total_input = N_2.5V_input + N_3.3V input
N_2.5V_output is the number of 2.5V interface output buffers used,
N_3.3V_output is the number of 3.3V interface output buffers used,
N_2.5V_bi is the number of 2.5V interface bi-directional buffers used,
N_3.3V_bi is the number of 3.3V interface bi-directional buffer used,
N_macro is the number of macro cells used,
G is the size of the design in gate count,
F is the operating frequency in MHz,
S is the estimated degree of switching activity (typically 0.1 for internal and 0.5 for I/O),
Sout is the output mode ratio of bi-directional buffers (typically 0.5),
C is the load capacitance in pF.
P is the characterized power for the i-th hard macro block (µW/MHz)

1.10.5 TEMPERATURE AND POWER DISSIPATION

The total power dissipation, P_{TOTAL} can be used to find out the device temperature by the following equation:

$$\theta_{JA} = (T_J - T_A) / P_{TOTAL}$$

where,

θ_{JA} is the thermal impedance,
T_J is the junction temperature of the device,
T_A is the ambient temperature.

Thermal impedances of the Samsung packages are given in the following table. The junction temperature, obtained by multiplying P_{TOTAL} by the appropriate θ_{JA} and adding T_A, determines the derating factor for the propagation delays and also indicates the reliability measures. Hence, designers can achieve the desired derating factor and reliability targets by choosing appropriate packages and system cooling methods.

Table 1-10. Thermal Impedances of Samsung Plastic Packages

	SOP/TSOP								
Pin Number	**20**	**24**	**28**	**32**	**44**	**50**	**54**	**62**	**66**
θ_{JA}[°C/W]	63	58	41-44	46-56	44-71	39-59	34-56	27-33	34-46

	QFP									
Pin Number	**44**	**48**	**80**	**100**	**120**	**128**	**160**	**208**	**240**	**256**
θ_{JA}[°C/W]	51-62	43-56	43-74	27-61	33-47	43-51	29-51	22-43	28-47	29-42

	TQFP/LQFP							
Pin Number	**32**	**64**	**100**	**144**	**160**	**176**	**208**	**256**
θ_{JA}[°C/W]	68-70	47	37-70	38	35-62	31-34	37-56	30-42

	PBGA			
Pin Number	**272**	**388**	**356 (TEPBGA)**	**452 (TEPBGA)**
θ_{JA}[°C/W]	19-22	16-19	16	14

	SBGA				
Pin Number	**256**	**304**	**352**	**432**	**600**
θ_{JA}[°C/W]	14.1	13.1	11.7	10.2	8.3

1.11 V_{DD}/V_{SS} Rules And Guidelines

There are three kinds of VDD and VSS in STDM110, providing power to internal and I/O area.

- Core logic
  – VDD1I, VSS1I
- Pre-driver (I/O area)
  – VDD2P, VDD3P, VSS2P, VSS3P
- Output-drive (I/O area)
  – VDD2O, VDD3O, VSS2O, VSS3O

The number of VDD and VSS pads required for a specific design depends on the following factors:

- Number of input and output buffers
- Number of simultaneous switching outputs
- Number of used gates and simultaneous switching gates
- Operating frequency

1.11.1 BASIC PLACEMENT GUIDELINES

The purpose of these guidelines is to minimize IR drop and noise for reliable device operations.

- Core logic and pre-driver V_{DD}/V_{SS} pads should be evenly distributed on all sides of the chip.
- If you have core block demanding high power (compiled memory, analog), extra power pads should be placed on that side.
- Power pads for SSO group should be evenly distributed in the SSO group.
- Do not place the quiet signal (analog, reference) or analog power (VDDA/VSSA) or bi-directional buffer next to a SSO group.
- The opposite types of power pads (V_{DD}/V_{SS}) should be placed as close as possible.
- If it is possible, do not place power pads (V_{DD}/V_{SS}) at the corner of the chip.

1.11.2 VDD1I/VSS1I ALLOCATION GUIDELINES

The purpose of these guidelines is to ensure that the minimum number of core logic power pad pairs meeting the electromigration current limit are used. The number of VDD1I/VSS1I pads required for a specific design is determined by the function of the operating frequency of a chip.

- VDD1I bus width and the number of pads are equal to those of VSS1I
- VDD1I/VSS1I buses and pads should be distributed evenly in the core and on each side of the chip.
- The total number of core logic VDD1I pads is equal to that of VSS1I pads.

The number of VDD1I/VSS1I pad pairs required for a design can be calculated from the following expression:
The number of VDD1I/VSS1I pad pairs =

$$\left\| \left[0.001 \times (0.0470 \times S + 0.0037) \times G \times F + \sum_{i}^{N_macro} (Pi \times Fi) \right] / I_{em} \right\| round-up$$

where,

G = The core (excluding hard macro blocks) size in the gate counts
S = The switching ratio (typically = 0.1)
F = Operating frequency (MHz)
Pi = Characterized current for the i-th hard macro block (mA/MHz)
Fi = Operating frequency for the i-th hard macro block (MHz)
I_{em} = Current limit per VDD/VSS pad pairs based on ElectroMigration rule (80mA)

For reliable device operation and minimize IR voltage drop, minimum number of VDD1I/VSS1I power pad pairs is 4.

Extra power may be needed for the demanding high power macro blocks (SRAM, analog block...).

1.11.3 VDD2P/VSS2P (VDD3P/VSS3P) ALLOCATION GUIDELINES.

These guidelines ensure that an adequate input threshold voltage margin is maintained during a switching.
The number of VDD2P/VSS2P (VDD3P/VSS3P) pads required for a design can be calculated from the following expression:

$$Number_ of_VDD2P/VSS2P(VDD3P/VSS3P)\ pairs = \left\| \frac{I_{eq_p}}{I_{em}} \right\| round-up$$

In above expression,
I_{eq_p} = ∑(Average current of input/output buffers and bi-direction pre-drivers at maximum operational I/O frequency) [mA] (Refer Table 1-11)

$$I_{eq_p} = \sum_{i}^{N_input} \left(I_{eq_p_in} \times \frac{F_i}{100} \right) + \sum_{j}^{N_output} \left(I_{j_eq_p_out} \times \frac{F_j}{100} \right) + \sum_{k}^{N_bi} \left[\left(I_{k_eq_p_in} \times \frac{F_k}{100} \right) (1 - S_{out}) + \left(I_{k_eq_p_out} \times \frac{F_k}{100} \right) \times S_{out} \right]$$

where

N_input is the number of input buffers used,
N_output is the number of output buffers used,
N_bi is the number of bi-directional buffers used,
F is the operating frequency in MHz,
S_{out} is the output mode ratio of bi-directional buffers (typically 0.5),
I_{em} = Current limit per VDD/VSS pad pairs based on electromigration rule. (80mA)

Table 1-11. 2.5V Interface

Input Buffer Type		**CMOS**			**CMOS Schmitt**		
Ieq_p (mA)		0.35			0.36		
Output Pre-Driver Type		**Driver**			**Tristate**		
		B1–4	**B6–8**	**B10–12**	**T1–4**	**T6–8**	**T10–12**
Ieq_p (mA)	Normal	0.14	0.27	0.41	0.24	0.36	0.53
	Slew rate	0.14	0.25	0.35	0.25	0.35	0.45

Table 1-12. 3.3V Interface

Input Buffer Type			CMOS		TTL	Schmitt Trigger		
Ieq_p (mA)	Normal		0.52		0.54	0.54		
	Tolerant		0.60		0.60	0.51		
Output Pre-driver Type			**CMOS Driver**			**Tristate**		
			B1–4	**B6–8**	**B10–12**	**T1–4**	**T6–8**	**T10–12**
Ieq_p (mA)	Normal	Normal	0.25	0.46	0.55	0.34	0.51	0.60
		Slew rate	0.28	0.37	0.46	0.36	0.45	0.55
	Tolerant		-	-	-	(T1,2,3) 0.50	-	-

For reliable device operation and minimum IR voltage drop, at least 4 pairs of VDD2P/VSS2P (VDD3P/VSS3P) power pads are needed.

1.11.4 VDD2O/VSS2O (VDD3O/VSS3O) ALLOCATION GUIDE

SSO (Simultaneous Switching Output) current induced in power and ground inductance can cause system failure because of voltage fluctuations. For the calculation of output drive power pad numbers, we consider the SSO noise as well as the current limit based on electromigration. We may define the SSO as outputs switching simultaneously in 1ns windows, such as bus type buffers.

NOTE: In case of heavy load, high frequency and low package inductance, the number of power pads for SSO block could be determined by electromigration rule rather than limit of SSO noise. So the number of power pads for SSO block should be determined as the worse one of the power pad number under the limit of SSO noise and that under the limit of electromigration rule.

1) Number of power pads for SSO block

- Number of power pads for SSO block under the limit of SSO noise

- Calculating the number of power pad for each SSO group from the following expressions:

$$NVDDO_{each_SSO} = \frac{number_of_SSO}{NBvdd} \times L_{pg} \times \frac{1}{D_{SSO_mode}}$$

$$NVSSO_{each_SSO} = \frac{number_of_SSO}{NBvss} \times L_{pg} \times \frac{1}{D_{SSO_mode}}$$

In above formula,

$NVDDO_{each_sso}$ = Number of VDD2O (VDD3O) pad required for each SSO group

$NVSSO_{each_sso}$ = Number of VSS2O (VSS3O) pad required for each SSO group

NBvdd =Number of buffers per VDD2O (VDD3O) power pad with 1nH lead inductance

NBvss = Number of buffers per VSS2O (VSS3O) ground pas with 1nH lead inductance

L_{pg} = Package lead frame inductance
(refer to 1.9 package capability by lead count)

$D_{sso_mode} = D_{L_mode} \times D_{P_mode} \times D_{V_mode} \times D_{T_mode} \times D_{C_mode}$ (Refer to Table 1-13. and Table 1-14.)

D_{L_mode} = Lead inductance derating factor
D_{P_mode} = Process derating factor
D_{V_mode} = Voltage derating factor
D_{T_mode} = Temperature derating factor
D_{C_mode} = Cload derating factor (*mode is either vdd or vss.)

Table 1-13. Derating Equation (external 2.5V interface)

Item	Mode	Equation	Range
Package Lead	D_{L_vdd}	0.0417 x Lpg + 0.9375 0.0417 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH ≤ Lpg ≤ 15nH
	D_{L_vss}	0.0417 x Lpg + 0.9375 0.0417 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH < Lpg ≤ 15nH
Process	D_{P_vdd}	1.0000 1.2549 1.7255	best typical worst
	D_{P_vss}	1.0000 1.2549 1.7451	best typical worst
Voltage	D_{V_vdd}	– 0.8824 x voltage + 3.3235 – 0.5882 x voltage + 2.5882	2.3 ≤ voltage ≤ 2.5 2.5 < voltage ≤ 2.7
	D_{V_vss}	– 0.8824 x voltage + 3.3235 – 0.5882 x voltage + 2.5882	2.3 ≤ voltage ≤ 2.5 2.5 < voltage ≤ 2.7
Temperature	D_{T_vdd}	0.0024 x temperature + 1.0000 0.0032 x temperature + 0.9786	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
	D_{T_vss}	0.0031 x temperature + 1.0000 0.0029 x temperature + 1.0071	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
Cload	D_{C_vdd}	0.0347 x Cload + 0.6525 0.0286 x Cload + 0.8369	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF
	D_{C_vss}	0.0354 x Cload + 0.6456 0.0285 x Cload + 0.8544	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF

Table 1-14. Derating Equation (external 3.3V interface)

Item	Mode	Equation	Range
Package Lead	D_{L_vdd}	0.0462 x Lpg + 1.1538 0.0231 x Lpg + 1.3846	3nH ≤ Lpg ≤ 10nH 10nH ≤ Lpg ≤ 15nH
	D_{L_vss}	0.0469 x Lpg + 0.7813 0.0313 x Lpg + 0.9375	3nH ≤ Lpg ≤ 10nH 10nH < Lpg ≤ 15nH
Process	D_{P_vdd}	1.0000 1.2537 2.2985	best typical worst
	D_{P_vss}	1.0000 1.1563 1.4063	best typical worst
Voltage	D_{V_vdd}	– 1.2936 x voltage + 5.4328 – 0.4478 x voltage + 2.6119	3.0 ≤ voltage ≤ 3.3 3.3 < voltage ≤ 3.6
	D_{V_vss}	– 0.4166 x voltage + 2.5000 – 0.4166 x voltage + 2.5000	3.0 ≤ voltage ≤ 3.3 3.3 < voltage ≤ 3.6
Temperature	D_{T_vdd}	0.0036 x temperature + 1.0000 0.0041 x temperature + 0.9878	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
	D_{T_vss}	0.0038 x temperature + 1.0000 0.0028 x temperature + 1.0227	-40 ≤ temperature ≤ 25 25 < temperature ≤ 125
Cload	D_{C_vdd}	0.0338 x Cload + 0.6618 0.0554 x Cload + 0.0146	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF
	D_{C_vss}	0.0444 x Cload + 0.5556 0.0370 x Cload + 0.7778	10pF ≤ Cload ≤ 30pF 30pF < Cload ≤ 50pF

Table 1-15. NBvdd/NBvss Parameter (Process = best, Volt =2.7V/3.6V Temp. = 0˚C, Llead = 1nH)

Buffer Type	Voltage Type	Normal		Slew-Rate Medium (sm)		Slew-Rate High (sh)	
		NBvdd	NBvss	NBvdd	NBvss	NBvdd	NBvss
pob1 (pot1)	2.5V Interface	176	178	–	–	–	–
pob2 (pot2)		140	142	–	–	–	–
pob4 (pot4)		102	102	160	160	–	–
pob6 (pot6)		84	84	142	142	–	–
pob8 (pot8)		72	72	116	116	–	–
pob8 (pot10)							
pob12 (pot12)		60	60	96	96	236	236
phob1 (phot1)	3.3V Interface	382	166	–	–	–	–
phob2 (phot2)		276	104	–	–	–	–
phob4 (phot4)		134	64	168	104	–	–
phob6 (phot6)		108	44	132	90	–	–
phob8 (phot8)		98	38	118	86	–	–
phob8 (phot10)							
phob12 (phot12)		86	32	92	62	130	124
ptot1	5V Tolerant	434	376	–			
ptot2		272	180				
ptot3		203	116				

NOTE: pob1 means 1mA output driver cell, and pob12 means 12mA output driver cell.

- Calculating the number of required power pad for total SSO from the following expression:

  NVDDO1sso = ∑NVDDOeach_sso
  NVSSO1sso = ∑NVSSOeach_sso

  In the above formula,

  NVDDOsso = Number of VDD2O (VDD3O) pad per total SSO buffers
  NVSSOsso = Number of VSS2O (VSS3O) pad per total SSO buffers

- Number of power pads for SSO block under the limit of electromigration rule

- Calculating the following expression:

$$NVDDO2_{SSO}/NVSSO2_{SSO} = \frac{I_{eq_o}}{I_{em}}$$

$$I_{eq_o} = \sum_{i}^{N_SSO_output} (0.001 \times C_{i_outload} \times V_i \times F_i \times S_i) + \sum_{j}^{N_SSO_bi} (0.001 \times C_{j_outload} \times V_j \times F_j \times S_j \times S_{j_out})$$

where

N_SSO_output is the number of simultaneous switching output buffers used,
N_SSO_bi is the number of simultaneous switching bi-directional buffers used,
$C_{outload}$ = Output load capacitance [pF]
V = Operating voltage [V]
F = Maximum I/O operating frequency [MHz]
S = Switching ratio (typically 0.5)
S_{out} = Output mode ratio of bidirectional buffers (typically 0.5)
I_{em} = Current limit per VDD/VSS pad paris based on electromigration rule. (80mA)

2) Number of power pads for non-SSO block

- Calculating the following expression:

$$NVDDO_{non_SSO}/NVSSO_{non_SSO} = \frac{I_{eq_o}}{I_{em}}$$

$$I_{eq_o} = \sum_{i}^{N_non_SSO_output} (0.001 \times C_{i_outload} \times V_i \times F_i \times S_i) + \sum_{j}^{N_non_SSO_bi} (0.001 \times C_{j_outload} \times V_j \times F_j \times S_j \times S_{j_out})$$

where

$N_non_SSO_output$ is the number of non-simultaneous switching output buffers used,
$N_non_SSO_bi$ is the number of non-simultaneous switching bi-directional buffers used,
$C_{outload}$ = Output load capacitance [pF]
V = Operating voltage [V]
F = Maximum I/O operating frequency [MHz]
S = Switching ratio (typically 0.5)
S_{out} = Output mode ratio of bidirectional buffers (typically 0.5)
I_{em} = Current limit per VDD/VSS pad paris based on electromigration rule. (80mA)

3) Total number of power pads for VDD2O/VSS2O (VDD3O/VSS3O)

- Calculating the following expressions:

$$\text{Number of VDD2O (VDD3O)} = \left\| \max(NVDDO1_{SSO}, NVDDO2_{SSO}) + NVDDO_{non_SSO} \right\| \text{ round-up}$$

$$\text{Number of VSS2O (VSS3O)} = \left\| \max(NVSSO1_{SSO}, NVSSO2_{SSO}) + NVSSO_{non_SSO} \right\| \text{ round-up}$$

When open drain type buffers are used, you can consider using VSS2O (VSS3O) pads since they have current sink only.

1.12 Crystal Oscillator Consideration

1.12.1 OVERVIEW

STDM110 contains a circuit commonly referred to as an “on-chip oscillator.” The on-chip circuit itself is not an oscillator but an amplifier which is suitable for being used as the amplifier part of a feedback oscillator. With proper selection of off-chip components, this oscillator circuit performs better than any other types of clock oscillators.

It is very important to select suitable off-chip components to work with the on-chip oscillator circuitry. It should be noted, however, that Samsung cannot assume the responsibility of writing specifications for the off-chip components of the complete oscillator circuit, nor of guaranteeing the performance of the finished design in production, any more than a transistor manufacturer, whose data sheets show a number of suggested amplifier circuits, can assume responsibility for the operation, in production, of any of them.

We are often asked why we don’t publish a list of required crystal or ceramic resonator specifications, and recommend values for the other off-chip components. This has been done in the past, but sometimes with consequences that were not intended.

Suppose we suggest a maximum crystal resistance of 30 ohms for some given frequency. Then your crystal supplier tells you the 30 ohm crystals are going to cost twice as much as 50 ohm crystals. Fearing that Samsung will not “guarantee operation” with 50 ohm crystals, you order the expensive ones.

In fact, Samsung guarantees only what is embodied within an Samsung product. Besides, there is no reason why 50 ohm crystals couldn’t be used, if the other off-chip components are suitably adjusted.

Should we recommend values for the other off-chip components? Should we do for 50 ohm crystals or 30 ohm crystals? With respect to what should we optimize their selection? Should we minimize start-up time or maximize frequency stability?

In many applications, neither start-up time nor frequency stability is particularly critical, and our “recommendations” are only restricting your system to unnecessary tolerances. It all depends on the application.

1.12.2 OSCILLATOR DESIGN CONSIDERATIONS

ASIC designers have a number of options for clocking the system. The main decision is whether to use the “on-chip” oscillator or an external oscillator. If the choice is to use the on-chip oscillator, what kinds of external components are to use an external oscillator, what type of oscillator would it be?

The decisions have to be based on both economic and technical requirements. In this section we will discuss some of the factors that should be considered.

1.12.2.1 On-Chip Oscillator

In most cases, the on-chip amplifier with the appropriate external components provides the most economical solution to the clocking problem. Exceptions may arise in server environments when frequency tolerances are tighter than about 0.01%.

The external components that commonly used for CMOS gate oscillator are a positive reactance (normal crystal oscillator), two capacitors, C1 and C2, and two resistor Rf and Rx as shown in the figure below.

Figure 1-19. CMOS Oscillator



1.12.2.2 Crystal Specifications

Specifications for an appropriate crystal are not very critical, unless the frequency is. Any fundamental-mode crystal of medium or better quality can be used.

We are often asked what maximum crystal resistance should be specified. The best answer to that question is the lower the better, but use what is available.

The crystal resistance will have some effect on start-up time and steady-state amplitude, but not so much that it can't be compensated for by appropriate selection of the capacitance, C1 and C2.

Similar questions are asked about specifications of load capacitance and shunt capacitance. The best advice we can give is to understand what these parameters mean and how they affect the operation of the circuit (that being the purpose of this application note), and then to decide for yourself if such specifications are meaningful in your frequency tolerances are tighter than about 0.1%.

Part of the problem is that crystal manufacturers are accustomed to talking "ppm" tolerances with radio engineers and simply won't take your order until you've filled out their list of frequency tolerance requirements, both for yourself and to the crystal manufacturer. Don't pay for 0.003% crystals if your actual frequency tolerance is 1%.

1.12.2.3 Oscillation Frequency

The oscillation frequency is determined 99.5% by the crystal and up to about 0.5% by the circuit external to the crystal.

The on-chip amplifier has little effect on the frequency, which is as it should be, since the amplifier parameterizes temperature and process dependent.

The influence of the on-chip amplifier on the frequency is by means of its input and output (pin-to-ground) capacitances, which parallel C1 and C2, and the PADA-to-PADY (pin-to-pin) capacitance, which parallels the crystal. The input and pin-to-pin capacitances are about 7 pF each.

Internal phase deviations capacitance of 25 to 30 pF. These deviations from the ideal have less effect in the positive reactance oscillator (with the inverting amplifier) than in a comparable series resonant oscillator (with the non-inverting amplifier) for two reasons: first, the effect of the output capacitor; second, the positive reactance oscillator is less sensitive, frequency-wise, to such phase errors.

1.12.2.4 C1 / C2 Selection

Optimal values for the capacitors C1 and C2 depend on whether a quartz crystal or ceramic resonator is being used, and also on application-specific requirements on start-up time and frequency tolerance.

Start-up time is sometimes more critical in microcontroller systems than frequency stability, because of various reset and initialization requirements.

Less commonly, accuracy of the oscillator frequency is also critical, for example, when the oscillator is being used as a time base. As a general rule, fast start-up and stable frequency tend to pull the oscillator design in opposite directions.

Considerations of both start-up time and frequency stability over temperature suggest that C1 and C2 should be about equal and at least 15pF. (But they don’t have to be either.)

Increasing the value of these capacitances above some 40 or 50 pF improves frequency stability. It also tends to increase the start-up time. These is a maximum value (several hundred pH, depending on the value of R1 of the quartz or ceramic resonator) above which the oscillator won’t start up at all.

If the on-chip amplifier is a simple inverter, the user can select values for C1 and C2 between some 15 and 50pF, depending on whether start-up time or frequency stability is the more critical parameter in a specific application.

1.12.2.5 Rf / Rx Selection

A CMOS inverter might work better in this application since a large Rf (1mega-ohm) can be used to hold the inverter in its linear region.

Logic gates tend to have a fairly low output resistance, which testabilizes the oscillator. For that reason a resistor Rx (several k-ohm) is often added to the feedback network, as shown in Figure 1-19.

At higher frequencies a 20 or 30 pF capacitor is sometimes used in the Rx position, to compensate for some of the internal propagation delay.

1.12.2.6 Pin Capacitance Rf / Rx Selection

Internal pin-to-ground and pin-to-pin capacitances, and PADA and PADY have some effect on the oscillator. These capacitances are normally taken to be in the range of 5 to 10pF, but they are extremely difficult to evaluate. Any measurement of one such capacitance necessarily include effects from the others.

One advantage of the positive reactance oscillator is that the pin-to ground cap. is paralleled by an external bulk capacitance, so a precise determination of their value is unnecessary.

We would suggest that there is little justification for more precision than to assign them a value of 7pF (PADA-to-ground and PADA-to-PADY). This value is probably not in error by more than 3 or 4pF.

The PADY-to-ground cap. is not entirely a “pin capacitance”, but more like an “equivalent output capacitance” of some 25 to 30pF, having to include the effect of internal phase delays. This value varies to some extent with temperature, process, and frequency.

1.12.2.7 Placement of Components

Noise glitches arising at PADA or PADY pins at the wrong time can cause a miscount in the internal clock-generating circuitry. These kinds of glitches can be produced through capacitive coupling between the oscillator components and PCB traces carrying digital signals with fast rise and fall times.

For this reason, the oscillator components should be mounted close to the chip and have short, direct traces to the PADA, PADY, and V_{SS} pins.

If possible, use dedicated V_{SS} and V_{DD} pin for only crystal feedback amplifier.

1.12.3 TROUBLESHOOTING OSCILLATOR PROBLEMS

The first thing to consider in case of difficulty is that there may be significant differences in stray caps between the test jig and the actual application, particularly if the actual application is on a multi-layer board.

Noise glitches, that are not present in the test jig but are in the application board, are another possibility. Capacitive coupling between the oscillator circuitry and other signal has already been mentioned as a source of miscounts in the internal clocking circuitry. Inductive coupling is also doubtful, if there is strong current nearby. These problems are a function of the PCB layout.

Surrounding oscillator components with “quit” traces (for example, VCC and ground) will alleviate capacitive coupling to signals having fast transition time. To minimize inductive coupling, the PCB layout should minimize the areas of the loops formed by oscillator components.

The loops demanding to be checked are as follows:

PADA through the resonator to PADY;
PADA through C1 to the V_{SS} pin;
PADY through C2 to the V_{SS} pin.

It is not unusual to find that the ground ends of C1 and C2 eventually connect up to the V_{SS} pin only after looping around the farthest ends of the board. Not good.

Finally, it should not be overlooked that software problems sometimes imitate the symptoms of a slow-starting oscillator or incorrect frequency. Never underestimate the perversity of a software problem.

Electrical Characteristics

2

Contents

DC Electrical Characteristics 2-1

DC ELECTRICAL CHARACTERISTICS

V_{DD} = 3.3 ± 0.3V, T_A = -40 to 85°C, V_{EXT} = 5 ± 0.25V (In case of 5V tolerant)

Symbol	Parameter	Condition	Min	Type	Max	Unit
V_{IH}	High level input voltage					V
	LVCMOS interface		$0.7V_{DD}$			
	LVTTL interface		2.0			
V_{IL}	Low level input voltage					V
	LVCMOS interface				$0.3V_{DD}$	
	LVTTL interface				0.8	
VT	Switching threshold	LVCMOS		0.5VDD		V
		LVTTL		1.4		
VT^+	Schmitt trigger, positive-going threshold	LVCMOS/LVTTL			2.0	
VT^-	Schmitt trigger, negative-going threshold	LVCMOS/LVTTL	0.8			
V_H	$VT^+ - VT^-$	Schmitt-trigger	0.5	0.575	0.65	
I_{IH}	High level input current					µA
	Input buffer	$V_{IN} = V_{DD}$	–10		10	
	Input buffer with pull-down		10	33	60	
I_{IL}	Low level input current					µA
	Input buffer	$V_{IN} = V_{SS}$	–10		10	
	Input buffer with pull-up		–60	–33	–10	
V_{OH}	High level output voltage					V
	Type B1 to B12[Note1]	I_{OH} = –1µA	V_{DD} – 0.05			
	Type B1	I_{OH} = –1mA	2.4			
	Type B2	I_{OH} = –2mA				
	Type B3	I_{OH} = –3mA				
	Type B4	I_{OH} = –4mA				
	Type B6	I_{OH} = –6mA				
	Type B8	I_{OH} = –8mA				
	Type B10	I_{OH} = –10mA				
	Type B12	I_{OH} = –12mA				
V_{OL}	Low level output voltage					V
	Type B1 to B12[Note1]	I_{OL} = 1µA			0.05	
	Type B1	I_{OL} = 1mA			0.4	
	Type B2	I_{OL} = 2mA				
	Type B3	I_{OL} = 3mA				
	Type B4	I_{OL} = 4mA				
	Type B6	I_{OL} = 6mA				
	Type B8	I_{OL} = 8mA				
	Type B10	I_{OL} = 10mA				
	Type B12	I_{OL} = 12mA				
I_{OZ}	Tri-state output leakage current	V_{OUT} =V_{SS} or V_{EXT}	–10		10	µA
I_{OS}	Output short circuit current	V_{DD} = 3.6V, V_O = V_{DD}			55	mA
		V_{DD} = 3.6V, V_O = V_{SS}	–55			
I_{DD}	Quiescent supply current	V_{IN} = V_{SS} or V_{DD}			100[Note2]	µA
C_{IN}	Input capacitance[Note3]	Any Input and Bidirectional Buffers			4	pF
C_{OUT}	Output capacitance[Note3]	Any Output Buffer			4	pF

V_{DD} = 2.5 ± 0.2V, T_A = -40 to 85°C (In case of general I/O)

Symbol	Parameter	Condition	Min	Type	Max	Unit
V_{IH}	High level input voltage					V
	LVCMOS interface		1.7			
V_{IL}	Low level input voltage					V
	LVCMOS interface				0.7	
VT	Switching threshold	LVCMOS		$0.5V_{DD}$		V
VT^+	Schmitt trigger, positive-going threshold	LVCMOS			1.9	
VT-	Schmitt trigger, negative-going threshold	LVCMOS	0.6			
V_H	$VT^+ - VT^-$	Schmitt-trigger	0.5	0.65	0.8	
I_{IH}	High level input current					µA
	Input buffer	$V_{IN} = V_{DD}$	–10		10	
	Input buffer with pull-down		10	25	50	
I_{IL}	Low level input current					µA
	Input buffer	$V_{IN} = V_{SS}$	–10		10	
	Input buffer with pull-up		–50	–25	–10	
V_{OH}	High level output voltage					V
	Type B1 to B12[Note1]	I_{OH} = –1µA	V_{DD} – 0.05			
	Type B1	I_{OH} = –1mA	1.9			
	Type B2	I_{OH} = –2mA				
	Type B4	I_{OH} = –4mA				
	Type B6	I_{OH} = –6mA				
	Type B8	I_{OH} = –8mA				
	Type B10	I_{OH} = –10mA				
	Type B12	I_{OH} = –12mA				
V_{OL}	Low level output voltage					V
	Type B1 to B12[Note1]	I_{OL} = 1µA			0.05	
	Type B1	I_{OL} = 1mA			0.5	
	Type B2	I_{OL} = 2mA				
	Type B4	I_{OL} = 4mA				
	Type B6	I_{OH} = 6mA				
	Type B8	I_{OH} = 8mA				
	Type B10	I_{OH} = 10mA				
	Type B12	I_{OH} = 12mA				
I_{OZ}	Tri-state output leakage current	V_{OUT} =V_{SS} or V_{EXT}	–10		10	µA
I_{OS}	Output short circuit current	V_{DD} = 3.6V, V_O = V_{DD}			55	mA
		V_{DD} = 3.6V, V_O = V_{SS}	–55			
I_{DD}	Quiescent supply current	V_{IN} = V_{SS} or V_{DD}			100[Note2]	µA
C_{IN}	Input capacitance[Note3]	Any Input and Bidirectional Buffers			4	pF
C_{OUT}	Output capacitance[Note3]	Any Output Buffer			4	pF

NOTES:

1. Type B1 means 1mA output driver cells, and type B6/B12 means 6mA/12mA output driver cells.
2. This value depends on the customer design.
3. This value exclude package parasitics.

Absolute Maximum Ratings

Symbol	Parameter	Rating		Unit
V_{DD}	DC supply voltage	2.5V V_{DD}	3.6	V
		3.3V V_{DD}	4.6	
V_{IN}	DC input voltage	2.5V input buffer	3.6	
		3.3V input buffer	4.6	
		3.3V interface/5V tolerant input buffer	6.5	
V_{OUT}	DC output voltage	2.5V output buffer	3.6	
		3.3V output buffer	4.6	
		3.3V interface/5V tolerant output buffer	6.5	
I_{latch}	Latch-up current	±200		mA
T_{STG}	Storage temperature	– 65 to 150		°C

Recommended Operating Conditions

Symbol	Parameter	Rating			Unit
			Min	Max	
V_{DD}	DC Supply Voltage for Internal (=V_{DDIN})	2.5V V_{DD}	2.3	2.7	V
	DC Supply Voltage for I/O Block (=V_{DDIO})	2.5V V_{DD}	2.3	2.7	
		3.3V V_{DD}	3.0	3.6	
	DC Supply Voltage for Analog Core (=V_{DDA})	2.5V V_{DD}	2.5 – 5%	2.5 + 5%	
		3.3V V_{DD}	3.3 – 5%	3.3 + 5%	
V_{IN}	DC Input Voltage	2.5V input buffer	–0.2	V_{DDIO}+0.2	
		3.3V input buffer	–0.3	V_{DDIO}+0.3	
		3.3V interface / 5V tolerant input buffer	–0.3	5.5	
V_{OUT}	DC Output Voltage	2.5V output buffer	–0.2	V_{DDIO}+0.2	
		3.3V output buffer	–0.3	V_{DDIO}+0.3	
		3.3V interface / 5V tolerant output buffer	–0.3	5.5	
T_A	Commercial temperature range			0 to 70	°C
	Industrial temperature range			–40 to 85	

Internal Macrocells

3

Contents

Overview 3-1
Summary Tables 3-2
Logic Cells 3-7
Flip-Flops 3-300
Latches 3-400
Bus Holder 3-437
Internal Clock Drivers 3-438
Decoders 3-440
Adders 3-449
Multiplexers 3-459

OVERVIEW

The third chapter contains data sheets of STDM110 logic cells, flip-flops, latches, bus holder, internal clock drivers, decoders, adders and multiplexers.

The electrical characteristics of each cell follow its basic cell data.

Summary tables in the following pages list the whole STDM110 internal macrocells by the type and show their reference page numbers for your convenience. Moreover, you can find the more detailed description tables on the leading pages of each category.

SUMMARY TABLES

Logic Cells

Cell Type	Cell Name	Page
AND Cells	AD2DH/AD2/AD2D2/AD2D4	3-17
	AD3DH/AD3/AD3D2/AD3D4	3-19
	AD4DH/AD4/AD4D2/AD4D4	3-21
	AD5/AD5D2/AD5D4	3-24
NAND Cells	ND2DH/ND2/ND2D2/ND2D4	3-27
	ND3DH/ND3/ND3D2/ND3D4	3-29
	ND4DH/ND4/ND4D2/ND4D2B/ND4D4	3-32
	ND5/ND5D2/ND5D4	3-35
	ND6/ND6D2/ND6D4	3-38
	ND8/ND8D2/ND8D4	3-42
NOR Cells	NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A	3-46
	NR3DH/NR3/NR3D2/NR3D2B/NR3D4/NR3A	3-49
	NR4DH/NR4/NR4D2/NR4D4	3-53
	NR5/NR5D2/NR5D4	3-56
	NR6/NR6D2/NR6D4	3-60
	NR8/NR8D2/NR8D4	3-64
OR Cells	OR2DH/OR2/OR2D2/OR2D4	3-68
	OR3DH/OR3/OR3D2/OR3D4	3-70
	OR4DH/OR4/OR4D2/OR4D4	3-73
	OR5/OR5D2/OR5D4	3-76
Exclusive-NOR Cells	XN2/XN2D2/XN2D4	3-80
	XN3/XN3D2/XN3D4	3-82
Exclusive-OR Cells	XO2/XO2D2/XO2D4	3-84
	XO3/XO3D2/XO3D4	3-86
Combinational Cells of AND and NOR	AO21DH/AO21/AO21D2/AO21D2B/AO21D4	3-88
	AO211DH/AO211/AO211D2/AO211D2B/AO211D4	3-91
	AO2111/AO2111D2	3-94
	AO22DH/AO22/AO22D2/AO22D2B/AO22D4	3-97
	AO22DHA/AO22A/AO22D2A/AO22D4A	3-100
	AO221/AO221D2/AO221D4	3-103
	AO222/AO222D2/AO222D2B/AO222D4	3-107
	AO222A/AO222D2A/AO222D4A	3-112
	AO2222/AO2222D2/AO2222D4	3-114
	AO31DH/AO31/AO31D2/AO31D4	3-118
	AO311/AO311D2/AO311D4	3-121
	AO3111/AO3111D2	3-125
	AO32/AO32D2/AO32D4	3-128

Cell Type	Cell Name	Page
	AO321/AO321D2/AO321D4	3-132
	AO322/AO322D2/AO322D4	3-136
	AO33/AO33D2/AO33D4	3-140
	AO331/AO331D2/AO331D4	3-144
	AO332/AO332D2/AO332D4	3-148
	AO4111/AO4111D2	3-152
Combinational Cells of OR and NAND	OA21DH/OA21/OA21D2/OA21D2B/OA21D4	3-155
	OA211DH/OA211/OA211D2/OA211D2B/OA211D4	3-158
	OA2111/OA2111D2	3-161
	OA22DH/OA22/OA22D2/OA22D2B/OA22D4	3-164
	OA22DHA/OA22A/OA22D2A/OA22D4A	3-167
	OA221/OA221D2/OA221D4	3-170
	OA222/OA222D2/OA222D2B/OA222D4	3-174
	OA2222/OA2222D2/OA2222D4	3-179
	OA31DH/OA31/OA31D2/OA31D4	3-183
	OA311/OA311D2/OA311D4	3-186
	OA3111/OA3111D2	3-190
	OA32/OA32D2/OA32D4	3-193
	OA321/OA321D2/OA321D4	3-197
	OA322/OA322D2/OA322D4	3-201
	OA33/OA33D2/OA33D4	3-205
	OA331/OA331D2/OA331D4	3-209
	OA332/OA332D2/OA332D4	3-213
	OA4111/OA4111D2	3-217
Complex Cells	SCG1/SCG1D2	3-220
	SCG2/SCG2D2	3-223
	SCG3/SCGD2	3-225
	SCG4/SCG4D2	3-228
	SCG5/SCG5D2	3-231
	SCG6/SCG6D2	3-234
	SCG7/SCG7D2	3-236
	SCG8/SCG8D2	3-239
	SCG9/SCG9D2	3-241
	SCG10/SCG10D2	3-243
	SCG11/SCG11D2	3-245
	SCG12/SCG12D2	3-248
	SCG13/SCG13D2	3-250
	SCG14/SCG14D2	3-252
	SCG15/SCG15D2	3-254
	SCG16/SCG16D2	3-256
	SCG17/SCG17D2	3-258

Cell Type	Cell Name	Page
Complex Cells	SCG18/SCG18D2	3-260
	SCG19/SCG19D2	3-263
	SCG20/SCG20D2	3-265
	SCG21/SCG21D2	3-267
	SCG22/SCG22D2	3-269
Delay Cells	DL1D2/DL1D4	3-271
	DL2D2/DL2D4	3-272
	DL3D2/DL3D4	3-273
	DL4D2/DL4D4	3-274
	DL5D2/DL5D4	3-275
	DL10D2/DL10D4	3-276
Inverters	IVDH/IV/IVD2/IVD3/IVD4/IVD6/IVD8/IVD16	3-277
	IVCD(11/13)/IVCD(22/26)/IVCD44	3-280
Inverting Tri-State Buffers	IVT/IVTD2/IVTD4/IVTD8/IVTD16	3-282
	IVTN/IVTND2/IVTND4/IVTND8/IVTND16	3-284
Non-Inverting Buffers	NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16	3-286
Clock Buffers for OAK core only	OAK_NID10P/OAK_NID 20P	3-289
Non-Inverting Tri-State Buffers	NIT/NITD2/NITD4/NITD8/NITD16	3-290
	NITN/NITND2/NITND4/NITND8/NITND16	3-293
2 Phase Clock Generator Buffers for OAK core only	OAK_DUCLK10/OAK_DUCLK16	3-296
Clock Tree Synthesis Buffers	CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/ CTSBD8/CTSBD16	3-298

Flip-Flops

Cell Type	Cell Name	Page
D Flip-Flop	FD1/FD1D2	3-304
	FD1CS/FD1CSD2	3-306
	FD1S/FD1SD2	3-308
	FD1SQ/FD1SQD2	3-310
	FD1Q/FD1QD2	3-312
D Flip-Flop with Reset	FD2/FD2D2	3-314
	FD2CS/FD2CSD2	3-316
	FD2S/FD2SD2	3-320
	FD2SQ/FD2SQD2	3-322
	FD2Q/FD2QD2	3-324
D Flip-Flop with Set	FD3/FD3D2	3-326
	FD3CS/FD3CSD2	3-328
	FD3S/FD3SD2	3-332
	FD3SQ/FD3SQD2	3-334
	FD3Q/FD3QD2	3-336

Cell Type	Cell Name	Page
D Flip-Flop with Reset, Set	FD4/FD4D2	3-338
	FD4CS/FD4CSD2	3-341
	FD4S/FD4SD2	3-345
	FD4SQ/FD4SQD2	3-349
	FD4Q/FD4QD2	3-352
D Flip-Flop with Negative Edge Trigger	FD5/FD5D2	3-354
	FD5S/FD5SD2	3-356
	FD6/FD6D2	3-358
	FD6S/FD6SD2	3-360
	FD7/FD7D2	3-362
	FD7S/FD7SD2	3-364
	FD8/FD8D2	3-366
	FD8S/FD8SD2	3-369
D Flip-Flop with Synchronous Clear	FDS2/FDS2D2	3-373
	FDS2CS/FDS2CSD2	3-375
	FDS2S/FDS2SD2	3-377
	FDS3/FDS3D2	3-379
	FDS3CS/FDS3CSD2	3-381
	FDS3S/FDS3SD2	3-383
JK Flip-Flop	FJ1/FJ1D2	3-385
	FJ1S/FJ1SD2	3-387
	FJ2/FJ2D2	3-389
	FJ2S/FJ2SD2	3-391
	FJ4/FJ4D2	3-393
	FJ4S/FJ4SD2	3-396
Toggle Flip-Flop	FT2/FT2D2	3-399

Latches

Cell Type	Cell Name	Page
D Latch with Active High	LD1/LD1D2	3-402
	LD1A/LD1D2A	3-404
	LD1Q/LD1QD2	3-406
	LD2/LD2D2	3-408
	LD2Q/LD2QD2	3-411
	LD3/LD3D2	3-413
	LD4/LD4D2	3-416
D Latch with Active Low	LD5/LD5D2	3-419
	LD5Q/LD5QD2	3-421
	LD6/LD6D2	3-423
	LD6Q/LD6QD2	3-426

Cell Type	Cell Name	Page
	LD7/LD7D2	3-428
	LD8/LD8D2	3-431
SR Latch	LS0/LS0D2	3-434
	LS1/LS1D2	3-436

Bus Holder

Cell Type	Cell Name	Page
Bus Holder	BUSHOLDER	3-437

Internal Clock Drivers

Cell Type	Cell Name	Page
Internal Clock Drivers	CK2/CK4/CK6/CK8	3-438

Decoders

Cell Type	Cell Name	Page
Non-Inverting Decoder	DC4	3-441
Inverting Decoders	DC4I	3-443
	DC8I	3-445

Adders

Cell Type	Cell Name	Page
Full Adders	FADH/FA/FAD2	3-450
Half Adders	HADH/HA/HAD2	3-453
Complex Cells	SCG23/SCG23D2	3-456

Multiplexers

Cell Type	Cell Name	Page
2 > 1 Non-Inverting Mux	MX2DH/MX2/MX2D2/MX2D4	3-460
	MX2X4	3-463
2 > 1 Inverting Mux	MX2IDH/MX2I/MX2ID2/MX2ID4	3-466
	MX2IDHA/MX2IA/MX2ID2A/MX2ID4A	3-469
	MX2IX4	3-472
3 > 1 Inverting Mux	MX3I/MX3ID2/MX3ID4	3-475
4 > 1 Non-Inverting Mux	MX4/MX4D2/MX4D4	3-479
8 > 1 Non-Inverting Mux	MX8/MX8D2/MX8D4	3-483

Cell Names & Function Descriptions

Cell Name	Function Description
AD2DH	2-Input AND with 0.5X Drive
AD2	2-Input AND with 1X Drive
AD2D2	2-Input AND with 2X Drive
AD2D4	2-Input AND with 4X Drive
AD3DH	3-Input AND with 0.5X Drive
AD3	3-Input AND with 1X Drive
AD3D2	3-Input AND with 2X Drive
AD3D4	3-Input AND with 4X Drive
AD4DH	4-Input AND with 0.5X Drive
AD4	4-Input AND with 1X Drive
AD4D2	4-Input AND with 2X Drive
AD4D4	4-Input AND with 4X Drive
AD5	5-Input AND with 1X Drive
AD5D2	5-Input AND with 2X Drive
AD5D4	5-Input AND with 4X Drive
ND2DH	2-Input NAND with 0.5X Drive
ND2	2-Input NAND with 1X Drive
ND2D2	2-Input NAND with 2X Drive
ND2D4	2-Input NAND with 4X Drive
ND3DH	3-Input NAND with 0.5X Drive
ND3	3-Input NAND with 1X Drive
ND3D2	3-Input NAND with 2X Drive
ND3D4	3-Input NAND with 4X Drive
ND4DH	4-Input NAND with 0.5X Drive
ND4	4-Input NAND with 1X Drive
ND4D2	4-Input NAND with 2X Drive
ND4D2B	4-Input NAND with 2X (Buffered) Drive
ND4D4	4-Input NAND with 4X Drive
ND5	5-Input NAND with 1X Drive
ND5D2	5-Input NAND with 2X Drive
ND5D4	5-Input NAND with 4X Drive
ND6	6-Input NAND with 1X Drive
ND6D2	6-Input NAND with 2X Drive
ND6D4	6-Input NAND with 4X Drive
ND8	8-Input NAND with 1X Drive
ND8D2	8-Input NAND with 2X Drive
ND8D4	8-Input NAND with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
NR2DH	2-Input NOR with 0.5X Drive
NR2	2-Input NOR with 1X Drive
NR2D2	2-Input NOR with 2X Drive
NR2D2B	2-Input NOR with 2X (Buffered) Drive
NR2D4	2-Input NOR with 4X Drive
NR2A	NR2 with 2X P-Transistor, 1X N-Transistor
NR3DH	3-Input NOR with 0.5X Drive
NR3	3-Input NOR with 1X Drive
NR3D2	3-Input NOR with 2X Drive
NR3D2B	3-Input NOR with 2X (Buffered) Drive
NR3D4	3-Input NOR with 4X Drive
NR3A	NR3 with 2X P-Transistor, 1X N-Transistor
NR4DH	4-Input NOR with 0.5X Drive
NR4	4-Input NOR with 1X Drive
NR4D2	4-Input NOR with 2X Drive
NR4D4	4-Input NOR with 4X Drive
NR5	5-Input NOR with 1X Drive
NR5D2	5-Input NOR with 2X Drive
NR5D4	5-Input NOR with 4X Drive
NR6	6-Input NOR with 1X Drive
NR6D2	6-Input NOR with 2X Drive
NR6D4	6-Input NOR with 4X Drive
NR8	8-Input NOR with 1X Drive
NR8D2	8-Input NOR with 2X Drive
NR8D4	8-Input NOR with 4X Drive
OR2DH	2-Input OR with 0.5X Drive
OR2	2-Input OR with 1X Drive
OR2D2	2-Input OR with 2X Drive
OR2D4	2-Input OR with 4X Drive
OR3DH	3-Input OR with 0.5X Drive
OR3	3-Input OR with 1X Drive
OR3D2	3-Input OR with 2X Drive
OR3D4	3-Input OR with 4X Drive
OR4DH	4-Input OR with 0.5X Drive
OR4	4-Input OR with 1X Drive
OR4D2	4-Input OR with 2X Drive
OR4D4	4-Input OR with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
OR5	5-Input OR with 1X Drive
OR5D2	5-Input OR with 2X Drive
OR5D4	5-Input OR with 4X Drive
XN2	2-Input Exclusive-NOR with 1X Drive
XN2D2	2-Input Exclusive-NOR with 2X Drive
XN2D4	2-Input Exclusive-NOR with 4X Drive
XN3	3-Input Exclusive-NOR with 1X Drive
XN3D2	3-Input Exclusive-NOR with 2X Drive
XN3D4	3-Input Exclusive-NOR with 4X Drive
XO2	2-Input Exclusive-OR with 1X Drive
XO2D2	2-Input Exclusive-OR with 2X Drive
XO2D4	2-Input Exclusive-OR with 4X Drive
XO3	3-Input Exclusive-OR with 1X Drive
XO3D2	3-Input Exclusive-OR with 2X Drive
XO3D4	3-Input Exclusive-OR with 4X Drive
AO21DH	2-AND into 2-NOR with 0.5X Drive
AO21	2-AND into 2-NOR with 1X Drive
AO21D2	2-AND into 2-NOR with 2X Drive
AO21D2B	2-AND into 2-NOR with 2X(Buffered) Drive
AO21D4	2-AND into 2-NOR with 4X Drive
AO211DH	2-AND into 3-NOR with 0.5X Drive
AO211	2-AND into 3-NOR with 1X Drive
AO211D2	2-AND into 3-NOR with 2X Drive
AO211D2B	2-AND into 3-NOR with 2X(Buffered) Drive
AO211D4	2-AND into 3-NOR with 4X Drive
AO2111	2-AND into 4-NOR with 1X Drive
AO2111D2	2-AND into 4-NOR with 2X Drive
AO22DH	Two 2-ANDs into 2-NOR with 0.5X Drive
AO22	Two 2-ANDs into 2-NOR with 1X Drive
AO22D2	Two 2-ANDs into 2-NOR with 2X Drive
AO22D2B	Two 2-ANDs into 2-NOR with 2X(Buffered) Drive
AO22D4	Two 2-ANDs into 2-NOR with 4X Drive
AO22DHA	2-AND and 2-NOR into 2-NOR with 0.5X Drive
AO22A	2-AND and 2-NOR into 2-NOR with 1X Drive
AO22D2A	2-AND and 2-NOR into 2-NOR with 2X Drive
AO22D4A	2-AND and 2-NOR into 2-NOR with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
AO221	Two 2-ANDs into 3-NOR with 1X Drive
AO221D2	Two 2-ANDs into 3-NOR with 2X Drive
AO221D4	Two 2-ANDs into 3-NOR with 4X Drive
AO222	Three 2-ANDs into 3-NOR with 1X Drive
AO222D2	Three 2-ANDs into 3-NOR with 2X Drive
AO222D2B	Three 2-ANDs into 3-NOR with 2X(Buffered) Drive
AO222D4	Three 2-ANDs into 3-NOR with 4X Drive
AO222A	Inverting 2-of-3 Majority with 1X Drive
AO222D2A	Inverting 2-of-3 Majority with 2X Drive
AO222D4A	Inverting 2-of-3 Majority with 4X Drive
AO2222	Four 2-ANDs into 4-NOR with 1X Drive
AO2222D2	Four 2-ANDs into 4-NOR with 2X Drive
AO2222D4	Four 2-ANDs into 4-NOR with 4X Drive
AO31DH	3-AND into 2-NOR with 0.5X Drive
AO31	3-AND into 2-NOR with 1X Drive
AO31D2	3-AND into 2-NOR with 2X Drive
AO31D4	3-AND into 2-NOR with 4X Drive
AO311	3-AND into 3-NOR with 1X Drive
AO311D2	3-AND into 3-NOR with 2X Drive
AO311D4	3-AND into 3-NOR with 4X Drive
AO3111	3-AND into 4-NOR with 1X Drive
AO3111D2	3-AND into 4-NOR with 2X Drive
AO32	3-AND and 2-AND into 2-NOR with 1X Drive
AO32D2	3-AND and 2-AND into 2-NOR with 2X Drive
AO32D4	3-AND and 2-AND into 2-NOR with 4X Drive
AO321	3-AND and 2-AND into 3-NOR with 1X Drive
AO321D2	3-AND and 2-AND into 3-NOR with 2X Drive
AO321D4	3-AND and 2-AND into 3-NOR with 4X Drive
AO322	3-AND and Two 2-ANDs into 3-NOR with 1X Drive
AO322D2	3-AND and Two 2-ANDs into 3-NOR with 2X Drive
AO322D4	3-AND and Two 2-ANDs into 3-NOR with 4X Drive
AO33	Two 3-ANDs into 2-NOR with 1X Drive
AO33D2	Two 3-ANDs into 2-NOR with 2X Drive
AO33D4	Two 3-ANDs into 2-NOR with 4X Drive
AO331	Two 3-ANDs into 3-NOR with 1X Drive
AO331D2	Two 3-ANDs into 3-NOR with 2X Drive
AO331D4	Two 3-ANDs into 3-NOR with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
AO332	Two 3-ANDs and 2-AND into 3-NOR
AO332D2	Two 3-ANDs and 2-AND into 3-NOR with 2X Drive
AO332D4	Two 3-ANDs and 2-AND into 3-NOR with 4X Drive
AO4111	4-AND into 4-NOR with 1X Drive
AO4111D2	4-AND into 4-NOR with 2X Drive
OA21DH	2-OR into 2-NAND with 0.5X Drive
OA21	2-OR into 2-NAND with 1X Drive
OA21D2	2-OR into 2-NAND with 2X Drive
OA21D2B	2-OR into 2-NAND with 2X(Buffered) Drive
OA21D4	2-OR into 2-NAND with 4X Drive
OA211DH	2-OR into 3-NAND with 0.5X Drive
OA211	2-OR into 3-NAND with 1X Drive
OA211D2	2-OR into 3-NAND with 2X Drive
OA211D2B	2-OR into 3-NAND with 2X(Buffered) Drive
OA211D4	2-OR into 3-NAND with 4X Drive
OA2111	2-OR into 4-NAND with 1X Drive
OA2111D2	2-OR into 4-NAND with 2X Drive
OA22DH	Two 2-ORs into 2-NAND with 0.5X Drive
OA22	Two 2-ORs into 2-NAND with 1X Drive
OA22D2	Two 2-ORs into 2-NAND with 2X Drive
OA22D2B	Two 2-ORs into 2-NAND with 2X(Buffered) Drive
OA22D4	Two 2-ORs into 2-NAND with 4X Drive
OA22DHA	2-OR and 2-NAND into 2-NAND with 0.5X Drive
OA22A	2-OR and 2-NAND into 2-NAND with 1X Drive
OA22D2A	2-OR and 2-NAND into 2-NAND with 2X Drive
OA22D4A	2-OR and 2-NAND into 2-NAND with 4X Drive
OA221	Two 2-ORs into 3-NAND with 1X Drive
OA221D2	Two 2-ORs into 3-NAND with 2X Drive
OA221D4	Two 2-ORs into 3-NAND with 4X Drive
OA222	Three 2-ORs into 3-NAND with 1X Drive
OA222D2	Three 2-ORs into 3-NAND with 2X Drive
OA222D2B	Three 2-ORs into 3-NAND with 2X(Buffered) Drive
OA222D4	Three 2-ORs into 3-NAND with 4X Drive
OA2222	Four 2-ORs into 4-NAND with 1X Drive
OA2222D2	Four 2-ORs into 4-NAND with 2X Drive
OA2222D4	Four 2-ORs into 4-NAND with 4X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
OA31DH	3-OR into 2-NAND with 0.5X Drive
OA31	3-OR into 2-NAND with 1X Drive
OA31D2	3-OR into 2-NAND with 2X Drive
OA31D4	3-OR into 2-NAND with 4X Drive
OA311	3-OR into 3-NAND with 1X Drive
OA311D2	3-OR into 3-NAND with 2X Drive
OA311D4	3-OR into 3-NAND with 4X Drive
OA3111	3-OR into 4-NAND with 1X Drive
OA3111D2	3-OR into 4-NAND with 2X Drive
OA32	3-OR and 2-OR into 2-NAND with 1X Drive
OA32D2	3-OR and 2-OR into 2-NAND with 2X Drive
OA32D4	3-OR and 2-OR into 2-NAND with 4X Drive
OA321	3-OR and 2-OR into 3-NAND with 1X Drive
OA321D2	3-OR and 2-OR into 3-NAND with 2X Drive
OA321D4	3-OR and 2-OR into 3-NAND with 4X Drive
OA322	3-OR and Two 2-ORs into 3-NAND with 1X Drive
OA322D2	3-OR and Two 2-ORs into 3-NAND with 2X Drive
OA322D4	3-OR and Two 2-ORs into 3-NAND with 4X Drive
OA33	Two 3-ORs into 2-NAND with 1X Drive
OA33D2	Two 3-ORs into 2-NAND with 2X Drive
OA33D4	Two 3-ORs into 2-NAND with 4X Drive
OA331	Two 3-ORs into 3-NAND with 1X Drive
OA331D2	Two 3-ORs into 3-NAND with 2X Drive
OA331D4	Two 3-ORs into 3-NAND with 4X Drive
OA332	Two 3-ORs and 2-OR into 3-NAND with 1X Drive
OA332D2	Two 3-ORs and 2-OR into 3-NAND with 2X Drive
OA332D4	Two 3-ORs and 2-OR into 3-NAND with 4X Drive
OA4111	4-OR into 4-NAND with 1X Drive
OA4111D2	4-OR into 4-NAND with 2X Drive
SCG1	2-NAND and two (2-AND into 2-NOR)s into 3-NAND
SCG1D2	2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 2X Drive
SCG2	Two 2-ANDs into 2-OR
SCG2D2	Two 2-ANDs into 2-OR with 2X Drive
SCG3	Two 2-NANDs into 3-NAND
SCG3D2	Two 2-NANDs into 3-NAND with 2X Drive
SCG4	Two (two 2-ANDs into 2-NOR)s into 2-NAND
SCG4D2	Two (two 2-ANDs into 2-NOR)s into 2-NAND with 2X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
SCG5	Three 2-ANDs into 3-OR
SCG5D2	Three 2-ANDs into 3-OR with 2X Drive
SCG6	2-AND into 2-OR
SCG6D2	2-AND into 2-OR with 2X Drive
SCG7	2-NAND and (2-AND into 2-NOR) into 2-NAND
SCG7D2	2-NAND and (2-AND into 2-NOR) into 2-NAND with 2X Drive
SCG8	2-AND into 3-OR
SCG8D2	2-AND into 3-OR with 2X Drive
SCG9	2-OR into 2-AND
SCG9D2	2-OR into 2-AND with 2X Drive
SCG10	Two 2-ORs into 2-AND
SCG10D2	Two 2-ORs into 2-AND with 2X Drive
SCG11	Two 2-NORs into 3-NOR
SCG11D2	Two 2-NORs into 3-NOR with 2X Drive
SCG12	2-NAND into 2-NOR
SCG12D2	2-NAND into 2-NOR with 2X Drive
SCG13	2-NOR into 2-NAND
SCG13D2	2-NOR into 2-NAND with 2X Drive
SCG14	2-NAND into 2-NAND
SCG14D2	2-NAND into 2-NAND with 2X Drive
SCG15	2-NAND into 3-NAND
SCG15D2	2-NAND into 3-NAND with 2X Drive
SCG16	2-OR with one inverted input into 2-NAND
SCG16D2	2-OR with one inverted input into 2-NAND with 2X Drive
SCG17	2-AND into 2-NOR into 2-NAND
SCG17D2	2-AND into 2-NOR into 2-NAND with 2X Drive
SCG18	2-AND into 2-NOR into 3-NAND
SCG18D2	2-AND into 2-NOR into 3-NAND with 2X Drive
SCG19	2-AND into 2-AND into 2-NOR
SCG19D2	2-AND into 2-AND into 2-NOR with 2X Drive
SCG20	2-NOR into 2-NOR
SCG20D2	2-NOR into 2-NOR with 2X Drive
SCG21	2-NOR into 3-NOR
SCG21D2	2-NOR into 3-NOR with 2X Drive
SCG22	2-NAND into 2-OR into 2-NAND
SCG22D2	2-NAND into 2-OR into 2-NAND with 2X Drive
SCG23	Full Adder with one inverted input with 1X Drive
SCG23D2	Full Adder with one inverted input with 2X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
DL1D2	1ns Delay Cell with 2X Drive
DL1D4	1ns Delay Cell with 4X Drive
DL2D2	2ns Delay Cell with 2X Drive
DL2D4	2ns Delay Cell with 4X Drive
DL3D2	3ns Delay Cell with 2X Drive
DL3D4	3ns Delay Cell with 4X Drive
DL4D2	4ns Delay Cell with 2X Drive
DL4D4	4ns Delay Cell with 4X Drive
DL5D2	5ns Delay Cell with 2X Drive
DL5D4	5ns Delay Cell with 4X Drive
DL10D2	10ns Delay Cell with 2X Drive
DL10D4	10ns Delay Cell with 4X Drive
IVDH	Inverter with 0.5X Drive
IV	Inverter with 1X Drive
IVD2	Inverter with 2X Drive
IVD3	Inverter with 3X Drive
IVD4	Inverter with 4X Drive
IVD6	Inverter with 6X Drive
IVD8	Inverter with 8X Drive
IVD16	Inverter with 16X Drive
IVCD11	1X Inverter into 1X Inverter
IVCD13	1X Inverter into 3X Inverter
IVCD22	2X Inverter into 2X Inverter
IVCD26	2X Inverter into 6X Inverter
IVCD44	4X Inverter into 4X Inverter
IVT	Inverting Tri-State Buffer with Enable High, 1X Drive
IVTD2	Inverting Tri-State Buffer with Enable High, 2X Drive
IVTD4	Inverting Tri-State Buffer with Enable High, 4X Drive
IVTD8	Inverting Tri-State Buffer with Enable High, 8X Drive
IVTD16	Inverting Tri-State Buffer with Enable High, 16X Drive
IVTN	Inverting Tri-State Buffer with Enable Low, 1X Drive
IVTND2	Inverting Tri-State Buffer with Enable Low, 2X Drive
IVTND4	Inverting Tri-State Buffer with Enable Low, 4X Drive
IVTND8	Inverting Tri-State Buffer with Enable Low, 8X Drive
IVTND16	Inverting Tri-State Buffer with Enable Low, 16X Drive
NIDH	Non-Inverting Buffer with 0.5X Drive
NID	Non-Inverting Buffer with 1X Drive
NID2	Non-Inverting Buffer with 2X Drive

Cell Names & Function Descriptions (Continued)

Cell Name	Function Description
NID3	Non-Inverting Buffer with 3X Drive
NID4	Non-Inverting Buffer with 4X Drive
NID6	Non-Inverting Buffer with 6X Drive
NID8	Non-Inverting Buffer with 8X Drive
NID16	Non-Inverting Buffer with 16X Drive
OAK_NID10P	Clock Buffer for 10pF Drive (for OAK core only)
OAK_NID20P	Clock Buffer for 20pF Drive (for OAK core only)
NIT	Non-Inverting Tri-State Buffer with Enable High, 1X Drive
NITD2	Non-Inverting Tri-State Buffer with Enable High, 2X Drive
NITD4	Non-Inverting Tri-State Buffer with Enable High, 4X Drive
NITD8	Non-Inverting Tri-State Buffer with Enable High, 8X Drive
NITD16	Non-Inverting Tri-State Buffer with Enable High, 16X Drive
NITN	Non-Inverting Tri-State Buffer with Enable Low, 1X Drive
NITND2	Non-Inverting Tri-State Buffer with Enable Low, 2X Drive
NITND4	Non-Inverting Tri-State Buffer with Enable Low, 4X Drive
NITND8	Non-Inverting Tri-State Buffer with Enable Low, 8X Drive
NITND16	Non-Inverting Tri-State Buffer with Enable Low, 16X Drive
OAK_DUCLK10	2 Phase Clock Generator (1ns Non-overlapped, for OAK core only)
OAK_DUCLK16	2 Phase Clock Generator (1.6ns Non-overlapped, for OAK core only)
CTSB	Clock Tree Synthesis Buffer with 1X Drive
CTSBD2	Clock Tree Synthesis Buffer with 2X Drive
CTSBD3	Clock Tree Synthesis Buffer with 3X Drive
CTSBD4	Clock Tree Synthesis Buffer with 4X Drive
CTSBD6	Clock Tree Synthesis Buffer with 6X Drive
CTSBD8	Clock Tree Synthesis Buffer with 8X Drive
CTSBD16	Clock Tree Synthesis Buffer with 16X Drive

NOTE

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	0
1	0	0
1	1	1

Cell Data

Input Load (SL)								Gate Count			
AD2DH		*AD2*		*AD2D2*		*AD2D4*		*AD2DH*	*AD2*	*AD2D2*	*AD2D4*
A	B	A	B	A	B	A	B				
0.6	0.6	0.8	0.9	0.8	0.8	1.1	1.2	1.33	1.33	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.252	0.090 + 0.081*SL	0.081 + 0.083*SL	0.073 + 0.084*SL
	t_F	0.196	0.072 + 0.062*SL	0.066 + 0.064*SL	0.058 + 0.065*SL
	t_{PLH}	0.267	0.188 + 0.040*SL	0.195 + 0.038*SL	0.196 + 0.038*SL
	t_{PHL}	0.259	0.188 + 0.035*SL	0.197 + 0.033*SL	0.198 + 0.033*SL
B to Y	t_R	0.252	0.090 + 0.081*SL	0.081 + 0.083*SL	0.073 + 0.084*SL
	t_F	0.198	0.074 + 0.062*SL	0.067 + 0.064*SL	0.060 + 0.065*SL
	t_{PLH}	0.264	0.185 + 0.040*SL	0.193 + 0.038*SL	0.194 + 0.038*SL
	t_{PHL}	0.279	0.207 + 0.036*SL	0.216 + 0.034*SL	0.218 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.152	0.080 + 0.036*SL	0.076 + 0.037*SL	0.070 + 0.038*SL
	t_F	0.128	0.068 + 0.030*SL	0.063 + 0.031*SL	0.060 + 0.032*SL
	t_{PLH}	0.214	0.174 + 0.020*SL	0.184 + 0.018*SL	0.188 + 0.017*SL
	t_{PHL}	0.217	0.178 + 0.020*SL	0.187 + 0.017*SL	0.191 + 0.017*SL
B to Y	t_R	0.152	0.081 + 0.036*SL	0.076 + 0.037*SL	0.070 + 0.038*SL
	t_F	0.129	0.068 + 0.031*SL	0.066 + 0.031*SL	0.061 + 0.032*SL
	t_{PLH}	0.211	0.171 + 0.020*SL	0.180 + 0.018*SL	0.185 + 0.017*SL
	t_{PHL}	0.235	0.196 + 0.020*SL	0.205 + 0.017*SL	0.210 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	0.074 + 0.019*SL	0.078 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.099	0.063 + 0.018*SL	0.070 + 0.016*SL	0.066 + 0.017*SL
	t_{PLH}	0.217	0.192 + 0.013*SL	0.203 + 0.010*SL	0.216 + 0.009*SL
	t_{PHL}	0.226	0.201 + 0.013*SL	0.212 + 0.010*SL	0.224 + 0.009*SL
B to Y	t_R	0.113	0.075 + 0.019*SL	0.078 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.072 + 0.016*SL	0.068 + 0.017*SL
	t_{PLH}	0.213	0.187 + 0.013*SL	0.199 + 0.010*SL	0.212 + 0.009*SL
	t_{PHL}	0.243	0.217 + 0.013*SL	0.228 + 0.010*SL	0.242 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AD2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.078 + 0.011*SL	0.086 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.086	0.066 + 0.010*SL	0.073 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.227	0.212 + 0.008*SL	0.220 + 0.006*SL	0.241 + 0.005*SL
	t_{PHL}	0.229	0.213 + 0.008*SL	0.221 + 0.006*SL	0.241 + 0.005*SL
B to Y	t_R	0.100	0.078 + 0.011*SL	0.084 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.089	0.069 + 0.010*SL	0.075 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.222	0.207 + 0.008*SL	0.215 + 0.006*SL	0.236 + 0.005*SL
	t_{PHL}	0.244	0.228 + 0.008*SL	0.237 + 0.006*SL	0.257 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	Y
0	x	x	0
x	0	x	0
x	x	0	0
1	1	1	1

Cell Data

Input Load (SL)												Gate Count			
AD3DH			*AD3*			*AD3D2*			*AD3D4*			*AD3DH*	*AD3*	*AD3D2*	*AD3D4*
A	B	C	A	B	C	A	B	C	A	B	C				
0.5	0.6	0.6	0.8	0.8	0.8	0.8	0.8	0.8	1.0	1.0	1.1	1.67	1.67	2.00	2.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.275	0.113 + 0.081*SL	0.108 + 0.082*SL	0.096 + 0.084*SL
	t_F	0.209	0.086 + 0.062*SL	0.081 + 0.063*SL	0.071 + 0.064*SL
	t_{PLH}	0.332	0.246 + 0.043*SL	0.264 + 0.039*SL	0.271 + 0.038*SL
	t_{PHL}	0.304	0.229 + 0.038*SL	0.244 + 0.034*SL	0.248 + 0.033*SL
B to Y	t_R	0.274	0.113 + 0.081*SL	0.108 + 0.082*SL	0.096 + 0.084*SL
	t_F	0.212	0.089 + 0.062*SL	0.085 + 0.063*SL	0.074 + 0.064*SL
	t_{PLH}	0.340	0.254 + 0.043*SL	0.272 + 0.039*SL	0.279 + 0.038*SL
	t_{PHL}	0.325	0.250 + 0.038*SL	0.265 + 0.034*SL	0.270 + 0.033*SL
C to Y	t_R	0.274	0.113 + 0.081*SL	0.107 + 0.082*SL	0.096 + 0.084*SL
	t_F	0.216	0.093 + 0.062*SL	0.089 + 0.063*SL	0.078 + 0.064*SL
	t_{PLH}	0.343	0.257 + 0.043*SL	0.275 + 0.039*SL	0.282 + 0.038*SL
	t_{PHL}	0.344	0.267 + 0.038*SL	0.284 + 0.034*SL	0.290 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.168	0.093 + 0.037*SL	0.097 + 0.037*SL	0.092 + 0.037*SL
	t_F	0.136	0.073 + 0.031*SL	0.073 + 0.031*SL	0.070 + 0.032*SL
	t_{PLH}	0.258	0.213 + 0.023*SL	0.228 + 0.019*SL	0.238 + 0.018*SL
	t_{PHL}	0.249	0.207 + 0.021*SL	0.219 + 0.018*SL	0.226 + 0.017*SL
B to Y	t_R	0.169	0.095 + 0.037*SL	0.098 + 0.036*SL	0.093 + 0.037*SL
	t_F	0.139	0.078 + 0.031*SL	0.076 + 0.031*SL	0.073 + 0.032*SL
	t_{PLH}	0.266	0.220 + 0.023*SL	0.235 + 0.019*SL	0.245 + 0.018*SL
	t_{PHL}	0.269	0.227 + 0.021*SL	0.239 + 0.018*SL	0.247 + 0.017*SL
C to Y	t_R	0.169	0.095 + 0.037*SL	0.097 + 0.037*SL	0.092 + 0.037*SL
	t_F	0.142	0.080 + 0.031*SL	0.081 + 0.031*SL	0.078 + 0.031*SL
	t_{PLH}	0.267	0.222 + 0.023*SL	0.237 + 0.019*SL	0.247 + 0.018*SL
	t_{PHL}	0.287	0.243 + 0.022*SL	0.256 + 0.018*SL	0.265 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.131	0.088 + 0.022*SL	0.098 + 0.019*SL	0.101 + 0.019*SL
	t_F	0.106	0.069 + 0.019*SL	0.078 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.267	0.237 + 0.015*SL	0.252 + 0.011*SL	0.274 + 0.009*SL
	t_{PHL}	0.256	0.228 + 0.014*SL	0.241 + 0.011*SL	0.258 + 0.009*SL
B to Y	t_R	0.131	0.088 + 0.021*SL	0.097 + 0.019*SL	0.101 + 0.019*SL
	t_F	0.110	0.073 + 0.019*SL	0.082 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.275	0.245 + 0.015*SL	0.259 + 0.011*SL	0.281 + 0.009*SL
	t_{PHL}	0.275	0.246 + 0.014*SL	0.260 + 0.011*SL	0.279 + 0.009*SL
C to Y	t_R	0.131	0.089 + 0.021*SL	0.097 + 0.019*SL	0.101 + 0.019*SL
	t_F	0.115	0.079 + 0.018*SL	0.085 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.276	0.246 + 0.015*SL	0.261 + 0.011*SL	0.283 + 0.009*SL
	t_{PHL}	0.292	0.263 + 0.015*SL	0.277 + 0.011*SL	0.296 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AD3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	0.099 + 0.012*SL	0.106 + 0.010*SL	0.119 + 0.009*SL
	t_F	0.098	0.077 + 0.010*SL	0.084 + 0.009*SL	0.092 + 0.008*SL
	t_{PLH}	0.288	0.270 + 0.009*SL	0.280 + 0.007*SL	0.310 + 0.005*SL
	t_{PHL}	0.269	0.252 + 0.008*SL	0.261 + 0.006*SL	0.286 + 0.005*SL
B to Y	t_R	0.123	0.100 + 0.011*SL	0.106 + 0.010*SL	0.119 + 0.009*SL
	t_F	0.102	0.083 + 0.010*SL	0.087 + 0.009*SL	0.096 + 0.008*SL
	t_{PLH}	0.296	0.278 + 0.009*SL	0.287 + 0.007*SL	0.317 + 0.005*SL
	t_{PHL}	0.287	0.270 + 0.009*SL	0.279 + 0.006*SL	0.305 + 0.005*SL
C to Y	t_R	0.124	0.101 + 0.011*SL	0.106 + 0.010*SL	0.118 + 0.009*SL
	t_F	0.106	0.086 + 0.010*SL	0.093 + 0.009*SL	0.101 + 0.008*SL
	t_{PLH}	0.297	0.279 + 0.009*SL	0.288 + 0.007*SL	0.318 + 0.005*SL
	t_{PHL}	0.303	0.285 + 0.009*SL	0.295 + 0.006*SL	0.322 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	x	x	0
x	0	x	x	0
x	x	0	x	0
x	x	x	0	0
1	1	1	1	1

Cell Data

Input Load (SL)															
AD4DH				*AD4*				*AD4D2*				*AD4D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.9	0.9	0.9	1.0
Gate Counts															
AD4DH				*AD4*				*AD4D2*				*AD4D4*			
2.00				2.00				2.33				3.00			

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.295	0.132 + 0.082*SL	0.133 + 0.081*SL	0.122 + 0.083*SL
	t_F	0.219	0.094 + 0.062*SL	0.093 + 0.063*SL	0.083 + 0.064*SL
	t_{PLH}	0.368	0.276 + 0.046*SL	0.302 + 0.040*SL	0.316 + 0.038*SL
	t_{PHL}	0.335	0.257 + 0.039*SL	0.276 + 0.034*SL	0.284 + 0.033*SL
B to Y	t_R	0.295	0.132 + 0.082*SL	0.133 + 0.081*SL	0.122 + 0.083*SL
	t_F	0.223	0.099 + 0.062*SL	0.097 + 0.062*SL	0.087 + 0.064*SL
	t_{PLH}	0.389	0.296 + 0.046*SL	0.323 + 0.040*SL	0.336 + 0.038*SL
	t_{PHL}	0.362	0.283 + 0.039*SL	0.303 + 0.035*SL	0.312 + 0.033*SL
C to Y	t_R	0.295	0.131 + 0.082*SL	0.134 + 0.081*SL	0.122 + 0.083*SL
	t_F	0.228	0.105 + 0.062*SL	0.103 + 0.062*SL	0.093 + 0.064*SL
	t_{PLH}	0.403	0.310 + 0.046*SL	0.336 + 0.040*SL	0.350 + 0.038*SL
	t_{PHL}	0.385	0.305 + 0.040*SL	0.326 + 0.035*SL	0.336 + 0.034*SL
D to Y	t_R	0.295	0.132 + 0.082*SL	0.133 + 0.081*SL	0.122 + 0.083*SL
	t_F	0.235	0.111 + 0.062*SL	0.111 + 0.062*SL	0.100 + 0.063*SL
	t_{PLH}	0.411	0.318 + 0.046*SL	0.344 + 0.040*SL	0.358 + 0.038*SL
	t_{PHL}	0.405	0.323 + 0.041*SL	0.346 + 0.035*SL	0.358 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.181	0.103 + 0.039*SL	0.112 + 0.037*SL	0.111 + 0.037*SL
	t_F	0.142	0.079 + 0.031*SL	0.080 + 0.031*SL	0.078 + 0.031*SL
	t_{PLH}	0.280	0.231 + 0.024*SL	0.248 + 0.020*SL	0.263 + 0.018*SL
	t_{PHL}	0.268	0.225 + 0.022*SL	0.238 + 0.018*SL	0.247 + 0.017*SL
B to Y	t_R	0.182	0.105 + 0.039*SL	0.112 + 0.037*SL	0.112 + 0.037*SL
	t_F	0.146	0.084 + 0.031*SL	0.086 + 0.031*SL	0.080 + 0.031*SL
	t_{PLH}	0.298	0.249 + 0.024*SL	0.266 + 0.020*SL	0.281 + 0.018*SL
	t_{PHL}	0.293	0.250 + 0.022*SL	0.263 + 0.019*SL	0.273 + 0.017*SL
C to Y	t_R	0.182	0.105 + 0.039*SL	0.113 + 0.037*SL	0.112 + 0.037*SL
	t_F	0.151	0.088 + 0.031*SL	0.092 + 0.031*SL	0.086 + 0.031*SL
	t_{PLH}	0.310	0.261 + 0.024*SL	0.278 + 0.020*SL	0.293 + 0.018*SL
	t_{PHL}	0.314	0.269 + 0.022*SL	0.284 + 0.019*SL	0.295 + 0.017*SL
D to Y	t_R	0.182	0.104 + 0.039*SL	0.113 + 0.037*SL	0.112 + 0.037*SL
	t_F	0.156	0.092 + 0.032*SL	0.098 + 0.031*SL	0.093 + 0.031*SL
	t_{PLH}	0.316	0.267 + 0.024*SL	0.285 + 0.020*SL	0.300 + 0.018*SL
	t_{PHL}	0.332	0.285 + 0.023*SL	0.301 + 0.019*SL	0.314 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.146	0.101 + 0.022*SL	0.112 + 0.020*SL	0.122 + 0.019*SL
	t_F	0.113	0.075 + 0.019*SL	0.086 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.292	0.260 + 0.016*SL	0.276 + 0.012*SL	0.302 + 0.010*SL
	t_{PHL}	0.278	0.249 + 0.015*SL	0.263 + 0.011*SL	0.283 + 0.009*SL
B to Y	t_R	0.144	0.099 + 0.023*SL	0.111 + 0.020*SL	0.122 + 0.019*SL
	t_F	0.119	0.082 + 0.019*SL	0.091 + 0.016*SL	0.092 + 0.016*SL
	t_{PLH}	0.311	0.279 + 0.016*SL	0.295 + 0.012*SL	0.321 + 0.010*SL
	t_{PHL}	0.302	0.272 + 0.015*SL	0.287 + 0.011*SL	0.308 + 0.009*SL
C to Y	t_R	0.145	0.100 + 0.023*SL	0.112 + 0.020*SL	0.121 + 0.019*SL
	t_F	0.124	0.087 + 0.019*SL	0.096 + 0.016*SL	0.098 + 0.016*SL
	t_{PLH}	0.323	0.291 + 0.016*SL	0.307 + 0.012*SL	0.333 + 0.010*SL
	t_{PHL}	0.323	0.292 + 0.015*SL	0.307 + 0.012*SL	0.330 + 0.010*SL
D to Y	t_R	0.146	0.102 + 0.022*SL	0.112 + 0.020*SL	0.122 + 0.019*SL
	t_F	0.128	0.089 + 0.020*SL	0.101 + 0.017*SL	0.104 + 0.016*SL
	t_{PLH}	0.330	0.297 + 0.016*SL	0.313 + 0.012*SL	0.340 + 0.010*SL
	t_{PHL}	0.340	0.309 + 0.016*SL	0.325 + 0.012*SL	0.349 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AD4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.144	0.120 + 0.012*SL	0.126 + 0.011*SL	0.147 + 0.009*SL
	t_F	0.111	0.090 + 0.010*SL	0.096 + 0.009*SL	0.110 + 0.008*SL
	t_{PLH}	0.333	0.314 + 0.010*SL	0.324 + 0.007*SL	0.359 + 0.005*SL
	t_{PHL}	0.307	0.289 + 0.009*SL	0.299 + 0.007*SL	0.328 + 0.005*SL
B to Y	t_R	0.144	0.120 + 0.012*SL	0.126 + 0.011*SL	0.146 + 0.010*SL
	t_F	0.116	0.094 + 0.011*SL	0.104 + 0.009*SL	0.114 + 0.008*SL
	t_{PLH}	0.352	0.332 + 0.010*SL	0.343 + 0.007*SL	0.377 + 0.005*SL
	t_{PHL}	0.330	0.312 + 0.009*SL	0.322 + 0.007*SL	0.352 + 0.005*SL
C to Y	t_R	0.145	0.122 + 0.012*SL	0.127 + 0.011*SL	0.146 + 0.010*SL
	t_F	0.122	0.101 + 0.011*SL	0.109 + 0.009*SL	0.121 + 0.008*SL
	t_{PLH}	0.364	0.344 + 0.010*SL	0.355 + 0.007*SL	0.389 + 0.005*SL
	t_{PHL}	0.350	0.332 + 0.009*SL	0.342 + 0.007*SL	0.373 + 0.005*SL
D to Y	t_R	0.145	0.122 + 0.012*SL	0.126 + 0.011*SL	0.147 + 0.009*SL
	t_F	0.128	0.108 + 0.010*SL	0.113 + 0.009*SL	0.127 + 0.008*SL
	t_{PLH}	0.370	0.350 + 0.010*SL	0.361 + 0.007*SL	0.395 + 0.005*SL
	t_{PHL}	0.367	0.348 + 0.009*SL	0.359 + 0.007*SL	0.392 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AD5/AD5D2/AD5D4

5-Input AND with 1X/2X/4XDrive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	x	x	x	0
x	0	x	x	x	0
x	x	0	x	x	0
x	x	x	0	x	0
x	x	x	x	0	0
1	1	1	1	1	1

Cell Data

Input Load (SL)														
AD5					*AD5D2*					*AD5D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.8	0.9	0.8	0.9	0.9	0.9	0.9
Gate Count														
AD5					*AD5D2*					*AD5D4*				
2.67					3.00					4.33				

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.292	0.144 + 0.074*SL	0.139 + 0.075*SL	0.132 + 0.076*SL
	t_F	0.149	0.082 + 0.033*SL	0.083 + 0.033*SL	0.080 + 0.033*SL
	t_{PLH}	0.278	0.205 + 0.037*SL	0.212 + 0.035*SL	0.215 + 0.035*SL
	t_{PHL}	0.279	0.234 + 0.022*SL	0.247 + 0.019*SL	0.256 + 0.018*SL
B to Y	t_R	0.292	0.144 + 0.074*SL	0.140 + 0.075*SL	0.132 + 0.076*SL
	t_F	0.154	0.088 + 0.033*SL	0.089 + 0.033*SL	0.085 + 0.033*SL
	t_{PLH}	0.287	0.213 + 0.037*SL	0.221 + 0.035*SL	0.224 + 0.035*SL
	t_{PHL}	0.310	0.265 + 0.023*SL	0.278 + 0.019*SL	0.288 + 0.018*SL
C to Y	t_R	0.292	0.143 + 0.074*SL	0.139 + 0.075*SL	0.132 + 0.076*SL
	t_F	0.157	0.091 + 0.033*SL	0.094 + 0.033*SL	0.089 + 0.033*SL
	t_{PLH}	0.289	0.216 + 0.037*SL	0.223 + 0.035*SL	0.226 + 0.035*SL
	t_{PHL}	0.330	0.284 + 0.023*SL	0.298 + 0.020*SL	0.308 + 0.018*SL
D to Y	t_R	0.280	0.129 + 0.076*SL	0.127 + 0.076*SL	0.123 + 0.077*SL
	t_F	0.167	0.102 + 0.032*SL	0.099 + 0.033*SL	0.094 + 0.034*SL
	t_{PLH}	0.256	0.184 + 0.036*SL	0.189 + 0.035*SL	0.191 + 0.035*SL
	t_{PHL}	0.273	0.232 + 0.020*SL	0.240 + 0.019*SL	0.245 + 0.018*SL
E to Y	t_R	0.280	0.129 + 0.075*SL	0.126 + 0.076*SL	0.123 + 0.077*SL
	t_F	0.171	0.106 + 0.032*SL	0.105 + 0.033*SL	0.098 + 0.033*SL
	t_{PLH}	0.256	0.184 + 0.036*SL	0.189 + 0.035*SL	0.191 + 0.035*SL
	t_{PHL}	0.305	0.263 + 0.021*SL	0.272 + 0.019*SL	0.277 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.208	0.130 + 0.039*SL	0.133 + 0.038*SL	0.125 + 0.039*SL
	t_F	0.122	0.085 + 0.018*SL	0.092 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.269	0.227 + 0.021*SL	0.237 + 0.019*SL	0.246 + 0.018*SL
	t_{PHL}	0.293	0.264 + 0.015*SL	0.277 + 0.011*SL	0.297 + 0.009*SL
B to Y	t_R	0.208	0.131 + 0.039*SL	0.132 + 0.038*SL	0.125 + 0.039*SL
	t_F	0.125	0.089 + 0.018*SL	0.097 + 0.016*SL	0.097 + 0.016*SL
	t_{PLH}	0.277	0.235 + 0.021*SL	0.245 + 0.019*SL	0.254 + 0.018*SL
	t_{PHL}	0.315	0.286 + 0.015*SL	0.300 + 0.011*SL	0.320 + 0.009*SL
C to Y	t_R	0.209	0.132 + 0.038*SL	0.133 + 0.038*SL	0.125 + 0.039*SL
	t_F	0.135	0.099 + 0.018*SL	0.106 + 0.016*SL	0.107 + 0.016*SL
	t_{PLH}	0.277	0.234 + 0.021*SL	0.245 + 0.019*SL	0.254 + 0.018*SL
	t_{PHL}	0.347	0.317 + 0.015*SL	0.332 + 0.012*SL	0.355 + 0.010*SL
D to Y	t_R	0.194	0.117 + 0.039*SL	0.116 + 0.039*SL	0.112 + 0.039*SL
	t_F	0.144	0.111 + 0.017*SL	0.113 + 0.016*SL	0.110 + 0.016*SL
	t_{PLH}	0.250	0.209 + 0.020*SL	0.217 + 0.018*SL	0.223 + 0.018*SL
	t_{PHL}	0.293	0.267 + 0.013*SL	0.276 + 0.010*SL	0.290 + 0.009*SL
E to Y	t_R	0.193	0.116 + 0.039*SL	0.115 + 0.039*SL	0.111 + 0.039*SL
	t_F	0.150	0.116 + 0.017*SL	0.120 + 0.016*SL	0.114 + 0.016*SL
	t_{PLH}	0.247	0.206 + 0.020*SL	0.214 + 0.018*SL	0.220 + 0.018*SL
	t_{PHL}	0.323	0.297 + 0.013*SL	0.306 + 0.011*SL	0.321 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AD5D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	0.077 + 0.010*SL	0.081 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.084	0.064 + 0.010*SL	0.070 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.464	0.449 + 0.007*SL	0.457 + 0.005*SL	0.473 + 0.004*SL
	t_{PHL}	0.448	0.432 + 0.008*SL	0.441 + 0.006*SL	0.460 + 0.005*SL
B to Y	t_R	0.097	0.079 + 0.009*SL	0.078 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.085	0.066 + 0.009*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.472	0.458 + 0.007*SL	0.466 + 0.005*SL	0.482 + 0.004*SL
	t_{PHL}	0.479	0.464 + 0.008*SL	0.473 + 0.006*SL	0.491 + 0.005*SL
C to Y	t_R	0.097	0.078 + 0.010*SL	0.081 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.084	0.063 + 0.010*SL	0.072 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.474	0.460 + 0.007*SL	0.468 + 0.005*SL	0.484 + 0.004*SL
	t_{PHL}	0.499	0.484 + 0.008*SL	0.492 + 0.006*SL	0.511 + 0.005*SL
D to Y	t_R	0.097	0.078 + 0.009*SL	0.079 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.086	0.067 + 0.009*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.441	0.427 + 0.007*SL	0.435 + 0.005*SL	0.451 + 0.004*SL
	t_{PHL}	0.446	0.431 + 0.008*SL	0.439 + 0.006*SL	0.458 + 0.005*SL
E to Y	t_R	0.097	0.077 + 0.010*SL	0.079 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.084	0.064 + 0.010*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.442	0.427 + 0.007*SL	0.435 + 0.005*SL	0.451 + 0.004*SL
	t_{PHL}	0.479	0.463 + 0.008*SL	0.472 + 0.006*SL	0.491 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	1
1	0	1
1	1	0

Cell Data

Input Load (SL)								Gate Count			
ND2DH		*ND2*		*ND2D2*		*ND2D4*		*ND2DH*	*ND2*	*ND2D2*	*ND2D4*
A	B	A	B	A	B	A	B				
0.6	0.6	1.1	1.1	2.3	2.3	4.7	4.6	1.00	1.00	1.67	2.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.279	0.117 + 0.081*SL	0.097 + 0.086*SL	0.076 + 0.089*SL
	t_F	0.276	0.119 + 0.079*SL	0.100 + 0.083*SL	0.080 + 0.086*SL
	t_{PLH}	0.185	0.104 + 0.040*SL	0.108 + 0.039*SL	0.108 + 0.039*SL
	t_{PHL}	0.179	0.093 + 0.043*SL	0.098 + 0.042*SL	0.098 + 0.042*SL
B to Y	t_R	0.297	0.134 + 0.082*SL	0.116 + 0.086*SL	0.096 + 0.089*SL
	t_F	0.267	0.105 + 0.081*SL	0.090 + 0.085*SL	0.079 + 0.086*SL
	t_{PLH}	0.200	0.120 + 0.040*SL	0.122 + 0.039*SL	0.122 + 0.039*SL
	t_{PHL}	0.174	0.087 + 0.043*SL	0.092 + 0.042*SL	0.093 + 0.042*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

ND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.180	0.113 + 0.033*SL	0.103 + 0.036*SL	0.090 + 0.038*SL
	t_F	0.186	0.116 + 0.035*SL	0.104 + 0.038*SL	0.093 + 0.039*SL
	t_{PLH}	0.125	0.082 + 0.022*SL	0.099 + 0.017*SL	0.100 + 0.017*SL
	t_{PHL}	0.125	0.077 + 0.024*SL	0.093 + 0.020*SL	0.093 + 0.020*SL
B to Y	t_R	0.195	0.127 + 0.034*SL	0.119 + 0.036*SL	0.107 + 0.038*SL
	t_F	0.173	0.099 + 0.037*SL	0.091 + 0.039*SL	0.082 + 0.040*SL
	t_{PLH}	0.142	0.102 + 0.020*SL	0.112 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.120	0.074 + 0.023*SL	0.085 + 0.020*SL	0.087 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.147	0.115 + 0.016*SL	0.111 + 0.017*SL	0.096 + 0.019*SL
	t_F	0.151	0.115 + 0.018*SL	0.113 + 0.018*SL	0.099 + 0.019*SL
	t_{PLH}	0.104	0.078 + 0.013*SL	0.092 + 0.009*SL	0.100 + 0.009*SL
	t_{PHL}	0.101	0.074 + 0.014*SL	0.087 + 0.011*SL	0.094 + 0.010*SL
B to Y	t_R	0.163	0.130 + 0.016*SL	0.126 + 0.017*SL	0.112 + 0.019*SL
	t_F	0.138	0.103 + 0.017*SL	0.098 + 0.019*SL	0.086 + 0.020*SL
	t_{PLH}	0.122	0.099 + 0.011*SL	0.109 + 0.009*SL	0.113 + 0.009*SL
	t_{PHL}	0.097	0.072 + 0.013*SL	0.081 + 0.011*SL	0.087 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

ND2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	0.109 + 0.009*SL	0.112 + 0.008*SL	0.097 + 0.009*SL
	t_F	0.128	0.107 + 0.011*SL	0.114 + 0.009*SL	0.099 + 0.010*SL
	t_{PLH}	0.088	0.073 + 0.007*SL	0.082 + 0.005*SL	0.099 + 0.004*SL
	t_{PHL}	0.086	0.070 + 0.008*SL	0.078 + 0.006*SL	0.093 + 0.005*SL
B to Y	t_R	0.144	0.128 + 0.008*SL	0.125 + 0.009*SL	0.113 + 0.009*SL
	t_F	0.118	0.101 + 0.009*SL	0.099 + 0.009*SL	0.086 + 0.010*SL
	t_{PLH}	0.108	0.096 + 0.006*SL	0.102 + 0.005*SL	0.111 + 0.004*SL
	t_{PHL}	0.083	0.069 + 0.007*SL	0.075 + 0.006*SL	0.086 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	Y
0	x	x	1
x	0	x	1
x	x	0	1
1	1	1	0

Cell Data

Input Load (SL)											
ND3DH			*ND3*			*ND3D2*			*ND3D4*		
A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.5	0.5	1.0	1.0	1.0	2.2	2.1	2.0	4.4	4.3	4.3
Gate Count											
ND3DH			*ND3*			*ND3D2*			*ND3D4*		
1.33			1.33			2.33			4.00		

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.358	0.159 + 0.099*SL	0.140 + 0.104*SL	0.124 + 0.106*SL
	t_F	0.427	0.188 + 0.119*SL	0.171 + 0.124*SL	0.158 + 0.125*SL
	t_{PLH}	0.226	0.131 + 0.047*SL	0.132 + 0.047*SL	0.132 + 0.047*SL
	t_{PHL}	0.247	0.128 + 0.059*SL	0.128 + 0.060*SL	0.128 + 0.059*SL
B to Y	t_R	0.380	0.179 + 0.100*SL	0.162 + 0.104*SL	0.148 + 0.106*SL
	t_F	0.423	0.181 + 0.121*SL	0.170 + 0.124*SL	0.159 + 0.125*SL
	t_{PLH}	0.244	0.149 + 0.047*SL	0.150 + 0.047*SL	0.151 + 0.047*SL
	t_{PHL}	0.257	0.137 + 0.060*SL	0.138 + 0.060*SL	0.139 + 0.060*SL
C to Y	t_R	0.403	0.202 + 0.100*SL	0.186 + 0.104*SL	0.172 + 0.106*SL
	t_F	0.419	0.174 + 0.122*SL	0.166 + 0.124*SL	0.159 + 0.125*SL
	t_{PLH}	0.259	0.163 + 0.048*SL	0.165 + 0.047*SL	0.166 + 0.047*SL
	t_{PHL}	0.259	0.139 + 0.060*SL	0.140 + 0.060*SL	0.141 + 0.060*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

ND3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.225	0.138 + 0.043*SL	0.127 + 0.046*SL	0.114 + 0.048*SL
	t_F	0.271	0.162 + 0.054*SL	0.153 + 0.057*SL	0.140 + 0.058*SL
	t_{PLH}	0.156	0.109 + 0.024*SL	0.116 + 0.022*SL	0.116 + 0.022*SL
	t_{PHL}	0.165	0.107 + 0.029*SL	0.110 + 0.028*SL	0.110 + 0.028*SL
B to Y	t_R	0.244	0.156 + 0.044*SL	0.146 + 0.047*SL	0.135 + 0.048*SL
	t_F	0.264	0.153 + 0.055*SL	0.145 + 0.058*SL	0.137 + 0.059*SL
	t_{PLH}	0.175	0.130 + 0.022*SL	0.132 + 0.022*SL	0.133 + 0.022*SL
	t_{PHL}	0.172	0.113 + 0.030*SL	0.118 + 0.028*SL	0.119 + 0.028*SL
C to Y	t_R	0.266	0.177 + 0.044*SL	0.168 + 0.047*SL	0.157 + 0.048*SL
	t_F	0.257	0.143 + 0.057*SL	0.138 + 0.058*SL	0.133 + 0.059*SL
	t_{PLH}	0.188	0.143 + 0.022*SL	0.144 + 0.022*SL	0.146 + 0.022*SL
	t_{PHL}	0.173	0.114 + 0.029*SL	0.118 + 0.028*SL	0.118 + 0.028*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.175	0.134 + 0.021*SL	0.126 + 0.023*SL	0.112 + 0.024*SL
	t_F	0.211	0.159 + 0.026*SL	0.152 + 0.028*SL	0.137 + 0.029*SL
	t_{PLH}	0.129	0.101 + 0.014*SL	0.112 + 0.011*SL	0.114 + 0.011*SL
	t_{PHL}	0.132	0.099 + 0.016*SL	0.108 + 0.014*SL	0.108 + 0.014*SL
B to Y	t_R	0.194	0.152 + 0.021*SL	0.146 + 0.023*SL	0.132 + 0.024*SL
	t_F	0.202	0.148 + 0.027*SL	0.142 + 0.028*SL	0.133 + 0.029*SL
	t_{PLH}	0.148	0.123 + 0.012*SL	0.129 + 0.011*SL	0.129 + 0.011*SL
	t_{PHL}	0.136	0.104 + 0.016*SL	0.111 + 0.014*SL	0.113 + 0.014*SL
C to Y	t_R	0.216	0.173 + 0.022*SL	0.169 + 0.023*SL	0.155 + 0.024*SL
	t_F	0.193	0.138 + 0.027*SL	0.133 + 0.029*SL	0.127 + 0.029*SL
	t_{PLH}	0.161	0.138 + 0.012*SL	0.141 + 0.011*SL	0.142 + 0.011*SL
	t_{PHL}	0.137	0.106 + 0.016*SL	0.111 + 0.014*SL	0.113 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

ND3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.152	0.131 + 0.011*SL	0.129 + 0.011*SL	0.113 + 0.012*SL
	t_F	0.183	0.157 + 0.013*SL	0.153 + 0.014*SL	0.138 + 0.014*SL
	t_{PLH}	0.113	0.097 + 0.008*SL	0.105 + 0.006*SL	0.113 + 0.005*SL
	t_{PHL}	0.114	0.096 + 0.009*SL	0.102 + 0.007*SL	0.106 + 0.007*SL
B to Y	t_R	0.172	0.151 + 0.010*SL	0.148 + 0.011*SL	0.134 + 0.012*SL
	t_F	0.174	0.149 + 0.013*SL	0.143 + 0.014*SL	0.132 + 0.015*SL
	t_{PLH}	0.134	0.120 + 0.007*SL	0.125 + 0.006*SL	0.128 + 0.005*SL
	t_{PHL}	0.119	0.102 + 0.009*SL	0.107 + 0.007*SL	0.112 + 0.007*SL
C to Y	t_R	0.194	0.174 + 0.010*SL	0.170 + 0.011*SL	0.157 + 0.012*SL
	t_F	0.164	0.137 + 0.014*SL	0.134 + 0.014*SL	0.125 + 0.015*SL
	t_{PLH}	0.149	0.136 + 0.006*SL	0.139 + 0.006*SL	0.142 + 0.005*SL
	t_{PHL}	0.121	0.105 + 0.008*SL	0.109 + 0.007*SL	0.113 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

ND4DH/ND4/ND4D2/ND4D2B/ND4D4

4-Input NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	x	x	1
x	0	x	x	1
x	x	0	x	1
x	x	x	0	1
1	1	1	1	0

Cell Data

Input Load (SL)																			
ND4DH				*ND4*				*ND4D2*				*ND4D2B*				*ND4D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	0.9	0.9	0.9	0.9	1.7	1.9	1.9	2.1	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9

Gate Count				
ND4DH	*ND4*	*ND4D2*	*ND4D2B*	*ND4D4*
1.67	1.67	2.67	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.424	0.170 + 0.127*SL	0.148 + 0.133*SL	0.141 + 0.134*SL
	t_F	0.546	0.228 + 0.159*SL	0.209 + 0.164*SL	0.206 + 0.164*SL
	t_{PLH}	0.262	0.143 + 0.060*SL	0.144 + 0.059*SL	0.145 + 0.059*SL
	t_{PHL}	0.286	0.131 + 0.077*SL	0.132 + 0.077*SL	0.132 + 0.077*SL
B to Y	t_R	0.453	0.197 + 0.128*SL	0.178 + 0.133*SL	0.172 + 0.134*SL
	t_F	0.547	0.226 + 0.160*SL	0.214 + 0.163*SL	0.208 + 0.164*SL
	t_{PLH}	0.285	0.166 + 0.060*SL	0.167 + 0.059*SL	0.168 + 0.059*SL
	t_{PHL}	0.308	0.153 + 0.078*SL	0.154 + 0.077*SL	0.155 + 0.077*SL
C to Y	t_R	0.484	0.227 + 0.129*SL	0.210 + 0.133*SL	0.204 + 0.134*SL
	t_F	0.544	0.222 + 0.161*SL	0.212 + 0.164*SL	0.208 + 0.164*SL
	t_{PLH}	0.305	0.184 + 0.060*SL	0.187 + 0.059*SL	0.189 + 0.059*SL
	t_{PHL}	0.323	0.167 + 0.078*SL	0.169 + 0.078*SL	0.170 + 0.077*SL
D to Y	t_R	0.516	0.259 + 0.128*SL	0.242 + 0.133*SL	0.236 + 0.133*SL
	t_F	0.541	0.217 + 0.162*SL	0.210 + 0.164*SL	0.208 + 0.164*SL
	t_{PLH}	0.318	0.196 + 0.061*SL	0.202 + 0.060*SL	0.205 + 0.059*SL
	t_{PHL}	0.327	0.171 + 0.078*SL	0.172 + 0.077*SL	0.173 + 0.077*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.255	0.143 + 0.056*SL	0.132 + 0.059*SL	0.118 + 0.061*SL
	t_F	0.341	0.195 + 0.073*SL	0.185 + 0.076*SL	0.171 + 0.077*SL
	t_{PLH}	0.177	0.121 + 0.028*SL	0.124 + 0.027*SL	0.125 + 0.027*SL
	t_{PHL}	0.184	0.111 + 0.036*SL	0.110 + 0.037*SL	0.111 + 0.037*SL
B to Y	t_R	0.282	0.169 + 0.056*SL	0.157 + 0.059*SL	0.146 + 0.061*SL
	t_F	0.340	0.192 + 0.074*SL	0.183 + 0.076*SL	0.175 + 0.077*SL
	t_{PLH}	0.201	0.145 + 0.028*SL	0.146 + 0.027*SL	0.147 + 0.027*SL
	t_{PHL}	0.203	0.128 + 0.038*SL	0.131 + 0.037*SL	0.132 + 0.037*SL
C to Y	t_R	0.310	0.196 + 0.057*SL	0.187 + 0.059*SL	0.175 + 0.061*SL
	t_F	0.335	0.184 + 0.075*SL	0.179 + 0.076*SL	0.173 + 0.077*SL
	t_{PLH}	0.218	0.161 + 0.028*SL	0.163 + 0.028*SL	0.165 + 0.027*SL
	t_{PHL}	0.216	0.141 + 0.038*SL	0.143 + 0.037*SL	0.144 + 0.037*SL
D to Y	t_R	0.339	0.225 + 0.057*SL	0.215 + 0.059*SL	0.204 + 0.061*SL
	t_F	0.330	0.178 + 0.076*SL	0.175 + 0.077*SL	0.170 + 0.078*SL
	t_{PLH}	0.229	0.171 + 0.029*SL	0.175 + 0.028*SL	0.178 + 0.028*SL
	t_{PHL}	0.220	0.145 + 0.037*SL	0.147 + 0.037*SL	0.148 + 0.037*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

ND4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.195	0.142 + 0.027*SL	0.134 + 0.029*SL	0.118 + 0.030*SL
	t_F	0.260	0.188 + 0.036*SL	0.183 + 0.037*SL	0.167 + 0.039*SL
	t_{PLH}	0.144	0.112 + 0.016*SL	0.120 + 0.014*SL	0.121 + 0.014*SL
	t_{PHL}	0.143	0.105 + 0.019*SL	0.108 + 0.018*SL	0.107 + 0.018*SL
B to Y	t_R	0.219	0.164 + 0.027*SL	0.157 + 0.029*SL	0.143 + 0.030*SL
	t_F	0.257	0.185 + 0.036*SL	0.179 + 0.038*SL	0.169 + 0.039*SL
	t_{PLH}	0.168	0.139 + 0.014*SL	0.142 + 0.014*SL	0.142 + 0.014*SL
	t_{PHL}	0.160	0.120 + 0.020*SL	0.125 + 0.019*SL	0.127 + 0.018*SL
C to Y	t_R	0.246	0.191 + 0.028*SL	0.186 + 0.029*SL	0.172 + 0.030*SL
	t_F	0.252	0.178 + 0.037*SL	0.173 + 0.038*SL	0.166 + 0.039*SL
	t_{PLH}	0.185	0.156 + 0.014*SL	0.158 + 0.014*SL	0.160 + 0.014*SL
	t_{PHL}	0.173	0.134 + 0.020*SL	0.138 + 0.019*SL	0.140 + 0.018*SL
D to Y	t_R	0.276	0.221 + 0.028*SL	0.215 + 0.029*SL	0.201 + 0.030*SL
	t_F	0.247	0.172 + 0.037*SL	0.168 + 0.038*SL	0.162 + 0.039*SL
	t_{PLH}	0.196	0.167 + 0.015*SL	0.169 + 0.014*SL	0.173 + 0.014*SL
	t_{PHL}	0.178	0.140 + 0.019*SL	0.142 + 0.019*SL	0.144 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND4D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	0.061 + 0.018*SL	0.060 + 0.019*SL	0.052 + 0.019*SL
	t_F	0.091	0.059 + 0.016*SL	0.059 + 0.016*SL	0.054 + 0.016*SL
	t_{PLH}	0.315	0.293 + 0.011*SL	0.301 + 0.009*SL	0.306 + 0.009*SL
	t_{PHL}	0.334	0.310 + 0.012*SL	0.320 + 0.009*SL	0.329 + 0.009*SL
B to Y	t_R	0.099	0.062 + 0.018*SL	0.060 + 0.019*SL	0.052 + 0.019*SL
	t_F	0.092	0.061 + 0.016*SL	0.060 + 0.016*SL	0.055 + 0.016*SL
	t_{PLH}	0.340	0.318 + 0.011*SL	0.326 + 0.009*SL	0.331 + 0.009*SL
	t_{PHL}	0.351	0.327 + 0.012*SL	0.337 + 0.009*SL	0.347 + 0.009*SL
C to Y	t_R	0.100	0.063 + 0.018*SL	0.061 + 0.019*SL	0.052 + 0.019*SL
	t_F	0.092	0.060 + 0.016*SL	0.061 + 0.016*SL	0.055 + 0.016*SL
	t_{PLH}	0.361	0.339 + 0.011*SL	0.347 + 0.009*SL	0.352 + 0.009*SL
	t_{PHL}	0.363	0.339 + 0.012*SL	0.349 + 0.009*SL	0.359 + 0.009*SL
D to Y	t_R	0.100	0.064 + 0.018*SL	0.062 + 0.019*SL	0.053 + 0.019*SL
	t_F	0.090	0.057 + 0.017*SL	0.062 + 0.016*SL	0.055 + 0.016*SL
	t_{PLH}	0.377	0.355 + 0.011*SL	0.363 + 0.009*SL	0.368 + 0.009*SL
	t_{PHL}	0.367	0.343 + 0.012*SL	0.354 + 0.009*SL	0.363 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

ND4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.094	0.076 + 0.009*SL	0.076 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.090	0.071 + 0.010*SL	0.077 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.360	0.346 + 0.007*SL	0.354 + 0.005*SL	0.369 + 0.004*SL
	t_{PHL}	0.388	0.372 + 0.008*SL	0.381 + 0.006*SL	0.401 + 0.005*SL
B to Y	t_R	0.095	0.075 + 0.010*SL	0.079 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.092	0.072 + 0.010*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.385	0.370 + 0.007*SL	0.378 + 0.005*SL	0.393 + 0.004*SL
	t_{PHL}	0.407	0.391 + 0.008*SL	0.400 + 0.006*SL	0.420 + 0.005*SL
C to Y	t_R	0.096	0.075 + 0.010*SL	0.080 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.079 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.408	0.394 + 0.007*SL	0.402 + 0.005*SL	0.417 + 0.004*SL
	t_{PHL}	0.418	0.402 + 0.008*SL	0.412 + 0.006*SL	0.431 + 0.005*SL
D to Y	t_R	0.097	0.077 + 0.010*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.077 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.425	0.410 + 0.007*SL	0.418 + 0.005*SL	0.434 + 0.004*SL
	t_{PHL}	0.426	0.410 + 0.008*SL	0.419 + 0.006*SL	0.439 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	x	x	x	1
x	0	x	x	x	1
x	x	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
1	1	1	1	1	0

Cell Data

Input Load (SL)															Gate Count		
ND5					*ND5D2*					*ND5D4*					*ND5*	*ND5D2*	*ND5D4*
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	3.33	3.67	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.141	0.067 + 0.037*SL	0.062 + 0.038*SL	0.057 + 0.039*SL
	t_F	0.144	0.079 + 0.032*SL	0.083 + 0.031*SL	0.083 + 0.031*SL
	t_{PLH}	0.347	0.309 + 0.019*SL	0.314 + 0.018*SL	0.315 + 0.017*SL
	t_{PHL}	0.357	0.312 + 0.022*SL	0.326 + 0.019*SL	0.337 + 0.017*SL
B to Y	t_R	0.143	0.069 + 0.037*SL	0.064 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.145	0.081 + 0.032*SL	0.085 + 0.031*SL	0.082 + 0.031*SL
	t_{PLH}	0.378	0.340 + 0.019*SL	0.345 + 0.018*SL	0.346 + 0.017*SL
	t_{PHL}	0.365	0.320 + 0.022*SL	0.334 + 0.019*SL	0.345 + 0.017*SL
C to Y	t_R	0.144	0.071 + 0.037*SL	0.064 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.144	0.079 + 0.032*SL	0.084 + 0.031*SL	0.083 + 0.031*SL
	t_{PLH}	0.404	0.366 + 0.019*SL	0.371 + 0.018*SL	0.373 + 0.017*SL
	t_{PHL}	0.366	0.322 + 0.022*SL	0.335 + 0.019*SL	0.346 + 0.017*SL
D to Y	t_R	0.145	0.071 + 0.037*SL	0.066 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.144	0.080 + 0.032*SL	0.084 + 0.031*SL	0.080 + 0.032*SL
	t_{PLH}	0.343	0.305 + 0.019*SL	0.310 + 0.018*SL	0.312 + 0.017*SL
	t_{PHL}	0.340	0.296 + 0.022*SL	0.309 + 0.019*SL	0.320 + 0.017*SL
E to Y	t_R	0.145	0.072 + 0.037*SL	0.064 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.143	0.079 + 0.032*SL	0.083 + 0.031*SL	0.081 + 0.031*SL
	t_{PLH}	0.371	0.333 + 0.019*SL	0.338 + 0.018*SL	0.340 + 0.017*SL
	t_{PHL}	0.338	0.294 + 0.022*SL	0.307 + 0.019*SL	0.317 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.064 + 0.018*SL	0.063 + 0.018*SL	0.053 + 0.019*SL
	t_F	0.114	0.078 + 0.018*SL	0.088 + 0.016*SL	0.092 + 0.016*SL
	t_{PLH}	0.347	0.324 + 0.011*SL	0.332 + 0.009*SL	0.338 + 0.009*SL
	t_{PHL}	0.368	0.339 + 0.014*SL	0.353 + 0.011*SL	0.374 + 0.009*SL
B to Y	t_R	0.101	0.064 + 0.018*SL	0.063 + 0.019*SL	0.054 + 0.019*SL
	t_F	0.114	0.078 + 0.018*SL	0.088 + 0.016*SL	0.092 + 0.016*SL
	t_{PLH}	0.378	0.355 + 0.011*SL	0.364 + 0.009*SL	0.370 + 0.009*SL
	t_{PHL}	0.376	0.347 + 0.014*SL	0.361 + 0.011*SL	0.382 + 0.009*SL
C to Y	t_R	0.102	0.066 + 0.018*SL	0.065 + 0.018*SL	0.055 + 0.019*SL
	t_F	0.114	0.077 + 0.019*SL	0.088 + 0.016*SL	0.092 + 0.016*SL
	t_{PLH}	0.405	0.382 + 0.011*SL	0.391 + 0.009*SL	0.397 + 0.009*SL
	t_{PHL}	0.377	0.348 + 0.014*SL	0.362 + 0.011*SL	0.383 + 0.009*SL
D to Y	t_R	0.102	0.067 + 0.018*SL	0.063 + 0.019*SL	0.056 + 0.019*SL
	t_F	0.113	0.076 + 0.018*SL	0.086 + 0.016*SL	0.091 + 0.016*SL
	t_{PLH}	0.340	0.317 + 0.011*SL	0.325 + 0.009*SL	0.332 + 0.009*SL
	t_{PHL}	0.349	0.321 + 0.014*SL	0.335 + 0.011*SL	0.356 + 0.009*SL
E to Y	t_R	0.103	0.066 + 0.018*SL	0.066 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.085 + 0.016*SL	0.091 + 0.016*SL
	t_{PLH}	0.369	0.346 + 0.012*SL	0.355 + 0.009*SL	0.361 + 0.009*SL
	t_{PHL}	0.347	0.319 + 0.014*SL	0.333 + 0.011*SL	0.354 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND5D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.095	0.077 + 0.009*SL	0.076 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.125	0.106 + 0.010*SL	0.110 + 0.009*SL	0.126 + 0.008*SL
	t_{PLH}	0.379	0.364 + 0.007*SL	0.372 + 0.005*SL	0.388 + 0.004*SL
	t_{PHL}	0.435	0.416 + 0.009*SL	0.426 + 0.007*SL	0.458 + 0.005*SL
B to Y	t_R	0.095	0.075 + 0.010*SL	0.080 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.125	0.103 + 0.011*SL	0.111 + 0.009*SL	0.128 + 0.008*SL
	t_{PLH}	0.411	0.396 + 0.007*SL	0.404 + 0.005*SL	0.420 + 0.004*SL
	t_{PHL}	0.443	0.425 + 0.009*SL	0.434 + 0.007*SL	0.467 + 0.005*SL
C to Y	t_R	0.096	0.079 + 0.009*SL	0.077 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.125	0.106 + 0.010*SL	0.110 + 0.009*SL	0.127 + 0.008*SL
	t_{PLH}	0.439	0.424 + 0.007*SL	0.432 + 0.005*SL	0.448 + 0.004*SL
	t_{PHL}	0.444	0.425 + 0.009*SL	0.435 + 0.007*SL	0.468 + 0.005*SL
D to Y	t_R	0.097	0.076 + 0.010*SL	0.082 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.124	0.103 + 0.011*SL	0.111 + 0.009*SL	0.127 + 0.008*SL
	t_{PLH}	0.369	0.355 + 0.007*SL	0.363 + 0.005*SL	0.379 + 0.004*SL
	t_{PHL}	0.416	0.397 + 0.009*SL	0.407 + 0.007*SL	0.440 + 0.005*SL
E to Y	t_R	0.098	0.080 + 0.009*SL	0.080 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.123	0.100 + 0.011*SL	0.111 + 0.009*SL	0.127 + 0.008*SL
	t_{PLH}	0.398	0.384 + 0.007*SL	0.392 + 0.005*SL	0.408 + 0.004*SL
	t_{PHL}	0.414	0.395 + 0.009*SL	0.405 + 0.007*SL	0.438 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 19, *Group3 : 19 < SL

ND6/ND6D2/ND6D4

6-Input NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	1	1	1	0
Other States						1

Cell Data

Input Load (SL)																	
ND6						*ND6D2*						*ND6D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.8	0.9	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.9	0.9	0.9

Gate Count		
ND6	*ND6D2*	*ND6D4*
3.33	3.67	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.140	0.067 + 0.037*SL	0.063 + 0.038*SL	0.058 + 0.038*SL
	t_F	0.149	0.082 + 0.034*SL	0.086 + 0.033*SL	0.083 + 0.033*SL
	t_{PLH}	0.351	0.314 + 0.019*SL	0.319 + 0.017*SL	0.321 + 0.017*SL
	t_{PHL}	0.364	0.318 + 0.023*SL	0.332 + 0.019*SL	0.343 + 0.018*SL
B to Y	t_R	0.142	0.070 + 0.036*SL	0.064 + 0.038*SL	0.058 + 0.038*SL
	t_F	0.149	0.082 + 0.034*SL	0.085 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.382	0.345 + 0.019*SL	0.350 + 0.017*SL	0.352 + 0.017*SL
	t_{PHL}	0.372	0.326 + 0.023*SL	0.340 + 0.019*SL	0.350 + 0.018*SL
C to Y	t_R	0.143	0.071 + 0.036*SL	0.064 + 0.038*SL	0.059 + 0.038*SL
	t_F	0.149	0.082 + 0.033*SL	0.086 + 0.033*SL	0.083 + 0.033*SL
	t_{PLH}	0.408	0.371 + 0.019*SL	0.376 + 0.017*SL	0.378 + 0.017*SL
	t_{PHL}	0.372	0.327 + 0.023*SL	0.341 + 0.019*SL	0.351 + 0.018*SL
D to Y	t_R	0.144	0.072 + 0.036*SL	0.066 + 0.038*SL	0.060 + 0.038*SL
	t_F	0.149	0.081 + 0.034*SL	0.087 + 0.032*SL	0.084 + 0.033*SL
	t_{PLH}	0.368	0.330 + 0.019*SL	0.336 + 0.017*SL	0.337 + 0.017*SL
	t_{PHL}	0.383	0.337 + 0.023*SL	0.352 + 0.019*SL	0.362 + 0.018*SL
E to Y	t_R	0.143	0.070 + 0.037*SL	0.066 + 0.038*SL	0.060 + 0.038*SL
	t_F	0.149	0.081 + 0.034*SL	0.086 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.399	0.361 + 0.019*SL	0.367 + 0.017*SL	0.369 + 0.017*SL
	t_{PHL}	0.391	0.345 + 0.023*SL	0.360 + 0.019*SL	0.370 + 0.018*SL
F to Y	t_R	0.145	0.072 + 0.036*SL	0.067 + 0.037*SL	0.061 + 0.038*SL
	t_F	0.149	0.083 + 0.033*SL	0.085 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.426	0.388 + 0.019*SL	0.394 + 0.017*SL	0.395 + 0.017*SL
	t_{PHL}	0.394	0.348 + 0.023*SL	0.363 + 0.019*SL	0.373 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.101	0.065 + 0.018*SL	0.063 + 0.018*SL	0.055 + 0.019*SL
	t_F	0.116	0.079 + 0.019*SL	0.089 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.353	0.330 + 0.011*SL	0.339 + 0.009*SL	0.345 + 0.009*SL
	t_{PHL}	0.372	0.343 + 0.015*SL	0.357 + 0.011*SL	0.379 + 0.009*SL
B to Y	t_R	0.102	0.066 + 0.018*SL	0.065 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.115	0.079 + 0.018*SL	0.087 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.384	0.361 + 0.011*SL	0.370 + 0.009*SL	0.377 + 0.009*SL
	t_{PHL}	0.380	0.351 + 0.015*SL	0.365 + 0.011*SL	0.387 + 0.009*SL
C to Y	t_R	0.103	0.066 + 0.018*SL	0.066 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.116	0.079 + 0.019*SL	0.089 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.411	0.388 + 0.012*SL	0.397 + 0.009*SL	0.404 + 0.009*SL
	t_{PHL}	0.381	0.352 + 0.015*SL	0.366 + 0.011*SL	0.388 + 0.009*SL
D to Y	t_R	0.104	0.068 + 0.018*SL	0.067 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.116	0.079 + 0.019*SL	0.089 + 0.016*SL	0.094 + 0.016*SL
	t_{PLH}	0.366	0.343 + 0.012*SL	0.352 + 0.009*SL	0.359 + 0.009*SL
	t_{PHL}	0.391	0.362 + 0.015*SL	0.376 + 0.011*SL	0.398 + 0.009*SL
E to Y	t_R	0.104	0.069 + 0.018*SL	0.066 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.115	0.079 + 0.018*SL	0.087 + 0.016*SL	0.094 + 0.016*SL
	t_{PLH}	0.398	0.375 + 0.012*SL	0.384 + 0.009*SL	0.391 + 0.009*SL
	t_{PHL}	0.399	0.370 + 0.015*SL	0.384 + 0.011*SL	0.406 + 0.009*SL
F to Y	t_R	0.105	0.069 + 0.018*SL	0.068 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.115	0.078 + 0.019*SL	0.088 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.425	0.402 + 0.012*SL	0.411 + 0.009*SL	0.418 + 0.009*SL
	t_{PHL}	0.402	0.373 + 0.015*SL	0.387 + 0.011*SL	0.409 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND6D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.075 + 0.010*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.126	0.106 + 0.010*SL	0.110 + 0.009*SL	0.129 + 0.008*SL
	t_{PLH}	0.386	0.372 + 0.007*SL	0.380 + 0.005*SL	0.396 + 0.004*SL
	t_{PHL}	0.438	0.420 + 0.009*SL	0.430 + 0.007*SL	0.462 + 0.005*SL
B to Y	t_R	0.097	0.079 + 0.009*SL	0.078 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.124	0.101 + 0.012*SL	0.112 + 0.009*SL	0.129 + 0.008*SL
	t_{PLH}	0.418	0.404 + 0.007*SL	0.412 + 0.005*SL	0.428 + 0.004*SL
	t_{PHL}	0.446	0.428 + 0.009*SL	0.438 + 0.007*SL	0.471 + 0.005*SL
C to Y	t_R	0.098	0.077 + 0.010*SL	0.082 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.126	0.105 + 0.010*SL	0.111 + 0.009*SL	0.129 + 0.008*SL
	t_{PLH}	0.446	0.431 + 0.007*SL	0.439 + 0.005*SL	0.456 + 0.004*SL
	t_{PHL}	0.447	0.429 + 0.009*SL	0.439 + 0.007*SL	0.471 + 0.005*SL
D to Y	t_R	0.098	0.080 + 0.009*SL	0.081 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.126	0.106 + 0.010*SL	0.110 + 0.009*SL	0.128 + 0.008*SL
	t_{PLH}	0.397	0.383 + 0.007*SL	0.391 + 0.005*SL	0.407 + 0.004*SL
	t_{PHL}	0.458	0.439 + 0.009*SL	0.449 + 0.007*SL	0.482 + 0.005*SL
E to Y	t_R	0.098	0.078 + 0.010*SL	0.083 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.125	0.103 + 0.011*SL	0.112 + 0.009*SL	0.129 + 0.008*SL
	t_{PLH}	0.429	0.415 + 0.007*SL	0.423 + 0.005*SL	0.439 + 0.004*SL
	t_{PHL}	0.465	0.447 + 0.009*SL	0.457 + 0.007*SL	0.490 + 0.005*SL
F to Y	t_R	0.100	0.081 + 0.010*SL	0.083 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.125	0.102 + 0.011*SL	0.112 + 0.009*SL	0.129 + 0.008*SL
	t_{PLH}	0.457	0.443 + 0.007*SL	0.451 + 0.005*SL	0.467 + 0.004*SL
	t_{PHL}	0.468	0.450 + 0.009*SL	0.460 + 0.007*SL	0.493 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

ND8/ND8D2/ND8D4

8-Input NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	1	1	1	1	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
ND8								*ND8*
A	B	C	D	E	F	G	H	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	4.00
ND8D2								*ND8D2*
A	B	C	D	E	F	G	H	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	4.33
ND8D4								*ND8D4*
A	B	C	D	E	F	G	H	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.143	0.069 + 0.037*SL	0.065 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.151	0.084 + 0.033*SL	0.087 + 0.033*SL	0.085 + 0.033*SL
	t_{PLH}	0.378	0.340 + 0.019*SL	0.346 + 0.018*SL	0.347 + 0.017*SL
	t_{PHL}	0.394	0.348 + 0.023*SL	0.362 + 0.020*SL	0.373 + 0.018*SL
B to Y	t_R	0.143	0.069 + 0.037*SL	0.065 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.150	0.083 + 0.034*SL	0.088 + 0.033*SL	0.085 + 0.033*SL
	t_{PLH}	0.416	0.377 + 0.019*SL	0.383 + 0.018*SL	0.385 + 0.017*SL
	t_{PHL}	0.413	0.367 + 0.023*SL	0.381 + 0.020*SL	0.392 + 0.018*SL
C to Y	t_R	0.146	0.073 + 0.036*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.150	0.082 + 0.034*SL	0.089 + 0.032*SL	0.085 + 0.033*SL
	t_{PLH}	0.447	0.409 + 0.019*SL	0.415 + 0.018*SL	0.417 + 0.017*SL
	t_{PHL}	0.425	0.379 + 0.023*SL	0.393 + 0.020*SL	0.404 + 0.018*SL
D to Y	t_R	0.146	0.074 + 0.036*SL	0.066 + 0.038*SL	0.061 + 0.039*SL
	t_F	0.151	0.084 + 0.033*SL	0.088 + 0.033*SL	0.085 + 0.033*SL
	t_{PLH}	0.475	0.436 + 0.019*SL	0.442 + 0.018*SL	0.444 + 0.017*SL
	t_{PHL}	0.432	0.386 + 0.023*SL	0.400 + 0.020*SL	0.411 + 0.018*SL
E to Y	t_R	0.146	0.073 + 0.036*SL	0.065 + 0.038*SL	0.061 + 0.039*SL
	t_F	0.151	0.083 + 0.034*SL	0.089 + 0.032*SL	0.086 + 0.033*SL
	t_{PLH}	0.396	0.358 + 0.019*SL	0.364 + 0.018*SL	0.366 + 0.017*SL
	t_{PHL}	0.409	0.363 + 0.023*SL	0.377 + 0.020*SL	0.389 + 0.018*SL
F to Y	t_R	0.147	0.075 + 0.036*SL	0.067 + 0.038*SL	0.062 + 0.039*SL
	t_F	0.151	0.083 + 0.034*SL	0.089 + 0.032*SL	0.086 + 0.033*SL
	t_{PLH}	0.433	0.395 + 0.019*SL	0.401 + 0.018*SL	0.403 + 0.017*SL
	t_{PHL}	0.426	0.380 + 0.023*SL	0.395 + 0.020*SL	0.406 + 0.018*SL
G to Y	t_R	0.147	0.073 + 0.037*SL	0.069 + 0.038*SL	0.061 + 0.039*SL
	t_F	0.151	0.083 + 0.034*SL	0.089 + 0.032*SL	0.086 + 0.033*SL
	t_{PLH}	0.466	0.428 + 0.019*SL	0.434 + 0.018*SL	0.436 + 0.017*SL
	t_{PHL}	0.439	0.392 + 0.023*SL	0.407 + 0.020*SL	0.418 + 0.018*SL
H to Y	t_R	0.149	0.076 + 0.036*SL	0.070 + 0.038*SL	0.063 + 0.039*SL
	t_F	0.151	0.084 + 0.034*SL	0.089 + 0.032*SL	0.086 + 0.033*SL
	t_{PLH}	0.493	0.455 + 0.019*SL	0.461 + 0.018*SL	0.463 + 0.017*SL
	t_{PHL}	0.446	0.399 + 0.023*SL	0.414 + 0.020*SL	0.425 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.101	0.065 + 0.018*SL	0.063 + 0.019*SL	0.055 + 0.019*SL
	t_F	0.118	0.080 + 0.019*SL	0.089 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.379	0.356 + 0.012*SL	0.365 + 0.009*SL	0.372 + 0.009*SL
	t_{PHL}	0.406	0.376 + 0.015*SL	0.391 + 0.011*SL	0.413 + 0.010*SL
B to Y	t_R	0.102	0.067 + 0.018*SL	0.064 + 0.018*SL	0.055 + 0.019*SL
	t_F	0.118	0.080 + 0.019*SL	0.089 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.417	0.394 + 0.012*SL	0.403 + 0.009*SL	0.410 + 0.009*SL
	t_{PHL}	0.425	0.395 + 0.015*SL	0.410 + 0.011*SL	0.432 + 0.010*SL
C to Y	t_R	0.103	0.067 + 0.018*SL	0.067 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.118	0.079 + 0.019*SL	0.091 + 0.017*SL	0.094 + 0.016*SL
	t_{PLH}	0.450	0.426 + 0.012*SL	0.436 + 0.009*SL	0.443 + 0.009*SL
	t_{PHL}	0.437	0.407 + 0.015*SL	0.422 + 0.011*SL	0.444 + 0.010*SL
D to Y	t_R	0.105	0.069 + 0.018*SL	0.066 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.118	0.080 + 0.019*SL	0.090 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.478	0.454 + 0.012*SL	0.464 + 0.009*SL	0.471 + 0.009*SL
	t_{PHL}	0.444	0.414 + 0.015*SL	0.429 + 0.011*SL	0.451 + 0.010*SL
E to Y	t_R	0.104	0.068 + 0.018*SL	0.066 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.118	0.079 + 0.019*SL	0.091 + 0.017*SL	0.094 + 0.016*SL
	t_{PLH}	0.394	0.371 + 0.012*SL	0.380 + 0.009*SL	0.388 + 0.009*SL
	t_{PHL}	0.419	0.389 + 0.015*SL	0.404 + 0.012*SL	0.426 + 0.010*SL
F to Y	t_R	0.105	0.068 + 0.018*SL	0.068 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.118	0.080 + 0.019*SL	0.090 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.432	0.408 + 0.012*SL	0.418 + 0.009*SL	0.425 + 0.009*SL
	t_{PHL}	0.437	0.406 + 0.015*SL	0.421 + 0.011*SL	0.444 + 0.010*SL
G to Y	t_R	0.106	0.070 + 0.018*SL	0.069 + 0.018*SL	0.059 + 0.019*SL
	t_F	0.118	0.080 + 0.019*SL	0.090 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.465	0.441 + 0.012*SL	0.451 + 0.009*SL	0.458 + 0.009*SL
	t_{PHL}	0.449	0.419 + 0.015*SL	0.434 + 0.011*SL	0.456 + 0.010*SL
H to Y	t_R	0.107	0.070 + 0.018*SL	0.071 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.119	0.080 + 0.019*SL	0.090 + 0.017*SL	0.095 + 0.016*SL
	t_{PLH}	0.493	0.469 + 0.012*SL	0.479 + 0.009*SL	0.487 + 0.009*SL
	t_{PHL}	0.456	0.426 + 0.015*SL	0.440 + 0.012*SL	0.463 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

ND8D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	0.078 + 0.010*SL	0.081 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.126	0.104 + 0.011*SL	0.114 + 0.009*SL	0.131 + 0.008*SL
	t_{PLH}	0.415	0.400 + 0.007*SL	0.408 + 0.005*SL	0.424 + 0.004*SL
	t_{PHL}	0.475	0.456 + 0.009*SL	0.466 + 0.007*SL	0.499 + 0.005*SL
B to Y	t_R	0.098	0.078 + 0.010*SL	0.082 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.128	0.107 + 0.010*SL	0.113 + 0.009*SL	0.130 + 0.008*SL
	t_{PLH}	0.453	0.438 + 0.007*SL	0.447 + 0.005*SL	0.463 + 0.004*SL
	t_{PHL}	0.494	0.475 + 0.009*SL	0.485 + 0.007*SL	0.518 + 0.005*SL
C to Y	t_R	0.099	0.079 + 0.010*SL	0.083 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.128	0.108 + 0.010*SL	0.111 + 0.009*SL	0.131 + 0.008*SL
	t_{PLH}	0.487	0.472 + 0.007*SL	0.480 + 0.005*SL	0.497 + 0.004*SL
	t_{PHL}	0.506	0.487 + 0.009*SL	0.497 + 0.007*SL	0.530 + 0.005*SL
D to Y	t_R	0.101	0.081 + 0.010*SL	0.084 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.127	0.105 + 0.011*SL	0.114 + 0.009*SL	0.131 + 0.008*SL
	t_{PLH}	0.516	0.501 + 0.007*SL	0.509 + 0.005*SL	0.527 + 0.004*SL
	t_{PHL}	0.513	0.494 + 0.009*SL	0.504 + 0.007*SL	0.537 + 0.005*SL
E to Y	t_R	0.100	0.080 + 0.010*SL	0.084 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.128	0.108 + 0.010*SL	0.113 + 0.009*SL	0.131 + 0.008*SL
	t_{PLH}	0.428	0.413 + 0.007*SL	0.421 + 0.005*SL	0.438 + 0.004*SL
	t_{PHL}	0.487	0.468 + 0.009*SL	0.478 + 0.007*SL	0.511 + 0.005*SL
F to Y	t_R	0.100	0.080 + 0.010*SL	0.084 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.128	0.107 + 0.010*SL	0.113 + 0.009*SL	0.130 + 0.008*SL
	t_{PLH}	0.466	0.451 + 0.007*SL	0.459 + 0.005*SL	0.476 + 0.004*SL
	t_{PHL}	0.504	0.485 + 0.009*SL	0.496 + 0.007*SL	0.529 + 0.005*SL
G to Y	t_R	0.102	0.083 + 0.009*SL	0.084 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.128	0.106 + 0.011*SL	0.113 + 0.009*SL	0.130 + 0.008*SL
	t_{PLH}	0.500	0.485 + 0.007*SL	0.494 + 0.005*SL	0.511 + 0.004*SL
	t_{PHL}	0.517	0.498 + 0.009*SL	0.508 + 0.007*SL	0.541 + 0.005*SL
H to Y	t_R	0.103	0.083 + 0.010*SL	0.087 + 0.009*SL	0.079 + 0.009*SL
	t_F	0.128	0.107 + 0.011*SL	0.114 + 0.009*SL	0.131 + 0.008*SL
	t_{PLH}	0.529	0.514 + 0.008*SL	0.523 + 0.005*SL	0.540 + 0.004*SL
	t_{PHL}	0.524	0.505 + 0.009*SL	0.515 + 0.007*SL	0.548 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NR2DH/NR2/NR2D2/NR2D2B/NR2D4/NR2A

2-Input NOR with 0.5X/1X/2X/2X(Buffered)/4X/(2X/1X) Drive

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	0

Cell Data

Input Load (SL)											
NR2DH		*NR2*		*NR2D2*		*NR2D2B*		*NR2D4*		*NR2A*	
A	B	A	B	A	B	A	B	A	B	A	B
0.5	0.5	1.0	1.0	1.9	2.1	1.0	1.1	1.0	1.1	1.5	1.7

Gate Count					
NR2DH	*NR2*	*NR2D2*	*NR2D2B*	*NR2D4*	*NR2A*
1.00	1.00	1.67	2.33	3.00	1.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.497	0.171 + 0.163*SL	0.145 + 0.169*SL	0.139 + 0.170*SL
	t_F	0.213	0.100 + 0.057*SL	0.080 + 0.062*SL	0.060 + 0.064*SL
	t_{PLH}	0.275	0.122 + 0.076*SL	0.121 + 0.076*SL	0.122 + 0.076*SL
	t_{PHL}	0.159	0.087 + 0.036*SL	0.097 + 0.033*SL	0.097 + 0.033*SL
B to Y	t_R	0.490	0.159 + 0.166*SL	0.145 + 0.169*SL	0.140 + 0.170*SL
	t_F	0.234	0.120 + 0.057*SL	0.101 + 0.062*SL	0.082 + 0.064*SL
	t_{PLH}	0.286	0.132 + 0.077*SL	0.133 + 0.077*SL	0.134 + 0.076*SL
	t_{PHL}	0.174	0.105 + 0.035*SL	0.110 + 0.033*SL	0.111 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NR2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.292	0.152 + 0.070*SL	0.138 + 0.074*SL	0.122 + 0.076*SL
	t_F	0.153	0.096 + 0.028*SL	0.086 + 0.031*SL	0.073 + 0.033*SL
	t_{PLH}	0.172	0.102 + 0.035*SL	0.105 + 0.034*SL	0.105 + 0.034*SL
	t_{PHL}	0.118	0.073 + 0.023*SL	0.093 + 0.018*SL	0.094 + 0.018*SL
B to Y	t_R	0.281	0.136 + 0.073*SL	0.126 + 0.075*SL	0.118 + 0.076*SL
	t_F	0.176	0.119 + 0.028*SL	0.108 + 0.031*SL	0.096 + 0.033*SL
	t_{PLH}	0.180	0.109 + 0.036*SL	0.113 + 0.035*SL	0.114 + 0.034*SL
	t_{PHL}	0.138	0.097 + 0.020*SL	0.108 + 0.018*SL	0.109 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.209	0.142 + 0.034*SL	0.132 + 0.036*SL	0.113 + 0.038*SL
	t_F	0.116	0.084 + 0.016*SL	0.090 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.128	0.087 + 0.020*SL	0.100 + 0.017*SL	0.099 + 0.017*SL
	t_{PHL}	0.088	0.059 + 0.014*SL	0.077 + 0.010*SL	0.090 + 0.009*SL
B to Y	t_R	0.195	0.125 + 0.035*SL	0.116 + 0.037*SL	0.106 + 0.038*SL
	t_F	0.142	0.114 + 0.014*SL	0.111 + 0.015*SL	0.096 + 0.016*SL
	t_{PLH}	0.137	0.097 + 0.020*SL	0.106 + 0.017*SL	0.108 + 0.017*SL
	t_{PHL}	0.112	0.087 + 0.012*SL	0.099 + 0.009*SL	0.105 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NR2D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	0.056 + 0.018*SL	0.052 + 0.019*SL	0.045 + 0.019*SL
	t_F	0.089	0.054 + 0.018*SL	0.060 + 0.016*SL	0.055 + 0.017*SL
	t_{PLH}	0.277	0.256 + 0.011*SL	0.262 + 0.009*SL	0.266 + 0.009*SL
	t_{PHL}	0.267	0.243 + 0.012*SL	0.253 + 0.010*SL	0.264 + 0.009*SL
B to Y	t_R	0.091	0.056 + 0.018*SL	0.052 + 0.018*SL	0.044 + 0.019*SL
	t_F	0.092	0.059 + 0.017*SL	0.060 + 0.016*SL	0.056 + 0.017*SL
	t_{PLH}	0.287	0.266 + 0.011*SL	0.272 + 0.009*SL	0.276 + 0.009*SL
	t_{PHL}	0.292	0.267 + 0.012*SL	0.278 + 0.010*SL	0.289 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NR2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	0.067 + 0.009*SL	0.069 + 0.009*SL	0.058 + 0.009*SL
	t_F	0.094	0.074 + 0.010*SL	0.081 + 0.008*SL	0.084 + 0.008*SL
	t_{PLH}	0.307	0.294 + 0.007*SL	0.300 + 0.005*SL	0.311 + 0.004*SL
	t_{PHL}	0.311	0.295 + 0.008*SL	0.304 + 0.006*SL	0.326 + 0.005*SL
B to Y	t_R	0.085	0.067 + 0.009*SL	0.066 + 0.009*SL	0.059 + 0.009*SL
	t_F	0.094	0.074 + 0.010*SL	0.081 + 0.008*SL	0.084 + 0.008*SL
	t_{PLH}	0.317	0.304 + 0.007*SL	0.310 + 0.005*SL	0.321 + 0.004*SL
	t_{PHL}	0.336	0.319 + 0.008*SL	0.329 + 0.006*SL	0.351 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.205	0.138 + 0.034*SL	0.128 + 0.036*SL	0.116 + 0.038*SL
	t_F	0.154	0.096 + 0.029*SL	0.088 + 0.031*SL	0.075 + 0.033*SL
	t_{PLH}	0.115	0.071 + 0.022*SL	0.088 + 0.018*SL	0.089 + 0.018*SL
	t_{PHL}	0.131	0.089 + 0.021*SL	0.103 + 0.018*SL	0.104 + 0.018*SL
B to Y	t_R	0.187	0.117 + 0.035*SL	0.107 + 0.038*SL	0.100 + 0.038*SL
	t_F	0.195	0.134 + 0.030*SL	0.127 + 0.032*SL	0.118 + 0.033*SL
	t_{PLH}	0.129	0.088 + 0.020*SL	0.098 + 0.018*SL	0.100 + 0.018*SL
	t_{PHL}	0.170	0.132 + 0.019*SL	0.136 + 0.018*SL	0.137 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	1
	Other States		0

Cell Data

Input Load (SL)																	
NR3DH			*NR3*			*NR3D2*			*NR3D2B*			*NR3D4*			*NR3A*		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.6	0.6	0.6	0.9	0.9	0.9	1.8	2.0	2.0	0.9	0.9	1.0	0.9	0.9	1.0	1.4	1.6	1.7

Gate Count					
NR3DH	*NR3*	*NR3D2*	*NR3D2B*	*NR3D4*	*NR3A*
1.33	1.33	2.33	2.67	3.33	2.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.626	0.265 + 0.181*SL	0.244 + 0.186*SL	0.246 + 0.185*SL
	t_F	0.227	0.110 + 0.058*SL	0.093 + 0.062*SL	0.077 + 0.065*SL
	t_{PLH}	0.307	0.139 + 0.084*SL	0.139 + 0.084*SL	0.140 + 0.084*SL
	t_{PHL}	0.175	0.106 + 0.035*SL	0.111 + 0.033*SL	0.111 + 0.033*SL
B to Y	t_R	0.628	0.265 + 0.182*SL	0.252 + 0.185*SL	0.248 + 0.185*SL
	t_F	0.253	0.135 + 0.059*SL	0.120 + 0.063*SL	0.105 + 0.065*SL
	t_{PLH}	0.350	0.180 + 0.085*SL	0.183 + 0.084*SL	0.185 + 0.084*SL
	t_{PHL}	0.197	0.129 + 0.034*SL	0.131 + 0.033*SL	0.132 + 0.033*SL
C to Y	t_R	0.625	0.259 + 0.183*SL	0.251 + 0.185*SL	0.248 + 0.185*SL
	t_F	0.283	0.164 + 0.059*SL	0.151 + 0.063*SL	0.136 + 0.065*SL
	t_{PLH}	0.367	0.198 + 0.085*SL	0.200 + 0.084*SL	0.202 + 0.084*SL
	t_{PHL}	0.207	0.136 + 0.035*SL	0.140 + 0.034*SL	0.145 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NR3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.459	0.238 + 0.111*SL	0.225 + 0.114*SL	0.211 + 0.116*SL
	t_F	0.182	0.109 + 0.037*SL	0.094 + 0.040*SL	0.082 + 0.042*SL
	t_{PLH}	0.229	0.126 + 0.051*SL	0.124 + 0.052*SL	0.124 + 0.052*SL
	t_{PHL}	0.146	0.097 + 0.025*SL	0.107 + 0.022*SL	0.107 + 0.022*SL
B to Y	t_R	0.459	0.236 + 0.112*SL	0.228 + 0.114*SL	0.218 + 0.115*SL
	t_F	0.208	0.132 + 0.038*SL	0.121 + 0.041*SL	0.110 + 0.042*SL
	t_{PLH}	0.267	0.162 + 0.053*SL	0.163 + 0.052*SL	0.165 + 0.052*SL
	t_{PHL}	0.169	0.123 + 0.023*SL	0.127 + 0.022*SL	0.128 + 0.022*SL
C to Y	t_R	0.455	0.230 + 0.113*SL	0.223 + 0.114*SL	0.217 + 0.115*SL
	t_F	0.237	0.160 + 0.039*SL	0.153 + 0.040*SL	0.140 + 0.042*SL
	t_{PLH}	0.284	0.178 + 0.053*SL	0.180 + 0.052*SL	0.181 + 0.052*SL
	t_{PHL}	0.180	0.133 + 0.024*SL	0.136 + 0.023*SL	0.140 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.318	0.210 + 0.054*SL	0.202 + 0.056*SL	0.182 + 0.058*SL
	t_F	0.134	0.098 + 0.018*SL	0.093 + 0.019*SL	0.076 + 0.021*SL
	t_{PLH}	0.161	0.110 + 0.026*SL	0.109 + 0.026*SL	0.108 + 0.026*SL
	t_{PHL}	0.110	0.079 + 0.016*SL	0.095 + 0.011*SL	0.100 + 0.011*SL
B to Y	t_R	0.317	0.208 + 0.054*SL	0.200 + 0.056*SL	0.188 + 0.057*SL
	t_F	0.160	0.125 + 0.018*SL	0.117 + 0.020*SL	0.103 + 0.021*SL
	t_{PLH}	0.199	0.144 + 0.027*SL	0.149 + 0.026*SL	0.151 + 0.026*SL
	t_{PHL}	0.137	0.110 + 0.013*SL	0.119 + 0.011*SL	0.121 + 0.011*SL
C to Y	t_R	0.311	0.201 + 0.055*SL	0.194 + 0.057*SL	0.185 + 0.058*SL
	t_F	0.189	0.152 + 0.018*SL	0.147 + 0.020*SL	0.134 + 0.021*SL
	t_{PLH}	0.216	0.162 + 0.027*SL	0.164 + 0.026*SL	0.166 + 0.026*SL
	t_{PHL}	0.147	0.121 + 0.013*SL	0.127 + 0.012*SL	0.131 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NR3D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.061 + 0.018*SL	0.059 + 0.018*SL	0.049 + 0.019*SL
	t_F	0.090	0.055 + 0.018*SL	0.060 + 0.016*SL	0.054 + 0.017*SL
	t_{PLH}	0.339	0.317 + 0.011*SL	0.325 + 0.009*SL	0.329 + 0.009*SL
	t_{PHL}	0.297	0.272 + 0.012*SL	0.282 + 0.010*SL	0.293 + 0.009*SL
B to Y	t_R	0.096	0.061 + 0.018*SL	0.059 + 0.018*SL	0.049 + 0.019*SL
	t_F	0.092	0.059 + 0.017*SL	0.060 + 0.016*SL	0.054 + 0.017*SL
	t_{PLH}	0.378	0.356 + 0.011*SL	0.364 + 0.009*SL	0.369 + 0.009*SL
	t_{PHL}	0.324	0.299 + 0.012*SL	0.309 + 0.010*SL	0.320 + 0.009*SL
C to Y	t_R	0.096	0.061 + 0.018*SL	0.059 + 0.018*SL	0.049 + 0.019*SL
	t_F	0.092	0.058 + 0.017*SL	0.062 + 0.016*SL	0.055 + 0.017*SL
	t_{PLH}	0.398	0.376 + 0.011*SL	0.384 + 0.009*SL	0.388 + 0.009*SL
	t_{PHL}	0.342	0.317 + 0.013*SL	0.328 + 0.010*SL	0.338 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.092	0.072 + 0.010*SL	0.076 + 0.009*SL	0.063 + 0.009*SL
	t_F	0.091	0.071 + 0.010*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.368	0.354 + 0.007*SL	0.361 + 0.005*SL	0.374 + 0.004*SL
	t_{PHL}	0.333	0.317 + 0.008*SL	0.326 + 0.006*SL	0.347 + 0.005*SL
B to Y	t_R	0.091	0.072 + 0.010*SL	0.076 + 0.009*SL	0.064 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.077 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.407	0.393 + 0.007*SL	0.400 + 0.005*SL	0.413 + 0.004*SL
	t_{PHL}	0.360	0.344 + 0.008*SL	0.354 + 0.006*SL	0.375 + 0.005*SL
C to Y	t_R	0.091	0.072 + 0.010*SL	0.076 + 0.009*SL	0.064 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.079 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.426	0.413 + 0.007*SL	0.420 + 0.005*SL	0.432 + 0.004*SL
	t_{PHL}	0.380	0.363 + 0.008*SL	0.373 + 0.006*SL	0.394 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NR3A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.304	0.195 + 0.054*SL	0.187 + 0.057*SL	0.176 + 0.058*SL
	t_F	0.186	0.109 + 0.038*SL	0.099 + 0.041*SL	0.086 + 0.042*SL
	t_{PLH}	0.146	0.091 + 0.027*SL	0.094 + 0.027*SL	0.094 + 0.027*SL
	t_{PHL}	0.161	0.114 + 0.024*SL	0.120 + 0.022*SL	0.121 + 0.022*SL
B to Y	t_R	0.301	0.190 + 0.056*SL	0.182 + 0.057*SL	0.176 + 0.058*SL
	t_F	0.236	0.156 + 0.040*SL	0.149 + 0.042*SL	0.141 + 0.043*SL
	t_{PLH}	0.188	0.131 + 0.028*SL	0.137 + 0.027*SL	0.138 + 0.027*SL
	t_{PHL}	0.208	0.162 + 0.023*SL	0.164 + 0.023*SL	0.167 + 0.022*SL
C to Y	t_R	0.295	0.183 + 0.056*SL	0.176 + 0.058*SL	0.170 + 0.059*SL
	t_F	0.292	0.211 + 0.041*SL	0.207 + 0.042*SL	0.200 + 0.043*SL
	t_{PLH}	0.207	0.151 + 0.028*SL	0.155 + 0.027*SL	0.156 + 0.027*SL
	t_{PHL}	0.234	0.184 + 0.025*SL	0.189 + 0.024*SL	0.195 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	0	1
Other States				0

Cell Data

Input Load (SL)															
NR4DH				*NR4*				*NR4D2*				*NR4D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.6	0.6	0.6	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.1	1.0	1.0	1.0	1.1

Gate Count			
NR4DH	*NR4*	*NR4D2*	*NR4D4*
3.00	3.00	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.257	0.095 + 0.081*SL	0.086 + 0.083*SL	0.078 + 0.084*SL
	t_F	0.213	0.089 + 0.062*SL	0.085 + 0.063*SL	0.076 + 0.064*SL
	t_{PLH}	0.422	0.343 + 0.039*SL	0.350 + 0.038*SL	0.351 + 0.038*SL
	t_{PHL}	0.379	0.306 + 0.037*SL	0.318 + 0.034*SL	0.322 + 0.033*SL
B to Y	t_R	0.257	0.093 + 0.082*SL	0.085 + 0.084*SL	0.079 + 0.084*SL
	t_F	0.213	0.089 + 0.062*SL	0.085 + 0.063*SL	0.076 + 0.064*SL
	t_{PLH}	0.434	0.356 + 0.039*SL	0.362 + 0.038*SL	0.364 + 0.038*SL
	t_{PHL}	0.401	0.327 + 0.037*SL	0.340 + 0.034*SL	0.344 + 0.033*SL
C to Y	t_R	0.257	0.094 + 0.081*SL	0.085 + 0.084*SL	0.078 + 0.085*SL
	t_F	0.218	0.095 + 0.061*SL	0.089 + 0.063*SL	0.079 + 0.064*SL
	t_{PLH}	0.413	0.334 + 0.040*SL	0.342 + 0.038*SL	0.343 + 0.038*SL
	t_{PHL}	0.399	0.324 + 0.038*SL	0.339 + 0.034*SL	0.344 + 0.033*SL
D to Y	t_R	0.257	0.094 + 0.081*SL	0.085 + 0.084*SL	0.078 + 0.084*SL
	t_F	0.218	0.095 + 0.061*SL	0.089 + 0.063*SL	0.079 + 0.064*SL
	t_{PLH}	0.427	0.348 + 0.040*SL	0.355 + 0.038*SL	0.357 + 0.038*SL
	t_{PHL}	0.422	0.347 + 0.038*SL	0.362 + 0.034*SL	0.367 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.148	0.075 + 0.036*SL	0.072 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.137	0.071 + 0.033*SL	0.072 + 0.033*SL	0.065 + 0.034*SL
	t_{PLH}	0.322	0.283 + 0.019*SL	0.291 + 0.018*SL	0.294 + 0.017*SL
	t_{PHL}	0.306	0.265 + 0.021*SL	0.275 + 0.018*SL	0.280 + 0.018*SL
B to Y	t_R	0.149	0.077 + 0.036*SL	0.072 + 0.037*SL	0.067 + 0.038*SL
	t_F	0.137	0.071 + 0.033*SL	0.070 + 0.033*SL	0.067 + 0.034*SL
	t_{PLH}	0.331	0.292 + 0.019*SL	0.299 + 0.018*SL	0.302 + 0.017*SL
	t_{PHL}	0.330	0.288 + 0.021*SL	0.298 + 0.018*SL	0.303 + 0.018*SL
C to Y	t_R	0.148	0.076 + 0.036*SL	0.071 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.141	0.076 + 0.032*SL	0.075 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.316	0.277 + 0.020*SL	0.285 + 0.018*SL	0.288 + 0.017*SL
	t_{PHL}	0.318	0.276 + 0.021*SL	0.286 + 0.019*SL	0.292 + 0.018*SL
D to Y	t_R	0.148	0.076 + 0.036*SL	0.072 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.141	0.076 + 0.032*SL	0.075 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.325	0.286 + 0.020*SL	0.294 + 0.018*SL	0.297 + 0.017*SL
	t_{PHL}	0.343	0.300 + 0.021*SL	0.311 + 0.019*SL	0.317 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NR4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.070 + 0.018*SL	0.070 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.101	0.066 + 0.017*SL	0.070 + 0.016*SL	0.067 + 0.017*SL
	t_{PLH}	0.319	0.295 + 0.012*SL	0.305 + 0.010*SL	0.316 + 0.009*SL
	t_{PHL}	0.296	0.270 + 0.013*SL	0.282 + 0.010*SL	0.295 + 0.009*SL
B to Y	t_R	0.108	0.071 + 0.019*SL	0.073 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.101	0.066 + 0.017*SL	0.070 + 0.016*SL	0.068 + 0.017*SL
	t_{PLH}	0.328	0.304 + 0.012*SL	0.314 + 0.010*SL	0.325 + 0.009*SL
	t_{PHL}	0.320	0.293 + 0.013*SL	0.305 + 0.010*SL	0.319 + 0.009*SL
C to Y	t_R	0.106	0.069 + 0.019*SL	0.071 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.075 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.314	0.289 + 0.012*SL	0.300 + 0.010*SL	0.310 + 0.009*SL
	t_{PHL}	0.310	0.284 + 0.013*SL	0.296 + 0.010*SL	0.311 + 0.009*SL
D to Y	t_R	0.106	0.069 + 0.019*SL	0.071 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.075 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.323	0.299 + 0.012*SL	0.309 + 0.010*SL	0.320 + 0.009*SL
	t_{PHL}	0.336	0.309 + 0.013*SL	0.321 + 0.010*SL	0.336 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.087 + 0.010*SL	0.091 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.101	0.082 + 0.009*SL	0.086 + 0.009*SL	0.093 + 0.008*SL
	t_{PLH}	0.369	0.354 + 0.008*SL	0.362 + 0.006*SL	0.383 + 0.005*SL
	t_{PHL}	0.335	0.318 + 0.008*SL	0.327 + 0.006*SL	0.351 + 0.005*SL
B to Y	t_R	0.107	0.086 + 0.010*SL	0.091 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.101	0.082 + 0.010*SL	0.087 + 0.009*SL	0.093 + 0.008*SL
	t_{PLH}	0.378	0.363 + 0.008*SL	0.371 + 0.006*SL	0.392 + 0.005*SL
	t_{PHL}	0.358	0.342 + 0.008*SL	0.351 + 0.006*SL	0.375 + 0.005*SL
C to Y	t_R	0.107	0.086 + 0.010*SL	0.090 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.106	0.087 + 0.010*SL	0.092 + 0.008*SL	0.099 + 0.008*SL
	t_{PLH}	0.360	0.344 + 0.008*SL	0.352 + 0.006*SL	0.374 + 0.005*SL
	t_{PHL}	0.345	0.328 + 0.008*SL	0.338 + 0.006*SL	0.363 + 0.005*SL
D to Y	t_R	0.107	0.086 + 0.010*SL	0.091 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.106	0.087 + 0.010*SL	0.092 + 0.009*SL	0.099 + 0.008*SL
	t_{PLH}	0.369	0.354 + 0.008*SL	0.362 + 0.006*SL	0.384 + 0.005*SL
	t_{PHL}	0.370	0.353 + 0.008*SL	0.363 + 0.006*SL	0.388 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NR5/NR5D2/NR5D4

5-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	0	0	1
Other States					0

Cell Data

Input Load (SL)															Gate Count		
NR5					*NR5D2*					*NR5D4*					*NR5*	*NR5D2*	*NR5D4*
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.9	0.9	1.0	1.0	1.1	0.9	0.9	1.0	1.0	1.1	0.9	0.9	1.0	1.0	1.1	3.33	3.67	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.152	0.080 + 0.036*SL	0.074 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.137	0.072 + 0.033*SL	0.069 + 0.033*SL	0.066 + 0.034*SL
	t_{PLH}	0.379	0.340 + 0.020*SL	0.347 + 0.018*SL	0.351 + 0.017*SL
	t_{PHL}	0.337	0.296 + 0.021*SL	0.305 + 0.018*SL	0.310 + 0.018*SL
B to Y	t_R	0.152	0.080 + 0.036*SL	0.075 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.137	0.072 + 0.033*SL	0.071 + 0.033*SL	0.065 + 0.034*SL
	t_{PLH}	0.417	0.378 + 0.020*SL	0.386 + 0.018*SL	0.389 + 0.017*SL
	t_{PHL}	0.364	0.322 + 0.021*SL	0.332 + 0.018*SL	0.337 + 0.018*SL
C to Y	t_R	0.152	0.080 + 0.036*SL	0.075 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.138	0.072 + 0.033*SL	0.071 + 0.033*SL	0.067 + 0.034*SL
	t_{PLH}	0.436	0.397 + 0.020*SL	0.405 + 0.018*SL	0.408 + 0.017*SL
	t_{PHL}	0.381	0.339 + 0.021*SL	0.349 + 0.018*SL	0.354 + 0.018*SL
D to Y	t_R	0.147	0.074 + 0.036*SL	0.069 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.141	0.076 + 0.032*SL	0.075 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.312	0.273 + 0.020*SL	0.281 + 0.018*SL	0.284 + 0.017*SL
	t_{PHL}	0.318	0.276 + 0.021*SL	0.286 + 0.019*SL	0.292 + 0.018*SL
E to Y	t_R	0.147	0.075 + 0.036*SL	0.071 + 0.037*SL	0.065 + 0.038*SL
	t_F	0.141	0.076 + 0.032*SL	0.075 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.321	0.282 + 0.019*SL	0.290 + 0.018*SL	0.293 + 0.017*SL
	t_{PHL}	0.343	0.301 + 0.021*SL	0.311 + 0.019*SL	0.317 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	0.076 + 0.018*SL	0.077 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.073 + 0.016*SL	0.071 + 0.017*SL
	t_{PLH}	0.387	0.362 + 0.012*SL	0.373 + 0.010*SL	0.384 + 0.009*SL
	t_{PHL}	0.340	0.314 + 0.013*SL	0.326 + 0.010*SL	0.341 + 0.009*SL
B to Y	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.069 + 0.018*SL	0.074 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.426	0.401 + 0.012*SL	0.412 + 0.010*SL	0.423 + 0.009*SL
	t_{PHL}	0.367	0.340 + 0.013*SL	0.353 + 0.010*SL	0.367 + 0.009*SL
C to Y	t_R	0.112	0.076 + 0.018*SL	0.076 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.074 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.444	0.420 + 0.012*SL	0.430 + 0.010*SL	0.442 + 0.009*SL
	t_{PHL}	0.385	0.358 + 0.014*SL	0.371 + 0.010*SL	0.386 + 0.009*SL
D to Y	t_R	0.106	0.069 + 0.019*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.079 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.313	0.288 + 0.012*SL	0.299 + 0.010*SL	0.310 + 0.009*SL
	t_{PHL}	0.318	0.291 + 0.014*SL	0.304 + 0.011*SL	0.319 + 0.009*SL
E to Y	t_R	0.106	0.069 + 0.019*SL	0.071 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.079 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.322	0.298 + 0.012*SL	0.308 + 0.010*SL	0.319 + 0.009*SL
	t_{PHL}	0.343	0.315 + 0.014*SL	0.329 + 0.011*SL	0.344 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR5D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.111	0.090 + 0.011*SL	0.096 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.111	0.091 + 0.010*SL	0.097 + 0.009*SL	0.105 + 0.008*SL
	t_{PLH}	0.440	0.424 + 0.008*SL	0.432 + 0.006*SL	0.454 + 0.005*SL
	t_{PHL}	0.398	0.381 + 0.009*SL	0.390 + 0.006*SL	0.417 + 0.005*SL
B to Y	t_R	0.111	0.090 + 0.011*SL	0.096 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.111	0.090 + 0.010*SL	0.096 + 0.009*SL	0.107 + 0.008*SL
	t_{PLH}	0.478	0.463 + 0.008*SL	0.471 + 0.006*SL	0.493 + 0.005*SL
	t_{PHL}	0.425	0.408 + 0.009*SL	0.417 + 0.006*SL	0.444 + 0.005*SL
C to Y	t_R	0.112	0.090 + 0.011*SL	0.096 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.111	0.090 + 0.010*SL	0.098 + 0.009*SL	0.108 + 0.008*SL
	t_{PLH}	0.497	0.481 + 0.008*SL	0.490 + 0.006*SL	0.512 + 0.005*SL
	t_{PHL}	0.444	0.427 + 0.009*SL	0.436 + 0.006*SL	0.463 + 0.005*SL
D to Y	t_R	0.105	0.084 + 0.011*SL	0.090 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.116	0.094 + 0.011*SL	0.103 + 0.009*SL	0.111 + 0.008*SL
	t_{PLH}	0.353	0.337 + 0.008*SL	0.345 + 0.006*SL	0.367 + 0.005*SL
	t_{PHL}	0.372	0.354 + 0.009*SL	0.364 + 0.006*SL	0.392 + 0.005*SL
E to Y	t_R	0.106	0.086 + 0.010*SL	0.089 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.116	0.095 + 0.011*SL	0.103 + 0.009*SL	0.112 + 0.008*SL
	t_{PLH}	0.362	0.347 + 0.008*SL	0.355 + 0.006*SL	0.376 + 0.005*SL
	t_{PHL}	0.397	0.379 + 0.009*SL	0.389 + 0.006*SL	0.417 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NR6/NR6D2/NR6D4

6-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	0	0	0	1
Other States						0

Cell Data

Input Load (SL)																	
NR6						*NR6D2*						*NR6D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.9	0.9	1.0	0.9	1.0	1.0	0.9	0.9	1.0	0.9	1.0	1.0	0.9	0.9	1.0	0.9	1.0	1.0

Gate Count		
NR6	*NR6D2*	*NR6D4*
3.67	4.00	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.152	0.081 + 0.036*SL	0.074 + 0.037*SL	0.070 + 0.038*SL
	t_F	0.136	0.071 + 0.033*SL	0.069 + 0.033*SL	0.066 + 0.034*SL
	t_{PLH}	0.381	0.342 + 0.020*SL	0.350 + 0.018*SL	0.354 + 0.017*SL
	t_{PHL}	0.335	0.294 + 0.021*SL	0.303 + 0.018*SL	0.308 + 0.018*SL
B to Y	t_R	0.152	0.081 + 0.036*SL	0.074 + 0.037*SL	0.070 + 0.038*SL
	t_F	0.137	0.072 + 0.033*SL	0.070 + 0.033*SL	0.065 + 0.034*SL
	t_{PLH}	0.420	0.381 + 0.020*SL	0.389 + 0.018*SL	0.392 + 0.017*SL
	t_{PHL}	0.362	0.320 + 0.021*SL	0.330 + 0.018*SL	0.335 + 0.018*SL
C to Y	t_R	0.152	0.081 + 0.036*SL	0.075 + 0.037*SL	0.070 + 0.038*SL
	t_F	0.137	0.072 + 0.033*SL	0.070 + 0.033*SL	0.067 + 0.034*SL
	t_{PLH}	0.439	0.399 + 0.020*SL	0.408 + 0.018*SL	0.411 + 0.017*SL
	t_{PHL}	0.379	0.337 + 0.021*SL	0.347 + 0.018*SL	0.353 + 0.018*SL
D to Y	t_R	0.151	0.079 + 0.036*SL	0.075 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.140	0.076 + 0.032*SL	0.074 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.365	0.325 + 0.020*SL	0.334 + 0.018*SL	0.338 + 0.017*SL
	t_{PHL}	0.347	0.305 + 0.021*SL	0.315 + 0.019*SL	0.321 + 0.018*SL
E to Y	t_R	0.151	0.079 + 0.036*SL	0.075 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.141	0.075 + 0.033*SL	0.075 + 0.033*SL	0.068 + 0.034*SL
	t_{PLH}	0.403	0.364 + 0.020*SL	0.372 + 0.018*SL	0.376 + 0.017*SL
	t_{PHL}	0.375	0.333 + 0.021*SL	0.343 + 0.019*SL	0.349 + 0.018*SL
F to Y	t_R	0.151	0.078 + 0.036*SL	0.075 + 0.037*SL	0.069 + 0.038*SL
	t_F	0.142	0.077 + 0.032*SL	0.076 + 0.033*SL	0.069 + 0.034*SL
	t_{PLH}	0.422	0.383 + 0.020*SL	0.391 + 0.018*SL	0.395 + 0.017*SL
	t_{PHL}	0.393	0.351 + 0.021*SL	0.362 + 0.019*SL	0.367 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.073 + 0.016*SL	0.071 + 0.017*SL
	t_{PLH}	0.387	0.363 + 0.012*SL	0.373 + 0.010*SL	0.385 + 0.009*SL
	t_{PHL}	0.340	0.314 + 0.013*SL	0.326 + 0.010*SL	0.340 + 0.009*SL
B to Y	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.069 + 0.017*SL	0.074 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.426	0.401 + 0.012*SL	0.412 + 0.010*SL	0.423 + 0.009*SL
	t_{PHL}	0.367	0.341 + 0.013*SL	0.353 + 0.010*SL	0.367 + 0.009*SL
C to Y	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.075 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.445	0.420 + 0.012*SL	0.431 + 0.010*SL	0.442 + 0.009*SL
	t_{PHL}	0.385	0.358 + 0.013*SL	0.371 + 0.010*SL	0.385 + 0.009*SL
D to Y	t_R	0.110	0.073 + 0.019*SL	0.075 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.078 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.367	0.342 + 0.012*SL	0.353 + 0.010*SL	0.365 + 0.009*SL
	t_{PHL}	0.351	0.323 + 0.014*SL	0.336 + 0.011*SL	0.352 + 0.009*SL
E to Y	t_R	0.110	0.072 + 0.019*SL	0.075 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.405	0.380 + 0.012*SL	0.392 + 0.010*SL	0.403 + 0.009*SL
	t_{PHL}	0.378	0.351 + 0.014*SL	0.364 + 0.011*SL	0.380 + 0.009*SL
F to Y	t_R	0.111	0.073 + 0.019*SL	0.076 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.081 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.424	0.399 + 0.012*SL	0.410 + 0.010*SL	0.422 + 0.009*SL
	t_{PHL}	0.397	0.370 + 0.014*SL	0.383 + 0.011*SL	0.399 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR6D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.111	0.091 + 0.010*SL	0.095 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.111	0.090 + 0.010*SL	0.097 + 0.009*SL	0.105 + 0.008*SL
	t_{PLH}	0.440	0.425 + 0.008*SL	0.433 + 0.006*SL	0.455 + 0.005*SL
	t_{PHL}	0.398	0.381 + 0.009*SL	0.390 + 0.006*SL	0.417 + 0.005*SL
B to Y	t_R	0.111	0.090 + 0.011*SL	0.096 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.110	0.090 + 0.010*SL	0.096 + 0.009*SL	0.107 + 0.008*SL
	t_{PLH}	0.479	0.464 + 0.008*SL	0.472 + 0.006*SL	0.494 + 0.005*SL
	t_{PHL}	0.425	0.408 + 0.009*SL	0.417 + 0.006*SL	0.444 + 0.005*SL
C to Y	t_R	0.111	0.090 + 0.011*SL	0.096 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.111	0.090 + 0.010*SL	0.097 + 0.009*SL	0.107 + 0.008*SL
	t_{PLH}	0.498	0.482 + 0.008*SL	0.491 + 0.006*SL	0.513 + 0.005*SL
	t_{PHL}	0.444	0.427 + 0.009*SL	0.436 + 0.006*SL	0.463 + 0.005*SL
D to Y	t_R	0.109	0.088 + 0.010*SL	0.093 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.117	0.096 + 0.010*SL	0.103 + 0.009*SL	0.112 + 0.008*SL
	t_{PLH}	0.410	0.395 + 0.008*SL	0.403 + 0.006*SL	0.426 + 0.005*SL
	t_{PHL}	0.404	0.387 + 0.009*SL	0.397 + 0.006*SL	0.425 + 0.005*SL
E to Y	t_R	0.109	0.087 + 0.011*SL	0.093 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.116	0.094 + 0.011*SL	0.103 + 0.009*SL	0.111 + 0.008*SL
	t_{PLH}	0.449	0.433 + 0.008*SL	0.442 + 0.006*SL	0.464 + 0.005*SL
	t_{PHL}	0.432	0.415 + 0.009*SL	0.425 + 0.006*SL	0.453 + 0.005*SL
F to Y	t_R	0.109	0.087 + 0.011*SL	0.093 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.116	0.095 + 0.011*SL	0.104 + 0.008*SL	0.112 + 0.008*SL
	t_{PLH}	0.468	0.452 + 0.008*SL	0.461 + 0.006*SL	0.483 + 0.005*SL
	t_{PHL}	0.452	0.434 + 0.009*SL	0.444 + 0.006*SL	0.473 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NR8/NR8D2/NR8D4

8-Input NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	0	0	0	0	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
NR8								*NR8*
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	4.67
NR8D2								*NR8D2*
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	1.0	5.00
NR8D4								*NR8D4*
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	1.0	5.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.165	0.091 + 0.037*SL	0.091 + 0.037*SL	0.086 + 0.038*SL
	t_F	0.144	0.077 + 0.033*SL	0.078 + 0.033*SL	0.075 + 0.033*SL
	t_{PLH}	0.408	0.364 + 0.022*SL	0.377 + 0.019*SL	0.385 + 0.018*SL
	t_{PHL}	0.379	0.335 + 0.022*SL	0.347 + 0.019*SL	0.355 + 0.018*SL
B to Y	t_R	0.165	0.091 + 0.037*SL	0.092 + 0.037*SL	0.086 + 0.038*SL
	t_F	0.145	0.079 + 0.033*SL	0.079 + 0.033*SL	0.074 + 0.033*SL
	t_{PLH}	0.447	0.404 + 0.022*SL	0.416 + 0.019*SL	0.424 + 0.018*SL
	t_{PHL}	0.412	0.368 + 0.022*SL	0.381 + 0.019*SL	0.388 + 0.018*SL
C to Y	t_R	0.166	0.092 + 0.037*SL	0.092 + 0.037*SL	0.086 + 0.038*SL
	t_F	0.145	0.079 + 0.033*SL	0.080 + 0.033*SL	0.076 + 0.033*SL
	t_{PLH}	0.466	0.422 + 0.022*SL	0.435 + 0.019*SL	0.443 + 0.018*SL
	t_{PHL}	0.436	0.392 + 0.022*SL	0.404 + 0.019*SL	0.412 + 0.018*SL
D to Y	t_R	0.167	0.092 + 0.037*SL	0.093 + 0.037*SL	0.087 + 0.038*SL
	t_F	0.149	0.083 + 0.033*SL	0.084 + 0.033*SL	0.080 + 0.033*SL
	t_{PLH}	0.410	0.366 + 0.022*SL	0.379 + 0.019*SL	0.388 + 0.018*SL
	t_{PHL}	0.401	0.356 + 0.022*SL	0.369 + 0.019*SL	0.378 + 0.018*SL
E to Y	t_R	0.166	0.092 + 0.037*SL	0.092 + 0.037*SL	0.088 + 0.038*SL
	t_F	0.150	0.085 + 0.032*SL	0.084 + 0.033*SL	0.079 + 0.033*SL
	t_{PLH}	0.449	0.405 + 0.022*SL	0.418 + 0.019*SL	0.427 + 0.018*SL
	t_{PHL}	0.435	0.390 + 0.022*SL	0.404 + 0.019*SL	0.412 + 0.018*SL
F to Y	t_R	0.166	0.092 + 0.037*SL	0.092 + 0.037*SL	0.088 + 0.038*SL
	t_F	0.150	0.086 + 0.032*SL	0.085 + 0.033*SL	0.081 + 0.033*SL
	t_{PLH}	0.468	0.424 + 0.022*SL	0.437 + 0.019*SL	0.445 + 0.018*SL
	t_{PHL}	0.459	0.414 + 0.022*SL	0.428 + 0.019*SL	0.436 + 0.018*SL
G to Y	t_R	0.164	0.090 + 0.037*SL	0.090 + 0.037*SL	0.085 + 0.038*SL
	t_F	0.155	0.088 + 0.033*SL	0.092 + 0.032*SL	0.087 + 0.033*SL
	t_{PLH}	0.379	0.335 + 0.022*SL	0.348 + 0.019*SL	0.356 + 0.018*SL
	t_{PHL}	0.410	0.364 + 0.023*SL	0.378 + 0.019*SL	0.388 + 0.018*SL
H to Y	t_R	0.163	0.088 + 0.037*SL	0.090 + 0.037*SL	0.085 + 0.038*SL
	t_F	0.156	0.091 + 0.032*SL	0.091 + 0.032*SL	0.087 + 0.033*SL
	t_{PLH}	0.389	0.345 + 0.022*SL	0.358 + 0.019*SL	0.366 + 0.018*SL
	t_{PHL}	0.439	0.393 + 0.023*SL	0.407 + 0.019*SL	0.417 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	0.082 + 0.020*SL	0.089 + 0.019*SL	0.088 + 0.019*SL
	t_F	0.108	0.070 + 0.019*SL	0.080 + 0.016*SL	0.080 + 0.016*SL
	t_{PLH}	0.414	0.385 + 0.014*SL	0.399 + 0.011*SL	0.417 + 0.009*SL
	t_{PHL}	0.381	0.353 + 0.014*SL	0.367 + 0.011*SL	0.385 + 0.009*SL
B to Y	t_R	0.123	0.082 + 0.021*SL	0.089 + 0.019*SL	0.088 + 0.019*SL
	t_F	0.108	0.071 + 0.019*SL	0.080 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.453	0.425 + 0.014*SL	0.438 + 0.011*SL	0.456 + 0.009*SL
	t_{PHL}	0.415	0.386 + 0.014*SL	0.400 + 0.011*SL	0.419 + 0.009*SL
C to Y	t_R	0.123	0.082 + 0.020*SL	0.089 + 0.019*SL	0.088 + 0.019*SL
	t_F	0.110	0.072 + 0.019*SL	0.082 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.471	0.442 + 0.014*SL	0.456 + 0.011*SL	0.474 + 0.009*SL
	t_{PHL}	0.438	0.410 + 0.014*SL	0.424 + 0.011*SL	0.443 + 0.009*SL
D to Y	t_R	0.123	0.081 + 0.021*SL	0.089 + 0.019*SL	0.089 + 0.019*SL
	t_F	0.115	0.078 + 0.018*SL	0.087 + 0.016*SL	0.086 + 0.016*SL
	t_{PLH}	0.412	0.383 + 0.014*SL	0.397 + 0.011*SL	0.416 + 0.009*SL
	t_{PHL}	0.401	0.371 + 0.015*SL	0.386 + 0.011*SL	0.406 + 0.009*SL
E to Y	t_R	0.124	0.083 + 0.020*SL	0.089 + 0.019*SL	0.089 + 0.019*SL
	t_F	0.115	0.078 + 0.019*SL	0.087 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.451	0.422 + 0.014*SL	0.436 + 0.011*SL	0.455 + 0.009*SL
	t_{PHL}	0.435	0.406 + 0.015*SL	0.421 + 0.011*SL	0.441 + 0.009*SL
F to Y	t_R	0.123	0.082 + 0.021*SL	0.090 + 0.019*SL	0.089 + 0.019*SL
	t_F	0.116	0.079 + 0.019*SL	0.089 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.469	0.441 + 0.014*SL	0.455 + 0.011*SL	0.474 + 0.009*SL
	t_{PHL}	0.460	0.430 + 0.015*SL	0.445 + 0.011*SL	0.465 + 0.009*SL
G to Y	t_R	0.121	0.080 + 0.020*SL	0.086 + 0.019*SL	0.086 + 0.019*SL
	t_F	0.121	0.084 + 0.018*SL	0.093 + 0.016*SL	0.094 + 0.016*SL
	t_{PLH}	0.376	0.347 + 0.014*SL	0.361 + 0.011*SL	0.380 + 0.009*SL
	t_{PHL}	0.405	0.375 + 0.015*SL	0.390 + 0.011*SL	0.412 + 0.009*SL
H to Y	t_R	0.121	0.080 + 0.020*SL	0.086 + 0.019*SL	0.085 + 0.019*SL
	t_F	0.120	0.082 + 0.019*SL	0.094 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.387	0.359 + 0.014*SL	0.373 + 0.011*SL	0.391 + 0.009*SL
	t_{PHL}	0.436	0.406 + 0.015*SL	0.421 + 0.011*SL	0.443 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NR8D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	0.105 + 0.011*SL	0.109 + 0.010*SL	0.120 + 0.009*SL
	t_F	0.113	0.091 + 0.011*SL	0.099 + 0.009*SL	0.111 + 0.008*SL
	t_{PLH}	0.480	0.463 + 0.009*SL	0.472 + 0.006*SL	0.501 + 0.005*SL
	t_{PHL}	0.433	0.415 + 0.009*SL	0.424 + 0.007*SL	0.454 + 0.005*SL
B to Y	t_R	0.127	0.105 + 0.011*SL	0.109 + 0.010*SL	0.120 + 0.009*SL
	t_F	0.113	0.092 + 0.010*SL	0.099 + 0.009*SL	0.112 + 0.008*SL
	t_{PLH}	0.520	0.502 + 0.009*SL	0.512 + 0.006*SL	0.541 + 0.005*SL
	t_{PHL}	0.466	0.448 + 0.009*SL	0.458 + 0.007*SL	0.488 + 0.005*SL
C to Y	t_R	0.127	0.105 + 0.011*SL	0.109 + 0.010*SL	0.120 + 0.009*SL
	t_F	0.114	0.092 + 0.011*SL	0.101 + 0.009*SL	0.112 + 0.008*SL
	t_{PLH}	0.538	0.520 + 0.009*SL	0.530 + 0.006*SL	0.558 + 0.005*SL
	t_{PHL}	0.491	0.473 + 0.009*SL	0.483 + 0.007*SL	0.512 + 0.005*SL
D to Y	t_R	0.126	0.104 + 0.011*SL	0.109 + 0.010*SL	0.121 + 0.009*SL
	t_F	0.120	0.100 + 0.010*SL	0.105 + 0.009*SL	0.118 + 0.008*SL
	t_{PLH}	0.471	0.453 + 0.009*SL	0.463 + 0.007*SL	0.492 + 0.005*SL
	t_{PHL}	0.446	0.428 + 0.009*SL	0.438 + 0.007*SL	0.469 + 0.005*SL
E to Y	t_R	0.126	0.105 + 0.011*SL	0.108 + 0.010*SL	0.120 + 0.009*SL
	t_F	0.121	0.101 + 0.010*SL	0.106 + 0.009*SL	0.118 + 0.008*SL
	t_{PLH}	0.510	0.492 + 0.009*SL	0.502 + 0.007*SL	0.531 + 0.005*SL
	t_{PHL}	0.481	0.462 + 0.009*SL	0.473 + 0.007*SL	0.504 + 0.005*SL
F to Y	t_R	0.126	0.102 + 0.012*SL	0.110 + 0.010*SL	0.121 + 0.009*SL
	t_F	0.121	0.101 + 0.010*SL	0.107 + 0.009*SL	0.119 + 0.008*SL
	t_{PLH}	0.528	0.511 + 0.009*SL	0.520 + 0.007*SL	0.550 + 0.005*SL
	t_{PHL}	0.506	0.488 + 0.009*SL	0.498 + 0.007*SL	0.529 + 0.005*SL
G to Y	t_R	0.123	0.100 + 0.012*SL	0.107 + 0.010*SL	0.119 + 0.009*SL
	t_F	0.125	0.102 + 0.011*SL	0.113 + 0.009*SL	0.125 + 0.008*SL
	t_{PLH}	0.436	0.418 + 0.009*SL	0.428 + 0.007*SL	0.457 + 0.005*SL
	t_{PHL}	0.453	0.434 + 0.009*SL	0.445 + 0.007*SL	0.478 + 0.005*SL
H to Y	t_R	0.124	0.102 + 0.011*SL	0.107 + 0.010*SL	0.119 + 0.009*SL
	t_F	0.126	0.107 + 0.010*SL	0.111 + 0.009*SL	0.124 + 0.008*SL
	t_{PLH}	0.447	0.429 + 0.009*SL	0.439 + 0.007*SL	0.468 + 0.005*SL
	t_{PHL}	0.484	0.465 + 0.010*SL	0.476 + 0.007*SL	0.509 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OR2DH/OR2/OR2D2/OR2D4

2-Input OR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	1

Cell Data

Input Load (SL)								Gate Count			
OR2DH		*OR2*		*OR2D2*		*OR2D4*		*OR2DH*	*OR2*	*OR2D2*	*OR2D4*
A	B	A	B	A	B	A	B				
0.5	0.6	0.8	0.8	0.8	0.8	1.0	1.0	1.33	1.33	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.243	0.079 + 0.082*SL	0.069 + 0.084*SL	0.065 + 0.085*SL
	t_F	0.223	0.098 + 0.063*SL	0.099 + 0.062*SL	0.090 + 0.064*SL
	t_{PLH}	0.240	0.164 + 0.038*SL	0.166 + 0.038*SL	0.167 + 0.038*SL
	t_{PHL}	0.324	0.244 + 0.040*SL	0.265 + 0.035*SL	0.275 + 0.033*SL
B to Y	t_R	0.244	0.081 + 0.082*SL	0.071 + 0.084*SL	0.066 + 0.085*SL
	t_F	0.223	0.098 + 0.063*SL	0.099 + 0.062*SL	0.090 + 0.064*SL
	t_{PLH}	0.264	0.187 + 0.039*SL	0.190 + 0.038*SL	0.191 + 0.038*SL
	t_{PHL}	0.339	0.259 + 0.040*SL	0.280 + 0.035*SL	0.289 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OR2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.144	0.071 + 0.037*SL	0.064 + 0.038*SL	0.057 + 0.039*SL
	t_F	0.152	0.084 + 0.034*SL	0.091 + 0.032*SL	0.088 + 0.033*SL
	t_{PLH}	0.193	0.155 + 0.019*SL	0.160 + 0.018*SL	0.161 + 0.017*SL
	t_{PHL}	0.268	0.222 + 0.023*SL	0.237 + 0.020*SL	0.248 + 0.018*SL
B to Y	t_R	0.145	0.072 + 0.036*SL	0.064 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.153	0.086 + 0.033*SL	0.090 + 0.032*SL	0.088 + 0.033*SL
	t_{PLH}	0.216	0.178 + 0.019*SL	0.183 + 0.018*SL	0.185 + 0.017*SL
	t_{PHL}	0.279	0.233 + 0.023*SL	0.248 + 0.020*SL	0.259 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.102	0.066 + 0.018*SL	0.063 + 0.019*SL	0.056 + 0.019*SL
	t_F	0.125	0.086 + 0.019*SL	0.095 + 0.017*SL	0.103 + 0.016*SL
	t_{PLH}	0.197	0.174 + 0.011*SL	0.182 + 0.009*SL	0.189 + 0.009*SL
	t_{PHL}	0.287	0.256 + 0.016*SL	0.271 + 0.012*SL	0.295 + 0.010*SL
B to Y	t_R	0.103	0.066 + 0.019*SL	0.066 + 0.019*SL	0.058 + 0.019*SL
	t_F	0.124	0.084 + 0.020*SL	0.096 + 0.017*SL	0.103 + 0.016*SL
	t_{PLH}	0.217	0.193 + 0.012*SL	0.203 + 0.009*SL	0.211 + 0.009*SL
	t_{PHL}	0.299	0.268 + 0.016*SL	0.283 + 0.012*SL	0.307 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OR2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.091	0.070 + 0.010*SL	0.074 + 0.009*SL	0.069 + 0.010*SL
	t_F	0.124	0.104 + 0.010*SL	0.109 + 0.009*SL	0.126 + 0.008*SL
	t_{PLH}	0.213	0.199 + 0.007*SL	0.206 + 0.005*SL	0.221 + 0.004*SL
	t_{PHL}	0.321	0.302 + 0.009*SL	0.313 + 0.007*SL	0.345 + 0.005*SL
B to Y	t_R	0.095	0.075 + 0.010*SL	0.079 + 0.009*SL	0.072 + 0.010*SL
	t_F	0.123	0.100 + 0.012*SL	0.110 + 0.009*SL	0.126 + 0.008*SL
	t_{PLH}	0.233	0.218 + 0.007*SL	0.226 + 0.005*SL	0.242 + 0.004*SL
	t_{PHL}	0.333	0.314 + 0.009*SL	0.324 + 0.007*SL	0.357 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OR3DH/OR3/OR3D2/OR3D4

3-Input OR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	0
1	x	x	1
x	1	x	1
x	x	1	1

Cell Data

Input Load (SL)											
OR3DH			*OR3*			*OR3D2*			*OR3D4*		
A	B	C	A	B	C	A	B	C	A	B	C
0.6	0.6	0.7	0.7	0.7	0.8	0.7	0.7	0.8	0.9	0.9	1.0
Gate Count											
OR3DH			*OR3*			*OR3D2*			*OR3D4*		
1.67			1.67			2.00			2.67		

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR3DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.247	0.083 + 0.082*SL	0.074 + 0.084*SL	0.068 + 0.085*SL
	t_F	0.250	0.119 + 0.065*SL	0.131 + 0.062*SL	0.127 + 0.063*SL
	t_{PLH}	0.266	0.188 + 0.039*SL	0.192 + 0.038*SL	0.193 + 0.038*SL
	t_{PHL}	0.369	0.280 + 0.045*SL	0.310 + 0.037*SL	0.331 + 0.034*SL
B to Y	t_R	0.249	0.086 + 0.081*SL	0.076 + 0.084*SL	0.070 + 0.085*SL
	t_F	0.250	0.121 + 0.065*SL	0.132 + 0.062*SL	0.127 + 0.063*SL
	t_{PLH}	0.292	0.214 + 0.039*SL	0.219 + 0.038*SL	0.220 + 0.038*SL
	t_{PHL}	0.411	0.322 + 0.045*SL	0.353 + 0.037*SL	0.373 + 0.034*SL
C to Y	t_R	0.255	0.091 + 0.082*SL	0.083 + 0.084*SL	0.077 + 0.084*SL
	t_F	0.250	0.120 + 0.065*SL	0.132 + 0.062*SL	0.127 + 0.063*SL
	t_{PLH}	0.310	0.230 + 0.040*SL	0.238 + 0.038*SL	0.241 + 0.038*SL
	t_{PHL}	0.433	0.344 + 0.045*SL	0.375 + 0.037*SL	0.396 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OR3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.150	0.077 + 0.037*SL	0.071 + 0.038*SL	0.065 + 0.039*SL
	t_F	0.186	0.112 + 0.037*SL	0.125 + 0.034*SL	0.133 + 0.033*SL
	t_{PLH}	0.226	0.186 + 0.020*SL	0.194 + 0.018*SL	0.196 + 0.018*SL
	t_{PHL}	0.338	0.283 + 0.028*SL	0.304 + 0.023*SL	0.324 + 0.020*SL
B to Y	t_R	0.153	0.079 + 0.037*SL	0.076 + 0.038*SL	0.068 + 0.039*SL
	t_F	0.187	0.113 + 0.037*SL	0.126 + 0.034*SL	0.134 + 0.033*SL
	t_{PLH}	0.251	0.211 + 0.020*SL	0.220 + 0.018*SL	0.223 + 0.018*SL
	t_{PHL}	0.379	0.324 + 0.028*SL	0.345 + 0.023*SL	0.366 + 0.020*SL
C to Y	t_R	0.159	0.086 + 0.037*SL	0.082 + 0.038*SL	0.075 + 0.039*SL
	t_F	0.187	0.113 + 0.037*SL	0.126 + 0.034*SL	0.133 + 0.033*SL
	t_{PLH}	0.268	0.227 + 0.021*SL	0.236 + 0.018*SL	0.241 + 0.018*SL
	t_{PHL}	0.400	0.345 + 0.028*SL	0.366 + 0.023*SL	0.387 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	0.074 + 0.019*SL	0.078 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.165	0.122 + 0.022*SL	0.135 + 0.018*SL	0.155 + 0.017*SL
	t_{PLH}	0.232	0.208 + 0.012*SL	0.219 + 0.010*SL	0.230 + 0.009*SL
	t_{PHL}	0.379	0.343 + 0.018*SL	0.359 + 0.014*SL	0.393 + 0.011*SL
B to Y	t_R	0.115	0.078 + 0.019*SL	0.081 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.165	0.122 + 0.022*SL	0.135 + 0.018*SL	0.155 + 0.017*SL
	t_{PLH}	0.257	0.232 + 0.013*SL	0.243 + 0.010*SL	0.255 + 0.009*SL
	t_{PHL}	0.421	0.385 + 0.018*SL	0.402 + 0.014*SL	0.435 + 0.011*SL
C to Y	t_R	0.121	0.084 + 0.019*SL	0.087 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.165	0.122 + 0.022*SL	0.135 + 0.018*SL	0.155 + 0.017*SL
	t_{PLH}	0.273	0.247 + 0.013*SL	0.260 + 0.010*SL	0.273 + 0.009*SL
	t_{PHL}	0.442	0.407 + 0.018*SL	0.423 + 0.014*SL	0.457 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OR3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.082 + 0.011*SL	0.089 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.172	0.150 + 0.011*SL	0.155 + 0.010*SL	0.182 + 0.008*SL
	t_{PLH}	0.253	0.238 + 0.008*SL	0.246 + 0.006*SL	0.266 + 0.004*SL
	t_{PHL}	0.430	0.408 + 0.011*SL	0.420 + 0.008*SL	0.458 + 0.006*SL
B to Y	t_R	0.109	0.088 + 0.010*SL	0.094 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.172	0.149 + 0.011*SL	0.155 + 0.010*SL	0.182 + 0.008*SL
	t_{PLH}	0.277	0.262 + 0.008*SL	0.271 + 0.006*SL	0.291 + 0.004*SL
	t_{PHL}	0.471	0.450 + 0.011*SL	0.461 + 0.008*SL	0.500 + 0.006*SL
C to Y	t_R	0.115	0.095 + 0.010*SL	0.099 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.172	0.149 + 0.011*SL	0.155 + 0.010*SL	0.182 + 0.008*SL
	t_{PLH}	0.295	0.279 + 0.008*SL	0.288 + 0.006*SL	0.310 + 0.005*SL
	t_{PHL}	0.491	0.470 + 0.011*SL	0.481 + 0.008*SL	0.520 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	0	0
1	x	x	x	1
x	1	x	x	1
x	x	1	x	1
x	x	x	1	1

Cell Data

Input Load (SL)															
OR4DH				*OR4*				*OR4D2*				*OR4D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.6	0.6	0.6	0.9	1.0	1.0	1.0	0.9	1.0	0.9	1.0	0.9	1.0	1.0	1.0

Gate Count			
OR4DH	*OR4*	*OR4D2*	*OR4D4*
2.67	2.67	3.00	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR4DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.254	0.089 + 0.083*SL	0.082 + 0.084*SL	0.078 + 0.085*SL
	t_F	0.293	0.125 + 0.084*SL	0.124 + 0.084*SL	0.115 + 0.085*SL
	t_{PLH}	0.253	0.176 + 0.038*SL	0.179 + 0.038*SL	0.180 + 0.038*SL
	t_{PHL}	0.356	0.262 + 0.047*SL	0.278 + 0.043*SL	0.284 + 0.042*SL
B to Y	t_R	0.256	0.090 + 0.083*SL	0.084 + 0.084*SL	0.080 + 0.085*SL
	t_F	0.293	0.126 + 0.084*SL	0.123 + 0.084*SL	0.115 + 0.085*SL
	t_{PLH}	0.275	0.197 + 0.039*SL	0.201 + 0.038*SL	0.202 + 0.038*SL
	t_{PHL}	0.369	0.275 + 0.047*SL	0.292 + 0.043*SL	0.298 + 0.042*SL
C to Y	t_R	0.274	0.109 + 0.083*SL	0.102 + 0.084*SL	0.097 + 0.085*SL
	t_F	0.283	0.114 + 0.084*SL	0.111 + 0.085*SL	0.106 + 0.086*SL
	t_{PLH}	0.264	0.188 + 0.038*SL	0.190 + 0.038*SL	0.191 + 0.038*SL
	t_{PHL}	0.352	0.260 + 0.046*SL	0.273 + 0.043*SL	0.279 + 0.042*SL
D to Y	t_R	0.275	0.110 + 0.083*SL	0.103 + 0.084*SL	0.099 + 0.085*SL
	t_F	0.283	0.114 + 0.084*SL	0.111 + 0.085*SL	0.106 + 0.086*SL
	t_{PLH}	0.287	0.210 + 0.038*SL	0.213 + 0.038*SL	0.214 + 0.038*SL
	t_{PHL}	0.366	0.274 + 0.046*SL	0.287 + 0.043*SL	0.292 + 0.042*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OR4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	0.083 + 0.036*SL	0.076 + 0.037*SL	0.071 + 0.038*SL
	t_F	0.188	0.105 + 0.042*SL	0.107 + 0.041*SL	0.102 + 0.042*SL
	t_{PLH}	0.214	0.176 + 0.019*SL	0.181 + 0.017*SL	0.183 + 0.017*SL
	t_{PHL}	0.264	0.215 + 0.024*SL	0.226 + 0.022*SL	0.233 + 0.021*SL
B to Y	t_R	0.156	0.083 + 0.037*SL	0.080 + 0.037*SL	0.075 + 0.038*SL
	t_F	0.188	0.105 + 0.041*SL	0.106 + 0.041*SL	0.103 + 0.042*SL
	t_{PLH}	0.241	0.203 + 0.019*SL	0.208 + 0.017*SL	0.210 + 0.017*SL
	t_{PHL}	0.275	0.225 + 0.025*SL	0.236 + 0.022*SL	0.243 + 0.021*SL
C to Y	t_R	0.171	0.099 + 0.036*SL	0.094 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.181	0.098 + 0.041*SL	0.098 + 0.042*SL	0.095 + 0.042*SL
	t_{PLH}	0.224	0.188 + 0.018*SL	0.191 + 0.017*SL	0.192 + 0.017*SL
	t_{PHL}	0.264	0.217 + 0.024*SL	0.225 + 0.022*SL	0.231 + 0.021*SL
D to Y	t_R	0.174	0.101 + 0.036*SL	0.097 + 0.037*SL	0.092 + 0.038*SL
	t_F	0.181	0.098 + 0.041*SL	0.097 + 0.042*SL	0.094 + 0.042*SL
	t_{PLH}	0.252	0.215 + 0.018*SL	0.219 + 0.017*SL	0.221 + 0.017*SL
	t_{PHL}	0.275	0.227 + 0.024*SL	0.235 + 0.022*SL	0.241 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	0.082 + 0.019*SL	0.083 + 0.018*SL	0.075 + 0.019*SL
	t_F	0.150	0.106 + 0.022*SL	0.111 + 0.021*SL	0.114 + 0.021*SL
	t_{PLH}	0.226	0.204 + 0.011*SL	0.211 + 0.009*SL	0.217 + 0.009*SL
	t_{PHL}	0.281	0.252 + 0.015*SL	0.262 + 0.012*SL	0.278 + 0.011*SL
B to Y	t_R	0.125	0.090 + 0.018*SL	0.087 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.151	0.106 + 0.022*SL	0.113 + 0.021*SL	0.113 + 0.021*SL
	t_{PLH}	0.251	0.228 + 0.011*SL	0.235 + 0.009*SL	0.243 + 0.009*SL
	t_{PHL}	0.292	0.262 + 0.015*SL	0.273 + 0.012*SL	0.289 + 0.011*SL
C to Y	t_R	0.141	0.105 + 0.018*SL	0.104 + 0.018*SL	0.095 + 0.019*SL
	t_F	0.144	0.100 + 0.022*SL	0.105 + 0.021*SL	0.105 + 0.021*SL
	t_{PLH}	0.244	0.223 + 0.011*SL	0.228 + 0.009*SL	0.233 + 0.009*SL
	t_{PHL}	0.290	0.262 + 0.014*SL	0.270 + 0.012*SL	0.283 + 0.011*SL
D to Y	t_R	0.144	0.108 + 0.018*SL	0.107 + 0.018*SL	0.099 + 0.019*SL
	t_F	0.146	0.103 + 0.021*SL	0.105 + 0.021*SL	0.105 + 0.021*SL
	t_{PLH}	0.270	0.248 + 0.011*SL	0.254 + 0.009*SL	0.259 + 0.009*SL
	t_{PHL}	0.301	0.272 + 0.014*SL	0.281 + 0.012*SL	0.294 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OR4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	0.075 + 0.009*SL	0.074 + 0.009*SL	0.069 + 0.009*SL
	t_F	0.086	0.067 + 0.009*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.405	0.390 + 0.007*SL	0.398 + 0.005*SL	0.413 + 0.004*SL
	t_{PHL}	0.428	0.412 + 0.008*SL	0.421 + 0.006*SL	0.440 + 0.005*SL
B to Y	t_R	0.093	0.072 + 0.010*SL	0.077 + 0.009*SL	0.069 + 0.010*SL
	t_F	0.083	0.062 + 0.010*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.431	0.417 + 0.007*SL	0.425 + 0.005*SL	0.440 + 0.004*SL
	t_{PHL}	0.438	0.423 + 0.008*SL	0.431 + 0.006*SL	0.450 + 0.005*SL
C to Y	t_R	0.093	0.073 + 0.010*SL	0.078 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.083	0.062 + 0.010*SL	0.070 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.413	0.399 + 0.007*SL	0.407 + 0.005*SL	0.422 + 0.004*SL
	t_{PHL}	0.414	0.399 + 0.008*SL	0.407 + 0.006*SL	0.426 + 0.005*SL
D to Y	t_R	0.093	0.072 + 0.010*SL	0.078 + 0.009*SL	0.069 + 0.009*SL
	t_F	0.085	0.067 + 0.009*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.442	0.428 + 0.007*SL	0.435 + 0.005*SL	0.450 + 0.004*SL
	t_{PHL}	0.425	0.409 + 0.008*SL	0.418 + 0.006*SL	0.437 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OR5/OR5D2/OR5D4

5-Input OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	0	0	0
1	x	x	x	x	1
x	1	x	x	x	1
x	x	1	x	x	1
x	x	x	1	x	1
x	x	x	x	1	1

Cell Data

Input Load (SL)															Gate Count		
OR5					*OR5D2*					*OR5D4*					*OR5*	*OR5D2*	*OR5D4*
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E			
0.9	0.9	0.9	1.0	1.0	0.8	0.9	0.9	0.9	1.0	0.9	0.9	1.0	1.0	1.1	3.00	3.33	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.161	0.088 + 0.036*SL	0.085 + 0.037*SL	0.079 + 0.038*SL
	t_F	0.213	0.126 + 0.044*SL	0.135 + 0.042*SL	0.138 + 0.041*SL
	t_{PLH}	0.248	0.209 + 0.019*SL	0.216 + 0.018*SL	0.219 + 0.017*SL
	t_{PHL}	0.322	0.266 + 0.028*SL	0.282 + 0.024*SL	0.298 + 0.022*SL
B to Y	t_R	0.166	0.094 + 0.036*SL	0.090 + 0.037*SL	0.083 + 0.038*SL
	t_F	0.214	0.127 + 0.044*SL	0.136 + 0.042*SL	0.138 + 0.041*SL
	t_{PLH}	0.281	0.241 + 0.020*SL	0.249 + 0.018*SL	0.253 + 0.017*SL
	t_{PHL}	0.362	0.306 + 0.028*SL	0.322 + 0.024*SL	0.338 + 0.022*SL
C to Y	t_R	0.173	0.100 + 0.036*SL	0.098 + 0.037*SL	0.091 + 0.038*SL
	t_F	0.214	0.127 + 0.044*SL	0.135 + 0.042*SL	0.138 + 0.041*SL
	t_{PLH}	0.302	0.261 + 0.020*SL	0.271 + 0.018*SL	0.276 + 0.017*SL
	t_{PHL}	0.381	0.325 + 0.028*SL	0.341 + 0.024*SL	0.357 + 0.022*SL
D to Y	t_R	0.171	0.098 + 0.036*SL	0.094 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.182	0.098 + 0.042*SL	0.098 + 0.042*SL	0.096 + 0.042*SL
	t_{PLH}	0.224	0.188 + 0.018*SL	0.191 + 0.017*SL	0.193 + 0.017*SL
	t_{PHL}	0.265	0.217 + 0.024*SL	0.225 + 0.022*SL	0.232 + 0.021*SL
E to Y	t_R	0.174	0.101 + 0.036*SL	0.097 + 0.037*SL	0.092 + 0.038*SL
	t_F	0.182	0.098 + 0.042*SL	0.098 + 0.042*SL	0.097 + 0.042*SL
	t_{PLH}	0.252	0.216 + 0.018*SL	0.219 + 0.017*SL	0.221 + 0.017*SL
	t_{PHL}	0.276	0.228 + 0.024*SL	0.236 + 0.022*SL	0.242 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.132	0.095 + 0.019*SL	0.096 + 0.018*SL	0.089 + 0.019*SL
	t_F	0.182	0.134 + 0.024*SL	0.143 + 0.022*SL	0.155 + 0.021*SL
	t_{PLH}	0.266	0.242 + 0.012*SL	0.251 + 0.010*SL	0.261 + 0.009*SL
	t_{PHL}	0.352	0.318 + 0.017*SL	0.330 + 0.014*SL	0.356 + 0.012*SL
B to Y	t_R	0.139	0.103 + 0.018*SL	0.101 + 0.018*SL	0.094 + 0.019*SL
	t_F	0.182	0.135 + 0.024*SL	0.144 + 0.022*SL	0.155 + 0.021*SL
	t_{PLH}	0.298	0.273 + 0.012*SL	0.283 + 0.010*SL	0.294 + 0.009*SL
	t_{PHL}	0.393	0.359 + 0.017*SL	0.371 + 0.014*SL	0.397 + 0.012*SL
C to Y	t_R	0.146	0.109 + 0.018*SL	0.109 + 0.018*SL	0.103 + 0.019*SL
	t_F	0.182	0.135 + 0.024*SL	0.143 + 0.022*SL	0.155 + 0.021*SL
	t_{PLH}	0.320	0.295 + 0.013*SL	0.305 + 0.010*SL	0.318 + 0.009*SL
	t_{PHL}	0.411	0.378 + 0.017*SL	0.390 + 0.014*SL	0.415 + 0.012*SL
D to Y	t_R	0.140	0.104 + 0.018*SL	0.104 + 0.018*SL	0.096 + 0.019*SL
	t_F	0.145	0.100 + 0.022*SL	0.105 + 0.021*SL	0.107 + 0.021*SL
	t_{PLH}	0.244	0.224 + 0.010*SL	0.229 + 0.009*SL	0.234 + 0.009*SL
	t_{PHL}	0.289	0.261 + 0.014*SL	0.269 + 0.012*SL	0.282 + 0.011*SL
E to Y	t_R	0.144	0.108 + 0.018*SL	0.108 + 0.018*SL	0.100 + 0.019*SL
	t_F	0.146	0.103 + 0.022*SL	0.105 + 0.021*SL	0.106 + 0.021*SL
	t_{PLH}	0.270	0.249 + 0.011*SL	0.254 + 0.009*SL	0.260 + 0.009*SL
	t_{PHL}	0.299	0.271 + 0.014*SL	0.279 + 0.012*SL	0.292 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OR5D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	0.073 + 0.010*SL	0.077 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.083	0.062 + 0.010*SL	0.070 + 0.008*SL	0.070 + 0.008*SL
	t_{PLH}	0.434	0.420 + 0.007*SL	0.428 + 0.005*SL	0.443 + 0.004*SL
	t_{PHL}	0.483	0.467 + 0.008*SL	0.476 + 0.006*SL	0.495 + 0.005*SL
B to Y	t_R	0.094	0.073 + 0.010*SL	0.078 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.083	0.063 + 0.010*SL	0.071 + 0.008*SL	0.070 + 0.008*SL
	t_{PLH}	0.461	0.447 + 0.007*SL	0.454 + 0.005*SL	0.470 + 0.004*SL
	t_{PHL}	0.522	0.506 + 0.008*SL	0.515 + 0.006*SL	0.533 + 0.005*SL
C to Y	t_R	0.093	0.073 + 0.010*SL	0.077 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.084	0.064 + 0.010*SL	0.071 + 0.008*SL	0.070 + 0.008*SL
	t_{PLH}	0.479	0.464 + 0.007*SL	0.472 + 0.005*SL	0.487 + 0.004*SL
	t_{PHL}	0.540	0.525 + 0.008*SL	0.533 + 0.006*SL	0.552 + 0.005*SL
D to Y	t_R	0.094	0.077 + 0.009*SL	0.075 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.083	0.063 + 0.010*SL	0.070 + 0.008*SL	0.070 + 0.008*SL
	t_{PLH}	0.417	0.403 + 0.007*SL	0.410 + 0.005*SL	0.426 + 0.004*SL
	t_{PHL}	0.411	0.396 + 0.008*SL	0.404 + 0.006*SL	0.422 + 0.005*SL
E to Y	t_R	0.094	0.076 + 0.009*SL	0.075 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.085	0.066 + 0.009*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.442	0.428 + 0.007*SL	0.436 + 0.005*SL	0.451 + 0.004*SL
	t_{PHL}	0.420	0.405 + 0.008*SL	0.414 + 0.006*SL	0.432 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

XN2/XN2D2/XN2D4

2-Input Exclusive-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	1

Cell Data

Input Load (SL)						Gate Count		
XN2		*XN2D2*		*XN2D4*		*XN2*	*XN2D2*	*XN2D4*
A	B	A	B	A	B			
0.8	1.5	0.8	1.5	0.8	1.5	2.33	2.67	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XN2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.169	0.096 + 0.037*SL	0.097 + 0.036*SL	0.091 + 0.037*SL
	t_F	0.171	0.104 + 0.033*SL	0.113 + 0.031*SL	0.115 + 0.031*SL
	t_{PLH}	0.367	0.324 + 0.021*SL	0.336 + 0.018*SL	0.344 + 0.017*SL
	t_{PHL}	0.396	0.349 + 0.024*SL	0.366 + 0.020*SL	0.380 + 0.018*SL
B to Y	t_R	0.165	0.090 + 0.037*SL	0.093 + 0.037*SL	0.088 + 0.037*SL
	t_F	0.164	0.096 + 0.034*SL	0.107 + 0.031*SL	0.110 + 0.031*SL
	t_{PLH}	0.331	0.288 + 0.021*SL	0.301 + 0.018*SL	0.308 + 0.017*SL
	t_{PHL}	0.311	0.261 + 0.025*SL	0.280 + 0.020*SL	0.297 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XN2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.137	0.095 + 0.021*SL	0.104 + 0.019*SL	0.105 + 0.019*SL
	t_F	0.150	0.108 + 0.021*SL	0.122 + 0.018*SL	0.136 + 0.016*SL
	t_{PLH}	0.380	0.351 + 0.014*SL	0.365 + 0.011*SL	0.384 + 0.009*SL
	t_{PHL}	0.422	0.389 + 0.016*SL	0.405 + 0.012*SL	0.433 + 0.010*SL
B to Y	t_R	0.134	0.092 + 0.021*SL	0.100 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.145	0.103 + 0.021*SL	0.118 + 0.018*SL	0.132 + 0.016*SL
	t_{PLH}	0.343	0.315 + 0.014*SL	0.329 + 0.011*SL	0.348 + 0.009*SL
	t_{PHL}	0.326	0.291 + 0.017*SL	0.309 + 0.013*SL	0.340 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

XN2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.155	0.133 + 0.011*SL	0.136 + 0.010*SL	0.155 + 0.009*SL
	t_F	0.184	0.160 + 0.012*SL	0.168 + 0.010*SL	0.196 + 0.008*SL
	t_{PLH}	0.458	0.440 + 0.009*SL	0.450 + 0.007*SL	0.481 + 0.005*SL
	t_{PHL}	0.523	0.502 + 0.010*SL	0.514 + 0.007*SL	0.551 + 0.005*SL
B to Y	t_R	0.155	0.132 + 0.011*SL	0.137 + 0.010*SL	0.154 + 0.009*SL
	t_F	0.182	0.158 + 0.012*SL	0.167 + 0.010*SL	0.195 + 0.008*SL
	t_{PLH}	0.416	0.398 + 0.009*SL	0.408 + 0.007*SL	0.439 + 0.005*SL
	t_{PHL}	0.415	0.392 + 0.011*SL	0.405 + 0.008*SL	0.447 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

XN3/XN3D2/XN3D4

3-Input Exclusive-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	1
0	0	1	0
0	1	0	0
0	1	1	1
1	0	0	0
1	0	1	1
1	1	0	1
1	1	1	0

Cell Data

Input Load (SL)									Gate Count		
XN3			*XN3D2*			*XN3D4*			*XN3*	*XN3D2*	*XN3D4*
A	B	C	A	B	C	A	B	C			
1.4	0.8	1.5	1.4	0.8	1.5	1.3	0.8	1.5	4.00	4.33	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XN3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.198	0.115 + 0.042*SL	0.130 + 0.038*SL	0.137 + 0.037*SL
	t_F	0.184	0.107 + 0.039*SL	0.125 + 0.034*SL	0.140 + 0.032*SL
	t_{PLH}	0.341	0.288 + 0.027*SL	0.307 + 0.022*SL	0.327 + 0.019*SL
	t_{PHL}	0.345	0.297 + 0.024*SL	0.314 + 0.020*SL	0.328 + 0.018*SL
B to Y	t_R	0.217	0.137 + 0.040*SL	0.149 + 0.037*SL	0.154 + 0.037*SL
	t_F	0.232	0.158 + 0.037*SL	0.177 + 0.032*SL	0.187 + 0.031*SL
	t_{PLH}	0.600	0.557 + 0.022*SL	0.570 + 0.019*SL	0.579 + 0.017*SL
	t_{PHL}	0.627	0.565 + 0.031*SL	0.591 + 0.024*SL	0.619 + 0.021*SL
C to Y	t_R	0.216	0.136 + 0.040*SL	0.148 + 0.037*SL	0.154 + 0.037*SL
	t_F	0.160	0.095 + 0.033*SL	0.103 + 0.031*SL	0.101 + 0.031*SL
	t_{PLH}	0.521	0.469 + 0.026*SL	0.488 + 0.021*SL	0.506 + 0.019*SL
	t_{PHL}	0.574	0.526 + 0.024*SL	0.544 + 0.020*SL	0.558 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XN3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.178	0.132 + 0.023*SL	0.142 + 0.020*SL	0.161 + 0.019*SL
	t_F	0.178	0.133 + 0.022*SL	0.146 + 0.019*SL	0.175 + 0.017*SL
	t_{PLH}	0.367	0.332 + 0.018*SL	0.349 + 0.013*SL	0.381 + 0.011*SL
	t_{PHL}	0.371	0.339 + 0.016*SL	0.354 + 0.012*SL	0.381 + 0.010*SL
B to Y	t_R	0.191	0.146 + 0.022*SL	0.156 + 0.020*SL	0.173 + 0.019*SL
	t_F	0.216	0.173 + 0.022*SL	0.187 + 0.018*SL	0.211 + 0.016*SL
	t_{PLH}	0.619	0.591 + 0.014*SL	0.605 + 0.011*SL	0.625 + 0.009*SL
	t_{PHL}	0.664	0.624 + 0.020*SL	0.645 + 0.015*SL	0.685 + 0.012*SL
C to Y	t_R	0.190	0.146 + 0.022*SL	0.155 + 0.020*SL	0.173 + 0.019*SL
	t_F	0.140	0.102 + 0.019*SL	0.113 + 0.016*SL	0.122 + 0.015*SL
	t_{PLH}	0.548	0.514 + 0.017*SL	0.530 + 0.013*SL	0.560 + 0.010*SL
	t_{PHL}	0.603	0.572 + 0.016*SL	0.587 + 0.012*SL	0.614 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

XN3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.217	0.194 + 0.011*SL	0.196 + 0.011*SL	0.220 + 0.010*SL
	t_F	0.273	0.246 + 0.013*SL	0.256 + 0.011*SL	0.289 + 0.009*SL
	t_{PLH}	0.469	0.446 + 0.012*SL	0.459 + 0.008*SL	0.501 + 0.006*SL
	t_{PHL}	0.497	0.469 + 0.014*SL	0.485 + 0.010*SL	0.538 + 0.007*SL
B to Y	t_R	0.145	0.123 + 0.011*SL	0.128 + 0.010*SL	0.140 + 0.009*SL
	t_F	0.259	0.234 + 0.013*SL	0.243 + 0.010*SL	0.273 + 0.009*SL
	t_{PLH}	0.691	0.673 + 0.009*SL	0.683 + 0.007*SL	0.714 + 0.005*SL
	t_{PHL}	0.786	0.760 + 0.013*SL	0.775 + 0.009*SL	0.824 + 0.007*SL
C to Y	t_R	0.200	0.177 + 0.011*SL	0.179 + 0.011*SL	0.203 + 0.010*SL
	t_F	0.292	0.266 + 0.013*SL	0.276 + 0.011*SL	0.308 + 0.009*SL
	t_{PLH}	0.640	0.618 + 0.011*SL	0.631 + 0.008*SL	0.669 + 0.006*SL
	t_{PHL}	0.693	0.665 + 0.014*SL	0.681 + 0.010*SL	0.734 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

XO2/XO2D2/XO2D4

2-Input Exclusive-OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	0

Cell Data

Input Load (SL)						Gate Count		
XO2		*XO2D2*		*XO2D4*		*XO2*	*XO2D2*	*XO2D4*
A	B	A	B	A	B			
0.8	1.3	0.8	1.3	0.8	1.3	2.33	2.67	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XO2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.176	0.101 + 0.037*SL	0.102 + 0.037*SL	0.097 + 0.038*SL
	t_F	0.180	0.110 + 0.035*SL	0.119 + 0.033*SL	0.122 + 0.032*SL
	t_{PLH}	0.376	0.332 + 0.022*SL	0.345 + 0.019*SL	0.353 + 0.018*SL
	t_{PHL}	0.418	0.368 + 0.025*SL	0.386 + 0.021*SL	0.401 + 0.019*SL
B to Y	t_R	0.175	0.099 + 0.038*SL	0.101 + 0.037*SL	0.096 + 0.038*SL
	t_F	0.171	0.099 + 0.036*SL	0.111 + 0.033*SL	0.115 + 0.033*SL
	t_{PLH}	0.312	0.266 + 0.023*SL	0.281 + 0.019*SL	0.291 + 0.018*SL
	t_{PHL}	0.360	0.311 + 0.025*SL	0.328 + 0.021*SL	0.343 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

XO2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.142	0.100 + 0.021*SL	0.108 + 0.019*SL	0.112 + 0.019*SL
	t_F	0.155	0.114 + 0.021*SL	0.125 + 0.018*SL	0.141 + 0.016*SL
	t_{PLH}	0.388	0.359 + 0.014*SL	0.373 + 0.011*SL	0.393 + 0.009*SL
	t_{PHL}	0.435	0.403 + 0.016*SL	0.418 + 0.012*SL	0.446 + 0.010*SL
B to Y	t_R	0.141	0.099 + 0.021*SL	0.108 + 0.019*SL	0.110 + 0.019*SL
	t_F	0.150	0.109 + 0.021*SL	0.120 + 0.018*SL	0.137 + 0.016*SL
	t_{PLH}	0.320	0.290 + 0.015*SL	0.305 + 0.011*SL	0.327 + 0.010*SL
	t_{PHL}	0.379	0.346 + 0.016*SL	0.362 + 0.012*SL	0.390 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

XO2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.157	0.135 + 0.011*SL	0.138 + 0.010*SL	0.156 + 0.009*SL
	t_F	0.182	0.159 + 0.012*SL	0.167 + 0.010*SL	0.195 + 0.008*SL
	t_{PLH}	0.457	0.439 + 0.009*SL	0.449 + 0.007*SL	0.480 + 0.005*SL
	t_{PHL}	0.528	0.507 + 0.010*SL	0.518 + 0.008*SL	0.556 + 0.006*SL
B to Y	t_R	0.157	0.135 + 0.011*SL	0.139 + 0.010*SL	0.156 + 0.009*SL
	t_F	0.182	0.159 + 0.012*SL	0.167 + 0.010*SL	0.194 + 0.008*SL
	t_{PLH}	0.383	0.363 + 0.010*SL	0.374 + 0.007*SL	0.408 + 0.005*SL
	t_{PHL}	0.470	0.450 + 0.010*SL	0.461 + 0.007*SL	0.499 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

XO3/XO3D2/XO3D4

3-Input Exclusive-OR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	0	0
0	0	1	1
0	1	0	1
0	1	1	0
1	0	0	1
1	0	1	0
1	1	0	0
1	1	1	1

Cell Data

Input Load (SL)									Gate Count		
XO3			*XO3D2*			*XO3D4*			*XO3*	*XO3D2*	*XO3D4*
A	B	C	A	B	C	A	B	C			
1.4	0.8	1.5	1.4	0.8	1.5	1.4	0.8	1.5	4.00	4.33	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XO3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.183	0.102 + 0.040*SL	0.112 + 0.038*SL	0.116 + 0.037*SL
	t_F	0.210	0.130 + 0.040*SL	0.150 + 0.035*SL	0.171 + 0.032*SL
	t_{PLH}	0.324	0.281 + 0.021*SL	0.294 + 0.018*SL	0.301 + 0.017*SL
	t_{PHL}	0.354	0.292 + 0.031*SL	0.316 + 0.025*SL	0.344 + 0.021*SL
B to Y	t_R	0.217	0.136 + 0.040*SL	0.148 + 0.037*SL	0.154 + 0.037*SL
	t_F	0.232	0.158 + 0.037*SL	0.176 + 0.032*SL	0.186 + 0.031*SL
	t_{PLH}	0.600	0.556 + 0.022*SL	0.570 + 0.019*SL	0.578 + 0.017*SL
	t_{PHL}	0.627	0.566 + 0.031*SL	0.592 + 0.024*SL	0.620 + 0.021*SL
C to Y	t_R	0.217	0.136 + 0.040*SL	0.149 + 0.037*SL	0.154 + 0.037*SL
	t_F	0.161	0.096 + 0.032*SL	0.102 + 0.031*SL	0.101 + 0.031*SL
	t_{PLH}	0.517	0.465 + 0.026*SL	0.485 + 0.021*SL	0.503 + 0.019*SL
	t_{PHL}	0.571	0.524 + 0.024*SL	0.541 + 0.020*SL	0.555 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

XO3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.159	0.113 + 0.023*SL	0.124 + 0.020*SL	0.140 + 0.019*SL
	t_F	0.209	0.163 + 0.023*SL	0.178 + 0.020*SL	0.209 + 0.017*SL
	t_{PLH}	0.340	0.312 + 0.014*SL	0.325 + 0.011*SL	0.344 + 0.009*SL
	t_{PHL}	0.390	0.348 + 0.021*SL	0.370 + 0.016*SL	0.412 + 0.012*SL
B to Y	t_R	0.191	0.146 + 0.022*SL	0.156 + 0.020*SL	0.174 + 0.019*SL
	t_F	0.216	0.174 + 0.021*SL	0.187 + 0.018*SL	0.211 + 0.016*SL
	t_{PLH}	0.620	0.592 + 0.014*SL	0.606 + 0.011*SL	0.625 + 0.009*SL
	t_{PHL}	0.666	0.626 + 0.020*SL	0.647 + 0.015*SL	0.687 + 0.012*SL
C to Y	t_R	0.190	0.145 + 0.022*SL	0.154 + 0.020*SL	0.173 + 0.019*SL
	t_F	0.140	0.102 + 0.019*SL	0.113 + 0.016*SL	0.122 + 0.015*SL
	t_{PLH}	0.544	0.510 + 0.017*SL	0.527 + 0.013*SL	0.557 + 0.010*SL
	t_{PHL}	0.602	0.570 + 0.016*SL	0.586 + 0.012*SL	0.612 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

XO3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.214	0.190 + 0.012*SL	0.194 + 0.011*SL	0.218 + 0.010*SL
	t_F	0.279	0.253 + 0.013*SL	0.263 + 0.011*SL	0.294 + 0.009*SL
	t_{PLH}	0.417	0.394 + 0.012*SL	0.407 + 0.008*SL	0.449 + 0.006*SL
	t_{PHL}	0.519	0.491 + 0.014*SL	0.507 + 0.010*SL	0.560 + 0.007*SL
B to Y	t_R	0.145	0.123 + 0.011*SL	0.127 + 0.010*SL	0.139 + 0.009*SL
	t_F	0.258	0.233 + 0.013*SL	0.243 + 0.010*SL	0.272 + 0.009*SL
	t_{PLH}	0.689	0.671 + 0.009*SL	0.681 + 0.007*SL	0.712 + 0.005*SL
	t_{PHL}	0.786	0.760 + 0.013*SL	0.775 + 0.009*SL	0.824 + 0.007*SL
C to Y	t_R	0.199	0.176 + 0.011*SL	0.178 + 0.011*SL	0.202 + 0.010*SL
	t_F	0.291	0.265 + 0.013*SL	0.275 + 0.010*SL	0.307 + 0.009*SL
	t_{PLH}	0.635	0.613 + 0.011*SL	0.625 + 0.008*SL	0.664 + 0.006*SL
	t_{PHL}	0.693	0.665 + 0.014*SL	0.682 + 0.010*SL	0.734 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO21DH/AO21/AO21D2/AO21D2B/AO21D4

2-AND into 2-NOR with 0.5X/1X/2X/2X(Bufferd)/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	0	1
x	0	0	1
Other States			0

Cell Data

Input Load (SL)														
AO21DH			*AO21*			*AO21D2*			*AO21D2B*			*AO21D4*		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.5	0.5	0.9	0.9	0.9	1.9	1.8	2.0	0.9	0.9	1.0	0.9	1.0	1.0

Gate Count				
AO21DH	*AO21*	*AO21D2*	*AO21D2B*	*AO21D4*
1.33	1.33	2.33	2.33	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO21DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.493	0.185 + 0.154*SL	0.163 + 0.159*SL	0.157 + 0.160*SL
	t_F	0.326	0.126 + 0.100*SL	0.108 + 0.105*SL	0.092 + 0.107*SL
	t_{PLH}	0.266	0.122 + 0.072*SL	0.122 + 0.072*SL	0.123 + 0.072*SL
	t_{PHL}	0.215	0.110 + 0.052*SL	0.112 + 0.052*SL	0.113 + 0.052*SL
B to Y	t_R	0.523	0.213 + 0.155*SL	0.192 + 0.160*SL	0.188 + 0.161*SL
	t_F	0.320	0.115 + 0.102*SL	0.103 + 0.105*SL	0.093 + 0.107*SL
	t_{PLH}	0.287	0.143 + 0.072*SL	0.143 + 0.072*SL	0.144 + 0.072*SL
	t_{PHL}	0.210	0.105 + 0.053*SL	0.108 + 0.052*SL	0.109 + 0.052*SL
C to Y	t_R	0.518	0.203 + 0.157*SL	0.193 + 0.160*SL	0.190 + 0.160*SL
	t_F	0.260	0.142 + 0.059*SL	0.128 + 0.063*SL	0.112 + 0.065*SL
	t_{PLH}	0.330	0.185 + 0.073*SL	0.187 + 0.072*SL	0.188 + 0.072*SL
	t_{PHL}	0.202	0.133 + 0.034*SL	0.136 + 0.034*SL	0.138 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.314	0.169 + 0.073*SL	0.157 + 0.076*SL	0.140 + 0.078*SL
	t_F	0.251	0.128 + 0.061*SL	0.116 + 0.064*SL	0.101 + 0.066*SL
	t_{PLH}	0.176	0.105 + 0.036*SL	0.107 + 0.035*SL	0.107 + 0.035*SL
	t_{PHL}	0.177	0.110 + 0.034*SL	0.114 + 0.033*SL	0.115 + 0.033*SL
B to Y	t_R	0.337	0.191 + 0.073*SL	0.178 + 0.076*SL	0.163 + 0.078*SL
	t_F	0.243	0.117 + 0.063*SL	0.108 + 0.065*SL	0.099 + 0.066*SL
	t_{PLH}	0.194	0.123 + 0.035*SL	0.123 + 0.035*SL	0.123 + 0.035*SL
	t_{PHL}	0.171	0.103 + 0.034*SL	0.108 + 0.033*SL	0.110 + 0.033*SL
C to Y	t_R	0.326	0.174 + 0.076*SL	0.167 + 0.078*SL	0.160 + 0.079*SL
	t_F	0.219	0.146 + 0.036*SL	0.139 + 0.038*SL	0.130 + 0.039*SL
	t_{PLH}	0.230	0.158 + 0.036*SL	0.159 + 0.036*SL	0.161 + 0.035*SL
	t_{PHL}	0.184	0.140 + 0.022*SL	0.142 + 0.021*SL	0.144 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AO21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.241	0.171 + 0.035*SL	0.164 + 0.037*SL	0.147 + 0.038*SL
	t_F	0.193	0.134 + 0.030*SL	0.126 + 0.032*SL	0.110 + 0.033*SL
	t_{PLH}	0.141	0.103 + 0.019*SL	0.110 + 0.017*SL	0.110 + 0.017*SL
	t_{PHL}	0.144	0.107 + 0.018*SL	0.115 + 0.016*SL	0.116 + 0.016*SL
B to Y	t_R	0.264	0.194 + 0.035*SL	0.186 + 0.037*SL	0.169 + 0.039*SL
	t_F	0.184	0.124 + 0.030*SL	0.115 + 0.032*SL	0.106 + 0.033*SL
	t_{PLH}	0.159	0.123 + 0.018*SL	0.126 + 0.017*SL	0.125 + 0.017*SL
	t_{PHL}	0.138	0.102 + 0.018*SL	0.109 + 0.016*SL	0.111 + 0.016*SL
C to Y	t_R	0.250	0.176 + 0.037*SL	0.171 + 0.038*SL	0.162 + 0.039*SL
	t_F	0.181	0.146 + 0.017*SL	0.141 + 0.019*SL	0.130 + 0.020*SL
	t_{PLH}	0.189	0.153 + 0.018*SL	0.155 + 0.018*SL	0.157 + 0.018*SL
	t_{PHL}	0.161	0.138 + 0.011*SL	0.141 + 0.011*SL	0.143 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO21D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	0.072 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.099	0.066 + 0.016*SL	0.069 + 0.016*SL	0.067 + 0.016*SL
	t_{PLH}	0.329	0.305 + 0.012*SL	0.315 + 0.009*SL	0.323 + 0.009*SL
	t_{PHL}	0.339	0.314 + 0.013*SL	0.325 + 0.010*SL	0.338 + 0.009*SL
B to Y	t_R	0.109	0.073 + 0.018*SL	0.073 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.097	0.063 + 0.017*SL	0.070 + 0.015*SL	0.067 + 0.016*SL
	t_{PLH}	0.349	0.325 + 0.012*SL	0.335 + 0.009*SL	0.343 + 0.009*SL
	t_{PHL}	0.333	0.307 + 0.013*SL	0.319 + 0.010*SL	0.332 + 0.009*SL
C to Y	t_R	0.109	0.072 + 0.018*SL	0.072 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.097	0.064 + 0.017*SL	0.068 + 0.016*SL	0.066 + 0.016*SL
	t_{PLH}	0.387	0.364 + 0.012*SL	0.374 + 0.009*SL	0.382 + 0.009*SL
	t_{PHL}	0.351	0.326 + 0.013*SL	0.338 + 0.010*SL	0.351 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO21D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.078 + 0.009*SL	0.078 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.087	0.068 + 0.009*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.356	0.342 + 0.007*SL	0.350 + 0.005*SL	0.365 + 0.004*SL
	t_{PHL}	0.353	0.338 + 0.008*SL	0.347 + 0.005*SL	0.365 + 0.004*SL
B to Y	t_R	0.097	0.078 + 0.009*SL	0.079 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.084	0.064 + 0.010*SL	0.072 + 0.008*SL	0.072 + 0.008*SL
	t_{PLH}	0.376	0.362 + 0.007*SL	0.370 + 0.005*SL	0.385 + 0.004*SL
	t_{PHL}	0.347	0.332 + 0.008*SL	0.340 + 0.005*SL	0.359 + 0.004*SL
C to Y	t_R	0.096	0.077 + 0.010*SL	0.080 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.083	0.064 + 0.010*SL	0.071 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.413	0.399 + 0.007*SL	0.406 + 0.005*SL	0.422 + 0.004*SL
	t_{PHL}	0.357	0.342 + 0.007*SL	0.351 + 0.005*SL	0.369 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	0	0	1
x	0	0	0	1
Other States				0

Cell Data

Input Load (SL)																			
AO211DH				*AO211*				*AO211D2*				*AO211D2B*				*AO211D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.6	0.6	0.6	0.9	0.9	0.8	0.9	1.7	1.8	1.8	2.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9

Gate Count				
AO211DH	*AO211*	*AO211D2*	*AO211D2B*	*AO211D4*
1.67	1.67	2.67	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO211DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.767	0.333 + 0.217*SL	0.317 + 0.221*SL	0.331 + 0.219*SL
	t_F	0.383	0.161 + 0.111*SL	0.145 + 0.115*SL	0.134 + 0.117*SL
	t_{PLH}	0.345	0.146 + 0.100*SL	0.147 + 0.099*SL	0.149 + 0.099*SL
	t_{PHL}	0.250	0.137 + 0.057*SL	0.138 + 0.056*SL	0.138 + 0.056*SL
B to Y	t_R	0.803	0.369 + 0.217*SL	0.354 + 0.220*SL	0.368 + 0.219*SL
	t_F	0.379	0.153 + 0.113*SL	0.143 + 0.115*SL	0.134 + 0.117*SL
	t_{PLH}	0.370	0.172 + 0.099*SL	0.173 + 0.099*SL	0.174 + 0.099*SL
	t_{PHL}	0.245	0.132 + 0.057*SL	0.133 + 0.057*SL	0.135 + 0.056*SL
C to Y	t_R	0.817	0.385 + 0.216*SL	0.378 + 0.218*SL	0.376 + 0.218*SL
	t_F	0.281	0.160 + 0.060*SL	0.149 + 0.063*SL	0.135 + 0.065*SL
	t_{PLH}	0.479	0.279 + 0.100*SL	0.282 + 0.099*SL	0.285 + 0.099*SL
	t_{PHL}	0.221	0.152 + 0.034*SL	0.155 + 0.034*SL	0.157 + 0.033*SL
D to Y	t_R	0.817	0.385 + 0.216*SL	0.378 + 0.218*SL	0.376 + 0.218*SL
	t_F	0.306	0.185 + 0.061*SL	0.175 + 0.063*SL	0.162 + 0.065*SL
	t_{PLH}	0.493	0.294 + 0.100*SL	0.296 + 0.099*SL	0.299 + 0.099*SL
	t_{PHL}	0.230	0.159 + 0.035*SL	0.164 + 0.034*SL	0.169 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO211

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.505	0.281 + 0.112*SL	0.270 + 0.115*SL	0.257 + 0.117*SL
	t_F	0.291	0.153 + 0.069*SL	0.142 + 0.072*SL	0.128 + 0.074*SL
	t_{PLH}	0.228	0.126 + 0.051*SL	0.120 + 0.053*SL	0.122 + 0.052*SL
	t_{PHL}	0.205	0.133 + 0.036*SL	0.134 + 0.036*SL	0.135 + 0.036*SL
B to Y	t_R	0.533	0.309 + 0.112*SL	0.299 + 0.115*SL	0.286 + 0.116*SL
	t_F	0.285	0.144 + 0.071*SL	0.136 + 0.073*SL	0.128 + 0.074*SL
	t_{PLH}	0.248	0.145 + 0.051*SL	0.141 + 0.052*SL	0.142 + 0.052*SL
	t_{PHL}	0.199	0.126 + 0.037*SL	0.128 + 0.036*SL	0.130 + 0.036*SL
C to Y	t_R	0.544	0.319 + 0.112*SL	0.311 + 0.114*SL	0.306 + 0.115*SL
	t_F	0.280	0.182 + 0.049*SL	0.176 + 0.051*SL	0.167 + 0.052*SL
	t_{PLH}	0.338	0.232 + 0.053*SL	0.235 + 0.052*SL	0.236 + 0.052*SL
	t_{PHL}	0.234	0.178 + 0.028*SL	0.181 + 0.027*SL	0.184 + 0.027*SL
D to Y	t_R	0.542	0.316 + 0.113*SL	0.310 + 0.115*SL	0.306 + 0.115*SL
	t_F	0.316	0.216 + 0.050*SL	0.212 + 0.051*SL	0.203 + 0.052*SL
	t_{PLH}	0.352	0.246 + 0.053*SL	0.248 + 0.052*SL	0.250 + 0.052*SL
	t_{PHL}	0.250	0.193 + 0.029*SL	0.197 + 0.028*SL	0.201 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AO211D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.375	0.263 + 0.056*SL	0.256 + 0.057*SL	0.239 + 0.059*SL
	t_F	0.213	0.146 + 0.033*SL	0.138 + 0.035*SL	0.122 + 0.037*SL
	t_{PLH}	0.175	0.124 + 0.025*SL	0.119 + 0.027*SL	0.119 + 0.027*SL
	t_{PHL}	0.161	0.122 + 0.019*SL	0.127 + 0.018*SL	0.128 + 0.018*SL
B to Y	t_R	0.403	0.292 + 0.055*SL	0.285 + 0.057*SL	0.268 + 0.059*SL
	t_F	0.205	0.137 + 0.034*SL	0.129 + 0.036*SL	0.120 + 0.037*SL
	t_{PLH}	0.195	0.145 + 0.025*SL	0.140 + 0.026*SL	0.140 + 0.026*SL
	t_{PHL}	0.155	0.116 + 0.019*SL	0.121 + 0.018*SL	0.123 + 0.018*SL
C to Y	t_R	0.408	0.296 + 0.056*SL	0.290 + 0.057*SL	0.282 + 0.058*SL
	t_F	0.216	0.168 + 0.024*SL	0.165 + 0.025*SL	0.154 + 0.026*SL
	t_{PLH}	0.271	0.216 + 0.027*SL	0.218 + 0.027*SL	0.221 + 0.026*SL
	t_{PHL}	0.196	0.168 + 0.014*SL	0.170 + 0.014*SL	0.173 + 0.013*SL
D to Y	t_R	0.406	0.293 + 0.056*SL	0.287 + 0.058*SL	0.281 + 0.058*SL
	t_F	0.251	0.202 + 0.024*SL	0.200 + 0.025*SL	0.189 + 0.026*SL
	t_{PLH}	0.287	0.233 + 0.027*SL	0.235 + 0.027*SL	0.237 + 0.026*SL
	t_{PHL}	0.213	0.183 + 0.015*SL	0.186 + 0.014*SL	0.191 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO211D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.116	0.080 + 0.018*SL	0.081 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.395	0.371 + 0.012*SL	0.382 + 0.010*SL	0.392 + 0.009*SL
	t_{PHL}	0.376	0.351 + 0.013*SL	0.362 + 0.010*SL	0.376 + 0.009*SL
B to Y	t_R	0.116	0.080 + 0.018*SL	0.080 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.420	0.396 + 0.012*SL	0.407 + 0.010*SL	0.417 + 0.009*SL
	t_{PHL}	0.371	0.346 + 0.013*SL	0.357 + 0.010*SL	0.371 + 0.009*SL
C to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.099	0.066 + 0.017*SL	0.072 + 0.015*SL	0.068 + 0.016*SL
	t_{PLH}	0.511	0.487 + 0.012*SL	0.497 + 0.010*SL	0.508 + 0.009*SL
	t_{PHL}	0.411	0.386 + 0.013*SL	0.398 + 0.010*SL	0.410 + 0.009*SL
D to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.527	0.502 + 0.012*SL	0.513 + 0.010*SL	0.523 + 0.009*SL
	t_{PHL}	0.435	0.410 + 0.013*SL	0.421 + 0.010*SL	0.434 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO211D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.105	0.085 + 0.010*SL	0.089 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.087	0.067 + 0.010*SL	0.075 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.429	0.415 + 0.007*SL	0.423 + 0.005*SL	0.440 + 0.004*SL
	t_{PHL}	0.389	0.374 + 0.008*SL	0.382 + 0.005*SL	0.401 + 0.004*SL
B to Y	t_R	0.104	0.084 + 0.010*SL	0.090 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.087	0.069 + 0.009*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.454	0.439 + 0.007*SL	0.448 + 0.005*SL	0.465 + 0.004*SL
	t_{PHL}	0.384	0.369 + 0.007*SL	0.377 + 0.005*SL	0.396 + 0.004*SL
C to Y	t_R	0.105	0.085 + 0.010*SL	0.089 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.086	0.069 + 0.009*SL	0.072 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.545	0.530 + 0.007*SL	0.538 + 0.005*SL	0.556 + 0.004*SL
	t_{PHL}	0.418	0.403 + 0.007*SL	0.411 + 0.005*SL	0.430 + 0.004*SL
D to Y	t_R	0.105	0.086 + 0.010*SL	0.090 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.088	0.070 + 0.009*SL	0.074 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.558	0.543 + 0.007*SL	0.552 + 0.005*SL	0.569 + 0.004*SL
	t_{PHL}	0.441	0.426 + 0.007*SL	0.434 + 0.005*SL	0.453 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO2111/AO2111D2

2-AND into 4-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	0
x	x	1	x	x	0
x	x	x	1	x	0
x	x	x	x	1	0
Other states					1

Cell Data

Input Load (SL)										Gate Count	
A02111					*AO2111D2*					*AO2111*	*AO2111D2*
A	B	C	D	E	A	B	C	D	E		
0.9	0.9	0.8	0.8	0.8	0.9	0.9	0.8	0.8	0.9	2.00	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO2111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.719	0.411 + 0.154*SL	0.402 + 0.156*SL	0.396 + 0.157*SL
	t_F	0.315	0.170 + 0.073*SL	0.158 + 0.076*SL	0.147 + 0.077*SL
	t_{PLH}	0.271	0.135 + 0.068*SL	0.124 + 0.071*SL	0.127 + 0.070*SL
	t_{PHL}	0.219	0.144 + 0.038*SL	0.144 + 0.038*SL	0.145 + 0.037*SL
B to Y	t_R	0.758	0.451 + 0.153*SL	0.441 + 0.156*SL	0.435 + 0.157*SL
	t_F	0.310	0.161 + 0.074*SL	0.155 + 0.076*SL	0.147 + 0.077*SL
	t_{PLH}	0.297	0.159 + 0.069*SL	0.153 + 0.070*SL	0.155 + 0.070*SL
	t_{PHL}	0.214	0.138 + 0.038*SL	0.140 + 0.038*SL	0.141 + 0.038*SL
C to Y	t_R	0.799	0.495 + 0.152*SL	0.489 + 0.153*SL	0.486 + 0.154*SL
	t_F	0.340	0.218 + 0.061*SL	0.213 + 0.062*SL	0.205 + 0.063*SL
	t_{PLH}	0.439	0.297 + 0.071*SL	0.300 + 0.070*SL	0.303 + 0.070*SL
	t_{PHL}	0.279	0.212 + 0.034*SL	0.215 + 0.033*SL	0.217 + 0.033*SL
D to Y	t_R	0.801	0.498 + 0.151*SL	0.491 + 0.153*SL	0.486 + 0.154*SL
	t_F	0.384	0.261 + 0.061*SL	0.257 + 0.062*SL	0.251 + 0.063*SL
	t_{PLH}	0.487	0.345 + 0.071*SL	0.348 + 0.070*SL	0.350 + 0.070*SL
	t_{PHL}	0.304	0.235 + 0.035*SL	0.240 + 0.033*SL	0.244 + 0.033*SL
E to Y	t_R	0.800	0.497 + 0.151*SL	0.491 + 0.153*SL	0.486 + 0.154*SL
	t_F	0.428	0.303 + 0.062*SL	0.300 + 0.063*SL	0.296 + 0.063*SL
	t_{PLH}	0.509	0.366 + 0.071*SL	0.369 + 0.070*SL	0.372 + 0.070*SL
	t_{PHL}	0.321	0.249 + 0.036*SL	0.256 + 0.034*SL	0.263 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO2111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	0.084 + 0.018*SL	0.085 + 0.018*SL	0.075 + 0.018*SL
	t_F	0.101	0.068 + 0.016*SL	0.072 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.421	0.396 + 0.012*SL	0.408 + 0.010*SL	0.419 + 0.009*SL
	t_{PHL}	0.380	0.355 + 0.013*SL	0.366 + 0.010*SL	0.380 + 0.009*SL
B to Y	t_R	0.121	0.085 + 0.018*SL	0.088 + 0.017*SL	0.076 + 0.018*SL
	t_F	0.100	0.066 + 0.017*SL	0.072 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.452	0.427 + 0.013*SL	0.439 + 0.010*SL	0.450 + 0.009*SL
	t_{PHL}	0.374	0.349 + 0.013*SL	0.360 + 0.010*SL	0.374 + 0.009*SL
C to Y	t_R	0.123	0.088 + 0.018*SL	0.089 + 0.017*SL	0.078 + 0.018*SL
	t_F	0.101	0.068 + 0.016*SL	0.073 + 0.015*SL	0.068 + 0.016*SL
	t_{PLH}	0.595	0.569 + 0.013*SL	0.581 + 0.010*SL	0.593 + 0.009*SL
	t_{PHL}	0.449	0.424 + 0.013*SL	0.435 + 0.010*SL	0.449 + 0.009*SL
D to Y	t_R	0.122	0.087 + 0.018*SL	0.087 + 0.018*SL	0.078 + 0.018*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.644	0.619 + 0.013*SL	0.630 + 0.010*SL	0.642 + 0.009*SL
	t_{PHL}	0.481	0.456 + 0.013*SL	0.468 + 0.010*SL	0.481 + 0.009*SL
E to Y	t_R	0.122	0.087 + 0.018*SL	0.087 + 0.018*SL	0.078 + 0.018*SL
	t_F	0.104	0.071 + 0.016*SL	0.076 + 0.015*SL	0.072 + 0.016*SL
	t_{PLH}	0.665	0.640 + 0.013*SL	0.652 + 0.010*SL	0.663 + 0.009*SL
	t_{PHL}	0.504	0.479 + 0.013*SL	0.491 + 0.010*SL	0.504 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	0
x	x	1	1	0
0	x	0	x	1
0	x	x	0	1
x	0	x	0	1
x	0	0	x	1

Cell Data

Input Load (SL)																			
AO22DH				*AO22*				*AO22D2*				*AO22D2B*				*AO22D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	2.0	1.9	2.1	2.0	1.0	1.1	1.1	1.0	1.0	1.1	1.0	1.0

Gate Count				
AO22DH	*AO22*	*AO22D2*	*AO22D2B*	*AO22D4*
1.67	1.67	2.67	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO22DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.578	0.238 + 0.170*SL	0.219 + 0.175*SL	0.221 + 0.175*SL
	t_F	0.379	0.166 + 0.106*SL	0.147 + 0.111*SL	0.131 + 0.113*SL
	t_{PLH}	0.305	0.147 + 0.079*SL	0.149 + 0.079*SL	0.150 + 0.078*SL
	t_{PHL}	0.232	0.121 + 0.056*SL	0.122 + 0.055*SL	0.125 + 0.055*SL
B to Y	t_R	0.608	0.267 + 0.171*SL	0.249 + 0.175*SL	0.251 + 0.175*SL
	t_F	0.372	0.155 + 0.109*SL	0.144 + 0.112*SL	0.132 + 0.113*SL
	t_{PLH}	0.326	0.168 + 0.079*SL	0.169 + 0.079*SL	0.170 + 0.078*SL
	t_{PHL}	0.226	0.114 + 0.056*SL	0.118 + 0.055*SL	0.121 + 0.055*SL
C to Y	t_R	0.580	0.237 + 0.172*SL	0.228 + 0.174*SL	0.226 + 0.174*SL
	t_F	0.445	0.228 + 0.109*SL	0.214 + 0.112*SL	0.206 + 0.113*SL
	t_{PLH}	0.382	0.223 + 0.080*SL	0.226 + 0.079*SL	0.228 + 0.078*SL
	t_{PHL}	0.304	0.189 + 0.057*SL	0.196 + 0.055*SL	0.200 + 0.055*SL
D to Y	t_R	0.610	0.266 + 0.172*SL	0.259 + 0.174*SL	0.256 + 0.174*SL
	t_F	0.442	0.221 + 0.110*SL	0.213 + 0.112*SL	0.206 + 0.113*SL
	t_{PLH}	0.404	0.246 + 0.079*SL	0.248 + 0.079*SL	0.249 + 0.078*SL
	t_{PHL}	0.299	0.185 + 0.057*SL	0.192 + 0.056*SL	0.196 + 0.055*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.355	0.208 + 0.074*SL	0.198 + 0.076*SL	0.186 + 0.078*SL
	t_F	0.255	0.157 + 0.049*SL	0.145 + 0.052*SL	0.134 + 0.053*SL
	t_{PLH}	0.202	0.133 + 0.035*SL	0.131 + 0.035*SL	0.132 + 0.035*SL
	t_{PHL}	0.164	0.108 + 0.028*SL	0.113 + 0.027*SL	0.114 + 0.027*SL
B to Y	t_R	0.381	0.233 + 0.074*SL	0.224 + 0.076*SL	0.211 + 0.078*SL
	t_F	0.246	0.145 + 0.051*SL	0.136 + 0.053*SL	0.128 + 0.054*SL
	t_{PLH}	0.221	0.151 + 0.035*SL	0.150 + 0.035*SL	0.151 + 0.035*SL
	t_{PHL}	0.158	0.101 + 0.028*SL	0.107 + 0.027*SL	0.109 + 0.027*SL
C to Y	t_R	0.351	0.201 + 0.075*SL	0.193 + 0.077*SL	0.187 + 0.078*SL
	t_F	0.312	0.210 + 0.051*SL	0.203 + 0.053*SL	0.194 + 0.054*SL
	t_{PLH}	0.260	0.188 + 0.036*SL	0.190 + 0.035*SL	0.192 + 0.035*SL
	t_{PHL}	0.232	0.176 + 0.028*SL	0.179 + 0.027*SL	0.182 + 0.027*SL
D to Y	t_R	0.376	0.225 + 0.076*SL	0.219 + 0.077*SL	0.213 + 0.078*SL
	t_F	0.306	0.202 + 0.052*SL	0.198 + 0.053*SL	0.192 + 0.054*SL
	t_{PLH}	0.280	0.209 + 0.036*SL	0.211 + 0.035*SL	0.212 + 0.035*SL
	t_{PHL}	0.227	0.170 + 0.028*SL	0.174 + 0.027*SL	0.178 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AO22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.284	0.211 + 0.037*SL	0.206 + 0.038*SL	0.191 + 0.039*SL
	t_F	0.217	0.168 + 0.025*SL	0.160 + 0.026*SL	0.144 + 0.028*SL
	t_{PLH}	0.172	0.137 + 0.018*SL	0.137 + 0.018*SL	0.137 + 0.018*SL
	t_{PHL}	0.138	0.106 + 0.016*SL	0.114 + 0.014*SL	0.116 + 0.014*SL
B to Y	t_R	0.312	0.238 + 0.037*SL	0.233 + 0.038*SL	0.220 + 0.039*SL
	t_F	0.206	0.155 + 0.025*SL	0.149 + 0.027*SL	0.137 + 0.028*SL
	t_{PLH}	0.193	0.158 + 0.018*SL	0.157 + 0.018*SL	0.158 + 0.018*SL
	t_{PHL}	0.134	0.103 + 0.016*SL	0.109 + 0.014*SL	0.112 + 0.014*SL
C to Y	t_R	0.276	0.201 + 0.037*SL	0.197 + 0.038*SL	0.188 + 0.039*SL
	t_F	0.257	0.207 + 0.025*SL	0.203 + 0.026*SL	0.193 + 0.027*SL
	t_{PLH}	0.221	0.185 + 0.018*SL	0.186 + 0.018*SL	0.189 + 0.018*SL
	t_{PHL}	0.200	0.171 + 0.014*SL	0.173 + 0.014*SL	0.177 + 0.014*SL
D to Y	t_R	0.305	0.228 + 0.038*SL	0.225 + 0.039*SL	0.218 + 0.039*SL
	t_F	0.250	0.198 + 0.026*SL	0.195 + 0.027*SL	0.189 + 0.027*SL
	t_{PLH}	0.244	0.208 + 0.018*SL	0.209 + 0.018*SL	0.211 + 0.018*SL
	t_{PHL}	0.196	0.167 + 0.015*SL	0.169 + 0.014*SL	0.173 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO22D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.110	0.075 + 0.018*SL	0.074 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.101	0.068 + 0.017*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.364	0.341 + 0.012*SL	0.350 + 0.009*SL	0.359 + 0.009*SL
	t_{PHL}	0.338	0.313 + 0.013*SL	0.325 + 0.010*SL	0.338 + 0.009*SL
B to Y	t_R	0.111	0.075 + 0.018*SL	0.075 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.072 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.390	0.366 + 0.012*SL	0.376 + 0.009*SL	0.384 + 0.009*SL
	t_{PHL}	0.334	0.308 + 0.013*SL	0.320 + 0.010*SL	0.333 + 0.009*SL
C to Y	t_R	0.110	0.074 + 0.018*SL	0.074 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.101	0.068 + 0.016*SL	0.072 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.406	0.383 + 0.012*SL	0.393 + 0.009*SL	0.401 + 0.009*SL
	t_{PHL}	0.399	0.374 + 0.013*SL	0.385 + 0.010*SL	0.398 + 0.009*SL
D to Y	t_R	0.111	0.075 + 0.018*SL	0.075 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.072 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.430	0.406 + 0.012*SL	0.416 + 0.009*SL	0.425 + 0.009*SL
	t_{PHL}	0.393	0.368 + 0.013*SL	0.379 + 0.010*SL	0.393 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO22D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.078 + 0.009*SL	0.079 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.087	0.068 + 0.009*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.382	0.367 + 0.007*SL	0.375 + 0.005*SL	0.391 + 0.004*SL
	t_{PHL}	0.345	0.329 + 0.008*SL	0.338 + 0.006*SL	0.357 + 0.005*SL
B to Y	t_R	0.097	0.077 + 0.010*SL	0.081 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.085	0.065 + 0.010*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.406	0.392 + 0.007*SL	0.400 + 0.005*SL	0.415 + 0.004*SL
	t_{PHL}	0.340	0.325 + 0.008*SL	0.333 + 0.006*SL	0.352 + 0.005*SL
C to Y	t_R	0.097	0.078 + 0.009*SL	0.080 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.089	0.071 + 0.009*SL	0.075 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.436	0.421 + 0.007*SL	0.429 + 0.005*SL	0.445 + 0.004*SL
	t_{PHL}	0.417	0.402 + 0.008*SL	0.411 + 0.006*SL	0.430 + 0.005*SL
D to Y	t_R	0.097	0.077 + 0.010*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.089	0.069 + 0.010*SL	0.076 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.463	0.448 + 0.007*SL	0.456 + 0.005*SL	0.472 + 0.004*SL
	t_{PHL}	0.415	0.399 + 0.008*SL	0.408 + 0.006*SL	0.427 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO22DHA/AO22A/AO22D2A/AO22D4A

2-AND and 2-NOR into 2-NOR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	0
x	x	0	0	0
Other States				1

Cell Data

Input Load (SL)															
AO22DHA				*AO22A*				*AO22D2A*				*AO22D4A*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.6	1.0	1.0	0.9	0.9	2.0	2.0	0.9	0.9	1.0	1.1	0.9	0.9

Gate Count			
AO22DHA	*AO22A*	*AO22D2A*	*AO22D4A*
2.67	2.67	3.67	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO22DHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.566	0.234 + 0.166*SL	0.215 + 0.171*SL	0.216 + 0.171*SL
	t_F	0.379	0.166 + 0.106*SL	0.147 + 0.111*SL	0.131 + 0.113*SL
	t_{PLH}	0.299	0.145 + 0.077*SL	0.146 + 0.077*SL	0.148 + 0.077*SL
	t_{PHL}	0.231	0.120 + 0.056*SL	0.122 + 0.055*SL	0.124 + 0.055*SL
B to Y	t_R	0.595	0.263 + 0.166*SL	0.244 + 0.171*SL	0.246 + 0.171*SL
	t_F	0.373	0.155 + 0.109*SL	0.144 + 0.112*SL	0.132 + 0.113*SL
	t_{PLH}	0.319	0.166 + 0.077*SL	0.167 + 0.077*SL	0.168 + 0.077*SL
	t_{PHL}	0.226	0.114 + 0.056*SL	0.117 + 0.055*SL	0.120 + 0.055*SL
C to Y	t_R	0.572	0.232 + 0.170*SL	0.227 + 0.172*SL	0.225 + 0.172*SL
	t_F	0.448	0.225 + 0.111*SL	0.220 + 0.113*SL	0.217 + 0.113*SL
	t_{PLH}	0.453	0.296 + 0.078*SL	0.300 + 0.077*SL	0.302 + 0.077*SL
	t_{PHL}	0.402	0.287 + 0.057*SL	0.295 + 0.056*SL	0.299 + 0.055*SL
D to Y	t_R	0.597	0.259 + 0.169*SL	0.254 + 0.170*SL	0.252 + 0.170*SL
	t_F	0.446	0.222 + 0.112*SL	0.219 + 0.113*SL	0.216 + 0.113*SL
	t_{PLH}	0.467	0.312 + 0.077*SL	0.315 + 0.077*SL	0.316 + 0.077*SL
	t_{PHL}	0.403	0.288 + 0.057*SL	0.296 + 0.056*SL	0.301 + 0.055*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AO22A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.356	0.209 + 0.074*SL	0.199 + 0.076*SL	0.186 + 0.078*SL
	t_F	0.256	0.158 + 0.049*SL	0.146 + 0.052*SL	0.134 + 0.053*SL
	t_{PLH}	0.202	0.133 + 0.035*SL	0.131 + 0.035*SL	0.132 + 0.035*SL
	t_{PHL}	0.164	0.108 + 0.028*SL	0.112 + 0.027*SL	0.114 + 0.027*SL
B to Y	t_R	0.382	0.234 + 0.074*SL	0.225 + 0.076*SL	0.212 + 0.078*SL
	t_F	0.246	0.144 + 0.051*SL	0.136 + 0.053*SL	0.128 + 0.054*SL
	t_{PLH}	0.221	0.151 + 0.035*SL	0.150 + 0.035*SL	0.151 + 0.035*SL
	t_{PHL}	0.158	0.101 + 0.028*SL	0.107 + 0.027*SL	0.108 + 0.027*SL
C to Y	t_R	0.348	0.196 + 0.076*SL	0.191 + 0.077*SL	0.187 + 0.078*SL
	t_F	0.301	0.194 + 0.053*SL	0.191 + 0.054*SL	0.190 + 0.054*SL
	t_{PLH}	0.382	0.310 + 0.036*SL	0.313 + 0.035*SL	0.315 + 0.035*SL
	t_{PHL}	0.295	0.238 + 0.028*SL	0.242 + 0.027*SL	0.246 + 0.027*SL
D to Y	t_R	0.375	0.222 + 0.076*SL	0.218 + 0.077*SL	0.214 + 0.078*SL
	t_F	0.300	0.192 + 0.054*SL	0.191 + 0.054*SL	0.189 + 0.054*SL
	t_{PLH}	0.400	0.328 + 0.036*SL	0.330 + 0.035*SL	0.332 + 0.035*SL
	t_{PHL}	0.299	0.242 + 0.028*SL	0.246 + 0.027*SL	0.250 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO22D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.286	0.212 + 0.037*SL	0.208 + 0.038*SL	0.193 + 0.039*SL
	t_F	0.217	0.168 + 0.025*SL	0.161 + 0.026*SL	0.145 + 0.028*SL
	t_{PLH}	0.172	0.136 + 0.018*SL	0.136 + 0.018*SL	0.137 + 0.018*SL
	t_{PHL}	0.138	0.106 + 0.016*SL	0.114 + 0.014*SL	0.115 + 0.014*SL
B to Y	t_R	0.314	0.240 + 0.037*SL	0.235 + 0.038*SL	0.222 + 0.039*SL
	t_F	0.207	0.156 + 0.025*SL	0.149 + 0.027*SL	0.138 + 0.028*SL
	t_{PLH}	0.193	0.158 + 0.018*SL	0.157 + 0.018*SL	0.158 + 0.018*SL
	t_{PHL}	0.134	0.102 + 0.016*SL	0.109 + 0.014*SL	0.111 + 0.014*SL
C to Y	t_R	0.278	0.202 + 0.038*SL	0.198 + 0.039*SL	0.193 + 0.039*SL
	t_F	0.249	0.195 + 0.027*SL	0.195 + 0.027*SL	0.191 + 0.027*SL
	t_{PLH}	0.374	0.336 + 0.019*SL	0.339 + 0.018*SL	0.343 + 0.018*SL
	t_{PHL}	0.302	0.273 + 0.015*SL	0.276 + 0.014*SL	0.281 + 0.014*SL
D to Y	t_R	0.306	0.230 + 0.038*SL	0.226 + 0.039*SL	0.221 + 0.039*SL
	t_F	0.246	0.192 + 0.027*SL	0.192 + 0.027*SL	0.190 + 0.027*SL
	t_{PLH}	0.388	0.351 + 0.018*SL	0.353 + 0.018*SL	0.355 + 0.018*SL
	t_{PHL}	0.303	0.273 + 0.015*SL	0.276 + 0.014*SL	0.282 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO22D4A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	0.077 + 0.010*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.088	0.069 + 0.010*SL	0.075 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.384	0.370 + 0.007*SL	0.378 + 0.005*SL	0.393 + 0.004*SL
	t_{PHL}	0.346	0.331 + 0.008*SL	0.340 + 0.006*SL	0.359 + 0.005*SL
B to Y	t_R	0.097	0.076 + 0.010*SL	0.082 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.088	0.070 + 0.009*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.409	0.395 + 0.007*SL	0.403 + 0.005*SL	0.418 + 0.004*SL
	t_{PHL}	0.342	0.326 + 0.008*SL	0.335 + 0.006*SL	0.354 + 0.005*SL
C to Y	t_R	0.097	0.077 + 0.010*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.088	0.070 + 0.009*SL	0.074 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.563	0.548 + 0.007*SL	0.556 + 0.005*SL	0.572 + 0.004*SL
	t_{PHL}	0.482	0.466 + 0.008*SL	0.475 + 0.006*SL	0.494 + 0.005*SL
D to Y	t_R	0.097	0.076 + 0.010*SL	0.082 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.086	0.066 + 0.010*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.588	0.574 + 0.007*SL	0.582 + 0.005*SL	0.597 + 0.004*SL
	t_{PHL}	0.488	0.472 + 0.008*SL	0.481 + 0.006*SL	0.500 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	0
x	x	1	1	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)														
AO221					*AO221D2*					*AO221D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.9	0.9	0.9	1.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9

Gate Count		
AO221	*AO221D2*	*AO221D4*
2.00	3.00	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO221

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.554	0.322 + 0.116*SL	0.313 + 0.118*SL	0.302 + 0.120*SL
	t_F	0.307	0.181 + 0.063*SL	0.169 + 0.066*SL	0.157 + 0.068*SL
	t_{PLH}	0.256	0.151 + 0.053*SL	0.147 + 0.054*SL	0.149 + 0.054*SL
	t_{PHL}	0.198	0.130 + 0.034*SL	0.132 + 0.034*SL	0.133 + 0.033*SL
B to Y	t_R	0.588	0.356 + 0.116*SL	0.346 + 0.119*SL	0.336 + 0.120*SL
	t_F	0.300	0.171 + 0.065*SL	0.162 + 0.067*SL	0.156 + 0.068*SL
	t_{PLH}	0.280	0.174 + 0.053*SL	0.172 + 0.054*SL	0.173 + 0.054*SL
	t_{PHL}	0.193	0.124 + 0.034*SL	0.127 + 0.034*SL	0.129 + 0.033*SL
C to Y	t_R	0.568	0.337 + 0.115*SL	0.330 + 0.117*SL	0.326 + 0.118*SL
	t_F	0.367	0.236 + 0.065*SL	0.229 + 0.067*SL	0.220 + 0.068*SL
	t_{PLH}	0.352	0.242 + 0.055*SL	0.246 + 0.054*SL	0.248 + 0.053*SL
	t_{PHL}	0.272	0.203 + 0.035*SL	0.206 + 0.034*SL	0.209 + 0.033*SL
D to Y	t_R	0.603	0.370 + 0.117*SL	0.364 + 0.118*SL	0.361 + 0.118*SL
	t_F	0.364	0.231 + 0.066*SL	0.226 + 0.067*SL	0.221 + 0.068*SL
	t_{PLH}	0.380	0.271 + 0.055*SL	0.274 + 0.054*SL	0.275 + 0.054*SL
	t_{PHL}	0.268	0.199 + 0.035*SL	0.203 + 0.034*SL	0.206 + 0.033*SL
E to Y	t_R	0.603	0.370 + 0.117*SL	0.365 + 0.118*SL	0.361 + 0.118*SL
	t_F	0.301	0.219 + 0.041*SL	0.215 + 0.042*SL	0.208 + 0.043*SL
	t_{PLH}	0.420	0.311 + 0.055*SL	0.313 + 0.054*SL	0.315 + 0.054*SL
	t_{PHL}	0.233	0.183 + 0.025*SL	0.188 + 0.024*SL	0.194 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO221D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.115	0.079 + 0.018*SL	0.080 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.102	0.069 + 0.016*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.417	0.392 + 0.012*SL	0.403 + 0.010*SL	0.413 + 0.009*SL
	t_{PHL}	0.382	0.356 + 0.013*SL	0.368 + 0.010*SL	0.382 + 0.009*SL
B to Y	t_R	0.117	0.081 + 0.018*SL	0.080 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.446	0.421 + 0.013*SL	0.432 + 0.010*SL	0.442 + 0.009*SL
	t_{PHL}	0.376	0.350 + 0.013*SL	0.362 + 0.010*SL	0.376 + 0.009*SL
C to Y	t_R	0.116	0.080 + 0.018*SL	0.079 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.103	0.070 + 0.016*SL	0.075 + 0.015*SL	0.071 + 0.016*SL
	t_{PLH}	0.542	0.517 + 0.012*SL	0.528 + 0.010*SL	0.538 + 0.009*SL
	t_{PHL}	0.475	0.449 + 0.013*SL	0.461 + 0.010*SL	0.476 + 0.009*SL
D to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.103	0.070 + 0.016*SL	0.075 + 0.015*SL	0.071 + 0.016*SL
	t_{PLH}	0.573	0.548 + 0.013*SL	0.560 + 0.010*SL	0.570 + 0.009*SL
	t_{PHL}	0.470	0.444 + 0.013*SL	0.457 + 0.010*SL	0.471 + 0.009*SL
E to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.612	0.587 + 0.013*SL	0.598 + 0.010*SL	0.609 + 0.009*SL
	t_{PHL}	0.429	0.403 + 0.013*SL	0.415 + 0.010*SL	0.429 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO221D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.088 + 0.010*SL	0.090 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.090	0.071 + 0.009*SL	0.076 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.462	0.447 + 0.008*SL	0.456 + 0.005*SL	0.475 + 0.004*SL
	t_{PHL}	0.393	0.378 + 0.008*SL	0.387 + 0.006*SL	0.406 + 0.005*SL
B to Y	t_R	0.108	0.088 + 0.010*SL	0.092 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.088	0.068 + 0.010*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.490	0.475 + 0.008*SL	0.484 + 0.005*SL	0.503 + 0.004*SL
	t_{PHL}	0.388	0.372 + 0.008*SL	0.381 + 0.006*SL	0.401 + 0.005*SL
C to Y	t_R	0.107	0.087 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.076 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.587	0.572 + 0.008*SL	0.580 + 0.005*SL	0.600 + 0.004*SL
	t_{PHL}	0.487	0.471 + 0.008*SL	0.480 + 0.006*SL	0.500 + 0.005*SL
D to Y	t_R	0.108	0.087 + 0.010*SL	0.093 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.091	0.072 + 0.009*SL	0.077 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.618	0.602 + 0.008*SL	0.611 + 0.006*SL	0.631 + 0.004*SL
	t_{PHL}	0.483	0.467 + 0.008*SL	0.476 + 0.006*SL	0.495 + 0.005*SL
E to Y	t_R	0.108	0.087 + 0.010*SL	0.093 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.088	0.070 + 0.009*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.658	0.642 + 0.008*SL	0.651 + 0.006*SL	0.670 + 0.004*SL
	t_{PHL}	0.437	0.421 + 0.008*SL	0.430 + 0.006*SL	0.449 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	x	x	x	x	0
x	x	1	1	x	x	0
x	x	x	x	1	1	0
Other States						1

Cell Data

Input Load (SL)												Gate Count	
AO222						*AO222D2*						*AO222*	*AO222D2*
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	0.9	1.0	0.9	1.0	1.0	1.8	1.9	1.8	1.9	1.8	2.0	2.33	4.33
AO222D2B						*AO222D4*						*AO22D2B*	*AO222D4*
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	0.9	1.0	0.9	1.0	0.9	0.9	0.9	1.0	1.0	1.0	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.594	0.361 + 0.116*SL	0.353 + 0.118*SL	0.344 + 0.120*SL
	t_F	0.327	0.206 + 0.061*SL	0.195 + 0.063*SL	0.182 + 0.065*SL
	t_{PLH}	0.273	0.168 + 0.053*SL	0.164 + 0.054*SL	0.166 + 0.053*SL
	t_{PHL}	0.196	0.130 + 0.033*SL	0.131 + 0.033*SL	0.135 + 0.032*SL
B to Y	t_R	0.627	0.394 + 0.116*SL	0.387 + 0.118*SL	0.378 + 0.120*SL
	t_F	0.320	0.196 + 0.062*SL	0.187 + 0.064*SL	0.180 + 0.065*SL
	t_{PLH}	0.297	0.191 + 0.053*SL	0.189 + 0.053*SL	0.190 + 0.053*SL
	t_{PHL}	0.190	0.123 + 0.033*SL	0.126 + 0.033*SL	0.130 + 0.032*SL
C to Y	t_R	0.617	0.387 + 0.115*SL	0.382 + 0.116*SL	0.378 + 0.117*SL
	t_F	0.404	0.278 + 0.063*SL	0.271 + 0.065*SL	0.263 + 0.066*SL
	t_{PLH}	0.400	0.292 + 0.054*SL	0.295 + 0.054*SL	0.298 + 0.053*SL
	t_{PHL}	0.284	0.216 + 0.034*SL	0.220 + 0.033*SL	0.224 + 0.032*SL
D to Y	t_R	0.654	0.423 + 0.116*SL	0.418 + 0.117*SL	0.414 + 0.118*SL
	t_F	0.401	0.273 + 0.064*SL	0.269 + 0.065*SL	0.264 + 0.066*SL
	t_{PLH}	0.426	0.318 + 0.054*SL	0.320 + 0.054*SL	0.322 + 0.053*SL
	t_{PHL}	0.278	0.210 + 0.034*SL	0.214 + 0.033*SL	0.219 + 0.032*SL
E to Y	t_R	0.619	0.389 + 0.115*SL	0.383 + 0.117*SL	0.379 + 0.117*SL
	t_F	0.471	0.343 + 0.064*SL	0.340 + 0.065*SL	0.334 + 0.066*SL
	t_{PLH}	0.448	0.339 + 0.054*SL	0.342 + 0.054*SL	0.345 + 0.053*SL
	t_{PHL}	0.332	0.260 + 0.036*SL	0.267 + 0.034*SL	0.275 + 0.033*SL
F to Y	t_R	0.655	0.423 + 0.116*SL	0.418 + 0.117*SL	0.414 + 0.118*SL
	t_F	0.471	0.342 + 0.065*SL	0.339 + 0.065*SL	0.336 + 0.066*SL
	t_{PLH}	0.475	0.366 + 0.054*SL	0.369 + 0.054*SL	0.371 + 0.053*SL
	t_{PHL}	0.327	0.255 + 0.036*SL	0.263 + 0.034*SL	0.271 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.490	0.375 + 0.058*SL	0.370 + 0.059*SL	0.359 + 0.060*SL
	t_F	0.275	0.216 + 0.030*SL	0.210 + 0.031*SL	0.195 + 0.032*SL
	t_{PLH}	0.235	0.183 + 0.026*SL	0.180 + 0.027*SL	0.181 + 0.027*SL
	t_{PHL}	0.169	0.136 + 0.017*SL	0.137 + 0.016*SL	0.140 + 0.016*SL
B to Y	t_R	0.524	0.408 + 0.058*SL	0.404 + 0.059*SL	0.393 + 0.060*SL
	t_F	0.267	0.206 + 0.031*SL	0.201 + 0.032*SL	0.192 + 0.033*SL
	t_{PLH}	0.261	0.208 + 0.027*SL	0.206 + 0.027*SL	0.207 + 0.027*SL
	t_{PHL}	0.164	0.129 + 0.017*SL	0.132 + 0.016*SL	0.136 + 0.016*SL
C to Y	t_R	0.511	0.395 + 0.058*SL	0.391 + 0.059*SL	0.386 + 0.059*SL
	t_F	0.330	0.268 + 0.031*SL	0.265 + 0.032*SL	0.255 + 0.033*SL
	t_{PLH}	0.334	0.278 + 0.028*SL	0.280 + 0.027*SL	0.284 + 0.027*SL
	t_{PHL}	0.241	0.207 + 0.017*SL	0.209 + 0.017*SL	0.213 + 0.016*SL
D to Y	t_R	0.542	0.426 + 0.058*SL	0.422 + 0.059*SL	0.418 + 0.059*SL
	t_F	0.326	0.263 + 0.032*SL	0.261 + 0.032*SL	0.255 + 0.033*SL
	t_{PLH}	0.361	0.306 + 0.027*SL	0.308 + 0.027*SL	0.310 + 0.027*SL
	t_{PHL}	0.237	0.203 + 0.017*SL	0.205 + 0.017*SL	0.210 + 0.016*SL
E to Y	t_R	0.511	0.396 + 0.058*SL	0.392 + 0.059*SL	0.387 + 0.059*SL
	t_F	0.402	0.338 + 0.032*SL	0.336 + 0.032*SL	0.329 + 0.033*SL
	t_{PLH}	0.389	0.334 + 0.028*SL	0.336 + 0.027*SL	0.339 + 0.027*SL
	t_{PHL}	0.291	0.254 + 0.018*SL	0.259 + 0.017*SL	0.267 + 0.017*SL
F to Y	t_R	0.542	0.426 + 0.058*SL	0.423 + 0.059*SL	0.419 + 0.059*SL
	t_F	0.400	0.336 + 0.032*SL	0.335 + 0.032*SL	0.331 + 0.033*SL
	t_{PLH}	0.416	0.361 + 0.027*SL	0.362 + 0.027*SL	0.365 + 0.027*SL
	t_{PHL}	0.287	0.250 + 0.018*SL	0.255 + 0.017*SL	0.264 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.116	0.080 + 0.018*SL	0.080 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.070 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.447	0.422 + 0.013*SL	0.433 + 0.010*SL	0.444 + 0.009*SL
	t_{PHL}	0.389	0.362 + 0.013*SL	0.374 + 0.010*SL	0.388 + 0.009*SL
B to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.070 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.476	0.451 + 0.013*SL	0.463 + 0.010*SL	0.473 + 0.009*SL
	t_{PHL}	0.384	0.357 + 0.013*SL	0.370 + 0.010*SL	0.384 + 0.009*SL
C to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.069 + 0.017*SL	0.075 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.572	0.547 + 0.013*SL	0.559 + 0.010*SL	0.569 + 0.009*SL
	t_{PHL}	0.480	0.453 + 0.013*SL	0.466 + 0.010*SL	0.480 + 0.009*SL
D to Y	t_R	0.117	0.081 + 0.018*SL	0.079 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.104	0.069 + 0.017*SL	0.075 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.603	0.578 + 0.013*SL	0.589 + 0.010*SL	0.600 + 0.009*SL
	t_{PHL}	0.476	0.449 + 0.013*SL	0.462 + 0.010*SL	0.476 + 0.009*SL
E to Y	t_R	0.117	0.080 + 0.018*SL	0.081 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.106	0.070 + 0.018*SL	0.078 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.618	0.592 + 0.013*SL	0.604 + 0.010*SL	0.614 + 0.009*SL
	t_{PHL}	0.531	0.504 + 0.013*SL	0.517 + 0.010*SL	0.531 + 0.009*SL
F to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.107	0.073 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.647	0.622 + 0.013*SL	0.633 + 0.010*SL	0.644 + 0.009*SL
	t_{PHL}	0.526	0.499 + 0.013*SL	0.512 + 0.010*SL	0.526 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.086 + 0.010*SL	0.092 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.090	0.070 + 0.010*SL	0.078 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.497	0.481 + 0.008*SL	0.490 + 0.005*SL	0.508 + 0.004*SL
	t_{PHL}	0.407	0.392 + 0.008*SL	0.400 + 0.006*SL	0.420 + 0.005*SL
B to Y	t_R	0.108	0.089 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.091	0.073 + 0.009*SL	0.076 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.523	0.508 + 0.008*SL	0.517 + 0.005*SL	0.535 + 0.004*SL
	t_{PHL}	0.401	0.386 + 0.008*SL	0.394 + 0.006*SL	0.414 + 0.005*SL
C to Y	t_R	0.108	0.089 + 0.009*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.622	0.607 + 0.008*SL	0.616 + 0.005*SL	0.634 + 0.004*SL
	t_{PHL}	0.497	0.481 + 0.008*SL	0.490 + 0.006*SL	0.510 + 0.005*SL
D to Y	t_R	0.108	0.089 + 0.010*SL	0.093 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.091	0.071 + 0.010*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.652	0.637 + 0.008*SL	0.646 + 0.005*SL	0.664 + 0.004*SL
	t_{PHL}	0.492	0.477 + 0.008*SL	0.486 + 0.006*SL	0.506 + 0.005*SL
E to Y	t_R	0.107	0.086 + 0.010*SL	0.092 + 0.009*SL	0.083 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.081 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.665	0.650 + 0.008*SL	0.658 + 0.005*SL	0.677 + 0.004*SL
	t_{PHL}	0.547	0.531 + 0.008*SL	0.540 + 0.006*SL	0.560 + 0.005*SL
F to Y	t_R	0.108	0.088 + 0.010*SL	0.093 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.093	0.073 + 0.010*SL	0.080 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.694	0.679 + 0.008*SL	0.688 + 0.005*SL	0.706 + 0.004*SL
	t_{PHL}	0.542	0.527 + 0.008*SL	0.535 + 0.006*SL	0.556 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO222A/AO222D2A/AO222D4A

Inverting 2-of-3 Majority with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	x	0
1	x	1	0
x	1	1	0
0	0	x	1
0	x	0	1
x	0	0	1

Cell Data

Input Load (SL)									Gate Count		
AO222A			*AO222D2A*			*AO222D4A*			*AO222A*	*AO222D2A*	*AO222D4A*
A	B	C	A	B	C	A	B	C			
1.7	1.9	1.9	1.7	2.0	1.9	1.7	1.9	1.9	2.33	3.33	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.523	0.376 + 0.073*SL	0.367 + 0.075*SL	0.356 + 0.077*SL
	t_F	0.361	0.239 + 0.061*SL	0.233 + 0.063*SL	0.226 + 0.064*SL
	t_{PLH}	0.245	0.175 + 0.035*SL	0.175 + 0.035*SL	0.176 + 0.035*SL
	t_{PHL}	0.261	0.197 + 0.032*SL	0.199 + 0.032*SL	0.202 + 0.031*SL
B to Y	t_R	0.521	0.372 + 0.074*SL	0.366 + 0.076*SL	0.359 + 0.077*SL
	t_F	0.377	0.254 + 0.061*SL	0.249 + 0.063*SL	0.243 + 0.064*SL
	t_{PLH}	0.267	0.197 + 0.035*SL	0.198 + 0.035*SL	0.199 + 0.035*SL
	t_{PHL}	0.295	0.231 + 0.032*SL	0.234 + 0.031*SL	0.237 + 0.031*SL
C to Y	t_R	0.483	0.335 + 0.074*SL	0.329 + 0.075*SL	0.322 + 0.076*SL
	t_F	0.380	0.256 + 0.062*SL	0.253 + 0.062*SL	0.248 + 0.063*SL
	t_{PLH}	0.264	0.195 + 0.035*SL	0.195 + 0.035*SL	0.196 + 0.034*SL
	t_{PHL}	0.270	0.206 + 0.032*SL	0.208 + 0.031*SL	0.210 + 0.031*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO222D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.069 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.433	0.408 + 0.013*SL	0.420 + 0.010*SL	0.430 + 0.009*SL
	t_{PHL}	0.456	0.430 + 0.013*SL	0.442 + 0.010*SL	0.456 + 0.009*SL
B to Y	t_R	0.117	0.081 + 0.018*SL	0.082 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.104	0.069 + 0.017*SL	0.075 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.443	0.419 + 0.012*SL	0.429 + 0.010*SL	0.438 + 0.009*SL
	t_{PHL}	0.490	0.464 + 0.013*SL	0.476 + 0.010*SL	0.490 + 0.009*SL
C to Y	t_R	0.114	0.079 + 0.018*SL	0.077 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.075 + 0.016*SL	0.069 + 0.016*SL
	t_{PLH}	0.443	0.418 + 0.012*SL	0.429 + 0.010*SL	0.439 + 0.009*SL
	t_{PHL}	0.462	0.436 + 0.013*SL	0.448 + 0.010*SL	0.462 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO222D4A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	0.087 + 0.009*SL	0.088 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.077 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.461	0.446 + 0.008*SL	0.455 + 0.005*SL	0.473 + 0.004*SL
	t_{PHL}	0.465	0.449 + 0.008*SL	0.458 + 0.006*SL	0.478 + 0.005*SL
B to Y	t_R	0.106	0.087 + 0.009*SL	0.088 + 0.009*SL	0.083 + 0.009*SL
	t_F	0.091	0.072 + 0.009*SL	0.077 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.468	0.453 + 0.007*SL	0.461 + 0.005*SL	0.478 + 0.004*SL
	t_{PHL}	0.498	0.482 + 0.008*SL	0.491 + 0.006*SL	0.510 + 0.005*SL
C to Y	t_R	0.103	0.083 + 0.010*SL	0.087 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.089	0.069 + 0.010*SL	0.076 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.471	0.456 + 0.007*SL	0.464 + 0.005*SL	0.482 + 0.004*SL
	t_{PHL}	0.472	0.456 + 0.008*SL	0.465 + 0.006*SL	0.484 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO2222/AO2222D2/AO2222D4

Four 2-ANDs into 4-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	0
x	x	1	1	x	x	x	x	0
x	x	x	x	1	1	x	x	0
x	x	x	x	x	x	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
AO2222								*AO2222*
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	3.00
AO2222D2								*AO2222D2*
A	B	C	D	E	F	G	H	
0.9	1.0	0.9	0.9	0.9	0.9	0.9	0.9	4.33
AO2222D4								*AO2222D4*
A	B	C	D	E	F	G	H	
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO2222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.831	0.513 + 0.159*SL	0.508 + 0.161*SL	0.502 + 0.161*SL
	t_F	0.385	0.249 + 0.068*SL	0.239 + 0.070*SL	0.224 + 0.072*SL
	t_{PLH}	0.303	0.168 + 0.068*SL	0.150 + 0.072*SL	0.152 + 0.072*SL
	t_{PHL}	0.220	0.146 + 0.037*SL	0.148 + 0.036*SL	0.153 + 0.036*SL
B to Y	t_R	0.873	0.554 + 0.159*SL	0.549 + 0.161*SL	0.543 + 0.162*SL
	t_F	0.379	0.240 + 0.069*SL	0.233 + 0.071*SL	0.225 + 0.072*SL
	t_{PLH}	0.329	0.191 + 0.069*SL	0.179 + 0.072*SL	0.180 + 0.072*SL
	t_{PHL}	0.213	0.139 + 0.037*SL	0.142 + 0.036*SL	0.148 + 0.036*SL
C to Y	t_R	0.911	0.601 + 0.155*SL	0.596 + 0.156*SL	0.593 + 0.157*SL
	t_F	0.473	0.333 + 0.070*SL	0.327 + 0.072*SL	0.320 + 0.073*SL
	t_{PLH}	0.498	0.352 + 0.073*SL	0.357 + 0.072*SL	0.361 + 0.072*SL
	t_{PHL}	0.321	0.247 + 0.037*SL	0.251 + 0.036*SL	0.256 + 0.036*SL
D to Y	t_R	0.953	0.642 + 0.156*SL	0.638 + 0.157*SL	0.635 + 0.157*SL
	t_F	0.472	0.330 + 0.071*SL	0.327 + 0.072*SL	0.321 + 0.072*SL
	t_{PLH}	0.528	0.383 + 0.073*SL	0.386 + 0.072*SL	0.389 + 0.072*SL
	t_{PHL}	0.315	0.241 + 0.037*SL	0.245 + 0.036*SL	0.250 + 0.036*SL
E to Y	t_R	0.959	0.651 + 0.154*SL	0.644 + 0.156*SL	0.638 + 0.157*SL
	t_F	0.560	0.419 + 0.071*SL	0.414 + 0.072*SL	0.409 + 0.073*SL
	t_{PLH}	0.633	0.486 + 0.073*SL	0.491 + 0.072*SL	0.495 + 0.072*SL
	t_{PHL}	0.370	0.292 + 0.039*SL	0.299 + 0.037*SL	0.306 + 0.036*SL
F to Y	t_R	0.998	0.689 + 0.154*SL	0.684 + 0.156*SL	0.678 + 0.156*SL
	t_F	0.560	0.418 + 0.071*SL	0.415 + 0.072*SL	0.411 + 0.072*SL
	t_{PLH}	0.664	0.518 + 0.073*SL	0.522 + 0.072*SL	0.524 + 0.071*SL
	t_{PHL}	0.366	0.289 + 0.039*SL	0.295 + 0.037*SL	0.303 + 0.036*SL
G to Y	t_R	0.961	0.652 + 0.154*SL	0.645 + 0.156*SL	0.639 + 0.157*SL
	t_F	0.665	0.520 + 0.072*SL	0.518 + 0.073*SL	0.517 + 0.073*SL
	t_{PLH}	0.699	0.552 + 0.073*SL	0.557 + 0.072*SL	0.561 + 0.072*SL
	t_{PHL}	0.408	0.325 + 0.041*SL	0.335 + 0.039*SL	0.347 + 0.037*SL
H to Y	t_R	0.998	0.690 + 0.154*SL	0.684 + 0.156*SL	0.678 + 0.156*SL
	t_F	0.665	0.519 + 0.073*SL	0.520 + 0.073*SL	0.520 + 0.073*SL
	t_{PLH}	0.728	0.583 + 0.073*SL	0.586 + 0.072*SL	0.589 + 0.071*SL
	t_{PHL}	0.404	0.321 + 0.041*SL	0.331 + 0.039*SL	0.343 + 0.037*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO2222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.122	0.085 + 0.018*SL	0.087 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.105	0.070 + 0.018*SL	0.076 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.468	0.442 + 0.013*SL	0.455 + 0.010*SL	0.467 + 0.009*SL
	t_{PHL}	0.416	0.389 + 0.013*SL	0.402 + 0.010*SL	0.417 + 0.009*SL
B to Y	t_R	0.123	0.087 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.502	0.475 + 0.013*SL	0.488 + 0.010*SL	0.501 + 0.009*SL
	t_{PHL}	0.411	0.384 + 0.013*SL	0.397 + 0.010*SL	0.411 + 0.009*SL
C to Y	t_R	0.124	0.088 + 0.018*SL	0.090 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.107	0.072 + 0.017*SL	0.077 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.663	0.637 + 0.013*SL	0.650 + 0.010*SL	0.663 + 0.009*SL
	t_{PHL}	0.525	0.498 + 0.014*SL	0.511 + 0.010*SL	0.526 + 0.009*SL
D to Y	t_R	0.126	0.089 + 0.018*SL	0.091 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.106	0.071 + 0.018*SL	0.078 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.698	0.672 + 0.013*SL	0.685 + 0.010*SL	0.698 + 0.009*SL
	t_{PHL}	0.519	0.492 + 0.014*SL	0.505 + 0.010*SL	0.520 + 0.009*SL
E to Y	t_R	0.125	0.089 + 0.018*SL	0.090 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.108	0.074 + 0.017*SL	0.079 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.802	0.776 + 0.013*SL	0.789 + 0.010*SL	0.801 + 0.009*SL
	t_{PHL}	0.584	0.557 + 0.014*SL	0.570 + 0.010*SL	0.585 + 0.009*SL
F to Y	t_R	0.126	0.090 + 0.018*SL	0.092 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.080 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.837	0.811 + 0.013*SL	0.824 + 0.010*SL	0.837 + 0.009*SL
	t_{PHL}	0.580	0.553 + 0.014*SL	0.566 + 0.010*SL	0.582 + 0.009*SL
G to Y	t_R	0.125	0.089 + 0.018*SL	0.091 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.112	0.077 + 0.017*SL	0.083 + 0.016*SL	0.080 + 0.016*SL
	t_{PLH}	0.868	0.842 + 0.013*SL	0.855 + 0.010*SL	0.868 + 0.009*SL
	t_{PHL}	0.634	0.606 + 0.014*SL	0.620 + 0.010*SL	0.636 + 0.009*SL
H to Y	t_R	0.126	0.090 + 0.018*SL	0.091 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.112	0.077 + 0.017*SL	0.084 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.902	0.876 + 0.013*SL	0.889 + 0.010*SL	0.902 + 0.009*SL
	t_{PHL}	0.630	0.602 + 0.014*SL	0.616 + 0.010*SL	0.632 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO2222D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.091	0.073 + 0.009*SL	0.077 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.520	0.504 + 0.008*SL	0.513 + 0.006*SL	0.534 + 0.005*SL
	t_{PHL}	0.424	0.408 + 0.008*SL	0.417 + 0.006*SL	0.437 + 0.005*SL
B to Y	t_R	0.116	0.096 + 0.010*SL	0.100 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.079 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.554	0.538 + 0.008*SL	0.548 + 0.006*SL	0.569 + 0.005*SL
	t_{PHL}	0.418	0.402 + 0.008*SL	0.412 + 0.006*SL	0.432 + 0.005*SL
C to Y	t_R	0.116	0.096 + 0.010*SL	0.101 + 0.009*SL	0.095 + 0.009*SL
	t_F	0.092	0.072 + 0.010*SL	0.080 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.718	0.702 + 0.008*SL	0.712 + 0.006*SL	0.734 + 0.005*SL
	t_{PHL}	0.533	0.517 + 0.008*SL	0.526 + 0.006*SL	0.546 + 0.005*SL
D to Y	t_R	0.118	0.098 + 0.010*SL	0.102 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.091	0.073 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.754	0.738 + 0.008*SL	0.747 + 0.006*SL	0.769 + 0.005*SL
	t_{PHL}	0.527	0.511 + 0.008*SL	0.520 + 0.006*SL	0.540 + 0.005*SL
E to Y	t_R	0.117	0.098 + 0.010*SL	0.102 + 0.009*SL	0.095 + 0.009*SL
	t_F	0.095	0.075 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.858	0.842 + 0.008*SL	0.851 + 0.006*SL	0.873 + 0.005*SL
	t_{PHL}	0.592	0.576 + 0.008*SL	0.585 + 0.006*SL	0.606 + 0.005*SL
F to Y	t_R	0.118	0.098 + 0.010*SL	0.102 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.094	0.075 + 0.010*SL	0.080 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.894	0.877 + 0.008*SL	0.887 + 0.006*SL	0.909 + 0.005*SL
	t_{PHL}	0.588	0.572 + 0.008*SL	0.581 + 0.006*SL	0.602 + 0.005*SL
G to Y	t_R	0.117	0.096 + 0.010*SL	0.102 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.098	0.079 + 0.010*SL	0.087 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.924	0.908 + 0.008*SL	0.918 + 0.006*SL	0.939 + 0.005*SL
	t_{PHL}	0.643	0.627 + 0.008*SL	0.636 + 0.006*SL	0.657 + 0.005*SL
H to Y	t_R	0.118	0.098 + 0.010*SL	0.103 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.099	0.079 + 0.010*SL	0.087 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.958	0.942 + 0.008*SL	0.952 + 0.006*SL	0.974 + 0.005*SL
	t_{PHL}	0.638	0.622 + 0.008*SL	0.632 + 0.006*SL	0.653 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO31DH/AO31/AO31D2/AO31D4

3-AND into 2-NOR with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	1	x	0
x	x	x	1	0
Other States				1

Cell Data

Input Load (SL)															
AO31DH				*AO31*				*AO31D2*				*AO31D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.9	2.1	2.2	1.9	1.0	1.0	1.0	1.0

Gate Count			
AO31DH	*AO31*	*AO31D2*	*AO31D4*
1.67	1.67	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO31DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.594	0.263 + 0.166*SL	0.244 + 0.170*SL	0.245 + 0.170*SL
	t_F	0.512	0.220 + 0.146*SL	0.204 + 0.150*SL	0.200 + 0.150*SL
	t_{PLH}	0.309	0.155 + 0.077*SL	0.156 + 0.077*SL	0.158 + 0.076*SL
	t_{PHL}	0.301	0.158 + 0.072*SL	0.159 + 0.071*SL	0.160 + 0.071*SL
B to Y	t_R	0.635	0.296 + 0.169*SL	0.280 + 0.173*SL	0.281 + 0.173*SL
	t_F	0.510	0.217 + 0.147*SL	0.206 + 0.149*SL	0.201 + 0.150*SL
	t_{PLH}	0.336	0.180 + 0.078*SL	0.181 + 0.078*SL	0.182 + 0.078*SL
	t_{PHL}	0.308	0.164 + 0.072*SL	0.166 + 0.071*SL	0.167 + 0.071*SL
C to Y	t_R	0.664	0.329 + 0.168*SL	0.312 + 0.172*SL	0.313 + 0.172*SL
	t_F	0.507	0.212 + 0.148*SL	0.204 + 0.150*SL	0.201 + 0.150*SL
	t_{PLH}	0.355	0.199 + 0.078*SL	0.201 + 0.077*SL	0.202 + 0.077*SL
	t_{PHL}	0.309	0.165 + 0.072*SL	0.167 + 0.072*SL	0.169 + 0.071*SL
D to Y	t_R	0.663	0.324 + 0.170*SL	0.317 + 0.172*SL	0.315 + 0.172*SL
	t_F	0.291	0.170 + 0.060*SL	0.159 + 0.063*SL	0.146 + 0.065*SL
	t_{PLH}	0.412	0.255 + 0.079*SL	0.259 + 0.078*SL	0.261 + 0.077*SL
	t_{PHL}	0.228	0.160 + 0.034*SL	0.162 + 0.034*SL	0.164 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

AO31

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.369	0.221 + 0.074*SL	0.210 + 0.076*SL	0.198 + 0.078*SL
	t_F	0.333	0.193 + 0.070*SL	0.183 + 0.072*SL	0.172 + 0.074*SL
	t_{PLH}	0.204	0.134 + 0.035*SL	0.133 + 0.035*SL	0.134 + 0.035*SL
	t_{PHL}	0.211	0.140 + 0.036*SL	0.141 + 0.035*SL	0.141 + 0.035*SL
B to Y	t_R	0.397	0.248 + 0.075*SL	0.238 + 0.077*SL	0.226 + 0.079*SL
	t_F	0.330	0.187 + 0.071*SL	0.181 + 0.073*SL	0.174 + 0.074*SL
	t_{PLH}	0.225	0.155 + 0.035*SL	0.154 + 0.035*SL	0.155 + 0.035*SL
	t_{PHL}	0.217	0.145 + 0.036*SL	0.147 + 0.036*SL	0.148 + 0.035*SL
C to Y	t_R	0.427	0.278 + 0.074*SL	0.267 + 0.077*SL	0.255 + 0.079*SL
	t_F	0.325	0.181 + 0.072*SL	0.177 + 0.073*SL	0.172 + 0.074*SL
	t_{PLH}	0.242	0.171 + 0.036*SL	0.172 + 0.036*SL	0.173 + 0.035*SL
	t_{PHL}	0.217	0.145 + 0.036*SL	0.147 + 0.036*SL	0.148 + 0.035*SL
D to Y	t_R	0.419	0.266 + 0.077*SL	0.261 + 0.078*SL	0.255 + 0.079*SL
	t_F	0.230	0.165 + 0.033*SL	0.161 + 0.034*SL	0.154 + 0.035*SL
	t_{PLH}	0.285	0.213 + 0.036*SL	0.215 + 0.036*SL	0.217 + 0.036*SL
	t_{PHL}	0.196	0.159 + 0.019*SL	0.160 + 0.019*SL	0.161 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO31D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.278	0.206 + 0.036*SL	0.200 + 0.037*SL	0.185 + 0.039*SL
	t_F	0.248	0.180 + 0.034*SL	0.174 + 0.036*SL	0.160 + 0.037*SL
	t_{PLH}	0.158	0.122 + 0.018*SL	0.124 + 0.018*SL	0.124 + 0.018*SL
	t_{PHL}	0.164	0.128 + 0.018*SL	0.130 + 0.018*SL	0.130 + 0.018*SL
B to Y	t_R	0.304	0.231 + 0.036*SL	0.226 + 0.038*SL	0.212 + 0.039*SL
	t_F	0.242	0.172 + 0.035*SL	0.168 + 0.036*SL	0.159 + 0.037*SL
	t_{PLH}	0.180	0.145 + 0.017*SL	0.144 + 0.018*SL	0.145 + 0.018*SL
	t_{PHL}	0.170	0.133 + 0.019*SL	0.136 + 0.018*SL	0.138 + 0.018*SL
C to Y	t_R	0.333	0.261 + 0.036*SL	0.255 + 0.037*SL	0.241 + 0.039*SL
	t_F	0.237	0.166 + 0.035*SL	0.162 + 0.036*SL	0.156 + 0.037*SL
	t_{PLH}	0.197	0.161 + 0.018*SL	0.161 + 0.018*SL	0.163 + 0.018*SL
	t_{PHL}	0.170	0.133 + 0.019*SL	0.136 + 0.018*SL	0.138 + 0.018*SL
D to Y	t_R	0.324	0.249 + 0.037*SL	0.246 + 0.038*SL	0.238 + 0.039*SL
	t_F	0.209	0.178 + 0.015*SL	0.175 + 0.016*SL	0.164 + 0.017*SL
	t_{PLH}	0.245	0.208 + 0.018*SL	0.210 + 0.018*SL	0.213 + 0.018*SL
	t_{PHL}	0.176	0.156 + 0.010*SL	0.157 + 0.009*SL	0.159 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO31D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	0.079 + 0.010*SL	0.083 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.089	0.071 + 0.009*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.394	0.380 + 0.007*SL	0.387 + 0.005*SL	0.403 + 0.004*SL
	t_{PHL}	0.403	0.388 + 0.007*SL	0.396 + 0.005*SL	0.416 + 0.004*SL
B to Y	t_R	0.100	0.082 + 0.009*SL	0.082 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.077 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.419	0.405 + 0.007*SL	0.413 + 0.005*SL	0.429 + 0.004*SL
	t_{PHL}	0.410	0.394 + 0.008*SL	0.403 + 0.005*SL	0.422 + 0.004*SL
C to Y	t_R	0.100	0.083 + 0.009*SL	0.082 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.088	0.069 + 0.010*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.440	0.426 + 0.007*SL	0.434 + 0.005*SL	0.450 + 0.004*SL
	t_{PHL}	0.409	0.394 + 0.008*SL	0.402 + 0.005*SL	0.421 + 0.004*SL
D to Y	t_R	0.099	0.078 + 0.010*SL	0.084 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.085	0.067 + 0.009*SL	0.072 + 0.008*SL	0.072 + 0.008*SL
	t_{PLH}	0.483	0.469 + 0.007*SL	0.477 + 0.005*SL	0.492 + 0.004*SL
	t_{PHL}	0.376	0.361 + 0.007*SL	0.370 + 0.005*SL	0.388 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	1	x	x	0
x	x	x	1	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)														
AO311					*AO311D2*					*AO311D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9

Gate Count		
AO311	*AO311D2*	*AO311D4*
2.00	3.00	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO311

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.576	0.349 + 0.113*SL	0.339 + 0.116*SL	0.329 + 0.117*SL
	t_F	0.412	0.235 + 0.088*SL	0.226 + 0.091*SL	0.217 + 0.092*SL
	t_{PLH}	0.257	0.153 + 0.052*SL	0.150 + 0.053*SL	0.152 + 0.053*SL
	t_{PHL}	0.257	0.169 + 0.044*SL	0.170 + 0.044*SL	0.171 + 0.044*SL
B to Y	t_R	0.611	0.383 + 0.114*SL	0.373 + 0.116*SL	0.365 + 0.118*SL
	t_F	0.411	0.232 + 0.089*SL	0.227 + 0.091*SL	0.218 + 0.092*SL
	t_{PLH}	0.283	0.178 + 0.053*SL	0.177 + 0.053*SL	0.178 + 0.053*SL
	t_{PHL}	0.264	0.175 + 0.044*SL	0.177 + 0.044*SL	0.179 + 0.044*SL
C to Y	t_R	0.647	0.420 + 0.114*SL	0.409 + 0.116*SL	0.401 + 0.118*SL
	t_F	0.408	0.228 + 0.090*SL	0.224 + 0.091*SL	0.218 + 0.092*SL
	t_{PLH}	0.305	0.198 + 0.053*SL	0.200 + 0.053*SL	0.201 + 0.053*SL
	t_{PHL}	0.264	0.175 + 0.045*SL	0.177 + 0.044*SL	0.179 + 0.044*SL
D to Y	t_R	0.659	0.430 + 0.114*SL	0.425 + 0.116*SL	0.421 + 0.116*SL
	t_F	0.322	0.222 + 0.050*SL	0.217 + 0.051*SL	0.210 + 0.052*SL
	t_{PLH}	0.406	0.299 + 0.054*SL	0.302 + 0.053*SL	0.304 + 0.053*SL
	t_{PHL}	0.269	0.214 + 0.028*SL	0.216 + 0.027*SL	0.218 + 0.027*SL
E to Y	t_R	0.659	0.429 + 0.115*SL	0.424 + 0.116*SL	0.421 + 0.116*SL
	t_F	0.356	0.256 + 0.050*SL	0.251 + 0.051*SL	0.245 + 0.052*SL
	t_{PLH}	0.420	0.312 + 0.054*SL	0.315 + 0.053*SL	0.317 + 0.053*SL
	t_{PHL}	0.288	0.232 + 0.028*SL	0.235 + 0.027*SL	0.238 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO311D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.118	0.082 + 0.018*SL	0.083 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.105	0.071 + 0.017*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.431	0.406 + 0.012*SL	0.417 + 0.010*SL	0.428 + 0.009*SL
	t_{PHL}	0.439	0.414 + 0.013*SL	0.426 + 0.010*SL	0.440 + 0.009*SL
B to Y	t_R	0.118	0.082 + 0.018*SL	0.083 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.106	0.073 + 0.016*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.460	0.436 + 0.012*SL	0.447 + 0.010*SL	0.457 + 0.009*SL
	t_{PHL}	0.446	0.421 + 0.013*SL	0.433 + 0.010*SL	0.447 + 0.009*SL
C to Y	t_R	0.119	0.084 + 0.017*SL	0.083 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.106	0.073 + 0.016*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.485	0.461 + 0.012*SL	0.472 + 0.010*SL	0.483 + 0.009*SL
	t_{PHL}	0.446	0.420 + 0.013*SL	0.432 + 0.010*SL	0.446 + 0.009*SL
D to Y	t_R	0.119	0.083 + 0.018*SL	0.084 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.072 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.585	0.560 + 0.012*SL	0.572 + 0.010*SL	0.582 + 0.009*SL
	t_{PHL}	0.452	0.426 + 0.013*SL	0.438 + 0.010*SL	0.451 + 0.009*SL
E to Y	t_R	0.120	0.084 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.599	0.574 + 0.012*SL	0.586 + 0.010*SL	0.596 + 0.009*SL
	t_{PHL}	0.476	0.451 + 0.013*SL	0.462 + 0.010*SL	0.476 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO311D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	0.086 + 0.010*SL	0.090 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.093	0.074 + 0.009*SL	0.079 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.468	0.453 + 0.008*SL	0.462 + 0.005*SL	0.480 + 0.004*SL
	t_{PHL}	0.459	0.443 + 0.008*SL	0.452 + 0.006*SL	0.472 + 0.005*SL
B to Y	t_R	0.107	0.086 + 0.010*SL	0.091 + 0.009*SL	0.083 + 0.009*SL
	t_F	0.091	0.073 + 0.009*SL	0.077 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.498	0.483 + 0.008*SL	0.492 + 0.005*SL	0.510 + 0.004*SL
	t_{PHL}	0.466	0.450 + 0.008*SL	0.459 + 0.006*SL	0.479 + 0.005*SL
C to Y	t_R	0.108	0.089 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.091	0.073 + 0.009*SL	0.077 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.524	0.509 + 0.008*SL	0.517 + 0.005*SL	0.536 + 0.004*SL
	t_{PHL}	0.466	0.450 + 0.008*SL	0.459 + 0.006*SL	0.479 + 0.005*SL
D to Y	t_R	0.108	0.088 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.086	0.067 + 0.009*SL	0.073 + 0.008*SL	0.072 + 0.008*SL
	t_{PLH}	0.624	0.609 + 0.008*SL	0.618 + 0.005*SL	0.636 + 0.004*SL
	t_{PHL}	0.462	0.447 + 0.008*SL	0.455 + 0.006*SL	0.474 + 0.005*SL
E to Y	t_R	0.107	0.087 + 0.010*SL	0.092 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.086	0.067 + 0.010*SL	0.073 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.638	0.623 + 0.008*SL	0.632 + 0.005*SL	0.651 + 0.004*SL
	t_{PHL}	0.487	0.472 + 0.008*SL	0.481 + 0.006*SL	0.499 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	x	x	0
x	x	x	x	1	x	0
x	x	x	x	x	1	0
Other States						1

Cell Data

Input Load (SL)												Gate Count	
AO3111						*AO3111D2*						*AO3111*	*AO3111*D2
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	0.9	0.9	0.8	0.8	0.9	0.9	0.9	0.9	0.8	0.8	0.9	2.33	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO3111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.787	0.477 + 0.155*SL	0.468 + 0.157*SL	0.465 + 0.157*SL
	t_F	0.440	0.248 + 0.096*SL	0.239 + 0.098*SL	0.231 + 0.099*SL
	t_{PLH}	0.295	0.156 + 0.069*SL	0.150 + 0.071*SL	0.153 + 0.070*SL
	t_{PHL}	0.274	0.179 + 0.048*SL	0.180 + 0.047*SL	0.181 + 0.047*SL
B to Y	t_R	0.832	0.521 + 0.155*SL	0.512 + 0.157*SL	0.510 + 0.158*SL
	t_F	0.438	0.245 + 0.096*SL	0.239 + 0.098*SL	0.233 + 0.099*SL
	t_{PLH}	0.327	0.186 + 0.070*SL	0.184 + 0.071*SL	0.186 + 0.070*SL
	t_{PHL}	0.281	0.186 + 0.048*SL	0.187 + 0.047*SL	0.189 + 0.047*SL
C to Y	t_R	0.877	0.567 + 0.155*SL	0.557 + 0.157*SL	0.555 + 0.158*SL
	t_F	0.436	0.242 + 0.097*SL	0.238 + 0.098*SL	0.232 + 0.099*SL
	t_{PLH}	0.354	0.212 + 0.071*SL	0.212 + 0.071*SL	0.215 + 0.070*SL
	t_{PHL}	0.281	0.185 + 0.048*SL	0.187 + 0.047*SL	0.189 + 0.047*SL
D to Y	t_R	0.918	0.612 + 0.153*SL	0.607 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.391	0.264 + 0.064*SL	0.259 + 0.065*SL	0.255 + 0.065*SL
	t_{PLH}	0.511	0.368 + 0.072*SL	0.371 + 0.071*SL	0.374 + 0.071*SL
	t_{PHL}	0.323	0.254 + 0.034*SL	0.256 + 0.034*SL	0.258 + 0.033*SL
E to Y	t_R	0.919	0.614 + 0.153*SL	0.607 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.433	0.304 + 0.064*SL	0.302 + 0.065*SL	0.298 + 0.065*SL
	t_{PLH}	0.556	0.412 + 0.072*SL	0.416 + 0.071*SL	0.419 + 0.071*SL
	t_{PHL}	0.350	0.281 + 0.035*SL	0.284 + 0.034*SL	0.287 + 0.034*SL
F to Y	t_R	0.919	0.613 + 0.153*SL	0.607 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.480	0.353 + 0.064*SL	0.350 + 0.064*SL	0.343 + 0.065*SL
	t_{PLH}	0.573	0.430 + 0.072*SL	0.433 + 0.071*SL	0.436 + 0.071*SL
	t_{PHL}	0.369	0.297 + 0.036*SL	0.302 + 0.035*SL	0.308 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO3111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	0.087 + 0.018*SL	0.090 + 0.017*SL	0.078 + 0.018*SL
	t_F	0.105	0.072 + 0.017*SL	0.078 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.471	0.445 + 0.013*SL	0.457 + 0.010*SL	0.469 + 0.009*SL
	t_{PHL}	0.457	0.432 + 0.013*SL	0.444 + 0.010*SL	0.458 + 0.009*SL
B to Y	t_R	0.124	0.089 + 0.018*SL	0.090 + 0.018*SL	0.080 + 0.018*SL
	t_F	0.106	0.073 + 0.016*SL	0.078 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.507	0.482 + 0.013*SL	0.494 + 0.010*SL	0.506 + 0.009*SL
	t_{PHL}	0.465	0.439 + 0.013*SL	0.451 + 0.010*SL	0.465 + 0.009*SL
C to Y	t_R	0.127	0.092 + 0.018*SL	0.092 + 0.017*SL	0.081 + 0.018*SL
	t_F	0.106	0.073 + 0.016*SL	0.078 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.539	0.513 + 0.013*SL	0.526 + 0.010*SL	0.538 + 0.009*SL
	t_{PHL}	0.464	0.438 + 0.013*SL	0.450 + 0.010*SL	0.465 + 0.009*SL
D to Y	t_R	0.127	0.091 + 0.018*SL	0.093 + 0.017*SL	0.082 + 0.018*SL
	t_F	0.103	0.070 + 0.016*SL	0.075 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.695	0.669 + 0.013*SL	0.682 + 0.010*SL	0.694 + 0.009*SL
	t_{PHL}	0.510	0.485 + 0.013*SL	0.496 + 0.010*SL	0.510 + 0.009*SL
E to Y	t_R	0.127	0.092 + 0.018*SL	0.093 + 0.017*SL	0.081 + 0.018*SL
	t_F	0.103	0.069 + 0.017*SL	0.075 + 0.015*SL	0.072 + 0.016*SL
	t_{PLH}	0.739	0.714 + 0.013*SL	0.726 + 0.010*SL	0.738 + 0.009*SL
	t_{PHL}	0.543	0.518 + 0.013*SL	0.530 + 0.010*SL	0.543 + 0.009*SL
F to Y	t_R	0.127	0.092 + 0.018*SL	0.093 + 0.017*SL	0.082 + 0.018*SL
	t_F	0.105	0.072 + 0.016*SL	0.077 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.758	0.733 + 0.013*SL	0.745 + 0.010*SL	0.758 + 0.009*SL
	t_{PHL}	0.569	0.544 + 0.013*SL	0.555 + 0.010*SL	0.569 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

AO32/AO32D2/AO32D4

3-AND and 2-AND into 2-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	1	x	x	0
x	x	x	1	1	0
Other States					1

Cell Data

Input Load (SL)														
AO32					*AO32D2*					*AO32D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
1.0	1.0	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1

Gate Count		
AO32	*AO32D2*	*AO32D4*
2.00	3.00	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO32

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.411	0.260 + 0.075*SL	0.252 + 0.077*SL	0.241 + 0.079*SL
	t_F	0.352	0.229 + 0.061*SL	0.221 + 0.063*SL	0.209 + 0.065*SL
	t_{PLH}	0.232	0.161 + 0.035*SL	0.161 + 0.036*SL	0.162 + 0.035*SL
	t_{PHL}	0.201	0.138 + 0.032*SL	0.138 + 0.032*SL	0.140 + 0.031*SL
B to Y	t_R	0.441	0.290 + 0.076*SL	0.283 + 0.077*SL	0.272 + 0.079*SL
	t_F	0.348	0.222 + 0.063*SL	0.217 + 0.064*SL	0.210 + 0.065*SL
	t_{PLH}	0.255	0.184 + 0.036*SL	0.184 + 0.035*SL	0.185 + 0.035*SL
	t_{PHL}	0.207	0.143 + 0.032*SL	0.145 + 0.032*SL	0.147 + 0.032*SL
C to Y	t_R	0.474	0.322 + 0.076*SL	0.315 + 0.078*SL	0.305 + 0.079*SL
	t_F	0.343	0.216 + 0.063*SL	0.211 + 0.065*SL	0.208 + 0.065*SL
	t_{PLH}	0.276	0.204 + 0.036*SL	0.205 + 0.036*SL	0.206 + 0.035*SL
	t_{PHL}	0.207	0.142 + 0.032*SL	0.145 + 0.032*SL	0.147 + 0.032*SL
D to Y	t_R	0.441	0.287 + 0.077*SL	0.281 + 0.078*SL	0.278 + 0.079*SL
	t_F	0.305	0.220 + 0.043*SL	0.216 + 0.044*SL	0.208 + 0.045*SL
	t_{PLH}	0.315	0.242 + 0.037*SL	0.245 + 0.036*SL	0.247 + 0.036*SL
	t_{PHL}	0.232	0.186 + 0.023*SL	0.188 + 0.023*SL	0.190 + 0.022*SL
E to Y	t_R	0.472	0.318 + 0.077*SL	0.313 + 0.078*SL	0.309 + 0.079*SL
	t_F	0.299	0.212 + 0.044*SL	0.209 + 0.044*SL	0.205 + 0.045*SL
	t_{PLH}	0.340	0.267 + 0.036*SL	0.269 + 0.036*SL	0.271 + 0.036*SL
	t_{PHL}	0.227	0.181 + 0.023*SL	0.183 + 0.023*SL	0.185 + 0.022*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO32D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.110	0.074 + 0.018*SL	0.075 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.397	0.373 + 0.012*SL	0.383 + 0.009*SL	0.393 + 0.009*SL
	t_{PHL}	0.393	0.367 + 0.013*SL	0.380 + 0.010*SL	0.394 + 0.009*SL
B to Y	t_R	0.112	0.077 + 0.018*SL	0.075 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.105	0.072 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.425	0.401 + 0.012*SL	0.411 + 0.009*SL	0.420 + 0.009*SL
	t_{PHL}	0.399	0.373 + 0.013*SL	0.386 + 0.010*SL	0.400 + 0.009*SL
C to Y	t_R	0.112	0.076 + 0.018*SL	0.077 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.104	0.071 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.449	0.425 + 0.012*SL	0.436 + 0.009*SL	0.445 + 0.009*SL
	t_{PHL}	0.401	0.374 + 0.013*SL	0.387 + 0.010*SL	0.401 + 0.009*SL
D to Y	t_R	0.112	0.077 + 0.018*SL	0.076 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.073 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.485	0.461 + 0.012*SL	0.471 + 0.009*SL	0.481 + 0.009*SL
	t_{PHL}	0.425	0.399 + 0.013*SL	0.411 + 0.010*SL	0.425 + 0.009*SL
E to Y	t_R	0.112	0.077 + 0.018*SL	0.078 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.103	0.070 + 0.017*SL	0.074 + 0.016*SL	0.069 + 0.016*SL
	t_{PLH}	0.514	0.490 + 0.012*SL	0.500 + 0.009*SL	0.510 + 0.009*SL
	t_{PHL}	0.421	0.395 + 0.013*SL	0.407 + 0.010*SL	0.420 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO32D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	0.079 + 0.010*SL	0.083 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.090	0.071 + 0.009*SL	0.077 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.424	0.409 + 0.007*SL	0.418 + 0.005*SL	0.434 + 0.004*SL
	t_{PHL}	0.406	0.390 + 0.008*SL	0.399 + 0.006*SL	0.419 + 0.005*SL
B to Y	t_R	0.100	0.079 + 0.010*SL	0.085 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.078 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.452	0.437 + 0.007*SL	0.445 + 0.005*SL	0.462 + 0.004*SL
	t_{PHL}	0.412	0.396 + 0.008*SL	0.405 + 0.006*SL	0.425 + 0.005*SL
C to Y	t_R	0.101	0.082 + 0.010*SL	0.085 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.477	0.462 + 0.007*SL	0.470 + 0.005*SL	0.487 + 0.004*SL
	t_{PHL}	0.413	0.397 + 0.008*SL	0.406 + 0.006*SL	0.426 + 0.005*SL
D to Y	t_R	0.100	0.080 + 0.010*SL	0.085 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.513	0.498 + 0.007*SL	0.507 + 0.005*SL	0.523 + 0.004*SL
	t_{PHL}	0.433	0.418 + 0.008*SL	0.427 + 0.006*SL	0.447 + 0.005*SL
E to Y	t_R	0.101	0.083 + 0.009*SL	0.083 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.089	0.070 + 0.010*SL	0.077 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.542	0.528 + 0.007*SL	0.536 + 0.005*SL	0.552 + 0.004*SL
	t_{PHL}	0.429	0.414 + 0.008*SL	0.423 + 0.006*SL	0.442 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO321/AO321D2/AO321D4

3-AND and 2-AND into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	1	x	0
x	x	x	x	x	1	0
Other States						1

Cell Data

Input Load (SL)																	
AO321						*AO321D2*						*AO321D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
1.0	1.0	1.0	0.9	0.9	0.9	1.0	1.0	1.0	0.9	0.9	0.9	1.0	1.0	1.0	0.9	0.9	0.9

Gate Count		
AO321	*AO321D2*	*AO321D4*
2.67	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO321

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.651	0.415 + 0.118*SL	0.408 + 0.119*SL	0.401 + 0.120*SL
	t_F	0.420	0.264 + 0.078*SL	0.255 + 0.080*SL	0.246 + 0.081*SL
	t_{PLH}	0.283	0.177 + 0.053*SL	0.174 + 0.054*SL	0.175 + 0.054*SL
	t_{PHL}	0.244	0.165 + 0.040*SL	0.166 + 0.039*SL	0.169 + 0.039*SL
B to Y	t_R	0.690	0.455 + 0.118*SL	0.447 + 0.120*SL	0.441 + 0.120*SL
	t_F	0.418	0.261 + 0.079*SL	0.255 + 0.080*SL	0.247 + 0.081*SL
	t_{PLH}	0.312	0.205 + 0.054*SL	0.204 + 0.054*SL	0.206 + 0.054*SL
	t_{PHL}	0.252	0.172 + 0.040*SL	0.174 + 0.039*SL	0.177 + 0.039*SL
C to Y	t_R	0.731	0.496 + 0.117*SL	0.488 + 0.119*SL	0.481 + 0.120*SL
	t_F	0.415	0.255 + 0.080*SL	0.252 + 0.080*SL	0.246 + 0.081*SL
	t_{PLH}	0.337	0.229 + 0.054*SL	0.229 + 0.054*SL	0.231 + 0.054*SL
	t_{PHL}	0.251	0.171 + 0.040*SL	0.173 + 0.039*SL	0.176 + 0.039*SL
D to Y	t_R	0.721	0.489 + 0.116*SL	0.484 + 0.117*SL	0.480 + 0.118*SL
	t_F	0.419	0.296 + 0.062*SL	0.292 + 0.063*SL	0.286 + 0.063*SL
	t_{PLH}	0.450	0.340 + 0.055*SL	0.343 + 0.054*SL	0.347 + 0.054*SL
	t_{PHL}	0.315	0.251 + 0.032*SL	0.253 + 0.031*SL	0.256 + 0.031*SL
E to Y	t_R	0.759	0.525 + 0.117*SL	0.521 + 0.118*SL	0.517 + 0.118*SL
	t_F	0.418	0.293 + 0.062*SL	0.291 + 0.063*SL	0.287 + 0.063*SL
	t_{PLH}	0.478	0.368 + 0.055*SL	0.371 + 0.054*SL	0.373 + 0.054*SL
	t_{PHL}	0.310	0.246 + 0.032*SL	0.249 + 0.031*SL	0.252 + 0.031*SL
F to Y	t_R	0.759	0.525 + 0.117*SL	0.521 + 0.118*SL	0.517 + 0.118*SL
	t_F	0.364	0.286 + 0.039*SL	0.282 + 0.040*SL	0.274 + 0.041*SL
	t_{PLH}	0.517	0.407 + 0.055*SL	0.410 + 0.054*SL	0.413 + 0.054*SL
	t_{PHL}	0.254	0.206 + 0.024*SL	0.210 + 0.023*SL	0.216 + 0.022*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO321D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.117	0.081 + 0.018*SL	0.081 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.107	0.072 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.460	0.434 + 0.013*SL	0.447 + 0.010*SL	0.457 + 0.009*SL
	t_{PHL}	0.444	0.417 + 0.014*SL	0.430 + 0.010*SL	0.445 + 0.009*SL
B to Y	t_R	0.119	0.083 + 0.018*SL	0.084 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.494	0.469 + 0.013*SL	0.481 + 0.010*SL	0.492 + 0.009*SL
	t_{PHL}	0.451	0.424 + 0.014*SL	0.437 + 0.010*SL	0.451 + 0.009*SL
C to Y	t_R	0.119	0.083 + 0.018*SL	0.083 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.525	0.499 + 0.013*SL	0.511 + 0.010*SL	0.523 + 0.009*SL
	t_{PHL}	0.451	0.424 + 0.014*SL	0.437 + 0.010*SL	0.451 + 0.009*SL
D to Y	t_R	0.119	0.083 + 0.018*SL	0.084 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.104	0.070 + 0.017*SL	0.074 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.631	0.605 + 0.013*SL	0.617 + 0.010*SL	0.629 + 0.009*SL
	t_{PHL}	0.514	0.487 + 0.013*SL	0.500 + 0.010*SL	0.514 + 0.009*SL
E to Y	t_R	0.119	0.083 + 0.018*SL	0.083 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.105	0.071 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.663	0.637 + 0.013*SL	0.650 + 0.010*SL	0.661 + 0.009*SL
	t_{PHL}	0.510	0.483 + 0.013*SL	0.495 + 0.010*SL	0.510 + 0.009*SL
F to Y	t_R	0.119	0.083 + 0.018*SL	0.084 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.073 + 0.016*SL	0.069 + 0.016*SL
	t_{PLH}	0.702	0.676 + 0.013*SL	0.688 + 0.010*SL	0.699 + 0.009*SL
	t_{PHL}	0.461	0.434 + 0.013*SL	0.447 + 0.010*SL	0.461 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO321D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	0.089 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.080 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.503	0.487 + 0.008*SL	0.496 + 0.005*SL	0.515 + 0.004*SL
	t_{PHL}	0.456	0.441 + 0.008*SL	0.450 + 0.006*SL	0.470 + 0.005*SL
B to Y	t_R	0.109	0.088 + 0.010*SL	0.094 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.538	0.523 + 0.008*SL	0.532 + 0.005*SL	0.551 + 0.004*SL
	t_{PHL}	0.463	0.448 + 0.008*SL	0.457 + 0.006*SL	0.477 + 0.005*SL
C to Y	t_R	0.110	0.090 + 0.010*SL	0.094 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.569	0.554 + 0.008*SL	0.563 + 0.006*SL	0.582 + 0.004*SL
	t_{PHL}	0.463	0.448 + 0.008*SL	0.457 + 0.006*SL	0.477 + 0.005*SL
D to Y	t_R	0.109	0.089 + 0.010*SL	0.094 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.675	0.660 + 0.008*SL	0.669 + 0.005*SL	0.688 + 0.004*SL
	t_{PHL}	0.523	0.507 + 0.008*SL	0.516 + 0.006*SL	0.535 + 0.005*SL
E to Y	t_R	0.109	0.089 + 0.010*SL	0.094 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.090	0.071 + 0.010*SL	0.078 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.708	0.692 + 0.008*SL	0.702 + 0.006*SL	0.721 + 0.004*SL
	t_{PHL}	0.518	0.503 + 0.008*SL	0.512 + 0.006*SL	0.531 + 0.005*SL
F to Y	t_R	0.110	0.090 + 0.010*SL	0.094 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.088	0.069 + 0.009*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.747	0.731 + 0.008*SL	0.740 + 0.006*SL	0.760 + 0.004*SL
	t_{PHL}	0.465	0.449 + 0.008*SL	0.458 + 0.006*SL	0.477 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO322/AO322D2/AO322D4

3-AND and Two 2-ANDs into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	x	x	x	x	0
x	x	x	1	1	x	x	0
x	x	x	x	x	1	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO322							*AO322*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.1	1.0	1.0	2.67
AO322D2							*AO322D2*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.2	1.0	1.0	3.67
AO322D4							*AO322D4*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.2	1.0	1.0	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO322

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.711	0.476 + 0.118*SL	0.469 + 0.119*SL	0.465 + 0.120*SL
	t_F	0.435	0.298 + 0.068*SL	0.289 + 0.070*SL	0.279 + 0.072*SL
	t_{PLH}	0.332	0.224 + 0.054*SL	0.224 + 0.054*SL	0.226 + 0.054*SL
	t_{PHL}	0.235	0.164 + 0.036*SL	0.166 + 0.035*SL	0.170 + 0.035*SL
B to Y	t_R	0.755	0.519 + 0.118*SL	0.513 + 0.119*SL	0.509 + 0.120*SL
	t_F	0.432	0.293 + 0.069*SL	0.287 + 0.071*SL	0.280 + 0.072*SL
	t_{PLH}	0.363	0.255 + 0.054*SL	0.256 + 0.054*SL	0.257 + 0.054*SL
	t_{PHL}	0.241	0.169 + 0.036*SL	0.172 + 0.035*SL	0.176 + 0.035*SL
C to Y	t_R	0.798	0.563 + 0.118*SL	0.557 + 0.119*SL	0.553 + 0.120*SL
	t_F	0.427	0.287 + 0.070*SL	0.282 + 0.071*SL	0.280 + 0.072*SL
	t_{PLH}	0.391	0.283 + 0.054*SL	0.285 + 0.054*SL	0.286 + 0.053*SL
	t_{PHL}	0.240	0.168 + 0.036*SL	0.171 + 0.035*SL	0.176 + 0.035*SL
D to Y	t_R	0.784	0.552 + 0.116*SL	0.548 + 0.117*SL	0.545 + 0.118*SL
	t_F	0.421	0.319 + 0.051*SL	0.314 + 0.052*SL	0.305 + 0.053*SL
	t_{PLH}	0.499	0.389 + 0.055*SL	0.393 + 0.054*SL	0.396 + 0.054*SL
	t_{PHL}	0.274	0.219 + 0.028*SL	0.222 + 0.027*SL	0.226 + 0.027*SL
E to Y	t_R	0.825	0.592 + 0.117*SL	0.589 + 0.117*SL	0.586 + 0.118*SL
	t_F	0.417	0.314 + 0.052*SL	0.310 + 0.053*SL	0.306 + 0.053*SL
	t_{PLH}	0.533	0.425 + 0.054*SL	0.427 + 0.054*SL	0.429 + 0.053*SL
	t_{PHL}	0.271	0.215 + 0.028*SL	0.218 + 0.027*SL	0.223 + 0.027*SL
F to Y	t_R	0.788	0.555 + 0.117*SL	0.551 + 0.118*SL	0.548 + 0.118*SL
	t_F	0.487	0.385 + 0.051*SL	0.380 + 0.052*SL	0.373 + 0.053*SL
	t_{PLH}	0.548	0.438 + 0.055*SL	0.442 + 0.054*SL	0.445 + 0.054*SL
	t_{PHL}	0.307	0.249 + 0.029*SL	0.254 + 0.028*SL	0.260 + 0.027*SL
G to Y	t_R	0.825	0.592 + 0.116*SL	0.589 + 0.117*SL	0.586 + 0.118*SL
	t_F	0.484	0.380 + 0.052*SL	0.378 + 0.053*SL	0.373 + 0.053*SL
	t_{PLH}	0.578	0.469 + 0.054*SL	0.472 + 0.054*SL	0.474 + 0.053*SL
	t_{PHL}	0.303	0.244 + 0.029*SL	0.249 + 0.028*SL	0.256 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO322D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.121	0.086 + 0.018*SL	0.086 + 0.018*SL	0.075 + 0.019*SL
	t_F	0.107	0.074 + 0.016*SL	0.079 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.519	0.494 + 0.013*SL	0.506 + 0.010*SL	0.517 + 0.009*SL
	t_{PHL}	0.445	0.419 + 0.013*SL	0.432 + 0.010*SL	0.447 + 0.009*SL
B to Y	t_R	0.123	0.087 + 0.018*SL	0.087 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.106	0.073 + 0.017*SL	0.079 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.555	0.530 + 0.013*SL	0.542 + 0.010*SL	0.553 + 0.009*SL
	t_{PHL}	0.451	0.425 + 0.013*SL	0.437 + 0.010*SL	0.452 + 0.009*SL
C to Y	t_R	0.123	0.087 + 0.018*SL	0.087 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.107	0.074 + 0.016*SL	0.079 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.588	0.562 + 0.013*SL	0.575 + 0.010*SL	0.586 + 0.009*SL
	t_{PHL}	0.450	0.424 + 0.013*SL	0.437 + 0.010*SL	0.452 + 0.009*SL
D to Y	t_R	0.123	0.087 + 0.018*SL	0.088 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.105	0.073 + 0.016*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.696	0.670 + 0.013*SL	0.682 + 0.010*SL	0.694 + 0.009*SL
	t_{PHL}	0.489	0.463 + 0.013*SL	0.475 + 0.010*SL	0.490 + 0.009*SL
E to Y	t_R	0.123	0.087 + 0.018*SL	0.089 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.105	0.073 + 0.016*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.732	0.706 + 0.013*SL	0.718 + 0.010*SL	0.730 + 0.009*SL
	t_{PHL}	0.485	0.459 + 0.013*SL	0.472 + 0.010*SL	0.486 + 0.009*SL
F to Y	t_R	0.123	0.087 + 0.018*SL	0.088 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.107	0.075 + 0.016*SL	0.079 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.739	0.714 + 0.013*SL	0.726 + 0.010*SL	0.737 + 0.009*SL
	t_{PHL}	0.529	0.503 + 0.013*SL	0.515 + 0.010*SL	0.530 + 0.009*SL
G to Y	t_R	0.124	0.087 + 0.018*SL	0.089 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.107	0.074 + 0.016*SL	0.079 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.774	0.748 + 0.013*SL	0.760 + 0.010*SL	0.772 + 0.009*SL
	t_{PHL}	0.524	0.498 + 0.013*SL	0.510 + 0.010*SL	0.526 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO322D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.110	0.091 + 0.010*SL	0.094 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.562	0.547 + 0.008*SL	0.556 + 0.005*SL	0.575 + 0.004*SL
	t_{PHL}	0.458	0.443 + 0.008*SL	0.452 + 0.006*SL	0.472 + 0.004*SL
B to Y	t_R	0.111	0.090 + 0.010*SL	0.096 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.081 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.599	0.583 + 0.008*SL	0.592 + 0.006*SL	0.612 + 0.004*SL
	t_{PHL}	0.464	0.448 + 0.008*SL	0.457 + 0.006*SL	0.478 + 0.004*SL
C to Y	t_R	0.113	0.093 + 0.010*SL	0.097 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.079 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.632	0.617 + 0.008*SL	0.626 + 0.006*SL	0.645 + 0.004*SL
	t_{PHL}	0.463	0.448 + 0.008*SL	0.457 + 0.006*SL	0.477 + 0.004*SL
D to Y	t_R	0.112	0.092 + 0.010*SL	0.097 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.735	0.720 + 0.008*SL	0.729 + 0.006*SL	0.748 + 0.004*SL
	t_{PHL}	0.497	0.481 + 0.008*SL	0.490 + 0.006*SL	0.510 + 0.004*SL
E to Y	t_R	0.113	0.092 + 0.010*SL	0.097 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.080 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.777	0.762 + 0.008*SL	0.771 + 0.006*SL	0.790 + 0.004*SL
	t_{PHL}	0.495	0.479 + 0.008*SL	0.488 + 0.006*SL	0.508 + 0.004*SL
F to Y	t_R	0.112	0.092 + 0.010*SL	0.096 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.081 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.785	0.769 + 0.008*SL	0.778 + 0.006*SL	0.798 + 0.004*SL
	t_{PHL}	0.538	0.523 + 0.008*SL	0.532 + 0.006*SL	0.552 + 0.004*SL
G to Y	t_R	0.112	0.091 + 0.010*SL	0.097 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.819	0.803 + 0.008*SL	0.813 + 0.006*SL	0.832 + 0.004*SL
	t_{PHL}	0.534	0.518 + 0.008*SL	0.527 + 0.006*SL	0.548 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 19, *Group3 : 19 < SL

AO33/AO33D2/AO33D4

Two 3-ANDs into 2-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	1	x	x	x	0
x	x	x	1	1	1	0
Other States						1

Cell Data

Input Load (SL)																	
AO33						*AO33D2*						*AO33D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.2
Gate Count																	
AO33						*AO33D2*						*AO33D4*					
2.33						3.00						3.67					

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO33

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.452	0.300 + 0.076*SL	0.293 + 0.078*SL	0.282 + 0.079*SL
	t_F	0.376	0.267 + 0.054*SL	0.258 + 0.057*SL	0.246 + 0.058*SL
	t_{PLH}	0.261	0.188 + 0.036*SL	0.190 + 0.036*SL	0.192 + 0.036*SL
	t_{PHL}	0.187	0.129 + 0.029*SL	0.130 + 0.029*SL	0.131 + 0.029*SL
B to Y	t_R	0.485	0.333 + 0.076*SL	0.326 + 0.078*SL	0.317 + 0.079*SL
	t_F	0.371	0.259 + 0.056*SL	0.252 + 0.058*SL	0.245 + 0.059*SL
	t_{PLH}	0.289	0.216 + 0.036*SL	0.218 + 0.036*SL	0.220 + 0.036*SL
	t_{PHL}	0.195	0.136 + 0.029*SL	0.138 + 0.029*SL	0.140 + 0.029*SL
C to Y	t_R	0.521	0.368 + 0.076*SL	0.361 + 0.078*SL	0.354 + 0.079*SL
	t_F	0.365	0.251 + 0.057*SL	0.246 + 0.058*SL	0.241 + 0.059*SL
	t_{PLH}	0.312	0.239 + 0.036*SL	0.241 + 0.036*SL	0.243 + 0.036*SL
	t_{PHL}	0.194	0.135 + 0.030*SL	0.137 + 0.029*SL	0.139 + 0.029*SL
D to Y	t_R	0.451	0.297 + 0.077*SL	0.292 + 0.078*SL	0.288 + 0.079*SL
	t_F	0.403	0.288 + 0.057*SL	0.284 + 0.058*SL	0.277 + 0.059*SL
	t_{PLH}	0.327	0.253 + 0.037*SL	0.256 + 0.036*SL	0.259 + 0.036*SL
	t_{PHL}	0.280	0.221 + 0.030*SL	0.224 + 0.029*SL	0.226 + 0.029*SL
E to Y	t_R	0.486	0.331 + 0.077*SL	0.328 + 0.078*SL	0.324 + 0.079*SL
	t_F	0.401	0.286 + 0.058*SL	0.283 + 0.059*SL	0.279 + 0.059*SL
	t_{PLH}	0.356	0.283 + 0.036*SL	0.286 + 0.036*SL	0.288 + 0.036*SL
	t_{PHL}	0.290	0.230 + 0.030*SL	0.233 + 0.029*SL	0.236 + 0.029*SL
F to Y	t_R	0.522	0.366 + 0.078*SL	0.364 + 0.078*SL	0.360 + 0.079*SL
	t_F	0.399	0.282 + 0.058*SL	0.280 + 0.059*SL	0.277 + 0.059*SL
	t_{PLH}	0.380	0.307 + 0.037*SL	0.309 + 0.036*SL	0.312 + 0.036*SL
	t_{PHL}	0.289	0.230 + 0.030*SL	0.233 + 0.029*SL	0.235 + 0.029*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO33D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.114	0.078 + 0.018*SL	0.077 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.107	0.075 + 0.016*SL	0.079 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.444	0.419 + 0.012*SL	0.430 + 0.010*SL	0.439 + 0.009*SL
	t_{PHL}	0.406	0.380 + 0.013*SL	0.393 + 0.010*SL	0.408 + 0.009*SL
B to Y	t_R	0.114	0.077 + 0.018*SL	0.078 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.107	0.074 + 0.016*SL	0.079 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.476	0.452 + 0.012*SL	0.462 + 0.010*SL	0.472 + 0.009*SL
	t_{PHL}	0.413	0.386 + 0.013*SL	0.399 + 0.010*SL	0.414 + 0.009*SL
C to Y	t_R	0.115	0.079 + 0.018*SL	0.077 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.106	0.073 + 0.017*SL	0.079 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.502	0.478 + 0.012*SL	0.488 + 0.010*SL	0.498 + 0.009*SL
	t_{PHL}	0.414	0.388 + 0.013*SL	0.400 + 0.010*SL	0.415 + 0.009*SL
D to Y	t_R	0.114	0.078 + 0.018*SL	0.078 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.106	0.073 + 0.017*SL	0.078 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.512	0.488 + 0.012*SL	0.498 + 0.010*SL	0.508 + 0.009*SL
	t_{PHL}	0.496	0.470 + 0.013*SL	0.482 + 0.010*SL	0.497 + 0.009*SL
E to Y	t_R	0.114	0.078 + 0.018*SL	0.076 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.106	0.074 + 0.016*SL	0.078 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.542	0.518 + 0.012*SL	0.528 + 0.010*SL	0.538 + 0.009*SL
	t_{PHL}	0.505	0.479 + 0.013*SL	0.492 + 0.010*SL	0.507 + 0.009*SL
F to Y	t_R	0.116	0.079 + 0.018*SL	0.080 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.106	0.074 + 0.016*SL	0.078 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.572	0.547 + 0.012*SL	0.558 + 0.010*SL	0.568 + 0.009*SL
	t_{PHL}	0.505	0.479 + 0.013*SL	0.491 + 0.010*SL	0.506 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO33D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.102	0.081 + 0.010*SL	0.088 + 0.009*SL	0.079 + 0.009*SL
	t_F	0.093	0.073 + 0.010*SL	0.081 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.473	0.458 + 0.007*SL	0.466 + 0.005*SL	0.483 + 0.004*SL
	t_{PHL}	0.409	0.394 + 0.008*SL	0.402 + 0.006*SL	0.423 + 0.005*SL
B to Y	t_R	0.103	0.083 + 0.010*SL	0.087 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.079 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.505	0.491 + 0.007*SL	0.499 + 0.005*SL	0.516 + 0.004*SL
	t_{PHL}	0.415	0.400 + 0.008*SL	0.409 + 0.006*SL	0.429 + 0.005*SL
C to Y	t_R	0.104	0.084 + 0.010*SL	0.089 + 0.009*SL	0.080 + 0.009*SL
	t_F	0.093	0.076 + 0.009*SL	0.079 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.532	0.517 + 0.007*SL	0.525 + 0.005*SL	0.543 + 0.004*SL
	t_{PHL}	0.416	0.401 + 0.008*SL	0.410 + 0.006*SL	0.430 + 0.005*SL
D to Y	t_R	0.101	0.080 + 0.010*SL	0.086 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.092	0.073 + 0.010*SL	0.081 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.541	0.526 + 0.007*SL	0.534 + 0.005*SL	0.551 + 0.004*SL
	t_{PHL}	0.493	0.477 + 0.008*SL	0.486 + 0.006*SL	0.506 + 0.005*SL
E to Y	t_R	0.104	0.083 + 0.010*SL	0.088 + 0.009*SL	0.079 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.078 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.571	0.556 + 0.007*SL	0.564 + 0.005*SL	0.582 + 0.004*SL
	t_{PHL}	0.501	0.486 + 0.008*SL	0.494 + 0.006*SL	0.514 + 0.005*SL
F to Y	t_R	0.105	0.086 + 0.009*SL	0.087 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.093	0.075 + 0.009*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.603	0.588 + 0.007*SL	0.596 + 0.005*SL	0.614 + 0.004*SL
	t_{PHL}	0.501	0.486 + 0.008*SL	0.495 + 0.006*SL	0.515 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO331/AO331D2/AO331D4

Two 3-ANDs into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	x	x	x	x	0
x	x	x	1	1	1	x	0
x	x	x	x	x	x	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO331							*AO331*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.0	1.0	0.9	2.67
AO331D2							*AO331D2*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.0	1.0	1.0	3.33
AO331D4							*AO331D4*
A	B	C	D	E	F	G	
1.0	1.0	1.0	1.0	1.0	1.0	1.0	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO331

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.710	0.474 + 0.118*SL	0.466 + 0.120*SL	0.461 + 0.120*SL
	t_F	0.449	0.307 + 0.071*SL	0.297 + 0.073*SL	0.285 + 0.075*SL
	t_{PLH}	0.321	0.213 + 0.054*SL	0.213 + 0.054*SL	0.216 + 0.054*SL
	t_{PHL}	0.233	0.160 + 0.037*SL	0.160 + 0.037*SL	0.162 + 0.036*SL
B to Y	t_R	0.751	0.515 + 0.118*SL	0.508 + 0.120*SL	0.504 + 0.120*SL
	t_F	0.446	0.302 + 0.072*SL	0.295 + 0.074*SL	0.287 + 0.075*SL
	t_{PLH}	0.353	0.245 + 0.054*SL	0.246 + 0.054*SL	0.248 + 0.054*SL
	t_{PHL}	0.240	0.166 + 0.037*SL	0.167 + 0.037*SL	0.170 + 0.036*SL
C to Y	t_R	0.792	0.557 + 0.118*SL	0.550 + 0.119*SL	0.545 + 0.120*SL
	t_F	0.442	0.296 + 0.073*SL	0.291 + 0.074*SL	0.285 + 0.075*SL
	t_{PLH}	0.380	0.272 + 0.054*SL	0.273 + 0.054*SL	0.276 + 0.054*SL
	t_{PHL}	0.239	0.165 + 0.037*SL	0.167 + 0.037*SL	0.169 + 0.036*SL
D to Y	t_R	0.738	0.506 + 0.116*SL	0.501 + 0.117*SL	0.497 + 0.118*SL
	t_F	0.512	0.364 + 0.074*SL	0.360 + 0.075*SL	0.356 + 0.075*SL
	t_{PLH}	0.465	0.354 + 0.055*SL	0.358 + 0.054*SL	0.362 + 0.054*SL
	t_{PHL}	0.358	0.283 + 0.037*SL	0.286 + 0.037*SL	0.289 + 0.036*SL
E to Y	t_R	0.782	0.548 + 0.117*SL	0.544 + 0.118*SL	0.541 + 0.118*SL
	t_F	0.512	0.364 + 0.074*SL	0.362 + 0.075*SL	0.357 + 0.075*SL
	t_{PLH}	0.499	0.389 + 0.055*SL	0.393 + 0.054*SL	0.396 + 0.054*SL
	t_{PHL}	0.366	0.291 + 0.037*SL	0.294 + 0.037*SL	0.297 + 0.036*SL
F to Y	t_R	0.823	0.589 + 0.117*SL	0.586 + 0.118*SL	0.582 + 0.118*SL
	t_F	0.511	0.362 + 0.075*SL	0.361 + 0.075*SL	0.357 + 0.075*SL
	t_{PLH}	0.529	0.419 + 0.055*SL	0.422 + 0.054*SL	0.425 + 0.054*SL
	t_{PHL}	0.366	0.291 + 0.037*SL	0.294 + 0.037*SL	0.297 + 0.036*SL
G to Y	t_R	0.823	0.590 + 0.116*SL	0.586 + 0.117*SL	0.582 + 0.118*SL
	t_F	0.360	0.288 + 0.036*SL	0.283 + 0.037*SL	0.275 + 0.038*SL
	t_{PLH}	0.573	0.463 + 0.055*SL	0.466 + 0.054*SL	0.469 + 0.054*SL
	t_{PHL}	0.241	0.196 + 0.023*SL	0.200 + 0.022*SL	0.205 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO331D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.122	0.086 + 0.018*SL	0.087 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.110	0.075 + 0.017*SL	0.082 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.513	0.488 + 0.013*SL	0.500 + 0.010*SL	0.511 + 0.009*SL
	t_{PHL}	0.456	0.429 + 0.014*SL	0.441 + 0.010*SL	0.457 + 0.009*SL
B to Y	t_R	0.123	0.086 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.111	0.077 + 0.017*SL	0.081 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.550	0.524 + 0.013*SL	0.537 + 0.010*SL	0.548 + 0.009*SL
	t_{PHL}	0.463	0.436 + 0.014*SL	0.448 + 0.010*SL	0.464 + 0.009*SL
C to Y	t_R	0.124	0.089 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.082 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.581	0.555 + 0.013*SL	0.568 + 0.010*SL	0.579 + 0.009*SL
	t_{PHL}	0.462	0.435 + 0.013*SL	0.447 + 0.010*SL	0.463 + 0.009*SL
D to Y	t_R	0.123	0.087 + 0.018*SL	0.087 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.109	0.074 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.655	0.629 + 0.013*SL	0.642 + 0.010*SL	0.653 + 0.009*SL
	t_{PHL}	0.574	0.547 + 0.013*SL	0.560 + 0.010*SL	0.575 + 0.009*SL
E to Y	t_R	0.124	0.087 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.110	0.075 + 0.017*SL	0.081 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.694	0.668 + 0.013*SL	0.681 + 0.010*SL	0.692 + 0.009*SL
	t_{PHL}	0.582	0.555 + 0.013*SL	0.568 + 0.010*SL	0.582 + 0.009*SL
F to Y	t_R	0.124	0.088 + 0.018*SL	0.088 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.727	0.702 + 0.013*SL	0.714 + 0.010*SL	0.726 + 0.009*SL
	t_{PHL}	0.582	0.555 + 0.013*SL	0.568 + 0.010*SL	0.583 + 0.009*SL
G to Y	t_R	0.124	0.087 + 0.018*SL	0.089 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.077 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.772	0.746 + 0.013*SL	0.759 + 0.010*SL	0.771 + 0.009*SL
	t_{PHL}	0.457	0.431 + 0.013*SL	0.443 + 0.010*SL	0.457 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO331D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.111	0.091 + 0.010*SL	0.097 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.095	0.076 + 0.009*SL	0.081 + 0.008*SL	0.083 + 0.008*SL
	t_{PLH}	0.558	0.543 + 0.008*SL	0.552 + 0.006*SL	0.571 + 0.004*SL
	t_{PHL}	0.467	0.451 + 0.008*SL	0.460 + 0.006*SL	0.481 + 0.005*SL
B to Y	t_R	0.113	0.093 + 0.010*SL	0.098 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.082 + 0.008*SL	0.083 + 0.008*SL
	t_{PLH}	0.596	0.580 + 0.008*SL	0.589 + 0.006*SL	0.609 + 0.004*SL
	t_{PHL}	0.474	0.458 + 0.008*SL	0.467 + 0.006*SL	0.488 + 0.005*SL
C to Y	t_R	0.113	0.093 + 0.010*SL	0.098 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.096	0.077 + 0.010*SL	0.084 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.627	0.612 + 0.008*SL	0.621 + 0.006*SL	0.641 + 0.004*SL
	t_{PHL}	0.473	0.457 + 0.008*SL	0.466 + 0.006*SL	0.487 + 0.005*SL
D to Y	t_R	0.111	0.092 + 0.010*SL	0.096 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.095	0.075 + 0.010*SL	0.083 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.701	0.686 + 0.008*SL	0.695 + 0.006*SL	0.714 + 0.004*SL
	t_{PHL}	0.586	0.570 + 0.008*SL	0.579 + 0.006*SL	0.599 + 0.005*SL
E to Y	t_R	0.112	0.092 + 0.010*SL	0.097 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.094	0.075 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.740	0.725 + 0.008*SL	0.734 + 0.006*SL	0.754 + 0.004*SL
	t_{PHL}	0.594	0.578 + 0.008*SL	0.587 + 0.006*SL	0.607 + 0.005*SL
F to Y	t_R	0.114	0.095 + 0.010*SL	0.098 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.094	0.074 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.774	0.759 + 0.008*SL	0.768 + 0.006*SL	0.788 + 0.004*SL
	t_{PHL}	0.594	0.578 + 0.008*SL	0.587 + 0.006*SL	0.607 + 0.005*SL
G to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.089	0.070 + 0.010*SL	0.076 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.818	0.803 + 0.008*SL	0.812 + 0.006*SL	0.832 + 0.004*SL
	t_{PHL}	0.460	0.445 + 0.008*SL	0.453 + 0.006*SL	0.473 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO332/AO332D2/AO332D4

Two 3-ANDs and 2-AND into 3-NOR with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	1	x	x	x	x	x	0
x	x	x	1	1	1	x	x	0
x	x	x	x	x	x	1	1	0
Other States								1

Cell Data

Input Load (SL)								Gate Count
AO332								*AO332*
A	B	C	D	E	F	G	H	
1.0	1.0	1.0	1.0	1.0	1.1	1.1	1.1	3.00
AO332D2								*AO332D2*
A	B	C	D	E	F	G	H	
1.0	1.1	1.1	1.0	1.1	1.1	1.1	1.1	4.00
AO332D4								*AO332D4*
A	B	C	D	E	F	G	H	
1.0	1.1	1.1	1.0	1.0	1.1	1.1	1.1	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO332

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.737	0.500 + 0.119*SL	0.494 + 0.120*SL	0.490 + 0.121*SL
	t_F	0.468	0.343 + 0.063*SL	0.333 + 0.065*SL	0.322 + 0.067*SL
	t_{PLH}	0.340	0.232 + 0.054*SL	0.232 + 0.054*SL	0.234 + 0.054*SL
	t_{PHL}	0.226	0.160 + 0.033*SL	0.160 + 0.033*SL	0.163 + 0.033*SL
B to Y	t_R	0.784	0.546 + 0.119*SL	0.541 + 0.120*SL	0.537 + 0.121*SL
	t_F	0.465	0.336 + 0.064*SL	0.330 + 0.066*SL	0.323 + 0.067*SL
	t_{PLH}	0.375	0.267 + 0.054*SL	0.267 + 0.054*SL	0.269 + 0.054*SL
	t_{PHL}	0.232	0.165 + 0.034*SL	0.167 + 0.033*SL	0.171 + 0.033*SL
C to Y	t_R	0.832	0.594 + 0.119*SL	0.589 + 0.120*SL	0.586 + 0.121*SL
	t_F	0.461	0.330 + 0.065*SL	0.326 + 0.066*SL	0.321 + 0.067*SL
	t_{PLH}	0.406	0.298 + 0.054*SL	0.299 + 0.054*SL	0.301 + 0.054*SL
	t_{PHL}	0.231	0.164 + 0.034*SL	0.166 + 0.033*SL	0.170 + 0.033*SL
D to Y	t_R	0.819	0.585 + 0.117*SL	0.581 + 0.118*SL	0.578 + 0.118*SL
	t_F	0.546	0.416 + 0.065*SL	0.410 + 0.066*SL	0.403 + 0.067*SL
	t_{PLH}	0.523	0.412 + 0.055*SL	0.416 + 0.054*SL	0.420 + 0.054*SL
	t_{PHL}	0.329	0.261 + 0.034*SL	0.265 + 0.033*SL	0.268 + 0.032*SL
E to Y	t_R	0.865	0.630 + 0.117*SL	0.627 + 0.118*SL	0.625 + 0.118*SL
	t_F	0.545	0.414 + 0.065*SL	0.411 + 0.066*SL	0.406 + 0.067*SL
	t_{PLH}	0.560	0.451 + 0.055*SL	0.453 + 0.054*SL	0.456 + 0.054*SL
	t_{PHL}	0.337	0.269 + 0.034*SL	0.273 + 0.033*SL	0.277 + 0.033*SL
F to Y	t_R	0.910	0.675 + 0.117*SL	0.673 + 0.118*SL	0.670 + 0.118*SL
	t_F	0.544	0.412 + 0.066*SL	0.409 + 0.067*SL	0.405 + 0.067*SL
	t_{PLH}	0.593	0.484 + 0.055*SL	0.486 + 0.054*SL	0.489 + 0.054*SL
	t_{PHL}	0.337	0.269 + 0.034*SL	0.273 + 0.033*SL	0.277 + 0.033*SL
G to Y	t_R	0.863	0.629 + 0.117*SL	0.626 + 0.118*SL	0.623 + 0.118*SL
	t_F	0.444	0.361 + 0.042*SL	0.355 + 0.043*SL	0.348 + 0.044*SL
	t_{PLH}	0.623	0.512 + 0.055*SL	0.516 + 0.054*SL	0.520 + 0.054*SL
	t_{PHL}	0.263	0.213 + 0.025*SL	0.218 + 0.024*SL	0.224 + 0.023*SL
H to Y	t_R	0.910	0.676 + 0.117*SL	0.674 + 0.118*SL	0.670 + 0.118*SL
	t_F	0.439	0.354 + 0.043*SL	0.350 + 0.044*SL	0.347 + 0.044*SL
	t_{PLH}	0.660	0.551 + 0.055*SL	0.553 + 0.054*SL	0.556 + 0.054*SL
	t_{PHL}	0.258	0.208 + 0.025*SL	0.213 + 0.024*SL	0.220 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO332D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.121	0.084 + 0.018*SL	0.084 + 0.018*SL	0.075 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.525	0.499 + 0.013*SL	0.512 + 0.010*SL	0.524 + 0.009*SL
	t_{PHL}	0.448	0.421 + 0.014*SL	0.434 + 0.010*SL	0.450 + 0.009*SL
B to Y	t_R	0.122	0.085 + 0.018*SL	0.086 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.081 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.565	0.539 + 0.013*SL	0.552 + 0.010*SL	0.564 + 0.009*SL
	t_{PHL}	0.454	0.427 + 0.014*SL	0.440 + 0.010*SL	0.455 + 0.009*SL
C to Y	t_R	0.124	0.088 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.601	0.575 + 0.013*SL	0.588 + 0.010*SL	0.600 + 0.009*SL
	t_{PHL}	0.453	0.426 + 0.014*SL	0.439 + 0.010*SL	0.454 + 0.009*SL
D to Y	t_R	0.122	0.086 + 0.018*SL	0.088 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.711	0.685 + 0.013*SL	0.698 + 0.010*SL	0.710 + 0.009*SL
	t_{PHL}	0.552	0.525 + 0.014*SL	0.538 + 0.010*SL	0.553 + 0.009*SL
E to Y	t_R	0.124	0.087 + 0.018*SL	0.089 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.754	0.728 + 0.013*SL	0.741 + 0.010*SL	0.753 + 0.009*SL
	t_{PHL}	0.560	0.532 + 0.014*SL	0.546 + 0.010*SL	0.561 + 0.009*SL
F to Y	t_R	0.124	0.088 + 0.018*SL	0.090 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.109	0.074 + 0.017*SL	0.081 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.791	0.765 + 0.013*SL	0.778 + 0.010*SL	0.790 + 0.009*SL
	t_{PHL}	0.560	0.533 + 0.014*SL	0.546 + 0.010*SL	0.561 + 0.009*SL
G to Y	t_R	0.124	0.087 + 0.018*SL	0.089 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.107	0.073 + 0.017*SL	0.077 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.815	0.789 + 0.013*SL	0.802 + 0.010*SL	0.814 + 0.009*SL
	t_{PHL}	0.486	0.458 + 0.014*SL	0.471 + 0.010*SL	0.486 + 0.009*SL
H to Y	t_R	0.125	0.089 + 0.018*SL	0.090 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.858	0.832 + 0.013*SL	0.845 + 0.010*SL	0.858 + 0.009*SL
	t_{PHL}	0.481	0.454 + 0.013*SL	0.467 + 0.010*SL	0.482 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO332D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	0.092 + 0.010*SL	0.096 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.095	0.075 + 0.010*SL	0.084 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.566	0.550 + 0.008*SL	0.559 + 0.006*SL	0.579 + 0.004*SL
	t_{PHL}	0.455	0.439 + 0.008*SL	0.448 + 0.006*SL	0.469 + 0.005*SL
B to Y	t_R	0.113	0.093 + 0.010*SL	0.097 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.095	0.076 + 0.009*SL	0.081 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.607	0.591 + 0.008*SL	0.601 + 0.006*SL	0.621 + 0.005*SL
	t_{PHL}	0.461	0.445 + 0.008*SL	0.454 + 0.006*SL	0.475 + 0.005*SL
C to Y	t_R	0.114	0.094 + 0.010*SL	0.098 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.083 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.644	0.628 + 0.008*SL	0.637 + 0.006*SL	0.658 + 0.005*SL
	t_{PHL}	0.460	0.444 + 0.008*SL	0.453 + 0.006*SL	0.474 + 0.005*SL
D to Y	t_R	0.114	0.094 + 0.010*SL	0.098 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.096	0.077 + 0.010*SL	0.084 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.754	0.738 + 0.008*SL	0.748 + 0.006*SL	0.768 + 0.005*SL
	t_{PHL}	0.558	0.542 + 0.008*SL	0.552 + 0.006*SL	0.572 + 0.005*SL
E to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.096	0.076 + 0.010*SL	0.084 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.797	0.781 + 0.008*SL	0.791 + 0.006*SL	0.811 + 0.005*SL
	t_{PHL}	0.566	0.550 + 0.008*SL	0.560 + 0.006*SL	0.580 + 0.005*SL
F to Y	t_R	0.116	0.096 + 0.010*SL	0.100 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.095	0.077 + 0.009*SL	0.081 + 0.008*SL	0.083 + 0.008*SL
	t_{PLH}	0.835	0.819 + 0.008*SL	0.829 + 0.006*SL	0.849 + 0.005*SL
	t_{PHL}	0.567	0.551 + 0.008*SL	0.560 + 0.006*SL	0.581 + 0.005*SL
G to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.092	0.073 + 0.010*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.858	0.842 + 0.008*SL	0.852 + 0.006*SL	0.872 + 0.005*SL
	t_{PHL}	0.489	0.473 + 0.008*SL	0.482 + 0.006*SL	0.502 + 0.005*SL
H to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.902	0.886 + 0.008*SL	0.895 + 0.006*SL	0.916 + 0.005*SL
	t_{PHL}	0.484	0.468 + 0.008*SL	0.478 + 0.006*SL	0.498 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

AO4111/AO4111D2

4-AND into 4-NOR with 1X/2X Drive

Logic SymbolCell Data



Truth Table

A	B	C	D	E	F	G	Y
1	1	1	1	x	x	x	0
x	x	x	x	1	x	x	0
x	x	x	x	x	1	x	0
x	x	x	x	x	x	1	0
Other States							1

Cell Data

Input Load (SL)							Gate Count
AO4111							*AO4111*
A	B	C	D	E	F	G	
0.9	0.9	0.9	0.9	0.8	0.8	0.9	2.67
AO4111D2							*AO4111D2*
A	B	C	D	E	F	G	
0.9	0.9	0.9	0.9	0.8	0.8	0.9	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO4111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.829	0.516 + 0.156*SL	0.510 + 0.158*SL	0.505 + 0.158*SL
	t_F	0.569	0.328 + 0.120*SL	0.320 + 0.122*SL	0.319 + 0.122*SL
	t_{PLH}	0.288	0.153 + 0.067*SL	0.139 + 0.071*SL	0.141 + 0.070*SL
	t_{PHL}	0.323	0.206 + 0.058*SL	0.208 + 0.058*SL	0.209 + 0.058*SL
B to Y	t_R	0.877	0.564 + 0.156*SL	0.557 + 0.158*SL	0.553 + 0.159*SL
	t_F	0.571	0.331 + 0.120*SL	0.324 + 0.122*SL	0.321 + 0.122*SL
	t_{PLH}	0.320	0.182 + 0.069*SL	0.174 + 0.071*SL	0.177 + 0.071*SL
	t_{PHL}	0.342	0.224 + 0.059*SL	0.226 + 0.058*SL	0.229 + 0.058*SL
C to Y	t_R	0.925	0.613 + 0.156*SL	0.604 + 0.158*SL	0.600 + 0.159*SL
	t_F	0.570	0.329 + 0.121*SL	0.323 + 0.122*SL	0.321 + 0.122*SL
	t_{PLH}	0.350	0.209 + 0.070*SL	0.207 + 0.071*SL	0.209 + 0.071*SL
	t_{PHL}	0.353	0.235 + 0.059*SL	0.238 + 0.058*SL	0.240 + 0.058*SL
D to Y	t_R	0.975	0.664 + 0.155*SL	0.653 + 0.158*SL	0.649 + 0.159*SL
	t_F	0.568	0.326 + 0.121*SL	0.322 + 0.122*SL	0.320 + 0.122*SL
	t_{PLH}	0.375	0.231 + 0.072*SL	0.233 + 0.071*SL	0.237 + 0.071*SL
	t_{PHL}	0.357	0.239 + 0.059*SL	0.242 + 0.058*SL	0.245 + 0.058*SL
E to Y	t_R	1.037	0.733 + 0.152*SL	0.726 + 0.154*SL	0.720 + 0.155*SL
	t_F	0.425	0.297 + 0.064*SL	0.294 + 0.065*SL	0.290 + 0.065*SL
	t_{PLH}	0.592	0.447 + 0.073*SL	0.452 + 0.071*SL	0.456 + 0.071*SL
	t_{PHL}	0.348	0.279 + 0.035*SL	0.282 + 0.034*SL	0.284 + 0.034*SL
F to Y	t_R	1.038	0.734 + 0.152*SL	0.727 + 0.154*SL	0.721 + 0.155*SL
	t_F	0.468	0.338 + 0.065*SL	0.337 + 0.065*SL	0.334 + 0.065*SL
	t_{PLH}	0.635	0.490 + 0.073*SL	0.495 + 0.071*SL	0.500 + 0.071*SL
	t_{PHL}	0.376	0.306 + 0.035*SL	0.309 + 0.034*SL	0.313 + 0.034*SL
G to Y	t_R	1.037	0.733 + 0.152*SL	0.726 + 0.154*SL	0.721 + 0.155*SL
	t_F	0.549	0.423 + 0.063*SL	0.417 + 0.065*SL	0.411 + 0.065*SL
	t_{PLH}	0.653	0.508 + 0.073*SL	0.513 + 0.071*SL	0.517 + 0.071*SL
	t_{PHL}	0.395	0.323 + 0.036*SL	0.328 + 0.035*SL	0.334 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

AO4111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	0.086 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.081 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.468	0.442 + 0.013*SL	0.455 + 0.010*SL	0.468 + 0.009*SL
	t_{PHL}	0.516	0.489 + 0.014*SL	0.502 + 0.010*SL	0.517 + 0.009*SL
B to Y	t_R	0.124	0.087 + 0.018*SL	0.089 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.081 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.506	0.480 + 0.013*SL	0.493 + 0.010*SL	0.506 + 0.009*SL
	t_{PHL}	0.534	0.506 + 0.014*SL	0.519 + 0.010*SL	0.535 + 0.009*SL
C to Y	t_R	0.126	0.091 + 0.018*SL	0.091 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.541	0.514 + 0.013*SL	0.527 + 0.010*SL	0.540 + 0.009*SL
	t_{PHL}	0.545	0.517 + 0.014*SL	0.530 + 0.010*SL	0.546 + 0.009*SL
D to Y	t_R	0.127	0.090 + 0.018*SL	0.092 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.570	0.543 + 0.013*SL	0.557 + 0.010*SL	0.570 + 0.009*SL
	t_{PHL}	0.549	0.521 + 0.014*SL	0.535 + 0.010*SL	0.550 + 0.009*SL
E to Y	t_R	0.128	0.092 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.784	0.757 + 0.013*SL	0.771 + 0.010*SL	0.785 + 0.009*SL
	t_{PHL}	0.548	0.521 + 0.013*SL	0.534 + 0.010*SL	0.548 + 0.009*SL
F to Y	t_R	0.127	0.091 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.106	0.071 + 0.018*SL	0.078 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.827	0.800 + 0.013*SL	0.814 + 0.010*SL	0.828 + 0.009*SL
	t_{PHL}	0.580	0.554 + 0.013*SL	0.566 + 0.010*SL	0.581 + 0.009*SL
G to Y	t_R	0.128	0.091 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.108	0.074 + 0.017*SL	0.078 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.846	0.819 + 0.013*SL	0.833 + 0.010*SL	0.847 + 0.009*SL
	t_{PHL}	0.605	0.578 + 0.014*SL	0.591 + 0.010*SL	0.606 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	Y
0	0	x	1
x	x	0	1
Others States			0

Cell Data

Input Load (SL)														
OA21DH			*OA21*			*OA21D2*			*OA21D2B*			*OA21D4*		
A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
0.5	0.6	0.6	0.9	1.0	0.9	1.8	2.0	1.9	1.0	1.0	1.0	1.0	1.0	1.0

Gate Count				
OA21DH	*OA21*	*OA21D2*	*OA21D2B*	*OA21D4*
1.33	1.33	2.33	2.33	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA21DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.565	0.236 + 0.164*SL	0.215 + 0.169*SL	0.212 + 0.170*SL
	t_F	0.326	0.146 + 0.090*SL	0.129 + 0.094*SL	0.113 + 0.096*SL
	t_{PLH}	0.306	0.152 + 0.077*SL	0.153 + 0.077*SL	0.154 + 0.076*SL
	t_{PHL}	0.219	0.125 + 0.047*SL	0.125 + 0.047*SL	0.126 + 0.047*SL
B to Y	t_R	0.560	0.227 + 0.167*SL	0.216 + 0.169*SL	0.212 + 0.170*SL
	t_F	0.355	0.175 + 0.090*SL	0.159 + 0.094*SL	0.144 + 0.096*SL
	t_{PLH}	0.319	0.164 + 0.077*SL	0.166 + 0.077*SL	0.168 + 0.076*SL
	t_{PHL}	0.240	0.145 + 0.047*SL	0.146 + 0.047*SL	0.147 + 0.047*SL
C to Y	t_R	0.331	0.173 + 0.079*SL	0.159 + 0.082*SL	0.142 + 0.085*SL
	t_F	0.344	0.157 + 0.094*SL	0.151 + 0.095*SL	0.144 + 0.096*SL
	t_{PLH}	0.222	0.146 + 0.038*SL	0.147 + 0.038*SL	0.148 + 0.038*SL
	t_{PHL}	0.238	0.142 + 0.048*SL	0.145 + 0.047*SL	0.146 + 0.047*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.341	0.198 + 0.071*SL	0.187 + 0.074*SL	0.172 + 0.076*SL
	t_F	0.298	0.167 + 0.066*SL	0.156 + 0.068*SL	0.143 + 0.070*SL
	t_{PLH}	0.197	0.128 + 0.035*SL	0.129 + 0.034*SL	0.129 + 0.034*SL
	t_{PHL}	0.201	0.132 + 0.034*SL	0.133 + 0.034*SL	0.134 + 0.034*SL
B to Y	t_R	0.331	0.184 + 0.074*SL	0.178 + 0.075*SL	0.170 + 0.076*SL
	t_F	0.342	0.210 + 0.066*SL	0.200 + 0.068*SL	0.189 + 0.070*SL
	t_{PLH}	0.205	0.135 + 0.035*SL	0.137 + 0.035*SL	0.138 + 0.034*SL
	t_{PHL}	0.232	0.163 + 0.035*SL	0.164 + 0.034*SL	0.166 + 0.034*SL
C to Y	t_R	0.218	0.151 + 0.034*SL	0.144 + 0.035*SL	0.133 + 0.037*SL
	t_F	0.333	0.197 + 0.068*SL	0.192 + 0.069*SL	0.185 + 0.070*SL
	t_{PLH}	0.154	0.117 + 0.019*SL	0.123 + 0.017*SL	0.123 + 0.017*SL
	t_{PHL}	0.251	0.181 + 0.035*SL	0.183 + 0.034*SL	0.185 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OA21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.239	0.169 + 0.035*SL	0.161 + 0.037*SL	0.143 + 0.039*SL
	t_F	0.190	0.134 + 0.028*SL	0.126 + 0.030*SL	0.109 + 0.032*SL
	t_{PLH}	0.145	0.106 + 0.019*SL	0.113 + 0.018*SL	0.113 + 0.018*SL
	t_{PHL}	0.138	0.103 + 0.018*SL	0.111 + 0.016*SL	0.112 + 0.016*SL
B to Y	t_R	0.227	0.154 + 0.036*SL	0.147 + 0.038*SL	0.137 + 0.039*SL
	t_F	0.230	0.173 + 0.028*SL	0.165 + 0.030*SL	0.150 + 0.032*SL
	t_{PLH}	0.155	0.116 + 0.019*SL	0.123 + 0.018*SL	0.124 + 0.018*SL
	t_{PHL}	0.170	0.137 + 0.016*SL	0.140 + 0.016*SL	0.142 + 0.016*SL
C to Y	t_R	0.171	0.139 + 0.016*SL	0.133 + 0.018*SL	0.120 + 0.019*SL
	t_F	0.215	0.154 + 0.030*SL	0.151 + 0.031*SL	0.143 + 0.032*SL
	t_{PLH}	0.128	0.106 + 0.011*SL	0.114 + 0.009*SL	0.117 + 0.009*SL
	t_{PHL}	0.179	0.145 + 0.017*SL	0.148 + 0.016*SL	0.151 + 0.016*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA21D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	0.070 + 0.018*SL	0.070 + 0.018*SL	0.060 + 0.019*SL
	t_F	0.098	0.062 + 0.018*SL	0.068 + 0.016*SL	0.064 + 0.017*SL
	t_{PLH}	0.328	0.304 + 0.012*SL	0.315 + 0.009*SL	0.323 + 0.009*SL
	t_{PHL}	0.333	0.306 + 0.013*SL	0.318 + 0.010*SL	0.331 + 0.009*SL
B to Y	t_R	0.105	0.069 + 0.018*SL	0.067 + 0.018*SL	0.059 + 0.019*SL
	t_F	0.100	0.065 + 0.018*SL	0.070 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.337	0.313 + 0.012*SL	0.323 + 0.009*SL	0.331 + 0.009*SL
	t_{PHL}	0.370	0.343 + 0.013*SL	0.355 + 0.010*SL	0.368 + 0.009*SL
C to Y	t_R	0.104	0.067 + 0.019*SL	0.068 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.100	0.065 + 0.018*SL	0.069 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.306	0.283 + 0.012*SL	0.292 + 0.009*SL	0.300 + 0.009*SL
	t_{PHL}	0.378	0.352 + 0.013*SL	0.364 + 0.010*SL	0.377 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA21D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.097	0.077 + 0.010*SL	0.081 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.084	0.065 + 0.010*SL	0.072 + 0.008*SL	0.071 + 0.008*SL
	t_{PLH}	0.367	0.352 + 0.007*SL	0.360 + 0.005*SL	0.376 + 0.004*SL
	t_{PHL}	0.343	0.328 + 0.008*SL	0.337 + 0.005*SL	0.355 + 0.005*SL
B to Y	t_R	0.097	0.078 + 0.009*SL	0.080 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.086	0.068 + 0.009*SL	0.072 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.376	0.362 + 0.007*SL	0.369 + 0.005*SL	0.386 + 0.004*SL
	t_{PHL}	0.380	0.365 + 0.008*SL	0.374 + 0.006*SL	0.393 + 0.005*SL
C to Y	t_R	0.095	0.075 + 0.010*SL	0.079 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.086	0.067 + 0.010*SL	0.074 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.334	0.320 + 0.007*SL	0.327 + 0.005*SL	0.343 + 0.004*SL
	t_{PHL}	0.390	0.375 + 0.008*SL	0.384 + 0.005*SL	0.402 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OA211DH/OA211/OA211D2/OA211D2B/OA211D4

2-OR into 3-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)																			
OA211DH				*OA211*				*OA211D2*				*OA211D2B*				*OA211D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.6	0.6	0.6	0.6	1.0	1.0	1.0	1.0	2.1	2.0	2.2	2.0	1.0	1.1	1.1	1.1	1.0	1.1	1.1	1.1

Gate Count				
OA211DH	*OA211*	*OA211D2*	*OA211D2B*	*OA211D4*
1.67	1.67	3.00	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA211DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.580	0.251 + 0.165*SL	0.231 + 0.170*SL	0.229 + 0.170*SL
	t_F	0.403	0.183 + 0.110*SL	0.167 + 0.114*SL	0.155 + 0.115*SL
	t_{PLH}	0.315	0.161 + 0.077*SL	0.162 + 0.077*SL	0.163 + 0.076*SL
	t_{PHL}	0.242	0.132 + 0.055*SL	0.132 + 0.055*SL	0.132 + 0.055*SL
B to Y	t_R	0.577	0.243 + 0.167*SL	0.232 + 0.170*SL	0.229 + 0.170*SL
	t_F	0.441	0.220 + 0.110*SL	0.204 + 0.114*SL	0.193 + 0.116*SL
	t_{PLH}	0.328	0.173 + 0.077*SL	0.175 + 0.077*SL	0.178 + 0.076*SL
	t_{PHL}	0.268	0.156 + 0.056*SL	0.158 + 0.055*SL	0.159 + 0.055*SL
C to Y	t_R	0.357	0.188 + 0.084*SL	0.174 + 0.088*SL	0.161 + 0.090*SL
	t_F	0.436	0.210 + 0.113*SL	0.203 + 0.115*SL	0.196 + 0.116*SL
	t_{PLH}	0.240	0.160 + 0.040*SL	0.161 + 0.040*SL	0.162 + 0.040*SL
	t_{PHL}	0.288	0.175 + 0.056*SL	0.178 + 0.056*SL	0.180 + 0.055*SL
D to Y	t_R	0.382	0.212 + 0.085*SL	0.199 + 0.088*SL	0.186 + 0.090*SL
	t_F	0.433	0.206 + 0.114*SL	0.200 + 0.115*SL	0.195 + 0.116*SL
	t_{PLH}	0.254	0.173 + 0.041*SL	0.176 + 0.040*SL	0.177 + 0.040*SL
	t_{PHL}	0.290	0.177 + 0.056*SL	0.180 + 0.056*SL	0.182 + 0.055*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA211

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.359	0.212 + 0.073*SL	0.201 + 0.076*SL	0.187 + 0.078*SL
	t_F	0.336	0.196 + 0.070*SL	0.186 + 0.072*SL	0.175 + 0.074*SL
	t_{PLH}	0.209	0.138 + 0.035*SL	0.139 + 0.035*SL	0.139 + 0.035*SL
	t_{PHL}	0.206	0.135 + 0.035*SL	0.135 + 0.035*SL	0.136 + 0.035*SL
B to Y	t_R	0.351	0.200 + 0.076*SL	0.193 + 0.077*SL	0.186 + 0.078*SL
	t_F	0.385	0.244 + 0.070*SL	0.234 + 0.073*SL	0.223 + 0.074*SL
	t_{PLH}	0.217	0.146 + 0.036*SL	0.147 + 0.035*SL	0.149 + 0.035*SL
	t_{PHL}	0.239	0.167 + 0.036*SL	0.168 + 0.036*SL	0.170 + 0.035*SL
C to Y	t_R	0.228	0.159 + 0.035*SL	0.152 + 0.037*SL	0.142 + 0.038*SL
	t_F	0.379	0.235 + 0.072*SL	0.231 + 0.073*SL	0.224 + 0.074*SL
	t_{PLH}	0.166	0.130 + 0.018*SL	0.133 + 0.017*SL	0.134 + 0.017*SL
	t_{PHL}	0.264	0.191 + 0.036*SL	0.194 + 0.036*SL	0.196 + 0.036*SL
D to Y	t_R	0.244	0.174 + 0.035*SL	0.168 + 0.037*SL	0.157 + 0.038*SL
	t_F	0.377	0.231 + 0.073*SL	0.228 + 0.074*SL	0.222 + 0.074*SL
	t_{PLH}	0.175	0.139 + 0.018*SL	0.141 + 0.018*SL	0.142 + 0.017*SL
	t_{PHL}	0.266	0.193 + 0.037*SL	0.195 + 0.036*SL	0.198 + 0.036*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OA211D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.292	0.220 + 0.036*SL	0.214 + 0.037*SL	0.199 + 0.039*SL
	t_F	0.270	0.202 + 0.034*SL	0.196 + 0.035*SL	0.184 + 0.037*SL
	t_{PLH}	0.176	0.140 + 0.018*SL	0.142 + 0.018*SL	0.142 + 0.018*SL
	t_{PHL}	0.174	0.138 + 0.018*SL	0.138 + 0.018*SL	0.139 + 0.018*SL
B to Y	t_R	0.282	0.207 + 0.037*SL	0.204 + 0.038*SL	0.196 + 0.039*SL
	t_F	0.318	0.249 + 0.035*SL	0.244 + 0.036*SL	0.232 + 0.037*SL
	t_{PLH}	0.183	0.147 + 0.018*SL	0.149 + 0.018*SL	0.151 + 0.018*SL
	t_{PHL}	0.205	0.169 + 0.018*SL	0.170 + 0.018*SL	0.171 + 0.018*SL
C to Y	t_R	0.197	0.163 + 0.017*SL	0.158 + 0.018*SL	0.148 + 0.019*SL
	t_F	0.312	0.241 + 0.036*SL	0.238 + 0.036*SL	0.231 + 0.037*SL
	t_{PLH}	0.150	0.130 + 0.010*SL	0.134 + 0.009*SL	0.135 + 0.009*SL
	t_{PHL}	0.231	0.194 + 0.018*SL	0.196 + 0.018*SL	0.199 + 0.018*SL
D to Y	t_R	0.212	0.177 + 0.017*SL	0.174 + 0.018*SL	0.164 + 0.019*SL
	t_F	0.308	0.236 + 0.036*SL	0.234 + 0.036*SL	0.229 + 0.037*SL
	t_{PLH}	0.158	0.138 + 0.010*SL	0.141 + 0.009*SL	0.143 + 0.009*SL
	t_{PHL}	0.230	0.194 + 0.018*SL	0.195 + 0.018*SL	0.198 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA211D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.110	0.073 + 0.018*SL	0.074 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.104	0.071 + 0.016*SL	0.075 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.373	0.349 + 0.012*SL	0.359 + 0.010*SL	0.367 + 0.009*SL
	t_{PHL}	0.386	0.360 + 0.013*SL	0.372 + 0.010*SL	0.386 + 0.009*SL
B to Y	t_R	0.110	0.074 + 0.018*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.104	0.072 + 0.016*SL	0.075 + 0.015*SL	0.072 + 0.016*SL
	t_{PLH}	0.382	0.358 + 0.012*SL	0.368 + 0.010*SL	0.376 + 0.009*SL
	t_{PHL}	0.427	0.401 + 0.013*SL	0.413 + 0.010*SL	0.427 + 0.009*SL
C to Y	t_R	0.107	0.071 + 0.018*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.103	0.070 + 0.017*SL	0.075 + 0.016*SL	0.072 + 0.016*SL
	t_{PLH}	0.335	0.311 + 0.012*SL	0.321 + 0.009*SL	0.329 + 0.009*SL
	t_{PHL}	0.452	0.426 + 0.013*SL	0.438 + 0.010*SL	0.452 + 0.009*SL
D to Y	t_R	0.109	0.072 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.104	0.071 + 0.017*SL	0.075 + 0.015*SL	0.072 + 0.016*SL
	t_{PLH}	0.345	0.321 + 0.012*SL	0.331 + 0.009*SL	0.339 + 0.009*SL
	t_{PHL}	0.450	0.425 + 0.013*SL	0.437 + 0.010*SL	0.451 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA211D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	0.080 + 0.009*SL	0.080 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.090	0.072 + 0.009*SL	0.076 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.401	0.387 + 0.007*SL	0.395 + 0.005*SL	0.410 + 0.004*SL
	t_{PHL}	0.401	0.386 + 0.008*SL	0.395 + 0.005*SL	0.414 + 0.004*SL
B to Y	t_R	0.098	0.077 + 0.010*SL	0.083 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.090	0.073 + 0.009*SL	0.076 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.411	0.396 + 0.007*SL	0.404 + 0.005*SL	0.420 + 0.004*SL
	t_{PHL}	0.443	0.427 + 0.008*SL	0.436 + 0.006*SL	0.455 + 0.004*SL
C to Y	t_R	0.095	0.077 + 0.009*SL	0.077 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.089	0.071 + 0.009*SL	0.076 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.352	0.338 + 0.007*SL	0.346 + 0.005*SL	0.361 + 0.004*SL
	t_{PHL}	0.468	0.452 + 0.008*SL	0.461 + 0.006*SL	0.480 + 0.004*SL
D to Y	t_R	0.095	0.075 + 0.010*SL	0.080 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.089	0.071 + 0.009*SL	0.076 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.364	0.350 + 0.007*SL	0.357 + 0.005*SL	0.372 + 0.004*SL
	t_{PHL}	0.468	0.452 + 0.008*SL	0.461 + 0.006*SL	0.480 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	1
x	x	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
OA2111					*OA2111D2*					*OA2111*	*OA2111D2*
A	B	C	D	E	A	B	C	D	E		
1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	2.00	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA2111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.409	0.263 + 0.073*SL	0.255 + 0.075*SL	0.243 + 0.077*SL
	t_F	0.432	0.280 + 0.076*SL	0.273 + 0.078*SL	0.263 + 0.079*SL
	t_{PLH}	0.235	0.166 + 0.035*SL	0.166 + 0.035*SL	0.167 + 0.034*SL
	t_{PHL}	0.233	0.159 + 0.037*SL	0.158 + 0.037*SL	0.159 + 0.037*SL
B to Y	t_R	0.404	0.254 + 0.075*SL	0.250 + 0.076*SL	0.244 + 0.076*SL
	t_F	0.481	0.330 + 0.075*SL	0.322 + 0.077*SL	0.313 + 0.079*SL
	t_{PLH}	0.243	0.173 + 0.035*SL	0.174 + 0.035*SL	0.175 + 0.035*SL
	t_{PHL}	0.266	0.191 + 0.037*SL	0.192 + 0.037*SL	0.193 + 0.037*SL
C to Y	t_R	0.261	0.189 + 0.036*SL	0.183 + 0.037*SL	0.176 + 0.038*SL
	t_F	0.483	0.329 + 0.077*SL	0.326 + 0.077*SL	0.320 + 0.078*SL
	t_{PLH}	0.188	0.153 + 0.018*SL	0.154 + 0.018*SL	0.154 + 0.017*SL
	t_{PHL}	0.311	0.235 + 0.038*SL	0.237 + 0.038*SL	0.239 + 0.037*SL
D to Y	t_R	0.278	0.206 + 0.036*SL	0.201 + 0.037*SL	0.194 + 0.038*SL
	t_F	0.481	0.328 + 0.077*SL	0.324 + 0.078*SL	0.319 + 0.078*SL
	t_{PLH}	0.199	0.163 + 0.018*SL	0.164 + 0.018*SL	0.165 + 0.018*SL
	t_{PHL}	0.322	0.246 + 0.038*SL	0.248 + 0.038*SL	0.250 + 0.037*SL
E to Y	t_R	0.297	0.225 + 0.036*SL	0.220 + 0.037*SL	0.212 + 0.038*SL
	t_F	0.479	0.325 + 0.077*SL	0.321 + 0.078*SL	0.319 + 0.078*SL
	t_{PLH}	0.207	0.170 + 0.018*SL	0.172 + 0.018*SL	0.174 + 0.018*SL
	t_{PHL}	0.328	0.252 + 0.038*SL	0.254 + 0.038*SL	0.256 + 0.037*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA2111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.115	0.078 + 0.018*SL	0.079 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.414	0.390 + 0.012*SL	0.400 + 0.010*SL	0.409 + 0.009*SL
	t_{PHL}	0.436	0.409 + 0.013*SL	0.422 + 0.010*SL	0.436 + 0.009*SL
B to Y	t_R	0.114	0.079 + 0.018*SL	0.076 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.082 + 0.015*SL	0.077 + 0.016*SL
	t_{PLH}	0.423	0.399 + 0.012*SL	0.409 + 0.010*SL	0.418 + 0.009*SL
	t_{PHL}	0.477	0.451 + 0.013*SL	0.463 + 0.010*SL	0.478 + 0.009*SL
C to Y	t_R	0.111	0.075 + 0.018*SL	0.075 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.083 + 0.015*SL	0.077 + 0.016*SL
	t_{PLH}	0.364	0.341 + 0.012*SL	0.350 + 0.009*SL	0.358 + 0.009*SL
	t_{PHL}	0.519	0.493 + 0.013*SL	0.505 + 0.010*SL	0.520 + 0.009*SL
D to Y	t_R	0.112	0.076 + 0.018*SL	0.074 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.082 + 0.015*SL	0.077 + 0.016*SL
	t_{PLH}	0.377	0.354 + 0.012*SL	0.363 + 0.009*SL	0.371 + 0.009*SL
	t_{PHL}	0.531	0.505 + 0.013*SL	0.517 + 0.010*SL	0.531 + 0.009*SL
E to Y	t_R	0.113	0.076 + 0.018*SL	0.076 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.082 + 0.015*SL	0.077 + 0.016*SL
	t_{PLH}	0.388	0.364 + 0.012*SL	0.374 + 0.010*SL	0.382 + 0.009*SL
	t_{PHL}	0.538	0.512 + 0.013*SL	0.524 + 0.010*SL	0.539 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA22DH/OA22/OA22D2/OA22D2B/OA22D4

Two 2-ORs into 2-NAND with 0.5X/1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	0	0	1
Other States				0

Cell Data

Input Load (SL)																			
OA22DH				*OA22*				*OA22D2*				*OA22D2B*				*OA22D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.6	0.5	0.6	0.9	0.9	0.9	0.9	1.9	1.8	1.9	1.8	0.9	1.0	1.1	0.9	0.9	1.0	1.1	0.9

Gate Count				
OA22DH	*OA22*	*OA22D2*	*OA22D2B*	*OA22D4*
2.00	2.00	3.00	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA22DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.576	0.278 + 0.149*SL	0.252 + 0.155*SL	0.244 + 0.157*SL
	t_F	0.400	0.176 + 0.112*SL	0.160 + 0.116*SL	0.151 + 0.117*SL
	t_{PLH}	0.276	0.133 + 0.071*SL	0.134 + 0.071*SL	0.136 + 0.071*SL
	t_{PHL}	0.263	0.148 + 0.058*SL	0.151 + 0.057*SL	0.153 + 0.057*SL
B to Y	t_R	0.570	0.265 + 0.152*SL	0.252 + 0.156*SL	0.245 + 0.156*SL
	t_F	0.439	0.214 + 0.112*SL	0.200 + 0.116*SL	0.191 + 0.117*SL
	t_{PLH}	0.288	0.144 + 0.072*SL	0.146 + 0.071*SL	0.148 + 0.071*SL
	t_{PHL}	0.291	0.175 + 0.058*SL	0.179 + 0.057*SL	0.181 + 0.057*SL
C to Y	t_R	0.568	0.263 + 0.152*SL	0.247 + 0.156*SL	0.244 + 0.157*SL
	t_F	0.393	0.165 + 0.114*SL	0.156 + 0.116*SL	0.152 + 0.117*SL
	t_{PLH}	0.336	0.194 + 0.071*SL	0.196 + 0.071*SL	0.198 + 0.070*SL
	t_{PHL}	0.291	0.175 + 0.058*SL	0.180 + 0.057*SL	0.182 + 0.057*SL
D to Y	t_R	0.565	0.257 + 0.154*SL	0.248 + 0.156*SL	0.245 + 0.157*SL
	t_F	0.433	0.204 + 0.115*SL	0.196 + 0.116*SL	0.193 + 0.117*SL
	t_{PLH}	0.348	0.205 + 0.071*SL	0.208 + 0.071*SL	0.210 + 0.070*SL
	t_{PHL}	0.319	0.203 + 0.058*SL	0.208 + 0.057*SL	0.210 + 0.057*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.391	0.248 + 0.071*SL	0.233 + 0.075*SL	0.214 + 0.078*SL
	t_F	0.327	0.180 + 0.074*SL	0.170 + 0.076*SL	0.159 + 0.078*SL
	t_{PLH}	0.184	0.112 + 0.036*SL	0.114 + 0.036*SL	0.114 + 0.036*SL
	t_{PHL}	0.233	0.156 + 0.039*SL	0.159 + 0.038*SL	0.161 + 0.038*SL
B to Y	t_R	0.379	0.231 + 0.074*SL	0.221 + 0.077*SL	0.212 + 0.078*SL
	t_F	0.375	0.227 + 0.074*SL	0.219 + 0.076*SL	0.208 + 0.078*SL
	t_{PLH}	0.194	0.120 + 0.037*SL	0.124 + 0.036*SL	0.125 + 0.036*SL
	t_{PHL}	0.269	0.192 + 0.039*SL	0.195 + 0.038*SL	0.197 + 0.038*SL
C to Y	t_R	0.357	0.210 + 0.074*SL	0.199 + 0.076*SL	0.186 + 0.078*SL
	t_F	0.321	0.170 + 0.075*SL	0.164 + 0.077*SL	0.158 + 0.078*SL
	t_{PLH}	0.223	0.152 + 0.036*SL	0.153 + 0.035*SL	0.154 + 0.035*SL
	t_{PHL}	0.253	0.175 + 0.039*SL	0.179 + 0.038*SL	0.182 + 0.038*SL
D to Y	t_R	0.349	0.197 + 0.076*SL	0.191 + 0.077*SL	0.185 + 0.078*SL
	t_F	0.369	0.217 + 0.076*SL	0.214 + 0.077*SL	0.208 + 0.078*SL
	t_{PLH}	0.233	0.161 + 0.036*SL	0.164 + 0.035*SL	0.165 + 0.035*SL
	t_{PHL}	0.291	0.213 + 0.039*SL	0.216 + 0.038*SL	0.219 + 0.038*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

OA22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.343	0.275 + 0.034*SL	0.266 + 0.036*SL	0.247 + 0.038*SL
	t_F	0.279	0.206 + 0.036*SL	0.201 + 0.037*SL	0.189 + 0.039*SL
	t_{PLH}	0.159	0.122 + 0.018*SL	0.127 + 0.017*SL	0.127 + 0.017*SL
	t_{PHL}	0.212	0.173 + 0.019*SL	0.175 + 0.019*SL	0.178 + 0.019*SL
B to Y	t_R	0.329	0.258 + 0.036*SL	0.252 + 0.037*SL	0.241 + 0.038*SL
	t_F	0.331	0.256 + 0.037*SL	0.253 + 0.038*SL	0.242 + 0.039*SL
	t_{PLH}	0.167	0.131 + 0.018*SL	0.134 + 0.018*SL	0.135 + 0.017*SL
	t_{PHL}	0.251	0.211 + 0.020*SL	0.213 + 0.019*SL	0.216 + 0.019*SL
C to Y	t_R	0.305	0.235 + 0.035*SL	0.229 + 0.037*SL	0.214 + 0.038*SL
	t_F	0.279	0.202 + 0.039*SL	0.199 + 0.039*SL	0.192 + 0.040*SL
	t_{PLH}	0.197	0.162 + 0.018*SL	0.163 + 0.017*SL	0.164 + 0.017*SL
	t_{PHL}	0.237	0.196 + 0.020*SL	0.198 + 0.020*SL	0.202 + 0.019*SL
D to Y	t_R	0.295	0.222 + 0.037*SL	0.218 + 0.038*SL	0.211 + 0.038*SL
	t_F	0.325	0.248 + 0.038*SL	0.246 + 0.039*SL	0.241 + 0.039*SL
	t_{PLH}	0.205	0.170 + 0.018*SL	0.171 + 0.017*SL	0.173 + 0.017*SL
	t_{PHL}	0.270	0.230 + 0.020*SL	0.232 + 0.019*SL	0.235 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA22D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.113	0.078 + 0.018*SL	0.077 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.016*SL	0.069 + 0.016*SL
	t_{PLH}	0.365	0.341 + 0.012*SL	0.351 + 0.009*SL	0.360 + 0.009*SL
	t_{PHL}	0.412	0.387 + 0.013*SL	0.398 + 0.010*SL	0.412 + 0.009*SL
B to Y	t_R	0.112	0.076 + 0.018*SL	0.077 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.102	0.068 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.375	0.351 + 0.012*SL	0.361 + 0.010*SL	0.371 + 0.009*SL
	t_{PHL}	0.458	0.432 + 0.013*SL	0.444 + 0.010*SL	0.458 + 0.009*SL
C to Y	t_R	0.113	0.077 + 0.018*SL	0.075 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.073 + 0.016*SL	0.069 + 0.016*SL
	t_{PLH}	0.400	0.376 + 0.012*SL	0.387 + 0.010*SL	0.396 + 0.009*SL
	t_{PHL}	0.426	0.400 + 0.013*SL	0.412 + 0.010*SL	0.426 + 0.009*SL
D to Y	t_R	0.113	0.077 + 0.018*SL	0.078 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.103	0.069 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.409	0.384 + 0.012*SL	0.395 + 0.009*SL	0.404 + 0.009*SL
	t_{PHL}	0.471	0.445 + 0.013*SL	0.457 + 0.010*SL	0.471 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA22D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.101	0.080 + 0.010*SL	0.086 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.089	0.071 + 0.009*SL	0.075 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.393	0.378 + 0.007*SL	0.386 + 0.005*SL	0.403 + 0.004*SL
	t_{PHL}	0.426	0.411 + 0.008*SL	0.420 + 0.006*SL	0.439 + 0.005*SL
B to Y	t_R	0.101	0.083 + 0.009*SL	0.083 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.089	0.070 + 0.010*SL	0.077 + 0.008*SL	0.077 + 0.008*SL
	t_{PLH}	0.403	0.388 + 0.007*SL	0.396 + 0.005*SL	0.413 + 0.004*SL
	t_{PHL}	0.472	0.456 + 0.008*SL	0.465 + 0.006*SL	0.484 + 0.005*SL
C to Y	t_R	0.102	0.082 + 0.010*SL	0.086 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.088	0.068 + 0.010*SL	0.075 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.429	0.414 + 0.007*SL	0.422 + 0.005*SL	0.439 + 0.004*SL
	t_{PHL}	0.441	0.426 + 0.008*SL	0.434 + 0.006*SL	0.454 + 0.005*SL
D to Y	t_R	0.102	0.083 + 0.010*SL	0.086 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.089	0.070 + 0.010*SL	0.077 + 0.008*SL	0.076 + 0.008*SL
	t_{PLH}	0.437	0.422 + 0.007*SL	0.431 + 0.005*SL	0.447 + 0.004*SL
	t_{PHL}	0.485	0.470 + 0.008*SL	0.479 + 0.006*SL	0.498 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	1
x	x	1	1	1
Other States				0

Cell Data

Input Load (SL)															
OA22DHA				*OA22A*				*OA22D2A*				*OA22D4A*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.5	0.5	0.5	0.5	1.0	1.0	0.6	0.6	2.0	1.9	0.6	0.6	1.0	1.0	0.6	0.6

Gate Count			
OA22DHA	*OA22A*	*OA22D2A*	*OA22D4A*
2.00	2.00	3.00	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA22DHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.521	0.194 + 0.164*SL	0.171 + 0.169*SL	0.167 + 0.170*SL
	t_F	0.294	0.122 + 0.086*SL	0.104 + 0.090*SL	0.087 + 0.093*SL
	t_{PLH}	0.289	0.135 + 0.077*SL	0.136 + 0.077*SL	0.137 + 0.076*SL
	t_{PHL}	0.201	0.109 + 0.046*SL	0.111 + 0.045*SL	0.112 + 0.045*SL
B to Y	t_R	0.516	0.184 + 0.166*SL	0.171 + 0.169*SL	0.167 + 0.170*SL
	t_F	0.325	0.153 + 0.086*SL	0.135 + 0.091*SL	0.117 + 0.093*SL
	t_{PLH}	0.299	0.145 + 0.077*SL	0.147 + 0.077*SL	0.149 + 0.076*SL
	t_{PHL}	0.221	0.129 + 0.046*SL	0.131 + 0.046*SL	0.132 + 0.045*SL
C to Y	t_R	0.309	0.146 + 0.082*SL	0.139 + 0.083*SL	0.132 + 0.084*SL
	t_F	0.307	0.124 + 0.092*SL	0.120 + 0.093*SL	0.117 + 0.093*SL
	t_{PLH}	0.342	0.263 + 0.039*SL	0.269 + 0.038*SL	0.271 + 0.038*SL
	t_{PHL}	0.343	0.249 + 0.047*SL	0.254 + 0.046*SL	0.256 + 0.046*SL
D to Y	t_R	0.309	0.146 + 0.082*SL	0.140 + 0.083*SL	0.132 + 0.084*SL
	t_F	0.308	0.125 + 0.091*SL	0.121 + 0.093*SL	0.118 + 0.093*SL
	t_{PLH}	0.339	0.260 + 0.039*SL	0.266 + 0.038*SL	0.268 + 0.038*SL
	t_{PHL}	0.359	0.265 + 0.047*SL	0.270 + 0.046*SL	0.272 + 0.046*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OA22A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.314	0.173 + 0.071*SL	0.160 + 0.074*SL	0.143 + 0.076*SL
	t_F	0.257	0.138 + 0.060*SL	0.126 + 0.063*SL	0.112 + 0.065*SL
	t_{PLH}	0.183	0.113 + 0.035*SL	0.116 + 0.034*SL	0.116 + 0.034*SL
	t_{PHL}	0.178	0.113 + 0.032*SL	0.116 + 0.032*SL	0.117 + 0.032*SL
B to Y	t_R	0.303	0.157 + 0.073*SL	0.148 + 0.075*SL	0.141 + 0.076*SL
	t_F	0.300	0.178 + 0.061*SL	0.168 + 0.063*SL	0.155 + 0.065*SL
	t_{PLH}	0.191	0.120 + 0.035*SL	0.124 + 0.035*SL	0.125 + 0.034*SL
	t_{PHL}	0.208	0.143 + 0.032*SL	0.145 + 0.032*SL	0.147 + 0.032*SL
C to Y	t_R	0.194	0.122 + 0.036*SL	0.120 + 0.037*SL	0.115 + 0.038*SL
	t_F	0.285	0.157 + 0.064*SL	0.154 + 0.065*SL	0.151 + 0.065*SL
	t_{PLH}	0.270	0.231 + 0.019*SL	0.238 + 0.018*SL	0.242 + 0.017*SL
	t_{PHL}	0.353	0.286 + 0.033*SL	0.291 + 0.032*SL	0.294 + 0.032*SL
D to Y	t_R	0.194	0.122 + 0.036*SL	0.119 + 0.037*SL	0.115 + 0.038*SL
	t_F	0.286	0.158 + 0.064*SL	0.155 + 0.065*SL	0.152 + 0.065*SL
	t_{PLH}	0.266	0.227 + 0.020*SL	0.234 + 0.018*SL	0.239 + 0.017*SL
	t_{PHL}	0.371	0.304 + 0.033*SL	0.308 + 0.032*SL	0.311 + 0.032*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA22D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.245	0.177 + 0.034*SL	0.168 + 0.036*SL	0.151 + 0.038*SL
	t_F	0.199	0.142 + 0.029*SL	0.134 + 0.031*SL	0.119 + 0.032*SL
	t_{PLH}	0.147	0.110 + 0.019*SL	0.116 + 0.017*SL	0.116 + 0.017*SL
	t_{PHL}	0.145	0.110 + 0.018*SL	0.117 + 0.016*SL	0.117 + 0.016*SL
B to Y	t_R	0.232	0.161 + 0.036*SL	0.155 + 0.037*SL	0.145 + 0.038*SL
	t_F	0.242	0.182 + 0.030*SL	0.176 + 0.031*SL	0.162 + 0.032*SL
	t_{PLH}	0.156	0.118 + 0.019*SL	0.124 + 0.017*SL	0.126 + 0.017*SL
	t_{PHL}	0.177	0.144 + 0.016*SL	0.146 + 0.016*SL	0.148 + 0.016*SL
C to Y	t_R	0.180	0.141 + 0.019*SL	0.145 + 0.018*SL	0.142 + 0.018*SL
	t_F	0.236	0.173 + 0.031*SL	0.170 + 0.032*SL	0.165 + 0.033*SL
	t_{PLH}	0.313	0.289 + 0.012*SL	0.296 + 0.010*SL	0.308 + 0.009*SL
	t_{PHL}	0.376	0.340 + 0.018*SL	0.345 + 0.017*SL	0.351 + 0.016*SL
D to Y	t_R	0.180	0.142 + 0.019*SL	0.145 + 0.018*SL	0.142 + 0.018*SL
	t_F	0.237	0.174 + 0.031*SL	0.172 + 0.032*SL	0.166 + 0.032*SL
	t_{PLH}	0.311	0.287 + 0.012*SL	0.294 + 0.010*SL	0.306 + 0.009*SL
	t_{PHL}	0.393	0.358 + 0.018*SL	0.362 + 0.017*SL	0.369 + 0.016*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA22D4A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.075 + 0.010*SL	0.081 + 0.009*SL	0.072 + 0.009*SL
	t_F	0.087	0.069 + 0.009*SL	0.073 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.368	0.353 + 0.007*SL	0.361 + 0.005*SL	0.377 + 0.004*SL
	t_{PHL}	0.358	0.343 + 0.008*SL	0.352 + 0.006*SL	0.371 + 0.005*SL
B to Y	t_R	0.097	0.078 + 0.009*SL	0.079 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.089	0.070 + 0.009*SL	0.075 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.376	0.362 + 0.007*SL	0.370 + 0.005*SL	0.385 + 0.004*SL
	t_{PHL}	0.396	0.380 + 0.008*SL	0.389 + 0.006*SL	0.408 + 0.005*SL
C to Y	t_R	0.094	0.074 + 0.010*SL	0.079 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.087	0.069 + 0.009*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.456	0.442 + 0.007*SL	0.450 + 0.005*SL	0.464 + 0.004*SL
	t_{PHL}	0.542	0.527 + 0.008*SL	0.536 + 0.006*SL	0.555 + 0.005*SL
D to Y	t_R	0.094	0.074 + 0.010*SL	0.078 + 0.009*SL	0.070 + 0.009*SL
	t_F	0.087	0.068 + 0.009*SL	0.074 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.452	0.438 + 0.007*SL	0.446 + 0.005*SL	0.461 + 0.004*SL
	t_{PHL}	0.560	0.545 + 0.008*SL	0.553 + 0.006*SL	0.572 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OA221/OA221D2/OA221D4

Two 2-ORs into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	1
x	x	0	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)														
OA221					*OA221D2*					*OA221D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
1.0	1.0	1.0	1.2	1.0	1.0	1.0	1.0	1.2	1.0	1.0	1.0	1.0	1.2	1.0

Gate Count		
OA221	*OA221D2*	*OA221D4*
2.00	3.00	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA221

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.448	0.306 + 0.071*SL	0.294 + 0.074*SL	0.280 + 0.076*SL
	t_F	0.448	0.280 + 0.084*SL	0.272 + 0.086*SL	0.264 + 0.087*SL
	t_{PLH}	0.214	0.144 + 0.035*SL	0.144 + 0.035*SL	0.145 + 0.035*SL
	t_{PHL}	0.282	0.197 + 0.042*SL	0.199 + 0.042*SL	0.201 + 0.042*SL
B to Y	t_R	0.440	0.293 + 0.074*SL	0.286 + 0.075*SL	0.278 + 0.076*SL
	t_F	0.507	0.337 + 0.085*SL	0.330 + 0.087*SL	0.324 + 0.088*SL
	t_{PLH}	0.224	0.154 + 0.035*SL	0.154 + 0.035*SL	0.156 + 0.035*SL
	t_{PHL}	0.325	0.240 + 0.042*SL	0.242 + 0.042*SL	0.244 + 0.042*SL
C to Y	t_R	0.414	0.268 + 0.073*SL	0.260 + 0.075*SL	0.248 + 0.077*SL
	t_F	0.447	0.278 + 0.085*SL	0.273 + 0.086*SL	0.268 + 0.087*SL
	t_{PLH}	0.252	0.183 + 0.035*SL	0.183 + 0.035*SL	0.184 + 0.034*SL
	t_{PHL}	0.312	0.226 + 0.043*SL	0.230 + 0.042*SL	0.232 + 0.041*SL
D to Y	t_R	0.408	0.258 + 0.075*SL	0.254 + 0.076*SL	0.248 + 0.077*SL
	t_F	0.506	0.335 + 0.086*SL	0.331 + 0.087*SL	0.327 + 0.087*SL
	t_{PLH}	0.265	0.194 + 0.035*SL	0.196 + 0.035*SL	0.197 + 0.035*SL
	t_{PHL}	0.359	0.273 + 0.043*SL	0.276 + 0.042*SL	0.279 + 0.042*SL
E to Y	t_R	0.255	0.187 + 0.034*SL	0.179 + 0.036*SL	0.170 + 0.037*SL
	t_F	0.504	0.331 + 0.086*SL	0.328 + 0.087*SL	0.327 + 0.087*SL
	t_{PLH}	0.180	0.144 + 0.018*SL	0.146 + 0.017*SL	0.148 + 0.017*SL
	t_{PHL}	0.373	0.287 + 0.043*SL	0.290 + 0.042*SL	0.293 + 0.042*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA221D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.114	0.079 + 0.018*SL	0.077 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.104	0.071 + 0.017*SL	0.077 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.403	0.378 + 0.012*SL	0.389 + 0.010*SL	0.399 + 0.009*SL
	t_{PHL}	0.474	0.448 + 0.013*SL	0.461 + 0.010*SL	0.475 + 0.009*SL
B to Y	t_R	0.115	0.079 + 0.018*SL	0.080 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.106	0.073 + 0.016*SL	0.078 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.412	0.387 + 0.012*SL	0.398 + 0.010*SL	0.408 + 0.009*SL
	t_{PHL}	0.524	0.497 + 0.013*SL	0.510 + 0.010*SL	0.525 + 0.009*SL
C to Y	t_R	0.115	0.079 + 0.018*SL	0.078 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.105	0.072 + 0.017*SL	0.077 + 0.015*SL	0.073 + 0.016*SL
	t_{PLH}	0.440	0.416 + 0.012*SL	0.426 + 0.010*SL	0.436 + 0.009*SL
	t_{PHL}	0.502	0.476 + 0.013*SL	0.488 + 0.010*SL	0.503 + 0.009*SL
D to Y	t_R	0.116	0.080 + 0.018*SL	0.080 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.106	0.073 + 0.017*SL	0.078 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.452	0.428 + 0.012*SL	0.439 + 0.010*SL	0.449 + 0.009*SL
	t_{PHL}	0.557	0.531 + 0.013*SL	0.543 + 0.010*SL	0.558 + 0.009*SL
E to Y	t_R	0.111	0.075 + 0.018*SL	0.075 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.106	0.073 + 0.016*SL	0.078 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.369	0.345 + 0.012*SL	0.355 + 0.010*SL	0.364 + 0.009*SL
	t_{PHL}	0.572	0.545 + 0.013*SL	0.558 + 0.010*SL	0.573 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA221D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.103	0.083 + 0.010*SL	0.088 + 0.009*SL	0.079 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.081 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.431	0.416 + 0.007*SL	0.425 + 0.005*SL	0.442 + 0.004*SL
	t_{PHL}	0.490	0.475 + 0.008*SL	0.484 + 0.006*SL	0.504 + 0.005*SL
B to Y	t_R	0.103	0.085 + 0.009*SL	0.086 + 0.009*SL	0.080 + 0.009*SL
	t_F	0.095	0.076 + 0.009*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.440	0.425 + 0.007*SL	0.434 + 0.005*SL	0.451 + 0.004*SL
	t_{PHL}	0.540	0.524 + 0.008*SL	0.533 + 0.006*SL	0.554 + 0.005*SL
C to Y	t_R	0.104	0.084 + 0.010*SL	0.089 + 0.009*SL	0.080 + 0.009*SL
	t_F	0.093	0.076 + 0.009*SL	0.079 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.469	0.455 + 0.007*SL	0.463 + 0.005*SL	0.481 + 0.004*SL
	t_{PHL}	0.523	0.507 + 0.008*SL	0.516 + 0.006*SL	0.537 + 0.005*SL
D to Y	t_R	0.104	0.086 + 0.009*SL	0.086 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.094	0.075 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.482	0.467 + 0.007*SL	0.476 + 0.005*SL	0.493 + 0.004*SL
	t_{PHL}	0.572	0.556 + 0.008*SL	0.565 + 0.006*SL	0.586 + 0.005*SL
E to Y	t_R	0.098	0.078 + 0.010*SL	0.083 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.093	0.075 + 0.009*SL	0.080 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.388	0.374 + 0.007*SL	0.382 + 0.005*SL	0.398 + 0.004*SL
	t_{PHL}	0.588	0.572 + 0.008*SL	0.581 + 0.006*SL	0.602 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OA222/OA222D2/OA222D2B/OA222D4

Three 2-ORs into 3-NAND with 1X/2X/2X(Buffered)/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	x	x	x	x	1
x	x	0	0	x	x	1
x	x	x	x	0	0	1
Other States						0

Cell Data

Input Load (SL)												Gate Count	
OA222						*OA222D2*						*OA222*	*OA222D2*
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	1.0	1.0	0.9	1.0	1.8	2.1	1.8	2.0	1.8	2.0	2.67	4.67
OA222D2B						*OA222D4*						*OA222D2B*	*OA222D4*
A	B	C	D	E	F	A	B	C	D	E	F		
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.9	1.0	3.67	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.537	0.395 + 0.071*SL	0.382 + 0.074*SL	0.368 + 0.076*SL
	t_F	0.556	0.368 + 0.094*SL	0.362 + 0.095*SL	0.361 + 0.095*SL
	t_{PLH}	0.221	0.150 + 0.035*SL	0.150 + 0.035*SL	0.151 + 0.035*SL
	t_{PHL}	0.358	0.265 + 0.047*SL	0.268 + 0.046*SL	0.271 + 0.045*SL
B to Y	t_R	0.529	0.382 + 0.073*SL	0.375 + 0.075*SL	0.366 + 0.076*SL
	t_F	0.614	0.426 + 0.094*SL	0.421 + 0.095*SL	0.421 + 0.095*SL
	t_{PLH}	0.229	0.158 + 0.035*SL	0.158 + 0.036*SL	0.159 + 0.035*SL
	t_{PHL}	0.401	0.308 + 0.046*SL	0.311 + 0.046*SL	0.313 + 0.045*SL
C to Y	t_R	0.509	0.364 + 0.073*SL	0.356 + 0.075*SL	0.343 + 0.077*SL
	t_F	0.554	0.366 + 0.094*SL	0.363 + 0.095*SL	0.362 + 0.095*SL
	t_{PLH}	0.266	0.195 + 0.035*SL	0.196 + 0.035*SL	0.197 + 0.035*SL
	t_{PHL}	0.402	0.308 + 0.047*SL	0.312 + 0.046*SL	0.315 + 0.046*SL
D to Y	t_R	0.504	0.355 + 0.074*SL	0.350 + 0.076*SL	0.344 + 0.076*SL
	t_F	0.616	0.428 + 0.094*SL	0.426 + 0.095*SL	0.425 + 0.095*SL
	t_{PLH}	0.278	0.206 + 0.036*SL	0.208 + 0.035*SL	0.210 + 0.035*SL
	t_{PHL}	0.450	0.357 + 0.046*SL	0.360 + 0.046*SL	0.362 + 0.045*SL
E to Y	t_R	0.478	0.331 + 0.073*SL	0.324 + 0.075*SL	0.314 + 0.077*SL
	t_F	0.554	0.366 + 0.094*SL	0.364 + 0.095*SL	0.363 + 0.095*SL
	t_{PLH}	0.294	0.222 + 0.036*SL	0.225 + 0.035*SL	0.228 + 0.035*SL
	t_{PHL}	0.420	0.326 + 0.047*SL	0.330 + 0.046*SL	0.333 + 0.045*SL
F to Y	t_R	0.474	0.324 + 0.075*SL	0.321 + 0.076*SL	0.315 + 0.077*SL
	t_F	0.615	0.427 + 0.094*SL	0.425 + 0.095*SL	0.425 + 0.095*SL
	t_{PLH}	0.304	0.233 + 0.036*SL	0.236 + 0.035*SL	0.239 + 0.035*SL
	t_{PHL}	0.466	0.373 + 0.046*SL	0.376 + 0.046*SL	0.379 + 0.045*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.464	0.394 + 0.035*SL	0.388 + 0.036*SL	0.371 + 0.038*SL
	t_F	0.456	0.364 + 0.046*SL	0.360 + 0.047*SL	0.355 + 0.048*SL
	t_{PLH}	0.185	0.149 + 0.018*SL	0.149 + 0.018*SL	0.150 + 0.018*SL
	t_{PHL}	0.310	0.263 + 0.023*SL	0.265 + 0.023*SL	0.268 + 0.023*SL
B to Y	t_R	0.453	0.380 + 0.036*SL	0.376 + 0.037*SL	0.367 + 0.038*SL
	t_F	0.516	0.423 + 0.047*SL	0.420 + 0.047*SL	0.416 + 0.048*SL
	t_{PLH}	0.195	0.159 + 0.018*SL	0.160 + 0.018*SL	0.161 + 0.018*SL
	t_{PHL}	0.357	0.311 + 0.023*SL	0.312 + 0.023*SL	0.315 + 0.023*SL
C to Y	t_R	0.429	0.357 + 0.036*SL	0.352 + 0.037*SL	0.338 + 0.038*SL
	t_F	0.459	0.365 + 0.047*SL	0.364 + 0.047*SL	0.360 + 0.048*SL
	t_{PLH}	0.223	0.187 + 0.018*SL	0.188 + 0.018*SL	0.189 + 0.017*SL
	t_{PHL}	0.345	0.297 + 0.024*SL	0.299 + 0.023*SL	0.304 + 0.023*SL
D to Y	t_R	0.421	0.347 + 0.037*SL	0.344 + 0.038*SL	0.336 + 0.038*SL
	t_F	0.517	0.424 + 0.047*SL	0.422 + 0.047*SL	0.420 + 0.047*SL
	t_{PLH}	0.234	0.198 + 0.018*SL	0.199 + 0.018*SL	0.200 + 0.017*SL
	t_{PHL}	0.391	0.345 + 0.023*SL	0.346 + 0.023*SL	0.350 + 0.023*SL
E to Y	t_R	0.400	0.327 + 0.036*SL	0.324 + 0.037*SL	0.312 + 0.038*SL
	t_F	0.456	0.361 + 0.047*SL	0.360 + 0.047*SL	0.358 + 0.048*SL
	t_{PLH}	0.255	0.218 + 0.018*SL	0.220 + 0.018*SL	0.224 + 0.017*SL
	t_{PHL}	0.367	0.319 + 0.024*SL	0.322 + 0.023*SL	0.326 + 0.023*SL
F to Y	t_R	0.395	0.320 + 0.037*SL	0.318 + 0.038*SL	0.312 + 0.038*SL
	t_F	0.516	0.421 + 0.047*SL	0.421 + 0.047*SL	0.419 + 0.047*SL
	t_{PLH}	0.267	0.231 + 0.018*SL	0.233 + 0.018*SL	0.236 + 0.017*SL
	t_{PHL}	0.415	0.368 + 0.023*SL	0.370 + 0.023*SL	0.374 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA222D2B

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	0.085 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.109	0.076 + 0.017*SL	0.081 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.434	0.409 + 0.012*SL	0.420 + 0.010*SL	0.431 + 0.009*SL
	t_{PHL}	0.566	0.539 + 0.013*SL	0.552 + 0.010*SL	0.567 + 0.009*SL
B to Y	t_R	0.119	0.083 + 0.018*SL	0.084 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.082 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.441	0.417 + 0.012*SL	0.428 + 0.010*SL	0.438 + 0.009*SL
	t_{PHL}	0.616	0.590 + 0.013*SL	0.602 + 0.010*SL	0.617 + 0.009*SL
C to Y	t_R	0.121	0.086 + 0.018*SL	0.086 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.110	0.077 + 0.016*SL	0.081 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.478	0.453 + 0.012*SL	0.465 + 0.010*SL	0.476 + 0.009*SL
	t_{PHL}	0.608	0.581 + 0.013*SL	0.594 + 0.010*SL	0.609 + 0.009*SL
D to Y	t_R	0.121	0.085 + 0.018*SL	0.086 + 0.018*SL	0.075 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.082 + 0.015*SL	0.079 + 0.016*SL
	t_{PLH}	0.491	0.466 + 0.012*SL	0.477 + 0.010*SL	0.488 + 0.009*SL
	t_{PHL}	0.665	0.638 + 0.013*SL	0.651 + 0.010*SL	0.666 + 0.009*SL
E to Y	t_R	0.122	0.086 + 0.018*SL	0.088 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.110	0.077 + 0.016*SL	0.081 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.511	0.485 + 0.013*SL	0.497 + 0.010*SL	0.508 + 0.009*SL
	t_{PHL}	0.628	0.602 + 0.013*SL	0.614 + 0.010*SL	0.629 + 0.009*SL
F to Y	t_R	0.122	0.087 + 0.018*SL	0.087 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.083 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.521	0.496 + 0.013*SL	0.508 + 0.010*SL	0.519 + 0.009*SL
	t_{PHL}	0.683	0.657 + 0.013*SL	0.669 + 0.010*SL	0.685 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA222D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	0.089 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.097	0.079 + 0.009*SL	0.082 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.464	0.449 + 0.008*SL	0.458 + 0.005*SL	0.476 + 0.004*SL
	t_{PHL}	0.585	0.569 + 0.008*SL	0.578 + 0.006*SL	0.599 + 0.005*SL
B to Y	t_R	0.108	0.089 + 0.010*SL	0.093 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.098	0.078 + 0.010*SL	0.086 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.472	0.457 + 0.008*SL	0.466 + 0.005*SL	0.484 + 0.004*SL
	t_{PHL}	0.635	0.619 + 0.008*SL	0.628 + 0.006*SL	0.649 + 0.005*SL
C to Y	t_R	0.109	0.089 + 0.010*SL	0.093 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.082 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.509	0.494 + 0.008*SL	0.503 + 0.005*SL	0.522 + 0.004*SL
	t_{PHL}	0.627	0.611 + 0.008*SL	0.620 + 0.006*SL	0.641 + 0.005*SL
D to Y	t_R	0.109	0.090 + 0.010*SL	0.092 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.098	0.080 + 0.009*SL	0.083 + 0.008*SL	0.086 + 0.008*SL
	t_{PLH}	0.522	0.507 + 0.008*SL	0.516 + 0.005*SL	0.534 + 0.004*SL
	t_{PHL}	0.684	0.668 + 0.008*SL	0.677 + 0.006*SL	0.699 + 0.005*SL
E to Y	t_R	0.110	0.091 + 0.010*SL	0.094 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.082 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.542	0.526 + 0.008*SL	0.535 + 0.005*SL	0.554 + 0.004*SL
	t_{PHL}	0.646	0.631 + 0.008*SL	0.639 + 0.006*SL	0.661 + 0.005*SL
F to Y	t_R	0.111	0.091 + 0.010*SL	0.095 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.098	0.080 + 0.009*SL	0.085 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.553	0.537 + 0.008*SL	0.546 + 0.005*SL	0.565 + 0.004*SL
	t_{PHL}	0.701	0.686 + 0.008*SL	0.695 + 0.006*SL	0.716 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	x	x	x	x	x	x	1
x	x	0	0	x	x	x	x	1
x	x	x	x	0	0	x	x	1
x	x	x	x	x	x	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
OA2222								*OA2222*
A	B	C	D	E	F	G	H	
0.9	1.0	0.9	1.0	1.0	1.0	1.1	1.0	3.33
OA2222D2								*OA2222D2*
A	B	C	D	E	F	G	H	
1.0	1.0	0.9	1.0	0.9	1.0	1.1	1.0	4.33
OA2222D4								*OA2222D4*
A	B	C	D	E	F	G	H	
1.0	1.0	0.9	1.0	1.0	1.0	1.1	1.0	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA2222

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.640	0.497 + 0.072*SL	0.486 + 0.074*SL	0.472 + 0.076*SL
	t_F	0.631	0.430 + 0.101*SL	0.424 + 0.102*SL	0.425 + 0.102*SL
	t_{PLH}	0.237	0.165 + 0.036*SL	0.166 + 0.036*SL	0.167 + 0.036*SL
	t_{PHL}	0.381	0.282 + 0.049*SL	0.285 + 0.049*SL	0.288 + 0.048*SL
B to Y	t_R	0.632	0.485 + 0.074*SL	0.478 + 0.075*SL	0.471 + 0.076*SL
	t_F	0.698	0.495 + 0.101*SL	0.491 + 0.102*SL	0.493 + 0.102*SL
	t_{PLH}	0.248	0.176 + 0.036*SL	0.175 + 0.036*SL	0.178 + 0.036*SL
	t_{PHL}	0.432	0.334 + 0.049*SL	0.336 + 0.049*SL	0.338 + 0.048*SL
C to Y	t_R	0.629	0.481 + 0.074*SL	0.472 + 0.076*SL	0.462 + 0.077*SL
	t_F	0.636	0.434 + 0.101*SL	0.432 + 0.101*SL	0.431 + 0.101*SL
	t_{PLH}	0.291	0.219 + 0.036*SL	0.220 + 0.036*SL	0.222 + 0.036*SL
	t_{PHL}	0.442	0.343 + 0.050*SL	0.346 + 0.049*SL	0.349 + 0.048*SL
D to Y	t_R	0.624	0.473 + 0.075*SL	0.469 + 0.076*SL	0.462 + 0.077*SL
	t_F	0.704	0.502 + 0.101*SL	0.500 + 0.101*SL	0.499 + 0.102*SL
	t_{PLH}	0.304	0.231 + 0.036*SL	0.232 + 0.036*SL	0.234 + 0.036*SL
	t_{PHL}	0.493	0.395 + 0.049*SL	0.397 + 0.049*SL	0.400 + 0.048*SL
E to Y	t_R	0.601	0.452 + 0.074*SL	0.445 + 0.076*SL	0.436 + 0.077*SL
	t_F	0.638	0.436 + 0.101*SL	0.435 + 0.101*SL	0.434 + 0.102*SL
	t_{PLH}	0.325	0.252 + 0.036*SL	0.254 + 0.036*SL	0.257 + 0.035*SL
	t_{PHL}	0.469	0.370 + 0.050*SL	0.373 + 0.049*SL	0.377 + 0.048*SL
F to Y	t_R	0.599	0.448 + 0.075*SL	0.444 + 0.077*SL	0.437 + 0.077*SL
	t_F	0.704	0.501 + 0.101*SL	0.500 + 0.102*SL	0.499 + 0.102*SL
	t_{PLH}	0.336	0.263 + 0.037*SL	0.266 + 0.036*SL	0.268 + 0.035*SL
	t_{PHL}	0.520	0.421 + 0.049*SL	0.424 + 0.049*SL	0.426 + 0.048*SL
G to Y	t_R	0.644	0.495 + 0.075*SL	0.488 + 0.076*SL	0.479 + 0.077*SL
	t_F	0.813	0.583 + 0.115*SL	0.582 + 0.116*SL	0.581 + 0.116*SL
	t_{PLH}	0.351	0.277 + 0.037*SL	0.281 + 0.036*SL	0.285 + 0.036*SL
	t_{PHL}	0.620	0.507 + 0.056*SL	0.511 + 0.055*SL	0.515 + 0.055*SL
H to Y	t_R	0.642	0.492 + 0.075*SL	0.487 + 0.076*SL	0.481 + 0.077*SL
	t_F	0.893	0.661 + 0.116*SL	0.661 + 0.116*SL	0.661 + 0.116*SL
	t_{PLH}	0.361	0.286 + 0.037*SL	0.290 + 0.036*SL	0.294 + 0.036*SL
	t_{PHL}	0.677	0.565 + 0.056*SL	0.568 + 0.055*SL	0.571 + 0.055*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA2222D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.123	0.087 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.111	0.077 + 0.017*SL	0.084 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.471	0.445 + 0.013*SL	0.458 + 0.010*SL	0.470 + 0.009*SL
	t_{PHL}	0.599	0.572 + 0.013*SL	0.585 + 0.010*SL	0.601 + 0.009*SL
B to Y	t_R	0.123	0.088 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.112	0.078 + 0.017*SL	0.085 + 0.015*SL	0.079 + 0.016*SL
	t_{PLH}	0.481	0.456 + 0.013*SL	0.468 + 0.010*SL	0.480 + 0.009*SL
	t_{PHL}	0.658	0.631 + 0.013*SL	0.644 + 0.010*SL	0.660 + 0.009*SL
C to Y	t_R	0.124	0.088 + 0.018*SL	0.089 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.111	0.077 + 0.017*SL	0.084 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.527	0.501 + 0.013*SL	0.514 + 0.010*SL	0.526 + 0.009*SL
	t_{PHL}	0.659	0.632 + 0.013*SL	0.645 + 0.010*SL	0.661 + 0.009*SL
D to Y	t_R	0.125	0.090 + 0.018*SL	0.090 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.112	0.078 + 0.017*SL	0.085 + 0.015*SL	0.079 + 0.016*SL
	t_{PLH}	0.540	0.514 + 0.013*SL	0.526 + 0.010*SL	0.538 + 0.009*SL
	t_{PHL}	0.719	0.692 + 0.013*SL	0.705 + 0.010*SL	0.721 + 0.009*SL
E to Y	t_R	0.126	0.091 + 0.018*SL	0.091 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.111	0.077 + 0.017*SL	0.084 + 0.015*SL	0.078 + 0.016*SL
	t_{PLH}	0.561	0.535 + 0.013*SL	0.547 + 0.010*SL	0.559 + 0.009*SL
	t_{PHL}	0.681	0.655 + 0.013*SL	0.668 + 0.010*SL	0.683 + 0.009*SL
F to Y	t_R	0.126	0.090 + 0.018*SL	0.091 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.111	0.078 + 0.017*SL	0.084 + 0.015*SL	0.080 + 0.016*SL
	t_{PLH}	0.575	0.549 + 0.013*SL	0.562 + 0.010*SL	0.574 + 0.009*SL
	t_{PHL}	0.745	0.718 + 0.013*SL	0.731 + 0.010*SL	0.748 + 0.009*SL
G to Y	t_R	0.127	0.090 + 0.018*SL	0.093 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.114	0.081 + 0.017*SL	0.086 + 0.015*SL	0.083 + 0.016*SL
	t_{PLH}	0.593	0.567 + 0.013*SL	0.580 + 0.010*SL	0.592 + 0.009*SL
	t_{PHL}	0.854	0.827 + 0.014*SL	0.840 + 0.010*SL	0.857 + 0.009*SL
H to Y	t_R	0.128	0.092 + 0.018*SL	0.093 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.117	0.083 + 0.017*SL	0.090 + 0.015*SL	0.084 + 0.016*SL
	t_{PLH}	0.605	0.579 + 0.013*SL	0.592 + 0.010*SL	0.604 + 0.009*SL
	t_{PHL}	0.922	0.895 + 0.014*SL	0.908 + 0.010*SL	0.925 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA2222D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.113	0.093 + 0.010*SL	0.097 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.098	0.079 + 0.009*SL	0.085 + 0.008*SL	0.086 + 0.008*SL
	t_{PLH}	0.506	0.490 + 0.008*SL	0.499 + 0.006*SL	0.519 + 0.004*SL
	t_{PHL}	0.610	0.594 + 0.008*SL	0.603 + 0.006*SL	0.625 + 0.005*SL
B to Y	t_R	0.113	0.093 + 0.010*SL	0.097 + 0.009*SL	0.089 + 0.009*SL
	t_F	0.098	0.081 + 0.009*SL	0.084 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	0.516	0.500 + 0.008*SL	0.509 + 0.006*SL	0.529 + 0.004*SL
	t_{PHL}	0.668	0.652 + 0.008*SL	0.661 + 0.006*SL	0.683 + 0.005*SL
C to Y	t_R	0.114	0.094 + 0.010*SL	0.098 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.098	0.079 + 0.009*SL	0.085 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.563	0.548 + 0.008*SL	0.557 + 0.006*SL	0.577 + 0.004*SL
	t_{PHL}	0.671	0.655 + 0.008*SL	0.665 + 0.006*SL	0.686 + 0.005*SL
D to Y	t_R	0.115	0.095 + 0.010*SL	0.099 + 0.009*SL	0.091 + 0.009*SL
	t_F	0.098	0.079 + 0.010*SL	0.086 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.575	0.560 + 0.008*SL	0.569 + 0.006*SL	0.589 + 0.005*SL
	t_{PHL}	0.729	0.713 + 0.008*SL	0.723 + 0.006*SL	0.744 + 0.005*SL
E to Y	t_R	0.116	0.096 + 0.010*SL	0.100 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.099	0.079 + 0.010*SL	0.087 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.594	0.579 + 0.008*SL	0.588 + 0.006*SL	0.609 + 0.005*SL
	t_{PHL}	0.698	0.682 + 0.008*SL	0.692 + 0.006*SL	0.713 + 0.005*SL
F to Y	t_R	0.115	0.095 + 0.010*SL	0.100 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.100	0.080 + 0.010*SL	0.088 + 0.008*SL	0.086 + 0.008*SL
	t_{PLH}	0.605	0.589 + 0.008*SL	0.598 + 0.006*SL	0.619 + 0.004*SL
	t_{PHL}	0.755	0.739 + 0.008*SL	0.749 + 0.006*SL	0.770 + 0.005*SL
G to Y	t_R	0.117	0.096 + 0.010*SL	0.102 + 0.009*SL	0.095 + 0.009*SL
	t_F	0.102	0.084 + 0.009*SL	0.089 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.627	0.611 + 0.008*SL	0.620 + 0.006*SL	0.642 + 0.005*SL
	t_{PHL}	0.866	0.850 + 0.008*SL	0.860 + 0.006*SL	0.882 + 0.005*SL
H to Y	t_R	0.117	0.097 + 0.010*SL	0.102 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.103	0.083 + 0.010*SL	0.091 + 0.008*SL	0.089 + 0.008*SL
	t_{PLH}	0.638	0.622 + 0.008*SL	0.631 + 0.006*SL	0.652 + 0.005*SL
	t_{PHL}	0.931	0.914 + 0.008*SL	0.924 + 0.006*SL	0.946 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)															
OA31DH				*OA31*				*OA31D2*				*OA31D4*			
A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
0.6	0.6	0.6	0.6	0.8	0.9	0.9	0.9	1.8	1.8	1.7	1.7	0.9	0.9	0.9	0.9

Gate Count			
OA31DH	*OA31*	*OA31D2*	*OA31D4*
2.00	2.00	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA31DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.815	0.384 + 0.216*SL	0.370 + 0.219*SL	0.377 + 0.218*SL
	t_F	0.347	0.168 + 0.090*SL	0.153 + 0.093*SL	0.140 + 0.095*SL
	t_{PLH}	0.391	0.193 + 0.099*SL	0.194 + 0.099*SL	0.196 + 0.099*SL
	t_{PHL}	0.235	0.142 + 0.047*SL	0.142 + 0.046*SL	0.143 + 0.046*SL
B to Y	t_R	0.819	0.387 + 0.216*SL	0.379 + 0.218*SL	0.378 + 0.218*SL
	t_F	0.382	0.201 + 0.090*SL	0.188 + 0.093*SL	0.176 + 0.095*SL
	t_{PLH}	0.442	0.242 + 0.100*SL	0.245 + 0.099*SL	0.248 + 0.099*SL
	t_{PHL}	0.262	0.168 + 0.047*SL	0.170 + 0.047*SL	0.172 + 0.046*SL
C to Y	t_R	0.816	0.383 + 0.217*SL	0.378 + 0.218*SL	0.378 + 0.218*SL
	t_F	0.420	0.241 + 0.090*SL	0.228 + 0.093*SL	0.216 + 0.094*SL
	t_{PLH}	0.465	0.265 + 0.100*SL	0.269 + 0.099*SL	0.271 + 0.099*SL
	t_{PHL}	0.279	0.181 + 0.049*SL	0.187 + 0.047*SL	0.192 + 0.047*SL
D to Y	t_R	0.361	0.201 + 0.080*SL	0.189 + 0.083*SL	0.175 + 0.085*SL
	t_F	0.411	0.226 + 0.093*SL	0.222 + 0.094*SL	0.216 + 0.094*SL
	t_{PLH}	0.242	0.166 + 0.038*SL	0.167 + 0.038*SL	0.168 + 0.038*SL
	t_{PHL}	0.272	0.175 + 0.049*SL	0.181 + 0.047*SL	0.186 + 0.047*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

OA31

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.538	0.316 + 0.111*SL	0.304 + 0.114*SL	0.293 + 0.116*SL
	t_F	0.370	0.204 + 0.083*SL	0.194 + 0.086*SL	0.183 + 0.087*SL
	t_{PLH}	0.261	0.157 + 0.052*SL	0.157 + 0.052*SL	0.158 + 0.052*SL
	t_{PHL}	0.249	0.164 + 0.043*SL	0.165 + 0.042*SL	0.166 + 0.042*SL
B to Y	t_R	0.540	0.315 + 0.112*SL	0.308 + 0.114*SL	0.300 + 0.115*SL
	t_F	0.425	0.258 + 0.084*SL	0.249 + 0.086*SL	0.241 + 0.087*SL
	t_{PLH}	0.304	0.198 + 0.053*SL	0.200 + 0.052*SL	0.202 + 0.052*SL
	t_{PHL}	0.293	0.207 + 0.043*SL	0.209 + 0.042*SL	0.211 + 0.042*SL
C to Y	t_R	0.536	0.309 + 0.113*SL	0.303 + 0.115*SL	0.300 + 0.115*SL
	t_F	0.489	0.322 + 0.083*SL	0.314 + 0.085*SL	0.306 + 0.087*SL
	t_{PLH}	0.326	0.220 + 0.053*SL	0.222 + 0.052*SL	0.224 + 0.052*SL
	t_{PHL}	0.325	0.236 + 0.044*SL	0.242 + 0.043*SL	0.246 + 0.042*SL
D to Y	t_R	0.226	0.159 + 0.034*SL	0.151 + 0.036*SL	0.141 + 0.037*SL
	t_F	0.484	0.314 + 0.085*SL	0.310 + 0.086*SL	0.305 + 0.087*SL
	t_{PLH}	0.159	0.122 + 0.018*SL	0.127 + 0.017*SL	0.127 + 0.017*SL
	t_{PHL}	0.340	0.250 + 0.045*SL	0.256 + 0.043*SL	0.262 + 0.043*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA31D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.395	0.284 + 0.056*SL	0.276 + 0.058*SL	0.260 + 0.059*SL
	t_F	0.249	0.173 + 0.038*SL	0.166 + 0.040*SL	0.151 + 0.041*SL
	t_{PLH}	0.198	0.145 + 0.026*SL	0.144 + 0.027*SL	0.145 + 0.027*SL
	t_{PHL}	0.185	0.144 + 0.020*SL	0.145 + 0.020*SL	0.147 + 0.020*SL
B to Y	t_R	0.395	0.281 + 0.057*SL	0.277 + 0.058*SL	0.266 + 0.059*SL
	t_F	0.301	0.224 + 0.039*SL	0.218 + 0.040*SL	0.205 + 0.041*SL
	t_{PLH}	0.236	0.182 + 0.027*SL	0.183 + 0.027*SL	0.186 + 0.027*SL
	t_{PHL}	0.224	0.182 + 0.021*SL	0.184 + 0.020*SL	0.187 + 0.020*SL
C to Y	t_R	0.390	0.276 + 0.057*SL	0.272 + 0.058*SL	0.265 + 0.059*SL
	t_F	0.360	0.282 + 0.039*SL	0.276 + 0.040*SL	0.263 + 0.041*SL
	t_{PLH}	0.254	0.199 + 0.027*SL	0.201 + 0.027*SL	0.203 + 0.027*SL
	t_{PHL}	0.248	0.204 + 0.022*SL	0.208 + 0.021*SL	0.215 + 0.020*SL
D to Y	t_R	0.182	0.148 + 0.017*SL	0.145 + 0.018*SL	0.132 + 0.019*SL
	t_F	0.350	0.269 + 0.040*SL	0.268 + 0.041*SL	0.261 + 0.041*SL
	t_{PLH}	0.135	0.113 + 0.011*SL	0.121 + 0.009*SL	0.122 + 0.009*SL
	t_{PHL}	0.260	0.216 + 0.022*SL	0.220 + 0.021*SL	0.228 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

OA31D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	0.086 + 0.010*SL	0.090 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.090	0.073 + 0.009*SL	0.076 + 0.008*SL	0.078 + 0.008*SL
	t_{PLH}	0.471	0.456 + 0.008*SL	0.464 + 0.005*SL	0.483 + 0.004*SL
	t_{PHL}	0.440	0.425 + 0.008*SL	0.434 + 0.006*SL	0.454 + 0.004*SL
B to Y	t_R	0.106	0.085 + 0.010*SL	0.091 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.091	0.072 + 0.010*SL	0.079 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.513	0.498 + 0.008*SL	0.507 + 0.005*SL	0.525 + 0.004*SL
	t_{PHL}	0.492	0.477 + 0.008*SL	0.486 + 0.006*SL	0.506 + 0.005*SL
C to Y	t_R	0.106	0.086 + 0.010*SL	0.090 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.080 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.531	0.516 + 0.008*SL	0.525 + 0.005*SL	0.543 + 0.004*SL
	t_{PHL}	0.530	0.515 + 0.008*SL	0.524 + 0.006*SL	0.544 + 0.005*SL
D to Y	t_R	0.099	0.081 + 0.009*SL	0.081 + 0.009*SL	0.076 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.079 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.359	0.344 + 0.007*SL	0.352 + 0.005*SL	0.369 + 0.004*SL
	t_{PHL}	0.547	0.532 + 0.008*SL	0.541 + 0.006*SL	0.561 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OA311/OA311D2/OA311D4

3-OR into 3-NAND with 1X/2X/4X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	x	x	1
x	x	x	0	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)														
OA311					*OA311D2*					*OA311D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.9	0.9	0.9	1.0	1.0	0.9	0.9	0.9	1.0	1.0	0.9	0.9	1.0	1.0	1.0
Gate Count														
OA311					*OA311D2*					*OA311D4*				
2.00					3.00					3.67				

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA311

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.565	0.342 + 0.112*SL	0.330 + 0.115*SL	0.322 + 0.116*SL
	t_F	0.465	0.269 + 0.098*SL	0.259 + 0.101*SL	0.253 + 0.101*SL
	t_{PLH}	0.276	0.171 + 0.052*SL	0.171 + 0.052*SL	0.172 + 0.052*SL
	t_{PHL}	0.277	0.179 + 0.049*SL	0.181 + 0.048*SL	0.182 + 0.048*SL
B to Y	t_R	0.568	0.342 + 0.113*SL	0.336 + 0.114*SL	0.330 + 0.115*SL
	t_F	0.534	0.336 + 0.099*SL	0.328 + 0.101*SL	0.324 + 0.101*SL
	t_{PLH}	0.321	0.215 + 0.053*SL	0.217 + 0.052*SL	0.219 + 0.052*SL
	t_{PHL}	0.330	0.232 + 0.049*SL	0.234 + 0.048*SL	0.236 + 0.048*SL
C to Y	t_R	0.565	0.338 + 0.113*SL	0.332 + 0.115*SL	0.330 + 0.115*SL
	t_F	0.605	0.408 + 0.098*SL	0.400 + 0.100*SL	0.396 + 0.101*SL
	t_{PLH}	0.339	0.233 + 0.053*SL	0.236 + 0.052*SL	0.238 + 0.052*SL
	t_{PHL}	0.366	0.265 + 0.050*SL	0.271 + 0.049*SL	0.275 + 0.048*SL
D to Y	t_R	0.237	0.169 + 0.034*SL	0.161 + 0.036*SL	0.152 + 0.037*SL
	t_F	0.603	0.405 + 0.099*SL	0.399 + 0.100*SL	0.397 + 0.101*SL
	t_{PLH}	0.169	0.134 + 0.018*SL	0.137 + 0.017*SL	0.137 + 0.017*SL
	t_{PHL}	0.403	0.301 + 0.051*SL	0.308 + 0.049*SL	0.314 + 0.049*SL
E to Y	t_R	0.251	0.181 + 0.035*SL	0.174 + 0.037*SL	0.165 + 0.038*SL
	t_F	0.603	0.404 + 0.099*SL	0.399 + 0.100*SL	0.397 + 0.101*SL
	t_{PLH}	0.178	0.142 + 0.018*SL	0.143 + 0.018*SL	0.144 + 0.017*SL
	t_{PHL}	0.402	0.300 + 0.051*SL	0.306 + 0.049*SL	0.312 + 0.049*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA311D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.116	0.080 + 0.018*SL	0.080 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.446	0.421 + 0.012*SL	0.432 + 0.010*SL	0.442 + 0.009*SL
	t_{PHL}	0.462	0.436 + 0.013*SL	0.448 + 0.010*SL	0.463 + 0.009*SL
B to Y	t_R	0.116	0.079 + 0.018*SL	0.081 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.107	0.074 + 0.017*SL	0.078 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.491	0.466 + 0.013*SL	0.477 + 0.010*SL	0.487 + 0.009*SL
	t_{PHL}	0.525	0.498 + 0.013*SL	0.511 + 0.010*SL	0.526 + 0.009*SL
C to Y	t_R	0.116	0.079 + 0.018*SL	0.081 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.109	0.076 + 0.017*SL	0.080 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.509	0.484 + 0.013*SL	0.496 + 0.010*SL	0.506 + 0.009*SL
	t_{PHL}	0.571	0.544 + 0.013*SL	0.557 + 0.010*SL	0.572 + 0.009*SL
D to Y	t_R	0.107	0.070 + 0.019*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.109	0.076 + 0.017*SL	0.080 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.342	0.318 + 0.012*SL	0.328 + 0.010*SL	0.336 + 0.009*SL
	t_{PHL}	0.607	0.580 + 0.013*SL	0.593 + 0.010*SL	0.609 + 0.009*SL
E to Y	t_R	0.107	0.071 + 0.018*SL	0.069 + 0.019*SL	0.061 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.080 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.352	0.328 + 0.012*SL	0.338 + 0.010*SL	0.346 + 0.009*SL
	t_{PHL}	0.606	0.579 + 0.013*SL	0.592 + 0.010*SL	0.607 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA311D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.105	0.085 + 0.010*SL	0.089 + 0.009*SL	0.082 + 0.009*SL
	t_F	0.093	0.076 + 0.009*SL	0.079 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.487	0.472 + 0.008*SL	0.480 + 0.005*SL	0.498 + 0.004*SL
	t_{PHL}	0.483	0.467 + 0.008*SL	0.476 + 0.006*SL	0.496 + 0.005*SL
B to Y	t_R	0.105	0.084 + 0.010*SL	0.090 + 0.009*SL	0.080 + 0.009*SL
	t_F	0.094	0.075 + 0.009*SL	0.080 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.534	0.519 + 0.008*SL	0.527 + 0.005*SL	0.545 + 0.004*SL
	t_{PHL}	0.547	0.532 + 0.008*SL	0.541 + 0.006*SL	0.561 + 0.005*SL
C to Y	t_R	0.105	0.086 + 0.010*SL	0.089 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.097	0.078 + 0.009*SL	0.084 + 0.008*SL	0.083 + 0.008*SL
	t_{PLH}	0.550	0.535 + 0.008*SL	0.544 + 0.005*SL	0.562 + 0.004*SL
	t_{PHL}	0.591	0.576 + 0.008*SL	0.585 + 0.006*SL	0.606 + 0.005*SL
D to Y	t_R	0.097	0.078 + 0.010*SL	0.080 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.082 + 0.008*SL	0.084 + 0.008*SL
	t_{PLH}	0.360	0.345 + 0.007*SL	0.353 + 0.005*SL	0.369 + 0.004*SL
	t_{PHL}	0.628	0.612 + 0.008*SL	0.621 + 0.006*SL	0.642 + 0.005*SL
E to Y	t_R	0.098	0.078 + 0.010*SL	0.083 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.096	0.078 + 0.009*SL	0.082 + 0.008*SL	0.084 + 0.008*SL
	t_{PLH}	0.371	0.356 + 0.007*SL	0.364 + 0.005*SL	0.380 + 0.004*SL
	t_{PHL}	0.626	0.610 + 0.008*SL	0.619 + 0.006*SL	0.640 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

OA3111/OA3111D2

3-OR into 4-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	x	x	1
x	x	x	x	0	x	1
x	x	x	x	x	0	1
Other States						0

Cell Data

Input Load (SL)												Gate Count	
OA3111						*OA3111D2*						*OA3111*	*OA3111D2*
A	B	C	D	E	F	A	B	C	D	E	F		
0.9	1.0	1.0	1.0	1.0	1.0	0.9	1.0	1.0	1.0	1.0	1.0	2.33	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA3111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.653	0.427 + 0.113*SL	0.418 + 0.115*SL	0.414 + 0.116*SL
	t_F	0.614	0.393 + 0.111*SL	0.386 + 0.112*SL	0.386 + 0.112*SL
	t_{PLH}	0.319	0.214 + 0.053*SL	0.215 + 0.052*SL	0.216 + 0.052*SL
	t_{PHL}	0.329	0.222 + 0.053*SL	0.223 + 0.053*SL	0.225 + 0.053*SL
B to Y	t_R	0.656	0.429 + 0.113*SL	0.423 + 0.115*SL	0.419 + 0.115*SL
	t_F	0.694	0.469 + 0.113*SL	0.463 + 0.114*SL	0.464 + 0.114*SL
	t_{PLH}	0.359	0.253 + 0.053*SL	0.255 + 0.052*SL	0.257 + 0.052*SL
	t_{PHL}	0.390	0.282 + 0.054*SL	0.283 + 0.054*SL	0.285 + 0.054*SL
C to Y	t_R	0.653	0.425 + 0.114*SL	0.421 + 0.115*SL	0.419 + 0.115*SL
	t_F	0.765	0.543 + 0.111*SL	0.536 + 0.113*SL	0.538 + 0.112*SL
	t_{PLH}	0.377	0.271 + 0.053*SL	0.274 + 0.053*SL	0.276 + 0.052*SL
	t_{PHL}	0.429	0.319 + 0.055*SL	0.323 + 0.054*SL	0.326 + 0.053*SL
D to Y	t_R	0.269	0.197 + 0.036*SL	0.192 + 0.037*SL	0.184 + 0.038*SL
	t_F	0.768	0.546 + 0.111*SL	0.542 + 0.112*SL	0.541 + 0.112*SL
	t_{PLH}	0.190	0.155 + 0.018*SL	0.156 + 0.017*SL	0.156 + 0.017*SL
	t_{PHL}	0.483	0.372 + 0.055*SL	0.377 + 0.054*SL	0.381 + 0.054*SL
E to Y	t_R	0.281	0.210 + 0.036*SL	0.204 + 0.037*SL	0.197 + 0.038*SL
	t_F	0.768	0.545 + 0.111*SL	0.542 + 0.112*SL	0.541 + 0.112*SL
	t_{PLH}	0.197	0.162 + 0.018*SL	0.163 + 0.018*SL	0.163 + 0.017*SL
	t_{PHL}	0.493	0.383 + 0.055*SL	0.387 + 0.054*SL	0.392 + 0.054*SL
F to Y	t_R	0.295	0.223 + 0.036*SL	0.219 + 0.037*SL	0.210 + 0.038*SL
	t_F	0.767	0.544 + 0.112*SL	0.542 + 0.112*SL	0.541 + 0.112*SL
	t_{PLH}	0.203	0.167 + 0.018*SL	0.168 + 0.018*SL	0.169 + 0.018*SL
	t_{PHL}	0.500	0.389 + 0.055*SL	0.394 + 0.054*SL	0.399 + 0.054*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA3111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	0.083 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.112	0.078 + 0.017*SL	0.085 + 0.015*SL	0.081 + 0.016*SL
	t_{PLH}	0.511	0.486 + 0.013*SL	0.498 + 0.010*SL	0.509 + 0.009*SL
	t_{PHL}	0.544	0.517 + 0.013*SL	0.530 + 0.010*SL	0.546 + 0.009*SL
B to Y	t_R	0.120	0.084 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.114	0.080 + 0.017*SL	0.085 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.551	0.525 + 0.013*SL	0.537 + 0.010*SL	0.548 + 0.009*SL
	t_{PHL}	0.614	0.587 + 0.014*SL	0.600 + 0.010*SL	0.617 + 0.009*SL
C to Y	t_R	0.120	0.084 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.116	0.083 + 0.017*SL	0.089 + 0.015*SL	0.083 + 0.016*SL
	t_{PLH}	0.568	0.543 + 0.013*SL	0.555 + 0.010*SL	0.566 + 0.009*SL
	t_{PHL}	0.661	0.634 + 0.014*SL	0.647 + 0.010*SL	0.664 + 0.009*SL
D to Y	t_R	0.109	0.073 + 0.018*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.115	0.081 + 0.017*SL	0.087 + 0.015*SL	0.084 + 0.016*SL
	t_{PLH}	0.374	0.350 + 0.012*SL	0.360 + 0.010*SL	0.369 + 0.009*SL
	t_{PHL}	0.715	0.687 + 0.014*SL	0.701 + 0.010*SL	0.718 + 0.009*SL
E to Y	t_R	0.110	0.073 + 0.018*SL	0.074 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.115	0.081 + 0.017*SL	0.088 + 0.015*SL	0.084 + 0.016*SL
	t_{PLH}	0.384	0.360 + 0.012*SL	0.370 + 0.010*SL	0.378 + 0.009*SL
	t_{PHL}	0.727	0.700 + 0.014*SL	0.713 + 0.010*SL	0.730 + 0.009*SL
F to Y	t_R	0.110	0.074 + 0.018*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.115	0.082 + 0.017*SL	0.086 + 0.016*SL	0.084 + 0.016*SL
	t_{PLH}	0.392	0.368 + 0.012*SL	0.378 + 0.010*SL	0.387 + 0.009*SL
	t_{PHL}	0.733	0.706 + 0.014*SL	0.719 + 0.010*SL	0.736 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	0	x	x	1
x	x	x	0	0	1
Other States					0

Cell Data

Input Load (SL)														
OA32					*OA32D2*					*OA32D4*				
A	B	C	D	E	A	B	C	D	E	A	B	C	D	E
0.8	0.9	0.9	0.8	0.9	0.8	0.9	0.9	0.9	0.9	0.8	0.9	0.9	0.8	0.9

Gate Count		
OA32	*OA32D2*	*OA32D4*
2.33	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA32

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.660	0.437 + 0.111*SL	0.424 + 0.115*SL	0.412 + 0.116*SL
	t_F	0.473	0.280 + 0.096*SL	0.272 + 0.098*SL	0.269 + 0.099*SL
	t_{PLH}	0.269	0.163 + 0.053*SL	0.163 + 0.053*SL	0.165 + 0.053*SL
	t_{PHL}	0.325	0.227 + 0.049*SL	0.230 + 0.048*SL	0.233 + 0.048*SL
B to Y	t_R	0.661	0.436 + 0.112*SL	0.428 + 0.115*SL	0.419 + 0.116*SL
	t_F	0.535	0.341 + 0.097*SL	0.335 + 0.099*SL	0.334 + 0.099*SL
	t_{PLH}	0.312	0.204 + 0.054*SL	0.206 + 0.054*SL	0.209 + 0.053*SL
	t_{PHL}	0.376	0.278 + 0.049*SL	0.281 + 0.048*SL	0.284 + 0.048*SL
C to Y	t_R	0.657	0.430 + 0.113*SL	0.423 + 0.115*SL	0.418 + 0.116*SL
	t_F	0.601	0.407 + 0.097*SL	0.402 + 0.098*SL	0.402 + 0.098*SL
	t_{PLH}	0.331	0.223 + 0.054*SL	0.225 + 0.054*SL	0.228 + 0.053*SL
	t_{PHL}	0.413	0.314 + 0.050*SL	0.318 + 0.049*SL	0.323 + 0.048*SL
D to Y	t_R	0.407	0.262 + 0.073*SL	0.253 + 0.075*SL	0.241 + 0.076*SL
	t_F	0.539	0.344 + 0.097*SL	0.340 + 0.098*SL	0.340 + 0.099*SL
	t_{PLH}	0.245	0.176 + 0.035*SL	0.177 + 0.035*SL	0.178 + 0.034*SL
	t_{PHL}	0.392	0.290 + 0.051*SL	0.297 + 0.049*SL	0.303 + 0.048*SL
E to Y	t_R	0.400	0.251 + 0.074*SL	0.246 + 0.076*SL	0.240 + 0.076*SL
	t_F	0.599	0.403 + 0.098*SL	0.401 + 0.098*SL	0.401 + 0.098*SL
	t_{PLH}	0.256	0.186 + 0.035*SL	0.188 + 0.035*SL	0.189 + 0.034*SL
	t_{PHL}	0.443	0.342 + 0.050*SL	0.348 + 0.049*SL	0.353 + 0.048*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA32D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.121	0.085 + 0.018*SL	0.086 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.106	0.074 + 0.016*SL	0.078 + 0.015*SL	0.074 + 0.016*SL
	t_{PLH}	0.465	0.439 + 0.013*SL	0.451 + 0.010*SL	0.462 + 0.009*SL
	t_{PHL}	0.510	0.484 + 0.013*SL	0.496 + 0.010*SL	0.511 + 0.009*SL
B to Y	t_R	0.122	0.086 + 0.018*SL	0.086 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.107	0.074 + 0.016*SL	0.078 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.508	0.483 + 0.013*SL	0.494 + 0.010*SL	0.506 + 0.009*SL
	t_{PHL}	0.571	0.545 + 0.013*SL	0.558 + 0.010*SL	0.572 + 0.009*SL
C to Y	t_R	0.121	0.085 + 0.018*SL	0.086 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.108	0.075 + 0.017*SL	0.080 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.525	0.500 + 0.013*SL	0.512 + 0.010*SL	0.523 + 0.009*SL
	t_{PHL}	0.616	0.590 + 0.013*SL	0.602 + 0.010*SL	0.617 + 0.009*SL
D to Y	t_R	0.121	0.085 + 0.018*SL	0.085 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.075 + 0.016*SL	0.080 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.439	0.413 + 0.013*SL	0.425 + 0.010*SL	0.436 + 0.009*SL
	t_{PHL}	0.586	0.560 + 0.013*SL	0.572 + 0.010*SL	0.587 + 0.009*SL
E to Y	t_R	0.121	0.084 + 0.018*SL	0.086 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.075 + 0.017*SL	0.080 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.449	0.424 + 0.013*SL	0.436 + 0.010*SL	0.447 + 0.009*SL
	t_{PHL}	0.644	0.618 + 0.013*SL	0.630 + 0.010*SL	0.645 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA32D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.109	0.088 + 0.010*SL	0.094 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.092	0.073 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	0.498	0.482 + 0.008*SL	0.491 + 0.005*SL	0.510 + 0.004*SL
	t_{PHL}	0.526	0.510 + 0.008*SL	0.519 + 0.006*SL	0.539 + 0.005*SL
B to Y	t_R	0.109	0.090 + 0.010*SL	0.093 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.079 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	0.542	0.526 + 0.008*SL	0.535 + 0.005*SL	0.554 + 0.004*SL
	t_{PHL}	0.587	0.571 + 0.008*SL	0.580 + 0.006*SL	0.600 + 0.005*SL
C to Y	t_R	0.109	0.089 + 0.010*SL	0.094 + 0.009*SL	0.086 + 0.009*SL
	t_F	0.095	0.076 + 0.010*SL	0.082 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.559	0.543 + 0.008*SL	0.552 + 0.005*SL	0.571 + 0.004*SL
	t_{PHL}	0.631	0.616 + 0.008*SL	0.625 + 0.006*SL	0.645 + 0.005*SL
D to Y	t_R	0.108	0.089 + 0.010*SL	0.091 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.080 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.464	0.449 + 0.008*SL	0.458 + 0.005*SL	0.476 + 0.004*SL
	t_{PHL}	0.602	0.586 + 0.008*SL	0.595 + 0.006*SL	0.616 + 0.005*SL
E to Y	t_R	0.108	0.088 + 0.010*SL	0.093 + 0.009*SL	0.084 + 0.009*SL
	t_F	0.096	0.077 + 0.009*SL	0.083 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	0.475	0.459 + 0.008*SL	0.468 + 0.005*SL	0.487 + 0.004*SL
	t_{PHL}	0.659	0.644 + 0.008*SL	0.653 + 0.006*SL	0.673 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	0	x	1
x	x	x	x	x	0	1
Other States						0

Cell Data

Input Load (SL)																	
OA321						*OA321D2*						*OA321D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.9	0.9	0.90	0.9	0.9	0.9	0.9	0.9	0.90	0.9	0.9	0.9	0.9	0.9	0.90	0.9	0.9	0.9

Gate Count		
OA321	*OA321D2*	*OA321D4*
3.00	3.67	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA321

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.705	0.480 + 0.112*SL	0.468 + 0.115*SL	0.459 + 0.116*SL
	t_F	0.602	0.380 + 0.111*SL	0.373 + 0.113*SL	0.374 + 0.113*SL
	t_{PLH}	0.292	0.185 + 0.054*SL	0.186 + 0.054*SL	0.188 + 0.053*SL
	t_{PHL}	0.364	0.255 + 0.055*SL	0.257 + 0.054*SL	0.260 + 0.054*SL
B to Y	t_R	0.707	0.481 + 0.113*SL	0.473 + 0.115*SL	0.466 + 0.116*SL
	t_F	0.674	0.450 + 0.112*SL	0.445 + 0.113*SL	0.449 + 0.113*SL
	t_{PLH}	0.336	0.227 + 0.054*SL	0.229 + 0.054*SL	0.232 + 0.053*SL
	t_{PHL}	0.423	0.314 + 0.055*SL	0.316 + 0.054*SL	0.319 + 0.054*SL
C to Y	t_R	0.704	0.476 + 0.114*SL	0.469 + 0.115*SL	0.466 + 0.116*SL
	t_F	0.751	0.527 + 0.112*SL	0.523 + 0.113*SL	0.526 + 0.113*SL
	t_{PLH}	0.354	0.245 + 0.054*SL	0.248 + 0.054*SL	0.251 + 0.053*SL
	t_{PHL}	0.468	0.356 + 0.056*SL	0.361 + 0.055*SL	0.365 + 0.054*SL
D to Y	t_R	0.447	0.300 + 0.073*SL	0.293 + 0.075*SL	0.282 + 0.077*SL
	t_F	0.680	0.458 + 0.111*SL	0.455 + 0.112*SL	0.454 + 0.112*SL
	t_{PLH}	0.272	0.202 + 0.035*SL	0.203 + 0.035*SL	0.204 + 0.034*SL
	t_{PHL}	0.465	0.352 + 0.056*SL	0.358 + 0.055*SL	0.365 + 0.054*SL
E to Y	t_R	0.441	0.291 + 0.075*SL	0.288 + 0.076*SL	0.283 + 0.077*SL
	t_F	0.753	0.529 + 0.112*SL	0.528 + 0.112*SL	0.527 + 0.112*SL
	t_{PLH}	0.283	0.213 + 0.035*SL	0.214 + 0.035*SL	0.215 + 0.034*SL
	t_{PHL}	0.523	0.412 + 0.056*SL	0.416 + 0.055*SL	0.421 + 0.054*SL
F to Y	t_R	0.359	0.294 + 0.033*SL	0.285 + 0.035*SL	0.272 + 0.036*SL
	t_F	0.753	0.529 + 0.112*SL	0.528 + 0.112*SL	0.527 + 0.112*SL
	t_{PLH}	0.186	0.151 + 0.018*SL	0.152 + 0.017*SL	0.153 + 0.017*SL
	t_{PHL}	0.539	0.427 + 0.056*SL	0.432 + 0.055*SL	0.438 + 0.054*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA321D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.120	0.084 + 0.018*SL	0.084 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.107	0.074 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.477	0.452 + 0.013*SL	0.464 + 0.010*SL	0.475 + 0.009*SL
	t_{PHL}	0.551	0.525 + 0.013*SL	0.537 + 0.010*SL	0.551 + 0.009*SL
B to Y	t_R	0.119	0.084 + 0.018*SL	0.084 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.109	0.074 + 0.017*SL	0.080 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.520	0.495 + 0.013*SL	0.507 + 0.010*SL	0.517 + 0.009*SL
	t_{PHL}	0.619	0.593 + 0.013*SL	0.605 + 0.010*SL	0.619 + 0.009*SL
C to Y	t_R	0.120	0.084 + 0.018*SL	0.084 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.080 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.538	0.513 + 0.013*SL	0.525 + 0.010*SL	0.535 + 0.009*SL
	t_{PHL}	0.673	0.646 + 0.013*SL	0.659 + 0.010*SL	0.673 + 0.009*SL
D to Y	t_R	0.113	0.077 + 0.018*SL	0.078 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.081 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.455	0.431 + 0.012*SL	0.442 + 0.009*SL	0.451 + 0.009*SL
	t_{PHL}	0.657	0.631 + 0.013*SL	0.643 + 0.010*SL	0.657 + 0.009*SL
E to Y	t_R	0.113	0.078 + 0.018*SL	0.077 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.110	0.077 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.467	0.442 + 0.012*SL	0.453 + 0.009*SL	0.462 + 0.009*SL
	t_{PHL}	0.728	0.701 + 0.013*SL	0.713 + 0.010*SL	0.728 + 0.009*SL
F to Y	t_R	0.108	0.072 + 0.018*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.364	0.341 + 0.012*SL	0.350 + 0.009*SL	0.358 + 0.009*SL
	t_{PHL}	0.745	0.718 + 0.013*SL	0.730 + 0.010*SL	0.745 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA321D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.112	0.093 + 0.010*SL	0.096 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.099	0.081 + 0.009*SL	0.085 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	0.530	0.515 + 0.008*SL	0.524 + 0.006*SL	0.544 + 0.004*SL
	t_{PHL}	0.584	0.568 + 0.008*SL	0.577 + 0.006*SL	0.599 + 0.005*SL
B to Y	t_R	0.113	0.093 + 0.010*SL	0.097 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.100	0.081 + 0.009*SL	0.087 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	0.573	0.557 + 0.008*SL	0.566 + 0.006*SL	0.586 + 0.004*SL
	t_{PHL}	0.652	0.636 + 0.008*SL	0.645 + 0.006*SL	0.667 + 0.005*SL
C to Y	t_R	0.112	0.093 + 0.010*SL	0.096 + 0.009*SL	0.090 + 0.009*SL
	t_F	0.101	0.083 + 0.009*SL	0.087 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.591	0.575 + 0.008*SL	0.585 + 0.006*SL	0.604 + 0.004*SL
	t_{PHL}	0.706	0.690 + 0.008*SL	0.699 + 0.006*SL	0.721 + 0.005*SL
D to Y	t_R	0.110	0.090 + 0.010*SL	0.096 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.100	0.081 + 0.009*SL	0.087 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.497	0.482 + 0.008*SL	0.491 + 0.005*SL	0.510 + 0.004*SL
	t_{PHL}	0.691	0.675 + 0.008*SL	0.684 + 0.006*SL	0.706 + 0.005*SL
E to Y	t_R	0.110	0.091 + 0.010*SL	0.094 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.102	0.083 + 0.010*SL	0.089 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.509	0.494 + 0.008*SL	0.503 + 0.005*SL	0.522 + 0.004*SL
	t_{PHL}	0.761	0.745 + 0.008*SL	0.754 + 0.006*SL	0.776 + 0.005*SL
F to Y	t_R	0.102	0.082 + 0.010*SL	0.086 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.102	0.082 + 0.010*SL	0.090 + 0.008*SL	0.089 + 0.008*SL
	t_{PLH}	0.395	0.380 + 0.007*SL	0.388 + 0.005*SL	0.405 + 0.004*SL
	t_{PHL}	0.778	0.762 + 0.008*SL	0.771 + 0.006*SL	0.793 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	x	x	x	x	1
x	x	x	0	0	x	x	1
x	x	x	x	x	0	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA322							*OA322*
A	B	C	D	E	F	G	
0.8	0.9	0.9	0.9	1.1	0.9	0.9	3.00
OA322D2							*OA322D2*
A	B	C	D	E	F	G	
0.9	0.9	0.9	0.9	1.1	0.9	0.9	4.00
OA322D4							*OA322D4*
A	B	C	D	E	F	G	
0.8	0.9	0.9	0.9	1.1	0.9	0.9	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA322

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.822	0.599 + 0.111*SL	0.587 + 0.114*SL	0.577 + 0.116*SL
	t_F	0.743	0.492 + 0.126*SL	0.490 + 0.126*SL	0.494 + 0.126*SL
	t_{PLH}	0.298	0.188 + 0.055*SL	0.191 + 0.054*SL	0.195 + 0.054*SL
	t_{PHL}	0.471	0.349 + 0.061*SL	0.352 + 0.060*SL	0.355 + 0.060*SL
B to Y	t_R	0.824	0.599 + 0.112*SL	0.591 + 0.114*SL	0.584 + 0.115*SL
	t_F	0.828	0.575 + 0.127*SL	0.576 + 0.126*SL	0.579 + 0.126*SL
	t_{PLH}	0.344	0.234 + 0.055*SL	0.236 + 0.054*SL	0.242 + 0.054*SL
	t_{PHL}	0.540	0.418 + 0.061*SL	0.421 + 0.060*SL	0.424 + 0.060*SL
C to Y	t_R	0.820	0.595 + 0.113*SL	0.588 + 0.115*SL	0.584 + 0.115*SL
	t_F	0.910	0.657 + 0.126*SL	0.660 + 0.126*SL	0.662 + 0.125*SL
	t_{PLH}	0.361	0.251 + 0.055*SL	0.254 + 0.054*SL	0.259 + 0.054*SL
	t_{PHL}	0.591	0.467 + 0.062*SL	0.471 + 0.061*SL	0.475 + 0.060*SL
D to Y	t_R	0.610	0.468 + 0.071*SL	0.455 + 0.074*SL	0.440 + 0.076*SL
	t_F	0.836	0.584 + 0.126*SL	0.584 + 0.126*SL	0.583 + 0.126*SL
	t_{PLH}	0.271	0.200 + 0.036*SL	0.201 + 0.036*SL	0.202 + 0.035*SL
	t_{PHL}	0.589	0.464 + 0.063*SL	0.469 + 0.061*SL	0.475 + 0.061*SL
E to Y	t_R	0.603	0.457 + 0.073*SL	0.449 + 0.075*SL	0.439 + 0.076*SL
	t_F	0.912	0.661 + 0.126*SL	0.661 + 0.125*SL	0.662 + 0.125*SL
	t_{PLH}	0.287	0.216 + 0.035*SL	0.217 + 0.035*SL	0.218 + 0.035*SL
	t_{PHL}	0.656	0.532 + 0.062*SL	0.536 + 0.061*SL	0.541 + 0.060*SL
F to Y	t_R	0.651	0.510 + 0.071*SL	0.497 + 0.074*SL	0.480 + 0.076*SL
	t_F	0.836	0.585 + 0.125*SL	0.585 + 0.126*SL	0.584 + 0.126*SL
	t_{PLH}	0.293	0.221 + 0.036*SL	0.223 + 0.035*SL	0.225 + 0.035*SL
	t_{PHL}	0.608	0.482 + 0.063*SL	0.488 + 0.061*SL	0.494 + 0.061*SL
G to Y	t_R	0.644	0.500 + 0.072*SL	0.491 + 0.074*SL	0.481 + 0.076*SL
	t_F	0.912	0.661 + 0.126*SL	0.662 + 0.125*SL	0.662 + 0.125*SL
	t_{PLH}	0.303	0.232 + 0.036*SL	0.234 + 0.035*SL	0.236 + 0.035*SL
	t_{PHL}	0.670	0.546 + 0.062*SL	0.550 + 0.061*SL	0.555 + 0.060*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA322D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.127	0.091 + 0.018*SL	0.092 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.084 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.519	0.492 + 0.013*SL	0.506 + 0.010*SL	0.518 + 0.009*SL
	t_{PHL}	0.683	0.656 + 0.014*SL	0.669 + 0.011*SL	0.685 + 0.009*SL
B to Y	t_R	0.127	0.091 + 0.018*SL	0.092 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.114	0.079 + 0.017*SL	0.086 + 0.016*SL	0.080 + 0.016*SL
	t_{PLH}	0.563	0.537 + 0.013*SL	0.550 + 0.010*SL	0.563 + 0.009*SL
	t_{PHL}	0.762	0.735 + 0.014*SL	0.748 + 0.011*SL	0.764 + 0.009*SL
C to Y	t_R	0.127	0.091 + 0.018*SL	0.092 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.116	0.081 + 0.017*SL	0.088 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.581	0.554 + 0.013*SL	0.568 + 0.010*SL	0.580 + 0.009*SL
	t_{PHL}	0.822	0.794 + 0.014*SL	0.808 + 0.011*SL	0.824 + 0.009*SL
D to Y	t_R	0.119	0.083 + 0.018*SL	0.082 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.114	0.079 + 0.017*SL	0.085 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.485	0.460 + 0.013*SL	0.472 + 0.010*SL	0.483 + 0.009*SL
	t_{PHL}	0.807	0.779 + 0.014*SL	0.793 + 0.011*SL	0.809 + 0.009*SL
E to Y	t_R	0.118	0.082 + 0.018*SL	0.082 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.115	0.081 + 0.017*SL	0.086 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.503	0.478 + 0.013*SL	0.490 + 0.010*SL	0.501 + 0.009*SL
	t_{PHL}	0.891	0.863 + 0.014*SL	0.876 + 0.011*SL	0.893 + 0.009*SL
F to Y	t_R	0.120	0.084 + 0.018*SL	0.085 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.114	0.079 + 0.018*SL	0.085 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.510	0.485 + 0.013*SL	0.497 + 0.010*SL	0.508 + 0.009*SL
	t_{PHL}	0.826	0.798 + 0.014*SL	0.812 + 0.011*SL	0.828 + 0.009*SL
G to Y	t_R	0.119	0.083 + 0.018*SL	0.083 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.116	0.081 + 0.017*SL	0.088 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.522	0.496 + 0.013*SL	0.509 + 0.010*SL	0.520 + 0.009*SL
	t_{PHL}	0.900	0.872 + 0.014*SL	0.886 + 0.011*SL	0.902 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA322D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.117	0.097 + 0.010*SL	0.102 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.100	0.082 + 0.009*SL	0.086 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.571	0.555 + 0.008*SL	0.565 + 0.006*SL	0.587 + 0.005*SL
	t_{PHL}	0.706	0.690 + 0.008*SL	0.700 + 0.006*SL	0.721 + 0.005*SL
B to Y	t_R	0.118	0.099 + 0.010*SL	0.103 + 0.009*SL	0.096 + 0.009*SL
	t_F	0.102	0.084 + 0.009*SL	0.089 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.616	0.600 + 0.008*SL	0.609 + 0.006*SL	0.631 + 0.005*SL
	t_{PHL}	0.785	0.769 + 0.008*SL	0.778 + 0.006*SL	0.800 + 0.005*SL
C to Y	t_R	0.118	0.098 + 0.010*SL	0.102 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.104	0.085 + 0.009*SL	0.091 + 0.008*SL	0.092 + 0.008*SL
	t_{PLH}	0.633	0.617 + 0.008*SL	0.627 + 0.006*SL	0.648 + 0.005*SL
	t_{PHL}	0.845	0.828 + 0.008*SL	0.838 + 0.006*SL	0.860 + 0.005*SL
D to Y	t_R	0.114	0.094 + 0.010*SL	0.099 + 0.009*SL	0.092 + 0.009*SL
	t_F	0.101	0.083 + 0.009*SL	0.087 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.529	0.513 + 0.008*SL	0.522 + 0.006*SL	0.543 + 0.005*SL
	t_{PHL}	0.829	0.813 + 0.008*SL	0.822 + 0.006*SL	0.844 + 0.005*SL
E to Y	t_R	0.115	0.094 + 0.010*SL	0.100 + 0.009*SL	0.093 + 0.009*SL
	t_F	0.104	0.086 + 0.009*SL	0.091 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.547	0.532 + 0.008*SL	0.541 + 0.006*SL	0.562 + 0.005*SL
	t_{PHL}	0.913	0.897 + 0.008*SL	0.906 + 0.006*SL	0.929 + 0.005*SL
F to Y	t_R	0.115	0.095 + 0.010*SL	0.100 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.101	0.083 + 0.009*SL	0.087 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.550	0.534 + 0.008*SL	0.544 + 0.006*SL	0.565 + 0.005*SL
	t_{PHL}	0.849	0.833 + 0.008*SL	0.842 + 0.006*SL	0.864 + 0.005*SL
G to Y	t_R	0.115	0.095 + 0.010*SL	0.100 + 0.009*SL	0.094 + 0.009*SL
	t_F	0.104	0.085 + 0.010*SL	0.092 + 0.008*SL	0.092 + 0.008*SL
	t_{PLH}	0.562	0.546 + 0.008*SL	0.556 + 0.006*SL	0.577 + 0.005*SL
	t_{PHL}	0.922	0.906 + 0.008*SL	0.916 + 0.006*SL	0.938 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
0	0	0	x	x	x	1
x	x	x	0	0	0	1
Other States						0

Cell Data

Input Load (SL)																	
OA33						*OA33D2*						*OA33D4*					
A	B	C	D	E	F	A	B	C	D	E	F	A	B	C	D	E	F
0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9	0.8	0.8	0.9

Gate Count		
OA33	*OA33D2*	*OA33D4*
2.33	3.33	4.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA33

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.671	0.450 + 0.111*SL	0.437 + 0.114*SL	0.424 + 0.115*SL
	t_F	0.645	0.413 + 0.116*SL	0.409 + 0.117*SL	0.411 + 0.117*SL
	t_{PLH}	0.270	0.164 + 0.053*SL	0.164 + 0.053*SL	0.166 + 0.053*SL
	t_{PHL}	0.436	0.316 + 0.060*SL	0.323 + 0.058*SL	0.329 + 0.057*SL
B to Y	t_R	0.672	0.448 + 0.112*SL	0.440 + 0.114*SL	0.432 + 0.115*SL
	t_F	0.721	0.487 + 0.117*SL	0.487 + 0.117*SL	0.489 + 0.117*SL
	t_{PLH}	0.315	0.208 + 0.054*SL	0.210 + 0.053*SL	0.212 + 0.053*SL
	t_{PHL}	0.502	0.384 + 0.059*SL	0.389 + 0.058*SL	0.395 + 0.057*SL
C to Y	t_R	0.668	0.443 + 0.113*SL	0.436 + 0.114*SL	0.431 + 0.115*SL
	t_F	0.796	0.562 + 0.117*SL	0.563 + 0.117*SL	0.565 + 0.116*SL
	t_{PLH}	0.333	0.225 + 0.054*SL	0.227 + 0.053*SL	0.229 + 0.053*SL
	t_{PHL}	0.550	0.430 + 0.060*SL	0.437 + 0.058*SL	0.443 + 0.057*SL
D to Y	t_R	0.740	0.515 + 0.113*SL	0.504 + 0.115*SL	0.495 + 0.116*SL
	t_F	0.645	0.412 + 0.116*SL	0.411 + 0.117*SL	0.410 + 0.117*SL
	t_{PLH}	0.323	0.216 + 0.054*SL	0.217 + 0.054*SL	0.219 + 0.053*SL
	t_{PHL}	0.465	0.345 + 0.060*SL	0.352 + 0.058*SL	0.359 + 0.057*SL
E to Y	t_R	0.743	0.516 + 0.113*SL	0.509 + 0.115*SL	0.503 + 0.116*SL
	t_F	0.720	0.486 + 0.117*SL	0.486 + 0.117*SL	0.486 + 0.117*SL
	t_{PLH}	0.368	0.260 + 0.054*SL	0.262 + 0.054*SL	0.265 + 0.053*SL
	t_{PHL}	0.531	0.412 + 0.059*SL	0.418 + 0.058*SL	0.423 + 0.057*SL
F to Y	t_R	0.740	0.512 + 0.114*SL	0.506 + 0.116*SL	0.502 + 0.116*SL
	t_F	0.797	0.563 + 0.117*SL	0.564 + 0.116*SL	0.564 + 0.116*SL
	t_{PLH}	0.388	0.280 + 0.054*SL	0.282 + 0.054*SL	0.284 + 0.053*SL
	t_{PHL}	0.582	0.462 + 0.060*SL	0.468 + 0.058*SL	0.475 + 0.057*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA33D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.125	0.088 + 0.018*SL	0.091 + 0.018*SL	0.079 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.080 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.466	0.440 + 0.013*SL	0.453 + 0.010*SL	0.467 + 0.009*SL
	t_{PHL}	0.616	0.589 + 0.014*SL	0.602 + 0.010*SL	0.617 + 0.009*SL
B to Y	t_R	0.125	0.089 + 0.018*SL	0.091 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.510	0.484 + 0.013*SL	0.497 + 0.010*SL	0.510 + 0.009*SL
	t_{PHL}	0.691	0.664 + 0.014*SL	0.677 + 0.010*SL	0.692 + 0.009*SL
C to Y	t_R	0.125	0.089 + 0.018*SL	0.090 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.112	0.078 + 0.017*SL	0.081 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.529	0.502 + 0.013*SL	0.516 + 0.010*SL	0.529 + 0.009*SL
	t_{PHL}	0.749	0.721 + 0.014*SL	0.735 + 0.011*SL	0.750 + 0.009*SL
D to Y	t_R	0.128	0.091 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.109	0.075 + 0.017*SL	0.079 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.517	0.490 + 0.013*SL	0.504 + 0.010*SL	0.517 + 0.009*SL
	t_{PHL}	0.648	0.621 + 0.014*SL	0.634 + 0.010*SL	0.649 + 0.009*SL
E to Y	t_R	0.128	0.092 + 0.018*SL	0.094 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.110	0.075 + 0.017*SL	0.080 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.562	0.536 + 0.013*SL	0.549 + 0.010*SL	0.563 + 0.009*SL
	t_{PHL}	0.725	0.698 + 0.014*SL	0.711 + 0.010*SL	0.726 + 0.009*SL
F to Y	t_R	0.128	0.092 + 0.018*SL	0.093 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.112	0.077 + 0.018*SL	0.083 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.581	0.554 + 0.013*SL	0.568 + 0.010*SL	0.581 + 0.009*SL
	t_{PHL}	0.783	0.756 + 0.014*SL	0.769 + 0.011*SL	0.784 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA33D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.119	0.099 + 0.010*SL	0.103 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.098	0.080 + 0.009*SL	0.084 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.519	0.503 + 0.008*SL	0.513 + 0.006*SL	0.535 + 0.005*SL
	t_{PHL}	0.644	0.628 + 0.008*SL	0.637 + 0.006*SL	0.658 + 0.005*SL
B to Y	t_R	0.118	0.098 + 0.010*SL	0.103 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.099	0.079 + 0.010*SL	0.087 + 0.008*SL	0.085 + 0.008*SL
	t_{PLH}	0.563	0.547 + 0.008*SL	0.557 + 0.006*SL	0.579 + 0.004*SL
	t_{PHL}	0.718	0.702 + 0.008*SL	0.711 + 0.006*SL	0.733 + 0.005*SL
C to Y	t_R	0.118	0.098 + 0.010*SL	0.103 + 0.009*SL	0.097 + 0.009*SL
	t_F	0.101	0.081 + 0.010*SL	0.089 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	0.582	0.566 + 0.008*SL	0.575 + 0.006*SL	0.597 + 0.004*SL
	t_{PHL}	0.776	0.760 + 0.008*SL	0.769 + 0.006*SL	0.791 + 0.005*SL
D to Y	t_R	0.119	0.099 + 0.010*SL	0.105 + 0.009*SL	0.100 + 0.009*SL
	t_F	0.097	0.078 + 0.010*SL	0.086 + 0.008*SL	0.084 + 0.008*SL
	t_{PLH}	0.571	0.555 + 0.008*SL	0.564 + 0.006*SL	0.587 + 0.005*SL
	t_{PHL}	0.676	0.660 + 0.008*SL	0.669 + 0.006*SL	0.690 + 0.005*SL
E to Y	t_R	0.120	0.101 + 0.010*SL	0.105 + 0.009*SL	0.099 + 0.009*SL
	t_F	0.099	0.080 + 0.009*SL	0.086 + 0.008*SL	0.086 + 0.008*SL
	t_{PLH}	0.617	0.600 + 0.008*SL	0.610 + 0.006*SL	0.632 + 0.005*SL
	t_{PHL}	0.752	0.736 + 0.008*SL	0.745 + 0.006*SL	0.767 + 0.005*SL
F to Y	t_R	0.120	0.101 + 0.010*SL	0.104 + 0.009*SL	0.099 + 0.009*SL
	t_F	0.100	0.081 + 0.009*SL	0.086 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.635	0.619 + 0.008*SL	0.628 + 0.006*SL	0.651 + 0.005*SL
	t_{PHL}	0.810	0.794 + 0.008*SL	0.803 + 0.006*SL	0.825 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	x	x	x	x	1
x	x	x	0	0	0	x	1
x	x	x	x	x	x	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA331							*OA331*
A	B	C	D	E	F	G	
0.9	0.9	1.0	0.9	0.9	0.9	0.9	3.00
OA331D2							*OA331D2*
A	B	C	D	E	F	G	
0.9	0.9	1.0	0.9	0.9	0.9	0.9	3.67
OA331D4							*OA331D4*
A	B	C	D	E	F	G	
0.9	0.9	1.0	0.9	0.9	0.9	0.9	4.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA331

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.701	0.477 + 0.112*SL	0.466 + 0.115*SL	0.456 + 0.116*SL
	t_F	0.681	0.458 + 0.112*SL	0.452 + 0.113*SL	0.456 + 0.113*SL
	t_{PLH}	0.289	0.182 + 0.053*SL	0.183 + 0.053*SL	0.185 + 0.053*SL
	t_{PHL}	0.415	0.302 + 0.056*SL	0.308 + 0.055*SL	0.313 + 0.054*SL
B to Y	t_R	0.703	0.478 + 0.112*SL	0.470 + 0.114*SL	0.464 + 0.115*SL
	t_F	0.755	0.530 + 0.112*SL	0.527 + 0.113*SL	0.531 + 0.113*SL
	t_{PLH}	0.334	0.226 + 0.054*SL	0.228 + 0.053*SL	0.231 + 0.053*SL
	t_{PHL}	0.477	0.366 + 0.056*SL	0.370 + 0.055*SL	0.375 + 0.054*SL
C to Y	t_R	0.700	0.473 + 0.113*SL	0.467 + 0.115*SL	0.463 + 0.115*SL
	t_F	0.827	0.602 + 0.112*SL	0.600 + 0.113*SL	0.605 + 0.112*SL
	t_{PLH}	0.352	0.244 + 0.054*SL	0.246 + 0.053*SL	0.249 + 0.053*SL
	t_{PHL}	0.523	0.410 + 0.056*SL	0.416 + 0.055*SL	0.422 + 0.054*SL
D to Y	t_R	0.790	0.565 + 0.113*SL	0.556 + 0.115*SL	0.551 + 0.116*SL
	t_F	0.680	0.457 + 0.111*SL	0.455 + 0.112*SL	0.453 + 0.112*SL
	t_{PLH}	0.363	0.256 + 0.054*SL	0.258 + 0.053*SL	0.260 + 0.053*SL
	t_{PHL}	0.467	0.354 + 0.056*SL	0.361 + 0.055*SL	0.367 + 0.054*SL
E to Y	t_R	0.794	0.568 + 0.113*SL	0.561 + 0.115*SL	0.557 + 0.115*SL
	t_F	0.755	0.530 + 0.112*SL	0.529 + 0.112*SL	0.529 + 0.112*SL
	t_{PLH}	0.408	0.301 + 0.054*SL	0.302 + 0.053*SL	0.305 + 0.053*SL
	t_{PHL}	0.531	0.419 + 0.056*SL	0.424 + 0.055*SL	0.429 + 0.054*SL
F to Y	t_R	0.792	0.564 + 0.114*SL	0.560 + 0.115*SL	0.557 + 0.115*SL
	t_F	0.831	0.607 + 0.112*SL	0.606 + 0.112*SL	0.605 + 0.112*SL
	t_{PLH}	0.428	0.321 + 0.054*SL	0.323 + 0.053*SL	0.326 + 0.053*SL
	t_{PHL}	0.580	0.467 + 0.056*SL	0.472 + 0.055*SL	0.479 + 0.054*SL
G to Y	t_R	0.455	0.390 + 0.033*SL	0.380 + 0.035*SL	0.366 + 0.037*SL
	t_F	0.830	0.607 + 0.112*SL	0.606 + 0.112*SL	0.606 + 0.112*SL
	t_{PLH}	0.193	0.156 + 0.018*SL	0.158 + 0.018*SL	0.160 + 0.018*SL
	t_{PHL}	0.599	0.486 + 0.057*SL	0.492 + 0.055*SL	0.499 + 0.054*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA331D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.128	0.091 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.112	0.077 + 0.018*SL	0.084 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.496	0.469 + 0.013*SL	0.483 + 0.010*SL	0.496 + 0.009*SL
	t_{PHL}	0.621	0.594 + 0.014*SL	0.607 + 0.011*SL	0.623 + 0.009*SL
B to Y	t_R	0.128	0.093 + 0.018*SL	0.093 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.113	0.079 + 0.017*SL	0.083 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.540	0.513 + 0.013*SL	0.527 + 0.010*SL	0.541 + 0.009*SL
	t_{PHL}	0.693	0.665 + 0.014*SL	0.679 + 0.011*SL	0.695 + 0.009*SL
C to Y	t_R	0.128	0.092 + 0.018*SL	0.094 + 0.018*SL	0.082 + 0.019*SL
	t_F	0.114	0.080 + 0.017*SL	0.085 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.558	0.531 + 0.013*SL	0.545 + 0.010*SL	0.558 + 0.009*SL
	t_{PHL}	0.747	0.720 + 0.014*SL	0.733 + 0.011*SL	0.749 + 0.009*SL
D to Y	t_R	0.123	0.087 + 0.018*SL	0.088 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.112	0.077 + 0.017*SL	0.082 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.567	0.541 + 0.013*SL	0.554 + 0.010*SL	0.566 + 0.009*SL
	t_{PHL}	0.673	0.645 + 0.014*SL	0.659 + 0.011*SL	0.674 + 0.009*SL
E to Y	t_R	0.123	0.087 + 0.018*SL	0.089 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.113	0.078 + 0.017*SL	0.083 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.611	0.585 + 0.013*SL	0.598 + 0.010*SL	0.610 + 0.009*SL
	t_{PHL}	0.746	0.718 + 0.014*SL	0.732 + 0.011*SL	0.747 + 0.009*SL
F to Y	t_R	0.123	0.087 + 0.018*SL	0.089 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.115	0.080 + 0.017*SL	0.086 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.632	0.606 + 0.013*SL	0.618 + 0.010*SL	0.630 + 0.009*SL
	t_{PHL}	0.804	0.776 + 0.014*SL	0.790 + 0.011*SL	0.806 + 0.009*SL
G to Y	t_R	0.113	0.077 + 0.018*SL	0.076 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.115	0.080 + 0.017*SL	0.086 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.382	0.357 + 0.012*SL	0.368 + 0.010*SL	0.378 + 0.009*SL
	t_{PHL}	0.824	0.796 + 0.014*SL	0.810 + 0.011*SL	0.826 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA331D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.119	0.099 + 0.010*SL	0.104 + 0.009*SL	0.098 + 0.009*SL
	t_F	0.100	0.082 + 0.009*SL	0.087 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.543	0.527 + 0.008*SL	0.536 + 0.006*SL	0.559 + 0.005*SL
	t_{PHL}	0.644	0.628 + 0.008*SL	0.637 + 0.006*SL	0.659 + 0.005*SL
B to Y	t_R	0.119	0.098 + 0.010*SL	0.104 + 0.009*SL	0.098 + 0.009*SL
	t_F	0.102	0.082 + 0.010*SL	0.090 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.588	0.572 + 0.008*SL	0.581 + 0.006*SL	0.603 + 0.005*SL
	t_{PHL}	0.716	0.700 + 0.008*SL	0.709 + 0.006*SL	0.731 + 0.005*SL
C to Y	t_R	0.119	0.098 + 0.010*SL	0.105 + 0.009*SL	0.098 + 0.009*SL
	t_F	0.102	0.084 + 0.009*SL	0.088 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.606	0.589 + 0.008*SL	0.599 + 0.006*SL	0.621 + 0.005*SL
	t_{PHL}	0.770	0.754 + 0.008*SL	0.763 + 0.006*SL	0.786 + 0.005*SL
D to Y	t_R	0.120	0.099 + 0.011*SL	0.106 + 0.009*SL	0.100 + 0.009*SL
	t_F	0.100	0.081 + 0.010*SL	0.088 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	0.611	0.595 + 0.008*SL	0.605 + 0.006*SL	0.627 + 0.005*SL
	t_{PHL}	0.696	0.680 + 0.008*SL	0.689 + 0.006*SL	0.711 + 0.005*SL
E to Y	t_R	0.121	0.102 + 0.010*SL	0.105 + 0.009*SL	0.100 + 0.009*SL
	t_F	0.100	0.082 + 0.009*SL	0.086 + 0.008*SL	0.089 + 0.008*SL
	t_{PLH}	0.656	0.639 + 0.008*SL	0.649 + 0.006*SL	0.672 + 0.005*SL
	t_{PHL}	0.768	0.752 + 0.008*SL	0.762 + 0.006*SL	0.784 + 0.005*SL
F to Y	t_R	0.121	0.102 + 0.010*SL	0.105 + 0.009*SL	0.100 + 0.009*SL
	t_F	0.102	0.084 + 0.009*SL	0.089 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.676	0.660 + 0.008*SL	0.670 + 0.006*SL	0.692 + 0.005*SL
	t_{PHL}	0.826	0.810 + 0.008*SL	0.820 + 0.006*SL	0.842 + 0.005*SL
G to Y	t_R	0.101	0.081 + 0.010*SL	0.085 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.102	0.084 + 0.009*SL	0.089 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.404	0.389 + 0.007*SL	0.397 + 0.005*SL	0.414 + 0.004*SL
	t_{PHL}	0.847	0.830 + 0.008*SL	0.840 + 0.006*SL	0.862 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
0	0	0	x	x	x	x	x	1
x	x	x	0	0	0	x	x	1
x	x	x	x	x	x	0	0	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
OA332								*OA332*
A	B	C	D	E	F	G	H	
0.8	0.9	0.9	0.8	0.9	0.9	0.8	0.9	3.33
OA332D2								*OA332D2*
A	B	C	D	E	F	G	H	
0.8	0.9	0.9	0.8	0.9	0.9	0.8	0.9	4.33
OA332D4								*OA332D4*
A	B	C	D	E	F	G	H	
0.8	0.9	0.9	0.8	0.9	0.9	0.8	0.9	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA332

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.952	0.732 + 0.110*SL	0.718 + 0.114*SL	0.705 + 0.115*SL
	t_F	0.701	0.461 + 0.120*SL	0.458 + 0.121*SL	0.462 + 0.120*SL
	t_{PLH}	0.295	0.186 + 0.055*SL	0.188 + 0.054*SL	0.192 + 0.054*SL
	t_{PHL}	0.454	0.336 + 0.059*SL	0.339 + 0.058*SL	0.343 + 0.058*SL
B to Y	t_R	0.954	0.731 + 0.111*SL	0.722 + 0.114*SL	0.713 + 0.115*SL
	t_F	0.782	0.541 + 0.121*SL	0.541 + 0.120*SL	0.543 + 0.120*SL
	t_{PLH}	0.341	0.231 + 0.055*SL	0.234 + 0.054*SL	0.238 + 0.054*SL
	t_{PHL}	0.517	0.397 + 0.060*SL	0.402 + 0.059*SL	0.407 + 0.058*SL
C to Y	t_R	0.951	0.727 + 0.112*SL	0.718 + 0.114*SL	0.712 + 0.115*SL
	t_F	0.859	0.618 + 0.120*SL	0.620 + 0.120*SL	0.621 + 0.120*SL
	t_{PLH}	0.359	0.249 + 0.055*SL	0.252 + 0.054*SL	0.257 + 0.054*SL
	t_{PHL}	0.567	0.446 + 0.060*SL	0.452 + 0.059*SL	0.458 + 0.058*SL
D to Y	t_R	0.891	0.666 + 0.112*SL	0.657 + 0.115*SL	0.650 + 0.116*SL
	t_F	0.936	0.650 + 0.143*SL	0.650 + 0.143*SL	0.649 + 0.143*SL
	t_{PLH}	0.359	0.249 + 0.055*SL	0.252 + 0.054*SL	0.257 + 0.054*SL
	t_{PHL}	0.657	0.515 + 0.071*SL	0.521 + 0.070*SL	0.528 + 0.069*SL
E to Y	t_R	0.894	0.669 + 0.113*SL	0.662 + 0.114*SL	0.657 + 0.115*SL
	t_F	1.028	0.741 + 0.143*SL	0.742 + 0.143*SL	0.742 + 0.143*SL
	t_{PLH}	0.405	0.295 + 0.055*SL	0.297 + 0.054*SL	0.303 + 0.054*SL
	t_{PHL}	0.736	0.595 + 0.070*SL	0.600 + 0.069*SL	0.606 + 0.069*SL
F to Y	t_R	0.891	0.664 + 0.114*SL	0.659 + 0.115*SL	0.656 + 0.115*SL
	t_F	1.122	0.836 + 0.143*SL	0.838 + 0.143*SL	0.839 + 0.143*SL
	t_{PLH}	0.425	0.315 + 0.055*SL	0.318 + 0.054*SL	0.323 + 0.054*SL
	t_{PHL}	0.802	0.660 + 0.071*SL	0.666 + 0.069*SL	0.672 + 0.069*SL
G to Y	t_R	0.815	0.675 + 0.070*SL	0.661 + 0.073*SL	0.644 + 0.076*SL
	t_F	1.034	0.749 + 0.142*SL	0.750 + 0.142*SL	0.749 + 0.142*SL
	t_{PLH}	0.296	0.223 + 0.037*SL	0.226 + 0.036*SL	0.228 + 0.035*SL
	t_{PHL}	0.763	0.619 + 0.072*SL	0.626 + 0.070*SL	0.635 + 0.069*SL
H to Y	t_R	0.808	0.663 + 0.072*SL	0.655 + 0.074*SL	0.645 + 0.076*SL
	t_F	1.122	0.836 + 0.143*SL	0.838 + 0.143*SL	0.838 + 0.143*SL
	t_{PLH}	0.306	0.233 + 0.036*SL	0.235 + 0.036*SL	0.239 + 0.035*SL
	t_{PHL}	0.834	0.692 + 0.071*SL	0.698 + 0.070*SL	0.704 + 0.069*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA332D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.133	0.096 + 0.018*SL	0.099 + 0.018*SL	0.087 + 0.019*SL
	t_F	0.112	0.077 + 0.018*SL	0.084 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.527	0.500 + 0.014*SL	0.514 + 0.010*SL	0.529 + 0.009*SL
	t_{PHL}	0.659	0.632 + 0.014*SL	0.645 + 0.011*SL	0.660 + 0.009*SL
B to Y	t_R	0.132	0.094 + 0.019*SL	0.098 + 0.018*SL	0.087 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.084 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.573	0.545 + 0.014*SL	0.560 + 0.010*SL	0.574 + 0.009*SL
	t_{PHL}	0.735	0.708 + 0.014*SL	0.721 + 0.011*SL	0.737 + 0.009*SL
C to Y	t_R	0.132	0.095 + 0.019*SL	0.098 + 0.018*SL	0.087 + 0.019*SL
	t_F	0.114	0.080 + 0.017*SL	0.085 + 0.016*SL	0.080 + 0.016*SL
	t_{PLH}	0.591	0.563 + 0.014*SL	0.578 + 0.010*SL	0.592 + 0.009*SL
	t_{PHL}	0.794	0.766 + 0.014*SL	0.779 + 0.011*SL	0.795 + 0.009*SL
D to Y	t_R	0.135	0.099 + 0.018*SL	0.101 + 0.017*SL	0.087 + 0.019*SL
	t_F	0.117	0.081 + 0.018*SL	0.089 + 0.016*SL	0.083 + 0.016*SL
	t_{PLH}	0.583	0.556 + 0.014*SL	0.570 + 0.010*SL	0.585 + 0.009*SL
	t_{PHL}	0.877	0.849 + 0.014*SL	0.862 + 0.011*SL	0.879 + 0.009*SL
E to Y	t_R	0.134	0.098 + 0.018*SL	0.101 + 0.018*SL	0.089 + 0.019*SL
	t_F	0.118	0.084 + 0.017*SL	0.089 + 0.016*SL	0.084 + 0.016*SL
	t_{PLH}	0.628	0.601 + 0.014*SL	0.616 + 0.010*SL	0.630 + 0.009*SL
	t_{PHL}	0.968	0.940 + 0.014*SL	0.954 + 0.011*SL	0.970 + 0.009*SL
F to Y	t_R	0.134	0.098 + 0.018*SL	0.101 + 0.018*SL	0.089 + 0.019*SL
	t_F	0.121	0.087 + 0.017*SL	0.093 + 0.016*SL	0.086 + 0.016*SL
	t_{PLH}	0.649	0.621 + 0.014*SL	0.636 + 0.010*SL	0.651 + 0.009*SL
	t_{PHL}	1.044	1.016 + 0.014*SL	1.030 + 0.011*SL	1.047 + 0.009*SL
G to Y	t_R	0.125	0.089 + 0.018*SL	0.090 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.119	0.084 + 0.017*SL	0.089 + 0.016*SL	0.086 + 0.016*SL
	t_{PLH}	0.516	0.490 + 0.013*SL	0.503 + 0.010*SL	0.515 + 0.009*SL
	t_{PHL}	0.994	0.965 + 0.014*SL	0.979 + 0.011*SL	0.996 + 0.009*SL
H to Y	t_R	0.124	0.088 + 0.018*SL	0.090 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.120	0.084 + 0.018*SL	0.092 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.526	0.500 + 0.013*SL	0.513 + 0.010*SL	0.525 + 0.009*SL
	t_{PHL}	1.077	1.048 + 0.014*SL	1.063 + 0.011*SL	1.080 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA332D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.124	0.105 + 0.010*SL	0.108 + 0.009*SL	0.103 + 0.009*SL
	t_F	0.100	0.082 + 0.009*SL	0.086 + 0.008*SL	0.088 + 0.008*SL
	t_{PLH}	0.580	0.563 + 0.008*SL	0.573 + 0.006*SL	0.597 + 0.005*SL
	t_{PHL}	0.686	0.670 + 0.008*SL	0.679 + 0.006*SL	0.701 + 0.005*SL
B to Y	t_R	0.124	0.104 + 0.010*SL	0.109 + 0.009*SL	0.103 + 0.009*SL
	t_F	0.102	0.083 + 0.010*SL	0.089 + 0.008*SL	0.090 + 0.008*SL
	t_{PLH}	0.625	0.608 + 0.008*SL	0.619 + 0.006*SL	0.642 + 0.005*SL
	t_{PHL}	0.761	0.745 + 0.008*SL	0.755 + 0.006*SL	0.777 + 0.005*SL
C to Y	t_R	0.124	0.105 + 0.010*SL	0.108 + 0.009*SL	0.103 + 0.009*SL
	t_F	0.103	0.084 + 0.010*SL	0.091 + 0.008*SL	0.091 + 0.008*SL
	t_{PLH}	0.643	0.626 + 0.008*SL	0.636 + 0.006*SL	0.660 + 0.005*SL
	t_{PHL}	0.820	0.803 + 0.008*SL	0.813 + 0.006*SL	0.836 + 0.005*SL
D to Y	t_R	0.125	0.105 + 0.010*SL	0.110 + 0.009*SL	0.105 + 0.009*SL
	t_F	0.105	0.087 + 0.009*SL	0.092 + 0.008*SL	0.095 + 0.008*SL
	t_{PLH}	0.636	0.620 + 0.008*SL	0.630 + 0.006*SL	0.653 + 0.005*SL
	t_{PHL}	0.908	0.892 + 0.008*SL	0.901 + 0.006*SL	0.925 + 0.005*SL
E to Y	t_R	0.126	0.106 + 0.010*SL	0.110 + 0.009*SL	0.104 + 0.009*SL
	t_F	0.109	0.090 + 0.009*SL	0.096 + 0.008*SL	0.096 + 0.008*SL
	t_{PLH}	0.682	0.665 + 0.008*SL	0.675 + 0.006*SL	0.699 + 0.005*SL
	t_{PHL}	0.999	0.982 + 0.008*SL	0.992 + 0.006*SL	1.016 + 0.005*SL
F to Y	t_R	0.126	0.106 + 0.010*SL	0.110 + 0.009*SL	0.104 + 0.009*SL
	t_F	0.110	0.092 + 0.009*SL	0.097 + 0.008*SL	0.098 + 0.008*SL
	t_{PLH}	0.702	0.685 + 0.008*SL	0.696 + 0.006*SL	0.719 + 0.005*SL
	t_{PHL}	1.075	1.058 + 0.008*SL	1.068 + 0.006*SL	1.092 + 0.005*SL
G to Y	t_R	0.121	0.101 + 0.010*SL	0.105 + 0.009*SL	0.099 + 0.009*SL
	t_F	0.108	0.089 + 0.009*SL	0.096 + 0.008*SL	0.097 + 0.008*SL
	t_{PLH}	0.557	0.541 + 0.008*SL	0.550 + 0.006*SL	0.573 + 0.005*SL
	t_{PHL}	1.025	1.008 + 0.008*SL	1.018 + 0.006*SL	1.042 + 0.005*SL
H to Y	t_R	0.120	0.099 + 0.010*SL	0.105 + 0.009*SL	0.099 + 0.009*SL
	t_F	0.109	0.090 + 0.009*SL	0.096 + 0.008*SL	0.099 + 0.008*SL
	t_{PLH}	0.567	0.551 + 0.008*SL	0.561 + 0.006*SL	0.583 + 0.005*SL
	t_{PHL}	1.107	1.091 + 0.008*SL	1.100 + 0.006*SL	1.125 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	G	Y
0	0	0	0	x	x	x	1
x	x	x	x	0	x	x	1
x	x	x	x	x	0	x	1
x	x	x	x	x	x	0	1
Other States							0

Cell Data

Input Load (SL)							Gate Count
OA4111							*OA4111*
A	B	C	D	E	F	G	
0.9	0.9	0.9	0.9	1.0	1.0	0.9	2.67
OA4111D2							*OA4111D2*
A	B	C	D	E	F	G	
0.9	0.9	0.9	0.9	1.0	1.0	1.0	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA4111

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.899	0.590 + 0.154*SL	0.582 + 0.157*SL	0.588 + 0.156*SL
	t_F	0.726	0.461 + 0.132*SL	0.455 + 0.134*SL	0.462 + 0.133*SL
	t_{PLH}	0.384	0.242 + 0.071*SL	0.243 + 0.071*SL	0.245 + 0.070*SL
	t_{PHL}	0.376	0.250 + 0.063*SL	0.251 + 0.063*SL	0.253 + 0.063*SL
B to Y	t_R	0.916	0.609 + 0.153*SL	0.605 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.815	0.549 + 0.133*SL	0.545 + 0.134*SL	0.553 + 0.133*SL
	t_{PLH}	0.460	0.317 + 0.072*SL	0.319 + 0.071*SL	0.322 + 0.070*SL
	t_{PHL}	0.447	0.320 + 0.063*SL	0.322 + 0.063*SL	0.324 + 0.063*SL
C to Y	t_R	0.916	0.609 + 0.153*SL	0.605 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.906	0.641 + 0.132*SL	0.637 + 0.133*SL	0.644 + 0.132*SL
	t_{PLH}	0.508	0.365 + 0.072*SL	0.368 + 0.071*SL	0.371 + 0.071*SL
	t_{PHL}	0.502	0.373 + 0.065*SL	0.377 + 0.063*SL	0.381 + 0.063*SL
D to Y	t_R	0.915	0.608 + 0.154*SL	0.605 + 0.154*SL	0.603 + 0.155*SL
	t_F	0.998	0.734 + 0.132*SL	0.730 + 0.133*SL	0.739 + 0.132*SL
	t_{PLH}	0.529	0.386 + 0.072*SL	0.389 + 0.071*SL	0.391 + 0.071*SL
	t_{PHL}	0.544	0.411 + 0.066*SL	0.418 + 0.065*SL	0.426 + 0.063*SL
E to Y	t_R	0.403	0.333 + 0.035*SL	0.329 + 0.036*SL	0.322 + 0.037*SL
	t_F	1.003	0.741 + 0.131*SL	0.740 + 0.131*SL	0.739 + 0.132*SL
	t_{PLH}	0.194	0.159 + 0.017*SL	0.160 + 0.017*SL	0.160 + 0.017*SL
	t_{PHL}	0.633	0.498 + 0.067*SL	0.507 + 0.065*SL	0.517 + 0.064*SL
F to Y	t_R	0.425	0.355 + 0.035*SL	0.349 + 0.036*SL	0.340 + 0.038*SL
	t_F	1.004	0.741 + 0.131*SL	0.741 + 0.131*SL	0.739 + 0.132*SL
	t_{PLH}	0.203	0.168 + 0.018*SL	0.169 + 0.018*SL	0.169 + 0.017*SL
	t_{PHL}	0.645	0.510 + 0.067*SL	0.519 + 0.065*SL	0.529 + 0.064*SL
G to Y	t_R	0.440	0.371 + 0.034*SL	0.364 + 0.036*SL	0.355 + 0.037*SL
	t_F	1.004	0.741 + 0.131*SL	0.741 + 0.131*SL	0.739 + 0.132*SL
	t_{PLH}	0.207	0.171 + 0.018*SL	0.172 + 0.018*SL	0.173 + 0.018*SL
	t_{PHL}	0.645	0.511 + 0.067*SL	0.519 + 0.065*SL	0.529 + 0.064*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OA4111D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.126	0.089 + 0.018*SL	0.091 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.115	0.082 + 0.016*SL	0.086 + 0.015*SL	0.084 + 0.015*SL
	t_{PLH}	0.569	0.543 + 0.013*SL	0.556 + 0.010*SL	0.568 + 0.009*SL
	t_{PHL}	0.590	0.562 + 0.014*SL	0.576 + 0.010*SL	0.593 + 0.009*SL
B to Y	t_R	0.126	0.090 + 0.018*SL	0.092 + 0.018*SL	0.080 + 0.019*SL
	t_F	0.116	0.083 + 0.016*SL	0.088 + 0.015*SL	0.086 + 0.015*SL
	t_{PLH}	0.644	0.618 + 0.013*SL	0.630 + 0.010*SL	0.643 + 0.009*SL
	t_{PHL}	0.673	0.646 + 0.014*SL	0.659 + 0.010*SL	0.676 + 0.009*SL
C to Y	t_R	0.126	0.089 + 0.018*SL	0.092 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.119	0.085 + 0.017*SL	0.093 + 0.015*SL	0.087 + 0.015*SL
	t_{PLH}	0.692	0.666 + 0.013*SL	0.679 + 0.010*SL	0.692 + 0.009*SL
	t_{PHL}	0.740	0.712 + 0.014*SL	0.726 + 0.010*SL	0.744 + 0.009*SL
D to Y	t_R	0.126	0.089 + 0.019*SL	0.092 + 0.018*SL	0.081 + 0.019*SL
	t_F	0.120	0.087 + 0.016*SL	0.092 + 0.015*SL	0.090 + 0.015*SL
	t_{PLH}	0.713	0.687 + 0.013*SL	0.700 + 0.010*SL	0.713 + 0.009*SL
	t_{PHL}	0.792	0.765 + 0.014*SL	0.779 + 0.010*SL	0.797 + 0.009*SL
E to Y	t_R	0.111	0.076 + 0.018*SL	0.073 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.122	0.089 + 0.017*SL	0.095 + 0.015*SL	0.090 + 0.015*SL
	t_{PLH}	0.377	0.352 + 0.012*SL	0.363 + 0.010*SL	0.372 + 0.009*SL
	t_{PHL}	0.883	0.855 + 0.014*SL	0.869 + 0.010*SL	0.887 + 0.009*SL
F to Y	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.120	0.087 + 0.017*SL	0.093 + 0.015*SL	0.090 + 0.015*SL
	t_{PLH}	0.388	0.363 + 0.012*SL	0.374 + 0.010*SL	0.383 + 0.009*SL
	t_{PHL}	0.894	0.867 + 0.014*SL	0.880 + 0.010*SL	0.898 + 0.009*SL
G to Y	t_R	0.109	0.074 + 0.018*SL	0.071 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.120	0.086 + 0.017*SL	0.095 + 0.015*SL	0.090 + 0.015*SL
	t_{PLH}	0.393	0.370 + 0.012*SL	0.379 + 0.010*SL	0.388 + 0.009*SL
	t_{PHL}	0.898	0.870 + 0.014*SL	0.884 + 0.010*SL	0.902 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG1/SCG1D2

2-NAND and two (2-AND into 2-NOR)s into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	1
x	x	1	1	x	x	x	x	1
x	x	x	x	1	x	x	x	1
x	x	x	x	x	1	1	x	1
x	x	x	x	x	x	x	1	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
SCG1								*SCG1*
A	B	C	D	E	F	G	H	
0.8	0.9	0.8	0.8	0.8	0.8	0.8	0.9	4.00
SCG1D2								*SCG1D2*
A	B	C	D	E	F	G	H	
0.8	0.9	0.8	0.8	0.8	0.8	0.8	0.8	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.216	0.120 + 0.048*SL	0.116 + 0.049*SL	0.111 + 0.050*SL
	t_F	0.258	0.142 + 0.058*SL	0.139 + 0.059*SL	0.136 + 0.059*SL
	t_{PLH}	0.254	0.206 + 0.024*SL	0.211 + 0.023*SL	0.214 + 0.022*SL
	t_{PHL}	0.267	0.209 + 0.029*SL	0.211 + 0.028*SL	0.212 + 0.028*SL
B to Y	t_R	0.216	0.120 + 0.048*SL	0.116 + 0.049*SL	0.111 + 0.050*SL
	t_F	0.260	0.144 + 0.058*SL	0.141 + 0.059*SL	0.138 + 0.059*SL
	t_{PLH}	0.251	0.203 + 0.024*SL	0.209 + 0.023*SL	0.211 + 0.022*SL
	t_{PHL}	0.290	0.231 + 0.029*SL	0.234 + 0.028*SL	0.235 + 0.028*SL
C to Y	t_R	0.247	0.155 + 0.046*SL	0.153 + 0.046*SL	0.147 + 0.047*SL
	t_F	0.276	0.161 + 0.058*SL	0.159 + 0.058*SL	0.154 + 0.059*SL
	t_{PLH}	0.336	0.288 + 0.024*SL	0.296 + 0.022*SL	0.300 + 0.022*SL
	t_{PHL}	0.337	0.274 + 0.031*SL	0.282 + 0.029*SL	0.288 + 0.029*SL
D to Y	t_R	0.247	0.156 + 0.046*SL	0.152 + 0.046*SL	0.146 + 0.047*SL
	t_F	0.278	0.163 + 0.057*SL	0.161 + 0.058*SL	0.157 + 0.059*SL
	t_{PLH}	0.332	0.284 + 0.024*SL	0.291 + 0.022*SL	0.296 + 0.022*SL
	t_{PHL}	0.355	0.293 + 0.031*SL	0.301 + 0.029*SL	0.307 + 0.029*SL
E to Y	t_R	0.236	0.144 + 0.046*SL	0.140 + 0.047*SL	0.134 + 0.048*SL
	t_F	0.278	0.163 + 0.057*SL	0.161 + 0.058*SL	0.157 + 0.058*SL
	t_{PLH}	0.318	0.272 + 0.023*SL	0.277 + 0.022*SL	0.280 + 0.022*SL
	t_{PHL}	0.396	0.333 + 0.031*SL	0.341 + 0.029*SL	0.347 + 0.029*SL
F to Y	t_R	0.272	0.178 + 0.047*SL	0.175 + 0.047*SL	0.169 + 0.048*SL
	t_F	0.271	0.154 + 0.058*SL	0.153 + 0.058*SL	0.150 + 0.059*SL
	t_{PLH}	0.346	0.298 + 0.024*SL	0.304 + 0.023*SL	0.309 + 0.022*SL
	t_{PHL}	0.340	0.279 + 0.031*SL	0.285 + 0.029*SL	0.290 + 0.029*SL
G to Y	t_R	0.272	0.180 + 0.046*SL	0.175 + 0.047*SL	0.169 + 0.048*SL
	t_F	0.272	0.156 + 0.058*SL	0.155 + 0.058*SL	0.152 + 0.059*SL
	t_{PLH}	0.340	0.292 + 0.024*SL	0.298 + 0.023*SL	0.303 + 0.022*SL
	t_{PHL}	0.357	0.295 + 0.031*SL	0.302 + 0.029*SL	0.307 + 0.029*SL
H to Y	t_R	0.262	0.168 + 0.047*SL	0.163 + 0.048*SL	0.158 + 0.049*SL
	t_F	0.272	0.156 + 0.058*SL	0.155 + 0.058*SL	0.152 + 0.059*SL
	t_{PLH}	0.331	0.284 + 0.023*SL	0.288 + 0.022*SL	0.291 + 0.022*SL
	t_{PHL}	0.402	0.340 + 0.031*SL	0.347 + 0.029*SL	0.352 + 0.029*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.163	0.117 + 0.023*SL	0.116 + 0.023*SL	0.109 + 0.024*SL
	t_F	0.189	0.131 + 0.029*SL	0.130 + 0.029*SL	0.126 + 0.029*SL
	t_{PLH}	0.263	0.236 + 0.014*SL	0.244 + 0.012*SL	0.253 + 0.011*SL
	t_{PHL}	0.265	0.233 + 0.016*SL	0.239 + 0.015*SL	0.243 + 0.014*SL
B to Y	t_R	0.163	0.116 + 0.023*SL	0.115 + 0.024*SL	0.109 + 0.024*SL
	t_F	0.191	0.133 + 0.029*SL	0.133 + 0.029*SL	0.128 + 0.029*SL
	t_{PLH}	0.258	0.230 + 0.014*SL	0.238 + 0.012*SL	0.248 + 0.011*SL
	t_{PHL}	0.281	0.249 + 0.016*SL	0.255 + 0.015*SL	0.260 + 0.014*SL
C to Y	t_R	0.209	0.162 + 0.024*SL	0.163 + 0.023*SL	0.157 + 0.024*SL
	t_F	0.213	0.154 + 0.029*SL	0.156 + 0.029*SL	0.153 + 0.029*SL
	t_{PLH}	0.364	0.335 + 0.014*SL	0.343 + 0.012*SL	0.356 + 0.011*SL
	t_{PHL}	0.347	0.311 + 0.018*SL	0.320 + 0.016*SL	0.333 + 0.015*SL
D to Y	t_R	0.209	0.163 + 0.023*SL	0.164 + 0.023*SL	0.157 + 0.024*SL
	t_F	0.216	0.158 + 0.029*SL	0.159 + 0.029*SL	0.156 + 0.029*SL
	t_{PLH}	0.358	0.329 + 0.014*SL	0.337 + 0.012*SL	0.350 + 0.011*SL
	t_{PHL}	0.364	0.328 + 0.018*SL	0.336 + 0.016*SL	0.350 + 0.015*SL
E to Y	t_R	0.188	0.143 + 0.023*SL	0.141 + 0.023*SL	0.131 + 0.024*SL
	t_F	0.216	0.158 + 0.029*SL	0.160 + 0.029*SL	0.156 + 0.029*SL
	t_{PLH}	0.323	0.297 + 0.013*SL	0.302 + 0.012*SL	0.309 + 0.011*SL
	t_{PHL}	0.404	0.369 + 0.018*SL	0.377 + 0.016*SL	0.390 + 0.015*SL
F to Y	t_R	0.233	0.188 + 0.023*SL	0.187 + 0.023*SL	0.180 + 0.024*SL
	t_F	0.208	0.149 + 0.030*SL	0.150 + 0.029*SL	0.149 + 0.029*SL
	t_{PLH}	0.378	0.350 + 0.014*SL	0.357 + 0.012*SL	0.368 + 0.011*SL
	t_{PHL}	0.351	0.316 + 0.017*SL	0.324 + 0.016*SL	0.336 + 0.015*SL
G to Y	t_R	0.234	0.187 + 0.023*SL	0.188 + 0.023*SL	0.180 + 0.024*SL
	t_F	0.210	0.150 + 0.030*SL	0.152 + 0.029*SL	0.151 + 0.029*SL
	t_{PLH}	0.373	0.345 + 0.014*SL	0.352 + 0.012*SL	0.363 + 0.011*SL
	t_{PHL}	0.368	0.333 + 0.017*SL	0.341 + 0.016*SL	0.353 + 0.015*SL
H to Y	t_R	0.211	0.165 + 0.023*SL	0.163 + 0.023*SL	0.155 + 0.024*SL
	t_F	0.210	0.151 + 0.030*SL	0.152 + 0.029*SL	0.151 + 0.029*SL
	t_{PLH}	0.335	0.309 + 0.013*SL	0.314 + 0.012*SL	0.320 + 0.011*SL
	t_{PHL}	0.408	0.373 + 0.017*SL	0.380 + 0.016*SL	0.392 + 0.015*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	1
x	x	1	1	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG2				*SCG2D2*				*SCG2*	*SCG2D2*
A	B	C	D	A	B	C	D		
0.8	0.8	0.9	0.8	0.8	0.8	0.9	0.8	2.00	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.174	0.099 + 0.038*SL	0.099 + 0.037*SL	0.094 + 0.038*SL
	t_F	0.162	0.095 + 0.034*SL	0.104 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.265	0.220 + 0.023*SL	0.234 + 0.019*SL	0.243 + 0.018*SL
	t_{PHL}	0.310	0.261 + 0.024*SL	0.278 + 0.020*SL	0.293 + 0.018*SL
B to Y	t_R	0.174	0.098 + 0.038*SL	0.100 + 0.037*SL	0.094 + 0.038*SL
	t_F	0.168	0.102 + 0.033*SL	0.110 + 0.031*SL	0.111 + 0.031*SL
	t_{PLH}	0.261	0.215 + 0.023*SL	0.230 + 0.019*SL	0.239 + 0.018*SL
	t_{PHL}	0.334	0.285 + 0.024*SL	0.303 + 0.020*SL	0.318 + 0.018*SL
C to Y	t_R	0.176	0.100 + 0.038*SL	0.102 + 0.037*SL	0.096 + 0.038*SL
	t_F	0.162	0.096 + 0.033*SL	0.104 + 0.031*SL	0.105 + 0.031*SL
	t_{PLH}	0.330	0.285 + 0.023*SL	0.299 + 0.019*SL	0.307 + 0.018*SL
	t_{PHL}	0.354	0.305 + 0.024*SL	0.323 + 0.020*SL	0.337 + 0.018*SL
D to Y	t_R	0.176	0.102 + 0.037*SL	0.101 + 0.037*SL	0.096 + 0.038*SL
	t_F	0.168	0.102 + 0.033*SL	0.111 + 0.031*SL	0.110 + 0.031*SL
	t_{PLH}	0.321	0.276 + 0.023*SL	0.290 + 0.019*SL	0.298 + 0.018*SL
	t_{PHL}	0.378	0.329 + 0.025*SL	0.346 + 0.020*SL	0.362 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.138	0.096 + 0.021*SL	0.104 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.142	0.103 + 0.019*SL	0.114 + 0.016*SL	0.125 + 0.016*SL
	t_{PLH}	0.279	0.249 + 0.015*SL	0.263 + 0.011*SL	0.284 + 0.009*SL
	t_{PHL}	0.333	0.302 + 0.016*SL	0.317 + 0.012*SL	0.344 + 0.010*SL
B to Y	t_R	0.137	0.095 + 0.021*SL	0.103 + 0.019*SL	0.105 + 0.019*SL
	t_F	0.147	0.109 + 0.019*SL	0.120 + 0.016*SL	0.131 + 0.015*SL
	t_{PLH}	0.275	0.245 + 0.015*SL	0.259 + 0.011*SL	0.281 + 0.009*SL
	t_{PHL}	0.358	0.325 + 0.016*SL	0.341 + 0.012*SL	0.370 + 0.010*SL
C to Y	t_R	0.144	0.103 + 0.020*SL	0.110 + 0.018*SL	0.107 + 0.019*SL
	t_F	0.140	0.101 + 0.019*SL	0.112 + 0.016*SL	0.124 + 0.015*SL
	t_{PLH}	0.345	0.315 + 0.015*SL	0.330 + 0.011*SL	0.350 + 0.009*SL
	t_{PHL}	0.378	0.346 + 0.016*SL	0.361 + 0.012*SL	0.389 + 0.010*SL
D to Y	t_R	0.142	0.100 + 0.021*SL	0.108 + 0.019*SL	0.108 + 0.019*SL
	t_F	0.146	0.109 + 0.019*SL	0.119 + 0.016*SL	0.130 + 0.015*SL
	t_{PLH}	0.336	0.307 + 0.015*SL	0.321 + 0.011*SL	0.341 + 0.009*SL
	t_{PHL}	0.401	0.369 + 0.016*SL	0.385 + 0.012*SL	0.413 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	1
x	x	1	1	x	1
x	x	x	x	0	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
SCG3					*SCG3D2*					*SCG3*	*SCG3D2*
A	B	C	D	E	A	B	C	D	E		
0.8	0.9	0.8	0.9	1.0	0.8	0.9	0.8	0.8	2.2	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.212	0.119 + 0.047*SL	0.115 + 0.048*SL	0.110 + 0.049*SL
	t_F	0.259	0.142 + 0.058*SL	0.141 + 0.059*SL	0.137 + 0.059*SL
	t_{PLH}	0.255	0.208 + 0.024*SL	0.213 + 0.022*SL	0.216 + 0.022*SL
	t_{PHL}	0.273	0.214 + 0.029*SL	0.217 + 0.029*SL	0.219 + 0.028*SL
B to Y	t_R	0.213	0.119 + 0.047*SL	0.116 + 0.048*SL	0.110 + 0.049*SL
	t_F	0.260	0.144 + 0.058*SL	0.142 + 0.059*SL	0.138 + 0.059*SL
	t_{PLH}	0.251	0.204 + 0.024*SL	0.210 + 0.022*SL	0.212 + 0.022*SL
	t_{PHL}	0.292	0.233 + 0.029*SL	0.236 + 0.029*SL	0.238 + 0.028*SL
C to Y	t_R	0.235	0.141 + 0.047*SL	0.137 + 0.048*SL	0.132 + 0.049*SL
	t_F	0.258	0.142 + 0.058*SL	0.140 + 0.059*SL	0.137 + 0.059*SL
	t_{PLH}	0.270	0.224 + 0.023*SL	0.228 + 0.022*SL	0.230 + 0.022*SL
	t_{PHL}	0.285	0.226 + 0.030*SL	0.230 + 0.029*SL	0.232 + 0.028*SL
D to Y	t_R	0.236	0.142 + 0.047*SL	0.137 + 0.048*SL	0.132 + 0.049*SL
	t_F	0.260	0.144 + 0.058*SL	0.140 + 0.059*SL	0.138 + 0.059*SL
	t_{PLH}	0.266	0.220 + 0.023*SL	0.224 + 0.022*SL	0.226 + 0.022*SL
	t_{PHL}	0.303	0.244 + 0.030*SL	0.248 + 0.029*SL	0.250 + 0.028*SL
E to Y	t_R	0.271	0.182 + 0.044*SL	0.173 + 0.047*SL	0.162 + 0.048*SL
	t_F	0.265	0.150 + 0.057*SL	0.146 + 0.058*SL	0.141 + 0.059*SL
	t_{PLH}	0.187	0.142 + 0.023*SL	0.144 + 0.022*SL	0.145 + 0.022*SL
	t_{PHL}	0.176	0.117 + 0.030*SL	0.121 + 0.029*SL	0.123 + 0.028*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.163	0.116 + 0.023*SL	0.115 + 0.023*SL	0.108 + 0.024*SL
	t_F	0.189	0.131 + 0.029*SL	0.131 + 0.029*SL	0.126 + 0.029*SL
	t_{PLH}	0.263	0.235 + 0.014*SL	0.243 + 0.012*SL	0.252 + 0.011*SL
	t_{PHL}	0.265	0.233 + 0.016*SL	0.238 + 0.015*SL	0.243 + 0.014*SL
B to Y	t_R	0.162	0.116 + 0.023*SL	0.115 + 0.024*SL	0.109 + 0.024*SL
	t_F	0.191	0.133 + 0.029*SL	0.133 + 0.029*SL	0.128 + 0.029*SL
	t_{PLH}	0.257	0.230 + 0.014*SL	0.238 + 0.012*SL	0.247 + 0.011*SL
	t_{PHL}	0.281	0.249 + 0.016*SL	0.254 + 0.015*SL	0.260 + 0.014*SL
C to Y	t_R	0.188	0.142 + 0.023*SL	0.141 + 0.023*SL	0.132 + 0.024*SL
	t_F	0.189	0.131 + 0.029*SL	0.131 + 0.029*SL	0.127 + 0.029*SL
	t_{PLH}	0.286	0.260 + 0.013*SL	0.266 + 0.012*SL	0.273 + 0.011*SL
	t_{PHL}	0.283	0.250 + 0.016*SL	0.256 + 0.015*SL	0.263 + 0.014*SL
D to Y	t_R	0.188	0.142 + 0.023*SL	0.140 + 0.023*SL	0.132 + 0.024*SL
	t_F	0.191	0.133 + 0.029*SL	0.133 + 0.029*SL	0.129 + 0.029*SL
	t_{PLH}	0.281	0.255 + 0.013*SL	0.261 + 0.012*SL	0.269 + 0.011*SL
	t_{PHL}	0.298	0.265 + 0.016*SL	0.271 + 0.015*SL	0.278 + 0.014*SL
E to Y	t_R	0.214	0.172 + 0.021*SL	0.165 + 0.023*SL	0.151 + 0.024*SL
	t_F	0.191	0.134 + 0.028*SL	0.132 + 0.029*SL	0.128 + 0.029*SL
	t_{PLH}	0.155	0.131 + 0.012*SL	0.135 + 0.011*SL	0.137 + 0.011*SL
	t_{PHL}	0.137	0.104 + 0.016*SL	0.111 + 0.015*SL	0.116 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG4/SCG4D2

Two (two 2-ANDs into 2-NOR)s into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	F	G	H	Y
1	1	x	x	x	x	x	x	1
x	x	1	1	x	x	x	x	1
x	x	x	x	1	1	x	x	1
x	x	x	x	x	x	1	1	1
Other States								0

Cell Data

Input Load (SL)								Gate Count
SCG4								*SCG4*
A	B	C	D	E	F	G	H	
0.8	0.8	0.9	0.8	0.8	0.8	0.8	0.8	3.67
SCG4D2								*SCG4D2*
A	B	C	D	E	F	G	H	
0.8	0.8	0.8	0.8	0.8	0.8	0.7	0.8	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.184	0.109 + 0.037*SL	0.112 + 0.037*SL	0.106 + 0.037*SL
	t_F	0.204	0.122 + 0.041*SL	0.128 + 0.040*SL	0.128 + 0.040*SL
	t_{PLH}	0.287	0.243 + 0.022*SL	0.256 + 0.019*SL	0.265 + 0.018*SL
	t_{PHL}	0.335	0.282 + 0.026*SL	0.297 + 0.023*SL	0.310 + 0.021*SL
B to Y	t_R	0.185	0.112 + 0.037*SL	0.110 + 0.037*SL	0.106 + 0.037*SL
	t_F	0.208	0.126 + 0.041*SL	0.132 + 0.039*SL	0.131 + 0.040*SL
	t_{PLH}	0.283	0.238 + 0.022*SL	0.251 + 0.019*SL	0.261 + 0.018*SL
	t_{PHL}	0.355	0.302 + 0.026*SL	0.318 + 0.023*SL	0.331 + 0.021*SL
C to Y	t_R	0.187	0.112 + 0.037*SL	0.115 + 0.037*SL	0.108 + 0.038*SL
	t_F	0.204	0.121 + 0.041*SL	0.128 + 0.040*SL	0.127 + 0.040*SL
	t_{PLH}	0.355	0.311 + 0.022*SL	0.323 + 0.019*SL	0.332 + 0.018*SL
	t_{PHL}	0.385	0.332 + 0.026*SL	0.347 + 0.023*SL	0.360 + 0.021*SL
D to Y	t_R	0.188	0.115 + 0.037*SL	0.113 + 0.037*SL	0.108 + 0.038*SL
	t_F	0.208	0.126 + 0.041*SL	0.132 + 0.039*SL	0.131 + 0.040*SL
	t_{PLH}	0.345	0.300 + 0.022*SL	0.313 + 0.019*SL	0.322 + 0.018*SL
	t_{PHL}	0.400	0.347 + 0.027*SL	0.363 + 0.023*SL	0.376 + 0.021*SL
E to Y	t_R	0.200	0.128 + 0.036*SL	0.127 + 0.037*SL	0.122 + 0.037*SL
	t_F	0.192	0.110 + 0.041*SL	0.113 + 0.040*SL	0.111 + 0.040*SL
	t_{PLH}	0.297	0.255 + 0.021*SL	0.265 + 0.019*SL	0.273 + 0.017*SL
	t_{PHL}	0.329	0.280 + 0.025*SL	0.290 + 0.022*SL	0.300 + 0.021*SL
F to Y	t_R	0.201	0.129 + 0.036*SL	0.128 + 0.036*SL	0.122 + 0.037*SL
	t_F	0.196	0.116 + 0.040*SL	0.117 + 0.040*SL	0.115 + 0.040*SL
	t_{PLH}	0.291	0.249 + 0.021*SL	0.259 + 0.019*SL	0.267 + 0.017*SL
	t_{PHL}	0.351	0.302 + 0.025*SL	0.312 + 0.022*SL	0.322 + 0.021*SL
G to Y	t_R	0.212	0.139 + 0.036*SL	0.139 + 0.036*SL	0.134 + 0.037*SL
	t_F	0.192	0.111 + 0.041*SL	0.114 + 0.040*SL	0.112 + 0.040*SL
	t_{PLH}	0.353	0.310 + 0.022*SL	0.321 + 0.019*SL	0.330 + 0.018*SL
	t_{PHL}	0.376	0.327 + 0.025*SL	0.337 + 0.022*SL	0.347 + 0.021*SL
H to Y	t_R	0.212	0.140 + 0.036*SL	0.140 + 0.036*SL	0.134 + 0.037*SL
	t_F	0.196	0.116 + 0.040*SL	0.118 + 0.040*SL	0.115 + 0.040*SL
	t_{PLH}	0.350	0.306 + 0.022*SL	0.317 + 0.019*SL	0.327 + 0.018*SL
	t_{PHL}	0.400	0.350 + 0.025*SL	0.361 + 0.022*SL	0.371 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.156	0.116 + 0.020*SL	0.121 + 0.019*SL	0.121 + 0.019*SL
	t_F	0.172	0.127 + 0.022*SL	0.135 + 0.020*SL	0.143 + 0.020*SL
	t_{PLH}	0.307	0.279 + 0.014*SL	0.291 + 0.011*SL	0.310 + 0.009*SL
	t_{PHL}	0.352	0.320 + 0.016*SL	0.332 + 0.013*SL	0.355 + 0.011*SL
B to Y	t_R	0.155	0.116 + 0.020*SL	0.120 + 0.019*SL	0.121 + 0.019*SL
	t_F	0.178	0.133 + 0.023*SL	0.142 + 0.020*SL	0.150 + 0.020*SL
	t_{PLH}	0.303	0.275 + 0.014*SL	0.287 + 0.011*SL	0.306 + 0.009*SL
	t_{PHL}	0.379	0.346 + 0.016*SL	0.358 + 0.013*SL	0.382 + 0.011*SL
C to Y	t_R	0.163	0.124 + 0.020*SL	0.128 + 0.019*SL	0.128 + 0.019*SL
	t_F	0.173	0.128 + 0.023*SL	0.137 + 0.020*SL	0.145 + 0.020*SL
	t_{PLH}	0.385	0.357 + 0.014*SL	0.369 + 0.011*SL	0.388 + 0.009*SL
	t_{PHL}	0.420	0.388 + 0.016*SL	0.400 + 0.013*SL	0.423 + 0.011*SL
D to Y	t_R	0.164	0.125 + 0.020*SL	0.130 + 0.018*SL	0.127 + 0.019*SL
	t_F	0.179	0.135 + 0.022*SL	0.143 + 0.020*SL	0.149 + 0.020*SL
	t_{PLH}	0.381	0.353 + 0.014*SL	0.365 + 0.011*SL	0.384 + 0.009*SL
	t_{PHL}	0.443	0.410 + 0.016*SL	0.423 + 0.013*SL	0.446 + 0.011*SL
E to Y	t_R	0.178	0.139 + 0.020*SL	0.144 + 0.019*SL	0.142 + 0.019*SL
	t_F	0.166	0.124 + 0.021*SL	0.127 + 0.020*SL	0.131 + 0.020*SL
	t_{PLH}	0.333	0.307 + 0.013*SL	0.316 + 0.011*SL	0.332 + 0.009*SL
	t_{PHL}	0.361	0.331 + 0.015*SL	0.341 + 0.012*SL	0.358 + 0.011*SL
F to Y	t_R	0.180	0.140 + 0.020*SL	0.145 + 0.018*SL	0.142 + 0.019*SL
	t_F	0.171	0.129 + 0.021*SL	0.133 + 0.020*SL	0.136 + 0.020*SL
	t_{PLH}	0.329	0.303 + 0.013*SL	0.312 + 0.011*SL	0.328 + 0.009*SL
	t_{PHL}	0.387	0.356 + 0.015*SL	0.367 + 0.013*SL	0.385 + 0.011*SL
G to Y	t_R	0.196	0.157 + 0.019*SL	0.161 + 0.018*SL	0.160 + 0.019*SL
	t_F	0.167	0.124 + 0.021*SL	0.128 + 0.020*SL	0.132 + 0.020*SL
	t_{PLH}	0.403	0.376 + 0.013*SL	0.385 + 0.011*SL	0.403 + 0.010*SL
	t_{PHL}	0.429	0.399 + 0.015*SL	0.409 + 0.013*SL	0.427 + 0.011*SL
H to Y	t_R	0.195	0.157 + 0.019*SL	0.161 + 0.018*SL	0.159 + 0.019*SL
	t_F	0.171	0.129 + 0.021*SL	0.133 + 0.020*SL	0.136 + 0.020*SL
	t_{PLH}	0.398	0.371 + 0.013*SL	0.381 + 0.011*SL	0.399 + 0.010*SL
	t_{PHL}	0.451	0.420 + 0.015*SL	0.431 + 0.013*SL	0.449 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	E	F	Y
1	1	x	x	x	x	1
x	x	1	1	x	x	1
x	x	x	x	1	1	1
Other States						0

Cell Data

Input Load (SL)						Gate Count
SCG5						*SCG5*
A	B	C	D	E	F	
0.7	0.7	0.7	0.8	0.7	0.8	3.00
SCG5D2						*SCG5D2*
A	B	C	D	E	F	
0.7	0.7	0.7	0.8	0.7	0.8	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.187	0.110 + 0.039*SL	0.115 + 0.037*SL	0.112 + 0.038*SL
	t_F	0.209	0.131 + 0.039*SL	0.148 + 0.035*SL	0.162 + 0.033*SL
	t_{PLH}	0.304	0.254 + 0.025*SL	0.272 + 0.020*SL	0.287 + 0.018*SL
	t_{PHL}	0.398	0.337 + 0.031*SL	0.361 + 0.025*SL	0.387 + 0.021*SL
B to Y	t_R	0.186	0.109 + 0.039*SL	0.115 + 0.037*SL	0.112 + 0.038*SL
	t_F	0.217	0.140 + 0.039*SL	0.157 + 0.035*SL	0.169 + 0.033*SL
	t_{PLH}	0.297	0.248 + 0.025*SL	0.266 + 0.020*SL	0.281 + 0.018*SL
	t_{PHL}	0.424	0.362 + 0.031*SL	0.387 + 0.025*SL	0.413 + 0.021*SL
C to Y	t_R	0.197	0.121 + 0.038*SL	0.124 + 0.037*SL	0.120 + 0.037*SL
	t_F	0.213	0.134 + 0.039*SL	0.152 + 0.035*SL	0.165 + 0.033*SL
	t_{PLH}	0.397	0.347 + 0.025*SL	0.366 + 0.021*SL	0.381 + 0.019*SL
	t_{PHL}	0.531	0.470 + 0.031*SL	0.494 + 0.025*SL	0.520 + 0.021*SL
D to Y	t_R	0.197	0.122 + 0.038*SL	0.124 + 0.037*SL	0.120 + 0.037*SL
	t_F	0.220	0.142 + 0.039*SL	0.160 + 0.034*SL	0.170 + 0.033*SL
	t_{PLH}	0.393	0.342 + 0.025*SL	0.362 + 0.021*SL	0.377 + 0.019*SL
	t_{PHL}	0.560	0.498 + 0.031*SL	0.523 + 0.025*SL	0.549 + 0.021*SL
E to Y	t_R	0.205	0.128 + 0.039*SL	0.135 + 0.037*SL	0.130 + 0.038*SL
	t_F	0.213	0.135 + 0.039*SL	0.152 + 0.035*SL	0.164 + 0.033*SL
	t_{PLH}	0.450	0.398 + 0.026*SL	0.418 + 0.021*SL	0.434 + 0.019*SL
	t_{PHL}	0.579	0.518 + 0.031*SL	0.542 + 0.025*SL	0.568 + 0.021*SL
F to Y	t_R	0.205	0.128 + 0.039*SL	0.135 + 0.037*SL	0.130 + 0.037*SL
	t_F	0.220	0.142 + 0.039*SL	0.159 + 0.035*SL	0.172 + 0.033*SL
	t_{PLH}	0.447	0.395 + 0.026*SL	0.415 + 0.021*SL	0.431 + 0.019*SL
	t_{PHL}	0.610	0.548 + 0.031*SL	0.572 + 0.025*SL	0.599 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.149	0.106 + 0.022*SL	0.116 + 0.019*SL	0.123 + 0.019*SL
	t_F	0.188	0.143 + 0.022*SL	0.156 + 0.019*SL	0.181 + 0.017*SL
	t_{PLH}	0.315	0.282 + 0.016*SL	0.299 + 0.012*SL	0.326 + 0.010*SL
	t_{PHL}	0.432	0.392 + 0.020*SL	0.413 + 0.015*SL	0.450 + 0.012*SL
B to Y	t_R	0.149	0.106 + 0.022*SL	0.116 + 0.019*SL	0.121 + 0.019*SL
	t_F	0.196	0.151 + 0.022*SL	0.164 + 0.019*SL	0.189 + 0.017*SL
	t_{PLH}	0.309	0.277 + 0.016*SL	0.293 + 0.012*SL	0.320 + 0.010*SL
	t_{PHL}	0.458	0.417 + 0.020*SL	0.438 + 0.015*SL	0.477 + 0.012*SL
C to Y	t_R	0.161	0.119 + 0.021*SL	0.127 + 0.019*SL	0.132 + 0.019*SL
	t_F	0.189	0.144 + 0.023*SL	0.159 + 0.019*SL	0.182 + 0.017*SL
	t_{PLH}	0.409	0.376 + 0.017*SL	0.394 + 0.012*SL	0.421 + 0.010*SL
	t_{PHL}	0.567	0.527 + 0.020*SL	0.547 + 0.015*SL	0.585 + 0.012*SL
D to Y	t_R	0.161	0.118 + 0.021*SL	0.127 + 0.019*SL	0.132 + 0.019*SL
	t_F	0.197	0.153 + 0.022*SL	0.165 + 0.019*SL	0.190 + 0.017*SL
	t_{PLH}	0.406	0.372 + 0.017*SL	0.390 + 0.012*SL	0.418 + 0.010*SL
	t_{PHL}	0.595	0.554 + 0.020*SL	0.576 + 0.015*SL	0.614 + 0.012*SL
E to Y	t_R	0.169	0.125 + 0.022*SL	0.137 + 0.019*SL	0.143 + 0.019*SL
	t_F	0.189	0.145 + 0.022*SL	0.157 + 0.019*SL	0.183 + 0.017*SL
	t_{PLH}	0.464	0.430 + 0.017*SL	0.448 + 0.013*SL	0.477 + 0.010*SL
	t_{PHL}	0.615	0.575 + 0.020*SL	0.596 + 0.015*SL	0.633 + 0.012*SL
F to Y	t_R	0.169	0.126 + 0.022*SL	0.136 + 0.019*SL	0.142 + 0.019*SL
	t_F	0.196	0.150 + 0.023*SL	0.167 + 0.019*SL	0.190 + 0.017*SL
	t_{PLH}	0.461	0.427 + 0.017*SL	0.445 + 0.013*SL	0.474 + 0.010*SL
	t_{PHL}	0.645	0.604 + 0.020*SL	0.625 + 0.015*SL	0.664 + 0.012*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG6/SCG6D2

2-AND into 2-OR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	x	1
x	x	1	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG6			*SCG6D2*			*SCG6*	*SCG6D2*
A	B	C	A	B	C		
0.8	0.8	0.8	0.8	0.8	0.8	1.67	2.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.166	0.092 + 0.037*SL	0.092 + 0.037*SL	0.085 + 0.038*SL
	t_F	0.155	0.085 + 0.035*SL	0.094 + 0.033*SL	0.093 + 0.033*SL
	t_{PLH}	0.264	0.220 + 0.022*SL	0.233 + 0.019*SL	0.240 + 0.018*SL
	t_{PHL}	0.269	0.221 + 0.024*SL	0.237 + 0.020*SL	0.249 + 0.018*SL
B to Y	t_R	0.165	0.090 + 0.037*SL	0.091 + 0.037*SL	0.084 + 0.038*SL
	t_F	0.158	0.089 + 0.035*SL	0.097 + 0.033*SL	0.097 + 0.033*SL
	t_{PLH}	0.257	0.213 + 0.022*SL	0.226 + 0.019*SL	0.234 + 0.018*SL
	t_{PHL}	0.287	0.239 + 0.024*SL	0.255 + 0.020*SL	0.268 + 0.018*SL
C to Y	t_R	0.151	0.078 + 0.037*SL	0.073 + 0.038*SL	0.068 + 0.039*SL
	t_F	0.158	0.089 + 0.035*SL	0.097 + 0.033*SL	0.097 + 0.033*SL
	t_{PLH}	0.261	0.221 + 0.020*SL	0.229 + 0.018*SL	0.232 + 0.018*SL
	t_{PHL}	0.329	0.281 + 0.024*SL	0.297 + 0.020*SL	0.310 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.131	0.090 + 0.021*SL	0.097 + 0.019*SL	0.096 + 0.019*SL
	t_F	0.126	0.087 + 0.020*SL	0.097 + 0.017*SL	0.106 + 0.016*SL
	t_{PLH}	0.280	0.251 + 0.015*SL	0.266 + 0.011*SL	0.286 + 0.009*SL
	t_{PHL}	0.285	0.254 + 0.016*SL	0.269 + 0.012*SL	0.294 + 0.010*SL
B to Y	t_R	0.129	0.088 + 0.021*SL	0.096 + 0.019*SL	0.097 + 0.019*SL
	t_F	0.130	0.090 + 0.020*SL	0.102 + 0.017*SL	0.110 + 0.016*SL
	t_{PLH}	0.274	0.245 + 0.015*SL	0.260 + 0.011*SL	0.280 + 0.009*SL
	t_{PHL}	0.303	0.271 + 0.016*SL	0.286 + 0.012*SL	0.312 + 0.010*SL
C to Y	t_R	0.112	0.074 + 0.019*SL	0.077 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.130	0.092 + 0.019*SL	0.101 + 0.017*SL	0.110 + 0.016*SL
	t_{PLH}	0.263	0.238 + 0.013*SL	0.249 + 0.010*SL	0.260 + 0.009*SL
	t_{PHL}	0.345	0.313 + 0.016*SL	0.329 + 0.012*SL	0.355 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG7/SCG7D2

2-NAND and (2-AND into 2-NOR) into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
1	1	x	x	x	1
x	x	1	1	x	1
x	x	x	x	1	1
Other States					0

Cell Data

Input Load (SL)										Gate Count	
SCG7					*SCG7D2*					*SCG7*	*SCG7D2*
A	B	C	D	E	A	B	C	D	E		
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	3.00	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.162	0.089 + 0.037*SL	0.084 + 0.038*SL	0.079 + 0.039*SL
	t_F	0.171	0.089 + 0.041*SL	0.087 + 0.041*SL	0.083 + 0.042*SL
	t_{PLH}	0.226	0.186 + 0.020*SL	0.194 + 0.018*SL	0.198 + 0.018*SL
	t_{PHL}	0.236	0.191 + 0.023*SL	0.197 + 0.021*SL	0.200 + 0.021*SL
B to Y	t_R	0.163	0.089 + 0.037*SL	0.084 + 0.038*SL	0.080 + 0.039*SL
	t_F	0.172	0.090 + 0.041*SL	0.089 + 0.041*SL	0.084 + 0.042*SL
	t_{PLH}	0.220	0.180 + 0.020*SL	0.188 + 0.018*SL	0.192 + 0.018*SL
	t_{PHL}	0.253	0.207 + 0.023*SL	0.214 + 0.021*SL	0.217 + 0.021*SL
C to Y	t_R	0.193	0.119 + 0.037*SL	0.118 + 0.037*SL	0.112 + 0.038*SL
	t_F	0.184	0.101 + 0.041*SL	0.102 + 0.041*SL	0.098 + 0.042*SL
	t_{PLH}	0.296	0.255 + 0.021*SL	0.264 + 0.019*SL	0.270 + 0.018*SL
	t_{PHL}	0.286	0.237 + 0.024*SL	0.247 + 0.022*SL	0.254 + 0.021*SL
D to Y	t_R	0.195	0.121 + 0.037*SL	0.118 + 0.037*SL	0.112 + 0.038*SL
	t_F	0.186	0.105 + 0.041*SL	0.104 + 0.041*SL	0.100 + 0.041*SL
	t_{PLH}	0.290	0.248 + 0.021*SL	0.257 + 0.019*SL	0.263 + 0.018*SL
	t_{PHL}	0.303	0.254 + 0.025*SL	0.264 + 0.022*SL	0.272 + 0.021*SL
E to Y	t_R	0.179	0.106 + 0.037*SL	0.101 + 0.038*SL	0.095 + 0.039*SL
	t_F	0.186	0.104 + 0.041*SL	0.104 + 0.041*SL	0.100 + 0.041*SL
	t_{PLH}	0.287	0.249 + 0.019*SL	0.254 + 0.018*SL	0.256 + 0.018*SL
	t_{PHL}	0.345	0.296 + 0.025*SL	0.306 + 0.022*SL	0.314 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG7D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.133	0.094 + 0.019*SL	0.097 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.134	0.092 + 0.021*SL	0.094 + 0.020*SL	0.091 + 0.021*SL
	t_{PLH}	0.246	0.222 + 0.012*SL	0.231 + 0.010*SL	0.243 + 0.009*SL
	t_{PHL}	0.249	0.223 + 0.013*SL	0.230 + 0.011*SL	0.240 + 0.010*SL
B to Y	t_R	0.133	0.095 + 0.019*SL	0.098 + 0.018*SL	0.092 + 0.019*SL
	t_F	0.137	0.095 + 0.021*SL	0.098 + 0.020*SL	0.093 + 0.021*SL
	t_{PLH}	0.240	0.215 + 0.012*SL	0.225 + 0.010*SL	0.237 + 0.009*SL
	t_{PHL}	0.264	0.238 + 0.013*SL	0.246 + 0.011*SL	0.256 + 0.010*SL
C to Y	t_R	0.178	0.140 + 0.019*SL	0.141 + 0.019*SL	0.140 + 0.019*SL
	t_F	0.156	0.114 + 0.021*SL	0.117 + 0.021*SL	0.117 + 0.021*SL
	t_{PLH}	0.342	0.316 + 0.013*SL	0.325 + 0.011*SL	0.340 + 0.009*SL
	t_{PHL}	0.323	0.293 + 0.015*SL	0.303 + 0.012*SL	0.318 + 0.011*SL
D to Y	t_R	0.177	0.137 + 0.020*SL	0.142 + 0.019*SL	0.139 + 0.019*SL
	t_F	0.160	0.117 + 0.021*SL	0.119 + 0.021*SL	0.121 + 0.020*SL
	t_{PLH}	0.336	0.310 + 0.013*SL	0.319 + 0.011*SL	0.335 + 0.009*SL
	t_{PHL}	0.339	0.310 + 0.015*SL	0.320 + 0.012*SL	0.335 + 0.011*SL
E to Y	t_R	0.151	0.115 + 0.018*SL	0.115 + 0.018*SL	0.106 + 0.019*SL
	t_F	0.160	0.118 + 0.021*SL	0.120 + 0.021*SL	0.121 + 0.020*SL
	t_{PLH}	0.309	0.287 + 0.011*SL	0.293 + 0.010*SL	0.301 + 0.009*SL
	t_{PHL}	0.382	0.353 + 0.015*SL	0.362 + 0.012*SL	0.378 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	x	x	1
x	x	1	x	1
x	x	x	1	1
	Other States			0

Cell Data

Input Load (SL)								Gate Count	
SCG8				*SCG8D2*				*SCG8*	*SCG8D2*
A	B	C	D	A	B	C	D		
0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	2.00	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.173	0.097 + 0.038*SL	0.101 + 0.037*SL	0.094 + 0.038*SL
	t_F	0.189	0.111 + 0.039*SL	0.129 + 0.035*SL	0.140 + 0.033*SL
	t_{PLH}	0.296	0.250 + 0.023*SL	0.265 + 0.019*SL	0.276 + 0.018*SL
	t_{PHL}	0.335	0.277 + 0.029*SL	0.299 + 0.024*SL	0.322 + 0.021*SL
B to Y	t_R	0.174	0.098 + 0.038*SL	0.101 + 0.037*SL	0.095 + 0.038*SL
	t_F	0.196	0.118 + 0.039*SL	0.135 + 0.035*SL	0.146 + 0.033*SL
	t_{PLH}	0.291	0.245 + 0.023*SL	0.260 + 0.019*SL	0.271 + 0.018*SL
	t_{PHL}	0.358	0.300 + 0.029*SL	0.322 + 0.024*SL	0.346 + 0.021*SL
C to Y	t_R	0.164	0.090 + 0.037*SL	0.088 + 0.037*SL	0.081 + 0.038*SL
	t_F	0.198	0.120 + 0.039*SL	0.138 + 0.034*SL	0.148 + 0.033*SL
	t_{PLH}	0.319	0.276 + 0.021*SL	0.288 + 0.018*SL	0.294 + 0.018*SL
	t_{PHL}	0.456	0.398 + 0.029*SL	0.420 + 0.024*SL	0.444 + 0.021*SL
D to Y	t_R	0.171	0.097 + 0.037*SL	0.096 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.198	0.121 + 0.039*SL	0.139 + 0.034*SL	0.148 + 0.033*SL
	t_{PLH}	0.340	0.296 + 0.022*SL	0.309 + 0.019*SL	0.316 + 0.018*SL
	t_{PHL}	0.472	0.413 + 0.029*SL	0.436 + 0.024*SL	0.459 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.138	0.094 + 0.022*SL	0.105 + 0.019*SL	0.110 + 0.019*SL
	t_F	0.166	0.121 + 0.022*SL	0.134 + 0.019*SL	0.158 + 0.017*SL
	t_{PLH}	0.316	0.285 + 0.015*SL	0.301 + 0.012*SL	0.324 + 0.010*SL
	t_{PHL}	0.368	0.330 + 0.019*SL	0.348 + 0.014*SL	0.384 + 0.011*SL
B to Y	t_R	0.139	0.096 + 0.021*SL	0.105 + 0.019*SL	0.110 + 0.019*SL
	t_F	0.172	0.128 + 0.022*SL	0.142 + 0.019*SL	0.164 + 0.017*SL
	t_{PLH}	0.311	0.280 + 0.015*SL	0.296 + 0.012*SL	0.319 + 0.010*SL
	t_{PHL}	0.391	0.352 + 0.019*SL	0.371 + 0.014*SL	0.407 + 0.011*SL
C to Y	t_R	0.129	0.090 + 0.019*SL	0.095 + 0.018*SL	0.089 + 0.019*SL
	t_F	0.173	0.129 + 0.022*SL	0.143 + 0.019*SL	0.165 + 0.017*SL
	t_{PLH}	0.327	0.299 + 0.014*SL	0.313 + 0.011*SL	0.330 + 0.009*SL
	t_{PHL}	0.490	0.452 + 0.019*SL	0.471 + 0.014*SL	0.506 + 0.011*SL
D to Y	t_R	0.135	0.097 + 0.019*SL	0.102 + 0.018*SL	0.096 + 0.019*SL
	t_F	0.172	0.127 + 0.023*SL	0.142 + 0.019*SL	0.165 + 0.017*SL
	t_{PLH}	0.348	0.319 + 0.014*SL	0.334 + 0.011*SL	0.353 + 0.009*SL
	t_{PHL}	0.506	0.468 + 0.019*SL	0.486 + 0.014*SL	0.522 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	Y
0	0	x	0
x	x	0	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG9			*SCG9D2*			*SCG9*	*SCG9D2*
A	B	C	A	B	C		
0.7	0.8	0.8	0.7	0.8	0.8	2.00	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG9

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.171	0.096 + 0.038*SL	0.098 + 0.037*SL	0.094 + 0.038*SL
	t_F	0.159	0.093 + 0.033*SL	0.101 + 0.031*SL	0.102 + 0.031*SL
	t_{PLH}	0.288	0.242 + 0.023*SL	0.257 + 0.019*SL	0.267 + 0.018*SL
	t_{PHL}	0.299	0.251 + 0.024*SL	0.268 + 0.020*SL	0.283 + 0.018*SL
B to Y	t_R	0.178	0.103 + 0.037*SL	0.104 + 0.037*SL	0.100 + 0.038*SL
	t_F	0.158	0.089 + 0.034*SL	0.101 + 0.031*SL	0.103 + 0.031*SL
	t_{PLH}	0.322	0.275 + 0.023*SL	0.291 + 0.020*SL	0.302 + 0.018*SL
	t_{PHL}	0.309	0.261 + 0.024*SL	0.278 + 0.020*SL	0.293 + 0.018*SL
C to Y	t_R	0.178	0.102 + 0.038*SL	0.106 + 0.037*SL	0.099 + 0.038*SL
	t_F	0.145	0.080 + 0.032*SL	0.086 + 0.031*SL	0.082 + 0.031*SL
	t_{PLH}	0.336	0.289 + 0.023*SL	0.305 + 0.020*SL	0.317 + 0.018*SL
	t_{PHL}	0.253	0.208 + 0.022*SL	0.223 + 0.019*SL	0.234 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG9D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.135	0.092 + 0.021*SL	0.102 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.132	0.091 + 0.021*SL	0.104 + 0.017*SL	0.115 + 0.016*SL
	t_{PLH}	0.300	0.270 + 0.015*SL	0.285 + 0.011*SL	0.308 + 0.009*SL
	t_{PHL}	0.319	0.286 + 0.016*SL	0.302 + 0.013*SL	0.330 + 0.010*SL
B to Y	t_R	0.141	0.099 + 0.021*SL	0.108 + 0.019*SL	0.112 + 0.019*SL
	t_F	0.134	0.093 + 0.020*SL	0.105 + 0.017*SL	0.116 + 0.016*SL
	t_{PLH}	0.334	0.303 + 0.016*SL	0.319 + 0.012*SL	0.342 + 0.010*SL
	t_{PHL}	0.329	0.296 + 0.016*SL	0.312 + 0.013*SL	0.340 + 0.010*SL
C to Y	t_R	0.142	0.100 + 0.021*SL	0.109 + 0.019*SL	0.112 + 0.019*SL
	t_F	0.111	0.074 + 0.019*SL	0.083 + 0.017*SL	0.086 + 0.016*SL
	t_{PLH}	0.348	0.317 + 0.016*SL	0.333 + 0.012*SL	0.357 + 0.010*SL
	t_{PHL}	0.250	0.220 + 0.015*SL	0.235 + 0.011*SL	0.256 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
0	0	x	x	0
x	x	0	0	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG10				*SCG10D2*				*SCG10*	*SCG10D2*
A	B	C	D	A	B	C	D		
0.7	0.8	0.7	0.7	0.7	0.8	0.7	0.7	2.33	2.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG10

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.177	0.102 + 0.038*SL	0.103 + 0.037*SL	0.099 + 0.038*SL
	t_F	0.177	0.105 + 0.036*SL	0.118 + 0.033*SL	0.122 + 0.033*SL
	t_{PLH}	0.321	0.274 + 0.023*SL	0.290 + 0.020*SL	0.301 + 0.018*SL
	t_{PHL}	0.297	0.242 + 0.027*SL	0.264 + 0.022*SL	0.284 + 0.019*SL
B to Y	t_R	0.185	0.110 + 0.037*SL	0.111 + 0.037*SL	0.106 + 0.038*SL
	t_F	0.177	0.104 + 0.036*SL	0.118 + 0.033*SL	0.123 + 0.033*SL
	t_{PLH}	0.366	0.318 + 0.024*SL	0.335 + 0.020*SL	0.347 + 0.018*SL
	t_{PHL}	0.310	0.256 + 0.027*SL	0.278 + 0.022*SL	0.297 + 0.019*SL
C to Y	t_R	0.177	0.102 + 0.038*SL	0.103 + 0.037*SL	0.099 + 0.038*SL
	t_F	0.188	0.115 + 0.036*SL	0.129 + 0.033*SL	0.133 + 0.032*SL
	t_{PLH}	0.345	0.298 + 0.024*SL	0.314 + 0.020*SL	0.325 + 0.018*SL
	t_{PHL}	0.340	0.284 + 0.028*SL	0.307 + 0.022*SL	0.329 + 0.020*SL
D to Y	t_R	0.185	0.110 + 0.037*SL	0.112 + 0.037*SL	0.106 + 0.038*SL
	t_F	0.187	0.114 + 0.037*SL	0.129 + 0.033*SL	0.132 + 0.032*SL
	t_{PLH}	0.388	0.340 + 0.024*SL	0.357 + 0.020*SL	0.369 + 0.018*SL
	t_{PHL}	0.352	0.296 + 0.028*SL	0.319 + 0.022*SL	0.341 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG10D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.144	0.100 + 0.022*SL	0.111 + 0.019*SL	0.114 + 0.019*SL
	t_F	0.145	0.103 + 0.021*SL	0.117 + 0.018*SL	0.134 + 0.016*SL
	t_{PLH}	0.342	0.311 + 0.016*SL	0.326 + 0.012*SL	0.350 + 0.010*SL
	t_{PHL}	0.310	0.275 + 0.018*SL	0.293 + 0.013*SL	0.326 + 0.010*SL
B to Y	t_R	0.152	0.109 + 0.021*SL	0.119 + 0.019*SL	0.122 + 0.019*SL
	t_F	0.144	0.101 + 0.022*SL	0.117 + 0.018*SL	0.133 + 0.016*SL
	t_{PLH}	0.386	0.354 + 0.016*SL	0.370 + 0.012*SL	0.396 + 0.010*SL
	t_{PHL}	0.324	0.288 + 0.018*SL	0.307 + 0.013*SL	0.340 + 0.010*SL
C to Y	t_R	0.145	0.102 + 0.021*SL	0.111 + 0.019*SL	0.114 + 0.019*SL
	t_F	0.156	0.115 + 0.021*SL	0.127 + 0.018*SL	0.145 + 0.016*SL
	t_{PLH}	0.366	0.335 + 0.016*SL	0.351 + 0.012*SL	0.375 + 0.010*SL
	t_{PHL}	0.352	0.316 + 0.018*SL	0.335 + 0.014*SL	0.370 + 0.011*SL
D to Y	t_R	0.152	0.110 + 0.021*SL	0.119 + 0.019*SL	0.122 + 0.019*SL
	t_F	0.156	0.114 + 0.021*SL	0.129 + 0.018*SL	0.145 + 0.016*SL
	t_{PLH}	0.408	0.377 + 0.016*SL	0.393 + 0.012*SL	0.418 + 0.010*SL
	t_{PHL}	0.365	0.327 + 0.019*SL	0.348 + 0.014*SL	0.382 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	0	x	x	x	0
x	x	0	0	x	0
x	x	x	x	1	0
Other States					1

Cell Data

Input Load (SL)										Gate Count	
SCG11					*SCG11D2*					*SCG11*	*SCG11D2*
A	B	C	D	E	A	B	C	D	E		
0.8	0.8	0.8	0.8	1.0	0.8	0.8	0.8	0.8	2.0	2.67	3.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG11

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.451	0.220 + 0.115*SL	0.218 + 0.116*SL	0.220 + 0.116*SL
	t_F	0.191	0.107 + 0.042*SL	0.110 + 0.041*SL	0.105 + 0.042*SL
	t_{PLH}	0.305	0.199 + 0.053*SL	0.201 + 0.052*SL	0.203 + 0.052*SL
	t_{PHL}	0.308	0.254 + 0.027*SL	0.268 + 0.024*SL	0.277 + 0.023*SL
B to Y	t_R	0.452	0.221 + 0.115*SL	0.219 + 0.116*SL	0.221 + 0.116*SL
	t_F	0.192	0.108 + 0.042*SL	0.110 + 0.041*SL	0.106 + 0.042*SL
	t_{PLH}	0.326	0.220 + 0.053*SL	0.222 + 0.052*SL	0.224 + 0.052*SL
	t_{PHL}	0.317	0.263 + 0.027*SL	0.277 + 0.024*SL	0.286 + 0.023*SL
C to Y	t_R	0.459	0.231 + 0.114*SL	0.227 + 0.115*SL	0.225 + 0.115*SL
	t_F	0.220	0.138 + 0.041*SL	0.137 + 0.041*SL	0.132 + 0.042*SL
	t_{PLH}	0.354	0.248 + 0.053*SL	0.251 + 0.052*SL	0.253 + 0.052*SL
	t_{PHL}	0.330	0.278 + 0.026*SL	0.288 + 0.024*SL	0.296 + 0.023*SL
D to Y	t_R	0.460	0.232 + 0.114*SL	0.227 + 0.115*SL	0.225 + 0.115*SL
	t_F	0.220	0.138 + 0.041*SL	0.137 + 0.041*SL	0.132 + 0.042*SL
	t_{PLH}	0.375	0.269 + 0.053*SL	0.271 + 0.052*SL	0.273 + 0.052*SL
	t_{PHL}	0.338	0.286 + 0.026*SL	0.296 + 0.024*SL	0.304 + 0.023*SL
E to Y	t_R	0.464	0.239 + 0.113*SL	0.230 + 0.115*SL	0.226 + 0.115*SL
	t_F	0.241	0.164 + 0.038*SL	0.155 + 0.040*SL	0.143 + 0.042*SL
	t_{PLH}	0.290	0.184 + 0.053*SL	0.186 + 0.052*SL	0.187 + 0.052*SL
	t_{PHL}	0.181	0.134 + 0.024*SL	0.137 + 0.023*SL	0.140 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG11D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.309	0.195 + 0.057*SL	0.192 + 0.058*SL	0.190 + 0.058*SL
	t_F	0.156	0.111 + 0.023*SL	0.118 + 0.021*SL	0.121 + 0.021*SL
	t_{PLH}	0.266	0.213 + 0.026*SL	0.212 + 0.026*SL	0.215 + 0.026*SL
	t_{PHL}	0.324	0.290 + 0.017*SL	0.304 + 0.014*SL	0.325 + 0.012*SL
B to Y	t_R	0.311	0.198 + 0.057*SL	0.194 + 0.058*SL	0.191 + 0.058*SL
	t_F	0.157	0.112 + 0.023*SL	0.119 + 0.021*SL	0.120 + 0.021*SL
	t_{PLH}	0.285	0.233 + 0.026*SL	0.232 + 0.026*SL	0.234 + 0.026*SL
	t_{PHL}	0.333	0.299 + 0.017*SL	0.313 + 0.014*SL	0.335 + 0.012*SL
C to Y	t_R	0.320	0.208 + 0.056*SL	0.203 + 0.057*SL	0.198 + 0.058*SL
	t_F	0.191	0.148 + 0.021*SL	0.151 + 0.021*SL	0.150 + 0.021*SL
	t_{PLH}	0.319	0.265 + 0.027*SL	0.268 + 0.026*SL	0.272 + 0.026*SL
	t_{PHL}	0.357	0.326 + 0.016*SL	0.335 + 0.013*SL	0.353 + 0.012*SL
D to Y	t_R	0.321	0.209 + 0.056*SL	0.204 + 0.057*SL	0.199 + 0.058*SL
	t_F	0.191	0.148 + 0.021*SL	0.152 + 0.021*SL	0.150 + 0.021*SL
	t_{PLH}	0.337	0.283 + 0.027*SL	0.286 + 0.026*SL	0.290 + 0.026*SL
	t_{PHL}	0.365	0.333 + 0.016*SL	0.344 + 0.013*SL	0.361 + 0.012*SL
E to Y	t_R	0.324	0.213 + 0.055*SL	0.208 + 0.057*SL	0.199 + 0.058*SL
	t_F	0.195	0.159 + 0.018*SL	0.153 + 0.020*SL	0.139 + 0.021*SL
	t_{PLH}	0.227	0.172 + 0.027*SL	0.175 + 0.026*SL	0.178 + 0.026*SL
	t_{PHL}	0.149	0.123 + 0.013*SL	0.129 + 0.012*SL	0.133 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG12/SCG12D2

2-NAND into 2-NOR with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
1	1	0	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG12			*SCG12D2*			*SCG12*	*SCG12D2*
A	B	C	A	B	C		
0.8	0.9	1.0	0.8	0.9	2.1	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG12

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.287	0.134 + 0.076*SL	0.129 + 0.078*SL	0.123 + 0.078*SL
	t_F	0.133	0.068 + 0.033*SL	0.065 + 0.033*SL	0.062 + 0.034*SL
	t_{PLH}	0.267	0.194 + 0.037*SL	0.198 + 0.036*SL	0.199 + 0.035*SL
	t_{PHL}	0.225	0.184 + 0.020*SL	0.193 + 0.018*SL	0.197 + 0.018*SL
B to Y	t_R	0.287	0.134 + 0.076*SL	0.129 + 0.078*SL	0.123 + 0.078*SL
	t_F	0.134	0.068 + 0.033*SL	0.068 + 0.033*SL	0.064 + 0.034*SL
	t_{PLH}	0.263	0.190 + 0.037*SL	0.194 + 0.036*SL	0.196 + 0.035*SL
	t_{PHL}	0.243	0.202 + 0.021*SL	0.211 + 0.018*SL	0.216 + 0.018*SL
C to Y	t_R	0.293	0.142 + 0.075*SL	0.134 + 0.077*SL	0.126 + 0.078*SL
	t_F	0.179	0.123 + 0.028*SL	0.111 + 0.031*SL	0.100 + 0.033*SL
	t_{PLH}	0.189	0.116 + 0.037*SL	0.121 + 0.036*SL	0.122 + 0.035*SL
	t_{PHL}	0.139	0.098 + 0.020*SL	0.108 + 0.018*SL	0.109 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG12D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.203	0.128 + 0.038*SL	0.126 + 0.038*SL	0.117 + 0.039*SL
	t_F	0.104	0.069 + 0.018*SL	0.074 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.259	0.219 + 0.020*SL	0.226 + 0.018*SL	0.231 + 0.018*SL
	t_{PHL}	0.234	0.208 + 0.013*SL	0.219 + 0.010*SL	0.231 + 0.009*SL
B to Y	t_R	0.203	0.127 + 0.038*SL	0.126 + 0.038*SL	0.117 + 0.039*SL
	t_F	0.109	0.076 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.254	0.214 + 0.020*SL	0.222 + 0.018*SL	0.227 + 0.018*SL
	t_{PHL}	0.250	0.225 + 0.013*SL	0.236 + 0.010*SL	0.248 + 0.009*SL
C to Y	t_R	0.205	0.131 + 0.037*SL	0.126 + 0.038*SL	0.117 + 0.039*SL
	t_F	0.145	0.117 + 0.014*SL	0.114 + 0.015*SL	0.098 + 0.016*SL
	t_{PLH}	0.145	0.103 + 0.021*SL	0.114 + 0.018*SL	0.117 + 0.018*SL
	t_{PHL}	0.110	0.085 + 0.012*SL	0.098 + 0.009*SL	0.104 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG13/SCG13D2

2-NOR into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	0	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG13			*SCG13D2*			*SCG13*	*SCG13D2*
A	B	C	A	B	C		
0.8	0.8	1.1	0.8	0.8	2.4	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG13

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.157	0.083 + 0.037*SL	0.078 + 0.038*SL	0.072 + 0.039*SL
	t_F	0.197	0.113 + 0.042*SL	0.117 + 0.041*SL	0.114 + 0.041*SL
	t_{PLH}	0.209	0.171 + 0.019*SL	0.176 + 0.018*SL	0.177 + 0.018*SL
	t_{PHL}	0.296	0.245 + 0.025*SL	0.258 + 0.022*SL	0.267 + 0.021*SL
B to Y	t_R	0.158	0.084 + 0.037*SL	0.079 + 0.039*SL	0.075 + 0.039*SL
	t_F	0.197	0.114 + 0.042*SL	0.116 + 0.041*SL	0.113 + 0.041*SL
	t_{PLH}	0.230	0.192 + 0.019*SL	0.197 + 0.018*SL	0.198 + 0.018*SL
	t_{PHL}	0.306	0.255 + 0.025*SL	0.268 + 0.022*SL	0.277 + 0.021*SL
C to Y	t_R	0.201	0.133 + 0.034*SL	0.125 + 0.036*SL	0.113 + 0.038*SL
	t_F	0.186	0.107 + 0.040*SL	0.101 + 0.041*SL	0.096 + 0.042*SL
	t_{PLH}	0.142	0.102 + 0.020*SL	0.112 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.129	0.081 + 0.024*SL	0.092 + 0.021*SL	0.094 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG13D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.121	0.084 + 0.018*SL	0.083 + 0.019*SL	0.075 + 0.019*SL
	t_F	0.163	0.118 + 0.023*SL	0.125 + 0.021*SL	0.129 + 0.021*SL
	t_{PLH}	0.220	0.198 + 0.011*SL	0.204 + 0.009*SL	0.210 + 0.009*SL
	t_{PHL}	0.321	0.290 + 0.015*SL	0.301 + 0.013*SL	0.320 + 0.011*SL
B to Y	t_R	0.123	0.086 + 0.019*SL	0.086 + 0.019*SL	0.078 + 0.019*SL
	t_F	0.163	0.118 + 0.023*SL	0.125 + 0.021*SL	0.129 + 0.021*SL
	t_{PLH}	0.239	0.217 + 0.011*SL	0.224 + 0.009*SL	0.230 + 0.009*SL
	t_{PHL}	0.332	0.301 + 0.016*SL	0.312 + 0.013*SL	0.332 + 0.011*SL
C to Y	t_R	0.161	0.130 + 0.016*SL	0.124 + 0.017*SL	0.110 + 0.018*SL
	t_F	0.140	0.100 + 0.020*SL	0.099 + 0.020*SL	0.093 + 0.021*SL
	t_{PLH}	0.115	0.091 + 0.012*SL	0.102 + 0.009*SL	0.108 + 0.009*SL
	t_{PHL}	0.100	0.072 + 0.014*SL	0.082 + 0.011*SL	0.092 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG14/SCG14D2

2-NAND into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	1	0
x	0	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG14			*SCG14D2*			*SCG14*	*SCG14D2*
A	B	C	A	B	C		
0.8	0.9	1.2	0.8	0.9	2.4	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG14

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.166	0.091 + 0.037*SL	0.088 + 0.038*SL	0.082 + 0.039*SL
	t_F	0.175	0.093 + 0.041*SL	0.090 + 0.041*SL	0.085 + 0.042*SL
	t_{PLH}	0.229	0.189 + 0.020*SL	0.197 + 0.018*SL	0.201 + 0.018*SL
	t_{PHL}	0.240	0.195 + 0.023*SL	0.201 + 0.021*SL	0.204 + 0.021*SL
B to Y	t_R	0.167	0.093 + 0.037*SL	0.088 + 0.038*SL	0.084 + 0.039*SL
	t_F	0.176	0.095 + 0.041*SL	0.092 + 0.041*SL	0.087 + 0.042*SL
	t_{PLH}	0.225	0.184 + 0.020*SL	0.193 + 0.018*SL	0.197 + 0.018*SL
	t_{PHL}	0.259	0.213 + 0.023*SL	0.220 + 0.021*SL	0.223 + 0.021*SL
C to Y	t_R	0.200	0.132 + 0.034*SL	0.124 + 0.036*SL	0.112 + 0.038*SL
	t_F	0.184	0.106 + 0.039*SL	0.099 + 0.041*SL	0.092 + 0.042*SL
	t_{PLH}	0.143	0.103 + 0.020*SL	0.113 + 0.017*SL	0.113 + 0.017*SL
	t_{PHL}	0.127	0.080 + 0.024*SL	0.091 + 0.021*SL	0.092 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG14D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.134	0.096 + 0.019*SL	0.099 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.136	0.093 + 0.021*SL	0.096 + 0.020*SL	0.092 + 0.021*SL
	t_{PLH}	0.245	0.221 + 0.012*SL	0.230 + 0.010*SL	0.241 + 0.009*SL
	t_{PHL}	0.249	0.223 + 0.013*SL	0.230 + 0.011*SL	0.240 + 0.011*SL
B to Y	t_R	0.135	0.096 + 0.019*SL	0.099 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.139	0.097 + 0.021*SL	0.099 + 0.020*SL	0.094 + 0.021*SL
	t_{PLH}	0.240	0.216 + 0.012*SL	0.225 + 0.010*SL	0.237 + 0.009*SL
	t_{PHL}	0.266	0.239 + 0.013*SL	0.247 + 0.011*SL	0.257 + 0.011*SL
C to Y	t_R	0.161	0.130 + 0.016*SL	0.123 + 0.017*SL	0.110 + 0.018*SL
	t_F	0.139	0.100 + 0.019*SL	0.098 + 0.020*SL	0.089 + 0.021*SL
	t_{PLH}	0.116	0.093 + 0.012*SL	0.104 + 0.009*SL	0.109 + 0.009*SL
	t_{PHL}	0.099	0.072 + 0.014*SL	0.082 + 0.011*SL	0.091 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG15/SCG15D2

2-NAND into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	1	1	0
x	0	1	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG15				*SCG15D2*				*SCG15*	*SCG15D2*
A	B	C	D	A	B	C	D		
0.8	0.9	1.0	1.0	0.8	0.8	2.1	2.3	2.00	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG15

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.217	0.123 + 0.047*SL	0.119 + 0.048*SL	0.113 + 0.049*SL
	t_F	0.262	0.145 + 0.058*SL	0.144 + 0.058*SL	0.139 + 0.059*SL
	t_{PLH}	0.258	0.211 + 0.024*SL	0.217 + 0.022*SL	0.219 + 0.022*SL
	t_{PHL}	0.277	0.218 + 0.029*SL	0.221 + 0.029*SL	0.223 + 0.028*SL
B to Y	t_R	0.217	0.122 + 0.047*SL	0.119 + 0.048*SL	0.114 + 0.049*SL
	t_F	0.263	0.148 + 0.058*SL	0.145 + 0.058*SL	0.141 + 0.059*SL
	t_{PLH}	0.254	0.207 + 0.024*SL	0.213 + 0.022*SL	0.215 + 0.022*SL
	t_{PHL}	0.295	0.236 + 0.029*SL	0.239 + 0.029*SL	0.241 + 0.028*SL
C to Y	t_R	0.251	0.162 + 0.044*SL	0.153 + 0.047*SL	0.141 + 0.048*SL
	t_F	0.271	0.159 + 0.056*SL	0.152 + 0.058*SL	0.146 + 0.059*SL
	t_{PLH}	0.176	0.131 + 0.023*SL	0.133 + 0.022*SL	0.133 + 0.022*SL
	t_{PHL}	0.176	0.117 + 0.030*SL	0.121 + 0.028*SL	0.123 + 0.028*SL
D to Y	t_R	0.273	0.184 + 0.044*SL	0.175 + 0.047*SL	0.164 + 0.048*SL
	t_F	0.265	0.151 + 0.057*SL	0.146 + 0.058*SL	0.142 + 0.059*SL
	t_{PLH}	0.189	0.144 + 0.022*SL	0.146 + 0.022*SL	0.147 + 0.022*SL
	t_{PHL}	0.177	0.119 + 0.029*SL	0.122 + 0.029*SL	0.123 + 0.028*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG15D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.166	0.120 + 0.023*SL	0.118 + 0.024*SL	0.111 + 0.024*SL
	t_F	0.192	0.134 + 0.029*SL	0.134 + 0.029*SL	0.130 + 0.029*SL
	t_{PLH}	0.265	0.237 + 0.014*SL	0.245 + 0.012*SL	0.253 + 0.011*SL
	t_{PHL}	0.267	0.236 + 0.016*SL	0.241 + 0.015*SL	0.246 + 0.014*SL
B to Y	t_R	0.165	0.118 + 0.023*SL	0.118 + 0.024*SL	0.111 + 0.024*SL
	t_F	0.194	0.137 + 0.029*SL	0.137 + 0.029*SL	0.131 + 0.029*SL
	t_{PLH}	0.260	0.232 + 0.014*SL	0.241 + 0.012*SL	0.249 + 0.011*SL
	t_{PHL}	0.284	0.252 + 0.016*SL	0.258 + 0.015*SL	0.263 + 0.014*SL
C to Y	t_R	0.193	0.151 + 0.021*SL	0.144 + 0.023*SL	0.130 + 0.024*SL
	t_F	0.198	0.143 + 0.027*SL	0.139 + 0.029*SL	0.132 + 0.029*SL
	t_{PLH}	0.143	0.118 + 0.013*SL	0.125 + 0.011*SL	0.126 + 0.011*SL
	t_{PHL}	0.134	0.101 + 0.017*SL	0.110 + 0.015*SL	0.113 + 0.014*SL
D to Y	t_R	0.215	0.173 + 0.021*SL	0.167 + 0.023*SL	0.151 + 0.024*SL
	t_F	0.190	0.134 + 0.028*SL	0.130 + 0.029*SL	0.127 + 0.029*SL
	t_{PLH}	0.159	0.135 + 0.012*SL	0.138 + 0.011*SL	0.140 + 0.011*SL
	t_{PHL}	0.139	0.106 + 0.016*SL	0.113 + 0.015*SL	0.117 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG16/SCG16D2

2-OR with one inverted input into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	Y
0	x	1	0
x	1	1	0
Other States			1

Cell Data

Input Load (SL)						Gate Count	
SCG16			*SCG16D2*			*SCG16*	*SCG16D2*
A	B	C	A	B	C		
0.8	1.0	1.0	0.8	2.0	2.1	2.00	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.334	0.181 + 0.076*SL	0.177 + 0.077*SL	0.175 + 0.078*SL
	t_F	0.267	0.142 + 0.063*SL	0.139 + 0.063*SL	0.135 + 0.064*SL
	t_{PLH}	0.271	0.200 + 0.035*SL	0.202 + 0.035*SL	0.204 + 0.035*SL
	t_{PHL}	0.280	0.217 + 0.032*SL	0.219 + 0.031*SL	0.221 + 0.031*SL
B to Y	t_R	0.345	0.195 + 0.075*SL	0.189 + 0.076*SL	0.182 + 0.077*SL
	t_F	0.319	0.201 + 0.059*SL	0.191 + 0.061*SL	0.180 + 0.063*SL
	t_{PLH}	0.213	0.141 + 0.036*SL	0.144 + 0.035*SL	0.145 + 0.035*SL
	t_{PHL}	0.219	0.157 + 0.031*SL	0.158 + 0.031*SL	0.159 + 0.031*SL
C to Y	t_R	0.226	0.157 + 0.034*SL	0.149 + 0.036*SL	0.138 + 0.038*SL
	t_F	0.309	0.187 + 0.061*SL	0.182 + 0.062*SL	0.175 + 0.063*SL
	t_{PLH}	0.158	0.121 + 0.019*SL	0.126 + 0.017*SL	0.126 + 0.017*SL
	t_{PHL}	0.230	0.166 + 0.032*SL	0.169 + 0.031*SL	0.171 + 0.031*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG16D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.247	0.172 + 0.038*SL	0.169 + 0.038*SL	0.163 + 0.039*SL
	t_F	0.202	0.139 + 0.031*SL	0.137 + 0.032*SL	0.131 + 0.032*SL
	t_{PLH}	0.256	0.220 + 0.018*SL	0.222 + 0.018*SL	0.224 + 0.017*SL
	t_{PHL}	0.275	0.241 + 0.017*SL	0.245 + 0.016*SL	0.249 + 0.016*SL
B to Y	t_R	0.257	0.183 + 0.037*SL	0.179 + 0.038*SL	0.170 + 0.039*SL
	t_F	0.249	0.193 + 0.028*SL	0.186 + 0.030*SL	0.172 + 0.031*SL
	t_{PLH}	0.172	0.134 + 0.019*SL	0.139 + 0.018*SL	0.141 + 0.017*SL
	t_{PHL}	0.181	0.150 + 0.016*SL	0.151 + 0.016*SL	0.153 + 0.015*SL
C to Y	t_R	0.182	0.149 + 0.017*SL	0.146 + 0.017*SL	0.132 + 0.019*SL
	t_F	0.237	0.177 + 0.030*SL	0.174 + 0.031*SL	0.166 + 0.031*SL
	t_{PLH}	0.134	0.112 + 0.011*SL	0.120 + 0.009*SL	0.122 + 0.009*SL
	t_{PHL}	0.188	0.156 + 0.016*SL	0.158 + 0.016*SL	0.161 + 0.016*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG17/SCG17D2

2-AND into 2-NOR into 2-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	Y
0	x	0	1	0
x	0	0	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG17				*SCG17D2*				*SCG17*	*SCG17D2*
A	B	C	D	A	B	C	D		
0.8	0.8	0.8	1.1	0.8	0.8	0.8	2.4	2.00	2.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG17

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.178	0.103 + 0.037*SL	0.103 + 0.037*SL	0.098 + 0.038*SL
	t_F	0.194	0.112 + 0.041*SL	0.115 + 0.040*SL	0.114 + 0.040*SL
	t_{PLH}	0.287	0.243 + 0.022*SL	0.255 + 0.019*SL	0.263 + 0.018*SL
	t_{PHL}	0.290	0.239 + 0.026*SL	0.252 + 0.022*SL	0.263 + 0.021*SL
B to Y	t_R	0.179	0.105 + 0.037*SL	0.103 + 0.038*SL	0.098 + 0.038*SL
	t_F	0.198	0.115 + 0.041*SL	0.119 + 0.040*SL	0.117 + 0.040*SL
	t_{PLH}	0.281	0.237 + 0.022*SL	0.249 + 0.019*SL	0.257 + 0.018*SL
	t_{PHL}	0.308	0.257 + 0.026*SL	0.271 + 0.022*SL	0.282 + 0.021*SL
C to Y	t_R	0.164	0.090 + 0.037*SL	0.086 + 0.038*SL	0.079 + 0.039*SL
	t_F	0.198	0.116 + 0.041*SL	0.119 + 0.040*SL	0.118 + 0.040*SL
	t_{PLH}	0.277	0.238 + 0.020*SL	0.245 + 0.018*SL	0.248 + 0.018*SL
	t_{PHL}	0.349	0.298 + 0.026*SL	0.311 + 0.022*SL	0.323 + 0.021*SL
D to Y	t_R	0.200	0.132 + 0.034*SL	0.124 + 0.036*SL	0.112 + 0.038*SL
	t_F	0.182	0.105 + 0.039*SL	0.098 + 0.040*SL	0.093 + 0.041*SL
	t_{PLH}	0.142	0.103 + 0.020*SL	0.112 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.126	0.079 + 0.024*SL	0.091 + 0.021*SL	0.093 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG17D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	0.114 + 0.020*SL	0.120 + 0.019*SL	0.119 + 0.019*SL
	t_F	0.161	0.117 + 0.022*SL	0.125 + 0.020*SL	0.130 + 0.020*SL
	t_{PLH}	0.317	0.290 + 0.014*SL	0.301 + 0.011*SL	0.319 + 0.009*SL
	t_{PHL}	0.313	0.283 + 0.015*SL	0.294 + 0.013*SL	0.314 + 0.011*SL
B to Y	t_R	0.155	0.115 + 0.020*SL	0.121 + 0.019*SL	0.119 + 0.019*SL
	t_F	0.165	0.121 + 0.022*SL	0.128 + 0.020*SL	0.135 + 0.020*SL
	t_{PLH}	0.312	0.284 + 0.014*SL	0.295 + 0.011*SL	0.313 + 0.009*SL
	t_{PHL}	0.331	0.300 + 0.015*SL	0.311 + 0.013*SL	0.332 + 0.011*SL
C to Y	t_R	0.133	0.098 + 0.018*SL	0.095 + 0.018*SL	0.089 + 0.019*SL
	t_F	0.165	0.121 + 0.022*SL	0.129 + 0.020*SL	0.134 + 0.020*SL
	t_{PLH}	0.290	0.266 + 0.012*SL	0.274 + 0.010*SL	0.283 + 0.009*SL
	t_{PHL}	0.373	0.342 + 0.015*SL	0.353 + 0.013*SL	0.374 + 0.011*SL
D to Y	t_R	0.162	0.131 + 0.016*SL	0.125 + 0.017*SL	0.111 + 0.019*SL
	t_F	0.138	0.100 + 0.019*SL	0.097 + 0.020*SL	0.092 + 0.020*SL
	t_{PLH}	0.117	0.094 + 0.012*SL	0.104 + 0.009*SL	0.109 + 0.009*SL
	t_{PHL}	0.097	0.070 + 0.013*SL	0.080 + 0.011*SL	0.090 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG18/SCG18D2

2-AND into 2-NOR into 3-NAND with 1X/2X Drive

Logic Symbol



Truth Table

A	B	C	D	E	Y
0	x	0	1	1	0
x	0	0	1	1	0
Other States					1

Cell Data

Input Load (SL)										Gate Count	
SCG18					*SCG18D2*					*SCG18*	*SCG18D2*
A	B	C	D	E	A	B	C	D	E		
0.8	0.8	0.8	1.0	1.0	0.8	0.8	0.8	2.1	2.2	2.33	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG18

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.227	0.134 + 0.046*SL	0.130 + 0.048*SL	0.124 + 0.048*SL
	t_F	0.283	0.165 + 0.059*SL	0.167 + 0.058*SL	0.163 + 0.059*SL
	t_{PLH}	0.314	0.264 + 0.025*SL	0.273 + 0.023*SL	0.279 + 0.022*SL
	t_{PHL}	0.327	0.263 + 0.032*SL	0.273 + 0.030*SL	0.279 + 0.029*SL
B to Y	t_R	0.227	0.134 + 0.047*SL	0.131 + 0.047*SL	0.124 + 0.048*SL
	t_F	0.286	0.168 + 0.059*SL	0.170 + 0.058*SL	0.166 + 0.059*SL
	t_{PLH}	0.308	0.258 + 0.025*SL	0.267 + 0.023*SL	0.273 + 0.022*SL
	t_{PHL}	0.346	0.281 + 0.032*SL	0.291 + 0.030*SL	0.298 + 0.029*SL
C to Y	t_R	0.212	0.117 + 0.047*SL	0.114 + 0.048*SL	0.108 + 0.049*SL
	t_F	0.286	0.168 + 0.059*SL	0.170 + 0.058*SL	0.166 + 0.059*SL
	t_{PLH}	0.303	0.256 + 0.023*SL	0.261 + 0.022*SL	0.263 + 0.022*SL
	t_{PHL}	0.386	0.322 + 0.032*SL	0.332 + 0.030*SL	0.339 + 0.029*SL
D to Y	t_R	0.248	0.160 + 0.044*SL	0.150 + 0.046*SL	0.139 + 0.048*SL
	t_F	0.273	0.159 + 0.057*SL	0.153 + 0.059*SL	0.148 + 0.059*SL
	t_{PLH}	0.174	0.130 + 0.022*SL	0.132 + 0.022*SL	0.132 + 0.022*SL
	t_{PHL}	0.177	0.116 + 0.030*SL	0.121 + 0.029*SL	0.123 + 0.029*SL
E to Y	t_R	0.273	0.184 + 0.044*SL	0.176 + 0.046*SL	0.164 + 0.048*SL
	t_F	0.266	0.150 + 0.058*SL	0.146 + 0.059*SL	0.143 + 0.060*SL
	t_{PLH}	0.189	0.144 + 0.022*SL	0.145 + 0.022*SL	0.147 + 0.022*SL
	t_{PHL}	0.181	0.121 + 0.030*SL	0.126 + 0.029*SL	0.128 + 0.029*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

2-AND into 2-NOR into 3-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG18D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.182	0.134 + 0.024*SL	0.136 + 0.023*SL	0.131 + 0.024*SL
	t_F	0.215	0.154 + 0.031*SL	0.159 + 0.029*SL	0.159 + 0.029*SL
	t_{PLH}	0.330	0.300 + 0.015*SL	0.310 + 0.013*SL	0.325 + 0.011*SL
	t_{PHL}	0.327	0.291 + 0.018*SL	0.300 + 0.016*SL	0.315 + 0.015*SL
B to Y	t_R	0.181	0.133 + 0.024*SL	0.137 + 0.023*SL	0.131 + 0.024*SL
	t_F	0.218	0.157 + 0.030*SL	0.162 + 0.029*SL	0.163 + 0.029*SL
	t_{PLH}	0.324	0.294 + 0.015*SL	0.304 + 0.013*SL	0.320 + 0.011*SL
	t_{PHL}	0.345	0.308 + 0.019*SL	0.318 + 0.016*SL	0.334 + 0.015*SL
C to Y	t_R	0.160	0.114 + 0.023*SL	0.112 + 0.023*SL	0.103 + 0.024*SL
	t_F	0.219	0.158 + 0.030*SL	0.163 + 0.029*SL	0.163 + 0.029*SL
	t_{PLH}	0.304	0.278 + 0.013*SL	0.284 + 0.012*SL	0.291 + 0.011*SL
	t_{PHL}	0.387	0.350 + 0.019*SL	0.360 + 0.016*SL	0.375 + 0.015*SL
D to Y	t_R	0.191	0.149 + 0.021*SL	0.142 + 0.022*SL	0.128 + 0.024*SL
	t_F	0.197	0.141 + 0.028*SL	0.136 + 0.029*SL	0.132 + 0.030*SL
	t_{PLH}	0.141	0.116 + 0.013*SL	0.123 + 0.011*SL	0.124 + 0.011*SL
	t_{PHL}	0.134	0.100 + 0.017*SL	0.109 + 0.015*SL	0.114 + 0.014*SL
E to Y	t_R	0.213	0.172 + 0.021*SL	0.165 + 0.022*SL	0.150 + 0.024*SL
	t_F	0.190	0.131 + 0.029*SL	0.129 + 0.030*SL	0.128 + 0.030*SL
	t_{PLH}	0.157	0.133 + 0.012*SL	0.136 + 0.011*SL	0.138 + 0.011*SL
	t_{PHL}	0.140	0.106 + 0.017*SL	0.113 + 0.015*SL	0.118 + 0.014*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	1	x	0
x	x	x	1	0
Other States				1

Cell Data

Input Load (SL)								Gate Count	
SCG19				*SCG19D2*				*SCG19*	*SCG19D2*
A	B	C	D	A	B	C	D		
0.8	0.8	0.9	0.9	0.9	0.8	1.8	2.1	2.67	3.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG19

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.294	0.139 + 0.078*SL	0.135 + 0.079*SL	0.135 + 0.079*SL
	t_F	0.237	0.106 + 0.065*SL	0.102 + 0.066*SL	0.099 + 0.067*SL
	t_{PLH}	0.341	0.269 + 0.036*SL	0.271 + 0.035*SL	0.272 + 0.035*SL
	t_{PHL}	0.349	0.281 + 0.034*SL	0.285 + 0.033*SL	0.287 + 0.033*SL
B to Y	t_R	0.294	0.139 + 0.078*SL	0.135 + 0.078*SL	0.135 + 0.079*SL
	t_F	0.237	0.106 + 0.065*SL	0.102 + 0.066*SL	0.098 + 0.067*SL
	t_{PLH}	0.361	0.290 + 0.036*SL	0.291 + 0.035*SL	0.293 + 0.035*SL
	t_{PHL}	0.343	0.276 + 0.034*SL	0.280 + 0.033*SL	0.282 + 0.033*SL
C to Y	t_R	0.339	0.193 + 0.073*SL	0.180 + 0.076*SL	0.164 + 0.078*SL
	t_F	0.247	0.120 + 0.063*SL	0.112 + 0.065*SL	0.104 + 0.066*SL
	t_{PLH}	0.193	0.123 + 0.035*SL	0.123 + 0.035*SL	0.123 + 0.035*SL
	t_{PHL}	0.173	0.105 + 0.034*SL	0.111 + 0.033*SL	0.112 + 0.033*SL
D to Y	t_R	0.328	0.177 + 0.076*SL	0.170 + 0.078*SL	0.162 + 0.079*SL
	t_F	0.221	0.148 + 0.036*SL	0.140 + 0.038*SL	0.131 + 0.039*SL
	t_{PLH}	0.231	0.158 + 0.036*SL	0.160 + 0.036*SL	0.162 + 0.035*SL
	t_{PHL}	0.184	0.141 + 0.022*SL	0.143 + 0.021*SL	0.145 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG19D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.234	0.158 + 0.038*SL	0.155 + 0.038*SL	0.148 + 0.039*SL
	t_F	0.189	0.125 + 0.032*SL	0.123 + 0.033*SL	0.116 + 0.033*SL
	t_{PLH}	0.365	0.327 + 0.019*SL	0.331 + 0.018*SL	0.334 + 0.018*SL
	t_{PHL}	0.361	0.324 + 0.018*SL	0.331 + 0.017*SL	0.337 + 0.016*SL
B to Y	t_R	0.234	0.159 + 0.038*SL	0.155 + 0.038*SL	0.148 + 0.039*SL
	t_F	0.189	0.125 + 0.032*SL	0.123 + 0.033*SL	0.116 + 0.033*SL
	t_{PLH}	0.385	0.347 + 0.019*SL	0.351 + 0.018*SL	0.354 + 0.018*SL
	t_{PHL}	0.356	0.319 + 0.018*SL	0.325 + 0.017*SL	0.331 + 0.016*SL
C to Y	t_R	0.270	0.199 + 0.036*SL	0.192 + 0.037*SL	0.174 + 0.039*SL
	t_F	0.191	0.129 + 0.031*SL	0.124 + 0.032*SL	0.115 + 0.033*SL
	t_{PLH}	0.161	0.124 + 0.018*SL	0.126 + 0.018*SL	0.126 + 0.018*SL
	t_{PHL}	0.142	0.105 + 0.019*SL	0.113 + 0.017*SL	0.116 + 0.016*SL
D to Y	t_R	0.258	0.184 + 0.037*SL	0.178 + 0.038*SL	0.168 + 0.039*SL
	t_F	0.184	0.149 + 0.017*SL	0.144 + 0.019*SL	0.133 + 0.020*SL
	t_{PLH}	0.191	0.153 + 0.019*SL	0.156 + 0.018*SL	0.158 + 0.018*SL
	t_{PHL}	0.160	0.137 + 0.011*SL	0.140 + 0.011*SL	0.142 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	Y
1	x	0	1
x	1	0	1
Other States			0

Cell Data

Input Load (SL)						Gate Count	
SCG20			*SCG20D2*			*SCG20*	*SCG20D2*
A	B	C	A	B	C		
0.8	0.8	1.0	0.8	0.8	2.1	1.67	2.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG20

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.274	0.124 + 0.075*SL	0.118 + 0.076*SL	0.115 + 0.077*SL
	t_F	0.156	0.089 + 0.034*SL	0.093 + 0.033*SL	0.089 + 0.033*SL
	t_{PLH}	0.246	0.176 + 0.035*SL	0.178 + 0.035*SL	0.179 + 0.034*SL
	t_{PHL}	0.276	0.229 + 0.024*SL	0.244 + 0.020*SL	0.256 + 0.018*SL
B to Y	t_R	0.275	0.125 + 0.075*SL	0.120 + 0.076*SL	0.116 + 0.077*SL
	t_F	0.155	0.086 + 0.034*SL	0.093 + 0.033*SL	0.091 + 0.033*SL
	t_{PLH}	0.268	0.198 + 0.035*SL	0.200 + 0.035*SL	0.201 + 0.035*SL
	t_{PHL}	0.285	0.238 + 0.024*SL	0.254 + 0.020*SL	0.265 + 0.018*SL
C to Y	t_R	0.286	0.140 + 0.073*SL	0.131 + 0.075*SL	0.124 + 0.076*SL
	t_F	0.178	0.121 + 0.028*SL	0.110 + 0.031*SL	0.099 + 0.033*SL
	t_{PLH}	0.184	0.113 + 0.036*SL	0.117 + 0.035*SL	0.118 + 0.034*SL
	t_{PHL}	0.139	0.099 + 0.020*SL	0.109 + 0.018*SL	0.110 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG20D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.190	0.117 + 0.037*SL	0.113 + 0.038*SL	0.106 + 0.038*SL
	t_F	0.133	0.094 + 0.019*SL	0.104 + 0.017*SL	0.111 + 0.016*SL
	t_{PLH}	0.235	0.198 + 0.018*SL	0.202 + 0.017*SL	0.204 + 0.017*SL
	t_{PHL}	0.300	0.269 + 0.015*SL	0.283 + 0.012*SL	0.306 + 0.010*SL
B to Y	t_R	0.193	0.119 + 0.037*SL	0.115 + 0.038*SL	0.108 + 0.038*SL
	t_F	0.134	0.097 + 0.019*SL	0.105 + 0.017*SL	0.110 + 0.016*SL
	t_{PLH}	0.255	0.218 + 0.019*SL	0.222 + 0.017*SL	0.224 + 0.017*SL
	t_{PHL}	0.310	0.280 + 0.015*SL	0.294 + 0.012*SL	0.317 + 0.010*SL
C to Y	t_R	0.202	0.131 + 0.035*SL	0.123 + 0.037*SL	0.114 + 0.038*SL
	t_F	0.145	0.117 + 0.014*SL	0.114 + 0.015*SL	0.098 + 0.016*SL
	t_{PLH}	0.141	0.101 + 0.020*SL	0.111 + 0.017*SL	0.113 + 0.017*SL
	t_{PHL}	0.112	0.087 + 0.012*SL	0.100 + 0.009*SL	0.105 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	x	0	0	1
x	1	0	0	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG21				*SCG21D2*				*SCG21*	*SCG21D2*
A	B	C	D	A	B	C	D		
0.8	0.8	0.9	0.9	0.8	0.8	1.9	2.0	2.00	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG21

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.452	0.221 + 0.115*SL	0.220 + 0.116*SL	0.222 + 0.115*SL
	t_F	0.191	0.107 + 0.042*SL	0.110 + 0.041*SL	0.105 + 0.042*SL
	t_{PLH}	0.305	0.199 + 0.053*SL	0.201 + 0.053*SL	0.203 + 0.052*SL
	t_{PHL}	0.307	0.253 + 0.027*SL	0.267 + 0.024*SL	0.276 + 0.023*SL
B to Y	t_R	0.453	0.222 + 0.115*SL	0.220 + 0.116*SL	0.223 + 0.115*SL
	t_F	0.192	0.108 + 0.042*SL	0.110 + 0.042*SL	0.106 + 0.042*SL
	t_{PLH}	0.327	0.221 + 0.053*SL	0.222 + 0.053*SL	0.225 + 0.052*SL
	t_{PHL}	0.317	0.262 + 0.027*SL	0.276 + 0.024*SL	0.286 + 0.023*SL
C to Y	t_R	0.468	0.244 + 0.112*SL	0.236 + 0.114*SL	0.228 + 0.115*SL
	t_F	0.212	0.136 + 0.038*SL	0.125 + 0.040*SL	0.114 + 0.042*SL
	t_{PLH}	0.272	0.166 + 0.053*SL	0.168 + 0.052*SL	0.170 + 0.052*SL
	t_{PHL}	0.170	0.124 + 0.023*SL	0.128 + 0.022*SL	0.129 + 0.022*SL
D to Y	t_R	0.464	0.239 + 0.113*SL	0.231 + 0.115*SL	0.226 + 0.115*SL
	t_F	0.243	0.167 + 0.038*SL	0.157 + 0.041*SL	0.146 + 0.042*SL
	t_{PLH}	0.292	0.186 + 0.053*SL	0.188 + 0.052*SL	0.190 + 0.052*SL
	t_{PHL}	0.182	0.135 + 0.024*SL	0.138 + 0.023*SL	0.142 + 0.023*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG21D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.305	0.190 + 0.057*SL	0.187 + 0.058*SL	0.185 + 0.058*SL
	t_F	0.154	0.108 + 0.023*SL	0.116 + 0.021*SL	0.117 + 0.021*SL
	t_{PLH}	0.262	0.209 + 0.026*SL	0.209 + 0.027*SL	0.211 + 0.026*SL
	t_{PHL}	0.317	0.283 + 0.017*SL	0.297 + 0.014*SL	0.319 + 0.012*SL
B to Y	t_R	0.307	0.193 + 0.057*SL	0.188 + 0.058*SL	0.186 + 0.058*SL
	t_F	0.154	0.108 + 0.023*SL	0.115 + 0.021*SL	0.117 + 0.021*SL
	t_{PLH}	0.282	0.229 + 0.026*SL	0.229 + 0.027*SL	0.231 + 0.026*SL
	t_{PHL}	0.328	0.293 + 0.017*SL	0.308 + 0.014*SL	0.329 + 0.012*SL
C to Y	t_R	0.323	0.213 + 0.055*SL	0.206 + 0.057*SL	0.195 + 0.058*SL
	t_F	0.163	0.127 + 0.018*SL	0.121 + 0.019*SL	0.106 + 0.021*SL
	t_{PLH}	0.203	0.148 + 0.028*SL	0.152 + 0.027*SL	0.155 + 0.026*SL
	t_{PHL}	0.136	0.109 + 0.013*SL	0.118 + 0.011*SL	0.120 + 0.011*SL
D to Y	t_R	0.317	0.206 + 0.056*SL	0.200 + 0.057*SL	0.191 + 0.058*SL
	t_F	0.193	0.158 + 0.018*SL	0.151 + 0.019*SL	0.137 + 0.021*SL
	t_{PLH}	0.224	0.170 + 0.027*SL	0.172 + 0.027*SL	0.175 + 0.026*SL
	t_{PHL}	0.149	0.123 + 0.013*SL	0.128 + 0.012*SL	0.133 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	C	D	Y
1	1	0	x	1
x	x	x	0	1
Other States				0

Cell Data

Input Load (SL)								Gate Count	
SCG22				*SCG22D2*				*SCG22*	*SCG22D2*
A	B	C	D	A	B	C	D		
0.8	0.9	1.0	1.0	0.8	0.9	2.0	2.0	2.00	3.00

2-NAND into 2-OR into 2-NAND with 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.338	0.186 + 0.076*SL	0.181 + 0.077*SL	0.177 + 0.078*SL
	t_F	0.271	0.145 + 0.063*SL	0.141 + 0.064*SL	0.136 + 0.065*SL
	t_{PLH}	0.296	0.223 + 0.036*SL	0.227 + 0.035*SL	0.229 + 0.035*SL
	t_{PHL}	0.302	0.237 + 0.033*SL	0.241 + 0.032*SL	0.242 + 0.032*SL
B to Y	t_R	0.338	0.185 + 0.076*SL	0.181 + 0.077*SL	0.176 + 0.078*SL
	t_F	0.271	0.144 + 0.064*SL	0.141 + 0.064*SL	0.137 + 0.065*SL
	t_{PLH}	0.293	0.220 + 0.036*SL	0.224 + 0.035*SL	0.226 + 0.035*SL
	t_{PHL}	0.315	0.250 + 0.033*SL	0.254 + 0.032*SL	0.256 + 0.032*SL
C to Y	t_R	0.343	0.192 + 0.075*SL	0.186 + 0.077*SL	0.179 + 0.078*SL
	t_F	0.320	0.200 + 0.060*SL	0.190 + 0.062*SL	0.178 + 0.064*SL
	t_{PLH}	0.212	0.140 + 0.036*SL	0.143 + 0.035*SL	0.144 + 0.035*SL
	t_{PHL}	0.220	0.156 + 0.032*SL	0.157 + 0.032*SL	0.159 + 0.031*SL
D to Y	t_R	0.224	0.155 + 0.034*SL	0.147 + 0.036*SL	0.136 + 0.038*SL
	t_F	0.311	0.187 + 0.062*SL	0.181 + 0.063*SL	0.174 + 0.064*SL
	t_{PLH}	0.158	0.120 + 0.019*SL	0.125 + 0.018*SL	0.126 + 0.017*SL
	t_{PHL}	0.231	0.166 + 0.032*SL	0.168 + 0.032*SL	0.171 + 0.032*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

SCG22D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.254	0.180 + 0.037*SL	0.177 + 0.038*SL	0.170 + 0.038*SL
	t_F	0.206	0.142 + 0.032*SL	0.141 + 0.032*SL	0.134 + 0.033*SL
	t_{PLH}	0.282	0.245 + 0.019*SL	0.249 + 0.018*SL	0.254 + 0.017*SL
	t_{PHL}	0.294	0.259 + 0.018*SL	0.264 + 0.017*SL	0.269 + 0.016*SL
B to Y	t_R	0.254	0.180 + 0.037*SL	0.177 + 0.038*SL	0.170 + 0.038*SL
	t_F	0.208	0.144 + 0.032*SL	0.143 + 0.032*SL	0.136 + 0.033*SL
	t_{PLH}	0.277	0.239 + 0.019*SL	0.244 + 0.018*SL	0.249 + 0.017*SL
	t_{PHL}	0.311	0.275 + 0.018*SL	0.280 + 0.017*SL	0.285 + 0.016*SL
C to Y	t_R	0.254	0.181 + 0.037*SL	0.177 + 0.038*SL	0.170 + 0.038*SL
	t_F	0.254	0.195 + 0.030*SL	0.189 + 0.031*SL	0.174 + 0.032*SL
	t_{PLH}	0.169	0.132 + 0.019*SL	0.137 + 0.018*SL	0.140 + 0.017*SL
	t_{PHL}	0.184	0.151 + 0.016*SL	0.152 + 0.016*SL	0.154 + 0.016*SL
D to Y	t_R	0.179	0.147 + 0.016*SL	0.142 + 0.017*SL	0.128 + 0.018*SL
	t_F	0.243	0.181 + 0.031*SL	0.177 + 0.032*SL	0.169 + 0.033*SL
	t_{PLH}	0.131	0.110 + 0.011*SL	0.118 + 0.009*SL	0.120 + 0.009*SL
	t_{PHL}	0.191	0.157 + 0.017*SL	0.159 + 0.016*SL	0.163 + 0.016*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL1D2	*DL1D4*	*DL1D2*	*DL1D4*
A	A		
0.7	0.7	4.00	4.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.103	0.068 + 0.018*SL	0.066 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.090	0.059 + 0.016*SL	0.060 + 0.015*SL	0.055 + 0.016*SL
	t_{PLH}	0.964	0.942 + 0.011*SL	0.951 + 0.009*SL	0.957 + 0.009*SL
	t_{PHL}	0.971	0.948 + 0.012*SL	0.957 + 0.009*SL	0.967 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL1D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	0.081 + 0.009*SL	0.080 + 0.009*SL	0.075 + 0.009*SL
	t_F	0.087	0.067 + 0.010*SL	0.075 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	1.001	0.987 + 0.007*SL	0.994 + 0.005*SL	1.010 + 0.004*SL
	t_{PHL}	1.004	0.989 + 0.007*SL	0.998 + 0.005*SL	1.016 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

DL2D2/DL2D4

2ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL2D2	*DL2D4*	*DL2D2*	*DL2D4*
A	A		
0.7	0.7	4.67	5.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.069 + 0.017*SL	0.066 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.094	0.063 + 0.015*SL	0.063 + 0.015*SL	0.058 + 0.016*SL
	t_{PLH}	1.957	1.934 + 0.011*SL	1.943 + 0.009*SL	1.950 + 0.009*SL
	t_{PHL}	1.956	1.932 + 0.012*SL	1.942 + 0.009*SL	1.953 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.082 + 0.009*SL	0.083 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.093	0.075 + 0.009*SL	0.079 + 0.008*SL	0.081 + 0.008*SL
	t_{PLH}	2.003	1.989 + 0.007*SL	1.996 + 0.005*SL	2.012 + 0.004*SL
	t_{PHL}	2.000	1.985 + 0.007*SL	1.993 + 0.005*SL	2.013 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL3D2	*DL3D4*	*DL3D2*	*DL3D4*
A	A		
0.7	0.7	5.33	6.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.069 + 0.018*SL	0.068 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.093	0.060 + 0.016*SL	0.064 + 0.015*SL	0.057 + 0.016*SL
	t_{PLH}	2.972	2.950 + 0.011*SL	2.959 + 0.009*SL	2.965 + 0.009*SL
	t_{PHL}	2.993	2.969 + 0.012*SL	2.979 + 0.009*SL	2.989 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL3D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.083 + 0.009*SL	0.082 + 0.009*SL	0.077 + 0.009*SL
	t_F	0.092	0.074 + 0.009*SL	0.078 + 0.008*SL	0.079 + 0.008*SL
	t_{PLH}	3.020	3.006 + 0.007*SL	3.014 + 0.005*SL	3.030 + 0.004*SL
	t_{PHL}	3.038	3.023 + 0.007*SL	3.031 + 0.005*SL	3.051 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

DL4D2/DL4D4

4ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL4D2	*DL4D4*	*DL4D2*	*DL4D4*
A	A		
0.7	0.7	6.00	6.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.069 + 0.018*SL	0.068 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.095	0.064 + 0.015*SL	0.064 + 0.015*SL	0.059 + 0.016*SL
	t_{PLH}	3.987	3.964 + 0.011*SL	3.973 + 0.009*SL	3.980 + 0.009*SL
	t_{PHL}	4.020	3.996 + 0.012*SL	4.006 + 0.009*SL	4.016 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.102	0.082 + 0.010*SL	0.087 + 0.009*SL	0.079 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.081 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	4.033	4.019 + 0.007*SL	4.026 + 0.005*SL	4.043 + 0.004*SL
	t_{PHL}	4.081	4.066 + 0.008*SL	4.074 + 0.005*SL	4.094 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL5D2	*DL5D4*	*DL5D2*	*DL5D4*
A	A		
0.7	0.7	6.67	7.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.069 + 0.017*SL	0.068 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.094	0.061 + 0.016*SL	0.067 + 0.015*SL	0.059 + 0.016*SL
	t_{PLH}	4.966	4.944 + 0.011*SL	4.953 + 0.009*SL	4.959 + 0.009*SL
	t_{PHL}	4.990	4.966 + 0.012*SL	4.977 + 0.009*SL	4.987 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL5D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.082 + 0.009*SL	0.083 + 0.009*SL	0.078 + 0.009*SL
	t_F	0.093	0.075 + 0.009*SL	0.079 + 0.008*SL	0.080 + 0.008*SL
	t_{PLH}	5.003	4.989 + 0.007*SL	4.996 + 0.005*SL	5.012 + 0.004*SL
	t_{PHL}	5.045	5.030 + 0.007*SL	5.038 + 0.005*SL	5.058 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

DL10D2/DL10D4

10ns Delay Cell with 2X/4X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
DL10D2	*DL10D4*	*DL10D2*	*DL2D4*
A	A	8.67	9.33
0.7	0.7		

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DL10D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	0.073 + 0.017*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.101	0.069 + 0.016*SL	0.072 + 0.015*SL	0.066 + 0.016*SL
	t_{PLH}	10.083	10.060 + 0.011*SL	10.070 + 0.009*SL	10.076 + 0.009*SL
	t_{PHL}	10.147	10.123 + 0.012*SL	10.133 + 0.010*SL	10.144 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

DL10D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.104	0.085 + 0.010*SL	0.088 + 0.009*SL	0.081 + 0.009*SL
	t_F	0.097	0.080 + 0.009*SL	0.083 + 0.008*SL	0.087 + 0.008*SL
	t_{PLH}	10.138	10.123 + 0.007*SL	10.132 + 0.005*SL	10.148 + 0.004*SL
	t_{PHL}	10.207	10.192 + 0.008*SL	10.200 + 0.006*SL	10.222 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

A	Y
0	1
1	0

Cell Data

Input Load (SL)							
IVDH	*IV*	*IVD2*	*IVD3*	*IVD4*	*IVD6*	*IVD8*	*IVD16*
A	A	A	A	A	A	A	A
0.5	1.0	2.0	2.9	3.9	5.9	7.9	15.9
Gate Count							
IVDH	*IV*	*IVD2*	*IVD3*	*IVD4*	*IVD6*	*IVD8*	*IVD16*
0.67	0.67	1.00	1.33	1.67	2.33	2.67	5.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.264	0.112 + 0.076*SL	0.090 + 0.081*SL	0.070 + 0.084*SL
	t_F	0.213	0.101 + 0.056*SL	0.079 + 0.061*SL	0.058 + 0.064*SL
	t_{PLH}	0.172	0.094 + 0.039*SL	0.100 + 0.037*SL	0.100 + 0.038*SL
	t_{PHL}	0.154	0.083 + 0.036*SL	0.093 + 0.033*SL	0.093 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

IV

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.175	0.108 + 0.033*SL	0.098 + 0.036*SL	0.086 + 0.037*SL
	t_F	0.151	0.096 + 0.027*SL	0.088 + 0.030*SL	0.075 + 0.031*SL
	t_{PLH}	0.117	0.073 + 0.022*SL	0.093 + 0.017*SL	0.094 + 0.017*SL
	t_{PHL}	0.113	0.068 + 0.022*SL	0.090 + 0.017*SL	0.091 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

IVD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.126	0.089 + 0.018*SL	0.094 + 0.017*SL	0.078 + 0.018*SL
	t_F	0.109	0.077 + 0.016*SL	0.086 + 0.014*SL	0.070 + 0.015*SL
	t_{PLH}	0.083	0.054 + 0.015*SL	0.073 + 0.010*SL	0.088 + 0.009*SL
	t_{PHL}	0.077	0.049 + 0.014*SL	0.067 + 0.010*SL	0.084 + 0.008*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

IVD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.117	0.091 + 0.013*SL	0.098 + 0.011*SL	0.077 + 0.012*SL
	t_F	0.102	0.078 + 0.012*SL	0.089 + 0.009*SL	0.068 + 0.011*SL
	t_{PLH}	0.076	0.055 + 0.010*SL	0.070 + 0.007*SL	0.089 + 0.006*SL
	t_{PHL}	0.072	0.051 + 0.010*SL	0.066 + 0.007*SL	0.086 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.114	0.093 + 0.010*SL	0.101 + 0.008*SL	0.085 + 0.009*SL
	t_F	0.099	0.080 + 0.009*SL	0.089 + 0.007*SL	0.075 + 0.008*SL
	t_{PLH}	0.073	0.057 + 0.008*SL	0.067 + 0.006*SL	0.090 + 0.004*SL
	t_{PHL}	0.070	0.053 + 0.008*SL	0.064 + 0.006*SL	0.087 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

IVD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.098	0.084 + 0.007*SL	0.089 + 0.006*SL	0.054 + 0.006*SL
	t_F	0.086	0.073 + 0.007*SL	0.080 + 0.005*SL	0.047 + 0.005*SL
	t_{PLH}	0.062	0.050 + 0.006*SL	0.061 + 0.003*SL	0.087 + 0.003*SL
	t_{PHL}	0.057	0.045 + 0.006*SL	0.057 + 0.003*SL	0.084 + 0.003*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.096	0.084 + 0.006*SL	0.090 + 0.004*SL	0.064 + 0.005*SL
	t_F	0.083	0.072 + 0.005*SL	0.079 + 0.004*SL	0.056 + 0.004*SL
	t_{PLH}	0.059	0.049 + 0.005*SL	0.058 + 0.003*SL	0.087 + 0.002*SL
	t_{PHL}	0.055	0.045 + 0.005*SL	0.054 + 0.003*SL	0.084 + 0.002*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVD16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	0.084 + 0.003*SL	0.086 + 0.002*SL	0.082 + 0.002*SL
	t_F	0.077	0.072 + 0.003*SL	0.075 + 0.002*SL	0.075 + 0.002*SL
	t_{PLH}	0.054	0.049 + 0.003*SL	0.053 + 0.002*SL	0.086 + 0.001*SL
	t_{PHL}	0.050	0.045 + 0.003*SL	0.048 + 0.002*SL	0.083 + 0.001*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVCD(11/13)/IVCD(22/26)/IVCD44

1X IV into (1X/3X) IV/2X IV into (2X/6X) IV/4X IV into 4X IV

Logic Symbol



Truth Table

A	Y	YN
1	0	1
0	1	0

Cell Data

Input Load (SL)					Gate Count				
IVCD11	*IVCD13*	*IVCD22*	*IVCD26*	*IVCD44*	*IVCD11*	*IVCD13*	*IVCD22*	*IVCD26*	*IVCD44*
A	A	A	A	A					
1.0	1.0	2.0	1.9	3.8	1.00	1.67	1.67	2.67	3.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVCD11

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.220	0.154 + 0.033*SL	0.143 + 0.036*SL	0.130 + 0.038*SL
	t_F	0.192	0.133 + 0.029*SL	0.126 + 0.031*SL	0.115 + 0.033*SL
	t_{PLH}	0.142	0.102 + 0.020*SL	0.112 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.139	0.099 + 0.020*SL	0.109 + 0.018*SL	0.109 + 0.018*SL
Y to YN	t_R	0.149	0.095 + 0.027*SL	0.088 + 0.029*SL	0.074 + 0.031*SL
	t_F	0.175	0.108 + 0.033*SL	0.098 + 0.036*SL	0.086 + 0.037*SL
	t_{PLH}	0.112	0.068 + 0.022*SL	0.089 + 0.017*SL	0.091 + 0.017*SL
	t_{PHL}	0.118	0.073 + 0.022*SL	0.093 + 0.017*SL	0.094 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

IVCD13

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.292	0.223 + 0.035*SL	0.210 + 0.038*SL	0.179 + 0.039*SL
	t_F	0.252	0.198 + 0.027*SL	0.182 + 0.031*SL	0.150 + 0.033*SL
	t_{PLH}	0.180	0.144 + 0.018*SL	0.145 + 0.018*SL	0.147 + 0.017*SL
	t_{PHL}	0.169	0.134 + 0.017*SL	0.136 + 0.017*SL	0.137 + 0.017*SL
Y to YN	t_R	0.102	0.078 + 0.012*SL	0.089 + 0.009*SL	0.068 + 0.011*SL
	t_F	0.117	0.091 + 0.013*SL	0.098 + 0.011*SL	0.077 + 0.012*SL
	t_{PLH}	0.072	0.051 + 0.010*SL	0.066 + 0.007*SL	0.086 + 0.006*SL
	t_{PHL}	0.076	0.055 + 0.010*SL	0.070 + 0.007*SL	0.089 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVCD22

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.170	0.139 + 0.016*SL	0.132 + 0.017*SL	0.118 + 0.019*SL
	t_F	0.149	0.122 + 0.013*SL	0.118 + 0.014*SL	0.104 + 0.015*SL
	t_{PLH}	0.111	0.087 + 0.012*SL	0.099 + 0.009*SL	0.105 + 0.009*SL
	t_{PHL}	0.104	0.079 + 0.012*SL	0.092 + 0.009*SL	0.100 + 0.008*SL
Y to YN	t_R	0.110	0.078 + 0.016*SL	0.087 + 0.014*SL	0.070 + 0.015*SL
	t_F	0.126	0.090 + 0.018*SL	0.095 + 0.017*SL	0.078 + 0.018*SL
	t_{PLH}	0.078	0.049 + 0.014*SL	0.068 + 0.010*SL	0.084 + 0.008*SL
	t_{PHL}	0.083	0.054 + 0.015*SL	0.073 + 0.010*SL	0.088 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

IVCD26

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.248	0.217 + 0.016*SL	0.204 + 0.019*SL	0.161 + 0.020*SL
	t_F	0.216	0.189 + 0.014*SL	0.179 + 0.016*SL	0.136 + 0.017*SL
	t_{PLH}	0.154	0.135 + 0.010*SL	0.138 + 0.009*SL	0.141 + 0.009*SL
	t_{PHL}	0.144	0.124 + 0.010*SL	0.129 + 0.008*SL	0.131 + 0.008*SL
Y to YN	t_R	0.087	0.073 + 0.007*SL	0.080 + 0.005*SL	0.047 + 0.005*SL
	t_F	0.098	0.084 + 0.007*SL	0.089 + 0.006*SL	0.055 + 0.006*SL
	t_{PLH}	0.058	0.046 + 0.006*SL	0.057 + 0.003*SL	0.084 + 0.003*SL
	t_{PHL}	0.062	0.050 + 0.006*SL	0.061 + 0.003*SL	0.087 + 0.003*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVCD44

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.153	0.137 + 0.008*SL	0.136 + 0.008*SL	0.119 + 0.009*SL
	t_F	0.134	0.119 + 0.008*SL	0.122 + 0.007*SL	0.106 + 0.008*SL
	t_{PLH}	0.097	0.084 + 0.007*SL	0.091 + 0.005*SL	0.104 + 0.004*SL
	t_{PHL}	0.091	0.078 + 0.007*SL	0.085 + 0.005*SL	0.100 + 0.004*SL
Y to YN	t_R	0.092	0.074 + 0.009*SL	0.082 + 0.007*SL	0.072 + 0.008*SL
	t_F	0.105	0.083 + 0.011*SL	0.094 + 0.008*SL	0.080 + 0.009*SL
	t_{PLH}	0.063	0.046 + 0.009*SL	0.058 + 0.006*SL	0.084 + 0.004*SL
	t_{PHL}	0.067	0.050 + 0.009*SL	0.062 + 0.006*SL	0.087 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

IVT/IVTD2/IVTD4/IVTD8/IVTD16

Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	E	Y
x	0	Hi-Z
0	1	1
1	1	0

Cell Data

Input Load (SL)										Output Load (SL)				
IVT		*IVTD2*		*IVTD4*		*IVTD8*		*IVTD16*		*IVT*	*IVTD2*	*IVTD4*	*IVTD8*	*IVTD16*
A	E	A	E	A	E	A	E	A	E	Y	Y	Y	Y	Y
0.5	1.3	0.5	1.3	0.5	1.3	1.0	3.0	1.0	3.0	0.9	1.1	2.2	4.4	8.5

Gate Count				
IVT	*IVTD2*	*IVTD4*	*IVTD8*	*IVTD16*
3.00	3.33	3.67	6.00	8.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.150	0.075 + 0.037*SL	0.071 + 0.038*SL	0.068 + 0.039*SL
	t_F	0.144	0.076 + 0.034*SL	0.080 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.359	0.318 + 0.020*SL	0.327 + 0.018*SL	0.331 + 0.018*SL
	t_{PHL}	0.382	0.336 + 0.023*SL	0.351 + 0.020*SL	0.361 + 0.018*SL
E to Y	t_R	0.177	0.092 + 0.043*SL	0.087 + 0.044*SL	0.079 + 0.045*SL
	t_F	0.164	0.089 + 0.037*SL	0.095 + 0.036*SL	0.090 + 0.037*SL
	t_{PLH}	0.199	0.158 + 0.021*SL	0.167 + 0.018*SL	0.171 + 0.018*SL
	t_{PHL}	0.316	0.268 + 0.024*SL	0.283 + 0.020*SL	0.294 + 0.019*SL
	t_{PLZ}	0.256	0.256 + 0.000*SL	0.256 + 0.000*SL	0.256 + 0.000*SL
	t_{PHZ}	0.189	0.189 + 0.000*SL	0.189 + 0.000*SL	0.189 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

IVTD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.068 + 0.020*SL	0.071 + 0.019*SL	0.067 + 0.019*SL
	t_F	0.103	0.065 + 0.019*SL	0.074 + 0.017*SL	0.078 + 0.017*SL
	t_{PLH}	0.352	0.326 + 0.013*SL	0.338 + 0.010*SL	0.351 + 0.009*SL
	t_{PHL}	0.364	0.334 + 0.015*SL	0.349 + 0.011*SL	0.370 + 0.009*SL
E to Y	t_R	0.119	0.079 + 0.020*SL	0.080 + 0.020*SL	0.074 + 0.021*SL
	t_F	0.116	0.077 + 0.020*SL	0.085 + 0.018*SL	0.088 + 0.017*SL
	t_{PLH}	0.192	0.165 + 0.013*SL	0.179 + 0.010*SL	0.191 + 0.009*SL
	t_{PHL}	0.294	0.263 + 0.015*SL	0.280 + 0.011*SL	0.301 + 0.010*SL
	t_{PLZ}	0.272	0.272 + 0.000*SL	0.272 + 0.000*SL	0.272 + 0.000*SL
	t_{PHZ}	0.225	0.224 + 0.000*SL	0.225 + 0.000*SL	0.225 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVTD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.102	0.079 + 0.011*SL	0.086 + 0.010*SL	0.092 + 0.009*SL
	t_F	0.095	0.075 + 0.010*SL	0.080 + 0.009*SL	0.097 + 0.008*SL
	t_{PLH}	0.377	0.360 + 0.009*SL	0.370 + 0.006*SL	0.395 + 0.005*SL
	t_{PHL}	0.382	0.364 + 0.009*SL	0.374 + 0.006*SL	0.403 + 0.005*SL
E to Y	t_R	0.111	0.087 + 0.012*SL	0.095 + 0.010*SL	0.097 + 0.010*SL
	t_F	0.106	0.083 + 0.012*SL	0.094 + 0.009*SL	0.109 + 0.008*SL
	t_{PLH}	0.215	0.197 + 0.009*SL	0.210 + 0.006*SL	0.236 + 0.005*SL
	t_{PHL}	0.312	0.292 + 0.010*SL	0.305 + 0.007*SL	0.338 + 0.005*SL
	t_{PLZ}	0.305	0.304 + 0.000*SL	0.305 + 0.000*SL	0.305 + 0.000*SL
	t_{PHZ}	0.293	0.293 + 0.000*SL	0.293 + 0.000*SL	0.294 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

IVTD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	0.068 + 0.006*SL	0.072 + 0.005*SL	0.066 + 0.005*SL
	t_F	0.074	0.064 + 0.005*SL	0.067 + 0.004*SL	0.075 + 0.004*SL
	t_{PLH}	0.339	0.331 + 0.004*SL	0.337 + 0.003*SL	0.362 + 0.002*SL
	t_{PHL}	0.362	0.353 + 0.004*SL	0.359 + 0.003*SL	0.396 + 0.002*SL
E to Y	t_R	0.086	0.074 + 0.006*SL	0.078 + 0.005*SL	0.068 + 0.005*SL
	t_F	0.079	0.068 + 0.006*SL	0.074 + 0.004*SL	0.080 + 0.004*SL
	t_{PLH}	0.170	0.161 + 0.005*SL	0.169 + 0.003*SL	0.197 + 0.002*SL
	t_{PHL}	0.278	0.269 + 0.005*SL	0.277 + 0.003*SL	0.317 + 0.002*SL
	t_{PLZ}	0.304	0.304 + 0.000*SL	0.304 + 0.000*SL	0.304 + 0.000*SL
	t_{PHZ}	0.230	0.230 + 0.000*SL	0.230 + 0.000*SL	0.231 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVTD16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	0.083 + 0.004*SL	0.087 + 0.003*SL	0.103 + 0.002*SL
	t_F	0.090	0.086 + 0.002*SL	0.086 + 0.002*SL	0.103 + 0.002*SL
	t_{PLH}	0.387	0.382 + 0.002*SL	0.385 + 0.002*SL	0.418 + 0.001*SL
	t_{PHL}	0.410	0.405 + 0.002*SL	0.408 + 0.002*SL	0.437 + 0.001*SL
E to Y	t_R	0.097	0.090 + 0.003*SL	0.093 + 0.003*SL	0.108 + 0.002*SL
	t_F	0.090	0.082 + 0.004*SL	0.089 + 0.002*SL	0.112 + 0.002*SL
	t_{PLH}	0.214	0.207 + 0.003*SL	0.213 + 0.002*SL	0.252 + 0.001*SL
	t_{PHL}	0.311	0.305 + 0.003*SL	0.310 + 0.002*SL	0.353 + 0.001*SL
	t_{PLZ}	0.355	0.355 + 0.000*SL	0.355 + 0.000*SL	0.355 + 0.000*SL
	t_{PHZ}	0.327	0.327 + 0.000*SL	0.328 + 0.000*SL	0.329 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVTN/IVTND2/IVTND4/IVTND8/IVTND16

Inverting Tri-State Buffer with Enable Low, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	EN	Y
x	1	Hi-Z
0	0	1
1	0	0

Cell Data

Input Load (SL)										Output Load (SL)				
IVTN		*IVTND2*		*IVTND4*		*IVTND8*		*IVTND16*		*IVTN*	*IVTND2*	*IVTND4*	*IVTND8*	*IVTND16*
A	EN	A	EN	A	EN	A	EN	A	EN	Y	Y	Y	Y	Y
0.5	1.1	0.5	1.1	0.5	1.1	1.0	2.1	1.0	2.1	0.9	1.1	2.2	4.4	8.4

Gate Count				
IVTN	*IVTND2*	*IVTND4*	*IVTND8*	*IVTND16*
3.00	3.33	3.67	6.00	8.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVTN

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.151	0.076 + 0.037*SL	0.073 + 0.038*SL	0.069 + 0.039*SL
	t_F	0.143	0.075 + 0.034*SL	0.080 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.361	0.320 + 0.020*SL	0.329 + 0.018*SL	0.333 + 0.018*SL
	t_{PHL}	0.378	0.332 + 0.023*SL	0.347 + 0.020*SL	0.357 + 0.018*SL
EN to Y	t_R	0.176	0.090 + 0.043*SL	0.085 + 0.044*SL	0.079 + 0.045*SL
	t_F	0.166	0.094 + 0.036*SL	0.094 + 0.036*SL	0.090 + 0.037*SL
	t_{PLH}	0.312	0.270 + 0.021*SL	0.280 + 0.019*SL	0.283 + 0.018*SL
	t_{PHL}	0.236	0.189 + 0.024*SL	0.204 + 0.020*SL	0.214 + 0.019*SL
	t_{PLZ}	0.140	0.140 + 0.000*SL	0.140 + 0.000*SL	0.140 + 0.000*SL
	t_{PHZ}	0.266	0.266 + 0.000*SL	0.266 + 0.000*SL	0.266 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

IVTND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.108	0.068 + 0.020*SL	0.073 + 0.019*SL	0.068 + 0.019*SL
	t_F	0.103	0.065 + 0.019*SL	0.074 + 0.017*SL	0.077 + 0.017*SL
	t_{PLH}	0.353	0.327 + 0.013*SL	0.339 + 0.010*SL	0.352 + 0.009*SL
	t_{PHL}	0.360	0.330 + 0.015*SL	0.345 + 0.011*SL	0.366 + 0.009*SL
EN to Y	t_R	0.118	0.077 + 0.021*SL	0.080 + 0.020*SL	0.074 + 0.021*SL
	t_F	0.116	0.077 + 0.019*SL	0.086 + 0.017*SL	0.088 + 0.017*SL
	t_{PLH}	0.303	0.276 + 0.013*SL	0.289 + 0.010*SL	0.302 + 0.009*SL
	t_{PHL}	0.215	0.185 + 0.015*SL	0.201 + 0.011*SL	0.222 + 0.010*SL
	t_{PLZ}	0.158	0.158 + 0.000*SL	0.158 + 0.000*SL	0.158 + 0.000*SL
	t_{PHZ}	0.302	0.302 + 0.000*SL	0.302 + 0.000*SL	0.302 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

IVTND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.103	0.080 + 0.011*SL	0.087 + 0.010*SL	0.094 + 0.009*SL
	t_F	0.096	0.075 + 0.010*SL	0.081 + 0.009*SL	0.098 + 0.008*SL
	t_{PLH}	0.381	0.364 + 0.009*SL	0.374 + 0.006*SL	0.400 + 0.005*SL
	t_{PHL}	0.381	0.364 + 0.009*SL	0.373 + 0.006*SL	0.402 + 0.005*SL
EN to Y	t_R	0.112	0.089 + 0.012*SL	0.096 + 0.010*SL	0.098 + 0.010*SL
	t_F	0.107	0.084 + 0.012*SL	0.095 + 0.009*SL	0.109 + 0.008*SL
	t_{PLH}	0.326	0.307 + 0.009*SL	0.320 + 0.006*SL	0.346 + 0.005*SL
	t_{PHL}	0.229	0.209 + 0.010*SL	0.223 + 0.007*SL	0.255 + 0.005*SL
	t_{PLZ}	0.193	0.193 + 0.000*SL	0.193 + 0.000*SL	0.193 + 0.000*SL
	t_{PHZ}	0.370	0.370 + 0.000*SL	0.370 + 0.000*SL	0.371 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

IVTND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.080	0.069 + 0.006*SL	0.072 + 0.005*SL	0.068 + 0.005*SL
	t_F	0.073	0.061 + 0.006*SL	0.069 + 0.004*SL	0.075 + 0.004*SL
	t_{PLH}	0.345	0.337 + 0.004*SL	0.342 + 0.003*SL	0.369 + 0.002*SL
	t_{PHL}	0.358	0.350 + 0.004*SL	0.356 + 0.003*SL	0.392 + 0.002*SL
EN to Y	t_R	0.086	0.075 + 0.006*SL	0.079 + 0.005*SL	0.070 + 0.005*SL
	t_F	0.083	0.073 + 0.005*SL	0.076 + 0.004*SL	0.081 + 0.004*SL
	t_{PLH}	0.312	0.303 + 0.005*SL	0.310 + 0.003*SL	0.340 + 0.002*SL
	t_{PHL}	0.179	0.170 + 0.005*SL	0.178 + 0.003*SL	0.218 + 0.002*SL
	t_{PLZ}	0.164	0.164 + 0.000*SL	0.164 + 0.000*SL	0.164 + 0.000*SL
	t_{PHZ}	0.342	0.342 + 0.000*SL	0.342 + 0.000*SL	0.342 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

IVTND16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	0.083 + 0.003*SL	0.087 + 0.003*SL	0.104 + 0.002*SL
	t_F	0.090	0.084 + 0.003*SL	0.086 + 0.002*SL	0.102 + 0.002*SL
	t_{PLH}	0.390	0.384 + 0.003*SL	0.388 + 0.002*SL	0.421 + 0.001*SL
	t_{PHL}	0.406	0.402 + 0.002*SL	0.405 + 0.002*SL	0.433 + 0.001*SL
EN to Y	t_R	0.099	0.092 + 0.004*SL	0.096 + 0.003*SL	0.109 + 0.002*SL
	t_F	0.091	0.086 + 0.003*SL	0.087 + 0.002*SL	0.113 + 0.002*SL
	t_{PLH}	0.353	0.347 + 0.003*SL	0.352 + 0.002*SL	0.392 + 0.001*SL
	t_{PHL}	0.214	0.208 + 0.003*SL	0.213 + 0.002*SL	0.257 + 0.001*SL
	t_{PLZ}	0.216	0.216 + 0.000*SL	0.216 + 0.000*SL	0.216 + 0.000*SL
	t_{PHZ}	0.439	0.439 + 0.000*SL	0.439 + 0.000*SL	0.440 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

NIDH/NID/NID2/NID3/NID4/NID6/NID8/NID16

Non-Inverting Buffer with 0.5X/1X/2X/3X/4X/6X/8X/16X Drive

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)							
NIDH	*NID*	*NID2*	*NID3*	*NID4*	*NID6*	*NID8*	*NID16*
A	A	A	A	A	A	A	A
0.6	0.6	0.7	0.8	1.0	1.4	1.9	3.9
Gate Count							
NIDH	*NID*	*NID2*	*NID3*	*NID4*	*NID6*	*NID8*	*NID16*
1.00	1.00	1.33	1.67	2.00	2.67	3.33	6.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NIDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.254	0.082 + 0.086*SL	0.073 + 0.088*SL	0.069 + 0.089*SL
	t_F	0.198	0.074 + 0.062*SL	0.067 + 0.064*SL	0.060 + 0.065*SL
	t_{PLH}	0.250	0.170 + 0.040*SL	0.172 + 0.039*SL	0.173 + 0.039*SL
	t_{PHL}	0.260	0.189 + 0.035*SL	0.197 + 0.033*SL	0.199 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NID

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	0.084 + 0.035*SL	0.075 + 0.037*SL	0.071 + 0.038*SL
	t_F	0.137	0.076 + 0.031*SL	0.074 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.220	0.182 + 0.019*SL	0.188 + 0.017*SL	0.190 + 0.017*SL
	t_{PHL}	0.233	0.194 + 0.020*SL	0.203 + 0.017*SL	0.207 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.110	0.072 + 0.019*SL	0.075 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.224	0.200 + 0.012*SL	0.210 + 0.010*SL	0.219 + 0.009*SL
	t_{PHL}	0.229	0.204 + 0.012*SL	0.215 + 0.010*SL	0.229 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NID3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.103	0.077 + 0.013*SL	0.080 + 0.012*SL	0.070 + 0.013*SL
	t_F	0.094	0.068 + 0.013*SL	0.077 + 0.011*SL	0.071 + 0.011*SL
	t_{PLH}	0.220	0.203 + 0.009*SL	0.212 + 0.007*SL	0.224 + 0.006*SL
	t_{PHL}	0.229	0.211 + 0.009*SL	0.220 + 0.007*SL	0.237 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NID4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	0.074 + 0.010*SL	0.076 + 0.009*SL	0.071 + 0.009*SL
	t_F	0.084	0.065 + 0.010*SL	0.073 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.218	0.204 + 0.007*SL	0.211 + 0.005*SL	0.225 + 0.004*SL
	t_{PHL}	0.222	0.208 + 0.007*SL	0.216 + 0.005*SL	0.234 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

NID6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	0.074 + 0.006*SL	0.072 + 0.006*SL	0.055 + 0.006*SL
	t_F	0.076	0.063 + 0.007*SL	0.068 + 0.005*SL	0.058 + 0.005*SL
	t_{PLH}	0.202	0.192 + 0.005*SL	0.199 + 0.003*SL	0.217 + 0.003*SL
	t_{PHL}	0.212	0.202 + 0.005*SL	0.209 + 0.003*SL	0.236 + 0.003*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

NID8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.081	0.074 + 0.004*SL	0.070 + 0.005*SL	0.057 + 0.005*SL
	t_F	0.071	0.061 + 0.005*SL	0.065 + 0.004*SL	0.060 + 0.004*SL
	t_{PLH}	0.196	0.188 + 0.004*SL	0.194 + 0.002*SL	0.212 + 0.002*SL
	t_{PHL}	0.203	0.195 + 0.004*SL	0.201 + 0.002*SL	0.227 + 0.002*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

NID16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.076	0.068 + 0.004*SL	0.075 + 0.002*SL	0.066 + 0.002*SL
	t_F	0.066	0.060 + 0.003*SL	0.063 + 0.002*SL	0.068 + 0.002*SL
	t_{PLH}	0.189	0.186 + 0.002*SL	0.187 + 0.001*SL	0.204 + 0.001*SL
	t_{PHL}	0.199	0.195 + 0.002*SL	0.197 + 0.001*SL	0.219 + 0.001*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)		Gate Count	
OAK_NID10P	*OAK_NID20P*	*OAK_NID10P*	*OAK_NID20P*
A	A		
1.0	2.0	23.24	43.70

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OAK_NID10P

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	0.088 + 0.001*SL	0.076 + 0.001*SL	0.069 + 0.001*SL
	t_F	0.074	0.073 + 0.001*SL	0.066 + 0.001*SL	0.060 + 0.001*SL
	t_{PLH}	0.529	0.528 + 0.000*SL	0.542 + 0.000*SL	0.544 + 0.000*SL
	t_{PHL}	0.469	0.468 + 0.000*SL	0.481 + 0.000*SL	0.483 + 0.000*SL

*Group1 : SL < 627, *Group2 : 627 ≦ SL ≦ 940, *Group3 : 940 < SL

OAK_NID20P

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.089	0.088 + 0.000*SL	0.082 + 0.000*SL	0.072 + 0.000*SL
	t_F	0.068	0.067 + 0.000*SL	0.062 + 0.000*SL	0.055 + 0.000*SL
	t_{PLH}	0.503	0.503 + 0.000*SL	0.522 + 0.000*SL	0.528 + 0.000*SL
	t_{PHL}	0.435	0.435 + 0.000*SL	0.450 + 0.000*SL	0.454 + 0.000*SL

*Group1 : SL < 784, *Group2 : 784 ≦ SL ≦ 1567, *Group3 : 1567 < SL

NIT/NITD2/NITD4/NITD8/NITD16

Non-Inverting Tri-State Buffer with Enable High, 1X/2X/4X/8X/16X Drive

Logic Symbol



Truth Table

A	E	Y
x	0	Hi-Z
0	1	0
1	1	1

Cell Data

Input Load (SL)										Output Load (SL)				
NIT		*NITD2*		*NITD4*		*NITD8*		*NITD16*		*NIT*	*NITD2*	*NITD4*	*NITD8*	*NITD16*
A	E	A	E	A	E	A	E	A	E	Y	Y	Y	Y	Y
1.7	1.2	1.7	1.2	1.7	1.2	4.6	2.5	4.6	2.5	0.9	1.1	2.2	4.4	8.5

Gate Count				
NIT	*NITD2*	*NITD4*	*NITD8*	*NITD16*
2.67	3.00	3.33	5.67	8.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.149	0.075 + 0.037*SL	0.073 + 0.038*SL	0.066 + 0.039*SL
	t_F	0.143	0.074 + 0.034*SL	0.081 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.194	0.154 + 0.020*SL	0.163 + 0.018*SL	0.166 + 0.017*SL
	t_{PHL}	0.249	0.202 + 0.023*SL	0.217 + 0.020*SL	0.228 + 0.018*SL
E to Y	t_R	0.177	0.091 + 0.043*SL	0.086 + 0.044*SL	0.079 + 0.045*SL
	t_F	0.164	0.090 + 0.037*SL	0.094 + 0.036*SL	0.090 + 0.037*SL
	t_{PLH}	0.199	0.157 + 0.021*SL	0.167 + 0.018*SL	0.170 + 0.018*SL
	t_{PHL}	0.315	0.268 + 0.024*SL	0.282 + 0.020*SL	0.293 + 0.019*SL
	t_{PLZ}	0.254	0.254 + 0.000*SL	0.254 + 0.000*SL	0.254 + 0.000*SL
	t_{PHZ}	0.189	0.189 + 0.000*SL	0.189 + 0.000*SL	0.189 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NITD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.106	0.066 + 0.020*SL	0.070 + 0.019*SL	0.065 + 0.019*SL
	t_F	0.101	0.063 + 0.019*SL	0.074 + 0.017*SL	0.078 + 0.016*SL
	t_{PLH}	0.187	0.162 + 0.013*SL	0.173 + 0.010*SL	0.185 + 0.009*SL
	t_{PHL}	0.232	0.202 + 0.015*SL	0.217 + 0.011*SL	0.237 + 0.009*SL
E to Y	t_R	0.119	0.080 + 0.020*SL	0.079 + 0.020*SL	0.073 + 0.021*SL
	t_F	0.115	0.076 + 0.019*SL	0.083 + 0.017*SL	0.089 + 0.017*SL
	t_{PLH}	0.191	0.164 + 0.013*SL	0.177 + 0.010*SL	0.190 + 0.009*SL
	t_{PHL}	0.294	0.263 + 0.015*SL	0.279 + 0.011*SL	0.300 + 0.009*SL
	t_{PLZ}	0.268	0.268 + 0.000*SL	0.268 + 0.000*SL	0.268 + 0.000*SL
	t_{PHZ}	0.222	0.222 + 0.000*SL	0.222 + 0.000*SL	0.222 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NITD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.099	0.075 + 0.012*SL	0.084 + 0.010*SL	0.089 + 0.009*SL
	t_F	0.095	0.072 + 0.011*SL	0.083 + 0.009*SL	0.099 + 0.008*SL
	t_{PLH}	0.213	0.196 + 0.008*SL	0.206 + 0.006*SL	0.229 + 0.005*SL
	t_{PHL}	0.253	0.236 + 0.009*SL	0.245 + 0.006*SL	0.274 + 0.005*SL
E to Y	t_R	0.111	0.087 + 0.012*SL	0.095 + 0.010*SL	0.097 + 0.010*SL
	t_F	0.107	0.085 + 0.011*SL	0.095 + 0.009*SL	0.111 + 0.008*SL
	t_{PLH}	0.214	0.196 + 0.009*SL	0.208 + 0.006*SL	0.234 + 0.005*SL
	t_{PHL}	0.308	0.288 + 0.010*SL	0.302 + 0.007*SL	0.334 + 0.005*SL
	t_{PLZ}	0.302	0.301 + 0.000*SL	0.302 + 0.000*SL	0.302 + 0.000*SL
	t_{PHZ}	0.291	0.291 + 0.000*SL	0.291 + 0.000*SL	0.292 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NITD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	0.066 + 0.006*SL	0.070 + 0.005*SL	0.064 + 0.005*SL
	t_F	0.073	0.062 + 0.005*SL	0.067 + 0.004*SL	0.074 + 0.004*SL
	t_{PLH}	0.172	0.164 + 0.004*SL	0.170 + 0.003*SL	0.194 + 0.002*SL
	t_{PHL}	0.202	0.194 + 0.004*SL	0.200 + 0.003*SL	0.235 + 0.002*SL
E to Y	t_R	0.086	0.075 + 0.005*SL	0.078 + 0.005*SL	0.067 + 0.005*SL
	t_F	0.080	0.068 + 0.006*SL	0.074 + 0.004*SL	0.080 + 0.004*SL
	t_{PLH}	0.171	0.162 + 0.005*SL	0.170 + 0.003*SL	0.197 + 0.002*SL
	t_{PHL}	0.278	0.269 + 0.005*SL	0.277 + 0.003*SL	0.317 + 0.002*SL
	t_{PLZ}	0.300	0.300 + 0.000*SL	0.300 + 0.000*SL	0.300 + 0.000*SL
	t_{PHZ}	0.231	0.231 + 0.000*SL	0.231 + 0.000*SL	0.231 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

NITD16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	0.078 + 0.004*SL	0.083 + 0.003*SL	0.100 + 0.002*SL
	t_F	0.089	0.083 + 0.003*SL	0.085 + 0.002*SL	0.101 + 0.002*SL
	t_{PLH}	0.216	0.210 + 0.003*SL	0.214 + 0.002*SL	0.247 + 0.001*SL
	t_{PHL}	0.250	0.246 + 0.002*SL	0.248 + 0.002*SL	0.277 + 0.001*SL
E to Y	t_R	0.097	0.090 + 0.003*SL	0.093 + 0.003*SL	0.107 + 0.002*SL
	t_F	0.090	0.082 + 0.004*SL	0.089 + 0.002*SL	0.113 + 0.002*SL
	t_{PLH}	0.213	0.207 + 0.003*SL	0.213 + 0.002*SL	0.251 + 0.001*SL
	t_{PHL}	0.312	0.306 + 0.003*SL	0.311 + 0.002*SL	0.354 + 0.001*SL
	t_{PLZ}	0.356	0.356 + 0.000*SL	0.356 + 0.000*SL	0.356 + 0.000*SL
	t_{PHZ}	0.328	0.327 + 0.000*SL	0.328 + 0.000*SL	0.329 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

Logic Symbol



Truth Table

A	EN	Y
x	1	Hi-Z
0	0	0
1	0	1

Cell Data

Input Load (SL)										Output Load (SL)				
NITN		*NITND2*		*NITND4*		*NITND8*		*NITND16*		*NITN*	*NITND2*	*NITND4*	*NITND8*	*NITND16*
A	EN	A	EN	A	EN	A	EN	A	EN	Y	Y	Y	Y	Y
1.7	1.3	1.7	1.3	1.7	1.3	4.6	2.7	4.5	2.7	0.9	1.1	2.3	4.4	8.4

Gate Count				
NITN	*NITND2*	*NITND4*	*NITND8*	*NITND16*
2.67	3.00	3.33	5.67	8.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NITN

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.151	0.076 + 0.037*SL	0.073 + 0.038*SL	0.067 + 0.039*SL
	t_F	0.143	0.074 + 0.035*SL	0.081 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.196	0.156 + 0.020*SL	0.165 + 0.018*SL	0.168 + 0.018*SL
	t_{PHL}	0.247	0.201 + 0.023*SL	0.215 + 0.020*SL	0.225 + 0.018*SL
EN to Y	t_R	0.176	0.090 + 0.043*SL	0.084 + 0.044*SL	0.079 + 0.045*SL
	t_F	0.166	0.094 + 0.036*SL	0.094 + 0.036*SL	0.090 + 0.037*SL
	t_{PLH}	0.307	0.266 + 0.021*SL	0.275 + 0.018*SL	0.278 + 0.018*SL
	t_{PHL}	0.237	0.190 + 0.024*SL	0.205 + 0.020*SL	0.215 + 0.019*SL
	t_{PLZ}	0.141	0.141 + 0.000*SL	0.141 + 0.000*SL	0.141 + 0.000*SL
	t_{PHZ}	0.266	0.266 + 0.000*SL	0.266 + 0.000*SL	0.266 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

NITND2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.068 + 0.020*SL	0.071 + 0.019*SL	0.067 + 0.019*SL
	t_F	0.101	0.062 + 0.020*SL	0.073 + 0.017*SL	0.077 + 0.017*SL
	t_{PLH}	0.189	0.163 + 0.013*SL	0.175 + 0.010*SL	0.188 + 0.009*SL
	t_{PHL}	0.229	0.200 + 0.015*SL	0.214 + 0.011*SL	0.233 + 0.009*SL
EN to Y	t_R	0.118	0.076 + 0.021*SL	0.080 + 0.020*SL	0.073 + 0.021*SL
	t_F	0.116	0.077 + 0.019*SL	0.085 + 0.017*SL	0.087 + 0.017*SL
	t_{PLH}	0.305	0.278 + 0.013*SL	0.291 + 0.010*SL	0.304 + 0.009*SL
	t_{PHL}	0.215	0.184 + 0.015*SL	0.200 + 0.011*SL	0.221 + 0.010*SL
	t_{PLZ}	0.158	0.158 + 0.000*SL	0.158 + 0.000*SL	0.158 + 0.000*SL
	t_{PHZ}	0.302	0.302 + 0.000*SL	0.302 + 0.000*SL	0.302 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

NITND4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.101	0.078 + 0.011*SL	0.085 + 0.010*SL	0.092 + 0.009*SL
	t_F	0.095	0.073 + 0.011*SL	0.083 + 0.009*SL	0.098 + 0.008*SL
	t_{PLH}	0.217	0.200 + 0.009*SL	0.210 + 0.006*SL	0.235 + 0.005*SL
	t_{PHL}	0.251	0.235 + 0.008*SL	0.243 + 0.006*SL	0.271 + 0.005*SL
EN to Y	t_R	0.112	0.089 + 0.012*SL	0.096 + 0.010*SL	0.099 + 0.010*SL
	t_F	0.106	0.083 + 0.011*SL	0.095 + 0.009*SL	0.108 + 0.008*SL
	t_{PLH}	0.325	0.306 + 0.009*SL	0.319 + 0.006*SL	0.345 + 0.005*SL
	t_{PHL}	0.229	0.209 + 0.010*SL	0.223 + 0.007*SL	0.255 + 0.005*SL
	t_{PLZ}	0.195	0.194 + 0.000*SL	0.195 + 0.000*SL	0.195 + 0.000*SL
	t_{PHZ}	0.377	0.377 + 0.000*SL	0.377 + 0.000*SL	0.378 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

NITND8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.078	0.066 + 0.006*SL	0.072 + 0.005*SL	0.066 + 0.005*SL
	t_F	0.072	0.060 + 0.006*SL	0.067 + 0.004*SL	0.073 + 0.004*SL
	t_{PLH}	0.175	0.167 + 0.004*SL	0.172 + 0.003*SL	0.198 + 0.002*SL
	t_{PHL}	0.200	0.191 + 0.004*SL	0.197 + 0.003*SL	0.232 + 0.002*SL
EN to Y	t_R	0.086	0.075 + 0.006*SL	0.079 + 0.005*SL	0.070 + 0.005*SL
	t_F	0.082	0.072 + 0.005*SL	0.076 + 0.004*SL	0.080 + 0.004*SL
	t_{PLH}	0.312	0.303 + 0.005*SL	0.311 + 0.003*SL	0.339 + 0.002*SL
	t_{PHL}	0.179	0.170 + 0.005*SL	0.178 + 0.003*SL	0.218 + 0.002*SL
	t_{PLZ}	0.164	0.164 + 0.000*SL	0.164 + 0.000*SL	0.164 + 0.000*SL
	t_{PHZ}	0.342	0.342 + 0.000*SL	0.342 + 0.000*SL	0.343 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

NITND16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.086	0.078 + 0.004*SL	0.085 + 0.003*SL	0.102 + 0.002*SL
	t_F	0.088	0.083 + 0.002*SL	0.084 + 0.002*SL	0.099 + 0.002*SL
	t_{PLH}	0.218	0.212 + 0.003*SL	0.216 + 0.002*SL	0.251 + 0.001*SL
	t_{PHL}	0.245	0.241 + 0.002*SL	0.243 + 0.002*SL	0.271 + 0.001*SL
EN to Y	t_R	0.099	0.093 + 0.003*SL	0.095 + 0.003*SL	0.109 + 0.002*SL
	t_F	0.088	0.080 + 0.004*SL	0.087 + 0.002*SL	0.110 + 0.002*SL
	t_{PLH}	0.355	0.348 + 0.003*SL	0.354 + 0.002*SL	0.394 + 0.001*SL
	t_{PHL}	0.210	0.204 + 0.003*SL	0.209 + 0.002*SL	0.252 + 0.001*SL
	t_{PLZ}	0.214	0.214 + 0.000*SL	0.214 + 0.000*SL	0.214 + 0.000*SL
	t_{PHZ}	0.440	0.440 + 0.000*SL	0.440 + 0.000*SL	0.442 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

OAK_DUCLK10/OAK_DUCLK16

2 Phase Clock Generator Buffer (1ns/1.6ns Non-overlapped)

Logic Symbol



Truth Table

A	CK	CKB
0	0	1
1	1	0

Cell Data

Input Load (SL)		Gate Count	
OAK_DUCLK10	*OAK_DUCLK16*	*OAK_DUCLK10*	*OAK_DUCLK16*
A	A	13.67	14.67
1.9	1.9		

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

OAK_DUCLK10

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to CK	t_R	0.092	0.084 + 0.004*SL	0.085 + 0.004*SL	0.075 + 0.004*SL
	t_F	0.084	0.075 + 0.004*SL	0.078 + 0.004*SL	0.071 + 0.004*SL
	t_{PLH}	2.239	2.232 + 0.003*SL	2.237 + 0.002*SL	2.261 + 0.002*SL
	t_{PHL}	1.310	1.304 + 0.003*SL	1.308 + 0.002*SL	1.332 + 0.002*SL
A to CKB	t_R	0.092	0.084 + 0.004*SL	0.086 + 0.004*SL	0.074 + 0.004*SL
	t_F	0.083	0.074 + 0.004*SL	0.077 + 0.004*SL	0.070 + 0.004*SL
	t_{PLH}	2.330	2.324 + 0.003*SL	2.329 + 0.002*SL	2.353 + 0.002*SL
	t_{PHL}	1.214	1.207 + 0.004*SL	1.212 + 0.002*SL	1.236 + 0.002*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

OAK_DUCLK16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to CK	t_R	0.097	0.089 + 0.004*SL	0.092 + 0.004*SL	0.079 + 0.004*SL
	t_F	0.093	0.085 + 0.004*SL	0.088 + 0.004*SL	0.078 + 0.004*SL
	t_{PLH}	3.215	3.208 + 0.003*SL	3.213 + 0.002*SL	3.238 + 0.002*SL
	t_{PHL}	1.770	1.763 + 0.004*SL	1.767 + 0.002*SL	1.794 + 0.002*SL
A to CKB	t_R	0.096	0.088 + 0.004*SL	0.090 + 0.004*SL	0.077 + 0.004*SL
	t_F	0.091	0.083 + 0.004*SL	0.086 + 0.004*SL	0.077 + 0.004*SL
	t_{PLH}	3.308	3.301 + 0.003*SL	3.306 + 0.002*SL	3.331 + 0.002*SL
	t_{PHL}	1.679	1.672 + 0.004*SL	1.677 + 0.002*SL	1.703 + 0.002*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

CTSB/CTSBD2/CTSBD3/CTSBD4/CTSBD6/CTSBD8/CTSBD16

Clock Tree Synthesis Buffers

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Input Load (SL)						
CTSB	*CTSBD2*	*CTSBD3*	*CTSBD4*	*CTSBD6*	*CTSBD8*	*CTSBD16*
A	A	A	A	A	A	A
0.8	0.9	0.9	0.9	1.7	1.8	3.5
Gate Count						
CTSB	*CTSBD2*	*CTSBD3*	*CTSBD4*	*CTSBD6*	*CTSBD8*	*CTSBD16*
1.00	1.33	1.67	2.00	2.67	3.33	6.33

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

CTSB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.154	0.082 + 0.036*SL	0.078 + 0.037*SL	0.071 + 0.038*SL
	t_F	0.144	0.072 + 0.036*SL	0.067 + 0.037*SL	0.061 + 0.038*SL
	t_{PLH}	0.230	0.191 + 0.019*SL	0.199 + 0.017*SL	0.201 + 0.017*SL
	t_{PHL}	0.204	0.162 + 0.021*SL	0.168 + 0.020*SL	0.170 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

CTSBD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.109	0.072 + 0.019*SL	0.073 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.099	0.063 + 0.018*SL	0.061 + 0.018*SL	0.055 + 0.019*SL
	t_{PLH}	0.222	0.198 + 0.012*SL	0.208 + 0.010*SL	0.217 + 0.009*SL
	t_{PHL}	0.197	0.171 + 0.013*SL	0.180 + 0.011*SL	0.188 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

CTSBD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.107	0.081 + 0.013*SL	0.083 + 0.012*SL	0.073 + 0.013*SL
	t_F	0.094	0.067 + 0.014*SL	0.070 + 0.013*SL	0.062 + 0.013*SL
	t_{PLH}	0.231	0.213 + 0.009*SL	0.223 + 0.007*SL	0.238 + 0.006*SL
	t_{PHL}	0.211	0.191 + 0.010*SL	0.200 + 0.008*SL	0.212 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

CTSBD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.102	0.083 + 0.010*SL	0.085 + 0.009*SL	0.083 + 0.009*SL
	t_F	0.088	0.067 + 0.011*SL	0.073 + 0.009*SL	0.071 + 0.009*SL
	t_{PLH}	0.243	0.228 + 0.008*SL	0.236 + 0.006*SL	0.255 + 0.005*SL
	t_{PHL}	0.223	0.207 + 0.008*SL	0.215 + 0.006*SL	0.232 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

CTSBD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.083	0.071 + 0.006*SL	0.070 + 0.006*SL	0.054 + 0.006*SL
	t_F	0.075	0.063 + 0.006*SL	0.062 + 0.006*SL	0.045 + 0.006*SL
	t_{PLH}	0.204	0.194 + 0.005*SL	0.201 + 0.003*SL	0.221 + 0.003*SL
	t_{PHL}	0.182	0.172 + 0.005*SL	0.178 + 0.003*SL	0.195 + 0.003*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

CTSBD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	0.074 + 0.005*SL	0.077 + 0.005*SL	0.064 + 0.005*SL
	t_F	0.073	0.061 + 0.006*SL	0.066 + 0.005*SL	0.057 + 0.005*SL
	t_{PLH}	0.214	0.206 + 0.004*SL	0.212 + 0.003*SL	0.236 + 0.002*SL
	t_{PHL}	0.202	0.193 + 0.004*SL	0.200 + 0.003*SL	0.223 + 0.002*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

CTSBD16

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.085	0.079 + 0.003*SL	0.081 + 0.002*SL	0.080 + 0.002*SL
	t_F	0.066	0.059 + 0.004*SL	0.064 + 0.002*SL	0.065 + 0.002*SL
	t_{PLH}	0.225	0.220 + 0.002*SL	0.223 + 0.001*SL	0.247 + 0.001*SL
	t_{PHL}	0.197	0.192 + 0.002*SL	0.195 + 0.002*SL	0.216 + 0.001*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 66, *Group3 : 66 < SL

FLIP-FLOPS

Cell List

Cell Name	Function Description
FD1	D Flip-Flop
FD1D2	D Flip-Flop with 2X Drive
FD1CS	D Flip-Flop with Scan Clock
FD1CSD2	D Flip-Flop with Scan Clock, 2X Drive
FD1S	D Flip-Flop with Scan
FD1SD2	D Flip-Flop with Scan, 2X Drive
FD1SQ	D Flip-Flop with Scan, Q Output Only
FD1SQD2	D Flip-Flop with Scan, Q Output Only, 2X Drive
FD1Q	D Flip-Flop with Q Output Only
FD1QD2	D Flip-Flop with Q Output Only, 2X Drive
FD2	D Flip-Flop with Reset
FD2D2	D Flip-Flop with Reset, 2X Drive
FD2CS	D Flip-Flop with Reset, Scan Clock
FD2CSD2	D Flip-Flop with Reset, Scan Clock, 2X Drive
FD2S	D Flip-Flop with Reset, Scan
FD2SD2	D Flip-Flop with Reset, Scan, 2X Drive
FD2SQ	D Flip-Flop with Reset, Scan, Q Output Only
FD2SQD2	D Flip-Flop with Reset, Scan, Q Output Only, 2X Drive
FD2Q	D Flip-Flop with Reset, Q Output Only
FD2QD2	D Flip-Flop with Reset, Q Output Only, 2X Drive
FD3	D Flip-Flop with Set
FD3D2	D Flip-Flop with Set, 2X Drive
FD3CS	D Flip-Flop with Set, Scan Clock
FD3CSD2	D Flip-Flop with Set, Scan Clock, 2X Drive
FD3S	D Flip-Flop with Set, Scan
FD3SD2	D Flip-Flop with Set, Scan, 2X Drive
FD3SQ	D Flip-Flop with Set, Scan, Q Output Only
FD3SQD2	D Flip-Flop with Set, Scan, Q Output Only, 2X Drive
FD3Q	D Flip-Flop with Set, Q Output Only
FD3QD2	D Flip-Flop with Set, Q Output Only, 2X Drive
FD4	D Flip-Flop with Reset, Set
FD4D2	D Flip-Flop with Reset, Set, 2X Drive
FD4CS	D Flip-Flop with Reset, Set, Scan Clock
FD4CSD2	D Flip-Flop with Reset, Set, Scan Clock, 2X Drive
FD4S	D Flip-Flop with Reset, Set, Scan
FD4SD2	D Flip-Flop with Reset, Set, Scan, 2X Drive
FD4SQ	D Flip-Flop with Reset, Set, Scan, Q Output Only
FD4SQD2	D Flip-Flop with Reset, Set, Scan, Q Output Only, 2X Drive

Cell List (Cont.)

Cell Name	Function Description
FD4Q	D Flip-Flop with Reset, Set, Q Output Only
FD4QD2	D Flip-Flop with Reset, Set, Q Output Only, 2X Drive
FD5	D Flip-Flop with Negative Edge Trigger
FD5D2	D Flip-Flop with Negative Edge Trigger, 2X Drive
FD5S	D Flip-Flop with Negative Edge Trigger, Scan
FD5SD2	D Flip-Flop with Negative Edge Trigger, Scan, 2X Drive
FD6	D Flip-Flop with Negative Edge Trigger, Reset
FD6D2	D Flip-Flop with Negative Edge Trigger, Reset, 2X Drive
FD6S	D Flip-Flop with Negative Edge Trigger, Reset, Scan
FD6SD2	D Flip-Flop with Negative Edge Trigger, Reset, Scan, 2X Drive
FD7	D Flip-Flop with Negative Edge Trigger, Set
FD7D2	D Flip-Flop with Negative Edge Trigger, Set, 2X Drive
FD7S	D Flip-Flop with Negative Edge Trigger, Set, Scan
FD7SD2	D Flip-Flop with Negative Edge Trigger, Set, Scan, 2X Drive
FD8	D Flip-Flop with Negative Edge Trigger, Reset, Set
FD8D2	D Flip-Flop with Negative Edge Trigger, Reset, Set, 2X Drive
FD8S	D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan
FD8SD2	D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 2X Drive
FDS2	D Flip-Flop with Synchronous Clear
FDS2D2	D Flip-Flop with Synchronous Clear, 2X Drive
FDS2CS	D Flip-Flop with Synchronous Clear, Scan Clock
FDS2CSD2	D Flip-Flop with Synchronous Clear, Scan Clock, 2X Drive
FDS2S	D Flip-Flop with Synchronous Clear, Scan
FDS2SD2	D Flip-Flop with Synchronous Clear, Scan, 2X Drive
FDS3	D Flip-Flop with Synchronous Set
FDS3D2	D Flip-Flop with Synchronous Set, 2X Drive
FDS3CS	D Flip-Flop with Synchronous Set, Scan Clock
FDS3CSD2	D Flip-Flop with Synchronous Set, Scan Clock, 2X Drive
FDS3S	Flip-Flop with Synchronous Set, Scan
FDS3SD2	Flip-Flop with Synchronous Set, Scan, 2x Drive
FJ1	JK Flip-Flop
FJ1D2	JK Flip-Flop with 2X Drive
FJ1S	JK Flip-Flop with Scan
FJ1SD2	JK Flip-Flop with Scan, 2X Drive
FJ2	JK Flip-Flop with Reset
FJ2D2	JK Flip-Flop with Reset, 2X Drive
FJ2S	JK Flip-Flop with Reset, Scan
FJ2SD2	JK Flip-Flop with Reset, Scan, 2X Drive

Cell List (Cont.)

Cell Name	Function Description
FJ4	JK Flip-Flop with Reset, Set
FJ4D2	JK Flip-Flop with Reset, Set, 2X Drive
FJ4S	JK Flip-Flop with Reset, Set, Scan
FJ4SD2	JK Flip-Flop with Reset, Set, Scan, 2X Drive
FT2	Toggle Flip-Flop with Reset
FT2D2	Toggle Flip-Flop with Reset, 2X Drive

NOTE

FD1/FD1D2

D Flip-Flop with 1X/2X Drive

Logic Symbol



Truth Table

D	CK	Q (n+1)	QN (n+1)
0	↑	0	1
1	↑	1	0
x	↓	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
FD1		*FD1D2*		*FD1*	*FD1D2*
D	CK	D	CK		
0.6	0.5	0.6	0.6	5.00	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1	FD1D2
Input Setup Time (D to CK)	t_{SU}	0.265	0.254
Input Hold Time (D to CK)	t_{HD}	0.153	0.144
Pulse Width Low (CK)	t_{PWL}	0.467	0.463
Pulse Width High (CK)	t_{PWH}	0.413	0.435

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.158	0.085 + 0.036*SL	0.081 + 0.037*SL	0.073 + 0.038*SL
	t_F	0.139	0.074 + 0.032*SL	0.080 + 0.031*SL	0.075 + 0.032*SL
	t_{PLH}	0.545	0.504 + 0.020*SL	0.513 + 0.018*SL	0.518 + 0.018*SL
	t_{PHL}	0.575	0.533 + 0.021*SL	0.545 + 0.018*SL	0.554 + 0.017*SL
CK to QN	t_R	0.145	0.073 + 0.036*SL	0.065 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.128	0.067 + 0.031*SL	0.064 + 0.031*SL	0.060 + 0.032*SL
	t_{PLH}	0.662	0.624 + 0.019*SL	0.630 + 0.018*SL	0.632 + 0.017*SL
	t_{PHL}	0.644	0.605 + 0.020*SL	0.614 + 0.017*SL	0.619 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	0.080 + 0.018*SL	0.080 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.109	0.072 + 0.018*SL	0.079 + 0.017*SL	0.080 + 0.016*SL
	t_{PLH}	0.541	0.515 + 0.013*SL	0.528 + 0.010*SL	0.539 + 0.009*SL
	t_{PHL}	0.577	0.549 + 0.014*SL	0.563 + 0.011*SL	0.580 + 0.009*SL
CK to QN	t_R	0.108	0.072 + 0.018*SL	0.071 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.103	0.068 + 0.017*SL	0.072 + 0.016*SL	0.069 + 0.017*SL
	t_{PLH}	0.709	0.685 + 0.012*SL	0.695 + 0.010*SL	0.704 + 0.009*SL
	t_{PHL}	0.691	0.664 + 0.013*SL	0.676 + 0.010*SL	0.690 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD1CS/FD1CSD2

D Flip-Flop with Scan Clock, 1X/2X Drive

Logic Symbol



Truth Table

SI	SCK	D	CK	Q (n+1)	QN (n+1)
x	0	0	↑	0	1
x	0	1	↑	1	0
0	↑	x	0	0	1
1	↑	x	0	1	0
x	0	x	↓	Q(n)	QN(n)
x	↓	x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)								Gate Count	
FD1CS				*FD1CSD2*				*FD1CS*	*FD1CSD2*
D	SI	CK	SCK	D	SI	CK	SCK		
0.6	0.5	0.5	1.4	0.6	0.5	0.86	1.4	8.00	8.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1CS	FD1CSD2
Input Setup Time (D to CK)	t_{SU}	0.264	0.255
Input Hold Time (D to CK)	t_{HD}	0.153	0.138
Input Setup Time (SI to SCK)	t_{SU}	0.470	0.469
Input Hold Time (SI to SCK)	t_{HD}	0.063	0.063
Pulse Width Low (CK)	t_{PWL}	0.462	0.448
Pulse Width High (CK)	t_{PWH}	0.427	0.453
Pulse Width Low (SCK)	t_{PWL}	0.410	0.410
Pulse Width High (SCK)	t_{PWH}	0.508	0.552

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD1CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.158	0.086 + 0.036*SL	0.080 + 0.037*SL	0.071 + 0.039*SL
	t_F	0.138	0.076 + 0.031*SL	0.076 + 0.031*SL	0.072 + 0.032*SL
	t_{PLH}	0.550	0.509 + 0.020*SL	0.519 + 0.018*SL	0.523 + 0.018*SL
	t_{PHL}	0.568	0.526 + 0.021*SL	0.538 + 0.018*SL	0.546 + 0.017*SL
SCK to Q	t_R	0.176	0.105 + 0.036*SL	0.103 + 0.036*SL	0.091 + 0.038*SL
	t_F	0.145	0.083 + 0.031*SL	0.086 + 0.031*SL	0.081 + 0.031*SL
	t_{PLH}	0.674	0.630 + 0.022*SL	0.644 + 0.018*SL	0.651 + 0.018*SL
	t_{PHL}	0.549	0.505 + 0.022*SL	0.519 + 0.018*SL	0.529 + 0.017*SL
CK to QN	t_R	0.164	0.086 + 0.039*SL	0.090 + 0.038*SL	0.087 + 0.038*SL
	t_F	0.140	0.074 + 0.033*SL	0.075 + 0.033*SL	0.078 + 0.032*SL
	t_{PLH}	0.680	0.634 + 0.023*SL	0.648 + 0.019*SL	0.659 + 0.018*SL
	t_{PHL}	0.680	0.637 + 0.021*SL	0.648 + 0.019*SL	0.656 + 0.018*SL
SCK to QN	t_R	0.146	0.072 + 0.037*SL	0.068 + 0.038*SL	0.061 + 0.039*SL
	t_F	0.129	0.068 + 0.031*SL	0.066 + 0.031*SL	0.060 + 0.032*SL
	t_{PLH}	0.635	0.597 + 0.019*SL	0.603 + 0.018*SL	0.605 + 0.017*SL
	t_{PHL}	0.774	0.735 + 0.020*SL	0.745 + 0.017*SL	0.749 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD1CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	0.079 + 0.019*SL	0.081 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.079 + 0.017*SL	0.079 + 0.017*SL
	t_{PLH}	0.550	0.523 + 0.013*SL	0.536 + 0.010*SL	0.549 + 0.009*SL
	t_{PHL}	0.566	0.537 + 0.014*SL	0.551 + 0.011*SL	0.568 + 0.009*SL
SCK to Q	t_R	0.138	0.099 + 0.019*SL	0.105 + 0.018*SL	0.095 + 0.019*SL
	t_F	0.115	0.079 + 0.018*SL	0.087 + 0.016*SL	0.088 + 0.016*SL
	t_{PLH}	0.683	0.654 + 0.014*SL	0.670 + 0.011*SL	0.688 + 0.009*SL
	t_{PHL}	0.555	0.526 + 0.015*SL	0.541 + 0.011*SL	0.560 + 0.009*SL
CK to QN	t_R	0.121	0.079 + 0.021*SL	0.087 + 0.019*SL	0.088 + 0.019*SL
	t_F	0.110	0.073 + 0.018*SL	0.077 + 0.017*SL	0.081 + 0.017*SL
	t_{PLH}	0.721	0.693 + 0.014*SL	0.705 + 0.011*SL	0.725 + 0.009*SL
	t_{PHL}	0.730	0.702 + 0.014*SL	0.714 + 0.011*SL	0.730 + 0.010*SL
SCK to QN	t_R	0.108	0.072 + 0.018*SL	0.071 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.071 + 0.016*SL	0.067 + 0.017*SL
	t_{PLH}	0.688	0.664 + 0.012*SL	0.674 + 0.009*SL	0.682 + 0.009*SL
	t_{PHL}	0.838	0.812 + 0.013*SL	0.824 + 0.010*SL	0.837 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD1S/FD1SD2

D Flip-Flop with Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CK	Q (n+1)	QN (n+1)
0	x	0	↑	0	1
1	x	0	↑	1	0
x	0	1	↑	0	1
x	1	1	↑	1	0
x	x	x	↓	Q(n)	QN(n)

Cell Data

Input Load (SL)								Gate Count	
FD1S				*FD1SD2*				*FD1S*	*FD1SD2*
D	CK	TI	TE	D	CK	TI	TE		
0.5	0.5	0.5	1.2	0.5	0.5	0.5	1.1	6.67	7.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1S	FD1SD2
Input Setup Time (D to CK)	t_{SU}	0.479	0.457
Input Hold Time (D to CK)	t_{HD}	0.057	0.059
Input Setup Time (TI to CK)	t_{SU}	0.515	0.495
Input Hold Time (TI to CK)	t_{HD}	0.005	0.002
Input Setup Time (TE to CK)	t_{SU}	0.531	0.524
Input Hold Time (TE to CK)	t_{HD}	0.003	0.007
Pulse Width Low (CK)	t_{PWL}	0.639	0.611
Pulse Width High (CK)	t_{PWH}	0.419	0.434

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD1S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.158	0.085 + 0.036*SL	0.081 + 0.038*SL	0.075 + 0.038*SL
	t_F	0.139	0.075 + 0.032*SL	0.080 + 0.031*SL	0.075 + 0.032*SL
	t_{PLH}	0.554	0.513 + 0.020*SL	0.522 + 0.018*SL	0.527 + 0.018*SL
	t_{PHL}	0.594	0.552 + 0.021*SL	0.563 + 0.018*SL	0.573 + 0.017*SL
CK to QN	t_R	0.146	0.073 + 0.036*SL	0.067 + 0.038*SL	0.061 + 0.039*SL
	t_F	0.128	0.067 + 0.031*SL	0.065 + 0.031*SL	0.061 + 0.032*SL
	t_{PLH}	0.682	0.643 + 0.019*SL	0.650 + 0.018*SL	0.651 + 0.017*SL
	t_{PHL}	0.654	0.614 + 0.020*SL	0.624 + 0.017*SL	0.629 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD1SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	0.080 + 0.018*SL	0.082 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.111	0.074 + 0.018*SL	0.080 + 0.017*SL	0.081 + 0.017*SL
	t_{PLH}	0.549	0.524 + 0.013*SL	0.536 + 0.010*SL	0.548 + 0.009*SL
	t_{PHL}	0.597	0.568 + 0.014*SL	0.582 + 0.011*SL	0.598 + 0.010*SL
CK to QN	t_R	0.108	0.071 + 0.018*SL	0.072 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.101	0.066 + 0.017*SL	0.070 + 0.016*SL	0.067 + 0.017*SL
	t_{PLH}	0.725	0.701 + 0.012*SL	0.711 + 0.010*SL	0.720 + 0.009*SL
	t_{PHL}	0.695	0.668 + 0.013*SL	0.680 + 0.010*SL	0.694 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD1SQ/FD1SQD2

D Flip-Flop with Scan, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CK	Q (n+1)
0	x	0	↑	0
1	x	0	↑	1
x	0	1	↑	0
x	1	1	↑	1
x	x	x	↓	Q(n)

Cell Data

Input Load (SL)								Gate Count	
FD1SQ				*FD1SQD2*				*FD1SQ*	*FD1SQD2*
D	CK	TI	TE	D	CK	TI	TE		
0.5	0.5	0.5	1.1	0.5	0.6	0.5	1.2	6.00	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1SQ	FD1SQD2
Input Setup Time (D to CK)	t_{SU}	0.453	0.501
Input Hold Time (D to CK)	t_{HD}	0.056	0.043
Input Setup Time (TI to CK)	t_{SU}	0.492	0.515
Input Hold Time (TI to CK)	t_{HD}	0.000	0.006
Input Setup Time (TE to CK)	t_{SU}	0.520	0.537
Input Hold Time (TE to CK)	t_{HD}	0.001	0.000
Pulse Width Low (CK)	t_{PWL}	0.608	0.635
Pulse Width High (CK)	t_{PWH}	0.385	0.433

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD1SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.151	0.079 + 0.036*SL	0.073 + 0.038*SL	0.065 + 0.039*SL
	t_F	0.137	0.071 + 0.033*SL	0.071 + 0.033*SL	0.066 + 0.034*SL
	t_{PLH}	0.520	0.481 + 0.020*SL	0.489 + 0.018*SL	0.491 + 0.017*SL
	t_{PHL}	0.568	0.526 + 0.021*SL	0.536 + 0.019*SL	0.542 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD1SQD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	0.079 + 0.018*SL	0.080 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.104	0.068 + 0.018*SL	0.075 + 0.017*SL	0.072 + 0.017*SL
	t_{PLH}	0.554	0.529 + 0.013*SL	0.541 + 0.010*SL	0.552 + 0.009*SL
	t_{PHL}	0.587	0.560 + 0.014*SL	0.572 + 0.011*SL	0.587 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD1Q/FD1QD2

D Flip-Flop with Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	CK	Q (n+1)
0	↑	0
1	↑	1
x	↓	Q (n)

Cell Data

Input Load (SL)				Gate Count	
FD1Q		*FD1QD2*		*FD1Q*	*FD1QD2*
D	CK	D	CK		
0.6	0.6	0.6	0.5	4.33	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD1Q	FD1QD2
Input Setup Time (D to CK)	t_{SU}	0.254	0.265
Input Hold Time (D to CK)	t_{HD}	0.138	0.156
Pulse Width Low (CK)	t_{PWL}	0.455	0.459
Pulse Width High (CK)	t_{PWH}	0.388	0.402

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD1Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.149	0.078 + 0.036*SL	0.074 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.137	0.071 + 0.033*SL	0.072 + 0.033*SL	0.065 + 0.034*SL
	t_{PLH}	0.515	0.476 + 0.020*SL	0.485 + 0.017*SL	0.487 + 0.017*SL
	t_{PHL}	0.554	0.511 + 0.021*SL	0.522 + 0.019*SL	0.528 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD1QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.113	0.077 + 0.018*SL	0.076 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.073 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.522	0.497 + 0.012*SL	0.509 + 0.010*SL	0.519 + 0.009*SL
	t_{PHL}	0.556	0.530 + 0.013*SL	0.542 + 0.010*SL	0.557 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD2/FD2D2

D Flip-Flop with Reset, 1X/2X Drive

Logic Symbol



Truth Table

D	CK	RN	Q (n+1)	QN (n+1)
0	↑	1	0	1
1	↑	1	1	0
x	x	0	0	1
x	↓	1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD2			*FD2D2*			*FD2*	*FD2D2*
D	CK	RN	D	CK	RN		
0.6	0.5	1.4	0.5	0.5	1.4	5.67	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2	FD2D2
Input Setup Time (D to CK)	t_{SU}	0.299	0.273
Input Hold Time (D to CK)	t_{HD}	0.178	0.181
Pulse Width Low (CK)	t_{PWL}	0.495	0.504
Pulse Width High (CK)	t_{PWH}	0.462	0.474
Pulse Width Low (RN)	t_{PWL}	0.345	0.387
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.624	0.601[

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.178	0.102 + 0.038*SL	0.107 + 0.037*SL	0.102 + 0.037*SL
	t_F	0.150	0.081 + 0.035*SL	0.088 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.623	0.577 + 0.023*SL	0.591 + 0.020*SL	0.603 + 0.018*SL
	t_{PHL}	0.602	0.556 + 0.023*SL	0.569 + 0.020*SL	0.580 + 0.018*SL
RN to Q	t_F	0.151	0.083 + 0.034*SL	0.086 + 0.033*SL	0.083 + 0.033*SL
	t_{PHL}	0.274	0.229 + 0.023*SL	0.241 + 0.020*SL	0.251 + 0.018*SL
CK to QN	t_R	0.145	0.075 + 0.035*SL	0.068 + 0.037*SL	0.062 + 0.038*SL
	t_F	0.137	0.072 + 0.032*SL	0.071 + 0.033*SL	0.064 + 0.034*SL
	t_{PLH}	0.687	0.649 + 0.019*SL	0.655 + 0.017*SL	0.657 + 0.017*SL
	t_{PHL}	0.735	0.693 + 0.021*SL	0.704 + 0.018*SL	0.709 + 0.018*SL
RN to QN	t_R	0.167	0.090 + 0.039*SL	0.097 + 0.037*SL	0.095 + 0.037*SL
	t_{PLH}	0.400	0.354 + 0.023*SL	0.368 + 0.020*SL	0.382 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.133	0.091 + 0.021*SL	0.099 + 0.019*SL	0.100 + 0.019*SL
	t_F	0.112	0.076 + 0.018*SL	0.081 + 0.017*SL	0.085 + 0.016*SL
	t_{PLH}	0.596	0.566 + 0.015*SL	0.581 + 0.011*SL	0.601 + 0.009*SL
	t_{PHL}	0.607	0.578 + 0.015*SL	0.592 + 0.011*SL	0.611 + 0.009*SL
RN to Q	t_F	0.109	0.072 + 0.019*SL	0.079 + 0.017*SL	0.082 + 0.016*SL
	t_{PHL}	0.260	0.232 + 0.014*SL	0.245 + 0.011*SL	0.262 + 0.009*SL
CK to QN	t_R	0.109	0.073 + 0.018*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.077 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.749	0.724 + 0.012*SL	0.735 + 0.010*SL	0.744 + 0.009*SL
	t_{PHL}	0.765	0.738 + 0.014*SL	0.751 + 0.010*SL	0.767 + 0.009*SL
RN to QN	t_R	0.122	0.080 + 0.021*SL	0.088 + 0.019*SL	0.091 + 0.019*SL
	t_{PLH}	0.435	0.406 + 0.014*SL	0.419 + 0.011*SL	0.439 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD2CS/FD2CSD2

D Flip-Flop with Reset, Scan Clock, 1X/2X Drive

Logic Symbol



Truth Table

SI	SCK	D	CK	RN	Q (n+1)	QN (n+1)
x	0	0	↑	1	0	1
x	0	1	↑	1	1	0
0	↑	x	0	1	0	1
1	↑	x	0	1	1	0
x	x	x	x	0	0	1
x	↓	x	0	1	Q(n)	QN(n)
x	0	x	↓	1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD2CS					*FD2CSD2*					*FD2CS*	*FD2CSD2*
D	SI	CK	SCK	RN	D	SI	CK	SCK	RN		
0.6	0.6	0.6	1.5	2.1	0.6	0.6	0.6	1.5	2.1	9.33	9.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2CS	FD2CSD2
Input Setup Time (D to CK)	t_{SU}	0.302	0.298
Input Hold Time (D to CK)	t_{HD}	0.174	0.178
Input Setup Time (SI to SCK)	t_{SU}	0.493	0.515
Input Hold Time (SI to SCK)	t_{HD}	0.030	0.025
Pulse Width Low (CK)	t_{PWL}	0.504	0.499
Pulse Width High (CK)	t_{PWH}	0.483	0.536
Pulse Width Low (SCK)	t_{PWL}	0.466	0.473
Pulse Width High (SCK)	t_{PWH}	0.583	0.623
Pulse Width Low (RN)	t_{PWL}	0.436	0.476
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.632	0.618
Recovery Time (RN to SCK)	t_{RC}	0.000	0.000
Removal Time (RN to SCK)	t_{RM}	0.574	0.622

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.176	0.103 + 0.037*SL	0.103 + 0.037*SL	0.100 + 0.037*SL
	t_F	0.147	0.081 + 0.033*SL	0.083 + 0.032*SL	0.080 + 0.033*SL
	t_{PLH}	0.630	0.585 + 0.022*SL	0.599 + 0.019*SL	0.608 + 0.018*SL
	t_{PHL}	0.598	0.554 + 0.022*SL	0.565 + 0.019*SL	0.574 + 0.018*SL
SCK to Q	t_R	0.193	0.121 + 0.036*SL	0.124 + 0.036*SL	0.117 + 0.037*SL
	t_F	0.154	0.087 + 0.033*SL	0.093 + 0.032*SL	0.088 + 0.033*SL
	t_{PLH}	0.763	0.716 + 0.024*SL	0.732 + 0.020*SL	0.745 + 0.018*SL
	t_{PHL}	0.589	0.544 + 0.023*SL	0.557 + 0.019*SL	0.568 + 0.018*SL
RN to Q	t_F	0.149	0.083 + 0.033*SL	0.084 + 0.032*SL	0.080 + 0.033*SL
	t_{PHL}	0.274	0.230 + 0.022*SL	0.241 + 0.019*SL	0.250 + 0.018*SL
CK to QN	t_R	0.170	0.093 + 0.038*SL	0.100 + 0.037*SL	0.096 + 0.037*SL
	t_F	0.155	0.085 + 0.035*SL	0.090 + 0.034*SL	0.092 + 0.034*SL
	t_{PLH}	0.728	0.681 + 0.023*SL	0.696 + 0.020*SL	0.710 + 0.018*SL
	t_{PHL}	0.804	0.757 + 0.024*SL	0.770 + 0.020*SL	0.780 + 0.019*SL
SCK to QN	t_R	0.151	0.080 + 0.035*SL	0.074 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.145	0.081 + 0.032*SL	0.079 + 0.032*SL	0.072 + 0.033*SL
	t_{PLH}	0.691	0.652 + 0.020*SL	0.661 + 0.018*SL	0.663 + 0.017*SL
	t_{PHL}	0.898	0.854 + 0.022*SL	0.866 + 0.019*SL	0.874 + 0.018*SL
RN to QN	t_R	0.177	0.093 + 0.042*SL	0.100 + 0.040*SL	0.115 + 0.038*SL
	t_{PLH}	0.412	0.363 + 0.024*SL	0.374 + 0.022*SL	0.387 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.137	0.097 + 0.020*SL	0.104 + 0.018*SL	0.104 + 0.018*SL
	t_F	0.115	0.078 + 0.019*SL	0.085 + 0.017*SL	0.086 + 0.017*SL
	t_{PLH}	0.657	0.628 + 0.015*SL	0.643 + 0.011*SL	0.663 + 0.009*SL
	t_{PHL}	0.617	0.588 + 0.015*SL	0.601 + 0.011*SL	0.620 + 0.010*SL
SCK to Q	t_R	0.153	0.112 + 0.020*SL	0.122 + 0.018*SL	0.124 + 0.018*SL
	t_F	0.121	0.084 + 0.019*SL	0.091 + 0.017*SL	0.096 + 0.016*SL
	t_{PLH}	0.780	0.749 + 0.015*SL	0.765 + 0.012*SL	0.789 + 0.009*SL
	t_{PHL}	0.613	0.583 + 0.015*SL	0.597 + 0.011*SL	0.618 + 0.010*SL
RN to Q	t_F	0.111	0.075 + 0.018*SL	0.080 + 0.017*SL	0.082 + 0.017*SL
	t_{PHL}	0.267	0.238 + 0.014*SL	0.251 + 0.011*SL	0.269 + 0.010*SL
CK to QN	t_R	0.122	0.080 + 0.021*SL	0.089 + 0.019*SL	0.092 + 0.018*SL
	t_F	0.116	0.079 + 0.018*SL	0.083 + 0.017*SL	0.088 + 0.017*SL
	t_{PLH}	0.777	0.750 + 0.014*SL	0.762 + 0.011*SL	0.782 + 0.009*SL
	t_{PHL}	0.867	0.838 + 0.015*SL	0.852 + 0.011*SL	0.869 + 0.010*SL
SCK to QN	t_R	0.109	0.074 + 0.018*SL	0.072 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.109	0.074 + 0.017*SL	0.078 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.750	0.726 + 0.012*SL	0.737 + 0.009*SL	0.747 + 0.009*SL
	t_{PHL}	0.957	0.930 + 0.014*SL	0.943 + 0.011*SL	0.958 + 0.009*SL
RN to QN	t_R	0.126	0.083 + 0.022*SL	0.087 + 0.021*SL	0.101 + 0.019*SL
	t_{PLH}	0.432	0.404 + 0.014*SL	0.415 + 0.012*SL	0.430 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD2S/FD2SD2

D Flip-Flop with Reset, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CK	RN	Q (n+1)	QN (n+1)
0	x	0	↑	1	0	1
1	x	0	↑	1	1	0
x	0	1	↑	1	0	1
x	1	1	↑	1	1	0
x	x	x	x	0	0	1
x	x	x	↓	1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD2S					*FD2SD2*					*FD2S*	*FD2SD2*
D	CK	RN	TI	TE	D	CK	RN	TI	TE		
0.5	0.6	1.4	0.6	1.2	0.5	0.6	1.4	0.6	1.2	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2S	FD2SD2
Input Setup Time (D to CK)	t_{SU}	0.497	0.505
Input Hold Time (D to CK)	t_{HD}	0.128	0.121
Input Setup Time (TI to CK)	t_{SU}	0.548	0.558
Input Hold Time (TI to CK)	t_{HD}	0.036	0.064
Input Setup Time (TE to CK)	t_{SU}	0.559	0.560
Input Hold Time (TE to CK)	t_{HD}	0.079	0.069
Pulse Width Low (CK)	t_{PWL}	0.657	0.663
Pulse Width High (CK)	t_{PWH}	0.474	0.507
Pulse Width Low (RN)	t_{PWL}	0.345	0.395
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.593	0.596

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.180	0.103 + 0.039*SL	0.106 + 0.038*SL	0.101 + 0.038*SL
	t_F	0.144	0.079 + 0.032*SL	0.085 + 0.031*SL	0.083 + 0.031*SL
	t_{PLH}	0.640	0.593 + 0.023*SL	0.607 + 0.020*SL	0.618 + 0.018*SL
	t_{PHL}	0.624	0.580 + 0.022*SL	0.592 + 0.019*SL	0.603 + 0.017*SL
RN to Q	t_F	0.144	0.080 + 0.032*SL	0.084 + 0.031*SL	0.081 + 0.031*SL
	t_{PHL}	0.269	0.226 + 0.022*SL	0.237 + 0.019*SL	0.247 + 0.017*SL
CK to QN	t_R	0.146	0.074 + 0.036*SL	0.069 + 0.037*SL	0.062 + 0.038*SL
	t_F	0.133	0.071 + 0.031*SL	0.072 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.714	0.676 + 0.019*SL	0.683 + 0.017*SL	0.685 + 0.017*SL
	t_{PHL}	0.750	0.709 + 0.020*SL	0.720 + 0.018*SL	0.726 + 0.017*SL
RN to QN	t_R	0.168	0.090 + 0.039*SL	0.097 + 0.037*SL	0.096 + 0.037*SL
	t_{PLH}	0.400	0.354 + 0.023*SL	0.368 + 0.020*SL	0.382 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD2SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.136	0.094 + 0.021*SL	0.102 + 0.019*SL	0.103 + 0.019*SL
	t_F	0.111	0.073 + 0.019*SL	0.081 + 0.017*SL	0.084 + 0.016*SL
	t_{PLH}	0.641	0.611 + 0.015*SL	0.625 + 0.011*SL	0.646 + 0.009*SL
	t_{PHL}	0.623	0.594 + 0.014*SL	0.607 + 0.011*SL	0.626 + 0.009*SL
RN to Q	t_F	0.111	0.074 + 0.018*SL	0.079 + 0.017*SL	0.085 + 0.016*SL
	t_{PHL}	0.267	0.238 + 0.014*SL	0.251 + 0.011*SL	0.269 + 0.010*SL
CK to QN	t_R	0.108	0.072 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.076 + 0.016*SL	0.073 + 0.016*SL
	t_{PLH}	0.757	0.733 + 0.012*SL	0.743 + 0.010*SL	0.752 + 0.009*SL
	t_{PHL}	0.808	0.780 + 0.014*SL	0.793 + 0.010*SL	0.808 + 0.009*SL
RN to QN	t_R	0.123	0.081 + 0.021*SL	0.089 + 0.019*SL	0.093 + 0.019*SL
	t_{PLH}	0.438	0.409 + 0.014*SL	0.421 + 0.011*SL	0.443 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	TI	TE	CK	RN	Q (n+1)
0	x	0	↑	1	0
1	x	0	↑	1	1
x	0	1	↑	1	0
x	1	1	↑	1	1
x	x	x	x	0	0
x	x	x	↓	1	Q(n)

Cell Data

Input Load (SL)										Gate Count	
FD2SQ					*FD2SQD2*					*FD2SQ*	*FD2SQD2*
D	CK	RN	TI	TE	D	CK	RN	TI	TE		
0.5	0.6	1.4	0.6	1.2	0.5	0.6	1.4	0.5	1.2	7.00	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2SQ	FD2SQD2
Input Setup Time (D to CK)	t_{SU}	0.501	0.505
Input Hold Time (D to CK)	t_{HD}	0.120	0.114
Input Setup Time (TI to CK)	t_{SU}	0.553	0.534
Input Hold Time (TI to CK)	t_{HD}	0.063	0.061
Input Setup Time (TE to CK)	t_{SU}	0.563	0.563
Input Hold Time (TE to CK)	t_{HD}	0.072	0.059
Pulse Width Low (CK)	t_{PWL}	0.656	0.655
Pulse Width High (CK)	t_{PWH}	0.441	0.461
Pulse Width Low (RN)	t_{PWL}	0.295	0.322
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.598	0.600

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.167	0.093 + 0.037*SL	0.091 + 0.037*SL	0.085 + 0.038*SL
	t_F	0.134	0.072 + 0.031*SL	0.072 + 0.031*SL	0.067 + 0.032*SL
	t_{PLH}	0.603	0.559 + 0.022*SL	0.572 + 0.019*SL	0.579 + 0.018*SL
	t_{PHL}	0.593	0.552 + 0.021*SL	0.564 + 0.018*SL	0.570 + 0.017*SL
RN to Q	t_F	0.135	0.073 + 0.031*SL	0.075 + 0.031*SL	0.069 + 0.032*SL
	t_{PHL}	0.248	0.207 + 0.021*SL	0.218 + 0.018*SL	0.225 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD2SQD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.128	0.087 + 0.020*SL	0.094 + 0.018*SL	0.091 + 0.019*SL
	t_F	0.105	0.069 + 0.018*SL	0.076 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.612	0.584 + 0.014*SL	0.598 + 0.011*SL	0.616 + 0.009*SL
	t_{PHL}	0.598	0.570 + 0.014*SL	0.583 + 0.011*SL	0.599 + 0.009*SL
RN to Q	t_F	0.106	0.070 + 0.018*SL	0.077 + 0.016*SL	0.074 + 0.017*SL
	t_{PHL}	0.249	0.221 + 0.014*SL	0.234 + 0.011*SL	0.250 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD2Q/FD2QD2

D Flip-Flop with Reset, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	CK	RN	Q (n+1)
0	↑	1	0
1	↑	1	1
x	x	0	0
x	↓	x	Q (n)

Cell Data

Input Load (SL)						Gate Count	
FD2Q			*FD2QD2*			*FD2Q*	*FD2QD2*
D	CK	RN	D	CK	RN		
0.6	0.6	1.4	0.6	0.6	1.4	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD2Q	FD2QD2
Input Setup Time (D to CK)	t_{SU}	0.291	0.275
Input Hold Time (D to CK)	t_{HD}	0.159	0.168
Pulse Width Low (CK)	t_{PWL}	0.492	0.479
Pulse Width High (CK)	t_{PWH}	0.440	0.459
Pulse Width Low (RN)	t_{PWL}	0.294	0.326
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.651	0.629

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD2Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.166	0.095 + 0.036*SL	0.092 + 0.036*SL	0.086 + 0.037*SL
	t_F	0.136	0.074 + 0.031*SL	0.075 + 0.031*SL	0.070 + 0.032*SL
	t_{PLH}	0.606	0.562 + 0.022*SL	0.576 + 0.018*SL	0.583 + 0.017*SL
	t_{PHL}	0.576	0.534 + 0.021*SL	0.546 + 0.018*SL	0.553 + 0.017*SL
RN to Q	t_F	0.136	0.073 + 0.031*SL	0.075 + 0.031*SL	0.069 + 0.032*SL
	t_{PHL}	0.249	0.207 + 0.021*SL	0.218 + 0.018*SL	0.225 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD2QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.128	0.089 + 0.020*SL	0.094 + 0.018*SL	0.091 + 0.019*SL
	t_F	0.105	0.069 + 0.018*SL	0.077 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.612	0.583 + 0.014*SL	0.598 + 0.011*SL	0.616 + 0.009*SL
	t_{PHL}	0.584	0.556 + 0.014*SL	0.569 + 0.011*SL	0.586 + 0.009*SL
RN to Q	t_F	0.106	0.071 + 0.018*SL	0.076 + 0.016*SL	0.074 + 0.016*SL
	t_{PHL}	0.250	0.223 + 0.014*SL	0.236 + 0.011*SL	0.252 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD3/FD3D2

D Flip-Flop with Set, 1X/2X Drive

Logic Symbol



Truth Table

D	CK	SN	Q (n+1)	QN (n+1)
0	↑	1	0	1
1	↑	1	1	0
x	x	0	1	0
x	↓	1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD3			*FD3D2*			*FD3*	*FD3D2*
D	CK	SN	D	CK	SN		
0.6	0.5	1.5	0.6	0.5	1.5	5.67	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3	FD3D2
Input Setup Time (D to CK)	t_{SU}	0.279	0.279
Input Hold Time (D to CK)	t_{HD}	0.128	0.128
Pulse Width Low (CK)	t_{PWL}	0.519	0.519
Pulse Width High (CK)	t_{PWH}	0.428	0.457
Pulse Width Low (SN)	t_{PWL}	0.381	0.428
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.327	0.329

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.160	0.089 + 0.036*SL	0.085 + 0.037*SL	0.078 + 0.038*SL
	t_F	0.151	0.083 + 0.034*SL	0.086 + 0.033*SL	0.083 + 0.033*SL
	t_{PLH}	0.554	0.513 + 0.020*SL	0.523 + 0.018*SL	0.528 + 0.017*SL
	t_{PHL}	0.627	0.583 + 0.022*SL	0.594 + 0.019*SL	0.603 + 0.018*SL
SN to Q	t_R	0.165	0.096 + 0.035*SL	0.090 + 0.036*SL	0.081 + 0.037*SL
	t_{PLH}	0.534	0.493 + 0.020*SL	0.504 + 0.018*SL	0.509 + 0.017*SL
CK to QN	t_R	0.163	0.090 + 0.036*SL	0.089 + 0.037*SL	0.083 + 0.037*SL
	t_F	0.137	0.074 + 0.032*SL	0.075 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.764	0.721 + 0.021*SL	0.734 + 0.018*SL	0.741 + 0.017*SL
	t_{PHL}	0.679	0.637 + 0.021*SL	0.648 + 0.018*SL	0.655 + 0.017*SL
SN to QN	t_F	0.153	0.085 + 0.034*SL	0.091 + 0.033*SL	0.096 + 0.032*SL
	t_{PHL}	0.291	0.244 + 0.023*SL	0.257 + 0.020*SL	0.269 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.120	0.082 + 0.019*SL	0.084 + 0.018*SL	0.076 + 0.019*SL
	t_F	0.112	0.076 + 0.018*SL	0.082 + 0.017*SL	0.083 + 0.017*SL
	t_{PLH}	0.555	0.528 + 0.013*SL	0.541 + 0.010*SL	0.554 + 0.009*SL
	t_{PHL}	0.626	0.597 + 0.014*SL	0.611 + 0.011*SL	0.628 + 0.009*SL
SN to Q	t_R	0.124	0.087 + 0.019*SL	0.089 + 0.018*SL	0.081 + 0.019*SL
	t_{PLH}	0.579	0.552 + 0.014*SL	0.565 + 0.010*SL	0.580 + 0.009*SL
CK to QN	t_R	0.125	0.084 + 0.020*SL	0.091 + 0.019*SL	0.090 + 0.019*SL
	t_F	0.105	0.069 + 0.018*SL	0.076 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.818	0.790 + 0.014*SL	0.803 + 0.011*SL	0.822 + 0.009*SL
	t_{PHL}	0.725	0.697 + 0.014*SL	0.711 + 0.011*SL	0.727 + 0.009*SL
SN to QN	t_F	0.118	0.078 + 0.020*SL	0.087 + 0.018*SL	0.097 + 0.017*SL
	t_{PHL}	0.288	0.258 + 0.015*SL	0.271 + 0.012*SL	0.291 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD3CS/FD3CSD2

D Flip-Flop with Set, Scan Clock, 1X/2X Drive

Logic Symbol



Truth Table

SI	SCK	D	CK	SN	Q (n+1)	QN (n+1)
x	0	0	↑	1	0	1
x	0	1	↑	1	1	0
0	↑	x	0	1	0	1
1	↑	x	0	1	1	0
x	x	x	x	0	1	0
x	0	x	↓	1	Q(n)	QN(n)
x	↓	x	0	1	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FD3CS					*FD3CSD2*					*FD3CS*	*FD3CSD2*
D	SI	CK	SCK	SN	D	SI	CK	SCK	SN		
0.6	0.6	0.5	1.6	2.3	0.5	0.5	0.5	1.6	2.4	9.00	9.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3CS	FD3CSD2
Input Setup Time (D to CK)	t_{SU}	0.279	0.279
Input Hold Time (D to CK)	t_{HD}	0.128	0.129
Input Setup Time (SI to SCK)	t_{SU}	0.497	0.499
Input Hold Time (SI to SCK)	t_{HD}	0.044	0.043
Pulse Width Low (CK)	t_{PWL}	0.519	0.520
Pulse Width High (CK)	t_{PWH}	0.447	0.483
Pulse Width Low (SCK)	t_{PWL}	0.424	0.429
Pulse Width High (SCK)	t_{PWH}	0.541	0.590
Pulse Width Low (SN)	t_{PWL}	0.520	0.566
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.322	0.321
Recovery Time (SN to SCK)	t_{RC}	0.214	0.212
RemovalTime (SN to SCK)	t_{RM}	0.073	0.074

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.164	0.091 + 0.036*SL	0.088 + 0.037*SL	0.080 + 0.038*SL
	t_F	0.152	0.085 + 0.033*SL	0.087 + 0.033*SL	0.082 + 0.033*SL
	t_{PLH}	0.563	0.522 + 0.021*SL	0.531 + 0.018*SL	0.535 + 0.018*SL
	t_{PHL}	0.631	0.586 + 0.022*SL	0.598 + 0.019*SL	0.606 + 0.018*SL
SCK to Q	t_R	0.184	0.112 + 0.036*SL	0.111 + 0.036*SL	0.100 + 0.037*SL
	t_F	0.158	0.091 + 0.034*SL	0.095 + 0.033*SL	0.092 + 0.033*SL
	t_{PLH}	0.699	0.655 + 0.022*SL	0.669 + 0.019*SL	0.677 + 0.018*SL
	t_{PHL}	0.638	0.592 + 0.023*SL	0.605 + 0.020*SL	0.615 + 0.018*SL
SN to Q	t_R	0.189	0.120 + 0.035*SL	0.115 + 0.036*SL	0.104 + 0.037*SL
	t_{PLH}	0.784	0.739 + 0.023*SL	0.755 + 0.019*SL	0.763 + 0.018*SL
CK to QN	t_R	0.195	0.115 + 0.040*SL	0.128 + 0.037*SL	0.130 + 0.037*SL
	t_F	0.152	0.084 + 0.034*SL	0.090 + 0.033*SL	0.092 + 0.032*SL
	t_{PLH}	0.810	0.758 + 0.026*SL	0.778 + 0.021*SL	0.798 + 0.019*SL
	t_{PHL}	0.727	0.682 + 0.023*SL	0.694 + 0.020*SL	0.704 + 0.018*SL
SCK to QN	t_R	0.167	0.094 + 0.036*SL	0.094 + 0.036*SL	0.087 + 0.037*SL
	t_F	0.141	0.078 + 0.031*SL	0.079 + 0.031*SL	0.073 + 0.032*SL
	t_{PLH}	0.778	0.735 + 0.021*SL	0.747 + 0.018*SL	0.754 + 0.017*SL
	t_{PHL}	0.830	0.788 + 0.021*SL	0.799 + 0.018*SL	0.806 + 0.017*SL
SN to QN	t_F	0.164	0.094 + 0.035*SL	0.097 + 0.034*SL	0.103 + 0.033*SL
	t_{PHL}	0.315	0.266 + 0.024*SL	0.280 + 0.021*SL	0.292 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.121	0.084 + 0.019*SL	0.086 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.114	0.078 + 0.018*SL	0.086 + 0.016*SL	0.083 + 0.017*SL
	t_{PLH}	0.570	0.543 + 0.013*SL	0.556 + 0.010*SL	0.569 + 0.009*SL
	t_{PHL}	0.635	0.607 + 0.014*SL	0.621 + 0.011*SL	0.638 + 0.009*SL
SCK to Q	t_R	0.143	0.104 + 0.019*SL	0.109 + 0.018*SL	0.103 + 0.018*SL
	t_F	0.123	0.087 + 0.018*SL	0.093 + 0.016*SL	0.093 + 0.016*SL
	t_{PLH}	0.715	0.686 + 0.015*SL	0.702 + 0.011*SL	0.720 + 0.009*SL
	t_{PHL}	0.649	0.620 + 0.015*SL	0.634 + 0.011*SL	0.653 + 0.010*SL
SN to Q	t_R	0.149	0.110 + 0.019*SL	0.118 + 0.017*SL	0.110 + 0.018*SL
	t_{PLH}	0.843	0.813 + 0.015*SL	0.830 + 0.011*SL	0.850 + 0.009*SL
CK to QN	t_R	0.146	0.099 + 0.023*SL	0.114 + 0.020*SL	0.128 + 0.019*SL
	t_F	0.117	0.079 + 0.019*SL	0.086 + 0.017*SL	0.091 + 0.017*SL
	t_{PLH}	0.862	0.829 + 0.016*SL	0.844 + 0.013*SL	0.874 + 0.010*SL
	t_{PHL}	0.776	0.746 + 0.015*SL	0.759 + 0.012*SL	0.778 + 0.010*SL
SCK to QN	t_R	0.126	0.086 + 0.020*SL	0.093 + 0.019*SL	0.090 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.079 + 0.016*SL	0.077 + 0.016*SL
	t_{PLH}	0.843	0.814 + 0.014*SL	0.828 + 0.011*SL	0.846 + 0.009*SL
	t_{PHL}	0.896	0.868 + 0.014*SL	0.881 + 0.011*SL	0.898 + 0.009*SL
SN to QN	t_F	0.126	0.086 + 0.020*SL	0.095 + 0.018*SL	0.100 + 0.017*SL
	t_{PHL}	0.311	0.279 + 0.016*SL	0.294 + 0.012*SL	0.315 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD3S/FD3SD2

D Flip-Flop with Set, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CK	SN	Q (n+1)	QN (n+1)
0	x	0	↑	1	0	1
1	x	0	↑	1	1	0
x	0	1	↑	1	0	1
x	1	1	↑	1	1	0
x	x	x	x	0	1	0
x	x	x	↓	1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD3S					*FD3SD2*					*FD3S*	*FD3SD2*
D	CK	SN	TI	TE	D	CK	SN	TI	TE		
0.5	0.5	1.5	0.6	1.2	0.5	0.5	1.5	0.6	1.2	7.33	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3S	FD3SD2
Input Setup Time (D to CK)	t_{SU}	0.573	0.561
Input Hold Time (D to CK)	t_{HD}	0.007	0.025
Pulse Width Low (CK)	t_{PWL}	0.717	0.701
Pulse Width High (CK)	t_{PWH}	0.430	0.461
Pulse Width Low (SN)	t_{PWL}	0.381	0.427
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.337	0.339
Input Setup Time (TI to CK)	t_{SU}	0.558	0.543
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.591	0.577
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.161	0.089 + 0.036*SL	0.085 + 0.037*SL	0.078 + 0.038*SL
	t_F	0.150	0.085 + 0.033*SL	0.084 + 0.033*SL	0.082 + 0.033*SL
	t_{PLH}	0.561	0.520 + 0.020*SL	0.530 + 0.018*SL	0.535 + 0.017*SL
	t_{PHL}	0.633	0.589 + 0.022*SL	0.600 + 0.019*SL	0.609 + 0.018*SL
SN to Q	t_R	0.165	0.095 + 0.035*SL	0.089 + 0.036*SL	0.079 + 0.038*SL
	t_{PLH}	0.533	0.492 + 0.021*SL	0.503 + 0.018*SL	0.507 + 0.017*SL
CK to QN	t_R	0.166	0.093 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.038*SL
	t_F	0.143	0.077 + 0.033*SL	0.077 + 0.033*SL	0.071 + 0.034*SL
	t_{PLH}	0.771	0.728 + 0.021*SL	0.740 + 0.018*SL	0.748 + 0.017*SL
	t_{PHL}	0.690	0.647 + 0.021*SL	0.658 + 0.019*SL	0.664 + 0.018*SL
SN to QN	t_F	0.158	0.087 + 0.036*SL	0.095 + 0.034*SL	0.099 + 0.033*SL
	t_{PHL}	0.296	0.248 + 0.024*SL	0.260 + 0.021*SL	0.273 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD3SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.120	0.083 + 0.019*SL	0.084 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.082 + 0.017*SL	0.084 + 0.017*SL
	t_{PLH}	0.564	0.538 + 0.013*SL	0.550 + 0.010*SL	0.563 + 0.009*SL
	t_{PHL}	0.630	0.602 + 0.014*SL	0.616 + 0.011*SL	0.633 + 0.009*SL
SN to Q	t_R	0.125	0.089 + 0.018*SL	0.090 + 0.018*SL	0.081 + 0.019*SL
	t_{PLH}	0.578	0.552 + 0.013*SL	0.565 + 0.010*SL	0.579 + 0.009*SL
CK to QN	t_R	0.126	0.086 + 0.020*SL	0.092 + 0.019*SL	0.089 + 0.019*SL
	t_F	0.106	0.070 + 0.018*SL	0.076 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.823	0.795 + 0.014*SL	0.808 + 0.011*SL	0.827 + 0.009*SL
	t_{PHL}	0.735	0.707 + 0.014*SL	0.720 + 0.011*SL	0.737 + 0.009*SL
SN to QN	t_F	0.118	0.079 + 0.020*SL	0.087 + 0.018*SL	0.097 + 0.017*SL
	t_{PHL}	0.288	0.258 + 0.015*SL	0.272 + 0.012*SL	0.291 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD3SQ/FD3SQD2

D Flip-Flop with Set, Scan, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CK	SN	Q (n+1)
0	x	0	↑	1	0
1	x	0	↑	1	1
x	0	1	↑	1	0
x	1	1	↑	1	1
x	x	x	x	0	1
x	x	x	↓	1	Q (n)

Cell Data

Input Load (SL)										Gate Count	
FD3SQ					*FD3SQD2*					*FD3SQ*	*FD3SQD2*
D	CK	SN	TI	TE	D	CK	SN	TI	TE		
0.5	0.5	1.1	0.6	1.2	0.5	0.5	1.1	0.6	1.2	7.00	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3SQ	FD3SQD2
Input Setup Time (D to CK)	t_{SU}	0.570	0.568
Input Hold Time (D to CK)	t_{HD}	0.008	0.008
Pulse Width Low (CK)	t_{PWL}	0.714	0.714
Pulse Width High (CK)	t_{PWH}	0.403	0.420
Pulse Width Low (SN)	t_{PWL}	0.768	0.798
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.330	0.334
Input Setup Time (TI to CK)	t_{SU}	0.556	0.554
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.590	0.588
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.153	0.081 + 0.036*SL	0.076 + 0.037*SL	0.068 + 0.039*SL
	t_F	0.138	0.077 + 0.030*SL	0.075 + 0.031*SL	0.071 + 0.031*SL
	t_{PLH}	0.535	0.495 + 0.020*SL	0.503 + 0.018*SL	0.507 + 0.017*SL
	t_{PHL}	0.613	0.572 + 0.021*SL	0.584 + 0.018*SL	0.591 + 0.017*SL
SN to Q	t_R	0.169	0.099 + 0.035*SL	0.092 + 0.037*SL	0.082 + 0.038*SL
	t_{PLH}	0.868	0.823 + 0.023*SL	0.840 + 0.019*SL	0.846 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD3SQD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.116	0.080 + 0.018*SL	0.079 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.109	0.074 + 0.018*SL	0.084 + 0.015*SL	0.081 + 0.016*SL
	t_{PLH}	0.544	0.518 + 0.013*SL	0.530 + 0.010*SL	0.541 + 0.009*SL
	t_{PHL}	0.630	0.602 + 0.014*SL	0.616 + 0.010*SL	0.634 + 0.009*SL
SN to Q	t_R	0.132	0.095 + 0.019*SL	0.100 + 0.018*SL	0.088 + 0.019*SL
	t_{PLH}	0.886	0.856 + 0.015*SL	0.876 + 0.010*SL	0.893 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	CK	SN	Q (n+1)
0	↑	1	0
1	↑	1	1
x	x	0	1
x	↓	x	Q (n)

Cell Data

Input Load (SL)						Gate Count	
FD3Q			*FD3QD2*			*FD3Q*	*FD3QD2*
D	CK	SN	D	CK	SN		
0.5	0.5	1.1	0.5	0.5	1.1	5.33	5.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD3Q	FD3QD2
Input Setup Time (D to CK)	t_{SU}	0.279	0.283
Input Hold Time (D to CK)	t_{HD}	0.127	0.127
Pulse Width Low (CK)	t_{PWL}	0.514	0.396
Pulse Width High (CK)	t_{PWH}	0.394	0.410
Pulse Width Low (SN)	t_{PWL}	0.727	0.758
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.334	0.334

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD3Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.153	0.081 + 0.036*SL	0.076 + 0.037*SL	0.068 + 0.038*SL
	t_F	0.137	0.075 + 0.031*SL	0.076 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.524	0.484 + 0.020*SL	0.492 + 0.018*SL	0.495 + 0.017*SL
	t_{PHL}	0.585	0.544 + 0.021*SL	0.555 + 0.018*SL	0.562 + 0.017*SL
SN to Q	t_R	0.167	0.097 + 0.035*SL	0.092 + 0.036*SL	0.081 + 0.038*SL
	t_{PLH}	0.813	0.769 + 0.022*SL	0.784 + 0.018*SL	0.790 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD3QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.115	0.078 + 0.019*SL	0.080 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.106	0.071 + 0.017*SL	0.080 + 0.015*SL	0.076 + 0.016*SL
	t_{PLH}	0.532	0.506 + 0.013*SL	0.518 + 0.010*SL	0.529 + 0.009*SL
	t_{PHL}	0.594	0.567 + 0.013*SL	0.580 + 0.010*SL	0.597 + 0.009*SL
SN to Q	t_R	0.131	0.094 + 0.018*SL	0.097 + 0.018*SL	0.085 + 0.019*SL
	t_{PLH}	0.829	0.800 + 0.015*SL	0.818 + 0.010*SL	0.834 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	CK	RN	SN	Q (n+1)	QN (n+1)
0	↑	1	1	0	1
1	↑	1	1	1	0
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	0	0
x	↓	1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD4				*FD4D2*				*FD4*	*FD4D2*
D	CK	RN	SN	D	CK	RN	SN		
0.6	0.6	1.5	1.6	0.5	0.6	1.5	1.6	6.67	7.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4	FD4D2
Input Setup Time (D to CK)	t_{SU}	0.273	0.273
Input Hold Time (D to CK)	t_{HD}	0.165	0.174
Pulse Width Low (CK)	t_{PWL}	0.518	0.510
Pulse Width High (CK)	t_{PWH}	0.459	0.497
Pulse Width Low (RN)	t_{PWL}	0.378	0.430
Pulse Width Low (SN)	t_{PWL}	0.397	0.451
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.633	0.616
Recovery Time (SN to CK)	t_{RC}	0.017	0.017
Removal Time (SN to CK)	t_{RM}	0.351	0.356
Removal Time (SN to RN)	t_{RM}	0.145	0.133
Recovery Time (SN to RN)	t_{RC}	0.134	0.146

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.177	0.102 + 0.038*SL	0.104 + 0.037*SL	0.099 + 0.038*SL
	t_F	0.147	0.084 + 0.031*SL	0.085 + 0.031*SL	0.082 + 0.031*SL
	t_{PLH}	0.616	0.570 + 0.023*SL	0.584 + 0.019*SL	0.594 + 0.018*SL
	t_{PHL}	0.634	0.590 + 0.022*SL	0.603 + 0.019*SL	0.612 + 0.017*SL
RN to Q	t_R	0.169	0.093 + 0.038*SL	0.094 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.143	0.080 + 0.031*SL	0.080 + 0.031*SL	0.078 + 0.032*SL
	t_{PLH}	0.257	0.212 + 0.022*SL	0.226 + 0.019*SL	0.234 + 0.018*SL
	t_{PHL}	0.270	0.228 + 0.021*SL	0.240 + 0.018*SL	0.247 + 0.017*SL
SN to Q	t_R	0.178	0.104 + 0.037*SL	0.103 + 0.037*SL	0.098 + 0.038*SL
	t_{PLH}	0.576	0.530 + 0.023*SL	0.545 + 0.019*SL	0.555 + 0.018*SL
CK to QN	t_R	0.163	0.090 + 0.036*SL	0.089 + 0.037*SL	0.083 + 0.037*SL
	t_F	0.141	0.076 + 0.033*SL	0.077 + 0.033*SL	0.072 + 0.033*SL
	t_{PLH}	0.776	0.733 + 0.022*SL	0.746 + 0.018*SL	0.754 + 0.017*SL
	t_{PHL}	0.747	0.703 + 0.022*SL	0.715 + 0.019*SL	0.723 + 0.018*SL
RN to QN	t_R	0.190	0.107 + 0.041*SL	0.122 + 0.037*SL	0.127 + 0.037*SL
	t_{PLH}	0.464	0.411 + 0.027*SL	0.431 + 0.022*SL	0.452 + 0.019*SL
SN to QN	t_R	0.186	0.104 + 0.041*SL	0.120 + 0.037*SL	0.123 + 0.037*SL
	t_F	0.155	0.084 + 0.036*SL	0.090 + 0.034*SL	0.095 + 0.033*SL
	t_{PLH}	0.283	0.230 + 0.026*SL	0.249 + 0.022*SL	0.270 + 0.019*SL
	t_{PHL}	0.295	0.247 + 0.024*SL	0.261 + 0.021*SL	0.273 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.135	0.094 + 0.021*SL	0.102 + 0.019*SL	0.101 + 0.019*SL
	t_F	0.114	0.077 + 0.019*SL	0.087 + 0.016*SL	0.085 + 0.017*SL
	t_{PLH}	0.619	0.589 + 0.015*SL	0.603 + 0.011*SL	0.624 + 0.009*SL
	t_{PHL}	0.638	0.609 + 0.015*SL	0.623 + 0.011*SL	0.642 + 0.009*SL
RN to Q	t_R	0.125	0.083 + 0.021*SL	0.092 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.110	0.073 + 0.018*SL	0.079 + 0.017*SL	0.081 + 0.017*SL
	t_{PLH}	0.256	0.228 + 0.014*SL	0.242 + 0.011*SL	0.261 + 0.009*SL
	t_{PHL}	0.266	0.237 + 0.014*SL	0.251 + 0.011*SL	0.268 + 0.009*SL
SN to Q	t_R	0.137	0.096 + 0.020*SL	0.103 + 0.019*SL	0.103 + 0.019*SL
	t_{PLH}	0.628	0.599 + 0.015*SL	0.614 + 0.011*SL	0.635 + 0.009*SL
CK to QN	t_R	0.126	0.086 + 0.020*SL	0.092 + 0.019*SL	0.090 + 0.019*SL
	t_F	0.109	0.072 + 0.018*SL	0.080 + 0.016*SL	0.079 + 0.016*SL
	t_{PLH}	0.832	0.804 + 0.014*SL	0.817 + 0.011*SL	0.836 + 0.009*SL
	t_{PHL}	0.801	0.772 + 0.014*SL	0.786 + 0.011*SL	0.804 + 0.009*SL
RN to QN	t_R	0.145	0.098 + 0.024*SL	0.112 + 0.020*SL	0.127 + 0.019*SL
	t_{PLH}	0.508	0.475 + 0.017*SL	0.490 + 0.013*SL	0.521 + 0.010*SL
SN to QN	t_R	0.142	0.096 + 0.023*SL	0.109 + 0.020*SL	0.123 + 0.019*SL
	t_F	0.119	0.079 + 0.020*SL	0.089 + 0.017*SL	0.096 + 0.017*SL
	t_{PLH}	0.284	0.251 + 0.016*SL	0.266 + 0.013*SL	0.296 + 0.010*SL
	t_{PHL}	0.294	0.263 + 0.015*SL	0.277 + 0.012*SL	0.298 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

SI	SCK	D	CK	RN	SN	Q (n+1)	QN (n+1)
x	0	0	↑	1	1	0	1
x	0	1	↑	1	1	1	0
0	↑	x	0	1	1	0	1
1	↑	x	0	1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	0	x	↓	1	1	Q(n)	QN(n)
x	↓	x	0	1	1	Q(n)	QN(n)

Cell Data

Input Load (SL)												Gate Count	
FD4CS						*FD4CSD2*						*FD4CS*	*FD4CSD2*
D	SI	CK	SCK	SN	RN	D	SI	CK	SCK	SN	RN		
0.6	0.6	0.6	1.4	2.5	2.2	0.6	0.6	0.6	1.4	2.4	2.2	10.33	11.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4CS	FD4CSD2
Input Setup Time (D to CK)	t_{SU}	0.308	0.308
Input Hold Time (D to CK)	t_{HD}	0.150	0.150
Input Setup Time (SI to SCK)	t_{SU}	0.520	0.521
Input Hold Time (SI to SCK)	t_{HD}	0.028	0.030
Pulse Width Low (CK)	t_{PWL}	0.550	0.550
Pulse Width High (CK)	t_{PWH}	0.485	0.528
Pulse Width Low (SCK)	t_{PWL}	0.470	0.470
Pulse Width High (SCK)	t_{PWH}	0.576	0.630
Pulse Width Low (SN)	t_{PWL}	0.559	0.619
Recovery Time (SN to CK)	t_{RC}	0.013	0.011
Removal Time (SN to CK)	t_{RM}	0.389	0.390
Recovery Time (SN to SCK)	t_{RC}	0.207	0.206
Removal Time (SN to SCK)	t_{RM}	0.117	0.118
Pulse Width Low (RN)	t_{PWL}	0.483	0.539
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.667	0.667
Recovery Time (RN to SCK)	t_{RC}	0.000	0.000
Removal Time (RN to SCK)	t_{RM}	0.604	0.611
Removal Time (SN to RN)	t_{RM}	0.105	0.106
Recovery Time (SN to RN)	t_{RC}	0.175	0.173

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.179	0.101 + 0.039*SL	0.105 + 0.038*SL	0.099 + 0.039*SL
	t_F	0.149	0.085 + 0.032*SL	0.086 + 0.032*SL	0.082 + 0.032*SL
	t_{PLH}	0.626	0.579 + 0.023*SL	0.593 + 0.020*SL	0.602 + 0.019*SL
	t_{PHL}	0.630	0.586 + 0.022*SL	0.599 + 0.019*SL	0.608 + 0.018*SL
SCK to Q	t_R	0.196	0.119 + 0.039*SL	0.124 + 0.037*SL	0.117 + 0.038*SL
	t_F	0.156	0.091 + 0.033*SL	0.096 + 0.031*SL	0.093 + 0.032*SL
	t_{PLH}	0.760	0.711 + 0.024*SL	0.728 + 0.020*SL	0.740 + 0.019*SL
	t_{PHL}	0.650	0.605 + 0.023*SL	0.619 + 0.019*SL	0.630 + 0.018*SL
SN to Q	t_R	0.197	0.122 + 0.038*SL	0.126 + 0.037*SL	0.115 + 0.038*SL
	t_{PLH}	0.830	0.781 + 0.024*SL	0.799 + 0.020*SL	0.810 + 0.018*SL
RN to Q	t_R	0.170	0.093 + 0.038*SL	0.094 + 0.038*SL	0.088 + 0.039*SL
	t_F	0.142	0.078 + 0.032*SL	0.079 + 0.032*SL	0.075 + 0.033*SL
	t_{PLH}	0.252	0.207 + 0.022*SL	0.221 + 0.019*SL	0.229 + 0.018*SL
	t_{PHL}	0.264	0.221 + 0.021*SL	0.232 + 0.019*SL	0.239 + 0.018*SL
CK to QN	t_R	0.201	0.119 + 0.041*SL	0.133 + 0.038*SL	0.135 + 0.037*SL
	t_F	0.159	0.092 + 0.034*SL	0.095 + 0.033*SL	0.098 + 0.033*SL
	t_{PLH}	0.821	0.768 + 0.027*SL	0.788 + 0.022*SL	0.809 + 0.019*SL
	t_{PHL}	0.810	0.764 + 0.023*SL	0.777 + 0.020*SL	0.787 + 0.019*SL
SCK to QN	t_R	0.171	0.097 + 0.037*SL	0.096 + 0.037*SL	0.091 + 0.038*SL
	t_F	0.146	0.083 + 0.032*SL	0.084 + 0.031*SL	0.079 + 0.032*SL
	t_{PLH}	0.800	0.757 + 0.022*SL	0.769 + 0.019*SL	0.777 + 0.018*SL
	t_{PHL}	0.903	0.860 + 0.021*SL	0.872 + 0.018*SL	0.880 + 0.017*SL
SN to QN	t_R	0.210	0.116 + 0.047*SL	0.133 + 0.043*SL	0.159 + 0.039*SL
	t_F	0.168	0.098 + 0.035*SL	0.102 + 0.034*SL	0.105 + 0.034*SL
	t_{PLH}	0.303	0.246 + 0.028*SL	0.261 + 0.025*SL	0.281 + 0.022*SL
	t_{PHL}	0.322	0.272 + 0.025*SL	0.287 + 0.021*SL	0.299 + 0.019*SL
RN to QN	t_R	0.214	0.120 + 0.047*SL	0.137 + 0.043*SL	0.163 + 0.039*SL
	t_{PLH}	0.470	0.412 + 0.029*SL	0.428 + 0.025*SL	0.448 + 0.022*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.139	0.099 + 0.020*SL	0.105 + 0.018*SL	0.104 + 0.018*SL
	t_F	0.118	0.081 + 0.018*SL	0.089 + 0.016*SL	0.087 + 0.017*SL
	t_{PLH}	0.636	0.607 + 0.014*SL	0.621 + 0.011*SL	0.641 + 0.009*SL
	t_{PHL}	0.637	0.608 + 0.014*SL	0.622 + 0.011*SL	0.640 + 0.009*SL
SCK to Q	t_R	0.156	0.115 + 0.020*SL	0.125 + 0.018*SL	0.124 + 0.018*SL
	t_F	0.127	0.091 + 0.018*SL	0.096 + 0.016*SL	0.097 + 0.016*SL
	t_{PLH}	0.778	0.748 + 0.015*SL	0.763 + 0.011*SL	0.787 + 0.009*SL
	t_{PHL}	0.668	0.639 + 0.015*SL	0.653 + 0.011*SL	0.673 + 0.010*SL
SN to Q	t_R	0.160	0.121 + 0.020*SL	0.128 + 0.018*SL	0.128 + 0.018*SL
	t_{PLH}	0.886	0.855 + 0.015*SL	0.871 + 0.011*SL	0.895 + 0.009*SL
RN to Q	t_R	0.128	0.087 + 0.020*SL	0.095 + 0.018*SL	0.095 + 0.018*SL
	t_F	0.113	0.078 + 0.018*SL	0.082 + 0.017*SL	0.083 + 0.017*SL
	t_{PLH}	0.256	0.228 + 0.014*SL	0.241 + 0.011*SL	0.260 + 0.009*SL
	t_{PHL}	0.270	0.242 + 0.014*SL	0.255 + 0.011*SL	0.272 + 0.009*SL
CK to QN	t_R	0.150	0.105 + 0.022*SL	0.117 + 0.020*SL	0.131 + 0.018*SL
	t_F	0.124	0.086 + 0.019*SL	0.094 + 0.017*SL	0.099 + 0.017*SL
	t_{PLH}	0.868	0.835 + 0.016*SL	0.850 + 0.013*SL	0.880 + 0.010*SL
	t_{PHL}	0.873	0.843 + 0.015*SL	0.857 + 0.012*SL	0.877 + 0.010*SL
SCK to QN	t_R	0.130	0.090 + 0.020*SL	0.097 + 0.018*SL	0.096 + 0.018*SL
	t_F	0.116	0.081 + 0.018*SL	0.086 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.867	0.839 + 0.014*SL	0.853 + 0.011*SL	0.872 + 0.009*SL
	t_{PHL}	0.984	0.956 + 0.014*SL	0.969 + 0.011*SL	0.988 + 0.009*SL
SN to QN	t_R	0.152	0.104 + 0.024*SL	0.112 + 0.022*SL	0.141 + 0.020*SL
	t_F	0.129	0.089 + 0.020*SL	0.098 + 0.018*SL	0.104 + 0.017*SL
	t_{PLH}	0.297	0.263 + 0.017*SL	0.276 + 0.013*SL	0.301 + 0.011*SL
	t_{PHL}	0.317	0.285 + 0.016*SL	0.300 + 0.012*SL	0.321 + 0.010*SL
RN to QN	t_R	0.159	0.111 + 0.024*SL	0.118 + 0.022*SL	0.146 + 0.020*SL
	t_{PLH}	0.518	0.484 + 0.017*SL	0.497 + 0.014*SL	0.522 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	TI	TE	CK	RN	SN	Q (n+1)	QN (n+1)
0	x	0	↑	1	1	0	1
1	x	0	↑	1	1	1	0
x	0	1	↑	1	1	0	1
x	1	1	↑	1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	x	x	↓	1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)												Gate Count	
FD4S						*FD4SD2*						*FD4S*	*FD4SD2*
D	CK	RN	SN	TI	IE	D	CK	RN	SN	TI	IE		
0.5	0.6	1.5	1.5	0.6	1.2	0.5	0.6	1.5	1.6	0.6	1.2	8.67	9.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4S	FD4SD2
Input Setup Time (D to CK)	t_{SU}	0.569	0.575
Input Hold Time (D to CK)	t_{HD}	0.086	0.083
Pulse Width Low (CK)	t_{PWL}	0.728	0.735
Pulse Width High (CK)	t_{PWH}	0.490	0.520
Pulse Width Low (RN)	t_{PWL}	0.379	0.440
Pulse Width Low (SN)	t_{PWL}	0.412	0.469
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.631	0.638
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.373	0.388
Input Setup Time (TI to CK)	t_{SU}	0.570	0.577
Input Hold Time (TI to CK)	t_{HD}	0.032	0.032
Input Setup Time (TE to CK)	t_{SU}	0.589	0.595
Input Hold Time (TE to CK)	t_{HD}	0.030	0.027
Recovery Time (SN to RN)	t_{RC}	0.148	0.144
Removal Time (SN to RN)	t_{RM}	0.132	0.135

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.177	0.102 + 0.038*SL	0.104 + 0.037*SL	0.098 + 0.038*SL
	t_F	0.151	0.083 + 0.034*SL	0.087 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.655	0.609 + 0.023*SL	0.624 + 0.019*SL	0.634 + 0.018*SL
	t_{PHL}	0.665	0.620 + 0.023*SL	0.632 + 0.020*SL	0.641 + 0.018*SL
RN to Q	t_R	0.166	0.090 + 0.038*SL	0.092 + 0.037*SL	0.086 + 0.038*SL
	t_F	0.146	0.079 + 0.034*SL	0.079 + 0.033*SL	0.077 + 0.034*SL
	t_{PLH}	0.249	0.205 + 0.022*SL	0.218 + 0.019*SL	0.226 + 0.018*SL
	t_{PHL}	0.267	0.223 + 0.022*SL	0.234 + 0.019*SL	0.241 + 0.018*SL
SN to Q	t_R	0.177	0.103 + 0.037*SL	0.104 + 0.037*SL	0.097 + 0.038*SL
	t_{PLH}	0.591	0.546 + 0.023*SL	0.561 + 0.019*SL	0.570 + 0.018*SL
CK to QN	t_R	0.165	0.091 + 0.037*SL	0.088 + 0.038*SL	0.083 + 0.038*SL
	t_F	0.144	0.078 + 0.033*SL	0.078 + 0.033*SL	0.071 + 0.034*SL
	t_{PLH}	0.801	0.758 + 0.022*SL	0.770 + 0.019*SL	0.777 + 0.018*SL
	t_{PHL}	0.786	0.742 + 0.022*SL	0.754 + 0.019*SL	0.761 + 0.018*SL
RN to QN	t_R	0.197	0.112 + 0.043*SL	0.129 + 0.039*SL	0.135 + 0.038*SL
	t_{PLH}	0.458	0.403 + 0.027*SL	0.423 + 0.023*SL	0.447 + 0.019*SL
SN to QN	t_R	0.193	0.108 + 0.043*SL	0.124 + 0.039*SL	0.131 + 0.038*SL
	t_F	0.161	0.090 + 0.036*SL	0.095 + 0.035*SL	0.101 + 0.034*SL
	t_{PLH}	0.285	0.231 + 0.027*SL	0.250 + 0.022*SL	0.272 + 0.019*SL
	t_{PHL}	0.304	0.255 + 0.025*SL	0.269 + 0.021*SL	0.281 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.136	0.095 + 0.021*SL	0.102 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.116	0.080 + 0.018*SL	0.087 + 0.016*SL	0.087 + 0.017*SL
	t_{PLH}	0.651	0.621 + 0.015*SL	0.635 + 0.011*SL	0.656 + 0.009*SL
	t_{PHL}	0.662	0.633 + 0.015*SL	0.647 + 0.011*SL	0.665 + 0.010*SL
RN to Q	t_R	0.126	0.084 + 0.021*SL	0.092 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.110	0.073 + 0.018*SL	0.078 + 0.017*SL	0.081 + 0.017*SL
	t_{PLH}	0.254	0.226 + 0.014*SL	0.239 + 0.011*SL	0.259 + 0.009*SL
	t_{PHL}	0.265	0.236 + 0.014*SL	0.250 + 0.011*SL	0.266 + 0.009*SL
SN to Q	t_R	0.139	0.098 + 0.020*SL	0.106 + 0.018*SL	0.103 + 0.019*SL
	t_{PLH}	0.651	0.621 + 0.015*SL	0.636 + 0.011*SL	0.657 + 0.009*SL
CK to QN	t_R	0.129	0.088 + 0.021*SL	0.095 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.111	0.075 + 0.018*SL	0.083 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.864	0.835 + 0.014*SL	0.849 + 0.011*SL	0.869 + 0.009*SL
	t_{PHL}	0.845	0.816 + 0.014*SL	0.830 + 0.011*SL	0.849 + 0.009*SL
RN to QN	t_R	0.150	0.103 + 0.024*SL	0.116 + 0.020*SL	0.134 + 0.019*SL
	t_{PLH}	0.515	0.481 + 0.017*SL	0.497 + 0.013*SL	0.529 + 0.010*SL
SN to QN	t_R	0.146	0.098 + 0.024*SL	0.113 + 0.020*SL	0.131 + 0.019*SL
	t_F	0.123	0.085 + 0.019*SL	0.092 + 0.018*SL	0.102 + 0.017*SL
	t_{PLH}	0.293	0.259 + 0.017*SL	0.274 + 0.013*SL	0.306 + 0.010*SL
	t_{PHL}	0.306	0.275 + 0.016*SL	0.290 + 0.012*SL	0.311 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	TI	TE	CK	RN	SN	Q (n+1)
0	x	0	↑	1	1	0
1	x	0	↑	1	1	1
x	0	1	↑	1	1	0
x	1	1	↑	1	1	1
x	x	x	x	1	0	1
x	x	x	x	0	1	0
x	x	x	x	0	0	0
x	x	x	↓	1	1	Q (n)

Cell Data

Input Load (SL)												Gate Count	
FD4SQ						*FD4SQD2*						*FD4SQ*	*FD4SQD2*
D	CK	RN	SN	TI	TE	D	CK	RN	SN	TI	TE		
0.5	0.6	1.5	1.1	0.6	1.2	0.5	0.6	1.5	1.1	0.6	1.2	8.00	8.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4SQ	FD4SQD2
Input Setup Time (D to CK)	t_{SU}	0.605	0.604
Input Hold Time (D to CK)	t_{HD}	0.081	0.081
Pulse Width Low (CK)	t_{PWL}	0.757	0.756
Pulse Width High (CK)	t_{PWH}	0.426	0.447
Pulse Width Low (RN)	t_{PWL}	0.345	0.372
Pulse Width Low (SN)	t_{PWL}	0.775	0.806
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.629	0.629
Recovery Time (SN to CK)	t_{RC}	0.029	0.029
Removal Time (SN to CK)	t_{RM}	0.373	0.373
Input Setup Time (TI to CK)	t_{SU}	0.600	0.599
Input Hold Time (TI to CK)	t_{HD}	0.032	0.032
Input Setup Time (TE to CK)	t_{SU}	0.619	0.618
Input Hold Time (TE to CK)	t_{HD}	0.029	0.029
Removal Time (SN to RN)	t_{RM}	0.140	0.142
Recovery Time (SN to RN)	t_{RC}	0.139	0.138

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4SQ

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.172	0.098 + 0.037*SL	0.096 + 0.037*SL	0.090 + 0.038*SL
	t_F	0.143	0.081 + 0.031*SL	0.083 + 0.031*SL	0.077 + 0.031*SL
	t_{PLH}	0.591	0.547 + 0.022*SL	0.560 + 0.019*SL	0.567 + 0.018*SL
	t_{PHL}	0.632	0.590 + 0.021*SL	0.602 + 0.018*SL	0.610 + 0.017*SL
RN to Q	t_R	0.164	0.090 + 0.037*SL	0.088 + 0.038*SL	0.083 + 0.038*SL
	t_F	0.137	0.075 + 0.031*SL	0.074 + 0.031*SL	0.070 + 0.032*SL
	t_{PLH}	0.242	0.199 + 0.021*SL	0.211 + 0.019*SL	0.217 + 0.018*SL
	t_{PHL}	0.253	0.211 + 0.021*SL	0.222 + 0.018*SL	0.228 + 0.017*SL
SN to Q	t_R	0.181	0.108 + 0.037*SL	0.107 + 0.037*SL	0.100 + 0.038*SL
	t_{PLH}	0.913	0.868 + 0.022*SL	0.883 + 0.019*SL	0.891 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD4SQD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.130	0.089 + 0.020*SL	0.097 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.110	0.075 + 0.018*SL	0.084 + 0.015*SL	0.082 + 0.015*SL
	t_{PLH}	0.600	0.571 + 0.014*SL	0.585 + 0.011*SL	0.604 + 0.009*SL
	t_{PHL}	0.636	0.609 + 0.014*SL	0.622 + 0.010*SL	0.641 + 0.009*SL
RN to Q	t_R	0.123	0.082 + 0.020*SL	0.088 + 0.019*SL	0.086 + 0.019*SL
	t_F	0.104	0.070 + 0.017*SL	0.076 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.248	0.220 + 0.014*SL	0.233 + 0.011*SL	0.250 + 0.009*SL
	t_{PHL}	0.251	0.224 + 0.013*SL	0.237 + 0.010*SL	0.253 + 0.009*SL
SN to Q	t_R	0.142	0.102 + 0.020*SL	0.109 + 0.018*SL	0.104 + 0.019*SL
	t_{PLH}	0.928	0.899 + 0.015*SL	0.913 + 0.011*SL	0.934 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD4Q/FD4QD2

D Flip-Flop with Reset, Set, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	CK	RN	SN	Q (n+1)
0	↑	1	1	0
1	↑	1	1	1
x	x	1	0	1
x	x	0	1	0
x	x	0	0	0
x	↓	1	1	Q (n)

Cell Data

Input Load (SL)								Gate Count	
FD4Q				*FD4QD2*				*FD4Q*	*FD4QD2*
D	CK	RN	SN	D	CK	RN	SN		
0.6	0.6	1.5	1.2	0.6	0.6	1.5	1.2	6.00	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD4Q	FD4QD2
Input Setup Time (D to CK)	t_{SU}	0.276	0.277
Input Hold Time (D to CK)	t_{HD}	0.167	0.167
Pulse Width Low (CK)	t_{PWL}	0.520	0.518
Pulse Width High (CK)	t_{PWH}	0.426	0.448
Pulse Width Low (RN)	t_{PWL}	0.343	0.375
Pulse Width Low (SN)	t_{PWL}	0.764	0.801
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.636	0.637
Recovery Time (SN to CK)	t_{RC}	0.015	0.015
Removal Time (SN to CK)	t_{RM}	0.350	0.350
Recovery Time (SN to RN)	t_{RC}	0.151	0.152
Removal Time (SN to RN)	t_{RM}	0.129	0.127

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD4Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.170	0.096 + 0.037*SL	0.095 + 0.037*SL	0.088 + 0.038*SL
	t_F	0.141	0.079 + 0.031*SL	0.081 + 0.031*SL	0.075 + 0.031*SL
	t_{PLH}	0.591	0.547 + 0.022*SL	0.560 + 0.019*SL	0.568 + 0.018*SL
	t_{PHL}	0.619	0.577 + 0.021*SL	0.590 + 0.018*SL	0.598 + 0.017*SL
RN to Q	t_R	0.163	0.088 + 0.037*SL	0.087 + 0.038*SL	0.082 + 0.038*SL
	t_F	0.136	0.073 + 0.032*SL	0.076 + 0.031*SL	0.070 + 0.032*SL
	t_{PLH}	0.243	0.200 + 0.022*SL	0.212 + 0.019*SL	0.219 + 0.018*SL
	t_{PHL}	0.256	0.214 + 0.021*SL	0.225 + 0.018*SL	0.232 + 0.017*SL
SN to Q	t_R	0.180	0.107 + 0.037*SL	0.107 + 0.037*SL	0.098 + 0.038*SL
	t_{PLH}	0.890	0.845 + 0.023*SL	0.859 + 0.019*SL	0.868 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD4QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.131	0.091 + 0.020*SL	0.098 + 0.019*SL	0.096 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.083 + 0.015*SL	0.083 + 0.015*SL
	t_{PLH}	0.605	0.576 + 0.014*SL	0.590 + 0.011*SL	0.609 + 0.009*SL
	t_{PHL}	0.627	0.600 + 0.014*SL	0.613 + 0.010*SL	0.632 + 0.009*SL
RN to Q	t_R	0.124	0.083 + 0.020*SL	0.090 + 0.019*SL	0.088 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.078 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.252	0.224 + 0.014*SL	0.237 + 0.011*SL	0.255 + 0.009*SL
	t_{PHL}	0.257	0.230 + 0.014*SL	0.243 + 0.010*SL	0.260 + 0.009*SL
SN to Q	t_R	0.142	0.102 + 0.020*SL	0.109 + 0.018*SL	0.108 + 0.019*SL
	t_{PLH}	0.911	0.881 + 0.015*SL	0.896 + 0.011*SL	0.916 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD5/FD5D2

D Flip-Flop with Negative Edge Trigger, 1X/2X Drive

Logic Symbol



Truth Table

D	CKN	Q (n+1)	QN (n+1)
0	↓	0	1
1	↓	1	0
x	↓	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
FD5		*FD5D2*		*FD5*	*FD5D2*
D	CKN	D	CKN		
0.6	0.5	0.6	0.5	5.00	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD5	FD5D2
Input Setup Time (D to CKN)	t_{SU}	0.289	0.287
Input Hold Time (D to CKN)	t_{HD}	0.219	0.216
Pulse Width Low (CKN)	t_{PWL}	0.425	0.435
Pulse Width High (CKN)	t_{PWH}	0.425	0.435

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.158	0.085 + 0.037*SL	0.082 + 0.037*SL	0.075 + 0.038*SL
	t_F	0.140	0.077 + 0.032*SL	0.080 + 0.031*SL	0.077 + 0.031*SL
	t_{PLH}	0.634	0.593 + 0.020*SL	0.602 + 0.018*SL	0.607 + 0.018*SL
	t_{PHL}	0.559	0.516 + 0.021*SL	0.528 + 0.018*SL	0.537 + 0.017*SL
CKN to QN	t_R	0.146	0.072 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.128	0.067 + 0.031*SL	0.064 + 0.031*SL	0.060 + 0.032*SL
	t_{PLH}	0.645	0.607 + 0.019*SL	0.613 + 0.018*SL	0.615 + 0.018*SL
	t_{PHL}	0.731	0.692 + 0.020*SL	0.701 + 0.017*SL	0.706 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.116	0.079 + 0.019*SL	0.080 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.077 + 0.017*SL	0.079 + 0.016*SL
	t_{PLH}	0.620	0.594 + 0.013*SL	0.606 + 0.010*SL	0.618 + 0.009*SL
	t_{PHL}	0.539	0.511 + 0.014*SL	0.524 + 0.011*SL	0.542 + 0.009*SL
CKN to QN	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.102	0.068 + 0.017*SL	0.072 + 0.016*SL	0.068 + 0.017*SL
	t_{PLH}	0.670	0.646 + 0.012*SL	0.656 + 0.010*SL	0.664 + 0.009*SL
	t_{PHL}	0.770	0.743 + 0.013*SL	0.755 + 0.010*SL	0.769 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD5S/FD5SD2

D Flip-Flop with Negative Edge Trigger, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CKN	Q (n+1)	QN (n+1)
0	x	0	↓	0	1
1	x	0	↓	1	0
x	0	1	↓	0	1
x	1	1	↓	1	0
x	x	x	↑	Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD5S				*FD5SD2*				*FD5S*	*FD5SD2*
D	CKN	TI	TE	D	CKN	TI	TE		
0.5	0.6	0.5	1.2	0.5	0.5	0.6	1.1	6.67	7.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD5S	FD5SD2
Input Setup Time (D to CKN)	t_{SU}	0.567	0.563
Input Hold Time (D to CKN)	t_{HD}	0.143	0.136
Pulse Width Low (CKN)	t_{PWL}	0.428	0.442
Pulse Width High (CKN)	t_{PWH}	0.428	0.442
Input Setup Time (TI to CKN)	t_{SU}	0.564	0.564
Input Hold Time (TI to CKN)	t_{HD}	0.139	0.130
Input Setup Time (TE to CKN)	t_{SU}	0.592	0.587
Input Hold Time (TE to CKN)	t_{HD}	0.166	0.168

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD5S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.159	0.086 + 0.036*SL	0.082 + 0.038*SL	0.075 + 0.038*SL
	t_F	0.139	0.074 + 0.032*SL	0.081 + 0.031*SL	0.075 + 0.032*SL
	t_{PLH}	0.646	0.605 + 0.021*SL	0.614 + 0.018*SL	0.619 + 0.018*SL
	t_{PHL}	0.557	0.514 + 0.021*SL	0.526 + 0.018*SL	0.536 + 0.017*SL
CKN to QN	t_R	0.146	0.073 + 0.037*SL	0.068 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.128	0.067 + 0.031*SL	0.064 + 0.031*SL	0.060 + 0.032*SL
	t_{PLH}	0.645	0.606 + 0.019*SL	0.613 + 0.018*SL	0.615 + 0.018*SL
	t_{PHL}	0.745	0.706 + 0.020*SL	0.715 + 0.017*SL	0.720 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD5SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.117	0.080 + 0.018*SL	0.082 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.109	0.072 + 0.018*SL	0.079 + 0.017*SL	0.080 + 0.017*SL
	t_{PLH}	0.632	0.606 + 0.013*SL	0.618 + 0.010*SL	0.630 + 0.009*SL
	t_{PHL}	0.557	0.529 + 0.014*SL	0.542 + 0.011*SL	0.559 + 0.009*SL
CKN to QN	t_R	0.107	0.072 + 0.018*SL	0.069 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.101	0.066 + 0.017*SL	0.070 + 0.016*SL	0.066 + 0.017*SL
	t_{PLH}	0.684	0.660 + 0.012*SL	0.670 + 0.010*SL	0.679 + 0.009*SL
	t_{PHL}	0.777	0.750 + 0.013*SL	0.763 + 0.010*SL	0.776 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD6/FD6D2

D Flip-Flop with Negative Edge Trigger, Reset, 1X/2X Drive

Logic Symbol



Truth Table

D	CKN	RN	Q (n+1)	QN (n+1)
0	↓	1	0	1
1	↓	1	1	0
x	x	0	0	1
x	↑	1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD6			*FD6D2*			*FD6*	*FD6D2*
D	CKN	RN	D	CKN	RN		
0.6	0.6	1.4	0.6	0.5	1.4	5.67	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD6	FD6D2
Input Setup Time (D to CKN)	t_{SU}	0.334	0.318
Input Hold Time (D to CKN)	t_{HD}	0.181	0.222
Pulse Width Low (CKN)	t_{PWL}	0.445	0.476
Pulse Width High (CKN)	t_{PWH}	0.445	0.476
Pulse Width Low (RN)	t_{PWL}	0.597	0.543
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.801	0.788

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.179	0.103 + 0.038*SL	0.107 + 0.037*SL	0.103 + 0.037*SL
	t_F	0.150	0.081 + 0.035*SL	0.088 + 0.033*SL	0.084 + 0.033*SL
	t_{PLH}	0.684	0.638 + 0.023*SL	0.652 + 0.020*SL	0.663 + 0.018*SL
	t_{PHL}	0.558	0.512 + 0.023*SL	0.525 + 0.020*SL	0.536 + 0.018*SL
RN to Q	t_F	0.151	0.084 + 0.034*SL	0.087 + 0.033*SL	0.084 + 0.033*SL
	t_{PHL}	0.274	0.229 + 0.023*SL	0.240 + 0.020*SL	0.250 + 0.018*SL
CKN to QN	t_R	0.146	0.075 + 0.036*SL	0.069 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.138	0.074 + 0.032*SL	0.071 + 0.033*SL	0.065 + 0.034*SL
	t_{PLH}	0.642	0.604 + 0.019*SL	0.611 + 0.017*SL	0.613 + 0.017*SL
	t_{PHL}	0.795	0.753 + 0.021*SL	0.763 + 0.019*SL	0.768 + 0.018*SL
RN to QN	t_R	0.168	0.090 + 0.039*SL	0.098 + 0.037*SL	0.096 + 0.037*SL
	t_{PLH}	0.399	0.352 + 0.023*SL	0.367 + 0.020*SL	0.381 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.134	0.093 + 0.020*SL	0.099 + 0.019*SL	0.100 + 0.019*SL
	t_F	0.112	0.076 + 0.018*SL	0.082 + 0.017*SL	0.085 + 0.016*SL
	t_{PLH}	0.681	0.652 + 0.015*SL	0.666 + 0.011*SL	0.686 + 0.009*SL
	t_{PHL}	0.569	0.540 + 0.015*SL	0.554 + 0.011*SL	0.572 + 0.009*SL
RN to Q	t_F	0.109	0.072 + 0.019*SL	0.079 + 0.017*SL	0.082 + 0.016*SL
	t_{PHL}	0.260	0.232 + 0.014*SL	0.245 + 0.011*SL	0.262 + 0.009*SL
CKN to QN	t_R	0.110	0.073 + 0.018*SL	0.074 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.106	0.072 + 0.017*SL	0.077 + 0.016*SL	0.074 + 0.016*SL
	t_{PLH}	0.710	0.685 + 0.012*SL	0.696 + 0.010*SL	0.706 + 0.009*SL
	t_{PHL}	0.850	0.823 + 0.014*SL	0.836 + 0.010*SL	0.852 + 0.009*SL
RN to QN	t_R	0.122	0.080 + 0.021*SL	0.088 + 0.019*SL	0.091 + 0.019*SL
	t_{PLH}	0.435	0.406 + 0.014*SL	0.419 + 0.011*SL	0.440 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD6S/FD6SD2

D Flip-Flop with Negative Edge Trigger, Reset, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CKN	RN	Q (n+1)	QN (n+1)
0	x	0	↓	1	0	1
1	x	0	↓	1	1	0
x	0	1	↓	1	0	1
x	1	1	↓	1	1	0
x	x	x	x	0	0	1
x	x	x	↑	1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD6S					*FD6SD2*					*FD6S*	*FD6SD2*
D	CKN	RN	TI	TE	D	CKN	RN	TI	TE		
0.6	0.5	1.4	0.6	1.2	0.6	0.6	1.4	0.6	1.2	7.67	8.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD6S	FD6SD2
Input Setup Time (D to CKN)	t_{SU}	0.614	0.617
Input Hold Time (D to CKN)	t_{HD}	0.130	0.128
Pulse Width Low (CKN)	t_{PWL}	0.459	0.493
Pulse Width High (CKN)	t_{PWH}	0.459	0.493
Pulse Width Low (RN)	t_{PWL}	0.559	0.563
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.784	0.787
Input Setup Time (TI to CKN)	t_{SU}	0.595	0.598
Input Hold Time (TI to CKN)	t_{HD}	0.125	0.122
Input Setup Time (TE to CKN)	t_{SU}	0.621	0.622
Input Hold Time (TE to CKN)	t_{HD}	0.153	0.151

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD6S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.180	0.104 + 0.038*SL	0.106 + 0.037*SL	0.101 + 0.038*SL
	t_F	0.144	0.079 + 0.033*SL	0.086 + 0.031*SL	0.082 + 0.031*SL
	t_{PLH}	0.719	0.673 + 0.023*SL	0.687 + 0.020*SL	0.698 + 0.018*SL
	t_{PHL}	0.580	0.537 + 0.022*SL	0.549 + 0.019*SL	0.560 + 0.017*SL
RN to Q	t_F	0.144	0.080 + 0.032*SL	0.084 + 0.031*SL	0.081 + 0.031*SL
	t_{PHL}	0.268	0.225 + 0.021*SL	0.237 + 0.019*SL	0.246 + 0.017*SL
CKN to QN	t_R	0.148	0.076 + 0.036*SL	0.069 + 0.038*SL	0.064 + 0.039*SL
	t_F	0.134	0.072 + 0.031*SL	0.071 + 0.031*SL	0.066 + 0.032*SL
	t_{PLH}	0.670	0.631 + 0.019*SL	0.638 + 0.018*SL	0.640 + 0.017*SL
	t_{PHL}	0.824	0.784 + 0.020*SL	0.794 + 0.018*SL	0.799 + 0.017*SL
RN to QN	t_R	0.171	0.092 + 0.039*SL	0.099 + 0.038*SL	0.098 + 0.038*SL
	t_{PLH}	0.398	0.352 + 0.023*SL	0.366 + 0.020*SL	0.380 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD6SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.136	0.095 + 0.021*SL	0.103 + 0.019*SL	0.103 + 0.019*SL
	t_F	0.112	0.075 + 0.019*SL	0.082 + 0.017*SL	0.084 + 0.016*SL
	t_{PLH}	0.723	0.693 + 0.015*SL	0.707 + 0.011*SL	0.728 + 0.009*SL
	t_{PHL}	0.580	0.552 + 0.014*SL	0.565 + 0.011*SL	0.584 + 0.009*SL
RN to Q	t_F	0.110	0.074 + 0.018*SL	0.079 + 0.017*SL	0.085 + 0.016*SL
	t_{PHL}	0.266	0.237 + 0.014*SL	0.251 + 0.011*SL	0.268 + 0.009*SL
CKN to QN	t_R	0.108	0.072 + 0.018*SL	0.070 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.104	0.068 + 0.018*SL	0.075 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.715	0.691 + 0.012*SL	0.701 + 0.010*SL	0.710 + 0.009*SL
	t_{PHL}	0.885	0.858 + 0.014*SL	0.870 + 0.010*SL	0.885 + 0.009*SL
RN to QN	t_R	0.123	0.080 + 0.021*SL	0.089 + 0.019*SL	0.093 + 0.019*SL
	t_{PLH}	0.436	0.407 + 0.014*SL	0.420 + 0.011*SL	0.441 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	CKN	SN	Q (n+1)	QN (n+1)
0	↓	1	0	1
1	↓	1	1	0
x	x	0	1	0
x	↑	1	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FD7			*FD7D2*			*FD7*	*FD7D2*
D	CKN	SN	D	CKN	SN		
0.6	0.6	1.5	0.6	0.6	1.5	5.67	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD7	FD7D2
Input Setup Time (D to CKN)	t_{SU}	0.326	0.326
Input Hold Time (D to CKN)	t_{HD}	0.209	0.213
Pulse Width Low (CKN)	t_{PWL}	0.443	0.465
Pulse Width High (CKN)	t_{PWH}	0.443	0.465
Pulse Width Low (SN)	t_{PWL}	0.373	0.373
Recovery Time (SN to CKN)	t_{RC}	0.018	0.019
Removal Time (SN to CKN)	t_{RM}	0.268	0.268

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.162	0.091 + 0.036*SL	0.087 + 0.037*SL	0.079 + 0.038*SL
	t_F	0.151	0.084 + 0.034*SL	0.087 + 0.033*SL	0.085 + 0.033*SL
	t_{PLH}	0.653	0.613 + 0.020*SL	0.622 + 0.018*SL	0.627 + 0.017*SL
	t_{PHL}	0.601	0.557 + 0.022*SL	0.568 + 0.019*SL	0.577 + 0.018*SL
SN to Q	t_R	0.165	0.096 + 0.035*SL	0.090 + 0.036*SL	0.081 + 0.037*SL
	t_{PLH}	0.535	0.494 + 0.020*SL	0.505 + 0.018*SL	0.509 + 0.017*SL
CKN to QN	t_R	0.165	0.092 + 0.036*SL	0.092 + 0.036*SL	0.084 + 0.037*SL
	t_F	0.138	0.075 + 0.031*SL	0.076 + 0.031*SL	0.071 + 0.032*SL
	t_{PLH}	0.741	0.698 + 0.021*SL	0.710 + 0.018*SL	0.718 + 0.017*SL
	t_{PHL}	0.780	0.738 + 0.021*SL	0.749 + 0.018*SL	0.757 + 0.017*SL
SN to QN	t_F	0.152	0.084 + 0.034*SL	0.092 + 0.032*SL	0.097 + 0.032*SL
	t_{PHL}	0.292	0.246 + 0.023*SL	0.259 + 0.020*SL	0.271 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD7D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.121	0.083 + 0.019*SL	0.086 + 0.018*SL	0.077 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.084 + 0.016*SL	0.082 + 0.017*SL
	t_{PLH}	0.655	0.629 + 0.013*SL	0.641 + 0.010*SL	0.654 + 0.009*SL
	t_{PHL}	0.598	0.570 + 0.014*SL	0.583 + 0.011*SL	0.601 + 0.009*SL
SN to Q	t_R	0.125	0.087 + 0.019*SL	0.091 + 0.018*SL	0.082 + 0.019*SL
	t_{PLH}	0.578	0.551 + 0.013*SL	0.565 + 0.010*SL	0.579 + 0.009*SL
CKN to QN	t_R	0.126	0.086 + 0.020*SL	0.092 + 0.019*SL	0.089 + 0.019*SL
	t_F	0.106	0.069 + 0.018*SL	0.077 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.792	0.763 + 0.014*SL	0.777 + 0.011*SL	0.795 + 0.009*SL
	t_{PHL}	0.828	0.800 + 0.014*SL	0.814 + 0.011*SL	0.831 + 0.009*SL
SN to QN	t_F	0.118	0.080 + 0.019*SL	0.086 + 0.018*SL	0.097 + 0.017*SL
	t_{PHL}	0.288	0.257 + 0.015*SL	0.271 + 0.012*SL	0.291 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	TI	TE	CKN	SN	Q (n+1)	QN (n+1)
0	x	0	↓	1	0	1
1	x	0	↓	1	1	0
x	0	1	↓	1	0	1
x	1	1	↓	1	1	0
x	x	x	x	0	1	0
x	x	x	↑	1	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FD7S					*FD7SD2*					*FD7S*	*FD7SD2*
D	CKN	SN	TI	TE	D	CKN	SN	TI	TE		
0.6	0.5	1.5	0.6	1.2	0.6	0.6	1.5	0.6	1.2	7.67	8.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD7S	FD7SD2
Input Setup Time (D to CKN)	t_{SU}	0.663	0.659
Input Hold Time (D to CKN)	t_{HD}	0.117	0.117
Pulse Width Low (CKN)	t_{PWL}	0.451	0.474
Pulse Width High (CKN)	t_{PWH}	0.451	0.474
Pulse Width Low (SN)	t_{PWL}	0.362	0.362
Recovery Time (SN to CKN)	t_{RC}	0.010	0.009
Removal Time (SN to CKN)	t_{RM}	0.279	0.279
Input Setup Time (TI to CKN)	t_{SU}	0.628	0.627
Input Hold Time (TI to CKN)	t_{HD}	0.108	0.109
Input Setup Time (TE to CKN)	t_{SU}	0.663	0.658
Input Hold Time (TE to CKN)	t_{HD}	0.144	0.145

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD7S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.163	0.091 + 0.036*SL	0.086 + 0.037*SL	0.080 + 0.038*SL
	t_F	0.151	0.085 + 0.033*SL	0.085 + 0.033*SL	0.083 + 0.033*SL
	t_{PLH}	0.670	0.629 + 0.020*SL	0.638 + 0.018*SL	0.643 + 0.017*SL
	t_{PHL}	0.612	0.567 + 0.022*SL	0.578 + 0.019*SL	0.587 + 0.018*SL
SN to Q	t_R	0.166	0.096 + 0.035*SL	0.090 + 0.036*SL	0.081 + 0.038*SL
	t_{PLH}	0.534	0.493 + 0.020*SL	0.504 + 0.018*SL	0.508 + 0.017*SL
CKN to QN	t_R	0.164	0.091 + 0.036*SL	0.090 + 0.037*SL	0.083 + 0.038*SL
	t_F	0.140	0.074 + 0.033*SL	0.075 + 0.032*SL	0.069 + 0.033*SL
	t_{PLH}	0.747	0.704 + 0.022*SL	0.717 + 0.018*SL	0.724 + 0.017*SL
	t_{PHL}	0.795	0.752 + 0.021*SL	0.764 + 0.019*SL	0.771 + 0.018*SL
SN to QN	t_F	0.155	0.084 + 0.036*SL	0.092 + 0.034*SL	0.097 + 0.033*SL
	t_{PHL}	0.293	0.245 + 0.024*SL	0.258 + 0.021*SL	0.271 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FD7SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.120	0.082 + 0.019*SL	0.085 + 0.018*SL	0.078 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.083 + 0.017*SL	0.083 + 0.017*SL
	t_{PLH}	0.672	0.645 + 0.013*SL	0.658 + 0.010*SL	0.671 + 0.009*SL
	t_{PHL}	0.613	0.585 + 0.014*SL	0.598 + 0.011*SL	0.616 + 0.009*SL
SN to Q	t_R	0.125	0.087 + 0.019*SL	0.090 + 0.018*SL	0.081 + 0.019*SL
	t_{PLH}	0.579	0.552 + 0.013*SL	0.566 + 0.010*SL	0.580 + 0.009*SL
CKN to QN	t_R	0.125	0.084 + 0.020*SL	0.092 + 0.019*SL	0.090 + 0.019*SL
	t_F	0.106	0.071 + 0.018*SL	0.077 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.806	0.778 + 0.014*SL	0.791 + 0.011*SL	0.810 + 0.009*SL
	t_{PHL}	0.845	0.817 + 0.014*SL	0.830 + 0.011*SL	0.847 + 0.009*SL
SN to QN	t_F	0.118	0.079 + 0.020*SL	0.087 + 0.018*SL	0.097 + 0.017*SL
	t_{PHL}	0.288	0.257 + 0.015*SL	0.271 + 0.012*SL	0.291 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD8/FD8D2

D Flip-Flop with Negative Edge Trigger, Reset, Set, 1X/2X Drive

Logic Symbol



Truth Table

D	CKN	RN	SN	Q (n+1)	QN (n+1)
0	↓	1	1	0	1
1	↓	1	1	1	0
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	0	0
x	↑	1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)								Gate Count	
FD8				*FD8D2*				*FD8*	*FD8D2*
D	CKN	RN	SN	D	CKN	RN	SN		
0.6	0.6	1.5	1.6	0.6	0.6	1.5	1.6	6.67	7.00

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD8	FD8D2
Input Setup Time (D to CKN)	t_{SU}	0.323	0.324
Input Hold Time (D to CKN)	t_{HD}	0.208	0.206
Pulse Width Low (CKN)	t_{PWL}	0.452	0.492
Pulse Width High (CKN)	t_{PWH}	0.452	0.492
Pulse Width Low (RN)	t_{PWL}	0.582	0.585
Pulse Width Low (SN)	t_{PWL}	0.411	0.412
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time (RN to CKN)	t_{RM}	0.807	0.810
Recovery Time (SN to CKN)	t_{RC}	0.026	0.026
Removal Time (SN to CKN)	t_{RM}	0.282	0.282
Recovery Time (SN to RN)	t_{RC}	0.140	0.141
Removal Time (SN to RN)	t_{RM}	0.140	0.138

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.178	0.102 + 0.038*SL	0.104 + 0.037*SL	0.100 + 0.038*SL
	t_F	0.146	0.084 + 0.031*SL	0.084 + 0.031*SL	0.082 + 0.032*SL
	t_{PLH}	0.697	0.651 + 0.023*SL	0.665 + 0.019*SL	0.675 + 0.018*SL
	t_{PHL}	0.594	0.550 + 0.022*SL	0.563 + 0.019*SL	0.571 + 0.017*SL
RN to Q	t_R	0.169	0.094 + 0.038*SL	0.095 + 0.037*SL	0.090 + 0.038*SL
	t_F	0.142	0.078 + 0.032*SL	0.080 + 0.031*SL	0.076 + 0.032*SL
	t_{PLH}	0.259	0.215 + 0.022*SL	0.228 + 0.019*SL	0.237 + 0.018*SL
	t_{PHL}	0.267	0.224 + 0.021*SL	0.236 + 0.018*SL	0.243 + 0.017*SL
SN to Q	t_R	0.178	0.103 + 0.037*SL	0.105 + 0.037*SL	0.099 + 0.038*SL
	t_{PLH}	0.576	0.531 + 0.023*SL	0.545 + 0.019*SL	0.555 + 0.018*SL
CKN to QN	t_R	0.167	0.092 + 0.037*SL	0.090 + 0.038*SL	0.084 + 0.039*SL
	t_F	0.138	0.075 + 0.031*SL	0.078 + 0.031*SL	0.072 + 0.031*SL
	t_{PLH}	0.738	0.694 + 0.022*SL	0.707 + 0.019*SL	0.714 + 0.018*SL
	t_{PHL}	0.825	0.782 + 0.021*SL	0.795 + 0.018*SL	0.803 + 0.017*SL
RN to QN	t_R	0.194	0.109 + 0.042*SL	0.124 + 0.038*SL	0.128 + 0.038*SL
	t_{PLH}	0.463	0.409 + 0.027*SL	0.429 + 0.022*SL	0.451 + 0.019*SL
SN to QN	t_R	0.190	0.106 + 0.042*SL	0.120 + 0.039*SL	0.124 + 0.038*SL
	t_F	0.151	0.084 + 0.033*SL	0.089 + 0.032*SL	0.094 + 0.032*SL
	t_{PLH}	0.287	0.233 + 0.027*SL	0.253 + 0.022*SL	0.273 + 0.019*SL
	t_{PHL}	0.292	0.246 + 0.023*SL	0.259 + 0.020*SL	0.272 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.138	0.097 + 0.020*SL	0.103 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.114	0.078 + 0.018*SL	0.087 + 0.016*SL	0.086 + 0.016*SL
	t_{PLH}	0.706	0.676 + 0.015*SL	0.691 + 0.011*SL	0.711 + 0.009*SL
	t_{PHL}	0.598	0.570 + 0.014*SL	0.584 + 0.011*SL	0.602 + 0.009*SL
RN to Q	t_R	0.128	0.086 + 0.021*SL	0.093 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.081 + 0.016*SL	0.084 + 0.016*SL
	t_{PLH}	0.261	0.233 + 0.014*SL	0.247 + 0.011*SL	0.266 + 0.009*SL
	t_{PHL}	0.269	0.241 + 0.014*SL	0.255 + 0.011*SL	0.272 + 0.009*SL
SN to Q	t_R	0.138	0.097 + 0.021*SL	0.104 + 0.019*SL	0.105 + 0.019*SL
	t_{PLH}	0.630	0.600 + 0.015*SL	0.615 + 0.011*SL	0.636 + 0.009*SL
CKN to QN	t_R	0.127	0.087 + 0.020*SL	0.093 + 0.019*SL	0.091 + 0.019*SL
	t_F	0.108	0.073 + 0.018*SL	0.082 + 0.015*SL	0.080 + 0.016*SL
	t_{PLH}	0.795	0.767 + 0.014*SL	0.781 + 0.011*SL	0.799 + 0.009*SL
	t_{PHL}	0.887	0.860 + 0.014*SL	0.873 + 0.010*SL	0.891 + 0.009*SL
RN to QN	t_R	0.147	0.101 + 0.023*SL	0.114 + 0.020*SL	0.129 + 0.019*SL
	t_{PLH}	0.514	0.481 + 0.016*SL	0.496 + 0.013*SL	0.526 + 0.010*SL
SN to QN	t_R	0.143	0.097 + 0.023*SL	0.109 + 0.020*SL	0.124 + 0.019*SL
	t_F	0.116	0.078 + 0.019*SL	0.088 + 0.016*SL	0.095 + 0.016*SL
	t_{PLH}	0.286	0.253 + 0.016*SL	0.268 + 0.013*SL	0.298 + 0.010*SL
	t_{PHL}	0.289	0.260 + 0.015*SL	0.274 + 0.011*SL	0.294 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FD8S/FD8SD2

D Flip-Flop with Negative Edge Trigger, Reset, Set, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	TI	TE	CKN	RN	SN	Q (n+1)	QN (n+1)
0	x	0	↓	1	1	0	1
1	x	0	↓	1	1	1	0
x	0	1	↓	1	1	0	1
x	1	1	↓	1	1	1	0
x	x	x	x	1	0	1	0
x	x	x	x	0	1	0	1
x	x	x	x	0	0	0	0
x	x	x	↑	1	1	Q (n)	QN (n)

Cell Data

Input Load (SL)												Gate Count	
FD8S						*FD8SD2*						*FD8S*	*FD8SD2*
D	CKN	RN	SN	TI	TE	D	CKN	RN	SN	TI	TE		
0.6	0.6	1.5	1.6	0.6	1.2	0.6	0.6	1.5	1.6	0.6	1.2	8.67	9.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FD8S	FD8SD2
Input Setup Time (D to CKN)	t_{SU}	0.645	0.632
Input Hold Time (D to CKN)	t_{HD}	0.135	0.134
Pulse Width Low (CKN)	t_{PWL}	0.484	0.520
Pulse Width High (CKN)	t_{PWH}	0.484	0.520
Pulse Width Low (RN)	t_{PWL}	0.596	0.599
Pulse Width Low (SN)	t_{PWL}	0.429	0.432
Recovery Time (RN to CKN)	t_{RC}	0.000	0.000
Removal Time(RN to CKN)	t_{RM}	0.820	0.822
Recovery Time (SN to CKN)	t_{RC}	0.021	0.022
Removal Time (SN to CKN)	t_{RM}	0.289	0.288
Input Setup Time (TI to CKN)	t_{SU}	0.615	0.618
Input Hold Time (TI to CKN)	t_{HD}	0.130	0.130
Input Setup Time (TE to CKN)	t_{SU}	0.657	0.640
Input Hold Time (TE to CKN)	t_{HD}	0.155	0.154
Recovery Time (SN to RN)	t_{RC}	0.142	0.144
Removal Time (SN to RN)	t_{RM}	0.138	0.135

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD8S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.178	0.104 + 0.037*SL	0.106 + 0.036*SL	0.102 + 0.037*SL
	t_F	0.147	0.084 + 0.032*SL	0.086 + 0.031*SL	0.083 + 0.031*SL
	t_{PLH}	0.747	0.701 + 0.023*SL	0.716 + 0.019*SL	0.726 + 0.018*SL
	t_{PHL}	0.630	0.586 + 0.022*SL	0.599 + 0.019*SL	0.608 + 0.017*SL
RN to Q	t_R	0.166	0.092 + 0.037*SL	0.093 + 0.037*SL	0.088 + 0.037*SL
	t_F	0.141	0.077 + 0.032*SL	0.079 + 0.031*SL	0.076 + 0.032*SL
	t_{PLH}	0.255	0.211 + 0.022*SL	0.224 + 0.019*SL	0.233 + 0.017*SL
	t_{PHL}	0.265	0.223 + 0.021*SL	0.234 + 0.018*SL	0.241 + 0.017*SL
SN to Q	t_R	0.178	0.106 + 0.036*SL	0.106 + 0.036*SL	0.099 + 0.037*SL
	t_{PLH}	0.602	0.557 + 0.023*SL	0.572 + 0.019*SL	0.582 + 0.018*SL
CKN to QN	t_R	0.163	0.090 + 0.036*SL	0.090 + 0.036*SL	0.085 + 0.037*SL
	t_F	0.140	0.078 + 0.031*SL	0.078 + 0.031*SL	0.074 + 0.031*SL
	t_{PLH}	0.774	0.731 + 0.022*SL	0.744 + 0.018*SL	0.752 + 0.017*SL
	t_{PHL}	0.882	0.839 + 0.021*SL	0.852 + 0.018*SL	0.860 + 0.017*SL
RN to QN	t_R	0.195	0.109 + 0.043*SL	0.129 + 0.038*SL	0.137 + 0.037*SL
	t_{PLH}	0.464	0.410 + 0.027*SL	0.429 + 0.022*SL	0.453 + 0.019*SL
SN to QN	t_R	0.192	0.107 + 0.042*SL	0.125 + 0.038*SL	0.133 + 0.037*SL
	t_F	0.153	0.084 + 0.035*SL	0.092 + 0.033*SL	0.098 + 0.032*SL
	t_{PLH}	0.290	0.236 + 0.027*SL	0.255 + 0.022*SL	0.278 + 0.019*SL
	t_{PHL}	0.299	0.252 + 0.023*SL	0.265 + 0.020*SL	0.277 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FD8SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CKN to Q	t_R	0.137	0.095 + 0.021*SL	0.103 + 0.019*SL	0.105 + 0.019*SL
	t_F	0.115	0.079 + 0.018*SL	0.086 + 0.016*SL	0.086 + 0.016*SL
	t_{PLH}	0.755	0.725 + 0.015*SL	0.740 + 0.011*SL	0.761 + 0.009*SL
	t_{PHL}	0.634	0.605 + 0.015*SL	0.619 + 0.011*SL	0.638 + 0.009*SL
RN to Q	t_R	0.126	0.084 + 0.021*SL	0.092 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.079 + 0.017*SL	0.079 + 0.017*SL
	t_{PLH}	0.255	0.227 + 0.014*SL	0.241 + 0.011*SL	0.260 + 0.009*SL
	t_{PHL}	0.262	0.234 + 0.014*SL	0.247 + 0.011*SL	0.263 + 0.009*SL
SN to Q	t_R	0.140	0.099 + 0.020*SL	0.107 + 0.018*SL	0.105 + 0.019*SL
	t_{PLH}	0.654	0.624 + 0.015*SL	0.639 + 0.011*SL	0.660 + 0.009*SL
CKN to QN	t_R	0.127	0.086 + 0.021*SL	0.094 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.112	0.075 + 0.018*SL	0.083 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.829	0.801 + 0.014*SL	0.815 + 0.011*SL	0.834 + 0.009*SL
	t_{PHL}	0.943	0.915 + 0.014*SL	0.928 + 0.011*SL	0.946 + 0.009*SL
RN to QN	t_R	0.150	0.101 + 0.024*SL	0.115 + 0.021*SL	0.136 + 0.019*SL
	t_{PLH}	0.506	0.472 + 0.017*SL	0.487 + 0.013*SL	0.518 + 0.010*SL
SN to QN	t_R	0.147	0.100 + 0.024*SL	0.113 + 0.021*SL	0.133 + 0.019*SL
	t_F	0.121	0.082 + 0.019*SL	0.090 + 0.018*SL	0.099 + 0.017*SL
	t_{PLH}	0.290	0.257 + 0.017*SL	0.271 + 0.013*SL	0.302 + 0.010*SL
	t_{PHL}	0.298	0.267 + 0.015*SL	0.282 + 0.012*SL	0.302 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FDS2/FDS2D2

D Flip-Flop with Synchronous Clear, 1X/2X Drive

Logic Symbol



Truth Table

D	CRN	CK	Q (n+1)	QN (n+1)
0	1	↑	0	1
1	1	↑	1	0
x	0	↑	0	1
x	x	↓	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FDS2			*FDS2D2*			*FDS2*	*FDS2D2*
D	CRN	CK	D	CRN	CK		
0.6	0.6	0.6	0.6	0.6	0.6	5.33	6.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2	FDS2D2
Input Setup Time (D to CK)	t_{SU}	0.435	0.422
Input Hold Time (D to CK)	t_{HD}	0.086	0.097
Pulse Width Low (CK)	t_{PWL}	0.534	0.532
Pulse Width High (CK)	t_{PWH}	0.421	0.451
Input Setup Time (CRN to CK)	t_{SU}	0.425	0.425
Input Hold Time (CRN to CK)	t_{HD}	0.083	0.091

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.163	0.089 + 0.037*SL	0.087 + 0.037*SL	0.080 + 0.038*SL
	t_F	0.146	0.081 + 0.032*SL	0.086 + 0.031*SL	0.082 + 0.032*SL
	t_{PLH}	0.554	0.513 + 0.020*SL	0.522 + 0.018*SL	0.527 + 0.018*SL
	t_{PHL}	0.585	0.542 + 0.022*SL	0.554 + 0.019*SL	0.564 + 0.017*SL
CK to QN	t_R	0.148	0.073 + 0.038*SL	0.070 + 0.039*SL	0.062 + 0.040*SL
	t_F	0.131	0.068 + 0.032*SL	0.067 + 0.032*SL	0.061 + 0.033*SL
	t_{PLH}	0.672	0.633 + 0.019*SL	0.640 + 0.018*SL	0.641 + 0.018*SL
	t_{PHL}	0.654	0.614 + 0.020*SL	0.623 + 0.018*SL	0.628 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	0.080 + 0.019*SL	0.082 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.073 + 0.018*SL	0.077 + 0.017*SL	0.080 + 0.016*SL
	t_{PLH}	0.559	0.533 + 0.013*SL	0.545 + 0.010*SL	0.557 + 0.009*SL
	t_{PHL}	0.588	0.559 + 0.014*SL	0.573 + 0.011*SL	0.590 + 0.009*SL
CK to QN	t_R	0.107	0.071 + 0.018*SL	0.069 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.100	0.064 + 0.018*SL	0.070 + 0.016*SL	0.066 + 0.017*SL
	t_{PLH}	0.719	0.695 + 0.012*SL	0.705 + 0.010*SL	0.713 + 0.009*SL
	t_{PHL}	0.706	0.679 + 0.013*SL	0.691 + 0.010*SL	0.705 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FDS2CS/FDS2CSD2

D Flip-Flop with Synchronous Clear, Scan Clock, 1X/2X Drive

Logic Symbol



Truth Table

SI	SCK	D	CRN	CK	Q (n+1)	QN (n+1)
x	0	0	1	↑	0	1
x	0	1	1	↑	1	0
0	↑	x	x	0	0	1
1	↑	x	x	0	1	0
x	0	x	0	↑	0	1
x	0	x	x	↓	Q(n)	QN(n)
x	↓	x	x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FDS2CS					*FDS2CSD2*					*FDS2CS*	*FDS2CSD2*
D	SI	CK	SCK	CRN	D	SI	CK	SCK	CRN		
0.6	0.6	0.6	1.6	0.6	0.6	0.6	0.6	1.5	0.6	8.67	9.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2CS	FDS2CSD2
Input Setup Time (D to CK)	t_{SU}	0.421	0.435
Input Hold Time (D to CK)	t_{HD}	0.089	0.090
Input Setup Time (SI to SCK)	t_{SU}	0.479	0.480
Input Hold Time (SI to SCK)	t_{HD}	0.050	0.050
Pulse Width Low (CK)	t_{PWL}	0.534	0.535
Pulse Width High (CK)	t_{PWH}	0.444	0.474
Pulse Width Low (SCK)	t_{PWL}	0.415	0.416
Pulse Width High (SCK)	t_{PWH}	0.535	0.584
Input Setup Time (CRN to CK)	t_{SU}	0.424	0.424
Input Hold Time (CRN to CK)	t_{HD}	0.086	0.087

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS2CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.161	0.089 + 0.036*SL	0.085 + 0.037*SL	0.078 + 0.038*SL
	t_F	0.144	0.080 + 0.032*SL	0.081 + 0.032*SL	0.079 + 0.032*SL
	t_{PLH}	0.566	0.526 + 0.020*SL	0.535 + 0.018*SL	0.539 + 0.017*SL
	t_{PHL}	0.586	0.543 + 0.021*SL	0.554 + 0.019*SL	0.563 + 0.017*SL
SCK to Q	t_R	0.181	0.110 + 0.035*SL	0.108 + 0.036*SL	0.098 + 0.037*SL
	t_F	0.150	0.085 + 0.032*SL	0.091 + 0.031*SL	0.086 + 0.032*SL
	t_{PLH}	0.686	0.643 + 0.022*SL	0.656 + 0.019*SL	0.663 + 0.018*SL
	t_{PHL}	0.566	0.522 + 0.022*SL	0.534 + 0.019*SL	0.545 + 0.017*SL
CK to QN	t_R	0.177	0.099 + 0.039*SL	0.104 + 0.038*SL	0.099 + 0.038*SL
	t_F	0.155	0.088 + 0.033*SL	0.090 + 0.033*SL	0.092 + 0.033*SL
	t_{PLH}	0.726	0.680 + 0.023*SL	0.694 + 0.020*SL	0.706 + 0.018*SL
	t_{PHL}	0.727	0.681 + 0.023*SL	0.694 + 0.020*SL	0.704 + 0.018*SL
SCK to QN	t_R	0.158	0.085 + 0.037*SL	0.080 + 0.038*SL	0.072 + 0.039*SL
	t_F	0.144	0.080 + 0.032*SL	0.081 + 0.032*SL	0.075 + 0.032*SL
	t_{PLH}	0.679	0.639 + 0.020*SL	0.647 + 0.018*SL	0.650 + 0.018*SL
	t_{PHL}	0.817	0.775 + 0.021*SL	0.786 + 0.018*SL	0.793 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS2CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.118	0.080 + 0.019*SL	0.082 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.077 + 0.017*SL	0.077 + 0.017*SL
	t_{PLH}	0.564	0.538 + 0.013*SL	0.551 + 0.010*SL	0.563 + 0.009*SL
	t_{PHL}	0.585	0.557 + 0.014*SL	0.571 + 0.011*SL	0.587 + 0.009*SL
SCK to Q	t_R	0.139	0.101 + 0.019*SL	0.106 + 0.018*SL	0.097 + 0.019*SL
	t_F	0.114	0.078 + 0.018*SL	0.085 + 0.016*SL	0.085 + 0.016*SL
	t_{PLH}	0.699	0.670 + 0.014*SL	0.686 + 0.011*SL	0.703 + 0.009*SL
	t_{PHL}	0.575	0.546 + 0.014*SL	0.560 + 0.011*SL	0.578 + 0.009*SL
CK to QN	t_R	0.125	0.083 + 0.021*SL	0.091 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.116	0.077 + 0.019*SL	0.085 + 0.017*SL	0.091 + 0.017*SL
	t_{PLH}	0.761	0.732 + 0.014*SL	0.745 + 0.011*SL	0.767 + 0.009*SL
	t_{PHL}	0.770	0.740 + 0.015*SL	0.754 + 0.012*SL	0.774 + 0.010*SL
SCK to QN	t_R	0.112	0.075 + 0.019*SL	0.077 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.079 + 0.016*SL	0.078 + 0.016*SL
	t_{PLH}	0.729	0.703 + 0.013*SL	0.715 + 0.010*SL	0.726 + 0.009*SL
	t_{PHL}	0.881	0.853 + 0.014*SL	0.867 + 0.011*SL	0.884 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	CRN	TI	TE	CK	Q (n+1)	QN (n+1)
0	1	x	0	↑	0	1
1	1	x	0	↑	1	0
x	0	x	0	↑	0	1
x	x	0	1	↑	0	1
x	x	1	1	↑	1	0
x	x	x	x	↓	Q (n)	QN (n)

Cell Data

Input Load (SL)										Gate Count	
FDS2S					*FDS2SD2*					*FDS2S*	*FDS2SD2*
D	CRN	CK	TI	TE	D	CRN	CK	TI	TE		
0.5	0.6	0.6	0.5	1.2	0.5	0.6	0.6	0.6	1.2	8.00	8.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS2S	FDS2SD2
Input Setup Time (D to CK)	t_{SU}	0.620	0.614
Input Hold Time (D to CK)	t_{HD}	0.000	0.000
Input Setup Time (CRN to CK)	t_{SU}	0.622	0.611
Input Hold Time (CRN to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.603	0.591
Pulse Width High (CK)	t_{PWH}	0.418	0.440
Input Setup Time (TI to CK)	t_{SU}	0.660	0.657
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.532	0.539
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.147	0.074 + 0.037*SL	0.070 + 0.038*SL	0.063 + 0.039*SL
	t_F	0.138	0.071 + 0.033*SL	0.069 + 0.034*SL	0.063 + 0.035*SL
	t_{PLH}	0.690	0.652 + 0.019*SL	0.658 + 0.017*SL	0.659 + 0.017*SL
	t_{PHL}	0.664	0.622 + 0.021*SL	0.631 + 0.019*SL	0.635 + 0.018*SL
CK to QN	t_R	0.159	0.087 + 0.036*SL	0.084 + 0.036*SL	0.076 + 0.038*SL
	t_F	0.142	0.078 + 0.032*SL	0.085 + 0.031*SL	0.078 + 0.031*SL
	t_{PLH}	0.554	0.514 + 0.020*SL	0.524 + 0.018*SL	0.529 + 0.017*SL
	t_{PHL}	0.603	0.560 + 0.022*SL	0.573 + 0.018*SL	0.583 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS2SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.106	0.070 + 0.018*SL	0.071 + 0.018*SL	0.059 + 0.019*SL
	t_F	0.100	0.065 + 0.017*SL	0.070 + 0.016*SL	0.066 + 0.017*SL
	t_{PLH}	0.725	0.700 + 0.012*SL	0.711 + 0.010*SL	0.719 + 0.009*SL
	t_{PHL}	0.700	0.674 + 0.013*SL	0.686 + 0.010*SL	0.699 + 0.009*SL
CK to QN	t_R	0.117	0.080 + 0.019*SL	0.082 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.071 + 0.018*SL	0.079 + 0.017*SL	0.080 + 0.016*SL
	t_{PLH}	0.552	0.525 + 0.013*SL	0.538 + 0.010*SL	0.550 + 0.009*SL
	t_{PHL}	0.596	0.567 + 0.014*SL	0.581 + 0.011*SL	0.598 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	CSN	CK	Q (n+1)	QN (n+1)
0	1	↑	0	1
1	1	↑	1	0
x	0	↑	1	0
x	x	↓	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FDS3			*FDS3D2*			*FDS3*	*FDS3D2*
D	CSN	CK	D	CSN	CK		
0.6	0.5	0.6	0.6	0.5	0.6	6.00	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3	FDS3D2
Input Setup Time (D to CK)	t_{SU}	0.510	0.512
Input Hold Time (D to CK)	t_{HD}	0.037	0.037
Input Setup Time (CSN to CK)	t_{SU}	0.412	0.414
Input Hold Time (CSN to CK)	t_{HD}	0.108	0.106
Pulse Width Low (CK)	t_{PWL}	0.522	0.525
Pulse Width High (CK)	t_{PWH}	0.428	0.453

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.146	0.073 + 0.036*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.133	0.068 + 0.032*SL	0.067 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.679	0.641 + 0.019*SL	0.647 + 0.018*SL	0.649 + 0.017*SL
	t_{PHL}	0.668	0.627 + 0.020*SL	0.636 + 0.018*SL	0.640 + 0.018*SL
CK to QN	t_R	0.162	0.089 + 0.036*SL	0.085 + 0.037*SL	0.078 + 0.038*SL
	t_F	0.145	0.078 + 0.034*SL	0.082 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.566	0.524 + 0.021*SL	0.534 + 0.018*SL	0.539 + 0.018*SL
	t_{PHL}	0.598	0.553 + 0.022*SL	0.565 + 0.019*SL	0.575 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.107	0.071 + 0.018*SL	0.069 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.071 + 0.016*SL	0.067 + 0.017*SL
	t_{PLH}	0.730	0.705 + 0.012*SL	0.716 + 0.010*SL	0.724 + 0.009*SL
	t_{PHL}	0.712	0.685 + 0.013*SL	0.698 + 0.010*SL	0.711 + 0.009*SL
CK to QN	t_R	0.117	0.080 + 0.018*SL	0.080 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.108	0.071 + 0.018*SL	0.077 + 0.017*SL	0.079 + 0.016*SL
	t_{PLH}	0.564	0.538 + 0.013*SL	0.550 + 0.010*SL	0.562 + 0.009*SL
	t_{PHL}	0.598	0.570 + 0.014*SL	0.583 + 0.011*SL	0.600 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

SI	SCK	D	CSN	CK	Q(n+1)	QN(n+1)
x	0	0	1	↑	0	1
x	0	1	1	↑	1	0
0	↑	x	x	0	0	1
1	↑	x	x	0	1	0
x	0	x	0	↑	1	0
x	0	x	x	↓	Q(n)	QN(n)
x	↓	x	x	0	Q(n)	QN(n)

Cell Data

Input Load (SL)										Gate Count	
FDS3CS					*FDS3CSD2*					*FDS3CS*	*FDS3CSD2*
D	SI	CK	SCK	CSN	D	SI	CK	SCK	CSN		
0.6	0.6	0.6	1.6	0.5	0.6	0.6	0.6	1.7	0.5	9.67	10.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3CS	FDS3CSD2
Input Setup Time (D to CK)	t_{SU}	0.511	0.512
Input Hold Time (D to CK)	t_{HD}	0.037	0.037
Input Setup Time (SI to SCK)	t_{SU}	0.557	0.559
Input Hold Time (SI to SCK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.524	0.525
Pulse Width High (CK)	t_{PWH}	0.446	0.471
Pulse Width Low (SCK)	t_{PWL}	0.420	0.420
Pulse Width High (SCK)	t_{PWH}	0.526	0.566
Input Setup Time (CSN to CK)	t_{SU}	0.412	0.414
Input Hold Time (CSN to CK)	t_{HD}	0.108	0.107

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS3CS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.169	0.094 + 0.038*SL	0.099 + 0.037*SL	0.095 + 0.037*SL
	t_F	0.152	0.085 + 0.033*SL	0.086 + 0.033*SL	0.089 + 0.033*SL
	t_{PLH}	0.733	0.687 + 0.023*SL	0.702 + 0.019*SL	0.714 + 0.018*SL
	t_{PHL}	0.729	0.683 + 0.023*SL	0.696 + 0.020*SL	0.706 + 0.018*SL
SCK to Q	t_R	0.152	0.082 + 0.035*SL	0.074 + 0.037*SL	0.068 + 0.038*SL
	t_F	0.141	0.078 + 0.031*SL	0.077 + 0.032*SL	0.071 + 0.032*SL
	t_{PLH}	0.672	0.633 + 0.019*SL	0.641 + 0.018*SL	0.644 + 0.017*SL
	t_{PHL}	0.809	0.767 + 0.021*SL	0.778 + 0.018*SL	0.785 + 0.017*SL
CK to QN	t_R	0.158	0.086 + 0.036*SL	0.083 + 0.037*SL	0.075 + 0.038*SL
	t_F	0.141	0.077 + 0.032*SL	0.080 + 0.031*SL	0.074 + 0.032*SL
	t_{PLH}	0.569	0.528 + 0.020*SL	0.537 + 0.018*SL	0.541 + 0.018*SL
	t_{PHL}	0.596	0.553 + 0.021*SL	0.564 + 0.019*SL	0.573 + 0.017*SL
SCK to QN	t_R	0.177	0.106 + 0.036*SL	0.105 + 0.036*SL	0.094 + 0.037*SL
	t_F	0.147	0.082 + 0.032*SL	0.088 + 0.031*SL	0.083 + 0.032*SL
	t_{PLH}	0.678	0.635 + 0.022*SL	0.648 + 0.019*SL	0.656 + 0.018*SL
	t_{PHL}	0.561	0.518 + 0.022*SL	0.530 + 0.019*SL	0.541 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS3CSD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.123	0.081 + 0.021*SL	0.090 + 0.019*SL	0.091 + 0.019*SL
	t_F	0.114	0.075 + 0.019*SL	0.083 + 0.017*SL	0.088 + 0.017*SL
	t_{PLH}	0.770	0.741 + 0.014*SL	0.754 + 0.011*SL	0.775 + 0.009*SL
	t_{PHL}	0.767	0.737 + 0.015*SL	0.751 + 0.011*SL	0.770 + 0.010*SL
SCK to Q	t_R	0.112	0.075 + 0.018*SL	0.076 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.106	0.069 + 0.018*SL	0.077 + 0.016*SL	0.075 + 0.016*SL
	t_{PLH}	0.719	0.693 + 0.013*SL	0.705 + 0.010*SL	0.716 + 0.009*SL
	t_{PHL}	0.861	0.833 + 0.014*SL	0.847 + 0.011*SL	0.863 + 0.009*SL
CK to QN	t_R	0.116	0.079 + 0.019*SL	0.081 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.106	0.069 + 0.018*SL	0.077 + 0.016*SL	0.076 + 0.017*SL
	t_{PLH}	0.568	0.542 + 0.013*SL	0.554 + 0.010*SL	0.566 + 0.009*SL
	t_{PHL}	0.595	0.567 + 0.014*SL	0.580 + 0.011*SL	0.597 + 0.009*SL
SCK to QN	t_R	0.136	0.098 + 0.019*SL	0.103 + 0.018*SL	0.094 + 0.019*SL
	t_F	0.113	0.077 + 0.018*SL	0.083 + 0.016*SL	0.084 + 0.016*SL
	t_{PLH}	0.684	0.655 + 0.014*SL	0.670 + 0.011*SL	0.688 + 0.009*SL
	t_{PHL}	0.564	0.535 + 0.014*SL	0.549 + 0.011*SL	0.567 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

FDS3S/FDS3SD2

Flip-Flop with Synchronous Set, Scan, 1X/2X Drive

Logic Symbol



Truth Table

D	CSN	TI	TE	CK	Q(n+1)	QN(n+1)
0	1	x	0	↑	0	1
1	1	x	0	↑	1	0
x	x	0	1	↑	0	1
x	x	1	1	↑	1	0
x	0	x	0	↑	1	0
x	x	x	x	↓	Q(n)	QN(n+1)

Cell Data

Input Load (SL)										Gate Count	
FDS3S					*FDS3SD2*					*FDS3S*	*FDS3SD2*
D	CSN	CK	TI	TE	D	CSN	CK	TI	TE		
0.6	0.5	0.5	0.6	1.2	0.6	0.5	0.6	0.6	1.2	8.00	8.67

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FDS3S	FDS3SD2
Input Setup Time (D to CK)	t_{SU}	0.712	0.714
Input Hold Time (D to CK)	t_{HD}	0.000	0.000
Input Setup Time (CSN to CK)	t_{SU}	0.605	0.609
Input Hold Time (CSN to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.595	0.588
Pulse Width High (CK)	t_{PWH}	0.415	0.441
Input Setup Time (TI to CK)	t_{SU}	0.542	0.546
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.547	0.551
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FDS3S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.162	0.088 + 0.037*SL	0.084 + 0.038*SL	0.076 + 0.039*SL
	t_F	0.146	0.079 + 0.033*SL	0.082 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.551	0.509 + 0.021*SL	0.519 + 0.018*SL	0.524 + 0.018*SL
	t_{PHL}	0.594	0.549 + 0.022*SL	0.562 + 0.019*SL	0.571 + 0.018*SL
CK to QN	t_R	0.146	0.074 + 0.036*SL	0.069 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.135	0.070 + 0.032*SL	0.068 + 0.033*SL	0.062 + 0.034*SL
	t_{PLH}	0.675	0.638 + 0.019*SL	0.644 + 0.017*SL	0.646 + 0.017*SL
	t_{PHL}	0.653	0.612 + 0.020*SL	0.621 + 0.018*SL	0.625 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FDS3SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	0.080 + 0.019*SL	0.082 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.077 + 0.017*SL	0.078 + 0.016*SL
	t_{PLH}	0.551	0.525 + 0.013*SL	0.537 + 0.010*SL	0.549 + 0.009*SL
	t_{PHL}	0.585	0.557 + 0.014*SL	0.570 + 0.011*SL	0.587 + 0.009*SL
CK to QN	t_R	0.107	0.070 + 0.018*SL	0.071 + 0.018*SL	0.060 + 0.019*SL
	t_F	0.099	0.064 + 0.018*SL	0.070 + 0.016*SL	0.066 + 0.017*SL
	t_{PLH}	0.717	0.692 + 0.012*SL	0.703 + 0.010*SL	0.712 + 0.009*SL
	t_{PHL}	0.698	0.671 + 0.013*SL	0.684 + 0.010*SL	0.697 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

J	CK	K	Q (n+1)	QN (n+1)
0	↑	1	0	1
1	↑	0	1	0
0	↑	0	Q (n)	QN (n)
1	↑	1	QN (n)	Q (n)
x	↓	x	Q (n)	QN (n)

Cell Data

Input Load (SL)						Gate Count	
FJ1			*FJ1D2*			*FJ1*	*FJ1D2*
J	K	CK	J	K	CK		
0.4	0.6	0.6	0.4	0.6	0.6	6.67	7.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ1	FJ1D2
Input Setup Time (J to CK)	t_{SU}	0.437	0.435
Input Hold Time (J to CK)	t_{HD}	0.000	0.003
Input Setup Time (K to CK)	t_{SU}	0.437	0.435
Input Hold Time (K to CK)	t_{HD}	0.000	0.003
Pulse Width Low (CK)	t_{PWL}	0.530	0.523
Pulse Width High (CK)	t_{PWH}	0.432	0.460

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.157	0.084 + 0.036*SL	0.079 + 0.038*SL	0.072 + 0.039*SL
	t_F	0.145	0.079 + 0.033*SL	0.080 + 0.033*SL	0.076 + 0.033*SL
	t_{PLH}	0.737	0.696 + 0.021*SL	0.706 + 0.018*SL	0.711 + 0.018*SL
	t_{PHL}	0.704	0.659 + 0.022*SL	0.672 + 0.019*SL	0.681 + 0.018*SL
CK to QN	t_R	0.156	0.084 + 0.036*SL	0.082 + 0.037*SL	0.074 + 0.038*SL
	t_F	0.145	0.079 + 0.033*SL	0.081 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.558	0.518 + 0.020*SL	0.527 + 0.018*SL	0.531 + 0.017*SL
	t_{PHL}	0.614	0.570 + 0.022*SL	0.581 + 0.019*SL	0.590 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FJ1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.117	0.079 + 0.019*SL	0.082 + 0.018*SL	0.074 + 0.019*SL
	t_F	0.110	0.073 + 0.018*SL	0.081 + 0.016*SL	0.082 + 0.016*SL
	t_{PLH}	0.784	0.758 + 0.013*SL	0.771 + 0.010*SL	0.784 + 0.009*SL
	t_{PHL}	0.746	0.717 + 0.014*SL	0.731 + 0.011*SL	0.750 + 0.009*SL
CK to QN	t_R	0.117	0.080 + 0.018*SL	0.080 + 0.018*SL	0.073 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.080 + 0.016*SL	0.080 + 0.017*SL
	t_{PLH}	0.563	0.537 + 0.013*SL	0.549 + 0.010*SL	0.561 + 0.009*SL
	t_{PHL}	0.616	0.588 + 0.014*SL	0.601 + 0.011*SL	0.618 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

J	CK	K	TI	TE	Q (n+1)	QN (n+1)
0	↑	1	x	0	0	1
1	↑	0	x	0	1	0
0	↑	0	x	0	Q (n)	QN (n)
1	↑	1	x	0	QN (n)	Q (n)
x	↓	x	x	x	Q (n)	QN (n)
x	↑	x	0	1	0	1
x	↑	x	1	1	1	0

Cell Data

Input Load (SL)										Gate Count	
FJ1S					*FJ1SD2*					*FJ1S*	*FJ1SD2*
J	K	CK	TI	TE	J	K	CK	TI	TE		
0.5	0.5	0.5	0.5	1.2	0.4	0.6	0.5	0.5	1.2	8.67	9.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ1S	FJ1SD2
Input Setup Time (J to CK)	t_{SU}	0.733	0.728
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.733	0.728
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.588	0.588
Pulse Width High (CK)	t_{PWH}	0.440	0.470
Input Setup Time (TI to CK)	t_{SU}	0.533	0.533
Input Hold Time (TI to CK)	t_{HD}	0.000	0.000
Input Setup Time (TE to CK)	t_{SU}	0.543	0.541
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ1S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.173	0.098 + 0.037*SL	0.095 + 0.038*SL	0.088 + 0.039*SL
	t_F	0.156	0.088 + 0.034*SL	0.096 + 0.032*SL	0.092 + 0.033*SL
	t_{PLH}	0.599	0.554 + 0.022*SL	0.567 + 0.019*SL	0.575 + 0.018*SL
	t_{PHL}	0.640	0.592 + 0.024*SL	0.608 + 0.020*SL	0.621 + 0.018*SL
CK to QN	t_R	0.147	0.074 + 0.036*SL	0.071 + 0.037*SL	0.064 + 0.038*SL
	t_F	0.131	0.069 + 0.031*SL	0.069 + 0.031*SL	0.063 + 0.032*SL
	t_{PLH}	0.726	0.688 + 0.019*SL	0.695 + 0.017*SL	0.697 + 0.017*SL
	t_{PHL}	0.699	0.660 + 0.020*SL	0.669 + 0.017*SL	0.674 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FJ1SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.127	0.087 + 0.020*SL	0.094 + 0.018*SL	0.088 + 0.019*SL
	t_F	0.117	0.080 + 0.018*SL	0.089 + 0.016*SL	0.097 + 0.015*SL
	t_{PLH}	0.597	0.569 + 0.014*SL	0.583 + 0.011*SL	0.600 + 0.009*SL
	t_{PHL}	0.635	0.606 + 0.015*SL	0.620 + 0.011*SL	0.643 + 0.009*SL
CK to QN	t_R	0.110	0.073 + 0.018*SL	0.075 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.099	0.066 + 0.017*SL	0.071 + 0.015*SL	0.067 + 0.016*SL
	t_{PLH}	0.778	0.754 + 0.012*SL	0.764 + 0.010*SL	0.773 + 0.009*SL
	t_{PHL}	0.747	0.722 + 0.013*SL	0.733 + 0.010*SL	0.747 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

J	CK	K	RN	Q (n+1)	QN (n+1)
0	↑	1	1	0	1
1	↑	0	1	1	0
0	↑	0	1	Q (n)	QN (n)
1	↑	1	1	QN (n)	Q (n)
x	↓	x	1	Q (n)	QN (n)
x	x	x	0	0	1

Cell Data

Input Load (SL)								Gate Count	
FJ2				*FJ2D2*				*FJ2*	*FJ2D2*
J	K	CK	RN	J	K	CK	RN		
0.4	0.5	0.6	1.5	0.4	0.5	0.6	1.6	8.00	8.33

Schematic Diagram



FJ2/FJ2D2

JK Flip-Flop with Reset, 1X/2X Drive

Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ2	FJ2D2
Input Setup Time (J to CK)	t_{SU}	0.482	0.481
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.482	0.481
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.580	0.581
Pulse Width High (CK)	t_{PWH}	0.435	0.463
Pulse Width Low (RN)	t_{PWL}	0.408	0.453
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.329	0.329

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.177	0.100 + 0.039*SL	0.103 + 0.038*SL	0.098 + 0.038*SL
	t_F	0.144	0.080 + 0.032*SL	0.085 + 0.031*SL	0.083 + 0.031*SL
	t_{PLH}	0.822	0.775 + 0.024*SL	0.791 + 0.020*SL	0.802 + 0.018*SL
	t_{PHL}	0.715	0.670 + 0.022*SL	0.685 + 0.019*SL	0.696 + 0.017*SL
RN to Q	t_F	0.163	0.095 + 0.034*SL	0.104 + 0.032*SL	0.109 + 0.031*SL
	t_{PHL}	0.329	0.279 + 0.025*SL	0.296 + 0.021*SL	0.313 + 0.018*SL
CK to QN	t_R	0.161	0.088 + 0.037*SL	0.084 + 0.038*SL	0.077 + 0.038*SL
	t_F	0.145	0.082 + 0.032*SL	0.083 + 0.031*SL	0.080 + 0.032*SL
	t_{PLH}	0.558	0.517 + 0.020*SL	0.526 + 0.018*SL	0.530 + 0.018*SL
	t_{PHL}	0.641	0.598 + 0.021*SL	0.610 + 0.018*SL	0.617 + 0.017*SL
RN to QN	t_R	0.166	0.095 + 0.035*SL	0.089 + 0.037*SL	0.080 + 0.038*SL
	t_{PLH}	0.574	0.533 + 0.021*SL	0.544 + 0.018*SL	0.548 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FJ2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.135	0.092 + 0.021*SL	0.102 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.114	0.076 + 0.019*SL	0.086 + 0.017*SL	0.090 + 0.016*SL
	t_{PLH}	0.871	0.841 + 0.015*SL	0.856 + 0.012*SL	0.879 + 0.009*SL
	t_{PHL}	0.759	0.729 + 0.015*SL	0.744 + 0.011*SL	0.765 + 0.009*SL
RN to Q	t_F	0.128	0.087 + 0.020*SL	0.099 + 0.017*SL	0.110 + 0.016*SL
	t_{PHL}	0.324	0.291 + 0.016*SL	0.307 + 0.012*SL	0.333 + 0.010*SL
CK to QN	t_R	0.117	0.080 + 0.018*SL	0.081 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.112	0.076 + 0.018*SL	0.082 + 0.016*SL	0.081 + 0.017*SL
	t_{PLH}	0.558	0.531 + 0.013*SL	0.544 + 0.010*SL	0.556 + 0.009*SL
	t_{PHL}	0.647	0.618 + 0.014*SL	0.632 + 0.011*SL	0.650 + 0.009*SL
RN to QN	t_R	0.125	0.088 + 0.018*SL	0.090 + 0.018*SL	0.079 + 0.019*SL
	t_{PLH}	0.616	0.589 + 0.014*SL	0.602 + 0.010*SL	0.616 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

J	CK	K	TI	TE	RN	Q (n+1)	QN (n+1)
0	↑	1	x	0	1	0	1
1	↑	0	x	0	1	1	0
0	↑	0	x	0	1	Q (n)	QN (n)
1	↑	1	x	0	1	QN (n)	Q (n)
x	↓	x	x	x	1	Q (n)	QN (n)
x	x	x	x	x	0	0	1
x	↑	x	0	1	1	0	1
x	↑	x	1	1	1	1	0

Cell Data

Input Load (SL)												Gate Count	
FJ2S						*FJ2SD2*						*FJ2S*	*FJ2SD2*
J	K	CK	RN	TI	TE	J	K	CK	RN	TI	TE		
0.5	0.5	0.6	1.6	0.6	1.2	0.5	0.5	0.6	1.5	0.6	1.2	9.67	10.33

Schematic Diagram



Timing Requirements

(Typical process, 25 °C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ2S	FJ2SD2
Input Setup Time (J to CK)	t_{SU}	0.763	0.765
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.763	0.765
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.670	0.660
Pulse Width High (CK)	t_{PWH}	0.504	0.554
Pulse Width Low (RN)	t_{PWL}	0.372	0.420
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.594	0.588
Input Setup Time (TI to CK)	t_{SU}	0.568	0.558
Input Hold Time (TI to CK)	t_{HD}	0.029	0.043
Input Setup Time (TE to CK)	t_{SU}	0.570	0.560
Input Hold Time (TE to CK)	t_{HD}	0.029	0.043

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ2S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.193	0.114 + 0.039*SL	0.121 + 0.038*SL	0.118 + 0.038*SL
	t_F	0.153	0.088 + 0.033*SL	0.097 + 0.031*SL	0.093 + 0.031*SL
	t_{PLH}	0.693	0.642 + 0.025*SL	0.661 + 0.021*SL	0.675 + 0.019*SL
	t_{PHL}	0.676	0.629 + 0.023*SL	0.645 + 0.019*SL	0.659 + 0.018*SL
RN to Q	t_F	0.153	0.088 + 0.033*SL	0.097 + 0.031*SL	0.094 + 0.031*SL
	t_{PHL}	0.304	0.257 + 0.023*SL	0.274 + 0.019*SL	0.288 + 0.018*SL
CK to QN	t_R	0.151	0.079 + 0.036*SL	0.073 + 0.037*SL	0.066 + 0.038*SL
	t_F	0.137	0.075 + 0.031*SL	0.074 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.769	0.731 + 0.019*SL	0.738 + 0.017*SL	0.740 + 0.017*SL
	t_{PHL}	0.806	0.766 + 0.020*SL	0.776 + 0.018*SL	0.782 + 0.017*SL
RN to QN	t_R	0.171	0.095 + 0.038*SL	0.100 + 0.037*SL	0.098 + 0.037*SL
	t_{PLH}	0.455	0.409 + 0.023*SL	0.422 + 0.019*SL	0.435 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FJ2SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.149	0.105 + 0.022*SL	0.116 + 0.019*SL	0.122 + 0.019*SL
	t_F	0.122	0.083 + 0.020*SL	0.094 + 0.017*SL	0.101 + 0.016*SL
	t_{PLH}	0.707	0.675 + 0.016*SL	0.691 + 0.012*SL	0.718 + 0.010*SL
	t_{PHL}	0.688	0.657 + 0.016*SL	0.672 + 0.012*SL	0.696 + 0.010*SL
RN to Q	t_F	0.122	0.083 + 0.020*SL	0.095 + 0.017*SL	0.100 + 0.016*SL
	t_{PHL}	0.301	0.270 + 0.016*SL	0.286 + 0.012*SL	0.311 + 0.010*SL
CK to QN	t_R	0.112	0.076 + 0.018*SL	0.076 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.110	0.076 + 0.017*SL	0.079 + 0.016*SL	0.076 + 0.016*SL
	t_{PLH}	0.830	0.805 + 0.012*SL	0.816 + 0.010*SL	0.825 + 0.009*SL
	t_{PHL}	0.884	0.857 + 0.014*SL	0.870 + 0.010*SL	0.885 + 0.009*SL
RN to QN	t_R	0.126	0.084 + 0.021*SL	0.091 + 0.019*SL	0.094 + 0.019*SL
	t_{PLH}	0.497	0.468 + 0.014*SL	0.481 + 0.011*SL	0.500 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol5



Truth Table

J	CK	K	RN	SN	Q (n+1)	QN (n+1)
0	↑	1	1	1	0	1
1	↑	0	1	1	1	0
0	↑	0	1	1	Q (n)	QN (n)
1	↑	1	1	1	QN (n)	Q (n)
x	↓	x	1	1	Q (n)	QN (n)
x	x	x	0	1	0	1
x	x	x	1	0	1	0
x	x	x	0	0	0	0

Cell Data

Input Load (SL)										Gate Count	
FJ4					*FJ4D2*					*FJ4*	*FJ4D2*
J	K	CK	RN	SN	J	K	CK	RN	SN		
0.4	0.6	0.6	1.7	1.5	0.4	0.6	0.6	1.7	1.5	8.33	8.67

Schematic Diagram



FJ4/FJ4D2

JK Flip-Flop with Reset, Set, 1X/2X Drive

Timing Requirements

(Typical process, 25°C, 1.8 V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ4	FJ4D2
Input Setup Time (J to CK)	t_{SU}	0.547	0.538
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.547	0.538
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.623	0.624
Pulse Width High (CK)	t_{PWH}	0.471	0.514
Pulse Width Low (RN)	t_{PWL}	0.433	0.486
Pulse Width Low (SN)	t_{PWL}	0.409	0.460
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.370	0.370
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.695	0.697
Recovery Time (SN to RN)	t_{RC}	0.151	0.150
Removal Time (SN to RN)	t_{RM}	0.129	0.131

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.180	0.104 + 0.038*SL	0.108 + 0.037*SL	0.104 + 0.038*SL
	t_F	0.155	0.088 + 0.034*SL	0.093 + 0.032*SL	0.089 + 0.033*SL
	t_{PLH}	0.843	0.794 + 0.024*SL	0.812 + 0.020*SL	0.825 + 0.018*SL
	t_{PHL}	0.803	0.755 + 0.024*SL	0.772 + 0.020*SL	0.784 + 0.018*SL
RN to Q	t_R	0.203	0.118 + 0.042*SL	0.136 + 0.038*SL	0.141 + 0.037*SL
	t_F	0.171	0.099 + 0.036*SL	0.109 + 0.033*SL	0.113 + 0.033*SL
	t_{PLH}	0.341	0.285 + 0.028*SL	0.307 + 0.023*SL	0.331 + 0.019*SL
	t_{PHL}	0.343	0.291 + 0.026*SL	0.309 + 0.022*SL	0.326 + 0.019*SL
SN to Q	t_R	0.204	0.119 + 0.043*SL	0.138 + 0.038*SL	0.143 + 0.037*SL
	t_{PLH}	0.518	0.462 + 0.028*SL	0.484 + 0.023*SL	0.508 + 0.020*SL
CK to QN	t_R	0.175	0.099 + 0.038*SL	0.101 + 0.037*SL	0.097 + 0.038*SL
	t_F	0.145	0.082 + 0.031*SL	0.084 + 0.031*SL	0.080 + 0.032*SL
	t_{PLH}	0.627	0.582 + 0.023*SL	0.596 + 0.019*SL	0.605 + 0.018*SL
	t_{PHL}	0.647	0.604 + 0.022*SL	0.616 + 0.018*SL	0.624 + 0.017*SL
RN to QN	t_R	0.180	0.107 + 0.037*SL	0.105 + 0.037*SL	0.100 + 0.038*SL
	t_{PLH}	0.628	0.582 + 0.023*SL	0.597 + 0.019*SL	0.607 + 0.018*SL
SN to QN	t_R	0.169	0.094 + 0.037*SL	0.095 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.142	0.081 + 0.031*SL	0.079 + 0.031*SL	0.075 + 0.032*SL
	t_{PLH}	0.257	0.213 + 0.022*SL	0.226 + 0.019*SL	0.234 + 0.018*SL
	t_{PHL}	0.270	0.228 + 0.021*SL	0.240 + 0.018*SL	0.247 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.138	0.095 + 0.022*SL	0.106 + 0.019*SL	0.109 + 0.019*SL
	t_F	0.119	0.081 + 0.019*SL	0.090 + 0.017*SL	0.096 + 0.016*SL
	t_{PLH}	0.902	0.870 + 0.016*SL	0.886 + 0.012*SL	0.911 + 0.010*SL
	t_{PHL}	0.861	0.830 + 0.015*SL	0.846 + 0.012*SL	0.869 + 0.010*SL
RN to Q	t_R	0.156	0.108 + 0.024*SL	0.122 + 0.020*SL	0.141 + 0.019*SL
	t_F	0.130	0.089 + 0.021*SL	0.101 + 0.018*SL	0.113 + 0.017*SL
	t_{PLH}	0.335	0.300 + 0.018*SL	0.317 + 0.013*SL	0.351 + 0.010*SL
	t_{PHL}	0.333	0.300 + 0.017*SL	0.316 + 0.013*SL	0.342 + 0.010*SL
SN to Q	t_R	0.157	0.109 + 0.024*SL	0.124 + 0.020*SL	0.143 + 0.019*SL
	t_{PLH}	0.562	0.526 + 0.018*SL	0.544 + 0.013*SL	0.577 + 0.010*SL
CK to QN	t_R	0.135	0.094 + 0.021*SL	0.101 + 0.019*SL	0.103 + 0.018*SL
	t_F	0.117	0.080 + 0.018*SL	0.089 + 0.016*SL	0.087 + 0.016*SL
	t_{PLH}	0.636	0.607 + 0.015*SL	0.621 + 0.011*SL	0.642 + 0.009*SL
	t_{PHL}	0.661	0.632 + 0.015*SL	0.646 + 0.011*SL	0.664 + 0.009*SL
RN to QN	t_R	0.140	0.100 + 0.020*SL	0.107 + 0.018*SL	0.107 + 0.018*SL
	t_{PLH}	0.682	0.653 + 0.015*SL	0.668 + 0.011*SL	0.689 + 0.009*SL
SN to QN	t_R	0.127	0.086 + 0.020*SL	0.094 + 0.019*SL	0.094 + 0.018*SL
	t_F	0.112	0.076 + 0.018*SL	0.081 + 0.017*SL	0.082 + 0.017*SL
	t_{PLH}	0.261	0.233 + 0.014*SL	0.246 + 0.011*SL	0.266 + 0.009*SL
	t_{PHL}	0.271	0.242 + 0.014*SL	0.256 + 0.011*SL	0.274 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

FJ4S/FJ4SD2

JK Flip-Flop with Reset, Set, Scan, 1X/2X Drive

Logic Symbol



Truth Table

J	CK	K	TI	TE	RN	SN	Q (n+1)	QN (n+1)
0	↑	1	x	0	1	1	0	1
1	↑	0	x	0	1	1	1	0
0	↑	0	x	0	1	1	Q (n)	QN (n)
1	↑	1	x	0	1	1	QN (n)	Q (n)
x	↓	x	x	x	1	1	Q (n)	QN (n)
x	x	x	x	x	0	1	0	1
x	x	x	x	x	1	0	1	0
x	x	x	x	x	0	0	0	0
x	↑	x	0	1	1	1	0	1
x	↑	x	1	1	1	1	1	0

Cell Data

Input Load (SL)														Gate Count	
FJ4S							*FJ4SD2*							*FJ4S*	*FJ4SD2*
J	K	CK	RN	SN	TI	TE	J	K	CK	RN	SN	TI	TE		
0.5	0.5	0.6	1.6	1.6	0.6	1.2	0.5	0.5	0.6	1.6	1.6	0.6	1.2	10.67	11.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FJ4S	FJ4SD2
Input Setup Time (J to CK)	t_{SU}	0.774	0.766
Input Hold Time (J to CK)	t_{HD}	0.000	0.000
Input Setup Time (K to CK)	t_{SU}	0.774	0.766
Input Hold Time (K to CK)	t_{HD}	0.000	0.000
Pulse Width Low (CK)	t_{PWL}	0.711	0.712
Pulse Width High (CK)	t_{PWH}	0.522	0.559
Pulse Width Low (RN)	t_{PWL}	0.419	0.474
Pulse Width Low (SN)	t_{PWL}	0.445	0.493
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.638	0.639
Recovery Time (SN to CK)	t_{RC}	0.000	0.000
Removal Time (SN to CK)	t_{RM}	0.638	0.639
Input Setup Time (TI to CK)	t_{SU}	0.612	0.612
Input Hold Time (TI to CK)	t_{HD}	0.032	0.032
Input Setup Time (TE to CK)	t_{SU}	0.614	0.614
Input Hold Time (TE to CK)	t_{HD}	0.000	0.000
Recovery Time (SN to RN)	t_{RC}	0.151	0.151
Removal Time (SN to RN)	t_{RM}	0.129	0.128

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ4S

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.192	0.116 + 0.038*SL	0.122 + 0.036*SL	0.122 + 0.037*SL
	t_F	0.160	0.094 + 0.033*SL	0.102 + 0.031*SL	0.101 + 0.031*SL
	t_{PLH}	0.711	0.661 + 0.025*SL	0.680 + 0.020*SL	0.695 + 0.018*SL
	t_{PHL}	0.708	0.661 + 0.024*SL	0.677 + 0.020*SL	0.691 + 0.018*SL
RN to Q	t_R	0.178	0.103 + 0.037*SL	0.107 + 0.036*SL	0.104 + 0.037*SL
	t_F	0.155	0.088 + 0.033*SL	0.098 + 0.031*SL	0.095 + 0.031*SL
	t_{PLH}	0.298	0.250 + 0.024*SL	0.267 + 0.019*SL	0.280 + 0.018*SL
	t_{PHL}	0.308	0.261 + 0.023*SL	0.278 + 0.019*SL	0.290 + 0.018*SL
SN to Q	t_R	0.189	0.115 + 0.037*SL	0.120 + 0.036*SL	0.114 + 0.037*SL
	t_{PLH}	0.654	0.606 + 0.024*SL	0.624 + 0.020*SL	0.638 + 0.018*SL
CK to QN	t_R	0.168	0.095 + 0.037*SL	0.094 + 0.037*SL	0.088 + 0.038*SL
	t_F	0.143	0.081 + 0.031*SL	0.083 + 0.031*SL	0.077 + 0.031*SL
	t_{PLH}	0.861	0.818 + 0.022*SL	0.830 + 0.019*SL	0.838 + 0.018*SL
	t_{PHL}	0.851	0.809 + 0.021*SL	0.821 + 0.018*SL	0.829 + 0.017*SL
RN to QN	t_R	0.200	0.115 + 0.042*SL	0.133 + 0.038*SL	0.139 + 0.037*SL
	t_{PLH}	0.519	0.465 + 0.027*SL	0.484 + 0.022*SL	0.508 + 0.019*SL
SN to QN	t_R	0.196	0.111 + 0.042*SL	0.128 + 0.038*SL	0.135 + 0.037*SL
	t_F	0.159	0.091 + 0.034*SL	0.095 + 0.033*SL	0.101 + 0.032*SL
	t_{PLH}	0.291	0.237 + 0.027*SL	0.256 + 0.022*SL	0.278 + 0.019*SL
	t_{PHL}	0.304	0.257 + 0.023*SL	0.270 + 0.020*SL	0.281 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FJ4SD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.149	0.105 + 0.022*SL	0.116 + 0.019*SL	0.121 + 0.019*SL
	t_F	0.125	0.086 + 0.020*SL	0.098 + 0.017*SL	0.102 + 0.016*SL
	t_{PLH}	0.712	0.679 + 0.016*SL	0.696 + 0.012*SL	0.722 + 0.010*SL
	t_{PHL}	0.708	0.677 + 0.016*SL	0.692 + 0.012*SL	0.717 + 0.010*SL
RN to Q	t_R	0.137	0.094 + 0.021*SL	0.104 + 0.019*SL	0.107 + 0.019*SL
	t_F	0.122	0.084 + 0.019*SL	0.094 + 0.017*SL	0.099 + 0.016*SL
	t_{PLH}	0.296	0.265 + 0.016*SL	0.281 + 0.012*SL	0.305 + 0.010*SL
	t_{PHL}	0.304	0.272 + 0.016*SL	0.288 + 0.012*SL	0.312 + 0.010*SL
SN to Q	t_R	0.148	0.106 + 0.021*SL	0.116 + 0.019*SL	0.119 + 0.018*SL
	t_{PLH}	0.698	0.666 + 0.016*SL	0.683 + 0.012*SL	0.709 + 0.010*SL
CK to QN	t_R	0.130	0.089 + 0.020*SL	0.096 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.113	0.075 + 0.019*SL	0.085 + 0.016*SL	0.084 + 0.016*SL
	t_{PLH}	0.912	0.884 + 0.014*SL	0.897 + 0.011*SL	0.916 + 0.009*SL
	t_{PHL}	0.909	0.881 + 0.014*SL	0.894 + 0.011*SL	0.912 + 0.009*SL
RN to QN	t_R	0.153	0.105 + 0.024*SL	0.118 + 0.021*SL	0.137 + 0.019*SL
	t_{PLH}	0.560	0.527 + 0.017*SL	0.542 + 0.013*SL	0.573 + 0.010*SL
SN to QN	t_R	0.148	0.100 + 0.024*SL	0.113 + 0.021*SL	0.131 + 0.019*SL
	t_F	0.124	0.084 + 0.020*SL	0.093 + 0.018*SL	0.100 + 0.017*SL
	t_{PLH}	0.287	0.254 + 0.017*SL	0.268 + 0.013*SL	0.299 + 0.010*SL
	t_{PHL}	0.301	0.270 + 0.015*SL	0.284 + 0.012*SL	0.304 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

CK	RN	Q (n+1)	QN (n+1)
⎍	1	QN (n)	Q (n)
⎎	1	Q (n)	QN (n)
x	0	0	1

Cell Data

Input Load (SL)				Gate Count	
FT2		*FT2D2*		*FT2*	*FT2D2*
CK	RN	CK	RN		
0.6	0.5	0.6	1.5	6.00	6.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		FT2	FT2D2
Pulse Width Low (CK)	t_{PWL}	0.370	0.369
Pulse Width High (CK)	t_{PWH}	0.458	0.489
Pulse Width Low (RN)	t_{PWL}	0.447	0.495
Recovery Time (RN to CK)	t_{RC}	0.000	0.000
Removal Time (RN to CK)	t_{RM}	0.303	0.304

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FT2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.173	0.099 + 0.037*SL	0.101 + 0.036*SL	0.097 + 0.037*SL
	t_F	0.150	0.083 + 0.034*SL	0.087 + 0.033*SL	0.083 + 0.033*SL
	t_{PLH}	0.794	0.749 + 0.023*SL	0.764 + 0.019*SL	0.775 + 0.018*SL
	t_{PHL}	0.738	0.692 + 0.023*SL	0.706 + 0.019*SL	0.716 + 0.018*SL
RN to Q	t_F	0.151	0.083 + 0.034*SL	0.087 + 0.033*SL	0.087 + 0.033*SL
	t_{PHL}	0.289	0.243 + 0.023*SL	0.256 + 0.020*SL	0.265 + 0.018*SL
CK to QN	t_R	0.159	0.089 + 0.035*SL	0.084 + 0.037*SL	0.076 + 0.038*SL
	t_F	0.148	0.081 + 0.033*SL	0.083 + 0.033*SL	0.079 + 0.033*SL
	t_{PLH}	0.575	0.535 + 0.020*SL	0.545 + 0.018*SL	0.548 + 0.017*SL
	t_{PHL}	0.622	0.578 + 0.022*SL	0.590 + 0.019*SL	0.597 + 0.018*SL
RN to QN	t_R	0.159	0.089 + 0.035*SL	0.082 + 0.036*SL	0.074 + 0.037*SL
	t_{PLH}	0.551	0.511 + 0.020*SL	0.521 + 0.018*SL	0.525 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

FT2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
CK to Q	t_R	0.133	0.090 + 0.021*SL	0.099 + 0.019*SL	0.102 + 0.019*SL
	t_F	0.114	0.075 + 0.019*SL	0.086 + 0.017*SL	0.088 + 0.016*SL
	t_{PLH}	0.845	0.815 + 0.015*SL	0.830 + 0.011*SL	0.852 + 0.009*SL
	t_{PHL}	0.779	0.749 + 0.015*SL	0.763 + 0.011*SL	0.784 + 0.009*SL
RN to Q	t_F	0.114	0.076 + 0.019*SL	0.085 + 0.017*SL	0.090 + 0.016*SL
	t_{PHL}	0.283	0.254 + 0.015*SL	0.268 + 0.011*SL	0.288 + 0.010*SL
CK to QN	t_R	0.120	0.083 + 0.019*SL	0.084 + 0.018*SL	0.075 + 0.019*SL
	t_F	0.113	0.078 + 0.018*SL	0.082 + 0.016*SL	0.080 + 0.017*SL
	t_{PLH}	0.581	0.554 + 0.013*SL	0.567 + 0.010*SL	0.579 + 0.009*SL
	t_{PHL}	0.625	0.597 + 0.014*SL	0.611 + 0.011*SL	0.628 + 0.009*SL
RN to QN	t_R	0.118	0.082 + 0.018*SL	0.082 + 0.018*SL	0.073 + 0.019*SL
	t_{PLH}	0.559	0.533 + 0.013*SL	0.545 + 0.010*SL	0.557 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LATCHES

Cell List

Cell Name	Function Description
LD1	D Latch with Active High
LD1D2	D Latch with Active High, 2X Drive
LD1A	D Latch with Active High, Tri-State Output
LD1D2A	D Latch with Active High, Tri-State Output, 2x Drive
LD1Q	D Latch with Active High, Q Output Only
LD1QD2	D Latch with Active High, Q Output Only, 2X Drive
LD2	D Latch with Active High, Reset
LD2D2	D Latch with Active High, Reset, 2X Drive
LD2Q	D Latch with Active High, Reset, Q Output Only
LD2QD2	D Latch with Active High, Reset, Q Output Only, 2X Drive
LD3	D Latch with Active High, Set
LD3D2	D Latch with Active High, Set, 2X Drive
LD4	D Latch with Active High, Reset, Set
LD4D2	D Latch with Active High, Reset, Set, 2X Drive
LD5	D Latch with Active Low
LD5D2	D Latch with Active Low, 2X Drive
LD5Q	D Latch with Active Low, Q Output Only
LD5QD2	D Latch with Active Low, Q Output Only, 2X Drive
LD6	D Latch with Active Low, Reset
LD6D2	D Latch with Active Low, Reset, 2X Drive
LD6Q	D Latch with Active Low, Reset, Q Output Only
LD6QD2	D Latch with Active Low, Reset, Q Output Only, 2X Drive
LD7	D Latch with Active Low, Set
LD7D2	D Latch with Active Low, Set, 2X Drive
LD8	D Latch with Active Low, Reset, Set
LD8D2	D Latch with Active Low, Reset, Set, 2X Drive
LS1	SR Latch with Separate Inputs
LS1D2	SR Latch with Separate Inputs, 2X Drive

NOTE

LD1/LD1D2

D Latch with Active High, 1X/2X Drive

Logic Symbol



Truth Table

D	G	Q (n+1)	QN (n+1)
0	1	0	1
1	1	1	0
x	0	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
LD1		*LD1D2*		*LD1*	*LD1D2*
D	G	D	G		
0.6	0.5	0.6	0.6	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1	LD1D2
Input Setup Time (D to G)	t_{SU}	0.329	0.356
Input Hold Time (D to G)	t_{HD}	0.062	0.026
Pulse Width High (G)	t_{PWH}	0.393	0.431

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.144	0.070 + 0.037*SL	0.065 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.133	0.068 + 0.032*SL	0.064 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.504	0.465 + 0.019*SL	0.472 + 0.018*SL	0.474 + 0.017*SL
	t_{PHL}	0.541	0.499 + 0.021*SL	0.509 + 0.018*SL	0.513 + 0.018*SL
G to Q	t_R	0.145	0.072 + 0.037*SL	0.067 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.133	0.067 + 0.033*SL	0.066 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.599	0.560 + 0.019*SL	0.567 + 0.018*SL	0.568 + 0.017*SL
	t_{PHL}	0.610	0.568 + 0.021*SL	0.578 + 0.018*SL	0.582 + 0.018*SL
D to QN	t_R	0.158	0.084 + 0.037*SL	0.081 + 0.038*SL	0.074 + 0.039*SL
	t_F	0.144	0.076 + 0.034*SL	0.081 + 0.033*SL	0.075 + 0.034*SL
	t_{PLH}	0.438	0.397 + 0.021*SL	0.406 + 0.018*SL	0.411 + 0.018*SL
	t_{PHL}	0.424	0.380 + 0.022*SL	0.391 + 0.019*SL	0.401 + 0.018*SL
G to QN	t_R	0.158	0.084 + 0.037*SL	0.079 + 0.038*SL	0.073 + 0.039*SL
	t_F	0.144	0.076 + 0.034*SL	0.079 + 0.033*SL	0.075 + 0.034*SL
	t_{PLH}	0.507	0.466 + 0.020*SL	0.475 + 0.018*SL	0.480 + 0.018*SL
	t_{PHL}	0.519	0.474 + 0.022*SL	0.486 + 0.019*SL	0.495 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.107	0.071 + 0.018*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.099	0.064 + 0.018*SL	0.069 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.552	0.528 + 0.012*SL	0.538 + 0.010*SL	0.546 + 0.009*SL
	t_{PHL}	0.585	0.559 + 0.013*SL	0.571 + 0.010*SL	0.584 + 0.009*SL
G to Q	t_R	0.107	0.071 + 0.018*SL	0.070 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.099	0.065 + 0.017*SL	0.069 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.652	0.628 + 0.012*SL	0.638 + 0.010*SL	0.647 + 0.009*SL
	t_{PHL}	0.666	0.640 + 0.013*SL	0.652 + 0.010*SL	0.665 + 0.009*SL
D to QN	t_R	0.115	0.078 + 0.018*SL	0.078 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.106	0.071 + 0.018*SL	0.075 + 0.017*SL	0.077 + 0.017*SL
	t_{PLH}	0.442	0.416 + 0.013*SL	0.428 + 0.010*SL	0.440 + 0.009*SL
	t_{PHL}	0.424	0.396 + 0.014*SL	0.409 + 0.011*SL	0.425 + 0.009*SL
G to QN	t_R	0.115	0.078 + 0.018*SL	0.078 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.106	0.070 + 0.018*SL	0.076 + 0.017*SL	0.077 + 0.016*SL
	t_{PLH}	0.523	0.497 + 0.013*SL	0.509 + 0.010*SL	0.520 + 0.009*SL
	t_{PHL}	0.524	0.496 + 0.014*SL	0.509 + 0.011*SL	0.525 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD1A/LD1D2A

D Latch with Active High, Tri-State Output, 1x/2x Drive

Logic Symbol



Truth Table

D	G	E	Q (n+1)
x	x	0	Hi-Z
0	1	1	0
1	1	1	1
x	0	1	Q (n)

Cell Data

Input Load (SL)						Output Load (SL)		Gate Count	
LD1A			*LD1D2A*			*LD1A*	*LD1D2A*	*LD1A*	*LD1D2A*
D	G	E	D	G	E	Q	Q		
0.6	0.5	1.3	0.6	0.6	1.7	1.0	1.3	4.33	5.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1A	LD1D2A
Input Setup Time (D to G)	t_{SU}	0.332	0.324
Input Hold Time (D to G)	t_{HD}	0.058	0.065
Pulse Width High (G)	t_{PWH}	0.388	0.398

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD1A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.165	0.091 + 0.037*SL	0.089 + 0.038*SL	0.083 + 0.038*SL
	t_F	0.163	0.073 + 0.045*SL	0.069 + 0.046*SL	0.067 + 0.046*SL
	t_{PLH}	0.523	0.485 + 0.019*SL	0.491 + 0.018*SL	0.495 + 0.017*SL
	t_{PHL}	0.539	0.491 + 0.024*SL	0.496 + 0.023*SL	0.498 + 0.023*SL
G to Q	t_R	0.164	0.090 + 0.037*SL	0.088 + 0.038*SL	0.084 + 0.038*SL
	t_F	0.163	0.073 + 0.045*SL	0.069 + 0.046*SL	0.067 + 0.046*SL
	t_{PLH}	0.612	0.573 + 0.019*SL	0.580 + 0.018*SL	0.583 + 0.017*SL
	t_{PHL}	0.601	0.553 + 0.024*SL	0.557 + 0.023*SL	0.559 + 0.023*SL
E to Q	t_R	0.204	0.123 + 0.040*SL	0.112 + 0.043*SL	0.104 + 0.044*SL
	t_F	0.234	0.140 + 0.047*SL	0.124 + 0.051*SL	0.107 + 0.053*SL
	t_{PLH}	0.201	0.160 + 0.020*SL	0.169 + 0.018*SL	0.172 + 0.018*SL
	t_{PHL}	0.124	0.070 + 0.027*SL	0.087 + 0.023*SL	0.085 + 0.023*SL
	t_{PLZ}	0.137	0.137 + 0.000*SL	0.137 + 0.000*SL	0.137 + 0.000*SL
	t_{PHZ}	0.208	0.208 + 0.000*SL	0.208 + 0.000*SL	0.208 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD1D2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.125	0.086 + 0.019*SL	0.088 + 0.019*SL	0.084 + 0.019*SL
	t_F	0.107	0.062 + 0.022*SL	0.061 + 0.023*SL	0.055 + 0.023*SL
	t_{PLH}	0.516	0.492 + 0.012*SL	0.501 + 0.010*SL	0.511 + 0.009*SL
	t_{PHL}	0.514	0.488 + 0.013*SL	0.493 + 0.012*SL	0.498 + 0.011*SL
G to Q	t_R	0.125	0.086 + 0.019*SL	0.088 + 0.019*SL	0.083 + 0.019*SL
	t_F	0.107	0.062 + 0.022*SL	0.061 + 0.023*SL	0.055 + 0.023*SL
	t_{PLH}	0.616	0.592 + 0.012*SL	0.601 + 0.010*SL	0.611 + 0.009*SL
	t_{PHL}	0.595	0.569 + 0.013*SL	0.575 + 0.012*SL	0.579 + 0.011*SL
E to Q	t_R	0.158	0.125 + 0.017*SL	0.114 + 0.019*SL	0.101 + 0.020*SL
	t_F	0.156	0.112 + 0.022*SL	0.112 + 0.022*SL	0.091 + 0.024*SL
	t_{PLH}	0.195	0.169 + 0.013*SL	0.180 + 0.010*SL	0.192 + 0.009*SL
	t_{PHL}	0.077	0.040 + 0.018*SL	0.065 + 0.012*SL	0.075 + 0.011*SL
	t_{PLZ}	0.137	0.137 + 0.000*SL	0.137 + 0.000*SL	0.137 + 0.000*SL
	t_{PHZ}	0.242	0.242 + 0.000*SL	0.242 + 0.000*SL	0.242 + 0.000*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD1Q/LD1QD2

D Latch with Active High, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	G	Q (n+1)
0	1	0
1	1	1
x	0	Q (n)

Cell Data

Input Load (SL)				Gate Count	
LD1Q		*LD1QD2*		*LD1Q*	*LD1QD2*
D	G	D	G		
0.6	0.6	0.6	0.6	3.33	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD1Q	LD1QD2
Input Setup Time (D to G)	t_{SU}	0.303	0.310
Input Hold Time (D to G)	t_{HD}	0.090	0.081
Pulse Width High (G)	t_{PWH}	0.372	0.382

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD1Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.142	0.069 + 0.037*SL	0.062 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.130	0.065 + 0.032*SL	0.062 + 0.033*SL	0.057 + 0.034*SL
	t_{PLH}	0.453	0.416 + 0.019*SL	0.421 + 0.018*SL	0.422 + 0.017*SL
	t_{PHL}	0.487	0.446 + 0.020*SL	0.454 + 0.018*SL	0.458 + 0.018*SL
G to Q	t_R	0.143	0.069 + 0.037*SL	0.064 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.130	0.065 + 0.033*SL	0.063 + 0.033*SL	0.057 + 0.034*SL
	t_{PLH}	0.548	0.510 + 0.019*SL	0.515 + 0.018*SL	0.516 + 0.017*SL
	t_{PHL}	0.566	0.526 + 0.020*SL	0.534 + 0.018*SL	0.538 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD1QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	0.065 + 0.019*SL	0.065 + 0.018*SL	0.057 + 0.019*SL
	t_F	0.096	0.062 + 0.017*SL	0.066 + 0.016*SL	0.061 + 0.017*SL
	t_{PLH}	0.454	0.431 + 0.012*SL	0.440 + 0.009*SL	0.448 + 0.009*SL
	t_{PHL}	0.489	0.463 + 0.013*SL	0.475 + 0.010*SL	0.487 + 0.009*SL
G to Q	t_R	0.101	0.064 + 0.019*SL	0.064 + 0.019*SL	0.057 + 0.019*SL
	t_F	0.097	0.063 + 0.017*SL	0.066 + 0.016*SL	0.061 + 0.017*SL
	t_{PLH}	0.554	0.531 + 0.012*SL	0.540 + 0.009*SL	0.548 + 0.009*SL
	t_{PHL}	0.570	0.544 + 0.013*SL	0.555 + 0.010*SL	0.568 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD2/LD2D2

D Latch with Active High, Reset, 1X/2X Drive

Logic Symbol



Truth Table

D	G	RN	Q (n+1)	QN (n+1)
0	1	1	0	1
1	1	1	1	0
x	0	1	Q (n)	QN (n)
x	x	0	0	1

Cell Data

Input Load (SL)						Gate Count	
LD2			*LD2D2*			*LD2*	*LD2D2*
D	G	RN	D	G	RN		
0.6	0.5	0.8	0.6	0.5	0.8	4.67	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD2	LD2D2
Input Setup Time (D to G)	t_{SU}	0.419	0.452
Input Hold Time (D to G)	t_{HD}	0.000	0.000
Pulse Width High (G)	t_{PWH}	0.420	0.459
Pulse Width Low (RN)	t_{PWL}	0.333	0.385
Recovery Time (RN to G)	t_{RC}	0.077	0.118
Removal Time (RN to G)	t_{RM}	0.204	0.162

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.174	0.097 + 0.038*SL	0.099 + 0.038*SL	0.094 + 0.039*SL
	t_F	0.145	0.078 + 0.034*SL	0.081 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.547	0.501 + 0.023*SL	0.514 + 0.020*SL	0.524 + 0.018*SL
	t_{PHL}	0.533	0.488 + 0.022*SL	0.501 + 0.019*SL	0.511 + 0.018*SL
G to Q	t_R	0.173	0.096 + 0.039*SL	0.099 + 0.038*SL	0.094 + 0.039*SL
	t_F	0.145	0.078 + 0.034*SL	0.081 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.553	0.507 + 0.023*SL	0.520 + 0.020*SL	0.531 + 0.018*SL
	t_{PHL}	0.538	0.494 + 0.022*SL	0.506 + 0.019*SL	0.516 + 0.018*SL
RN to Q	t_R	0.168	0.090 + 0.039*SL	0.094 + 0.038*SL	0.090 + 0.039*SL
	t_F	0.144	0.077 + 0.034*SL	0.082 + 0.033*SL	0.076 + 0.033*SL
	t_{PLH}	0.253	0.208 + 0.023*SL	0.221 + 0.020*SL	0.230 + 0.018*SL
	t_{PHL}	0.264	0.219 + 0.022*SL	0.231 + 0.019*SL	0.241 + 0.018*SL
D to QN	t_R	0.145	0.073 + 0.036*SL	0.068 + 0.037*SL	0.061 + 0.038*SL
	t_F	0.135	0.070 + 0.033*SL	0.069 + 0.033*SL	0.064 + 0.034*SL
	t_{PLH}	0.618	0.580 + 0.019*SL	0.587 + 0.017*SL	0.589 + 0.017*SL
	t_{PHL}	0.653	0.612 + 0.021*SL	0.622 + 0.018*SL	0.627 + 0.018*SL
G to QN	t_R	0.145	0.073 + 0.036*SL	0.068 + 0.037*SL	0.061 + 0.038*SL
	t_F	0.136	0.071 + 0.032*SL	0.070 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.624	0.585 + 0.019*SL	0.592 + 0.017*SL	0.594 + 0.017*SL
	t_{PHL}	0.660	0.618 + 0.021*SL	0.628 + 0.018*SL	0.633 + 0.018*SL
RN to QN	t_R	0.144	0.072 + 0.036*SL	0.067 + 0.037*SL	0.060 + 0.038*SL
	t_F	0.135	0.071 + 0.032*SL	0.067 + 0.033*SL	0.062 + 0.034*SL
	t_{PLH}	0.349	0.310 + 0.019*SL	0.317 + 0.017*SL	0.319 + 0.017*SL
	t_{PHL}	0.360	0.318 + 0.021*SL	0.328 + 0.018*SL	0.333 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.131	0.090 + 0.020*SL	0.096 + 0.019*SL	0.098 + 0.019*SL
	t_F	0.110	0.072 + 0.019*SL	0.080 + 0.017*SL	0.082 + 0.017*SL
	t_{PLH}	0.553	0.524 + 0.015*SL	0.538 + 0.011*SL	0.558 + 0.009*SL
	t_{PHL}	0.535	0.506 + 0.014*SL	0.520 + 0.011*SL	0.538 + 0.009*SL
G to Q	t_R	0.131	0.089 + 0.021*SL	0.097 + 0.019*SL	0.096 + 0.019*SL
	t_F	0.110	0.072 + 0.019*SL	0.080 + 0.017*SL	0.082 + 0.017*SL
	t_{PLH}	0.559	0.530 + 0.015*SL	0.544 + 0.011*SL	0.564 + 0.009*SL
	t_{PHL}	0.540	0.511 + 0.014*SL	0.525 + 0.011*SL	0.543 + 0.009*SL
RN to Q	t_R	0.126	0.085 + 0.021*SL	0.091 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.108	0.071 + 0.018*SL	0.078 + 0.017*SL	0.080 + 0.017*SL
	t_{PLH}	0.256	0.227 + 0.014*SL	0.241 + 0.011*SL	0.259 + 0.009*SL
	t_{PHL}	0.261	0.233 + 0.014*SL	0.246 + 0.011*SL	0.263 + 0.009*SL
D to QN	t_R	0.108	0.072 + 0.018*SL	0.070 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.074 + 0.016*SL	0.071 + 0.017*SL
	t_{PLH}	0.669	0.644 + 0.012*SL	0.655 + 0.010*SL	0.664 + 0.009*SL
	t_{PHL}	0.713	0.686 + 0.014*SL	0.699 + 0.010*SL	0.713 + 0.009*SL
G to QN	t_R	0.108	0.072 + 0.018*SL	0.070 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.104	0.068 + 0.018*SL	0.075 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.674	0.650 + 0.012*SL	0.660 + 0.010*SL	0.669 + 0.009*SL
	t_{PHL}	0.719	0.692 + 0.014*SL	0.705 + 0.010*SL	0.719 + 0.009*SL
RN to QN	t_R	0.108	0.071 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.074 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.394	0.370 + 0.012*SL	0.380 + 0.010*SL	0.389 + 0.009*SL
	t_{PHL}	0.414	0.387 + 0.014*SL	0.400 + 0.010*SL	0.414 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	G	RN	Q (n+1)
0	1	1	0
1	1	1	1
x	0	1	Q (n)
x	x	0	0

Cell Data

Input Load (SL)						Gate Count	
LD2Q			*LD2QD2*			*LD2Q*	*LD2QD2*
D	G	RN	D	G	RN		
0.6	0.6	0.8	0.6	0.6	0.8	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD2Q	LD2QD2
Input Setup Time (D to G)	t_{SU}	0.311	0.317
Input Hold Time (D to G)	t_{HD}	0.083	0.078
Pulse Width High (G)	t_{PWH}	0.389	0.397
Pulse Width Low (RN)	t_{PWL}	0.345	0.375
Recovery Time (RN to G)	t_{RC}	0.000	0.000
Removal Time (RN to G)	t_{RM}	0.483	0.459

LD2Q/LD2QD2

D Latch with Active High, Reset, Q Output Only, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD2Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.163	0.089 + 0.037*SL	0.088 + 0.037*SL	0.081 + 0.038*SL
	t_F	0.132	0.070 + 0.031*SL	0.069 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.513	0.471 + 0.021*SL	0.482 + 0.019*SL	0.489 + 0.018*SL
	t_{PHL}	0.516	0.475 + 0.020*SL	0.485 + 0.018*SL	0.491 + 0.017*SL
G to Q	t_R	0.163	0.089 + 0.037*SL	0.088 + 0.037*SL	0.081 + 0.038*SL
	t_F	0.133	0.070 + 0.031*SL	0.070 + 0.031*SL	0.066 + 0.032*SL
	t_{PLH}	0.618	0.575 + 0.021*SL	0.587 + 0.019*SL	0.594 + 0.018*SL
	t_{PHL}	0.602	0.562 + 0.020*SL	0.572 + 0.018*SL	0.578 + 0.017*SL
RN to Q	t_R	0.164	0.089 + 0.037*SL	0.089 + 0.037*SL	0.082 + 0.038*SL
	t_F	0.136	0.075 + 0.031*SL	0.073 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.243	0.200 + 0.021*SL	0.212 + 0.019*SL	0.219 + 0.018*SL
	t_{PHL}	0.250	0.209 + 0.020*SL	0.220 + 0.018*SL	0.226 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD2QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.123	0.082 + 0.020*SL	0.088 + 0.019*SL	0.087 + 0.019*SL
	t_F	0.101	0.067 + 0.017*SL	0.072 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.519	0.491 + 0.014*SL	0.504 + 0.011*SL	0.522 + 0.009*SL
	t_{PHL}	0.516	0.490 + 0.013*SL	0.502 + 0.010*SL	0.518 + 0.009*SL
G to Q	t_R	0.123	0.082 + 0.020*SL	0.088 + 0.019*SL	0.087 + 0.019*SL
	t_F	0.099	0.064 + 0.017*SL	0.072 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.625	0.597 + 0.014*SL	0.610 + 0.011*SL	0.628 + 0.009*SL
	t_{PHL}	0.604	0.578 + 0.013*SL	0.590 + 0.010*SL	0.606 + 0.009*SL
RN to Q	t_R	0.123	0.083 + 0.020*SL	0.089 + 0.019*SL	0.087 + 0.019*SL
	t_F	0.104	0.071 + 0.017*SL	0.076 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.249	0.221 + 0.014*SL	0.234 + 0.011*SL	0.252 + 0.009*SL
	t_{PHL}	0.250	0.223 + 0.013*SL	0.236 + 0.010*SL	0.252 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	G	SN	Q (n+1)	QN (n+1)
0	1	1	0	1
1	1	1	1	0
x	0	1	Q (n)	QN (n)
x	x	0	1	0

Cell Data

Input Load (SL)						Gate Count	
LD3			*LD3D2*			*LD3*	*LD3D2*
D	G	SN	D	G	SN		
0.6	0.5	0.8	0.6	0.6	0.8	4.33	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD3	LD3D2
Input Setup Time (D to G)	t_{SU}	0.359	0.386
Input Hold Time (D to G)	t_{HD}	0.046	0.014
Pulse Width High (G)	t_{PWH}	0.424	0.465
Pulse Width Low (SN)	t_{PWL}	0.334	0.388
Recovery Time (SN to G)	t_{RC}	0.082	0.115
Removal Time (SN to G)	t_{RM}	0.198	0.165

D Latch with Active High, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD3

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.146	0.073 + 0.036*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.136	0.072 + 0.032*SL	0.068 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.522	0.483 + 0.019*SL	0.490 + 0.018*SL	0.491 + 0.017*SL
	t_{PHL}	0.594	0.552 + 0.021*SL	0.562 + 0.018*SL	0.568 + 0.018*SL
G to Q	t_R	0.145	0.071 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.135	0.070 + 0.033*SL	0.069 + 0.033*SL	0.064 + 0.034*SL
	t_{PLH}	0.617	0.578 + 0.019*SL	0.585 + 0.018*SL	0.587 + 0.017*SL
	t_{PHL}	0.666	0.624 + 0.021*SL	0.634 + 0.018*SL	0.639 + 0.018*SL
SN to Q	t_R	0.145	0.072 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.136	0.071 + 0.032*SL	0.070 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.350	0.311 + 0.019*SL	0.318 + 0.018*SL	0.320 + 0.017*SL
	t_{PHL}	0.365	0.323 + 0.021*SL	0.333 + 0.018*SL	0.338 + 0.018*SL
D to QN	t_R	0.173	0.097 + 0.038*SL	0.100 + 0.037*SL	0.097 + 0.038*SL
	t_F	0.145	0.077 + 0.034*SL	0.082 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.485	0.439 + 0.023*SL	0.453 + 0.019*SL	0.463 + 0.018*SL
	t_{PHL}	0.438	0.393 + 0.022*SL	0.405 + 0.019*SL	0.415 + 0.018*SL
G to QN	t_R	0.174	0.098 + 0.038*SL	0.100 + 0.037*SL	0.095 + 0.038*SL
	t_F	0.146	0.078 + 0.034*SL	0.083 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.557	0.511 + 0.023*SL	0.525 + 0.019*SL	0.535 + 0.018*SL
	t_{PHL}	0.533	0.488 + 0.022*SL	0.500 + 0.019*SL	0.510 + 0.018*SL
SN to QN	t_R	0.168	0.092 + 0.038*SL	0.095 + 0.038*SL	0.091 + 0.038*SL
	t_F	0.145	0.078 + 0.034*SL	0.083 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.256	0.211 + 0.023*SL	0.224 + 0.019*SL	0.234 + 0.018*SL
	t_{PHL}	0.265	0.221 + 0.022*SL	0.233 + 0.019*SL	0.242 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD3D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.109	0.073 + 0.018*SL	0.071 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.105	0.071 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.573	0.549 + 0.012*SL	0.559 + 0.010*SL	0.568 + 0.009*SL
	t_{PHL}	0.650	0.623 + 0.013*SL	0.636 + 0.010*SL	0.650 + 0.009*SL
G to Q	t_R	0.108	0.072 + 0.018*SL	0.071 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.675	0.650 + 0.012*SL	0.661 + 0.010*SL	0.670 + 0.009*SL
	t_{PHL}	0.732	0.705 + 0.013*SL	0.718 + 0.010*SL	0.732 + 0.009*SL
SN to Q	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.074 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.400	0.375 + 0.012*SL	0.386 + 0.010*SL	0.395 + 0.009*SL
	t_{PHL}	0.417	0.390 + 0.013*SL	0.403 + 0.010*SL	0.417 + 0.009*SL
D to QN	t_R	0.131	0.090 + 0.021*SL	0.097 + 0.019*SL	0.098 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.079 + 0.017*SL	0.081 + 0.016*SL
	t_{PLH}	0.490	0.461 + 0.015*SL	0.475 + 0.011*SL	0.495 + 0.009*SL
	t_{PHL}	0.441	0.412 + 0.014*SL	0.426 + 0.011*SL	0.443 + 0.009*SL
G to QN	t_R	0.131	0.089 + 0.021*SL	0.096 + 0.019*SL	0.098 + 0.019*SL
	t_F	0.110	0.073 + 0.018*SL	0.080 + 0.017*SL	0.082 + 0.016*SL
	t_{PLH}	0.572	0.543 + 0.015*SL	0.557 + 0.011*SL	0.577 + 0.009*SL
	t_{PHL}	0.542	0.514 + 0.014*SL	0.527 + 0.011*SL	0.545 + 0.009*SL
SN to QN	t_R	0.127	0.086 + 0.020*SL	0.093 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.110	0.074 + 0.018*SL	0.079 + 0.017*SL	0.082 + 0.016*SL
	t_{PLH}	0.259	0.230 + 0.014*SL	0.244 + 0.011*SL	0.263 + 0.009*SL
	t_{PHL}	0.267	0.238 + 0.014*SL	0.252 + 0.011*SL	0.270 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD4/LD4D2

D Latch with Active High, Reset, Set, 1X/2X Drive

Logic Symbol



Truth Table

D	G	RN	SN	Q (n+1)	QN (n+1)
0	1	1	1	0	1
1	1	1	1	1	0
x	0	1	1	Q (n)	QN (n)
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	1	0

Cell Data

Input Load (SL)								Gate Count	
LD4				*LD4D2*				*LD4*	*LD4D2*
D	G	SN	RN	D	G	SN	RN		
0.6	0.5	0.8	0.8	0.6	0.5	0.8	0.8	6.00	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD4	LD4D2
Input Setup Time (D to G)	t_{SU}	0.478	0.520
Input Hold Time (D to G)	t_{HD}	0.000	0.000
Pulse Width High (G)	t_{PWH}	0.489	0.533
Pulse Width Low (SN)	t_{PWL}	0.717	0.741
Recovery Time (SN to G)	t_{RC}	0.000	0.000
Removal Time (SN to G)	t_{RM}	0.641	0.583
Pulse Width Low (RN)	t_{PWL}	0.416	0.483
Recovery Time (RN to G)	t_{RC}	0.152	0.201
Removal Time (RN to G)	t_{RM}	0.141	0.092
Recovery Time (SN to RN)	t_{RC}	0.324	0.389
Removal Time (SN to RN)	t_{RM}	0.000	0.000

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.147	0.076 + 0.036*SL	0.071 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.134	0.072 + 0.031*SL	0.073 + 0.031*SL	0.067 + 0.032*SL
	t_{PLH}	0.738	0.699 + 0.019*SL	0.707 + 0.017*SL	0.709 + 0.017*SL
	t_{PHL}	0.755	0.714 + 0.020*SL	0.725 + 0.018*SL	0.731 + 0.017*SL
G to Q	t_R	0.146	0.074 + 0.036*SL	0.070 + 0.037*SL	0.064 + 0.038*SL
	t_F	0.134	0.071 + 0.031*SL	0.073 + 0.031*SL	0.067 + 0.032*SL
	t_{PLH}	0.747	0.708 + 0.019*SL	0.716 + 0.017*SL	0.719 + 0.017*SL
	t_{PHL}	0.761	0.720 + 0.020*SL	0.732 + 0.018*SL	0.738 + 0.017*SL
SN to Q	t_R	0.146	0.076 + 0.035*SL	0.068 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.134	0.073 + 0.031*SL	0.072 + 0.031*SL	0.066 + 0.032*SL
	t_{PLH}	0.366	0.328 + 0.019*SL	0.335 + 0.017*SL	0.338 + 0.017*SL
	t_{PHL}	0.372	0.331 + 0.020*SL	0.342 + 0.018*SL	0.349 + 0.017*SL
RN to Q	t_R	0.146	0.075 + 0.036*SL	0.068 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.134	0.072 + 0.031*SL	0.073 + 0.031*SL	0.066 + 0.032*SL
	t_{PLH}	0.443	0.405 + 0.019*SL	0.413 + 0.017*SL	0.415 + 0.017*SL
	t_{PHL}	0.487	0.446 + 0.020*SL	0.457 + 0.018*SL	0.464 + 0.017*SL
D to QN	t_R	0.168	0.091 + 0.039*SL	0.094 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.139	0.075 + 0.032*SL	0.077 + 0.031*SL	0.076 + 0.031*SL
	t_{PLH}	0.639	0.593 + 0.023*SL	0.606 + 0.019*SL	0.616 + 0.018*SL
	t_{PHL}	0.637	0.594 + 0.021*SL	0.606 + 0.019*SL	0.616 + 0.017*SL
G to QN	t_R	0.168	0.091 + 0.039*SL	0.094 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.139	0.075 + 0.032*SL	0.079 + 0.031*SL	0.077 + 0.031*SL
	t_{PLH}	0.645	0.600 + 0.023*SL	0.613 + 0.019*SL	0.622 + 0.018*SL
	t_{PHL}	0.646	0.603 + 0.021*SL	0.615 + 0.019*SL	0.625 + 0.017*SL
SN to QN	t_R	0.168	0.091 + 0.039*SL	0.094 + 0.038*SL	0.089 + 0.038*SL
	t_F	0.141	0.077 + 0.032*SL	0.080 + 0.031*SL	0.078 + 0.031*SL
	t_{PLH}	0.256	0.211 + 0.023*SL	0.224 + 0.019*SL	0.233 + 0.018*SL
	t_{PHL}	0.266	0.223 + 0.022*SL	0.235 + 0.019*SL	0.245 + 0.017*SL
RN to QN	t_R	0.169	0.092 + 0.038*SL	0.093 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.139	0.074 + 0.032*SL	0.079 + 0.031*SL	0.076 + 0.031*SL
	t_{PLH}	0.372	0.326 + 0.023*SL	0.340 + 0.019*SL	0.349 + 0.018*SL
	t_{PHL}	0.343	0.300 + 0.021*SL	0.312 + 0.019*SL	0.322 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

D Latch with Active High, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.111	0.075 + 0.018*SL	0.074 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.078 + 0.016*SL	0.075 + 0.017*SL
	t_{PLH}	0.787	0.762 + 0.012*SL	0.773 + 0.010*SL	0.784 + 0.009*SL
	t_{PHL}	0.814	0.786 + 0.014*SL	0.800 + 0.011*SL	0.816 + 0.009*SL
G to Q	t_R	0.110	0.073 + 0.018*SL	0.076 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.078 + 0.016*SL	0.075 + 0.017*SL
	t_{PLH}	0.796	0.772 + 0.012*SL	0.783 + 0.010*SL	0.793 + 0.009*SL
	t_{PHL}	0.820	0.793 + 0.014*SL	0.806 + 0.011*SL	0.822 + 0.009*SL
SN to Q	t_R	0.110	0.074 + 0.018*SL	0.076 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.078 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.413	0.388 + 0.012*SL	0.400 + 0.010*SL	0.410 + 0.009*SL
	t_{PHL}	0.432	0.404 + 0.014*SL	0.417 + 0.011*SL	0.433 + 0.009*SL
RN to Q	t_R	0.109	0.073 + 0.018*SL	0.075 + 0.018*SL	0.064 + 0.019*SL
	t_F	0.108	0.073 + 0.017*SL	0.077 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.491	0.466 + 0.012*SL	0.477 + 0.010*SL	0.488 + 0.009*SL
	t_{PHL}	0.546	0.518 + 0.014*SL	0.532 + 0.011*SL	0.548 + 0.009*SL
D to QN	t_R	0.125	0.083 + 0.021*SL	0.092 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.078 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.642	0.613 + 0.014*SL	0.627 + 0.011*SL	0.646 + 0.009*SL
	t_{PHL}	0.641	0.613 + 0.014*SL	0.626 + 0.011*SL	0.644 + 0.009*SL
G to QN	t_R	0.125	0.083 + 0.021*SL	0.091 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.108	0.073 + 0.017*SL	0.078 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.648	0.619 + 0.014*SL	0.633 + 0.011*SL	0.652 + 0.009*SL
	t_{PHL}	0.651	0.623 + 0.014*SL	0.636 + 0.011*SL	0.654 + 0.009*SL
SN to QN	t_R	0.126	0.086 + 0.020*SL	0.093 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.110	0.074 + 0.018*SL	0.080 + 0.016*SL	0.083 + 0.016*SL
	t_{PLH}	0.259	0.230 + 0.014*SL	0.244 + 0.011*SL	0.263 + 0.009*SL
	t_{PHL}	0.268	0.239 + 0.014*SL	0.253 + 0.011*SL	0.271 + 0.009*SL
RN to QN	t_R	0.126	0.084 + 0.021*SL	0.092 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.107	0.072 + 0.018*SL	0.077 + 0.016*SL	0.081 + 0.016*SL
	t_{PLH}	0.374	0.345 + 0.014*SL	0.359 + 0.011*SL	0.379 + 0.009*SL
	t_{PHL}	0.346	0.317 + 0.014*SL	0.331 + 0.011*SL	0.349 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	GN	Q (n+1)	QN (n+1)
0	0	0	1
1	0	1	0
x	1	Q (n)	QN (n)

Cell Data

Input Load (SL)				Gate Count	
LD5		*LD5D2*		*LD5*	*LD5D2*
D	GN	D	GN		
0.6	0.5	0.6	0.6	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD5	LD5D2
Input Setup Time (D to GN)	t_{SU}	0.303	0.322
Input Hold Time (D to GN)	t_{HD}	0.016	0.000
Pulse Width Low (GN)	t_{PWL}	0.386	0.413

LD5/LD5D2

D Latch with Active Low, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD5

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.144	0.071 + 0.037*SL	0.064 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.132	0.067 + 0.033*SL	0.064 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.503	0.465 + 0.019*SL	0.471 + 0.018*SL	0.473 + 0.017*SL
	t_{PHL}	0.537	0.496 + 0.021*SL	0.505 + 0.018*SL	0.509 + 0.018*SL
GN to Q	t_R	0.145	0.071 + 0.037*SL	0.066 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.133	0.067 + 0.033*SL	0.066 + 0.033*SL	0.059 + 0.034*SL
	t_{PLH}	0.593	0.554 + 0.019*SL	0.561 + 0.018*SL	0.562 + 0.017*SL
	t_{PHL}	0.666	0.625 + 0.021*SL	0.634 + 0.018*SL	0.638 + 0.018*SL
D to QN	t_R	0.157	0.083 + 0.037*SL	0.080 + 0.038*SL	0.073 + 0.038*SL
	t_F	0.144	0.076 + 0.034*SL	0.080 + 0.033*SL	0.076 + 0.034*SL
	t_{PLH}	0.435	0.394 + 0.020*SL	0.403 + 0.018*SL	0.408 + 0.018*SL
	t_{PHL}	0.424	0.379 + 0.022*SL	0.391 + 0.019*SL	0.401 + 0.018*SL
GN to QN	t_R	0.157	0.084 + 0.037*SL	0.080 + 0.038*SL	0.073 + 0.038*SL
	t_F	0.144	0.076 + 0.034*SL	0.081 + 0.033*SL	0.075 + 0.034*SL
	t_{PLH}	0.564	0.523 + 0.020*SL	0.532 + 0.018*SL	0.537 + 0.018*SL
	t_{PHL}	0.514	0.469 + 0.022*SL	0.481 + 0.019*SL	0.491 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD5D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.107	0.071 + 0.018*SL	0.071 + 0.018*SL	0.061 + 0.019*SL
	t_F	0.099	0.064 + 0.017*SL	0.069 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.552	0.528 + 0.012*SL	0.539 + 0.010*SL	0.547 + 0.009*SL
	t_{PHL}	0.586	0.559 + 0.013*SL	0.571 + 0.010*SL	0.585 + 0.009*SL
GN to Q	t_R	0.107	0.070 + 0.018*SL	0.070 + 0.018*SL	0.060 + 0.019*SL
	t_F	0.099	0.064 + 0.018*SL	0.070 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.640	0.616 + 0.012*SL	0.626 + 0.010*SL	0.635 + 0.009*SL
	t_{PHL}	0.705	0.678 + 0.013*SL	0.690 + 0.010*SL	0.703 + 0.009*SL
D to QN	t_R	0.115	0.078 + 0.018*SL	0.078 + 0.018*SL	0.071 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.076 + 0.017*SL	0.076 + 0.017*SL
	t_{PLH}	0.442	0.417 + 0.013*SL	0.429 + 0.010*SL	0.440 + 0.009*SL
	t_{PHL}	0.425	0.397 + 0.014*SL	0.410 + 0.011*SL	0.426 + 0.009*SL
GN to QN	t_R	0.115	0.078 + 0.019*SL	0.079 + 0.018*SL	0.072 + 0.019*SL
	t_F	0.106	0.070 + 0.018*SL	0.076 + 0.017*SL	0.076 + 0.017*SL
	t_{PLH}	0.561	0.535 + 0.013*SL	0.547 + 0.010*SL	0.559 + 0.009*SL
	t_{PHL}	0.512	0.484 + 0.014*SL	0.498 + 0.011*SL	0.514 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	GN	Q (n+1)
0	0	0
1	0	1
x	1	Q (n)

Cell Data

Input Load (SL)				Gate Count	
LD5Q		*LD5QD2*		*LD5Q*	*LD5QD2*
D	GN	D	GN		
0.6	0.6	0.6	0.6	3.33	3.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD5Q	LD5QD2
Input Setup Time (D to GN)	t_{SU}	0.288	0.290
Input Hold Time (D to GN)	t_{HD}	0.038	0.034
Pulse Width Low (GN)	t_{PWL}	0.363	0.365

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD5Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.143	0.069 + 0.037*SL	0.063 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.130	0.065 + 0.033*SL	0.063 + 0.033*SL	0.058 + 0.034*SL
	t_{PLH}	0.456	0.418 + 0.019*SL	0.424 + 0.018*SL	0.425 + 0.017*SL
	t_{PHL}	0.489	0.448 + 0.020*SL	0.456 + 0.018*SL	0.460 + 0.018*SL
GN to Q	t_R	0.141	0.067 + 0.037*SL	0.063 + 0.038*SL	0.058 + 0.039*SL
	t_F	0.130	0.065 + 0.032*SL	0.062 + 0.033*SL	0.057 + 0.034*SL
	t_{PLH}	0.547	0.509 + 0.019*SL	0.514 + 0.018*SL	0.515 + 0.017*SL
	t_{PHL}	0.610	0.570 + 0.020*SL	0.578 + 0.018*SL	0.582 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD5QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.102	0.065 + 0.019*SL	0.065 + 0.018*SL	0.056 + 0.019*SL
	t_F	0.096	0.062 + 0.017*SL	0.065 + 0.016*SL	0.061 + 0.017*SL
	t_{PLH}	0.455	0.431 + 0.012*SL	0.441 + 0.009*SL	0.448 + 0.009*SL
	t_{PHL}	0.489	0.463 + 0.013*SL	0.474 + 0.010*SL	0.487 + 0.009*SL
GN to Q	t_R	0.101	0.065 + 0.018*SL	0.063 + 0.019*SL	0.056 + 0.019*SL
	t_F	0.095	0.060 + 0.018*SL	0.064 + 0.016*SL	0.062 + 0.017*SL
	t_{PLH}	0.541	0.518 + 0.012*SL	0.527 + 0.009*SL	0.535 + 0.009*SL
	t_{PHL}	0.608	0.582 + 0.013*SL	0.594 + 0.010*SL	0.606 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	GN	RN	Q (n+1)	QN (n+1)
0	0	1	0	1
1	0	1	1	0
x	1	1	Q (n)	QN (n)
x	x	0	0	1

Cell Data

Input Load (SL)						Gate Count	
LD6			*LD6D2*			*LD6*	*LD6D2*
D	GN	RN	D	GN	RN		
0.6	0.6	0.8	0.6	0.6	0.8	4.67	5.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD6	LD6D2
Input Setup Time (D to GN)	t_{SU}	0.402	0.421
Input Hold Time (D to GN)	t_{HD}	0.000	0.000
Pulse Width Low (GN)	t_{PWL}	0.403	0.443
Pulse Width Low (RN)	t_{PWL}	0.334	0.385
Recovery Time (RN to GN)	t_{RC}	0.029	0.071
Removal Time (RN to GN)	t_{RM}	0.251	0.208

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.173	0.097 + 0.038*SL	0.099 + 0.038*SL	0.094 + 0.038*SL
	t_F	0.145	0.078 + 0.034*SL	0.081 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.547	0.501 + 0.023*SL	0.514 + 0.020*SL	0.525 + 0.018*SL
	t_{PHL}	0.533	0.488 + 0.022*SL	0.500 + 0.019*SL	0.511 + 0.018*SL
GN to Q	t_R	0.173	0.096 + 0.038*SL	0.099 + 0.038*SL	0.095 + 0.038*SL
	t_F	0.146	0.078 + 0.034*SL	0.083 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.607	0.561 + 0.023*SL	0.575 + 0.020*SL	0.585 + 0.018*SL
	t_{PHL}	0.529	0.484 + 0.022*SL	0.497 + 0.019*SL	0.507 + 0.018*SL
RN to Q	t_R	0.168	0.090 + 0.039*SL	0.094 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.145	0.077 + 0.034*SL	0.082 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.253	0.208 + 0.023*SL	0.221 + 0.019*SL	0.231 + 0.018*SL
	t_{PHL}	0.265	0.220 + 0.022*SL	0.232 + 0.019*SL	0.242 + 0.018*SL
D to QN	t_R	0.146	0.073 + 0.036*SL	0.068 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.135	0.070 + 0.033*SL	0.068 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.618	0.580 + 0.019*SL	0.586 + 0.018*SL	0.588 + 0.017*SL
	t_{PHL}	0.654	0.612 + 0.021*SL	0.622 + 0.018*SL	0.628 + 0.018*SL
GN to QN	t_R	0.145	0.072 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.135	0.071 + 0.032*SL	0.068 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.614	0.576 + 0.019*SL	0.583 + 0.018*SL	0.584 + 0.017*SL
	t_{PHL}	0.714	0.672 + 0.021*SL	0.683 + 0.018*SL	0.688 + 0.018*SL
RN to QN	t_R	0.145	0.072 + 0.036*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.135	0.070 + 0.032*SL	0.067 + 0.033*SL	0.062 + 0.034*SL
	t_{PLH}	0.350	0.311 + 0.019*SL	0.318 + 0.018*SL	0.320 + 0.017*SL
	t_{PHL}	0.360	0.318 + 0.021*SL	0.328 + 0.018*SL	0.334 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD6D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.131	0.090 + 0.020*SL	0.096 + 0.019*SL	0.097 + 0.019*SL
	t_F	0.109	0.072 + 0.019*SL	0.080 + 0.017*SL	0.082 + 0.017*SL
	t_{PLH}	0.552	0.523 + 0.015*SL	0.537 + 0.011*SL	0.557 + 0.009*SL
	t_{PHL}	0.534	0.506 + 0.014*SL	0.519 + 0.011*SL	0.537 + 0.009*SL
GN to Q	t_R	0.130	0.089 + 0.021*SL	0.096 + 0.019*SL	0.097 + 0.019*SL
	t_F	0.110	0.074 + 0.018*SL	0.079 + 0.017*SL	0.082 + 0.017*SL
	t_{PLH}	0.613	0.584 + 0.015*SL	0.598 + 0.011*SL	0.617 + 0.009*SL
	t_{PHL}	0.530	0.501 + 0.014*SL	0.515 + 0.011*SL	0.533 + 0.009*SL
RN to Q	t_R	0.126	0.085 + 0.021*SL	0.091 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.108	0.071 + 0.018*SL	0.078 + 0.017*SL	0.079 + 0.017*SL
	t_{PLH}	0.255	0.226 + 0.014*SL	0.240 + 0.011*SL	0.259 + 0.009*SL
	t_{PHL}	0.261	0.232 + 0.014*SL	0.246 + 0.011*SL	0.263 + 0.009*SL
D to QN	t_R	0.108	0.072 + 0.018*SL	0.070 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.017*SL
	t_{PLH}	0.668	0.644 + 0.012*SL	0.654 + 0.010*SL	0.663 + 0.009*SL
	t_{PHL}	0.714	0.687 + 0.014*SL	0.700 + 0.010*SL	0.715 + 0.009*SL
GN to QN	t_R	0.108	0.072 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.075 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.664	0.639 + 0.012*SL	0.650 + 0.010*SL	0.659 + 0.009*SL
	t_{PHL}	0.775	0.748 + 0.014*SL	0.760 + 0.010*SL	0.775 + 0.009*SL
RN to QN	t_R	0.108	0.071 + 0.018*SL	0.072 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.104	0.069 + 0.018*SL	0.074 + 0.016*SL	0.071 + 0.017*SL
	t_{PLH}	0.394	0.370 + 0.012*SL	0.380 + 0.010*SL	0.389 + 0.009*SL
	t_{PHL}	0.415	0.388 + 0.014*SL	0.401 + 0.010*SL	0.416 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD6Q/LD6QD2

D Latch with Active Low, Reset, Q Output Only, 1X/2X Drive

Logic Symbol



Truth Table

D	GN	RN	Q (n+1)
0	0	1	0
1	0	1	1
x	1	1	Q (n)
x	x	0	0

Cell Data

Input Load (SL)						Gate Count	
LD6Q			*LD6QD2*			*LD6Q*	*LD6QD2*
D	GN	RN	D	GN	RN		
0.6	0.6	0.8	0.6	0.6	0.8	4.00	4.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C,1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD6Q	LD6QD2
Input Setup Time (D to GN)	t_{SU}	0.295	0.298
Input Hold Time (D to GN)	t_{HD}	0.033	0.029
Pulse Width Low (GN)	t_{PWL}	0.372	0.373
Pulse Width Low (RN)	t_{PWL}	0.345	0.375
Recovery Time (RN to GN)	t_{RC}	0.000	0.000
Removal Time (RN to GN)	t_{RM}	0.457	0.435

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD6Q

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.163	0.089 + 0.037*SL	0.088 + 0.037*SL	0.082 + 0.038*SL
	t_F	0.132	0.070 + 0.031*SL	0.069 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.512	0.469 + 0.021*SL	0.480 + 0.019*SL	0.487 + 0.018*SL
	t_{PHL}	0.513	0.473 + 0.020*SL	0.483 + 0.018*SL	0.489 + 0.017*SL
GN to Q	t_R	0.162	0.088 + 0.037*SL	0.086 + 0.038*SL	0.081 + 0.038*SL
	t_F	0.132	0.070 + 0.031*SL	0.069 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.603	0.561 + 0.021*SL	0.572 + 0.018*SL	0.579 + 0.018*SL
	t_{PHL}	0.636	0.596 + 0.020*SL	0.606 + 0.018*SL	0.612 + 0.017*SL
RN to Q	t_R	0.164	0.089 + 0.037*SL	0.090 + 0.037*SL	0.082 + 0.038*SL
	t_F	0.136	0.075 + 0.031*SL	0.073 + 0.031*SL	0.069 + 0.032*SL
	t_{PLH}	0.244	0.201 + 0.021*SL	0.213 + 0.019*SL	0.220 + 0.018*SL
	t_{PHL}	0.251	0.210 + 0.020*SL	0.220 + 0.018*SL	0.227 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LD6QD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.122	0.082 + 0.020*SL	0.087 + 0.019*SL	0.087 + 0.019*SL
	t_F	0.100	0.066 + 0.017*SL	0.072 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.517	0.489 + 0.014*SL	0.502 + 0.011*SL	0.520 + 0.009*SL
	t_{PHL}	0.513	0.487 + 0.013*SL	0.499 + 0.010*SL	0.515 + 0.009*SL
GN to Q	t_R	0.123	0.083 + 0.020*SL	0.088 + 0.019*SL	0.085 + 0.019*SL
	t_F	0.099	0.065 + 0.017*SL	0.071 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.606	0.578 + 0.014*SL	0.592 + 0.011*SL	0.609 + 0.009*SL
	t_{PHL}	0.634	0.608 + 0.013*SL	0.620 + 0.010*SL	0.636 + 0.009*SL
RN to Q	t_R	0.123	0.083 + 0.020*SL	0.089 + 0.019*SL	0.087 + 0.019*SL
	t_F	0.104	0.070 + 0.017*SL	0.076 + 0.015*SL	0.075 + 0.016*SL
	t_{PLH}	0.249	0.222 + 0.014*SL	0.235 + 0.011*SL	0.252 + 0.009*SL
	t_{PHL}	0.250	0.224 + 0.013*SL	0.236 + 0.010*SL	0.252 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LD7/LD7D2

D Latch with Active Low, Set, 1X/2X Drive

Logic Symbol



Truth Table

D	GN	SN	Q (n+1)	QN (n+1)
0	0	1	0	1
1	0	1	1	0
x	1	1	Q (n)	QN (n)
x	x	0	1	0

Cell Data

Input Load (SL)						Gate Count	
LD7			*LD7D2*			*LD7*	*LD7D2*
D	GN	SN	D	GN	SN		
0.6	0.6	0.8	0.6	0.6	0.8	4.33	4.67

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD7	LD7D2
Input Setup Time (D to GN)	t_{SU}	0.312	0.331
Input Hold Time (D to GN)	t_{HD}	0.000	0.000
Pulse Width Low (GN)	t_{PWL}	0.406	0.446
Pulse Width Low (SN)	t_{PWL}	0.333	0.388
Recovery Time (SN to GN)	t_{RC}	0.037	0.083
Removal Time (SN to GN)	t_{RM}	0.243	0.197

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD7

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.146	0.073 + 0.036*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.136	0.072 + 0.032*SL	0.068 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.522	0.483 + 0.019*SL	0.490 + 0.018*SL	0.491 + 0.017*SL
	t_{PHL}	0.595	0.553 + 0.021*SL	0.563 + 0.018*SL	0.568 + 0.018*SL
GN to Q	t_R	0.145	0.072 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.136	0.072 + 0.032*SL	0.068 + 0.033*SL	0.064 + 0.034*SL
	t_{PLH}	0.606	0.567 + 0.019*SL	0.574 + 0.018*SL	0.576 + 0.017*SL
	t_{PHL}	0.716	0.674 + 0.021*SL	0.684 + 0.018*SL	0.690 + 0.018*SL
SN to Q	t_R	0.145	0.071 + 0.037*SL	0.067 + 0.038*SL	0.060 + 0.039*SL
	t_F	0.136	0.071 + 0.032*SL	0.070 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.349	0.310 + 0.019*SL	0.317 + 0.018*SL	0.319 + 0.017*SL
	t_{PHL}	0.365	0.323 + 0.021*SL	0.333 + 0.018*SL	0.338 + 0.018*SL
D to QN	t_R	0.173	0.097 + 0.038*SL	0.100 + 0.037*SL	0.096 + 0.038*SL
	t_F	0.145	0.077 + 0.034*SL	0.082 + 0.033*SL	0.078 + 0.033*SL
	t_{PLH}	0.485	0.439 + 0.023*SL	0.453 + 0.019*SL	0.464 + 0.018*SL
	t_{PHL}	0.438	0.393 + 0.022*SL	0.405 + 0.019*SL	0.415 + 0.018*SL
GN to QN	t_R	0.174	0.097 + 0.038*SL	0.100 + 0.037*SL	0.096 + 0.038*SL
	t_F	0.145	0.078 + 0.034*SL	0.083 + 0.032*SL	0.077 + 0.033*SL
	t_{PLH}	0.606	0.561 + 0.023*SL	0.574 + 0.019*SL	0.585 + 0.018*SL
	t_{PHL}	0.522	0.477 + 0.022*SL	0.490 + 0.019*SL	0.499 + 0.018*SL
SN to QN	t_R	0.168	0.092 + 0.038*SL	0.094 + 0.038*SL	0.091 + 0.038*SL
	t_F	0.145	0.078 + 0.034*SL	0.083 + 0.033*SL	0.077 + 0.033*SL
	t_{PLH}	0.256	0.211 + 0.023*SL	0.224 + 0.019*SL	0.233 + 0.018*SL
	t_{PHL}	0.264	0.220 + 0.022*SL	0.232 + 0.019*SL	0.241 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

D Latch with Active Low, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD7D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.109	0.073 + 0.018*SL	0.072 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.074 + 0.016*SL	0.070 + 0.016*SL
	t_{PLH}	0.573	0.549 + 0.012*SL	0.560 + 0.010*SL	0.568 + 0.009*SL
	t_{PHL}	0.650	0.624 + 0.013*SL	0.636 + 0.010*SL	0.650 + 0.009*SL
GN to Q	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.105	0.070 + 0.017*SL	0.075 + 0.016*SL	0.071 + 0.016*SL
	t_{PLH}	0.662	0.638 + 0.012*SL	0.649 + 0.010*SL	0.657 + 0.009*SL
	t_{PHL}	0.770	0.743 + 0.014*SL	0.756 + 0.010*SL	0.770 + 0.009*SL
SN to Q	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.103	0.068 + 0.018*SL	0.074 + 0.016*SL	0.070 + 0.017*SL
	t_{PLH}	0.399	0.375 + 0.012*SL	0.385 + 0.010*SL	0.394 + 0.009*SL
	t_{PHL}	0.416	0.390 + 0.013*SL	0.402 + 0.010*SL	0.416 + 0.009*SL
D to QN	t_R	0.131	0.090 + 0.021*SL	0.097 + 0.019*SL	0.098 + 0.019*SL
	t_F	0.109	0.073 + 0.018*SL	0.079 + 0.017*SL	0.081 + 0.016*SL
	t_{PLH}	0.491	0.462 + 0.015*SL	0.476 + 0.011*SL	0.496 + 0.009*SL
	t_{PHL}	0.441	0.413 + 0.014*SL	0.426 + 0.011*SL	0.444 + 0.009*SL
GN to QN	t_R	0.132	0.091 + 0.020*SL	0.097 + 0.019*SL	0.099 + 0.019*SL
	t_F	0.110	0.074 + 0.018*SL	0.080 + 0.017*SL	0.081 + 0.016*SL
	t_{PLH}	0.610	0.581 + 0.015*SL	0.595 + 0.011*SL	0.615 + 0.009*SL
	t_{PHL}	0.530	0.502 + 0.014*SL	0.515 + 0.011*SL	0.533 + 0.009*SL
SN to QN	t_R	0.127	0.086 + 0.020*SL	0.093 + 0.019*SL	0.092 + 0.019*SL
	t_F	0.110	0.074 + 0.018*SL	0.079 + 0.017*SL	0.082 + 0.016*SL
	t_{PLH}	0.258	0.229 + 0.014*SL	0.243 + 0.011*SL	0.262 + 0.009*SL
	t_{PHL}	0.266	0.238 + 0.014*SL	0.251 + 0.011*SL	0.269 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

D	GN	RN	SN	Q (n+1)	QN (n+1)
0	0	1	1	0	1
1	0	1	1	1	0
x	1	1	1	Q (n)	QN (n)
x	x	1	0	1	0
x	x	0	1	0	1
x	x	0	0	1	0

Cell Data

Input Load (SL)								Gate Count	
LD8				*LD8D2*				*LD8*	*LD8D2*
D	GN	SN	RN	D	GN	SN	RN		
0.6	0.5	0.8	0.8	0.6	0.5	0.8	0.8	6.00	6.33

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LD8	LD8D2
Input Setup Time (D to GN)	t_{SU}	0.417	0.442
Input Hold Time (D to GN)	t_{HD}	0.000	0.000
Pulse Width Low (GN)	t_{PWL}	0.452	0.490
Pulse Width Low (SN)	t_{PWL}	0.721	0.741
Recovery Time (SN to GN)	t_{RC}	0.000	0.000
Removal Time (SN to GN)	t_{RM}	0.505	0.444
Pulse Width Low (RN)	t_{PWL}	0.417	0.487
Recovery Time (RN to GN)	t_{RC}	0.081	0.127
Removal Time (RN to GN)	t_{RM}	0.211	0.165
Recovery Time (SN to RN)	t_{RC}	0.325	0.393
Removal Time (SN to RN)	t_{RM}	0.000	0.000

D Latch with Active Low, Reset, Set, 1X/2X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.147	0.076 + 0.035*SL	0.070 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.134	0.072 + 0.031*SL	0.073 + 0.031*SL	0.067 + 0.032*SL
	t_{PLH}	0.739	0.701 + 0.019*SL	0.708 + 0.017*SL	0.711 + 0.017*SL
	t_{PHL}	0.756	0.715 + 0.021*SL	0.726 + 0.018*SL	0.732 + 0.017*SL
GN to Q	t_R	0.146	0.074 + 0.036*SL	0.070 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.133	0.071 + 0.031*SL	0.071 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.791	0.753 + 0.019*SL	0.761 + 0.017*SL	0.763 + 0.017*SL
	t_{PHL}	0.741	0.700 + 0.020*SL	0.711 + 0.018*SL	0.718 + 0.017*SL
SN to Q	t_R	0.147	0.077 + 0.035*SL	0.070 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.134	0.073 + 0.031*SL	0.072 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.366	0.328 + 0.019*SL	0.335 + 0.017*SL	0.338 + 0.017*SL
	t_{PHL}	0.372	0.331 + 0.020*SL	0.343 + 0.018*SL	0.349 + 0.017*SL
RN to Q	t_R	0.146	0.075 + 0.036*SL	0.068 + 0.037*SL	0.063 + 0.038*SL
	t_F	0.133	0.072 + 0.031*SL	0.071 + 0.031*SL	0.065 + 0.032*SL
	t_{PLH}	0.443	0.405 + 0.019*SL	0.413 + 0.017*SL	0.415 + 0.017*SL
	t_{PHL}	0.487	0.446 + 0.020*SL	0.457 + 0.018*SL	0.464 + 0.017*SL
D to QN	t_R	0.168	0.091 + 0.038*SL	0.094 + 0.038*SL	0.091 + 0.038*SL
	t_F	0.139	0.075 + 0.032*SL	0.078 + 0.031*SL	0.076 + 0.031*SL
	t_{PLH}	0.639	0.594 + 0.023*SL	0.607 + 0.019*SL	0.617 + 0.018*SL
	t_{PHL}	0.639	0.596 + 0.021*SL	0.608 + 0.019*SL	0.618 + 0.017*SL
GN to QN	t_R	0.168	0.092 + 0.038*SL	0.094 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.140	0.075 + 0.032*SL	0.080 + 0.031*SL	0.077 + 0.031*SL
	t_{PLH}	0.625	0.580 + 0.022*SL	0.593 + 0.019*SL	0.602 + 0.018*SL
	t_{PHL}	0.691	0.648 + 0.021*SL	0.660 + 0.019*SL	0.670 + 0.017*SL
SN to QN	t_R	0.167	0.091 + 0.038*SL	0.094 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.141	0.078 + 0.032*SL	0.080 + 0.031*SL	0.078 + 0.031*SL
	t_{PLH}	0.256	0.211 + 0.022*SL	0.224 + 0.019*SL	0.233 + 0.018*SL
	t_{PHL}	0.266	0.223 + 0.022*SL	0.236 + 0.019*SL	0.245 + 0.017*SL
RN to QN	t_R	0.168	0.092 + 0.038*SL	0.093 + 0.038*SL	0.090 + 0.038*SL
	t_F	0.139	0.075 + 0.032*SL	0.079 + 0.031*SL	0.076 + 0.031*SL
	t_{PLH}	0.371	0.326 + 0.023*SL	0.339 + 0.019*SL	0.348 + 0.018*SL
	t_{PHL}	0.343	0.300 + 0.021*SL	0.312 + 0.019*SL	0.322 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LD8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D to Q	t_R	0.110	0.075 + 0.018*SL	0.073 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.078 + 0.016*SL	0.075 + 0.017*SL
	t_{PLH}	0.785	0.760 + 0.012*SL	0.771 + 0.010*SL	0.781 + 0.009*SL
	t_{PHL}	0.818	0.790 + 0.014*SL	0.804 + 0.011*SL	0.820 + 0.009*SL
GN to Q	t_R	0.111	0.074 + 0.018*SL	0.076 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.079 + 0.016*SL	0.075 + 0.017*SL
	t_{PLH}	0.837	0.812 + 0.012*SL	0.823 + 0.010*SL	0.833 + 0.009*SL
	t_{PHL}	0.804	0.776 + 0.014*SL	0.789 + 0.011*SL	0.805 + 0.009*SL
SN to Q	t_R	0.111	0.074 + 0.018*SL	0.076 + 0.018*SL	0.065 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.079 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.415	0.390 + 0.012*SL	0.402 + 0.010*SL	0.412 + 0.009*SL
	t_{PHL}	0.434	0.407 + 0.014*SL	0.420 + 0.011*SL	0.436 + 0.009*SL
RN to Q	t_R	0.110	0.075 + 0.018*SL	0.074 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.107	0.072 + 0.018*SL	0.078 + 0.016*SL	0.074 + 0.017*SL
	t_{PLH}	0.488	0.463 + 0.012*SL	0.474 + 0.010*SL	0.484 + 0.009*SL
	t_{PHL}	0.549	0.522 + 0.014*SL	0.535 + 0.011*SL	0.551 + 0.009*SL
D to QN	t_R	0.126	0.085 + 0.021*SL	0.092 + 0.019*SL	0.095 + 0.019*SL
	t_F	0.108	0.072 + 0.018*SL	0.078 + 0.016*SL	0.080 + 0.016*SL
	t_{PLH}	0.645	0.616 + 0.014*SL	0.630 + 0.011*SL	0.650 + 0.009*SL
	t_{PHL}	0.640	0.611 + 0.014*SL	0.625 + 0.011*SL	0.643 + 0.009*SL
GN to QN	t_R	0.127	0.086 + 0.020*SL	0.093 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.107	0.072 + 0.018*SL	0.077 + 0.017*SL	0.081 + 0.016*SL
	t_{PLH}	0.630	0.601 + 0.014*SL	0.616 + 0.011*SL	0.635 + 0.009*SL
	t_{PHL}	0.692	0.663 + 0.014*SL	0.677 + 0.011*SL	0.695 + 0.009*SL
SN to QN	t_R	0.127	0.086 + 0.020*SL	0.093 + 0.019*SL	0.093 + 0.019*SL
	t_F	0.111	0.075 + 0.018*SL	0.081 + 0.016*SL	0.083 + 0.016*SL
	t_{PLH}	0.260	0.232 + 0.014*SL	0.246 + 0.011*SL	0.265 + 0.009*SL
	t_{PHL}	0.270	0.241 + 0.014*SL	0.255 + 0.011*SL	0.273 + 0.009*SL
RN to QN	t_R	0.126	0.085 + 0.021*SL	0.093 + 0.019*SL	0.094 + 0.019*SL
	t_F	0.107	0.071 + 0.018*SL	0.076 + 0.017*SL	0.080 + 0.016*SL
	t_{PLH}	0.376	0.347 + 0.014*SL	0.361 + 0.011*SL	0.381 + 0.009*SL
	t_{PHL}	0.344	0.315 + 0.014*SL	0.329 + 0.011*SL	0.347 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LS0/LS0D2

SR Latch with 1X/2X Drive

Logic Symbol



Truth Table

RN	SN	Q (n+1)	QN (n+1)
0	0	*	*
1	0	1	0
0	1	0	1
1	1	Q (n)	QN (n)

* Both Q and QN outputs will remain high during RN and SN are low. However, if RN and SN go high simultaneously, the output states are unpredictable.

Cell Data

Input Load (SL)				Gate Count	
LS0		*LS0D2*		*LS0*	*LS0D2*
RN	SN	RN	SN		
1.1	1.1	2.2	2.2	1.67	3.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 2.5V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LS0	LS0D2
Pulse Width Low (SN)	t_{PWL}	0.314	0.275
Removal Time (SN to RN)	t_{RM}	0.047	0.089
Recovery Time (Sn to RN)	t_{RC}	0.231	0.191
Pulse Width Low (RN)	t_{PWL}	0.315	0.274

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LS0

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN to Q	t_R	0.221	0.165 + 0.028*SL	0.171 + 0.027*SL	0.171 + 0.027*SL
	t_F	0.229	0.156 + 0.036*SL	0.149 + 0.038*SL	0.138 + 0.040*SL
	t_{PLH}	0.151	0.112 + 0.019*SL	0.119 + 0.017*SL	0.119 + 0.018*SL
	t_{PHL}	0.152	0.109 + 0.021*SL	0.115 + 0.020*SL	0.115 + 0.020*SL
RN to Q	t_F	0.203	0.124 + 0.039*SL	0.119 + 0.041*SL	0.118 + 0.041*SL
	t_{PHL}	0.241	0.199 + 0.021*SL	0.202 + 0.020*SL	0.204 + 0.020*SL
SN to QN	t_F	0.203	0.124 + 0.040*SL	0.119 + 0.041*SL	0.118 + 0.041*SL
	t_{PHL}	0.241	0.200 + 0.021*SL	0.202 + 0.020*SL	0.204 + 0.020*SL
RN to QN	t_R	0.221	0.165 + 0.028*SL	0.171 + 0.027*SL	0.171 + 0.027*SL
	t_F	0.229	0.157 + 0.036*SL	0.149 + 0.038*SL	0.139 + 0.040*SL
	t_{PLH}	0.151	0.112 + 0.019*SL	0.119 + 0.017*SL	0.119 + 0.018*SL
	t_{PHL}	0.152	0.109 + 0.021*SL	0.115 + 0.020*SL	0.115 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

LS0D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN to Q	t_R	0.191	0.162 + 0.015*SL	0.166 + 0.014*SL	0.170 + 0.013*SL
	t_F	0.191	0.155 + 0.018*SL	0.151 + 0.019*SL	0.139 + 0.020*SL
	t_{PLH}	0.129	0.107 + 0.011*SL	0.115 + 0.009*SL	0.118 + 0.009*SL
	t_{PHL}	0.129	0.104 + 0.012*SL	0.112 + 0.010*SL	0.114 + 0.010*SL
RN to Q	t_F	0.160	0.121 + 0.020*SL	0.119 + 0.020*SL	0.115 + 0.020*SL
	t_{PHL}	0.216	0.195 + 0.011*SL	0.197 + 0.010*SL	0.200 + 0.010*SL
SN to QN	t_F	0.160	0.121 + 0.020*SL	0.119 + 0.020*SL	0.114 + 0.020*SL
	t_{PHL}	0.217	0.195 + 0.011*SL	0.197 + 0.010*SL	0.200 + 0.010*SL
RN to QN	t_R	0.191	0.161 + 0.015*SL	0.166 + 0.014*SL	0.170 + 0.013*SL
	t_F	0.190	0.155 + 0.018*SL	0.151 + 0.019*SL	0.138 + 0.020*SL
	t_{PLH}	0.129	0.107 + 0.011*SL	0.115 + 0.009*SL	0.117 + 0.009*SL
	t_{PHL}	0.128	0.104 + 0.012*SL	0.112 + 0.010*SL	0.114 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

LS1/LS1D2

SR Latch with Separate Inputs, 1X/2X Drive

Logic Symbol



Truth Table

RN	SN	RN*	SN*	Q (n+1)	QN (n+1)
0	0	x	x	*	*
x	0	0	x	*	*
x	x	0	0	*	*
0	x	x	0	*	*
1	0	1	x	1	0
0	1	x	1	0	1
1	x	1	0	1	0
x	1	0	1	0	1
1	1	1	1	Q (n)	QN (n)

RN* = RN1 + RN2, SN* = SN1 + SN2

* Both Q and QN outputs will be unknown when RN (RN*) and SN (SN*) are low.

Cell Data

Input Load (SL)												Gate Count	
LS1						*LS1D2*						*LS1*	*LS1*D2
SN1	SN2	SN	RN1	RN2	RN	SN1	SN2	SN	RN1	RN2	RN		
1.0	1.0	1.1	1.0	1.0	1.1	1.0	1.0	1.1	1.0	1.0	1.1	3.00	5.00

Schematic Diagram



Timing Requirements

(Typical process, 25°C, 1.8V, Unit = ns)

Parameter	Symbol	Value (ns)	
		LS1	LS1D2
Pulse Width Low (SN1)	t_{PWL}	0.551	0.463
Removal Time (SN1 to RN1)	t_{RM}	0.008	0.135
Recovery Time (SN1 to RN1)	t_{RC}	0.271	0.145
Removal Time (SN1 to RN2)	t_{RM}	0.043	0.167
Recovery Time (SN1 to RN2)	t_{RC}	0.237	0.112
Removal Time (SN1 to RN)	t_{RM}	0.032	0.152
Recovery Time (SN1 to RN)	t_{RC}	0.245	0.128
Pulse Width Low (SN2)	t_{PWL}	0.557	0.464
Removal Time (SN2 to RN1)	t_{RM}	0.000	0.103
Recovery Time (SN2 to RN1)	t_{RC}	0.300	0.177
Removal Time (SN2 to RN2)	t_{RM}	0.014	0.136
Recovery Time (SN2 to RN2)	t_{RC}	0.265	0.144
Removal Time (SN2 to RN)	t_{RM}	0.007	0.121
Recovery Time (SN2 to RN)	t_{RC}	0.274	0.159
Pulse Width Low (SN)	t_{PWL}	0.404	0.356
Removal Time (SN to RN1)	t_{RM}	0.000	0.000
Recovery Time (SN to RN1)	t_{RC}	0.293	0.168
Removal Time (SN to RN2)	t_{RM}	0.028	0.148
Recovery Time (SN to RN2)	t_{RC}	0.257	0.138
Removal Time (SN to RN)	t_{RM}	0.019	0.133
Recovery Time (SN to RN)	t_{RC}	0.264	0.153
Pulse Width Low (RN1)	t_{PWL}	0.551	0.461
Pulse Width Low (RN2)	t_{PWL}	0.557	0.462
Pulse Width Low (RN)	t_{PWL}	0.404	0.357

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LS1

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN1 to Q	t_R	0.412	0.309 + 0.051*SL	0.317 + 0.049*SL	0.322 + 0.049*SL
	t_F	0.413	0.273 + 0.070*SL	0.265 + 0.072*SL	0.255 + 0.073*SL
	t_{PLH}	0.247	0.176 + 0.035*SL	0.176 + 0.035*SL	0.177 + 0.035*SL
	t_{PHL}	0.241	0.171 + 0.035*SL	0.171 + 0.035*SL	0.172 + 0.035*SL
SN2 to Q	t_R	0.422	0.308 + 0.057*SL	0.328 + 0.052*SL	0.345 + 0.049*SL
	t_F	0.459	0.318 + 0.070*SL	0.312 + 0.072*SL	0.302 + 0.073*SL
	t_{PLH}	0.258	0.186 + 0.036*SL	0.187 + 0.036*SL	0.188 + 0.035*SL
	t_{PHL}	0.275	0.204 + 0.035*SL	0.205 + 0.035*SL	0.207 + 0.035*SL
SN to Q	t_R	0.270	0.203 + 0.034*SL	0.217 + 0.030*SL	0.229 + 0.029*SL
	t_F	0.410	0.268 + 0.071*SL	0.264 + 0.072*SL	0.257 + 0.073*SL
	t_{PLH}	0.180	0.145 + 0.018*SL	0.146 + 0.018*SL	0.146 + 0.017*SL
	t_{PHL}	0.263	0.192 + 0.036*SL	0.193 + 0.035*SL	0.194 + 0.035*SL
RN1 to Q	t_F	0.417	0.273 + 0.072*SL	0.270 + 0.073*SL	0.267 + 0.073*SL
	t_{PHL}	0.444	0.370 + 0.037*SL	0.375 + 0.036*SL	0.379 + 0.035*SL
RN2 to Q	t_F	0.462	0.318 + 0.072*SL	0.316 + 0.072*SL	0.312 + 0.073*SL
	t_{PHL}	0.496	0.422 + 0.037*SL	0.427 + 0.036*SL	0.431 + 0.035*SL
RN to Q	t_F	0.405	0.260 + 0.072*SL	0.258 + 0.073*SL	0.256 + 0.073*SL
	t_{PHL}	0.398	0.326 + 0.036*SL	0.329 + 0.035*SL	0.331 + 0.035*SL
SN1 to QN	t_F	0.417	0.273 + 0.072*SL	0.270 + 0.073*SL	0.267 + 0.073*SL
	t_{PHL}	0.444	0.370 + 0.037*SL	0.375 + 0.036*SL	0.379 + 0.035*SL
SN2 to QN	t_F	0.462	0.319 + 0.072*SL	0.316 + 0.072*SL	0.313 + 0.073*SL
	t_{PHL}	0.496	0.422 + 0.037*SL	0.426 + 0.036*SL	0.431 + 0.035*SL
SN to QN	t_F	0.406	0.261 + 0.073*SL	0.258 + 0.073*SL	0.256 + 0.073*SL
	t_{PHL}	0.398	0.326 + 0.036*SL	0.329 + 0.035*SL	0.331 + 0.035*SL
RN1 to QN	t_R	0.412	0.309 + 0.051*SL	0.317 + 0.049*SL	0.322 + 0.049*SL
	t_F	0.413	0.273 + 0.070*SL	0.266 + 0.072*SL	0.255 + 0.073*SL
	t_{PLH}	0.247	0.176 + 0.035*SL	0.176 + 0.035*SL	0.177 + 0.035*SL
	t_{PHL}	0.242	0.171 + 0.035*SL	0.172 + 0.035*SL	0.173 + 0.035*SL
RN2 to QN	t_R	0.422	0.309 + 0.057*SL	0.328 + 0.052*SL	0.345 + 0.049*SL
	t_F	0.459	0.319 + 0.070*SL	0.312 + 0.072*SL	0.303 + 0.073*SL
	t_{PLH}	0.258	0.186 + 0.036*SL	0.188 + 0.036*SL	0.189 + 0.035*SL
	t_{PHL}	0.275	0.204 + 0.035*SL	0.206 + 0.035*SL	0.207 + 0.035*SL
RN to QN	t_R	0.270	0.203 + 0.034*SL	0.217 + 0.030*SL	0.229 + 0.029*SL
	t_F	0.411	0.268 + 0.071*SL	0.264 + 0.072*SL	0.257 + 0.073*SL
	t_{PLH}	0.180	0.145 + 0.018*SL	0.146 + 0.018*SL	0.147 + 0.017*SL
	t_{PHL}	0.263	0.192 + 0.036*SL	0.193 + 0.035*SL	0.195 + 0.035*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

LS1D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
SN1 to Q	t_R	0.114	0.077 + 0.018*SL	0.077 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.107	0.072 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.431	0.407 + 0.012*SL	0.418 + 0.010*SL	0.427 + 0.009*SL
	t_{PHL}	0.446	0.419 + 0.014*SL	0.432 + 0.010*SL	0.446 + 0.009*SL
SN2 to Q	t_R	0.113	0.076 + 0.018*SL	0.077 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.108	0.073 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.441	0.417 + 0.012*SL	0.428 + 0.010*SL	0.437 + 0.009*SL
	t_{PHL}	0.486	0.459 + 0.014*SL	0.472 + 0.010*SL	0.486 + 0.009*SL
SN to Q	t_R	0.106	0.070 + 0.018*SL	0.068 + 0.019*SL	0.062 + 0.019*SL
	t_F	0.107	0.072 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.351	0.327 + 0.012*SL	0.337 + 0.009*SL	0.345 + 0.009*SL
	t_{PHL}	0.467	0.440 + 0.014*SL	0.453 + 0.010*SL	0.467 + 0.009*SL
RN1 to Q	t_F	0.106	0.071 + 0.018*SL	0.076 + 0.016*SL	0.072 + 0.017*SL
	t_{PHL}	0.686	0.658 + 0.014*SL	0.671 + 0.011*SL	0.686 + 0.009*SL
RN2 to Q	t_F	0.108	0.073 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PHL}	0.745	0.717 + 0.014*SL	0.730 + 0.011*SL	0.745 + 0.009*SL
RN to Q	t_F	0.107	0.072 + 0.017*SL	0.076 + 0.016*SL	0.072 + 0.017*SL
	t_{PHL}	0.622	0.594 + 0.014*SL	0.607 + 0.010*SL	0.622 + 0.009*SL
SN1 to QN	t_F	0.107	0.071 + 0.018*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PHL}	0.686	0.658 + 0.014*SL	0.671 + 0.011*SL	0.686 + 0.009*SL
SN2 to QN	t_F	0.108	0.074 + 0.017*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PHL}	0.746	0.719 + 0.014*SL	0.732 + 0.011*SL	0.747 + 0.009*SL
SN to QN	t_F	0.106	0.070 + 0.018*SL	0.077 + 0.016*SL	0.072 + 0.017*SL
	t_{PHL}	0.621	0.593 + 0.014*SL	0.606 + 0.011*SL	0.621 + 0.009*SL
RN1 to QN	t_R	0.113	0.078 + 0.018*SL	0.076 + 0.018*SL	0.068 + 0.019*SL
	t_F	0.106	0.071 + 0.018*SL	0.076 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.426	0.401 + 0.012*SL	0.413 + 0.010*SL	0.422 + 0.009*SL
	t_{PHL}	0.442	0.414 + 0.014*SL	0.427 + 0.010*SL	0.442 + 0.009*SL
RN2 to QN	t_R	0.113	0.077 + 0.018*SL	0.076 + 0.018*SL	0.067 + 0.019*SL
	t_F	0.107	0.072 + 0.018*SL	0.077 + 0.016*SL	0.073 + 0.017*SL
	t_{PLH}	0.437	0.412 + 0.012*SL	0.423 + 0.010*SL	0.432 + 0.009*SL
	t_{PHL}	0.482	0.455 + 0.014*SL	0.468 + 0.011*SL	0.482 + 0.009*SL
RN to QN	t_R	0.105	0.070 + 0.018*SL	0.066 + 0.019*SL	0.062 + 0.019*SL
	t_F	0.106	0.070 + 0.018*SL	0.077 + 0.016*SL	0.072 + 0.017*SL
	t_{PLH}	0.347	0.324 + 0.012*SL	0.333 + 0.010*SL	0.341 + 0.009*SL
	t_{PHL}	0.460	0.433 + 0.014*SL	0.445 + 0.010*SL	0.460 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 11, *Group3 : 11 < SL

Cell List

Cell Name	Function Description
BUSHOLDER	Bus Holder

Logic Symbol



Cell Data

Input Load (SL)	Gate Count
Y	
9.5	1.33

INTERNAL CLOCK DRIVERS

Cell List

Cell Name	Function Description
CK2	Internal Clock Driver CMOS 2mA
CK4	Internal Clock Driver CMOS 4mA
CK6	Internal Clock Driver CMOS 6mA
CK8	Internal Clock Driver CMOS 8mA

Logic Symbol



Truth Table

A	Y
0	0
1	1

Cell Data

Standard Load (SL)				I/O Slot			
CK2	*CK4*	*CK6*	*CK8*	*CK2*	*CK4*	*CK6*	*CK8*
A	A	A	A				
16.001	15.857	30.343	30.203	1.0	1.0	1.0	1.0

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.19ns, SL: Standard Load)

CK2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.084	0.079 + 0.002*SL	0.075 + 0.002*SL	0.075 + 0.002*SL
	t_F	0.076	0.071 + 0.002*SL	0.065 + 0.002*SL	0.062 + 0.002*SL
	t_{PLH}	0.196	0.194 + 0.001*SL	0.194 + 0.001*SL	0.195 + 0.001*SL
	t_{PHL}	0.250	0.247 + 0.001*SL	0.249 + 0.001*SL	0.249 + 0.001*SL

*Group1 : SL < 642, *Group2 : 642 ≦ SL ≦ 963, *Group3 : 963 < SL

CK4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.093	0.091 + 0.001*SL	0.083 + 0.001*SL	0.080 + 0.001*SL
	t_F	0.094	0.091 + 0.001*SL	0.081 + 0.001*SL	0.075 + 0.001*SL
	t_{PLH}	0.252	0.251 + 0.001*SL	0.252 + 0.001*SL	0.252 + 0.001*SL
	t_{PHL}	0.336	0.335 + 0.001*SL	0.337 + 0.001*SL	0.338 + 0.001*SL

*Group1 : SL < 1282, *Group2 : 1282 ≦SL ≦ 1923, *Group3 : 1923 < SL

CK6

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.090	0.088 + 0.001*SL	0.080 + 0.001*SL	0.078 + 0.001*SL
	t_F	0.084	0.082 + 0.001*SL	0.075 + 0.001*SL	0.072 + 0.001*SL
	t_{PLH}	0.245	0.244 + 0.000*SL	0.244 + 0.000*SL	0.245 + 0.000*SL
	t_{PHL}	0.292	0.291 + 0.000*SL	0.292 + 0.000*SL	0.293 + 0.000*SL

*Group1 : SL < 1924, *Group2 : 1924 ≦ SL ≦ 2886, *Group3 : 2886 < SL

CK8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to Y	t_R	0.100	0.099 + 0.001*SL	0.088 + 0.001*SL	0.083 + 0.001*SL
	t_F	0.092	0.091 + 0.001*SL	0.080 + 0.001*SL	0.076 + 0.001*SL
	t_{PLH}	0.283	0.282 + 0.000*SL	0.283 + 0.000*SL	0.284 + 0.000*SL
	t_{PHL}	0.333	0.332 + 0.000*SL	0.334 + 0.000*SL	0.335 + 0.000*SL

*Group1 : SL < 2562, *Group2 : 2562 ≦SL ≦ 3843, *Group3 : 3843 < SL

DECODERS

Cell List

Cell Name	Function Description
DC4	2 > 4 Non-Inverting Decoder
DC4I	2 > 4 Inverting Decoder
DC8I	3 > 8 Inverting Decoder

Logic Symbol



Truth Table

S1	S0	Y0	Y1	Y2	Y3
0	0	1	0	0	0
0	1	0	1	0	0
1	0	0	0	1	0
1	1	0	0	0	1

Cell Data

Input Load (SL)		Gate Count
S0	S1	
2.5	2.4	6.33

Schematic Diagram



DC4

2 > 4 Non-Inverting Decoder

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DC4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to Y0	t_R	0.154	0.081 + 0.037*SL	0.076 + 0.038*SL	0.071 + 0.038*SL
	t_F	0.132	0.067 + 0.033*SL	0.065 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.335	0.294 + 0.021*SL	0.304 + 0.018*SL	0.309 + 0.018*SL
	t_{PHL}	0.314	0.273 + 0.021*SL	0.282 + 0.018*SL	0.287 + 0.018*SL
S1 to Y0	t_R	0.154	0.080 + 0.037*SL	0.076 + 0.038*SL	0.071 + 0.038*SL
	t_F	0.134	0.070 + 0.032*SL	0.066 + 0.033*SL	0.062 + 0.034*SL
	t_{PLH}	0.339	0.298 + 0.021*SL	0.308 + 0.018*SL	0.313 + 0.018*SL
	t_{PHL}	0.336	0.294 + 0.021*SL	0.304 + 0.018*SL	0.309 + 0.018*SL
S0 to Y1	t_R	0.152	0.078 + 0.037*SL	0.075 + 0.038*SL	0.071 + 0.039*SL
	t_F	0.132	0.067 + 0.033*SL	0.064 + 0.033*SL	0.061 + 0.034*SL
	t_{PLH}	0.211	0.170 + 0.020*SL	0.179 + 0.018*SL	0.183 + 0.018*SL
	t_{PHL}	0.220	0.179 + 0.020*SL	0.187 + 0.018*SL	0.192 + 0.018*SL
S1 to Y1	t_R	0.151	0.077 + 0.037*SL	0.074 + 0.038*SL	0.068 + 0.039*SL
	t_F	0.132	0.068 + 0.032*SL	0.064 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.331	0.291 + 0.020*SL	0.300 + 0.018*SL	0.304 + 0.018*SL
	t_{PHL}	0.329	0.288 + 0.020*SL	0.297 + 0.018*SL	0.301 + 0.018*SL
S0 to Y2	t_R	0.153	0.079 + 0.037*SL	0.078 + 0.038*SL	0.070 + 0.039*SL
	t_F	0.132	0.067 + 0.033*SL	0.066 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.335	0.293 + 0.021*SL	0.304 + 0.018*SL	0.308 + 0.018*SL
	t_{PHL}	0.314	0.273 + 0.021*SL	0.282 + 0.018*SL	0.287 + 0.018*SL
S1 to Y2	t_R	0.155	0.082 + 0.037*SL	0.078 + 0.038*SL	0.072 + 0.038*SL
	t_F	0.134	0.068 + 0.033*SL	0.070 + 0.033*SL	0.063 + 0.034*SL
	t_{PLH}	0.216	0.175 + 0.021*SL	0.185 + 0.018*SL	0.190 + 0.018*SL
	t_{PHL}	0.245	0.203 + 0.021*SL	0.213 + 0.018*SL	0.218 + 0.018*SL
S0 to Y3	t_R	0.155	0.080 + 0.037*SL	0.078 + 0.038*SL	0.073 + 0.039*SL
	t_F	0.129	0.067 + 0.031*SL	0.066 + 0.031*SL	0.063 + 0.032*SL
	t_{PLH}	0.216	0.175 + 0.020*SL	0.184 + 0.018*SL	0.189 + 0.018*SL
	t_{PHL}	0.220	0.181 + 0.020*SL	0.190 + 0.018*SL	0.195 + 0.017*SL
S1 to Y3	t_R	0.155	0.082 + 0.037*SL	0.077 + 0.038*SL	0.072 + 0.039*SL
	t_F	0.130	0.068 + 0.031*SL	0.068 + 0.031*SL	0.063 + 0.032*SL
	t_{PLH}	0.209	0.169 + 0.020*SL	0.178 + 0.018*SL	0.182 + 0.018*SL
	t_{PHL}	0.236	0.197 + 0.020*SL	0.206 + 0.018*SL	0.211 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Logic Symbol



Truth Table

S1	S0	YN0	YN1	YN2	YN3
0	0	0	1	1	1
0	1	1	0	1	1
1	0	1	1	0	1
1	1	1	1	1	0

Cell Data

Input Load (SL)		Gate Count
S0	S1	
2.9	3.1	4.00

Schematic Diagram



DC4I

2 > 4 Inverting Decoder

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DC4I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to YN0	t_R	0.161	0.088 + 0.037*SL	0.084 + 0.038*SL	0.077 + 0.038*SL
	t_F	0.178	0.097 + 0.040*SL	0.096 + 0.041*SL	0.090 + 0.042*SL
	t_{PLH}	0.238	0.198 + 0.020*SL	0.206 + 0.018*SL	0.210 + 0.017*SL
	t_{PHL}	0.269	0.222 + 0.024*SL	0.231 + 0.021*SL	0.236 + 0.021*SL
S1 to YN0	t_R	0.176	0.102 + 0.037*SL	0.099 + 0.038*SL	0.093 + 0.039*SL
	t_F	0.172	0.092 + 0.040*SL	0.088 + 0.041*SL	0.084 + 0.042*SL
	t_{PLH}	0.253	0.214 + 0.019*SL	0.220 + 0.018*SL	0.222 + 0.018*SL
	t_{PHL}	0.271	0.225 + 0.023*SL	0.232 + 0.021*SL	0.236 + 0.021*SL
S0 to YN1	t_R	0.180	0.114 + 0.033*SL	0.101 + 0.036*SL	0.090 + 0.038*SL
	t_F	0.190	0.116 + 0.037*SL	0.109 + 0.039*SL	0.093 + 0.041*SL
	t_{PLH}	0.125	0.082 + 0.021*SL	0.099 + 0.017*SL	0.099 + 0.017*SL
	t_{PHL}	0.127	0.079 + 0.024*SL	0.094 + 0.020*SL	0.092 + 0.020*SL
S1 to YN1	t_R	0.177	0.102 + 0.037*SL	0.100 + 0.038*SL	0.094 + 0.039*SL
	t_F	0.172	0.092 + 0.040*SL	0.088 + 0.041*SL	0.083 + 0.042*SL
	t_{PLH}	0.254	0.216 + 0.019*SL	0.221 + 0.018*SL	0.224 + 0.017*SL
	t_{PHL}	0.271	0.226 + 0.023*SL	0.232 + 0.021*SL	0.236 + 0.021*SL
S0 to YN2	t_R	0.162	0.088 + 0.037*SL	0.085 + 0.038*SL	0.078 + 0.039*SL
	t_F	0.179	0.098 + 0.040*SL	0.096 + 0.041*SL	0.090 + 0.041*SL
	t_{PLH}	0.241	0.201 + 0.020*SL	0.209 + 0.018*SL	0.213 + 0.018*SL
	t_{PHL}	0.272	0.225 + 0.024*SL	0.234 + 0.021*SL	0.239 + 0.021*SL
S1 to YN2	t_R	0.196	0.129 + 0.033*SL	0.119 + 0.036*SL	0.108 + 0.037*SL
	t_F	0.179	0.105 + 0.037*SL	0.095 + 0.039*SL	0.082 + 0.041*SL
	t_{PLH}	0.140	0.100 + 0.020*SL	0.111 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.125	0.077 + 0.024*SL	0.093 + 0.020*SL	0.093 + 0.020*SL
S0 to YN3	t_R	0.180	0.113 + 0.033*SL	0.103 + 0.036*SL	0.092 + 0.037*SL
	t_F	0.190	0.117 + 0.037*SL	0.106 + 0.039*SL	0.094 + 0.041*SL
	t_{PLH}	0.126	0.084 + 0.021*SL	0.100 + 0.017*SL	0.100 + 0.017*SL
	t_{PHL}	0.129	0.081 + 0.024*SL	0.095 + 0.020*SL	0.095 + 0.021*SL
S1 to YN3	t_R	0.196	0.128 + 0.034*SL	0.119 + 0.036*SL	0.108 + 0.038*SL
	t_F	0.178	0.102 + 0.038*SL	0.093 + 0.040*SL	0.084 + 0.041*SL
	t_{PLH}	0.142	0.103 + 0.020*SL	0.113 + 0.017*SL	0.112 + 0.017*SL
	t_{PHL}	0.124	0.077 + 0.023*SL	0.088 + 0.021*SL	0.089 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Logic Symbol



Truth Table

S2	S1	S0	YN0	YN1	YN2	YN3	YN4	YN5	YN6	YN7
0	0	0	0	1	1	1	1	1	1	1
0	0	1	1	0	1	1	1	1	1	1
0	1	0	1	1	0	1	1	1	1	1
0	1	1	1	1	1	0	1	1	1	1
1	0	0	1	1	1	1	0	1	1	1
1	0	1	1	1	1	1	1	0	1	1
1	1	0	1	1	1	1	1	1	0	1
1	1	1	1	1	1	1	1	1	1	0

Cell Data

Input Load (SL)			Gate Count
S0	S1	S2	
5.1	5.1	5.2	10.67

Schematic Diagram



DC8I

3 > 8 Inverting Decoder

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DC8I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S0 to YN0	t_R	0.237	0.134 + 0.052*SL	0.131 + 0.053*SL	0.123 + 0.054*SL
	t_F	0.263	0.150 + 0.057*SL	0.146 + 0.058*SL	0.138 + 0.059*SL
	t_{PLH}	0.323	0.269 + 0.027*SL	0.278 + 0.025*SL	0.283 + 0.024*SL
	t_{PHL}	0.325	0.265 + 0.030*SL	0.272 + 0.028*SL	0.274 + 0.028*SL
S1 to YN0	t_R	0.250	0.154 + 0.048*SL	0.149 + 0.049*SL	0.142 + 0.050*SL
	t_F	0.261	0.147 + 0.057*SL	0.142 + 0.058*SL	0.138 + 0.059*SL
	t_{PLH}	0.350	0.300 + 0.025*SL	0.307 + 0.023*SL	0.311 + 0.023*SL
	t_{PHL}	0.339	0.278 + 0.030*SL	0.284 + 0.029*SL	0.288 + 0.028*SL
S2 to YN0	t_R	0.284	0.181 + 0.051*SL	0.175 + 0.053*SL	0.168 + 0.054*SL
	t_F	0.255	0.139 + 0.058*SL	0.136 + 0.059*SL	0.133 + 0.059*SL
	t_{PLH}	0.363	0.311 + 0.026*SL	0.317 + 0.025*SL	0.319 + 0.024*SL
	t_{PHL}	0.332	0.272 + 0.030*SL	0.277 + 0.029*SL	0.280 + 0.028*SL
S0 to YN1	t_R	0.230	0.139 + 0.046*SL	0.128 + 0.048*SL	0.114 + 0.050*SL
	t_F	0.267	0.159 + 0.054*SL	0.149 + 0.057*SL	0.136 + 0.058*SL
	t_{PLH}	0.160	0.111 + 0.024*SL	0.117 + 0.023*SL	0.117 + 0.023*SL
	t_{PHL}	0.164	0.106 + 0.029*SL	0.110 + 0.028*SL	0.109 + 0.028*SL
S1 to YN1	t_R	0.261	0.159 + 0.051*SL	0.155 + 0.052*SL	0.149 + 0.053*SL
	t_F	0.261	0.147 + 0.057*SL	0.144 + 0.058*SL	0.138 + 0.059*SL
	t_{PLH}	0.357	0.304 + 0.026*SL	0.312 + 0.024*SL	0.315 + 0.024*SL
	t_{PHL}	0.339	0.278 + 0.030*SL	0.284 + 0.029*SL	0.288 + 0.028*SL
S2 to YN1	t_R	0.271	0.174 + 0.048*SL	0.169 + 0.050*SL	0.163 + 0.050*SL
	t_F	0.255	0.140 + 0.058*SL	0.136 + 0.059*SL	0.133 + 0.059*SL
	t_{PLH}	0.355	0.306 + 0.025*SL	0.312 + 0.023*SL	0.315 + 0.023*SL
	t_{PHL}	0.333	0.273 + 0.030*SL	0.278 + 0.029*SL	0.280 + 0.028*SL
S0 to YN2	t_R	0.238	0.137 + 0.051*SL	0.133 + 0.052*SL	0.126 + 0.053*SL
	t_F	0.269	0.155 + 0.057*SL	0.151 + 0.058*SL	0.145 + 0.059*SL
	t_{PLH}	0.324	0.270 + 0.027*SL	0.279 + 0.024*SL	0.284 + 0.024*SL
	t_{PHL}	0.329	0.268 + 0.030*SL	0.275 + 0.029*SL	0.278 + 0.028*SL
S1 to YN2	t_R	0.256	0.161 + 0.047*SL	0.153 + 0.049*SL	0.140 + 0.051*SL
	t_F	0.267	0.158 + 0.055*SL	0.149 + 0.057*SL	0.138 + 0.058*SL
	t_{PLH}	0.186	0.138 + 0.024*SL	0.140 + 0.023*SL	0.142 + 0.023*SL
	t_{PHL}	0.178	0.119 + 0.030*SL	0.125 + 0.028*SL	0.126 + 0.028*SL
S2 to YN2	t_R	0.281	0.182 + 0.050*SL	0.176 + 0.051*SL	0.168 + 0.052*SL
	t_F	0.259	0.143 + 0.058*SL	0.139 + 0.059*SL	0.137 + 0.059*SL
	t_{PLH}	0.362	0.311 + 0.025*SL	0.316 + 0.024*SL	0.319 + 0.024*SL
	t_{PHL}	0.335	0.275 + 0.030*SL	0.280 + 0.029*SL	0.282 + 0.028*SL
S0 to YN3	t_R	0.231	0.139 + 0.046*SL	0.128 + 0.048*SL	0.115 + 0.050*SL
	t_F	0.270	0.161 + 0.054*SL	0.151 + 0.057*SL	0.138 + 0.058*SL
	t_{PLH}	0.160	0.112 + 0.024*SL	0.118 + 0.023*SL	0.118 + 0.023*SL
	t_{PHL}	0.165	0.107 + 0.029*SL	0.111 + 0.028*SL	0.110 + 0.028*SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DC8I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S1 to YN3	t_R	0.254	0.158 + 0.048*SL	0.150 + 0.050*SL	0.138 + 0.052*SL
	t_F	0.263	0.152 + 0.056*SL	0.144 + 0.058*SL	0.136 + 0.059*SL
	t_{PLH}	0.186	0.139 + 0.024*SL	0.140 + 0.023*SL	0.140 + 0.023*SL
	t_{PHL}	0.176	0.117 + 0.029*SL	0.121 + 0.028*SL	0.122 + 0.028*SL
S2 to YN3	t_R	0.277	0.179 + 0.049*SL	0.173 + 0.050*SL	0.166 + 0.051*SL
	t_F	0.257	0.141 + 0.058*SL	0.138 + 0.058*SL	0.135 + 0.059*SL
	t_{PLH}	0.361	0.311 + 0.025*SL	0.316 + 0.024*SL	0.319 + 0.023*SL
	t_{PHL}	0.335	0.275 + 0.030*SL	0.280 + 0.029*SL	0.283 + 0.028*SL
S0 to YN4	t_R	0.238	0.135 + 0.052*SL	0.131 + 0.053*SL	0.123 + 0.054*SL
	t_F	0.264	0.150 + 0.057*SL	0.147 + 0.058*SL	0.139 + 0.059*SL
	t_{PLH}	0.323	0.269 + 0.027*SL	0.278 + 0.025*SL	0.283 + 0.024*SL
	t_{PHL}	0.326	0.265 + 0.030*SL	0.272 + 0.028*SL	0.274 + 0.028*SL
S1 to YN4	t_R	0.251	0.154 + 0.048*SL	0.150 + 0.049*SL	0.143 + 0.050*SL
	t_F	0.262	0.148 + 0.057*SL	0.144 + 0.058*SL	0.139 + 0.059*SL
	t_{PLH}	0.350	0.299 + 0.025*SL	0.306 + 0.023*SL	0.311 + 0.023*SL
	t_{PHL}	0.340	0.279 + 0.031*SL	0.285 + 0.029*SL	0.289 + 0.028*SL
S2 to YN4	t_R	0.286	0.186 + 0.050*SL	0.177 + 0.052*SL	0.166 + 0.054*SL
	t_F	0.257	0.146 + 0.056*SL	0.138 + 0.058*SL	0.130 + 0.059*SL
	t_{PLH}	0.199	0.149 + 0.025*SL	0.151 + 0.024*SL	0.154 + 0.024*SL
	t_{PHL}	0.172	0.113 + 0.030*SL	0.120 + 0.028*SL	0.122 + 0.028*SL
S0 to YN5	t_R	0.229	0.138 + 0.046*SL	0.127 + 0.048*SL	0.113 + 0.050*SL
	t_F	0.266	0.158 + 0.054*SL	0.148 + 0.057*SL	0.135 + 0.058*SL
	t_{PLH}	0.160	0.111 + 0.024*SL	0.118 + 0.023*SL	0.118 + 0.023*SL
	t_{PHL}	0.165	0.107 + 0.029*SL	0.110 + 0.028*SL	0.109 + 0.028*SL
S1 to YN5	t_R	0.264	0.161 + 0.052*SL	0.157 + 0.053*SL	0.149 + 0.054*SL
	t_F	0.262	0.147 + 0.057*SL	0.144 + 0.058*SL	0.139 + 0.059*SL
	t_{PLH}	0.357	0.304 + 0.027*SL	0.311 + 0.025*SL	0.315 + 0.024*SL
	t_{PHL}	0.338	0.278 + 0.030*SL	0.284 + 0.029*SL	0.287 + 0.028*SL
S2 to YN5	t_R	0.273	0.180 + 0.046*SL	0.172 + 0.048*SL	0.160 + 0.050*SL
	t_F	0.257	0.144 + 0.056*SL	0.137 + 0.058*SL	0.131 + 0.059*SL
	t_{PLH}	0.191	0.144 + 0.023*SL	0.146 + 0.023*SL	0.148 + 0.023*SL
	t_{PHL}	0.171	0.112 + 0.029*SL	0.117 + 0.028*SL	0.119 + 0.028*SL
S0 to YN6	t_R	0.238	0.136 + 0.051*SL	0.132 + 0.052*SL	0.125 + 0.053*SL
	t_F	0.267	0.154 + 0.057*SL	0.150 + 0.058*SL	0.144 + 0.059*SL
	t_{PLH}	0.323	0.270 + 0.027*SL	0.279 + 0.024*SL	0.283 + 0.024*SL
	t_{PHL}	0.328	0.268 + 0.030*SL	0.274 + 0.029*SL	0.277 + 0.028*SL
S1 to YN6	t_R	0.255	0.160 + 0.047*SL	0.153 + 0.049*SL	0.140 + 0.051*SL
	t_F	0.266	0.156 + 0.055*SL	0.147 + 0.057*SL	0.137 + 0.058*SL
	t_{PLH}	0.181	0.133 + 0.024*SL	0.134 + 0.023*SL	0.137 + 0.023*SL
	t_{PHL}	0.173	0.113 + 0.030*SL	0.120 + 0.028*SL	0.121 + 0.028*SL

Switching Characteristics (Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

DC8I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
S2 to YN6	t_R	0.281	0.185 + 0.048*SL	0.176 + 0.050*SL	0.164 + 0.052*SL
	t_F	0.258	0.146 + 0.056*SL	0.139 + 0.058*SL	0.132 + 0.059*SL
	t_{PLH}	0.196	0.148 + 0.024*SL	0.150 + 0.024*SL	0.151 + 0.023*SL
	t_{PHL}	0.173	0.114 + 0.029*SL	0.120 + 0.028*SL	0.121 + 0.028*SL
S0 to YN7	t_R	0.231	0.139 + 0.046*SL	0.128 + 0.048*SL	0.115 + 0.050*SL
	t_F	0.270	0.161 + 0.054*SL	0.152 + 0.057*SL	0.139 + 0.058*SL
	t_{PLH}	0.160	0.112 + 0.024*SL	0.118 + 0.023*SL	0.118 + 0.023*SL
	t_{PHL}	0.166	0.107 + 0.029*SL	0.111 + 0.028*SL	0.111 + 0.028*SL
S1 to YN7	t_R	0.256	0.158 + 0.049*SL	0.150 + 0.051*SL	0.139 + 0.052*SL
	t_F	0.261	0.150 + 0.056*SL	0.142 + 0.058*SL	0.134 + 0.059*SL
	t_{PLH}	0.183	0.135 + 0.024*SL	0.136 + 0.024*SL	0.136 + 0.024*SL
	t_{PHL}	0.170	0.112 + 0.029*SL	0.116 + 0.028*SL	0.116 + 0.028*SL
S2 to YN7	t_R	0.275	0.181 + 0.047*SL	0.173 + 0.049*SL	0.161 + 0.050*SL
	t_F	0.257	0.143 + 0.057*SL	0.137 + 0.058*SL	0.132 + 0.059*SL
	t_{PLH}	0.193	0.146 + 0.023*SL	0.148 + 0.023*SL	0.149 + 0.023*SL
	t_{PHL}	0.172	0.113 + 0.029*SL	0.117 + 0.028*SL	0.118 + 0.028*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Cell List

Cell Name	Function Description
FADH	Full Adder with 0.5X Drive
FA	Full Adder with 1X Drive
FAD2	Full Adder with 2X Drive
HADH	Half Adder with 0.5x Drive
HA	Half Adder with 1x Drive
HAD2	Half Adder with 2X Drive
SCG23	Full Adder with one inverted input, 1X Drive
SCG23D2	Full Adder with one inverted input, 2X Drive

FADH/FA/FAD2

Full Adder with 0.5X/1X/2X Drive

Logic Symbol



Truth Table

CI	A	B	S	CO
0	0	0	0	0
1	0	0	1	0
0	0	1	1	0
1	0	1	0	1
0	1	0	1	0
1	1	0	0	1
0	1	1	0	1
1	1	1	1	1

Cell Data

Input Load (SL)									Gate Count		
FADH			*FA*			*FAD2*			*FADH*	*FA*	*FAD2*
CI	A	B	CI	A	B	CI	A	B			
0.8	0.8	0.5	1.0	1.0	0.5	1.0	1.0	0.5	6.00	6.33	6.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FADH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.291	0.123 + 0.084*SL	0.115 + 0.086*SL	0.104 + 0.088*SL
	t_F	0.243	0.113 + 0.065*SL	0.123 + 0.063*SL	0.119 + 0.063*SL
	t_{PLH}	0.649	0.560 + 0.044*SL	0.576 + 0.040*SL	0.582 + 0.040*SL
	t_{PHL}	0.663	0.578 + 0.043*SL	0.602 + 0.036*SL	0.620 + 0.034*SL
B to S	t_R	0.295	0.126 + 0.084*SL	0.119 + 0.086*SL	0.109 + 0.087*SL
	t_F	0.244	0.113 + 0.065*SL	0.126 + 0.062*SL	0.122 + 0.063*SL
	t_{PLH}	0.747	0.659 + 0.044*SL	0.675 + 0.040*SL	0.681 + 0.040*SL
	t_{PHL}	0.762	0.676 + 0.043*SL	0.701 + 0.036*SL	0.719 + 0.034*SL
CI to S	t_R	0.297	0.130 + 0.084*SL	0.122 + 0.086*SL	0.108 + 0.087*SL
	t_F	0.272	0.147 + 0.062*SL	0.153 + 0.061*SL	0.143 + 0.062*SL
	t_{PLH}	0.600	0.512 + 0.044*SL	0.528 + 0.040*SL	0.532 + 0.039*SL
	t_{PHL}	0.574	0.489 + 0.042*SL	0.516 + 0.036*SL	0.530 + 0.034*SL
A to CO	t_R	0.286	0.117 + 0.085*SL	0.111 + 0.086*SL	0.101 + 0.088*SL
	t_F	0.241	0.111 + 0.065*SL	0.121 + 0.063*SL	0.118 + 0.063*SL
	t_{PLH}	0.632	0.545 + 0.043*SL	0.558 + 0.040*SL	0.563 + 0.039*SL
	t_{PHL}	0.645	0.563 + 0.041*SL	0.585 + 0.036*SL	0.599 + 0.034*SL
B to CO	t_R	0.362	0.223 + 0.070*SL	0.178 + 0.081*SL	0.142 + 0.086*SL
	t_F	0.293	0.177 + 0.058*SL	0.176 + 0.058*SL	0.151 + 0.062*SL
	t_{PLH}	0.728	0.641 + 0.044*SL	0.654 + 0.040*SL	0.659 + 0.039*SL
	t_{PHL}	0.750	0.668 + 0.041*SL	0.691 + 0.036*SL	0.705 + 0.034*SL
CI to CO	t_R	0.297	0.130 + 0.084*SL	0.122 + 0.086*SL	0.111 + 0.087*SL
	t_F	0.272	0.143 + 0.064*SL	0.158 + 0.061*SL	0.152 + 0.062*SL
	t_{PLH}	0.437	0.343 + 0.047*SL	0.367 + 0.041*SL	0.376 + 0.040*SL
	t_{PHL}	0.464	0.368 + 0.048*SL	0.409 + 0.038*SL	0.435 + 0.035*SL

*Group1 : SL < 4, *Group2 : 4 ≤ SL ≤ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.194	0.117 + 0.038*SL	0.123 + 0.037*SL	0.120 + 0.037*SL
	t_F	0.183	0.111 + 0.036*SL	0.123 + 0.033*SL	0.134 + 0.032*SL
	t_{PLH}	0.619	0.570 + 0.024*SL	0.586 + 0.020*SL	0.600 + 0.019*SL
	t_{PHL}	0.620	0.566 + 0.027*SL	0.585 + 0.022*SL	0.605 + 0.019*SL
B to S	t_R	0.193	0.115 + 0.039*SL	0.121 + 0.037*SL	0.117 + 0.038*SL
	t_F	0.186	0.114 + 0.036*SL	0.128 + 0.033*SL	0.137 + 0.032*SL
	t_{PLH}	0.722	0.674 + 0.024*SL	0.690 + 0.020*SL	0.703 + 0.019*SL
	t_{PHL}	0.728	0.675 + 0.027*SL	0.693 + 0.022*SL	0.714 + 0.019*SL
CI to S	t_R	0.200	0.122 + 0.039*SL	0.131 + 0.037*SL	0.128 + 0.037*SL
	t_F	0.218	0.147 + 0.036*SL	0.163 + 0.032*SL	0.172 + 0.030*SL
	t_{PLH}	0.648	0.599 + 0.024*SL	0.617 + 0.020*SL	0.630 + 0.018*SL
	t_{PHL}	0.624	0.571 + 0.027*SL	0.592 + 0.021*SL	0.612 + 0.019*SL
A to CO	t_R	0.184	0.103 + 0.040*SL	0.112 + 0.038*SL	0.112 + 0.038*SL
	t_F	0.180	0.106 + 0.037*SL	0.119 + 0.034*SL	0.133 + 0.032*SL
	t_{PLH}	0.587	0.542 + 0.022*SL	0.555 + 0.019*SL	0.564 + 0.018*SL
	t_{PHL}	0.578	0.531 + 0.024*SL	0.547 + 0.020*SL	0.561 + 0.018*SL
B to CO	t_R	0.279	0.215 + 0.032*SL	0.221 + 0.031*SL	0.192 + 0.034*SL
	t_F	0.245	0.183 + 0.031*SL	0.191 + 0.029*SL	0.189 + 0.029*SL
	t_{PLH}	0.688	0.643 + 0.023*SL	0.657 + 0.019*SL	0.666 + 0.018*SL
	t_{PHL}	0.688	0.640 + 0.024*SL	0.657 + 0.020*SL	0.671 + 0.018*SL
CI to CO	t_R	0.199	0.120 + 0.039*SL	0.129 + 0.037*SL	0.127 + 0.037*SL
	t_F	0.215	0.141 + 0.037*SL	0.159 + 0.032*SL	0.169 + 0.031*SL
	t_{PLH}	0.417	0.366 + 0.026*SL	0.385 + 0.021*SL	0.402 + 0.019*SL
	t_{PHL}	0.462	0.402 + 0.030*SL	0.428 + 0.024*SL	0.454 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

FAD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.153	0.111 + 0.021*SL	0.119 + 0.019*SL	0.127 + 0.018*SL
	t_F	0.162	0.118 + 0.022*SL	0.131 + 0.019*SL	0.152 + 0.017*SL
	t_{PLH}	0.628	0.596 + 0.016*SL	0.612 + 0.012*SL	0.637 + 0.010*SL
	t_{PHL}	0.641	0.605 + 0.018*SL	0.622 + 0.014*SL	0.654 + 0.011*SL
B to S	t_R	0.156	0.114 + 0.021*SL	0.123 + 0.019*SL	0.129 + 0.018*SL
	t_F	0.164	0.121 + 0.022*SL	0.134 + 0.019*SL	0.155 + 0.017*SL
	t_{PLH}	0.728	0.696 + 0.016*SL	0.712 + 0.012*SL	0.738 + 0.010*SL
	t_{PHL}	0.744	0.708 + 0.018*SL	0.725 + 0.014*SL	0.758 + 0.011*SL
CI to S	t_R	0.159	0.116 + 0.022*SL	0.127 + 0.019*SL	0.136 + 0.018*SL
	t_F	0.193	0.149 + 0.022*SL	0.164 + 0.018*SL	0.185 + 0.016*SL
	t_{PLH}	0.708	0.675 + 0.016*SL	0.692 + 0.012*SL	0.719 + 0.010*SL
	t_{PHL}	0.684	0.647 + 0.018*SL	0.666 + 0.014*SL	0.700 + 0.011*SL
A to CO	t_R	0.146	0.102 + 0.022*SL	0.112 + 0.019*SL	0.123 + 0.018*SL
	t_F	0.158	0.114 + 0.022*SL	0.126 + 0.019*SL	0.151 + 0.017*SL
	t_{PLH}	0.593	0.564 + 0.015*SL	0.579 + 0.011*SL	0.599 + 0.009*SL
	t_{PHL}	0.592	0.560 + 0.016*SL	0.575 + 0.012*SL	0.601 + 0.010*SL
B to CO	t_R	0.240	0.214 + 0.013*SL	0.205 + 0.015*SL	0.183 + 0.017*SL
	t_F	0.235	0.204 + 0.016*SL	0.207 + 0.015*SL	0.197 + 0.016*SL
	t_{PLH}	0.692	0.663 + 0.015*SL	0.678 + 0.011*SL	0.699 + 0.009*SL
	t_{PHL}	0.698	0.666 + 0.016*SL	0.681 + 0.012*SL	0.707 + 0.010*SL
CI to CO	t_R	0.157	0.113 + 0.022*SL	0.124 + 0.019*SL	0.135 + 0.018*SL
	t_F	0.189	0.145 + 0.022*SL	0.159 + 0.019*SL	0.182 + 0.017*SL
	t_{PLH}	0.423	0.390 + 0.017*SL	0.407 + 0.012*SL	0.436 + 0.010*SL
	t_{PHL}	0.480	0.440 + 0.020*SL	0.461 + 0.015*SL	0.501 + 0.011*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Logic Symbol



Truth Table

A	B	S	CO
0	0	0	0
0	1	1	0
1	0	1	0
1	1	0	1

Cell Data

Input Load (SL)						Gate Count		
HADH		*HA*		*HAD2*		*HADH*	*HA*	*HAD2*
A	B	A	B	A	B			
1.1	1.7	1.3	2.0	1.3	2.2	3.67	3.67	4.00

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

HADH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.268	0.107 + 0.080*SL	0.099 + 0.082*SL	0.087 + 0.084*SL
	t_F	0.253	0.130 + 0.062*SL	0.133 + 0.061*SL	0.120 + 0.063*SL
	t_{PLH}	0.430	0.348 + 0.041*SL	0.360 + 0.038*SL	0.363 + 0.038*SL
	t_{PHL}	0.437	0.353 + 0.042*SL	0.379 + 0.036*SL	0.394 + 0.034*SL
B to S	t_R	0.262	0.100 + 0.081*SL	0.093 + 0.083*SL	0.084 + 0.084*SL
	t_F	0.236	0.110 + 0.063*SL	0.115 + 0.062*SL	0.106 + 0.063*SL
	t_{PLH}	0.349	0.267 + 0.041*SL	0.280 + 0.038*SL	0.283 + 0.038*SL
	t_{PHL}	0.359	0.275 + 0.042*SL	0.301 + 0.036*SL	0.315 + 0.034*SL
A to CO	t_R	0.259	0.091 + 0.084*SL	0.082 + 0.086*SL	0.073 + 0.087*SL
	t_F	0.198	0.074 + 0.062*SL	0.067 + 0.064*SL	0.060 + 0.065*SL
	t_{PLH}	0.270	0.188 + 0.041*SL	0.196 + 0.039*SL	0.197 + 0.039*SL
	t_{PHL}	0.280	0.208 + 0.036*SL	0.218 + 0.034*SL	0.220 + 0.033*SL
B to CO	t_R	0.259	0.091 + 0.084*SL	0.082 + 0.086*SL	0.073 + 0.087*SL
	t_F	0.197	0.073 + 0.062*SL	0.066 + 0.064*SL	0.057 + 0.065*SL
	t_{PLH}	0.273	0.191 + 0.041*SL	0.199 + 0.039*SL	0.200 + 0.039*SL
	t_{PHL}	0.261	0.190 + 0.036*SL	0.199 + 0.033*SL	0.201 + 0.033*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

HA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.180	0.104 + 0.038*SL	0.108 + 0.037*SL	0.104 + 0.038*SL
	t_F	0.191	0.123 + 0.034*SL	0.136 + 0.031*SL	0.140 + 0.030*SL
	t_{PLH}	0.429	0.383 + 0.023*SL	0.398 + 0.019*SL	0.409 + 0.018*SL
	t_{PHL}	0.437	0.385 + 0.026*SL	0.406 + 0.021*SL	0.425 + 0.019*SL
B to S	t_R	0.175	0.099 + 0.038*SL	0.102 + 0.037*SL	0.099 + 0.038*SL
	t_F	0.176	0.107 + 0.035*SL	0.119 + 0.031*SL	0.123 + 0.031*SL
	t_{PLH}	0.324	0.277 + 0.023*SL	0.292 + 0.020*SL	0.303 + 0.018*SL
	t_{PHL}	0.337	0.285 + 0.026*SL	0.305 + 0.021*SL	0.324 + 0.019*SL
A to CO	t_R	0.154	0.081 + 0.037*SL	0.076 + 0.038*SL	0.071 + 0.038*SL
	t_F	0.133	0.068 + 0.032*SL	0.066 + 0.033*SL	0.060 + 0.034*SL
	t_{PLH}	0.213	0.171 + 0.021*SL	0.181 + 0.018*SL	0.186 + 0.018*SL
	t_{PHL}	0.234	0.193 + 0.021*SL	0.202 + 0.018*SL	0.206 + 0.018*SL
B to CO	t_R	0.153	0.079 + 0.037*SL	0.076 + 0.038*SL	0.070 + 0.039*SL
	t_F	0.130	0.066 + 0.032*SL	0.061 + 0.033*SL	0.058 + 0.034*SL
	t_{PLH}	0.217	0.176 + 0.020*SL	0.185 + 0.018*SL	0.189 + 0.018*SL
	t_{PHL}	0.217	0.176 + 0.020*SL	0.185 + 0.018*SL	0.188 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

HAD2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to S	t_R	0.146	0.103 + 0.021*SL	0.112 + 0.019*SL	0.117 + 0.019*SL
	t_F	0.170	0.129 + 0.021*SL	0.142 + 0.017*SL	0.159 + 0.016*SL
	t_{PLH}	0.448	0.418 + 0.015*SL	0.433 + 0.012*SL	0.457 + 0.010*SL
	t_{PHL}	0.465	0.429 + 0.018*SL	0.448 + 0.013*SL	0.481 + 0.010*SL
B to S	t_R	0.141	0.097 + 0.022*SL	0.108 + 0.019*SL	0.114 + 0.019*SL
	t_F	0.159	0.118 + 0.021*SL	0.131 + 0.018*SL	0.149 + 0.016*SL
	t_{PLH}	0.338	0.307 + 0.015*SL	0.322 + 0.012*SL	0.346 + 0.010*SL
	t_{PHL}	0.357	0.321 + 0.018*SL	0.340 + 0.013*SL	0.374 + 0.010*SL
A to CO	t_R	0.117	0.076 + 0.020*SL	0.083 + 0.019*SL	0.080 + 0.019*SL
	t_F	0.102	0.068 + 0.017*SL	0.072 + 0.016*SL	0.068 + 0.017*SL
	t_{PLH}	0.227	0.200 + 0.014*SL	0.213 + 0.010*SL	0.228 + 0.009*SL
	t_{PHL}	0.243	0.216 + 0.013*SL	0.228 + 0.010*SL	0.242 + 0.009*SL
B to CO	t_R	0.116	0.077 + 0.020*SL	0.082 + 0.019*SL	0.078 + 0.019*SL
	t_F	0.098	0.061 + 0.018*SL	0.070 + 0.016*SL	0.065 + 0.017*SL
	t_{PLH}	0.239	0.212 + 0.014*SL	0.225 + 0.010*SL	0.240 + 0.009*SL
	t_{PHL}	0.234	0.207 + 0.013*SL	0.219 + 0.010*SL	0.233 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

SCG23/SCG23D2

Full Adder with one inverted input, 1X/2X Drive

Logic Symbol



Truth Table

AN	B	CI	S	CO
0	0	0	1	0
0	0	1	0	1
0	1	0	0	1
0	1	1	1	1
1	0	0	0	0
1	0	1	1	0
1	1	0	1	0
1	1	1	0	1

Cell Data

Input Load (SL)						Gate Count	
SCG23			*SCG23D2*			*SCG23*	*SCG23D2*
CI	AN	B	CI	AN	B		
0.5	0.5	1.0	0.5	0.6	1.0	6.67	7.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG23

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
AN to S	t_R	0.195	0.117 + 0.039*SL	0.125 + 0.037*SL	0.122 + 0.037*SL
	t_F	0.183	0.108 + 0.037*SL	0.123 + 0.034*SL	0.137 + 0.032*SL
	t_{PLH}	0.767	0.718 + 0.024*SL	0.734 + 0.021*SL	0.749 + 0.019*SL
	t_{PHL}	0.741	0.687 + 0.027*SL	0.706 + 0.023*SL	0.728 + 0.020*SL
B to S	t_R	0.194	0.116 + 0.039*SL	0.124 + 0.037*SL	0.120 + 0.038*SL
	t_F	0.189	0.116 + 0.036*SL	0.129 + 0.033*SL	0.141 + 0.032*SL
	t_{PLH}	0.742	0.693 + 0.024*SL	0.710 + 0.021*SL	0.724 + 0.019*SL
	t_{PHL}	0.735	0.681 + 0.027*SL	0.700 + 0.023*SL	0.721 + 0.020*SL
CI to S	t_R	0.200	0.121 + 0.039*SL	0.131 + 0.037*SL	0.128 + 0.037*SL
	t_F	0.222	0.151 + 0.036*SL	0.167 + 0.032*SL	0.177 + 0.031*SL
	t_{PLH}	0.663	0.614 + 0.024*SL	0.632 + 0.020*SL	0.645 + 0.018*SL
	t_{PHL}	0.625	0.571 + 0.027*SL	0.592 + 0.022*SL	0.613 + 0.019*SL
AN to CO	t_R	0.184	0.104 + 0.040*SL	0.112 + 0.038*SL	0.113 + 0.038*SL
	t_F	0.182	0.107 + 0.038*SL	0.123 + 0.034*SL	0.137 + 0.032*SL
	t_{PLH}	0.733	0.688 + 0.023*SL	0.701 + 0.019*SL	0.711 + 0.018*SL
	t_{PHL}	0.684	0.637 + 0.024*SL	0.653 + 0.020*SL	0.667 + 0.018*SL
B to CO	t_R	0.287	0.225 + 0.031*SL	0.229 + 0.030*SL	0.198 + 0.034*SL
	t_F	0.246	0.183 + 0.031*SL	0.192 + 0.029*SL	0.190 + 0.029*SL
	t_{PLH}	0.706	0.661 + 0.023*SL	0.675 + 0.019*SL	0.685 + 0.018*SL
	t_{PHL}	0.691	0.643 + 0.024*SL	0.659 + 0.020*SL	0.674 + 0.018*SL
CI to CO	t_R	0.199	0.120 + 0.039*SL	0.129 + 0.037*SL	0.127 + 0.037*SL
	t_F	0.217	0.143 + 0.037*SL	0.161 + 0.033*SL	0.175 + 0.031*SL
	t_{PLH}	0.417	0.366 + 0.026*SL	0.385 + 0.021*SL	0.402 + 0.019*SL
	t_{PHL}	0.475	0.415 + 0.030*SL	0.440 + 0.024*SL	0.468 + 0.020*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

SCG23D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
AN to S	t_R	0.165	0.120 + 0.022*SL	0.131 + 0.019*SL	0.142 + 0.018*SL
	t_F	0.158	0.113 + 0.023*SL	0.127 + 0.019*SL	0.152 + 0.017*SL
	t_{PLH}	0.776	0.744 + 0.016*SL	0.760 + 0.012*SL	0.786 + 0.010*SL
	t_{PHL}	0.775	0.739 + 0.018*SL	0.755 + 0.014*SL	0.789 + 0.011*SL
B to S	t_R	0.158	0.116 + 0.021*SL	0.123 + 0.019*SL	0.130 + 0.019*SL
	t_F	0.167	0.124 + 0.022*SL	0.135 + 0.019*SL	0.157 + 0.017*SL
	t_{PLH}	0.746	0.714 + 0.016*SL	0.730 + 0.012*SL	0.756 + 0.010*SL
	t_{PHL}	0.749	0.712 + 0.018*SL	0.729 + 0.014*SL	0.763 + 0.011*SL
CI to S	t_R	0.159	0.115 + 0.022*SL	0.126 + 0.019*SL	0.135 + 0.019*SL
	t_F	0.199	0.156 + 0.022*SL	0.169 + 0.018*SL	0.192 + 0.016*SL
	t_{PLH}	0.729	0.696 + 0.016*SL	0.713 + 0.012*SL	0.740 + 0.010*SL
	t_{PHL}	0.682	0.646 + 0.018*SL	0.665 + 0.014*SL	0.699 + 0.011*SL
AN to CO	t_R	0.147	0.102 + 0.022*SL	0.112 + 0.020*SL	0.123 + 0.019*SL
	t_F	0.162	0.117 + 0.022*SL	0.129 + 0.019*SL	0.154 + 0.017*SL
	t_{PLH}	0.743	0.713 + 0.015*SL	0.728 + 0.011*SL	0.748 + 0.009*SL
	t_{PHL}	0.699	0.667 + 0.016*SL	0.682 + 0.012*SL	0.707 + 0.010*SL
B to CO	t_R	0.243	0.218 + 0.012*SL	0.206 + 0.016*SL	0.182 + 0.018*SL
	t_F	0.236	0.205 + 0.016*SL	0.207 + 0.015*SL	0.199 + 0.016*SL
	t_{PLH}	0.711	0.681 + 0.015*SL	0.696 + 0.011*SL	0.717 + 0.009*SL
	t_{PHL}	0.699	0.666 + 0.016*SL	0.682 + 0.012*SL	0.708 + 0.010*SL
CI to CO	t_R	0.158	0.114 + 0.022*SL	0.125 + 0.020*SL	0.136 + 0.019*SL
	t_F	0.196	0.151 + 0.022*SL	0.165 + 0.019*SL	0.189 + 0.017*SL
	t_{PLH}	0.425	0.392 + 0.017*SL	0.409 + 0.013*SL	0.438 + 0.010*SL
	t_{PHL}	0.496	0.455 + 0.021*SL	0.477 + 0.015*SL	0.518 + 0.012*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Cell List

Cell Name	Function Description
MX2DH	2 > 1 Non-Inverting Mux with 0.5X Drive
MX2	2 > 1 Non-Inverting Mux
MX2D2	2 > 1 Non-Inverting Mux with 2X Drive
MX2D4	2 > 1 Non-Inverting Mux with 4X Drive
MX2X4	4-Bit 2 > 1 Non-Inverting Mux
MX2IDH	2 > 1 Inverting Mux with 0.5X Drive
MX2I	2 > 1 Inverting Mux
MX2ID2	2 > 1 Inverting Mux with 2X Drive
MX2ID4	2 > 1 Inverting Mux with 4X Drive
MX2IDHA	2 > 1 Inverting Mux with Separate S and SN Inputs, 0.5X Drive
MX2IA	2 > 1 Inverting Mux with Separate S and SN Inputs
MX2ID2A	2 > 1 Inverting Mux with Separate S and SN Inputs, 2X Drive
MX2ID4A	2 > 1 Inverting Mux with Separate S and SN Inputs, 4X Drive
MX2IX4	4-Bit 2 > 1 Inverting Mux
MX3I	3 > 1 Inverting Mux
MX3ID2	3 > 1 Inverting Mux with 2X Drive
MX3ID4	3 > 1 Inverting Mux with 4X Drive
MX4	4 > 1 Non-Inverting Mux
MX4D2	4 > 1 Non-Inverting Mux with 2X Drive
MX4D4	4 > 1 Non-Inverting Mux with 4X Drive
MX8	8 > 1 Non-Inverting Mux
MX8D2	8 > 1 Non-Inverting Mux with 2X Drive
MX8D4	8 > 1 Non-inverting Mux with 4X Drive

MX2DH/MX2/MX2D2/MX2D4

2 > 1 Non-Inverting MUX with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

D0	D1	S	Y
0	x	0	0
1	x	0	1
x	0	1	0
x	1	1	1

Cell Data

Input Load (SL)											
MX2DH			*MX2*			*MX2D2*			*MX2D4*		
D0	D1	S	D0	D1	S	D0	D1	S	D0	D1	S
0.6	0.6	1.0	0.8	0.8	1.0	0.8	0.8	1.0	0.8	0.8	1.0
Gate Count											
MX2DH			*MX2*			*MX2D2*			*MX2D4*		
2.33			2.33			2.67			3.33		

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2DH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.268	0.107 + 0.080*SL	0.099 + 0.082*SL	0.088 + 0.084*SL
	t_F	0.238	0.113 + 0.063*SL	0.117 + 0.062*SL	0.107 + 0.063*SL
	t_{PLH}	0.351	0.268 + 0.041*SL	0.281 + 0.038*SL	0.285 + 0.038*SL
	t_{PHL}	0.373	0.289 + 0.042*SL	0.315 + 0.036*SL	0.329 + 0.034*SL
D1 to Y	t_R	0.267	0.107 + 0.080*SL	0.098 + 0.082*SL	0.087 + 0.084*SL
	t_F	0.237	0.112 + 0.063*SL	0.115 + 0.062*SL	0.106 + 0.063*SL
	t_{PLH}	0.353	0.270 + 0.041*SL	0.283 + 0.038*SL	0.287 + 0.038*SL
	t_{PHL}	0.378	0.294 + 0.042*SL	0.319 + 0.036*SL	0.333 + 0.034*SL
S to Y	t_R	0.268	0.106 + 0.081*SL	0.099 + 0.082*SL	0.088 + 0.084*SL
	t_F	0.235	0.108 + 0.063*SL	0.113 + 0.062*SL	0.104 + 0.063*SL
	t_{PLH}	0.364	0.281 + 0.041*SL	0.294 + 0.038*SL	0.298 + 0.038*SL
	t_{PHL}	0.359	0.276 + 0.042*SL	0.300 + 0.036*SL	0.314 + 0.034*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

MX2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.168	0.094 + 0.037*SL	0.094 + 0.037*SL	0.088 + 0.038*SL
	t_F	0.170	0.100 + 0.035*SL	0.109 + 0.033*SL	0.108 + 0.033*SL
	t_{PLH}	0.278	0.234 + 0.022*SL	0.247 + 0.019*SL	0.255 + 0.018*SL
	t_{PHL}	0.309	0.258 + 0.025*SL	0.277 + 0.021*SL	0.292 + 0.019*SL
D1 to Y	t_R	0.167	0.094 + 0.037*SL	0.093 + 0.037*SL	0.087 + 0.038*SL
	t_F	0.170	0.100 + 0.035*SL	0.109 + 0.033*SL	0.109 + 0.033*SL
	t_{PLH}	0.276	0.232 + 0.022*SL	0.245 + 0.019*SL	0.254 + 0.018*SL
	t_{PHL}	0.313	0.263 + 0.025*SL	0.281 + 0.021*SL	0.296 + 0.019*SL
S to Y	t_R	0.170	0.096 + 0.037*SL	0.096 + 0.037*SL	0.089 + 0.038*SL
	t_F	0.168	0.097 + 0.035*SL	0.108 + 0.033*SL	0.107 + 0.033*SL
	t_{PLH}	0.318	0.273 + 0.022*SL	0.287 + 0.019*SL	0.295 + 0.018*SL
	t_{PHL}	0.324	0.274 + 0.025*SL	0.292 + 0.021*SL	0.307 + 0.019*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.135	0.093 + 0.021*SL	0.101 + 0.019*SL	0.104 + 0.019*SL
	t_F	0.143	0.102 + 0.021*SL	0.116 + 0.017*SL	0.131 + 0.016*SL
	t_{PLH}	0.292	0.263 + 0.015*SL	0.277 + 0.011*SL	0.299 + 0.009*SL
	t_{PHL}	0.323	0.290 + 0.017*SL	0.306 + 0.013*SL	0.336 + 0.010*SL
D1 to Y	t_R	0.135	0.093 + 0.021*SL	0.101 + 0.019*SL	0.102 + 0.019*SL
	t_F	0.144	0.103 + 0.020*SL	0.117 + 0.017*SL	0.130 + 0.016*SL
	t_{PLH}	0.289	0.260 + 0.015*SL	0.274 + 0.011*SL	0.295 + 0.009*SL
	t_{PHL}	0.327	0.293 + 0.017*SL	0.310 + 0.013*SL	0.340 + 0.010*SL
S to Y	t_R	0.139	0.097 + 0.021*SL	0.105 + 0.019*SL	0.105 + 0.019*SL
	t_F	0.144	0.104 + 0.020*SL	0.115 + 0.017*SL	0.129 + 0.016*SL
	t_{PLH}	0.328	0.298 + 0.015*SL	0.313 + 0.011*SL	0.334 + 0.009*SL
	t_{PHL}	0.333	0.300 + 0.017*SL	0.317 + 0.013*SL	0.347 + 0.010*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

MX2D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.155	0.132 + 0.011*SL	0.136 + 0.010*SL	0.152 + 0.009*SL
	t_F	0.176	0.154 + 0.011*SL	0.159 + 0.010*SL	0.188 + 0.008*SL
	t_{PLH}	0.361	0.342 + 0.010*SL	0.353 + 0.007*SL	0.387 + 0.005*SL
	t_{PHL}	0.409	0.387 + 0.011*SL	0.400 + 0.008*SL	0.442 + 0.006*SL
D1 to Y	t_R	0.153	0.131 + 0.011*SL	0.134 + 0.010*SL	0.151 + 0.009*SL
	t_F	0.177	0.154 + 0.012*SL	0.161 + 0.010*SL	0.188 + 0.008*SL
	t_{PLH}	0.358	0.338 + 0.010*SL	0.349 + 0.007*SL	0.383 + 0.005*SL
	t_{PHL}	0.413	0.391 + 0.011*SL	0.403 + 0.008*SL	0.445 + 0.006*SL
S to Y	t_R	0.155	0.133 + 0.011*SL	0.136 + 0.010*SL	0.153 + 0.009*SL
	t_F	0.177	0.153 + 0.012*SL	0.162 + 0.010*SL	0.188 + 0.008*SL
	t_{PLH}	0.390	0.371 + 0.010*SL	0.382 + 0.007*SL	0.416 + 0.005*SL
	t_{PHL}	0.414	0.391 + 0.011*SL	0.404 + 0.008*SL	0.446 + 0.006*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

S	Y0	Y1	Y2	Y3
0	D00	D01	D02	D03
1	D10	D11	D12	D13

Cell Data

Input Load (SL)									Gate Count
D00	D10	D01	D11	D02	D12	D03	D13	S	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	3.4	8.67

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2X4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D00 to Y0	t_R	0.165	0.093 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.105 + 0.031*SL
	t_{PLH}	0.275	0.232 + 0.022*SL	0.245 + 0.018*SL	0.252 + 0.017*SL
	t_{PHL}	0.304	0.256 + 0.024*SL	0.274 + 0.020*SL	0.289 + 0.018*SL
D10 to Y0	t_R	0.165	0.092 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.163	0.097 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.276	0.233 + 0.022*SL	0.246 + 0.018*SL	0.254 + 0.017*SL
	t_{PHL}	0.309	0.260 + 0.024*SL	0.278 + 0.020*SL	0.293 + 0.018*SL
S to Y0	t_R	0.169	0.096 + 0.036*SL	0.096 + 0.036*SL	0.090 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.321	0.278 + 0.022*SL	0.291 + 0.018*SL	0.299 + 0.017*SL
	t_{PHL}	0.336	0.287 + 0.024*SL	0.305 + 0.020*SL	0.320 + 0.018*SL
D01 to Y1	t_R	0.165	0.093 + 0.036*SL	0.092 + 0.037*SL	0.087 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.276	0.232 + 0.022*SL	0.245 + 0.018*SL	0.254 + 0.017*SL
	t_{PHL}	0.305	0.257 + 0.024*SL	0.274 + 0.020*SL	0.290 + 0.018*SL
D11 to Y1	t_R	0.165	0.093 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.274	0.230 + 0.022*SL	0.243 + 0.018*SL	0.251 + 0.017*SL
	t_{PHL}	0.306	0.257 + 0.024*SL	0.275 + 0.020*SL	0.290 + 0.018*SL
S to Y1	t_R	0.169	0.096 + 0.036*SL	0.097 + 0.036*SL	0.090 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.107 + 0.031*SL	0.106 + 0.031*SL
	t_{PLH}	0.324	0.280 + 0.022*SL	0.294 + 0.019*SL	0.302 + 0.017*SL
	t_{PHL}	0.338	0.289 + 0.024*SL	0.307 + 0.020*SL	0.322 + 0.018*SL
D02 to Y2	t_R	0.165	0.093 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.164	0.099 + 0.033*SL	0.106 + 0.031*SL	0.106 + 0.031*SL
	t_{PLH}	0.275	0.232 + 0.021*SL	0.245 + 0.018*SL	0.253 + 0.017*SL
	t_{PHL}	0.305	0.256 + 0.024*SL	0.274 + 0.020*SL	0.289 + 0.018*SL
D12 to Y2	t_R	0.165	0.093 + 0.036*SL	0.092 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.164	0.097 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.277	0.234 + 0.022*SL	0.246 + 0.018*SL	0.254 + 0.017*SL
	t_{PHL}	0.309	0.261 + 0.024*SL	0.278 + 0.020*SL	0.293 + 0.018*SL
S to Y2	t_R	0.169	0.097 + 0.036*SL	0.097 + 0.036*SL	0.090 + 0.037*SL
	t_F	0.165	0.098 + 0.033*SL	0.107 + 0.031*SL	0.108 + 0.031*SL
	t_{PLH}	0.321	0.278 + 0.022*SL	0.291 + 0.018*SL	0.299 + 0.017*SL
	t_{PHL}	0.336	0.287 + 0.024*SL	0.305 + 0.020*SL	0.320 + 0.018*SL
D03 to Y3	t_R	0.165	0.093 + 0.036*SL	0.092 + 0.037*SL	0.087 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.276	0.232 + 0.022*SL	0.245 + 0.018*SL	0.253 + 0.017*SL
	t_{PHL}	0.305	0.256 + 0.024*SL	0.274 + 0.020*SL	0.290 + 0.018*SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2X4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D13 to Y3	t_R	0.165	0.093 + 0.036*SL	0.091 + 0.037*SL	0.086 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.106 + 0.031*SL	0.107 + 0.031*SL
	t_{PLH}	0.274	0.230 + 0.022*SL	0.243 + 0.018*SL	0.251 + 0.017*SL
	t_{PHL}	0.306	0.257 + 0.024*SL	0.275 + 0.020*SL	0.290 + 0.018*SL
S to Y3	t_R	0.169	0.096 + 0.036*SL	0.097 + 0.036*SL	0.090 + 0.037*SL
	t_F	0.164	0.098 + 0.033*SL	0.107 + 0.031*SL	0.106 + 0.031*SL
	t_{PLH}	0.324	0.280 + 0.022*SL	0.294 + 0.019*SL	0.302 + 0.017*SL
	t_{PHL}	0.338	0.289 + 0.024*SL	0.307 + 0.020*SL	0.322 + 0.018*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

MX2IDH/MX2I/MX2ID2/MX2ID4

2 > 1 Inverting MUX with 0.5X/1X/2X/4X Drive

Logic Symbol



Truth Table

D0	D1	S	YN
0	x	0	1
1	x	0	0
x	0	1	1
x	1	1	0

Cell Data

Input Load (SL)											
MX2IDH			*MX2I*			*MX2ID2*			*MX2ID4*		
D0	D1	S	D0	D1	S	D0	D1	S	D0	D1	S
0.5	0.6	1.0	1.0	1.1	1.5	1.0	1.1	1.5	1.0	1.1	1.5

Gate Count			
MX2IDH	*MX2I*	*MX2ID2*	*MX2ID4*
2.00	2.00	3.00	3.67

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2IDH

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.623	0.281 + 0.171*SL	0.265 + 0.175*SL	0.267 + 0.174*SL
	t_F	0.443	0.224 + 0.109*SL	0.203 + 0.115*SL	0.189 + 0.116*SL
	t_{PLH}	0.346	0.187 + 0.080*SL	0.190 + 0.079*SL	0.192 + 0.078*SL
	t_{PHL}	0.245	0.130 + 0.057*SL	0.131 + 0.057*SL	0.132 + 0.057*SL
D1 to YN	t_R	0.597	0.252 + 0.173*SL	0.244 + 0.175*SL	0.242 + 0.175*SL
	t_F	0.487	0.265 + 0.111*SL	0.247 + 0.115*SL	0.236 + 0.117*SL
	t_{PLH}	0.383	0.223 + 0.080*SL	0.227 + 0.079*SL	0.229 + 0.079*SL
	t_{PHL}	0.306	0.189 + 0.058*SL	0.194 + 0.057*SL	0.197 + 0.057*SL
S to YN	t_R	0.621	0.276 + 0.173*SL	0.269 + 0.174*SL	0.268 + 0.174*SL
	t_F	0.447	0.216 + 0.116*SL	0.209 + 0.118*SL	0.210 + 0.117*SL
	t_{PLH}	0.386	0.227 + 0.079*SL	0.230 + 0.079*SL	0.232 + 0.078*SL
	t_{PHL}	0.337	0.223 + 0.057*SL	0.225 + 0.056*SL	0.226 + 0.056*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

MX2I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.344	0.199 + 0.072*SL	0.190 + 0.075*SL	0.176 + 0.076*SL
	t_F	0.254	0.155 + 0.049*SL	0.144 + 0.052*SL	0.133 + 0.053*SL
	t_{PLH}	0.200	0.131 + 0.034*SL	0.130 + 0.035*SL	0.131 + 0.034*SL
	t_{PHL}	0.162	0.105 + 0.028*SL	0.110 + 0.027*SL	0.112 + 0.027*SL
D1 to YN	t_R	0.345	0.193 + 0.076*SL	0.188 + 0.077*SL	0.181 + 0.078*SL
	t_F	0.324	0.225 + 0.049*SL	0.215 + 0.052*SL	0.202 + 0.053*SL
	t_{PLH}	0.254	0.181 + 0.036*SL	0.184 + 0.036*SL	0.186 + 0.035*SL
	t_{PHL}	0.222	0.167 + 0.028*SL	0.170 + 0.027*SL	0.173 + 0.027*SL
S to YN	t_R	0.337	0.182 + 0.077*SL	0.179 + 0.078*SL	0.176 + 0.079*SL
	t_F	0.277	0.174 + 0.052*SL	0.167 + 0.053*SL	0.158 + 0.055*SL
	t_{PLH}	0.294	0.223 + 0.036*SL	0.224 + 0.035*SL	0.225 + 0.035*SL
	t_{PHL}	0.281	0.225 + 0.028*SL	0.230 + 0.027*SL	0.232 + 0.026*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2ID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.105	0.069 + 0.018*SL	0.069 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.098	0.065 + 0.016*SL	0.067 + 0.016*SL	0.063 + 0.016*SL
	t_{PLH}	0.353	0.329 + 0.012*SL	0.339 + 0.009*SL	0.346 + 0.009*SL
	t_{PHL}	0.333	0.307 + 0.013*SL	0.319 + 0.010*SL	0.331 + 0.009*SL
D1 to YN	t_R	0.106	0.070 + 0.018*SL	0.069 + 0.018*SL	0.059 + 0.019*SL
	t_F	0.099	0.066 + 0.016*SL	0.069 + 0.016*SL	0.065 + 0.016*SL
	t_{PLH}	0.407	0.384 + 0.012*SL	0.394 + 0.009*SL	0.401 + 0.009*SL
	t_{PHL}	0.400	0.375 + 0.013*SL	0.387 + 0.010*SL	0.399 + 0.009*SL
S to YN	t_R	0.106	0.069 + 0.018*SL	0.069 + 0.018*SL	0.059 + 0.019*SL
	t_F	0.097	0.064 + 0.017*SL	0.067 + 0.016*SL	0.064 + 0.016*SL
	t_{PLH}	0.449	0.425 + 0.012*SL	0.435 + 0.009*SL	0.443 + 0.009*SL
	t_{PHL}	0.442	0.417 + 0.013*SL	0.428 + 0.010*SL	0.440 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

MX2ID4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.105	0.086 + 0.010*SL	0.088 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.103	0.082 + 0.010*SL	0.090 + 0.008*SL	0.095 + 0.008*SL
	t_{PLH}	0.403	0.388 + 0.008*SL	0.396 + 0.006*SL	0.415 + 0.005*SL
	t_{PHL}	0.390	0.373 + 0.008*SL	0.383 + 0.006*SL	0.408 + 0.005*SL
D1 to YN	t_R	0.105	0.085 + 0.010*SL	0.090 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.105	0.084 + 0.010*SL	0.092 + 0.008*SL	0.097 + 0.008*SL
	t_{PLH}	0.456	0.441 + 0.008*SL	0.450 + 0.006*SL	0.469 + 0.005*SL
	t_{PHL}	0.456	0.440 + 0.008*SL	0.449 + 0.006*SL	0.474 + 0.005*SL
S to YN	t_R	0.106	0.085 + 0.010*SL	0.090 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.102	0.083 + 0.010*SL	0.088 + 0.009*SL	0.096 + 0.008*SL
	t_{PLH}	0.498	0.482 + 0.008*SL	0.491 + 0.006*SL	0.510 + 0.005*SL
	t_{PHL}	0.496	0.479 + 0.008*SL	0.489 + 0.006*SL	0.513 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

D0	D1	S	SN	YN
0	x	0	1	1
1	x	0	1	0
x	0	1	0	1
x	1	1	0	0

Cell Data

Input Load (SL)															
MX2IDHA				*MX2IA*				*MX2ID2A*				*MX2ID4A*			
D0	D1	S	SN	D0	D1	S	SN	D0	D1	S	SN	D0	D1	S	SN
0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.0	1.2	1.0	1.1	1.0	1.1	1.0	1.0

Gate Count			
MX2IDHA	*MX2IA*	*MX2ID2A*	*MX2ID4A*
1.67	1.67	2.67	3.33

Schematic Diagram



2 > 1 Inverting MUX with Separate S and SN Inputs, 0.5X/1X/2X/4X Drive

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2IDHA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.578	0.237 + 0.170*SL	0.218 + 0.175*SL	0.220 + 0.175*SL
	t_F	0.387	0.168 + 0.110*SL	0.148 + 0.115*SL	0.134 + 0.117*SL
	t_{PLH}	0.304	0.146 + 0.079*SL	0.148 + 0.079*SL	0.149 + 0.078*SL
	t_{PHL}	0.237	0.122 + 0.057*SL	0.124 + 0.057*SL	0.127 + 0.056*SL
D1 to YN	t_R	0.580	0.236 + 0.172*SL	0.228 + 0.174*SL	0.225 + 0.174*SL
	t_F	0.457	0.232 + 0.112*SL	0.218 + 0.116*SL	0.211 + 0.117*SL
	t_{PLH}	0.381	0.222 + 0.080*SL	0.225 + 0.079*SL	0.227 + 0.078*SL
	t_{PHL}	0.311	0.194 + 0.059*SL	0.200 + 0.057*SL	0.204 + 0.057*SL
S to YN	t_R	0.609	0.264 + 0.172*SL	0.257 + 0.174*SL	0.255 + 0.174*SL
	t_F	0.454	0.226 + 0.114*SL	0.219 + 0.116*SL	0.212 + 0.117*SL
	t_{PLH}	0.402	0.244 + 0.079*SL	0.246 + 0.079*SL	0.248 + 0.078*SL
	t_{PHL}	0.307	0.189 + 0.059*SL	0.196 + 0.057*SL	0.201 + 0.057*SL
SN to YN	t_R	0.607	0.266 + 0.171*SL	0.248 + 0.175*SL	0.250 + 0.175*SL
	t_F	0.382	0.157 + 0.112*SL	0.145 + 0.115*SL	0.135 + 0.116*SL
	t_{PLH}	0.325	0.167 + 0.079*SL	0.168 + 0.079*SL	0.169 + 0.078*SL
	t_{PHL}	0.232	0.117 + 0.058*SL	0.120 + 0.057*SL	0.123 + 0.056*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

MX2IA

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.355	0.208 + 0.074*SL	0.199 + 0.076*SL	0.186 + 0.078*SL
	t_F	0.255	0.157 + 0.049*SL	0.145 + 0.052*SL	0.134 + 0.053*SL
	t_{PLH}	0.202	0.133 + 0.035*SL	0.131 + 0.035*SL	0.132 + 0.035*SL
	t_{PHL}	0.164	0.108 + 0.028*SL	0.113 + 0.027*SL	0.114 + 0.027*SL
D1 to YN	t_R	0.351	0.201 + 0.075*SL	0.193 + 0.077*SL	0.187 + 0.078*SL
	t_F	0.312	0.210 + 0.051*SL	0.203 + 0.053*SL	0.194 + 0.054*SL
	t_{PLH}	0.260	0.188 + 0.036*SL	0.190 + 0.035*SL	0.192 + 0.035*SL
	t_{PHL}	0.232	0.176 + 0.028*SL	0.179 + 0.027*SL	0.183 + 0.027*SL
S to YN	t_R	0.376	0.225 + 0.076*SL	0.219 + 0.077*SL	0.213 + 0.078*SL
	t_F	0.306	0.201 + 0.052*SL	0.198 + 0.053*SL	0.192 + 0.054*SL
	t_{PLH}	0.280	0.209 + 0.036*SL	0.210 + 0.035*SL	0.212 + 0.035*SL
	t_{PHL}	0.227	0.170 + 0.028*SL	0.174 + 0.027*SL	0.178 + 0.027*SL
SN to YN	t_R	0.381	0.233 + 0.074*SL	0.224 + 0.076*SL	0.212 + 0.078*SL
	t_F	0.246	0.144 + 0.051*SL	0.136 + 0.053*SL	0.128 + 0.054*SL
	t_{PLH}	0.221	0.152 + 0.035*SL	0.150 + 0.035*SL	0.151 + 0.035*SL
	t_{PHL}	0.158	0.102 + 0.028*SL	0.107 + 0.027*SL	0.109 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2ID2A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.109	0.073 + 0.018*SL	0.072 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.099	0.065 + 0.017*SL	0.071 + 0.015*SL	0.067 + 0.016*SL
	t_{PLH}	0.365	0.341 + 0.012*SL	0.351 + 0.010*SL	0.360 + 0.009*SL
	t_{PHL}	0.341	0.315 + 0.013*SL	0.328 + 0.010*SL	0.341 + 0.009*SL
D1 to YN	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.063 + 0.019*SL
	t_F	0.100	0.067 + 0.016*SL	0.071 + 0.015*SL	0.067 + 0.016*SL
	t_{PLH}	0.409	0.385 + 0.012*SL	0.395 + 0.010*SL	0.404 + 0.009*SL
	t_{PHL}	0.402	0.377 + 0.013*SL	0.389 + 0.010*SL	0.403 + 0.009*SL
S to YN	t_R	0.109	0.072 + 0.018*SL	0.073 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.099	0.065 + 0.017*SL	0.070 + 0.015*SL	0.068 + 0.016*SL
	t_{PLH}	0.432	0.408 + 0.012*SL	0.418 + 0.010*SL	0.427 + 0.009*SL
	t_{PHL}	0.397	0.371 + 0.013*SL	0.383 + 0.010*SL	0.397 + 0.009*SL
SN to YN	t_R	0.109	0.073 + 0.018*SL	0.073 + 0.018*SL	0.062 + 0.019*SL
	t_F	0.099	0.066 + 0.016*SL	0.070 + 0.015*SL	0.067 + 0.016*SL
	t_{PLH}	0.391	0.367 + 0.012*SL	0.377 + 0.010*SL	0.386 + 0.009*SL
	t_{PHL}	0.335	0.310 + 0.013*SL	0.322 + 0.010*SL	0.335 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

MX2ID4A

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.097	0.077 + 0.010*SL	0.082 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.087	0.069 + 0.009*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.390	0.375 + 0.007*SL	0.383 + 0.005*SL	0.398 + 0.004*SL
	t_{PHL}	0.352	0.336 + 0.008*SL	0.345 + 0.006*SL	0.363 + 0.005*SL
D1 to YN	t_R	0.098	0.078 + 0.010*SL	0.081 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.088	0.069 + 0.010*SL	0.075 + 0.008*SL	0.074 + 0.008*SL
	t_{PLH}	0.433	0.419 + 0.007*SL	0.426 + 0.005*SL	0.442 + 0.004*SL
	t_{PHL}	0.412	0.397 + 0.008*SL	0.406 + 0.006*SL	0.424 + 0.005*SL
S to YN	t_R	0.098	0.080 + 0.009*SL	0.081 + 0.009*SL	0.073 + 0.009*SL
	t_F	0.086	0.066 + 0.010*SL	0.074 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.457	0.442 + 0.007*SL	0.450 + 0.005*SL	0.466 + 0.004*SL
	t_{PHL}	0.407	0.392 + 0.008*SL	0.400 + 0.006*SL	0.419 + 0.005*SL
SN to YN	t_R	0.098	0.079 + 0.010*SL	0.081 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.086	0.067 + 0.010*SL	0.073 + 0.008*SL	0.073 + 0.008*SL
	t_{PLH}	0.416	0.401 + 0.007*SL	0.409 + 0.005*SL	0.425 + 0.004*SL
	t_{PHL}	0.346	0.330 + 0.008*SL	0.339 + 0.006*SL	0.357 + 0.005*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

MX2IX4

4-Bit 2 > 1 Inverting MUX

Logic Symbol



Truth Table

S	YN0	YN1	YN2	YN3
0	$\overline{D00}$	$\overline{D01}$	$\overline{D02}$	$\overline{D03}$
1	$\overline{D10}$	$\overline{D11}$	$\overline{D12}$	$\overline{D13}$

Cell Data

Input Load (SL)									Gate Count
D00	D10	D01	D11	D02	D12	D03	D13	S	
1.0	1.1	1.0	1.1	1.0	1.1	1.0	1.1	5.3	6.00

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2IX4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D00 to YN0	t_R	0.344	0.198 + 0.073*SL	0.189 + 0.075*SL	0.175 + 0.077*SL
	t_F	0.253	0.155 + 0.049*SL	0.144 + 0.052*SL	0.132 + 0.053*SL
	t_{PLH}	0.202	0.132 + 0.035*SL	0.131 + 0.035*SL	0.132 + 0.035*SL
	t_{PHL}	0.161	0.104 + 0.028*SL	0.110 + 0.027*SL	0.111 + 0.027*SL
D10 to YN0	t_R	0.341	0.190 + 0.075*SL	0.183 + 0.077*SL	0.176 + 0.078*SL
	t_F	0.327	0.226 + 0.050*SL	0.215 + 0.053*SL	0.203 + 0.055*SL
	t_{PLH}	0.249	0.177 + 0.036*SL	0.179 + 0.035*SL	0.182 + 0.035*SL
	t_{PHL}	0.224	0.167 + 0.028*SL	0.170 + 0.028*SL	0.173 + 0.027*SL
S to YN0	t_R	0.337	0.187 + 0.075*SL	0.178 + 0.077*SL	0.172 + 0.078*SL
	t_F	0.276	0.168 + 0.054*SL	0.167 + 0.054*SL	0.158 + 0.055*SL
	t_{PLH}	0.345	0.275 + 0.035*SL	0.276 + 0.035*SL	0.275 + 0.035*SL
	t_{PHL}	0.287	0.229 + 0.029*SL	0.236 + 0.027*SL	0.240 + 0.027*SL
D01 to YN1	t_R	0.344	0.197 + 0.074*SL	0.188 + 0.076*SL	0.174 + 0.078*SL
	t_F	0.252	0.155 + 0.049*SL	0.143 + 0.052*SL	0.130 + 0.053*SL
	t_{PLH}	0.202	0.132 + 0.035*SL	0.132 + 0.035*SL	0.132 + 0.035*SL
	t_{PHL}	0.160	0.104 + 0.028*SL	0.109 + 0.027*SL	0.111 + 0.027*SL
D11 to YN1	t_R	0.341	0.190 + 0.075*SL	0.183 + 0.077*SL	0.176 + 0.078*SL
	t_F	0.319	0.221 + 0.049*SL	0.210 + 0.052*SL	0.199 + 0.053*SL
	t_{PLH}	0.249	0.177 + 0.036*SL	0.179 + 0.035*SL	0.181 + 0.035*SL
	t_{PHL}	0.220	0.164 + 0.028*SL	0.167 + 0.027*SL	0.170 + 0.027*SL
S to YN1	t_R	0.337	0.187 + 0.075*SL	0.178 + 0.077*SL	0.172 + 0.078*SL
	t_F	0.269	0.164 + 0.053*SL	0.162 + 0.053*SL	0.154 + 0.054*SL
	t_{PLH}	0.345	0.275 + 0.035*SL	0.276 + 0.035*SL	0.275 + 0.035*SL
	t_{PHL}	0.287	0.229 + 0.029*SL	0.236 + 0.027*SL	0.240 + 0.027*SL
D02 to YN2	t_R	0.348	0.199 + 0.074*SL	0.189 + 0.077*SL	0.176 + 0.078*SL
	t_F	0.253	0.155 + 0.049*SL	0.143 + 0.052*SL	0.131 + 0.053*SL
	t_{PLH}	0.204	0.134 + 0.035*SL	0.133 + 0.035*SL	0.134 + 0.035*SL
	t_{PHL}	0.161	0.104 + 0.028*SL	0.110 + 0.027*SL	0.111 + 0.027*SL
D12 to YN2	t_R	0.342	0.191 + 0.076*SL	0.184 + 0.077*SL	0.177 + 0.078*SL
	t_F	0.318	0.219 + 0.049*SL	0.209 + 0.052*SL	0.198 + 0.053*SL
	t_{PLH}	0.249	0.176 + 0.036*SL	0.179 + 0.036*SL	0.181 + 0.035*SL
	t_{PHL}	0.219	0.163 + 0.028*SL	0.166 + 0.027*SL	0.169 + 0.027*SL
S to YN2	t_R	0.339	0.188 + 0.075*SL	0.179 + 0.077*SL	0.174 + 0.078*SL
	t_F	0.268	0.163 + 0.053*SL	0.160 + 0.053*SL	0.153 + 0.054*SL
	t_{PLH}	0.346	0.276 + 0.035*SL	0.277 + 0.035*SL	0.276 + 0.035*SL
	t_{PHL}	0.287	0.230 + 0.029*SL	0.237 + 0.027*SL	0.241 + 0.027*SL
D03 to YN3	t_R	0.348	0.199 + 0.074*SL	0.189 + 0.077*SL	0.176 + 0.079*SL
	t_F	0.253	0.155 + 0.049*SL	0.143 + 0.052*SL	0.130 + 0.053*SL
	t_{PLH}	0.204	0.133 + 0.035*SL	0.133 + 0.036*SL	0.133 + 0.035*SL
	t_{PHL}	0.160	0.104 + 0.028*SL	0.109 + 0.027*SL	0.111 + 0.027*SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX2IX4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D13 to YN3	t_R	0.340	0.190 + 0.075*SL	0.182 + 0.077*SL	0.176 + 0.078*SL
	t_F	0.318	0.219 + 0.049*SL	0.209 + 0.052*SL	0.197 + 0.053*SL
	t_{PLH}	0.248	0.176 + 0.036*SL	0.178 + 0.035*SL	0.180 + 0.035*SL
	t_{PHL}	0.219	0.163 + 0.028*SL	0.166 + 0.027*SL	0.169 + 0.027*SL
S to YN3	t_R	0.335	0.181 + 0.077*SL	0.176 + 0.078*SL	0.169 + 0.079*SL
	t_F	0.268	0.162 + 0.053*SL	0.160 + 0.053*SL	0.152 + 0.054*SL
	t_{PLH}	0.346	0.276 + 0.035*SL	0.276 + 0.035*SL	0.276 + 0.035*SL
	t_{PHL}	0.287	0.229 + 0.029*SL	0.237 + 0.027*SL	0.241 + 0.027*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Logic Symbol



Truth Table

S0	S1	YN
0	0	$\overline{D0}$
1	0	$\overline{D1}$
x	1	$\overline{D2}$

Cell Data

Input Load (SL)														
MX3I					*MX3ID2*					*MX3ID4*				
D0	D1	D2	S0	S1	D0	D1	D2	S0	S1	D0	D1	D2	S0	S1
0.8	0.8	0.8	1.0	1.0	0.8	0.8	0.8	1.0	1.0	0.8	0.8	0.8	1.0	1.0

Gate Count		
MX3I	*MX3ID2*	*MX3ID4*
5.00	5.33	6.00

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX3I

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.154	0.083 + 0.036*SL	0.074 + 0.038*SL	0.067 + 0.039*SL
	t_F	0.130	0.069 + 0.030*SL	0.067 + 0.031*SL	0.061 + 0.032*SL
	t_{PLH}	0.522	0.483 + 0.020*SL	0.490 + 0.018*SL	0.492 + 0.018*SL
	t_{PHL}	0.505	0.466 + 0.020*SL	0.475 + 0.017*SL	0.480 + 0.017*SL
D1 to YN	t_R	0.154	0.083 + 0.036*SL	0.074 + 0.038*SL	0.066 + 0.039*SL
	t_F	0.130	0.069 + 0.031*SL	0.067 + 0.031*SL	0.062 + 0.032*SL
	t_{PLH}	0.526	0.486 + 0.020*SL	0.494 + 0.018*SL	0.496 + 0.018*SL
	t_{PHL}	0.500	0.460 + 0.020*SL	0.470 + 0.017*SL	0.475 + 0.017*SL
D2 to YN	t_R	0.145	0.071 + 0.037*SL	0.066 + 0.038*SL	0.059 + 0.039*SL
	t_F	0.125	0.064 + 0.031*SL	0.060 + 0.031*SL	0.056 + 0.032*SL
	t_{PLH}	0.365	0.327 + 0.019*SL	0.332 + 0.018*SL	0.334 + 0.018*SL
	t_{PHL}	0.350	0.311 + 0.019*SL	0.319 + 0.017*SL	0.323 + 0.017*SL
S0 to YN	t_R	0.154	0.083 + 0.036*SL	0.074 + 0.038*SL	0.067 + 0.039*SL
	t_F	0.130	0.069 + 0.031*SL	0.067 + 0.031*SL	0.062 + 0.032*SL
	t_{PLH}	0.533	0.494 + 0.020*SL	0.501 + 0.018*SL	0.503 + 0.018*SL
	t_{PHL}	0.541	0.501 + 0.020*SL	0.511 + 0.017*SL	0.515 + 0.017*SL
S1 to YN	t_R	0.148	0.075 + 0.037*SL	0.070 + 0.038*SL	0.062 + 0.039*SL
	t_F	0.129	0.068 + 0.030*SL	0.066 + 0.031*SL	0.059 + 0.032*SL
	t_{PLH}	0.388	0.349 + 0.020*SL	0.356 + 0.018*SL	0.358 + 0.018*SL
	t_{PHL}	0.430	0.391 + 0.020*SL	0.400 + 0.017*SL	0.405 + 0.017*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX3ID2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.117	0.081 + 0.018*SL	0.081 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.102	0.069 + 0.016*SL	0.074 + 0.015*SL	0.070 + 0.016*SL
	t_{PLH}	0.540	0.515 + 0.013*SL	0.526 + 0.010*SL	0.536 + 0.009*SL
	t_{PHL}	0.520	0.494 + 0.013*SL	0.506 + 0.010*SL	0.520 + 0.009*SL
D1 to YN	t_R	0.117	0.081 + 0.018*SL	0.079 + 0.018*SL	0.070 + 0.019*SL
	t_F	0.101	0.068 + 0.017*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.543	0.518 + 0.013*SL	0.530 + 0.010*SL	0.540 + 0.009*SL
	t_{PHL}	0.515	0.489 + 0.013*SL	0.501 + 0.010*SL	0.515 + 0.009*SL
D2 to YN	t_R	0.106	0.070 + 0.018*SL	0.069 + 0.018*SL	0.058 + 0.019*SL
	t_F	0.096	0.064 + 0.016*SL	0.066 + 0.015*SL	0.063 + 0.016*SL
	t_{PLH}	0.374	0.351 + 0.012*SL	0.360 + 0.009*SL	0.368 + 0.009*SL
	t_{PHL}	0.358	0.333 + 0.013*SL	0.345 + 0.010*SL	0.357 + 0.009*SL
S0 to YN	t_R	0.118	0.082 + 0.018*SL	0.082 + 0.018*SL	0.069 + 0.019*SL
	t_F	0.103	0.071 + 0.016*SL	0.074 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.551	0.526 + 0.013*SL	0.537 + 0.010*SL	0.547 + 0.009*SL
	t_{PHL}	0.555	0.529 + 0.013*SL	0.542 + 0.010*SL	0.556 + 0.009*SL
S1 to YN	t_R	0.113	0.077 + 0.018*SL	0.076 + 0.018*SL	0.066 + 0.019*SL
	t_F	0.102	0.070 + 0.016*SL	0.073 + 0.015*SL	0.069 + 0.016*SL
	t_{PLH}	0.403	0.378 + 0.012*SL	0.389 + 0.010*SL	0.398 + 0.009*SL
	t_{PHL}	0.444	0.418 + 0.013*SL	0.431 + 0.010*SL	0.445 + 0.009*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX3ID4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to YN	t_R	0.112	0.092 + 0.010*SL	0.096 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.094	0.075 + 0.009*SL	0.081 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.594	0.579 + 0.008*SL	0.588 + 0.006*SL	0.607 + 0.005*SL
	t_{PHL}	0.550	0.535 + 0.008*SL	0.543 + 0.006*SL	0.564 + 0.004*SL
D1 to YN	t_R	0.111	0.090 + 0.010*SL	0.096 + 0.009*SL	0.088 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.080 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.598	0.582 + 0.008*SL	0.591 + 0.006*SL	0.610 + 0.005*SL
	t_{PHL}	0.545	0.529 + 0.008*SL	0.538 + 0.006*SL	0.559 + 0.004*SL
D2 to YN	t_R	0.099	0.079 + 0.010*SL	0.083 + 0.009*SL	0.074 + 0.009*SL
	t_F	0.087	0.069 + 0.009*SL	0.073 + 0.008*SL	0.075 + 0.008*SL
	t_{PLH}	0.413	0.399 + 0.007*SL	0.407 + 0.005*SL	0.422 + 0.004*SL
	t_{PHL}	0.380	0.365 + 0.007*SL	0.374 + 0.005*SL	0.393 + 0.004*SL
S0 to YN	t_R	0.112	0.092 + 0.010*SL	0.096 + 0.009*SL	0.087 + 0.009*SL
	t_F	0.094	0.076 + 0.009*SL	0.083 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.605	0.589 + 0.008*SL	0.598 + 0.006*SL	0.617 + 0.005*SL
	t_{PHL}	0.585	0.570 + 0.008*SL	0.578 + 0.006*SL	0.599 + 0.004*SL
S1 to YN	t_R	0.108	0.088 + 0.010*SL	0.092 + 0.009*SL	0.085 + 0.009*SL
	t_F	0.093	0.074 + 0.010*SL	0.082 + 0.008*SL	0.082 + 0.008*SL
	t_{PLH}	0.459	0.444 + 0.008*SL	0.453 + 0.005*SL	0.471 + 0.005*SL
	t_{PHL}	0.473	0.457 + 0.008*SL	0.466 + 0.006*SL	0.487 + 0.004*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

S0	S1	Y
0	0	D0
1	0	D1
0	1	D2
1	1	D3

Cell Data

Input Load (SL)																	
MX4						*MX4D2*						*MX4D4*					
D0	D1	D2	D3	S0	S1	D0	D1	D2	D3	S0	S1	D0	D1	D2	D3	S0	S1
0.8	0.8	0.8	0.8	1.9	1.0	0.8	0.8	0.8	0.8	1.9	1.0	0.8	0.8	0.8	0.8	1.9	1.0

Gate Count		
MX4	*MX4*D2	*MX4*D4
5.67	6.00	6.67

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.205	0.124 + 0.041*SL	0.136 + 0.038*SL	0.137 + 0.038*SL
	t_F	0.233	0.154 + 0.039*SL	0.173 + 0.035*SL	0.186 + 0.033*SL
	t_{PLH}	0.431	0.377 + 0.027*SL	0.397 + 0.022*SL	0.416 + 0.019*SL
	t_{PHL}	0.479	0.415 + 0.032*SL	0.442 + 0.025*SL	0.470 + 0.022*SL
D1 to Y	t_R	0.205	0.124 + 0.041*SL	0.136 + 0.038*SL	0.136 + 0.038*SL
	t_F	0.232	0.154 + 0.039*SL	0.172 + 0.035*SL	0.186 + 0.033*SL
	t_{PLH}	0.430	0.376 + 0.027*SL	0.396 + 0.022*SL	0.415 + 0.019*SL
	t_{PHL}	0.480	0.416 + 0.032*SL	0.443 + 0.025*SL	0.471 + 0.022*SL
D2 to Y	t_R	0.204	0.123 + 0.040*SL	0.135 + 0.038*SL	0.136 + 0.038*SL
	t_F	0.229	0.151 + 0.039*SL	0.170 + 0.034*SL	0.182 + 0.033*SL
	t_{PLH}	0.424	0.370 + 0.027*SL	0.390 + 0.022*SL	0.409 + 0.019*SL
	t_{PHL}	0.475	0.411 + 0.032*SL	0.438 + 0.025*SL	0.465 + 0.022*SL
D3 to Y	t_R	0.204	0.124 + 0.040*SL	0.134 + 0.038*SL	0.136 + 0.038*SL
	t_F	0.230	0.152 + 0.039*SL	0.170 + 0.034*SL	0.182 + 0.033*SL
	t_{PLH}	0.421	0.367 + 0.027*SL	0.388 + 0.022*SL	0.406 + 0.019*SL
	t_{PHL}	0.476	0.413 + 0.032*SL	0.439 + 0.025*SL	0.467 + 0.022*SL
S0 to Y	t_R	0.206	0.125 + 0.041*SL	0.138 + 0.038*SL	0.138 + 0.038*SL
	t_F	0.232	0.153 + 0.039*SL	0.173 + 0.034*SL	0.186 + 0.033*SL
	t_{PLH}	0.470	0.416 + 0.027*SL	0.437 + 0.022*SL	0.456 + 0.019*SL
	t_{PHL}	0.497	0.434 + 0.032*SL	0.460 + 0.025*SL	0.489 + 0.022*SL
S1 to Y	t_R	0.197	0.115 + 0.041*SL	0.127 + 0.038*SL	0.130 + 0.038*SL
	t_F	0.211	0.131 + 0.040*SL	0.150 + 0.035*SL	0.167 + 0.033*SL
	t_{PLH}	0.346	0.293 + 0.026*SL	0.312 + 0.022*SL	0.330 + 0.019*SL
	t_{PHL}	0.365	0.303 + 0.031*SL	0.328 + 0.025*SL	0.355 + 0.021*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 8, *Group3 : 8 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX4D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.176	0.131 + 0.023*SL	0.140 + 0.020*SL	0.157 + 0.019*SL
	t_F	0.217	0.171 + 0.023*SL	0.186 + 0.019*SL	0.212 + 0.017*SL
	t_{PLH}	0.457	0.422 + 0.018*SL	0.440 + 0.013*SL	0.471 + 0.011*SL
	t_{PHL}	0.512	0.469 + 0.022*SL	0.492 + 0.016*SL	0.534 + 0.012*SL
D1 to Y	t_R	0.176	0.130 + 0.023*SL	0.140 + 0.020*SL	0.156 + 0.019*SL
	t_F	0.216	0.170 + 0.023*SL	0.185 + 0.019*SL	0.212 + 0.017*SL
	t_{PLH}	0.456	0.421 + 0.018*SL	0.439 + 0.013*SL	0.470 + 0.011*SL
	t_{PHL}	0.513	0.470 + 0.021*SL	0.493 + 0.016*SL	0.535 + 0.012*SL
D2 to Y	t_R	0.176	0.130 + 0.023*SL	0.140 + 0.020*SL	0.156 + 0.019*SL
	t_F	0.214	0.168 + 0.023*SL	0.182 + 0.019*SL	0.210 + 0.017*SL
	t_{PLH}	0.450	0.415 + 0.018*SL	0.432 + 0.013*SL	0.464 + 0.011*SL
	t_{PHL}	0.508	0.465 + 0.021*SL	0.488 + 0.016*SL	0.529 + 0.012*SL
D3 to Y	t_R	0.175	0.129 + 0.023*SL	0.141 + 0.020*SL	0.155 + 0.019*SL
	t_F	0.214	0.169 + 0.023*SL	0.183 + 0.019*SL	0.210 + 0.017*SL
	t_{PLH}	0.447	0.412 + 0.018*SL	0.430 + 0.013*SL	0.461 + 0.011*SL
	t_{PHL}	0.510	0.467 + 0.021*SL	0.490 + 0.016*SL	0.531 + 0.012*SL
S0 to Y	t_R	0.177	0.132 + 0.023*SL	0.141 + 0.020*SL	0.158 + 0.019*SL
	t_F	0.215	0.169 + 0.023*SL	0.183 + 0.020*SL	0.212 + 0.017*SL
	t_{PLH}	0.496	0.460 + 0.018*SL	0.478 + 0.013*SL	0.510 + 0.011*SL
	t_{PHL}	0.529	0.486 + 0.021*SL	0.509 + 0.016*SL	0.551 + 0.012*SL
S1 to Y	t_R	0.171	0.125 + 0.023*SL	0.136 + 0.020*SL	0.152 + 0.019*SL
	t_F	0.203	0.156 + 0.023*SL	0.171 + 0.020*SL	0.201 + 0.017*SL
	t_{PLH}	0.368	0.332 + 0.018*SL	0.350 + 0.013*SL	0.382 + 0.011*SL
	t_{PHL}	0.398	0.356 + 0.021*SL	0.378 + 0.016*SL	0.420 + 0.012*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 11, *Group3 : 11 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX4D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.211	0.187 + 0.012*SL	0.191 + 0.011*SL	0.216 + 0.010*SL
	t_F	0.273	0.246 + 0.013*SL	0.256 + 0.011*SL	0.289 + 0.009*SL
	t_{PLH}	0.565	0.541 + 0.012*SL	0.555 + 0.008*SL	0.597 + 0.006*SL
	t_{PHL}	0.648	0.620 + 0.014*SL	0.636 + 0.010*SL	0.688 + 0.007*SL
D1 to Y	t_R	0.211	0.188 + 0.012*SL	0.190 + 0.011*SL	0.216 + 0.010*SL
	t_F	0.271	0.245 + 0.013*SL	0.255 + 0.011*SL	0.288 + 0.009*SL
	t_{PLH}	0.564	0.540 + 0.012*SL	0.554 + 0.008*SL	0.596 + 0.006*SL
	t_{PHL}	0.648	0.621 + 0.014*SL	0.637 + 0.010*SL	0.688 + 0.007*SL
D2 to Y	t_R	0.211	0.186 + 0.012*SL	0.191 + 0.011*SL	0.215 + 0.010*SL
	t_F	0.271	0.244 + 0.013*SL	0.255 + 0.011*SL	0.286 + 0.009*SL
	t_{PLH}	0.557	0.534 + 0.012*SL	0.548 + 0.008*SL	0.589 + 0.006*SL
	t_{PHL}	0.643	0.616 + 0.014*SL	0.632 + 0.010*SL	0.683 + 0.007*SL
D3 to Y	t_R	0.211	0.187 + 0.012*SL	0.191 + 0.011*SL	0.214 + 0.010*SL
	t_F	0.271	0.244 + 0.013*SL	0.255 + 0.011*SL	0.286 + 0.009*SL
	t_{PLH}	0.555	0.531 + 0.012*SL	0.545 + 0.008*SL	0.587 + 0.006*SL
	t_{PHL}	0.645	0.618 + 0.014*SL	0.634 + 0.010*SL	0.685 + 0.007*SL
S0 to Y	t_R	0.212	0.187 + 0.012*SL	0.192 + 0.011*SL	0.217 + 0.010*SL
	t_F	0.273	0.246 + 0.013*SL	0.256 + 0.011*SL	0.289 + 0.009*SL
	t_{PLH}	0.602	0.578 + 0.012*SL	0.592 + 0.008*SL	0.634 + 0.006*SL
	t_{PHL}	0.665	0.638 + 0.014*SL	0.654 + 0.010*SL	0.706 + 0.007*SL
S1 to Y	t_R	0.210	0.187 + 0.012*SL	0.189 + 0.011*SL	0.214 + 0.010*SL
	t_F	0.270	0.243 + 0.013*SL	0.253 + 0.011*SL	0.284 + 0.009*SL
	t_{PLH}	0.470	0.447 + 0.012*SL	0.460 + 0.008*SL	0.502 + 0.006*SL
	t_{PHL}	0.538	0.510 + 0.014*SL	0.526 + 0.010*SL	0.578 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 19, *Group3 : 19 < SL

Logic Symbol



Truth Table

S0	S1	S2	Y
0	0	0	D0
1	0	0	D1
0	1	0	D2
1	1	0	D3
0	0	1	D4
1	0	1	D5
0	1	1	D6
1	1	1	D7

Cell Data

Input Load (SL)											Gate Count
MX8											*MX8*
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	1.0	1.8	1.0	10.67
MX8D2											*MX8D2*
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	1.0	1.8	1.0	11.00
MX8D4											*MX8D4*
D0	D1	D2	D3	D4	D5	D6	D7	S0	S1	S2	
0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	1.0	1.8	1.1	11.67

8 > 1 Non-Inverting MUX with 1X/2X/4X Drive

Schematic Diagram



Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX8

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.238	0.155 + 0.042*SL	0.170 + 0.038*SL	0.181 + 0.037*SL
	t_F	0.299	0.219 + 0.040*SL	0.240 + 0.035*SL	0.261 + 0.032*SL
	t_{PLH}	0.616	0.557 + 0.029*SL	0.579 + 0.024*SL	0.604 + 0.021*SL
	t_{PHL}	0.730	0.658 + 0.036*SL	0.690 + 0.028*SL	0.724 + 0.023*SL
D1 to Y	t_R	0.238	0.155 + 0.042*SL	0.170 + 0.038*SL	0.180 + 0.037*SL
	t_F	0.299	0.218 + 0.040*SL	0.240 + 0.035*SL	0.261 + 0.032*SL
	t_{PLH}	0.616	0.558 + 0.029*SL	0.580 + 0.024*SL	0.604 + 0.021*SL
	t_{PHL}	0.731	0.659 + 0.036*SL	0.691 + 0.028*SL	0.725 + 0.023*SL
D2 to Y	t_R	0.238	0.154 + 0.042*SL	0.170 + 0.038*SL	0.178 + 0.037*SL
	t_F	0.295	0.216 + 0.040*SL	0.236 + 0.035*SL	0.256 + 0.032*SL
	t_{PLH}	0.604	0.545 + 0.029*SL	0.568 + 0.024*SL	0.592 + 0.020*SL
	t_{PHL}	0.720	0.648 + 0.036*SL	0.679 + 0.028*SL	0.714 + 0.023*SL
D3 to Y	t_R	0.238	0.154 + 0.042*SL	0.170 + 0.038*SL	0.178 + 0.037*SL
	t_F	0.295	0.216 + 0.040*SL	0.236 + 0.035*SL	0.256 + 0.032*SL
	t_{PLH}	0.603	0.545 + 0.029*SL	0.567 + 0.024*SL	0.591 + 0.020*SL
	t_{PHL}	0.720	0.649 + 0.036*SL	0.680 + 0.028*SL	0.714 + 0.023*SL
D4 to Y	t_R	0.237	0.153 + 0.042*SL	0.169 + 0.038*SL	0.178 + 0.037*SL
	t_F	0.294	0.214 + 0.040*SL	0.235 + 0.035*SL	0.256 + 0.032*SL
	t_{PLH}	0.599	0.541 + 0.029*SL	0.563 + 0.024*SL	0.587 + 0.020*SL
	t_{PHL}	0.715	0.644 + 0.035*SL	0.675 + 0.028*SL	0.709 + 0.023*SL
D5 to Y	t_R	0.237	0.153 + 0.042*SL	0.169 + 0.038*SL	0.178 + 0.037*SL
	t_F	0.294	0.214 + 0.040*SL	0.235 + 0.035*SL	0.256 + 0.032*SL
	t_{PLH}	0.599	0.541 + 0.029*SL	0.563 + 0.024*SL	0.587 + 0.020*SL
	t_{PHL}	0.715	0.644 + 0.035*SL	0.675 + 0.028*SL	0.709 + 0.023*SL
D6 to Y	t_R	0.236	0.153 + 0.042*SL	0.167 + 0.038*SL	0.177 + 0.037*SL
	t_F	0.293	0.214 + 0.040*SL	0.234 + 0.035*SL	0.254 + 0.032*SL
	t_{PLH}	0.593	0.535 + 0.029*SL	0.557 + 0.024*SL	0.581 + 0.020*SL
	t_{PHL}	0.711	0.641 + 0.035*SL	0.671 + 0.028*SL	0.705 + 0.023*SL
D7 to Y	t_R	0.236	0.153 + 0.042*SL	0.167 + 0.038*SL	0.177 + 0.037*SL
	t_F	0.293	0.214 + 0.040*SL	0.234 + 0.035*SL	0.254 + 0.032*SL
	t_{PLH}	0.593	0.535 + 0.029*SL	0.557 + 0.024*SL	0.581 + 0.020*SL
	t_{PHL}	0.711	0.641 + 0.035*SL	0.671 + 0.028*SL	0.705 + 0.023*SL
S0 to Y	t_R	0.240	0.157 + 0.042*SL	0.172 + 0.038*SL	0.180 + 0.037*SL
	t_F	0.295	0.216 + 0.040*SL	0.235 + 0.035*SL	0.255 + 0.032*SL
	t_{PLH}	0.864	0.806 + 0.029*SL	0.829 + 0.024*SL	0.853 + 0.020*SL
	t_{PHL}	0.974	0.903 + 0.035*SL	0.934 + 0.028*SL	0.968 + 0.023*SL
S1 to Y	t_R	0.234	0.150 + 0.042*SL	0.166 + 0.038*SL	0.174 + 0.037*SL
	t_F	0.282	0.202 + 0.040*SL	0.221 + 0.035*SL	0.242 + 0.032*SL
	t_{PLH}	0.504	0.446 + 0.029*SL	0.468 + 0.024*SL	0.492 + 0.020*SL
	t_{PHL}	0.551	0.481 + 0.035*SL	0.511 + 0.028*SL	0.545 + 0.023*SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX8D2

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.216	0.170 + 0.023*SL	0.178 + 0.021*SL	0.201 + 0.019*SL
	t_F	0.293	0.245 + 0.024*SL	0.263 + 0.020*SL	0.292 + 0.017*SL
	t_{PLH}	0.660	0.622 + 0.019*SL	0.641 + 0.015*SL	0.676 + 0.011*SL
	t_{PHL}	0.786	0.739 + 0.024*SL	0.765 + 0.017*SL	0.812 + 0.013*SL
D1 to Y	t_R	0.216	0.170 + 0.023*SL	0.178 + 0.021*SL	0.201 + 0.019*SL
	t_F	0.293	0.245 + 0.024*SL	0.263 + 0.020*SL	0.292 + 0.017*SL
	t_{PLH}	0.661	0.622 + 0.019*SL	0.641 + 0.015*SL	0.676 + 0.011*SL
	t_{PHL}	0.787	0.740 + 0.024*SL	0.766 + 0.017*SL	0.813 + 0.013*SL
D2 to Y	t_R	0.215	0.169 + 0.023*SL	0.178 + 0.021*SL	0.201 + 0.019*SL
	t_F	0.290	0.242 + 0.024*SL	0.259 + 0.020*SL	0.289 + 0.017*SL
	t_{PLH}	0.648	0.610 + 0.019*SL	0.629 + 0.015*SL	0.664 + 0.011*SL
	t_{PHL}	0.776	0.728 + 0.024*SL	0.754 + 0.017*SL	0.801 + 0.013*SL
D3 to Y	t_R	0.215	0.169 + 0.023*SL	0.178 + 0.021*SL	0.201 + 0.019*SL
	t_F	0.290	0.242 + 0.024*SL	0.259 + 0.020*SL	0.289 + 0.017*SL
	t_{PLH}	0.648	0.609 + 0.019*SL	0.629 + 0.015*SL	0.663 + 0.011*SL
	t_{PHL}	0.776	0.728 + 0.024*SL	0.754 + 0.017*SL	0.801 + 0.013*SL
D4 to Y	t_R	0.215	0.168 + 0.023*SL	0.177 + 0.021*SL	0.200 + 0.019*SL
	t_F	0.289	0.242 + 0.023*SL	0.258 + 0.020*SL	0.288 + 0.017*SL
	t_{PLH}	0.644	0.605 + 0.019*SL	0.625 + 0.014*SL	0.659 + 0.011*SL
	t_{PHL}	0.772	0.725 + 0.024*SL	0.751 + 0.017*SL	0.797 + 0.013*SL
D5 to Y	t_R	0.215	0.168 + 0.023*SL	0.177 + 0.021*SL	0.200 + 0.019*SL
	t_F	0.289	0.242 + 0.023*SL	0.258 + 0.020*SL	0.288 + 0.017*SL
	t_{PLH}	0.644	0.605 + 0.019*SL	0.624 + 0.014*SL	0.659 + 0.011*SL
	t_{PHL}	0.772	0.725 + 0.024*SL	0.751 + 0.017*SL	0.798 + 0.013*SL
D6 to Y	t_R	0.214	0.167 + 0.023*SL	0.176 + 0.021*SL	0.199 + 0.019*SL
	t_F	0.288	0.241 + 0.024*SL	0.257 + 0.019*SL	0.287 + 0.017*SL
	t_{PLH}	0.638	0.600 + 0.019*SL	0.619 + 0.014*SL	0.654 + 0.011*SL
	t_{PHL}	0.769	0.721 + 0.024*SL	0.747 + 0.017*SL	0.794 + 0.013*SL
D7 to Y	t_R	0.213	0.167 + 0.023*SL	0.176 + 0.021*SL	0.199 + 0.019*SL
	t_F	0.288	0.241 + 0.024*SL	0.257 + 0.019*SL	0.287 + 0.017*SL
	t_{PLH}	0.638	0.600 + 0.019*SL	0.619 + 0.014*SL	0.654 + 0.011*SL
	t_{PHL}	0.769	0.721 + 0.024*SL	0.747 + 0.017*SL	0.794 + 0.013*SL
S0 to Y	t_R	0.216	0.169 + 0.023*SL	0.179 + 0.021*SL	0.201 + 0.019*SL
	t_F	0.289	0.241 + 0.024*SL	0.259 + 0.019*SL	0.288 + 0.017*SL
	t_{PLH}	0.909	0.871 + 0.019*SL	0.890 + 0.014*SL	0.925 + 0.011*SL
	t_{PHL}	1.031	0.983 + 0.024*SL	1.010 + 0.017*SL	1.056 + 0.013*SL
S1 to Y	t_R	0.213	0.166 + 0.023*SL	0.176 + 0.021*SL	0.198 + 0.019*SL
	t_F	0.280	0.232 + 0.024*SL	0.251 + 0.020*SL	0.280 + 0.017*SL
	t_{PLH}	0.548	0.510 + 0.019*SL	0.529 + 0.014*SL	0.564 + 0.011*SL
	t_{PHL}	0.608	0.561 + 0.024*SL	0.587 + 0.017*SL	0.633 + 0.013*SL

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.27ns, SL: Standard Load)

MX8D4

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
D0 to Y	t_R	0.269	0.245 + 0.012*SL	0.247 + 0.011*SL	0.269 + 0.010*SL
	t_F	0.372	0.346 + 0.013*SL	0.354 + 0.011*SL	0.389 + 0.009*SL
	t_{PLH}	0.802	0.777 + 0.012*SL	0.792 + 0.009*SL	0.836 + 0.007*SL
	t_{PHL}	0.968	0.938 + 0.015*SL	0.955 + 0.011*SL	1.012 + 0.008*SL
D1 to Y	t_R	0.269	0.245 + 0.012*SL	0.247 + 0.011*SL	0.269 + 0.010*SL
	t_F	0.372	0.346 + 0.013*SL	0.354 + 0.011*SL	0.389 + 0.009*SL
	t_{PLH}	0.803	0.778 + 0.012*SL	0.792 + 0.009*SL	0.836 + 0.007*SL
	t_{PHL}	0.968	0.939 + 0.015*SL	0.956 + 0.011*SL	1.013 + 0.008*SL
D2 to Y	t_R	0.267	0.243 + 0.012*SL	0.247 + 0.011*SL	0.269 + 0.010*SL
	t_F	0.371	0.344 + 0.013*SL	0.353 + 0.011*SL	0.386 + 0.009*SL
	t_{PLH}	0.790	0.765 + 0.012*SL	0.780 + 0.009*SL	0.824 + 0.007*SL
	t_{PHL}	0.957	0.928 + 0.015*SL	0.944 + 0.011*SL	1.001 + 0.008*SL
D3 to Y	t_R	0.267	0.243 + 0.012*SL	0.247 + 0.011*SL	0.269 + 0.010*SL
	t_F	0.371	0.344 + 0.013*SL	0.354 + 0.011*SL	0.386 + 0.009*SL
	t_{PLH}	0.790	0.765 + 0.012*SL	0.780 + 0.009*SL	0.823 + 0.007*SL
	t_{PHL}	0.957	0.928 + 0.015*SL	0.944 + 0.011*SL	1.001 + 0.008*SL
D4 to Y	t_R	0.267	0.244 + 0.012*SL	0.246 + 0.011*SL	0.268 + 0.010*SL
	t_F	0.369	0.343 + 0.013*SL	0.352 + 0.011*SL	0.386 + 0.009*SL
	t_{PLH}	0.786	0.761 + 0.012*SL	0.776 + 0.009*SL	0.819 + 0.007*SL
	t_{PHL}	0.954	0.924 + 0.015*SL	0.941 + 0.011*SL	0.998 + 0.008*SL
D5 to Y	t_R	0.267	0.244 + 0.012*SL	0.246 + 0.011*SL	0.268 + 0.010*SL
	t_F	0.370	0.343 + 0.013*SL	0.352 + 0.011*SL	0.386 + 0.009*SL
	t_{PLH}	0.786	0.761 + 0.012*SL	0.775 + 0.009*SL	0.819 + 0.007*SL
	t_{PHL}	0.954	0.924 + 0.015*SL	0.941 + 0.011*SL	0.998 + 0.008*SL
D6 to Y	t_R	0.267	0.243 + 0.012*SL	0.245 + 0.011*SL	0.267 + 0.010*SL
	t_F	0.368	0.342 + 0.013*SL	0.350 + 0.011*SL	0.385 + 0.009*SL
	t_{PLH}	0.780	0.755 + 0.012*SL	0.770 + 0.009*SL	0.813 + 0.007*SL
	t_{PHL}	0.950	0.921 + 0.015*SL	0.937 + 0.011*SL	0.994 + 0.008*SL
D7 to Y	t_R	0.267	0.243 + 0.012*SL	0.245 + 0.011*SL	0.267 + 0.010*SL
	t_F	0.368	0.342 + 0.013*SL	0.350 + 0.011*SL	0.385 + 0.009*SL
	t_{PLH}	0.780	0.755 + 0.012*SL	0.770 + 0.009*SL	0.813 + 0.007*SL
	t_{PHL}	0.950	0.921 + 0.015*SL	0.937 + 0.011*SL	0.994 + 0.008*SL
S0 to Y	t_R	0.268	0.244 + 0.012*SL	0.247 + 0.011*SL	0.269 + 0.010*SL
	t_F	0.370	0.343 + 0.013*SL	0.352 + 0.011*SL	0.385 + 0.009*SL
	t_{PLH}	1.052	1.027 + 0.012*SL	1.042 + 0.009*SL	1.085 + 0.007*SL
	t_{PHL}	1.213	1.184 + 0.015*SL	1.200 + 0.011*SL	1.258 + 0.008*SL
S1 to Y	t_R	0.266	0.242 + 0.012*SL	0.245 + 0.011*SL	0.267 + 0.010*SL
	t_F	0.366	0.340 + 0.013*SL	0.348 + 0.011*SL	0.382 + 0.009*SL
	t_{PLH}	0.690	0.666 + 0.012*SL	0.680 + 0.009*SL	0.724 + 0.007*SL
	t_{PHL}	0.790	0.761 + 0.015*SL	0.778 + 0.011*SL	0.834 + 0.008*SL

Input/Output Cells

4

Contents

Overview 4-1
Summary Tables 4-2
Input Buffers 4-7
Output Buffers 4-19
Bi-Directional Buffers 4-58
Oscillators 4-60
PCI Buffers 4-76
USB (Universal Serial Bus) I/O Buffers 4-81
Power Pads 4-92
Analog Interface 4-93
Slot Cells 4-100

OVERVIEW

The fourth chapter describes various kinds of Input/Output cells only (2.5V/ 3.3V/ 5V-tolerant) in STDM110 library.

The switching characteristics of each cell are attached to its basic cell information. The AC characteristics of bi-directional buffers are not included in this data sheet. However, they can be derived from different combinations of input and output buffers.

There are so many possible combinations of input/output cells, therefore, the naming conventions are adopted to help you memorize and use this cell library efficiently. You can refer to the naming conventions contained in “Summary Tables” section.

The “Summary Tables” section shows the list of 2.5V, 3.3V interface and 5V-tolerant I/O cells separated by the category (input, output, bi-directional, etc.), and the more detailed description tables can be found on the leading part of each category.

All 1.8V, 2.5V, 3.3V-interface and 5V-tolerant buffers use 1 I/O slot. The default pitch of a regular I/O buffer is 52 µm. All 2.5V, 3.3V-interface and 5V-tolerant buffers use this regular I/O slot if the data sheet do not state differently.

NOTE: When both A and B driving signals do not exist, SEC tolerant IO’s pad voltage goes high state. However, those 5V tolerant input and bi-directional cells with 100kΩ pull-up resistor have NMOS pass transistor like Figure 4.1. Therefore, pad voltage of 5V tolerant IO for 3.3V interface could be 1.7V instead of VDD.



Figure 4-1.

SUMMARY TABLES

Input Buffers

Cell Type	Cell Name	Page
CMOS Level	PIC/PICD/PICU	4-8
	PHIC/PHICD/PHICU	
	PTIC/PTICD/PTICU	
CMOS Schmitt Trigger Level	PIS/PISD/PISU	4-12
	PHIS/PHISD/PHISU	
	PTIS/PTISD/PTISU	
LVTTL Level	PHIT/PHITD/PHITU	4-16
	PTIT/PTITD/PTITU	

<Naming Convention of Input Buffers>

Pvlab					
v		**a**		**b**	
None	2.5V interface	C	CMOS level	None	No resistor
H	3.3V interface	S	Schmitt trigger level	D	Pull-down resistor
T	5V-tolerant	T	LVTTL level	U	Pull-up resistor

Output Buffers

Cell Type	Cell Name	Current Drive (mA)	Page
Normal	POBy	1/2/4/6/8/10/12	4-20
	POBySM	4/6/8/10/12	
	POBySH	10/12	
	PHOBy	1/2/4/6/8/10/12	
	PHOBySM	4/6/8/10/12	
	PHOBySH	10/12	
Open Drain	PODy	1/2/4/6/8/10/12	4-29
	PODySM	4/6/8/10/12	
	PODySH	10/12	
	PHODy	1/2/4/6/8/10/12	
	PHODySM	4/6/8/10/12	
	PHODySH	10/12	
	PTODy	1/2/3	

Cell Type	Cell Name	Current Drive (mA)	Page
Tri-State	POTy	1/2/4/6/8/10/12	4-41
	POTySM	4/6/8/10/12	
	POTySH	10/12	
	PHOTy	1/2/4/6/8/10/12	
	PHOTySM	4/6/8/10/12	
	PHOTySH	10/12	
	PTOTy	1/2/3	

<Naming Convention of Output Buffers>

P wO x y z			
w		**y**	
None	2.5V interface	1	1mA drive
H	3.3V interface	2	2mA drive
x		4	4mA drive
B	Normal buffer	6	6mA drive
D	Open drain buffer	8	8mA drive
T	Tri-state buffer	10	10mA drive
z		12	12mA drive
None	No slew-rate control		
SM	Medium slew-rate control		
SH	High slew-rate control		
P T O x y			
x		**y**	
D	Open drain buffer	1	1mA drive
T	Tri-state buffer	2	2mA drive
		3	3mA drive

Bi-Directional Buffers

Cell Type	Cell Name	Page
Open Drain	PBaDyz/PBaUDyz	4-59
	PHBaDyz/PHBaUDyz	
	PTBaDyz/PTBaUDyz	
Tri-State	PBaTyz/PBaDTyz/PBaUTyz	
	PHBaTy/PHBaDTy/PHBaUTy	
	PTBaTy/PTBaDTy/PTBaUTy	

<Naming Convention of Bi-Directional Buffers>

Pw B a b x y z			
w		**y**	
None	2.5V interface	1	1mA drive
H	3.3V interface	2	2mA drive
a		4	4mA drive
C	LVCMOS level	6	6mA drive
S	LVCMOS Schmitt trigger level	8	8mA drive
T	LVTTL level	10	10mA drive
b		12	12mA drive
None	No resistor	**z**	
D	Pull-down resistor	None	No slew-rate control
U	Pull-up resistor	SM	Medium slew -rate control
x		SH	High slew-rate control
B	Normal buffer		
D	Open drain buffer		
T	Tri-state buffer		
P T B a b x y			
a		**x**	
C	LVCMOS level	D	Open drain buffer
S	LVCMOS Schmitt trigger level	T	Tri-state buffer
T	LVTTL level	**y**	
b		1	1mA drive
None	No resistor	2	2mA drive
D	Pull-down resistor	3	3mA drive
U	Pull-up resistor		

Oscillators

Cell Type	Cell Name	Page
Oscillator	PHSOSCK1/K2/M1/M2	4-61
	PH2SOSCK1/K2/M1/M2	4-66
	PSOSCK1/K2/M1/M2	4-71

PCI Buffers

Cell Type	Cell Name	Page
5V-tolerant PCI Input	PTIPCI	4-78
5V-tolerant PCI Output	PTOPCI	4-79
5V-tolerant PCI Bi-directional Buffer	PTBPCI	4-80

USB (Universal Serial Bus) I/O Buffers *(Under development)*

Cell Type	Cell Name	Page
Bi-directional USB buffer	PBUSB/PBUSB1	4-83
	PBUSB_LS	4-84
	PBUSB_FS	4-85

Power Pads

Cell Type	Cell Name	Page
2.5V VDD	VDD2(I/P/O/IP/OP/T)	4-92
3.3V VDD	VDD3(P/O/OP)	
VSS	VSS2(I/P/O/IP/OP/T)	
	VSS3(P/O/OP)	
Analog VDD Power Pads	VDD2I_ABB/VDD2OP_ABB/VDD2T_ABB	
Analog VSS Power Pads	VSS2I_ABB/VSS2OP_ABB/VSS2T_ABB	
	VBB_ABB/VSSBB_ABB	

Analog Interface

Cell Type	Cell Name	Page
Analog Input with Seperated Bulk-Bias	PIC_ABB	4-94
	PICC_ABB	4-95
	PICEN_ABB	4-96
Analog Output with Seperated Bulk-Bias	POT(1/2/4/8)_ABB	4-97

Slot Cells

Cell Type	Cell Name	Page
ESD Slot Cells	EV1I	4-100
	EV2P/EV2O/EV2OP	
	EV3P/EV3O/EV3OP	
	EV1I_ABB/EV2OP_ABB	
Common Slot Cells	EC0C0/EC0C0D	4-101
	EC0CA0/EC0CA0D	
	EC0C0_BB/EC0C0D_BB/ EC0C0_VBB/EC0C0D_VBB	

Cell List

Cell Name	Function Description
PIC/PICD/PICU	2.5V LVCMOS Level Input Buffers
PHIC/PHICD/PHICU	3.3V LVCMOS Level Input Buffers
PTIC/PTICD/PTICU	5V-Tolerant LVCMOS Level Input Buffers
PIS/PISD/PISU	2.5V LVCMOS Schmitt Trigger Level Input Buffers
PHIS/PHISD/PHISU	3.3V LVCMOS Schmitt Trigger Level Input Buffers
PTIS/PTISD/PTISU	5V-Tolerant LVCMOS Schmitt Trigger Level Input Buffers
PHIT/PHITD/PHITU	3.3V LVTTL Level Input Buffers
PTIT/PTITD/PTITU	5V-tolerant LVTTL Level Input Buffers

PvIC/PvICD/PvICU

LVCMOS Level Input Buffers

Cell Availability

2.5V Interface	3.3V Interface	5V Tolerant
PIC/PICD/PICU	PHIC/PHICD/PHICU	PTIC/PTICD/PTICU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIC/PICD/PICU	2.835
PHIC/PHICD/PHICU	2.835
PTIC/PTICD/PTICU	2.835

Switching Characteristics

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)

PIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.196	0.181 + 0.008*SL	0.180 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.995	0.984 + 0.005*SL	0.987 + 0.004*SL	1.003 + 0.004*SL
	t_{PHL}	1.392	1.381 + 0.006*SL	1.388 + 0.004*SL	1.462 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.196	0.181 + 0.008*SL	0.180 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.006*SL	0.198 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.064	1.053 + 0.005*SL	1.056 + 0.004*SL	1.072 + 0.004*SL
	t_{PHL}	1.349	1.337 + 0.006*SL	1.344 + 0.004*SL	1.419 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.196	0.181 + 0.008*SL	0.179 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.938	0.927 + 0.005*SL	0.930 + 0.004*SL	0.947 + 0.004*SL
	t_{PHL}	1.465	1.453 + 0.006*SL	1.460 + 0.004*SL	1.535 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

NOTE: The delay measure point of LVCMOS input buffer is from PAD(VDD/2) to Y(VDD/2).

Switching Characteristics (Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PHIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.168 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.791	0.781 + 0.005*SL	0.783 + 0.004*SL	0.795 + 0.004*SL
	t_{PHL}	1.151	1.139 + 0.006*SL	1.146 + 0.004*SL	1.220 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.198 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.869	0.859 + 0.005*SL	0.861 + 0.004*SL	0.873 + 0.004*SL
	t_{PHL}	1.115	1.103 + 0.006*SL	1.110 + 0.004*SL	1.184 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.736	0.726 + 0.005*SL	0.728 + 0.004*SL	0.740 + 0.004*SL
	t_{PHL}	1.226	1.215 + 0.006*SL	1.222 + 0.004*SL	1.296 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

NOTE: The delay measure point of LVCMOS input buffer is from PAD(VDD/2) to Y(VDD/2).

Switching Characteristics (Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PTIC

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.185	0.169 + 0.008*SL	0.168 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.940	0.930 + 0.005*SL	0.932 + 0.004*SL	0.944 + 0.004*SL
	t_{PHL}	1.532	1.520 + 0.006*SL	1.527 + 0.004*SL	1.601 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTICD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.169 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.021	1.011 + 0.005*SL	1.014 + 0.004*SL	1.026 + 0.004*SL
	t_{PHL}	1.496	1.485 + 0.006*SL	1.491 + 0.004*SL	1.566 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTICU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.169 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.198 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.787	0.777 + 0.005*SL	0.779 + 0.004*SL	0.792 + 0.004*SL
	t_{PHL}	1.727	1.715 + 0.006*SL	1.722 + 0.004*SL	1.797 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PvIS/PvISD/PvISU

LVCMOS Schmitt Trigger Level Input Buffers

Cell Availability

2.5V Interface	3.3V Interface	5V Tolerant
PIS/PISD/PISU	PHIS/PHISD/PHISU	PTIS/PTISD/PTISU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIS/PISD/PISU	2.835
PHIS/PHISD/PHISU	2.835
PTIS/PTISD/PTISU	2.835

Switching Characteristics (Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)

PIS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.197	0.182 + 0.008*SL	0.180 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.006*SL	0.198 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.412	1.401 + 0.005*SL	1.404 + 0.004*SL	1.421 + 0.004*SL
	t_{PHL}	1.825	1.813 + 0.006*SL	1.820 + 0.004*SL	1.895 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PISD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.197	0.181 + 0.008*SL	0.180 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.211	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.419	1.409 + 0.005*SL	1.412 + 0.004*SL	1.428 + 0.004*SL
	t_{PHL}	1.857	1.846 + 0.006*SL	1.853 + 0.004*SL	1.928 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PISU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.196	0.181 + 0.008*SL	0.179 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.424	1.414 + 0.005*SL	1.417 + 0.004*SL	1.433 + 0.004*SL
	t_{PHL}	1.838	1.826 + 0.006*SL	1.833 + 0.004*SL	1.908 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

Switching Characteristics (Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PHIS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.156 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.020	1.010 + 0.005*SL	1.013 + 0.004*SL	1.024 + 0.004*SL
	t_{PHL}	1.596	1.584 + 0.006*SL	1.591 + 0.004*SL	1.666 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHISD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.185	0.169 + 0.008*SL	0.168 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.522	1.513 + 0.005*SL	1.515 + 0.004*SL	1.527 + 0.004*SL
	t_{PHL}	1.838	1.826 + 0.006*SL	1.833 + 0.004*SL	1.907 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHISU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.169 + 0.007*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.034	1.024 + 0.005*SL	1.026 + 0.004*SL	1.038 + 0.004*SL
	t_{PHL}	1.605	1.593 + 0.006*SL	1.601 + 0.004*SL	1.675 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

Switching Characteristics

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PTIS

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.186	0.170 + 0.008*SL	0.169 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.180	1.170 + 0.005*SL	1.173 + 0.004*SL	1.186 + 0.004*SL
	t_{PHL}	1.643	1.632 + 0.006*SL	1.639 + 0.004*SL	1.713 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTISD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.186	0.170 + 0.008*SL	0.169 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.207	1.197 + 0.005*SL	1.199 + 0.004*SL	1.212 + 0.004*SL
	t_{PHL}	1.687	1.675 + 0.006*SL	1.683 + 0.004*SL	1.757 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTISU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.186	0.170 + 0.008*SL	0.169 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.147	1.138 + 0.005*SL	1.140 + 0.004*SL	1.153 + 0.004*SL
	t_{PHL}	1.691	1.679 + 0.006*SL	1.686 + 0.004*SL	1.760 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PvIT/PvITD/PvITU

LVTTL Level Input Buffers

Cell Availability

3.3V Interface	5V Tolerant
PHIT/PHITD/PHITU	PTIT/PTITD/PTITU

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PHIT/PHITD/PHITU	3.620
PTIT/PTITD/PTITU	3.620

Switching Characteristics (Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PHIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.169 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.681	0.671 + 0.005*SL	0.673 + 0.004*SL	0.685 + 0.004*SL
	t_{PHL}	1.183	1.171 + 0.006*SL	1.178 + 0.004*SL	1.253 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHITD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.710	0.700 + 0.005*SL	0.702 + 0.004*SL	0.714 + 0.004*SL
	t_{PHL}	1.215	1.203 + 0.006*SL	1.210 + 0.004*SL	1.285 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PHITU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.685	0.675 + 0.005*SL	0.677 + 0.004*SL	0.689 + 0.004*SL
	t_{PHL}	1.191	1.179 + 0.006*SL	1.186 + 0.004*SL	1.260 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

NOTE: The delay measure point of LVTTL input buffer is from PAD(1.4) to Y(VDD/2).

Switching Characteristics

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 3.00ns, SL: Standard Load)

PTIT

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.169 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.767	0.757 + 0.005*SL	0.759 + 0.004*SL	0.771 + 0.004*SL
	t_{PHL}	1.446	1.434 + 0.006*SL	1.441 + 0.004*SL	1.516 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTITD

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.798	0.789 + 0.005*SL	0.791 + 0.004*SL	0.803 + 0.004*SL
	t_{PHL}	1.479	1.467 + 0.006*SL	1.474 + 0.004*SL	1.549 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PTITU

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.184	0.168 + 0.008*SL	0.167 + 0.008*SL	0.157 + 0.008*SL
	t_F	0.210	0.196 + 0.007*SL	0.198 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.774	0.764 + 0.005*SL	0.767 + 0.004*SL	0.779 + 0.004*SL
	t_{PHL}	1.503	1.491 + 0.006*SL	1.498 + 0.004*SL	1.573 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

Cell List

Cell Name	Function Description
POB(1/2/4/6/8/10/12)	2.5V LVCMOS Normal Output Buffers
POB(4/6/8/10/12)SM	2.5V LVCMOS Normal Output Buffers with Medium Slew-Rate
POB(10/12)SH	2.5V LVCMOS Normal Output Buffers with High Slew-Rate
PHOB(1/2/4/6/8/10/12)	3.3V LVCMOS Normal Output Buffers
PHOB(4/6/8/10/12)SM	3.3V LVCMOS Normal Output Buffers with Medium Slew-Rate
PHOB(10/12)SH	3.3V LVCMOS Normal Output Buffers with High Slew-Rate
POD(1/2/4/6/8/10/12)	2.5V LVCMOS Open Drain Output Buffers
POD(4/6/8/10/12)SM	2.5V LVCMOS Open Drain Output Buffers with Medium Slew-Rate
POD(10/12)SH	2.5V LVCMOS Open Drain Output Buffers with High Slew-Rate
PHOD(1/2/4/6/8/10/12)	3.3V LVCMOS Open Drain Output Buffers
PHOD(4/6/8/10/12)SM	3.3V LVCMOS Open Drain Output Buffers with Medium Slew-Rate
PHOD(10/12)SH	3.3V LVCMOS Open Drain Output Buffers with High Slew-Rate
PTOD(1/2/3)	5V Tolerant Open Drain Output Buffers
POT(1/2/4/6/8/10/12)	2.5V LVCMOS Tri-State Output Buffers
POT(4/6/8/10/12)SM	2.5V LVCMOS Tri-State Output Buffers with Medium Slew-Rate
POT(10/12)SH	2.5V LVCMOS Tri-State Output Buffers with High Slew-Rate
PHOT(1/2/4/6/8/10/12)	3.3V LVCMOS Tri-State Output Buffers
PHOT(4/6/8/10/12)SM	3.3V LVCMOS Tri-State Output Buffers with Medium Slew-Rate
PHOT(10/12)SH	3.3V LVCMOS Tri-State Output Buffers with High Slew-Rate
PTOT(1/2/3)	5V Tolerant Tri-State Output Buffers

PvOByz

Normal Output Buffers

Cell Availability

2.5V Interface	3.3V Interface
POB(1/2/4/6/8/10/12) POB(4/6/8/10/12)SM POB(10/12)SH	PHOB(1/2/4/6/8/10/12) PHOB(4/6/8/10/12)SM PHOB(10/12)SH

Logic Symbol



Truth Table

A	PAD
0	0
1	1

Standard Load (SL)

Cell Name	A
POB(1/2/4/6/8/10/12)	5.147
POB(4/6/8/10/12)SM	5.147
POB(10/12)SH	5.147
PHOB(1/2/4/6/8/10/12)	5.147
PHOB(4/6/8/10/12)SM	5.147
PHOB(10/12)SH	5.147

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POB1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	31.508	1.210 + 0.606*CL	1.212 + 0.606*CL	1.209 + 0.606*CL
	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PLH}	16.185	1.678 + 0.290*CL	1.679 + 0.290*CL	1.676 + 0.290*CL
	t_{PHL}	17.834	1.724 + 0.322*CL	1.726 + 0.322*CL	1.726 + 0.322*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	15.772	0.624 + 0.303*CL	0.622 + 0.303*CL	0.625 + 0.303*CL
	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PLH}	8.752	1.498 + 0.145*CL	1.499 + 0.145*CL	1.498 + 0.145*CL
	t_{PHL}	10.468	1.350 + 0.182*CL	1.348 + 0.182*CL	1.351 + 0.182*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.917	0.349 + 0.151*CL	0.342 + 0.151*CL	0.343 + 0.151*CL
	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PLH}	5.190	1.563 + 0.073*CL	1.563 + 0.073*CL	1.563 + 0.073*CL
	t_{PHL}	5.801	1.243 + 0.091*CL	1.242 + 0.091*CL	1.242 + 0.091*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.317	0.312 + 0.100*CL	0.281 + 0.101*CL	0.265 + 0.101*CL
	t_F	6.097	0.261 + 0.117*CL	0.257 + 0.117*CL	0.256 + 0.117*CL
	t_{PLH}	4.128	1.708 + 0.048*CL	1.709 + 0.048*CL	1.710 + 0.048*CL
	t_{PHL}	4.296	1.264 + 0.061*CL	1.260 + 0.061*CL	1.258 + 0.061*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POB8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.050	0.355 + 0.074*CL	0.305 + 0.075*CL	0.270 + 0.075*CL
	t_F	4.592	0.229 + 0.087*CL	0.216 + 0.088*CL	0.210 + 0.088*CL
	t_{PLH}	3.689	1.870 + 0.036*CL	1.874 + 0.036*CL	1.875 + 0.036*CL
	t_{PHL}	3.586	1.322 + 0.045*CL	1.314 + 0.045*CL	1.308 + 0.046*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.222	0.252 + 0.059*CL	0.216 + 0.060*CL	0.194 + 0.060*CL
	t_F	3.669	0.176 + 0.070*CL	0.167 + 0.070*CL	0.164 + 0.070*CL
	t_{PLH}	3.362	1.908 + 0.029*CL	1.910 + 0.029*CL	1.911 + 0.029*CL
	t_{PHL}	3.189	1.374 + 0.036*CL	1.369 + 0.036*CL	1.367 + 0.036*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	2.726	0.284 + 0.049*CL	0.242 + 0.050*CL	0.210 + 0.050*CL
	t_F	3.070	0.169 + 0.058*CL	0.156 + 0.058*CL	0.149 + 0.058*CL
	t_{PLH}	3.208	1.992 + 0.024*CL	1.998 + 0.024*CL	1.999 + 0.024*CL
	t_{PHL}	2.915	1.409 + 0.030*CL	1.402 + 0.030*CL	1.397 + 0.030*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POB4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.138	0.760 + 0.148*CL	0.666 + 0.149*CL	0.591 + 0.150*CL
	t_F	9.484	1.002 + 0.170*CL	0.891 + 0.172*CL	0.787 + 0.173*CL
	t_{PLH}	6.684	3.028 + 0.073*CL	3.050 + 0.073*CL	3.056 + 0.073*CL
	t_{PHL}	7.944	3.307 + 0.093*CL	3.367 + 0.092*CL	3.386 + 0.091*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.055	1.322 + 0.095*CL	1.260 + 0.096*CL	1.160 + 0.097*CL
	t_F	6.974	1.437 + 0.111*CL	1.402 + 0.111*CL	1.310 + 0.113*CL
	t_{PLH}	6.333	3.623 + 0.054*CL	3.806 + 0.051*CL	3.909 + 0.049*CL
	t_{PHL}	7.242	3.835 + 0.068*CL	4.055 + 0.064*CL	4.190 + 0.062*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.172	1.681 + 0.070*CL	1.692 + 0.070*CL	1.619 + 0.071*CL
	t_F	5.696	1.539 + 0.083*CL	1.580 + 0.082*CL	1.530 + 0.083*CL
	t_{PLH}	5.933	3.590 + 0.047*CL	3.875 + 0.041*CL	4.070 + 0.039*CL
	t_{PHL}	6.524	3.752 + 0.055*CL	4.013 + 0.050*CL	4.197 + 0.048*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.217	1.340 + 0.058*CL	1.378 + 0.057*CL	1.357 + 0.057*CL
	t_F	4.723	1.348 + 0.068*CL	1.409 + 0.066*CL	1.397 + 0.066*CL
	t_{PLH}	5.573	3.656 + 0.038*CL	3.883 + 0.034*CL	4.053 + 0.032*CL
	t_{PHL}	6.086	3.775 + 0.046*CL	4.014 + 0.041*CL	4.193 + 0.039*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POB12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.209	1.652 + 0.051*CL	1.797 + 0.048*CL	1.869 + 0.047*CL
	t_F	4.538	1.532 + 0.060*CL	1.712 + 0.057*CL	1.801 + 0.055*CL
	t_{PLH}	5.807	3.846 + 0.039*CL	4.152 + 0.033*CL	4.409 + 0.030*CL
	t_{PHL}	6.287	4.066 + 0.044*CL	4.350 + 0.039*CL	4.594 + 0.035*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.241	2.972 + 0.065*CL	3.254 + 0.060*CL	3.439 + 0.057*CL
	t_F	6.418	2.686 + 0.075*CL	2.964 + 0.069*CL	3.140 + 0.067*CL
	t_{PLH}	8.790	5.851 + 0.059*CL	6.408 + 0.048*CL	6.878 + 0.041*CL
	t_{PHL}	9.014	5.815 + 0.064*CL	6.331 + 0.054*CL	6.774 + 0.048*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POB12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.624	3.594 + 0.061*CL	3.976 + 0.053*CL	4.247 + 0.049*CL
	t_F	6.506	3.047 + 0.069*CL	3.447 + 0.061*CL	3.723 + 0.057*CL
	t_{PLH}	9.300	6.148 + 0.063*CL	6.835 + 0.049*CL	7.418 + 0.042*CL
	t_{PHL}	9.482	6.255 + 0.065*CL	6.844 + 0.053*CL	7.354 + 0.046*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOB1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	42.148	1.623 + 0.811*CL	1.624 + 0.810*CL	1.621 + 0.811*CL
	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PLH}	20.566	1.821 + 0.375*CL	1.818 + 0.375*CL	1.818 + 0.375*CL
	t_{PHL}	17.535	1.970 + 0.311*CL	1.971 + 0.311*CL	1.971 + 0.311*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	21.098	0.836 + 0.405*CL	0.836 + 0.405*CL	0.833 + 0.405*CL
	t_F	18.189	0.704 + 0.350*CL	0.705 + 0.350*CL	0.705 + 0.350*CL
	t_{PLH}	10.867	1.494 + 0.187*CL	1.493 + 0.187*CL	1.493 + 0.187*CL
	t_{PHL}	10.485	1.590 + 0.178*CL	1.589 + 0.178*CL	1.592 + 0.178*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.563	0.433 + 0.203*CL	0.431 + 0.203*CL	0.431 + 0.203*CL
	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PLH}	6.093	1.407 + 0.094*CL	1.407 + 0.094*CL	1.407 + 0.094*CL
	t_{PHL}	5.923	1.476 + 0.089*CL	1.476 + 0.089*CL	1.477 + 0.089*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.047	0.294 + 0.135*CL	0.294 + 0.135*CL	0.293 + 0.135*CL
	t_F	6.082	0.255 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PLH}	4.682	1.559 + 0.062*CL	1.558 + 0.062*CL	1.558 + 0.062*CL
	t_{PHL}	4.601	1.636 + 0.059*CL	1.636 + 0.059*CL	1.636 + 0.059*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOB8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.293	0.230 + 0.101*CL	0.228 + 0.101*CL	0.228 + 0.101*CL
	t_F	4.572	0.206 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PLH}	3.920	1.579 + 0.047*CL	1.577 + 0.047*CL	1.577 + 0.047*CL
	t_{PHL}	3.869	1.645 + 0.044*CL	1.645 + 0.044*CL	1.645 + 0.044*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.243	0.197 + 0.081*CL	0.191 + 0.081*CL	0.190 + 0.081*CL
	t_F	3.670	0.185 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PLH}	3.480	1.610 + 0.037*CL	1.607 + 0.037*CL	1.606 + 0.037*CL
	t_{PHL}	3.444	1.665 + 0.036*CL	1.664 + 0.036*CL	1.665 + 0.036*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.544	0.181 + 0.067*CL	0.170 + 0.067*CL	0.167 + 0.068*CL
	t_F	3.071	0.179 + 0.058*CL	0.164 + 0.058*CL	0.157 + 0.058*CL
	t_{PLH}	3.201	1.647 + 0.031*CL	1.643 + 0.031*CL	1.640 + 0.031*CL
	t_{PHL}	3.172	1.689 + 0.030*CL	1.689 + 0.030*CL	1.690 + 0.030*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOB4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.608	0.517 + 0.202*CL	0.486 + 0.202*CL	0.477 + 0.203*CL
	t_F	9.435	0.948 + 0.170*CL	0.843 + 0.172*CL	0.750 + 0.173*CL
	t_{PLH}	6.842	2.153 + 0.094*CL	2.155 + 0.094*CL	2.155 + 0.094*CL
	t_{PHL}	7.858	3.349 + 0.090*CL	3.398 + 0.089*CL	3.410 + 0.089*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.211	0.618 + 0.132*CL	0.540 + 0.133*CL	0.478 + 0.134*CL
	t_F	6.906	1.349 + 0.111*CL	1.323 + 0.112*CL	1.241 + 0.113*CL
	t_{PLH}	5.604	2.461 + 0.063*CL	2.476 + 0.063*CL	2.479 + 0.063*CL
	t_{PHL}	7.116	3.806 + 0.066*CL	4.013 + 0.062*CL	4.138 + 0.060*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.691	0.887 + 0.096*CL	0.802 + 0.098*CL	0.711 + 0.099*CL
	t_F	6.049	1.774 + 0.085*CL	1.892 + 0.083*CL	1.916 + 0.083*CL
	t_{PLH}	5.246	2.791 + 0.049*CL	2.873 + 0.047*CL	2.905 + 0.047*CL
	t_{PHL}	7.131	4.167 + 0.059*CL	4.512 + 0.052*CL	4.780 + 0.049*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.501	0.614 + 0.078*CL	0.553 + 0.079*CL	0.502 + 0.080*CL
	t_F	5.266	1.797 + 0.069*CL	1.949 + 0.066*CL	2.003 + 0.066*CL
	t_{PLH}	4.440	2.524 + 0.038*CL	2.561 + 0.038*CL	2.571 + 0.037*CL
	t_{PHL}	6.537	3.940 + 0.052*CL	4.301 + 0.045*CL	4.591 + 0.041*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOByz

Normal Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOB12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.001	0.794 + 0.064*CL	0.770 + 0.065*CL	0.723 + 0.065*CL
	t_F	4.472	1.497 + 0.059*CL	1.644 + 0.057*CL	1.721 + 0.056*CL
	t_{PLH}	4.402	2.680 + 0.034*CL	2.782 + 0.032*CL	2.840 + 0.032*CL
	t_{PHL}	6.119	3.911 + 0.044*CL	4.209 + 0.038*CL	4.456 + 0.035*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.281	1.455 + 0.077*CL	1.475 + 0.076*CL	1.424 + 0.077*CL
	t_F	6.193	2.408 + 0.076*CL	2.688 + 0.070*CL	2.878 + 0.068*CL
	t_{PLH}	6.206	3.869 + 0.047*CL	4.111 + 0.042*CL	4.281 + 0.040*CL
	t_{PHL}	8.553	5.444 + 0.062*CL	5.939 + 0.052*CL	6.363 + 0.047*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOB12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.972	1.688 + 0.066*CL	1.804 + 0.063*CL	1.821 + 0.063*CL
	t_F	6.207	2.739 + 0.069*CL	3.098 + 0.062*CL	3.372 + 0.059*CL
	t_{PLH}	6.356	4.127 + 0.045*CL	4.428 + 0.039*CL	4.667 + 0.035*CL
	t_{PHL}	8.874	5.720 + 0.063*CL	6.292 + 0.052*CL	6.793 + 0.045*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Cell Availability

2.5V Interface	3.3V Interface	5V Tolerant
POD(1/2/4/6/8/10/12) POD(4/6/8/10/12)SM POD(10/12)SH	PHOD(1/2/4/6/8/10/12) PHOD(4/6/8/10/12)SM PHOD(10/12)SH	PTOD(1/2/3)

Logic Symbol



Truth Table

TN	EN	PAD
1	0	0
0	x	Hi-Z
x	1	Hi-Z

Standard Load (SL)

Cell Name	TN	EN
POD(1/2/4/6/8/10/12)	2.833	2.816
POD(4/6/8/10/12)SM	2.833	2.816
POD(10/12)SH	2.833	2.816
PHOD(1/2/4/6/8/10/12)	2.833	2.816
PHOD(4/6/8/10/12)SM	2.833	2.816
PHOD(10/12)SH	2.833	2.816
PTOD(1/2/3)	2.833	2.816

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PHL}	18.398	2.288 + 0.322*CL	2.290 + 0.322*CL	2.290 + 0.322*CL
	t_{PLZ}	1.756	1.755 + 0.000*CL	1.756 + 0.000*CL	1.756 + 0.000*CL
EN to PAD	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PHL}	18.570	2.460 + 0.322*CL	2.462 + 0.322*CL	2.462 + 0.322*CL
	t_{PLZ}	1.839	1.839 + 0.000*CL	1.839 + 0.000*CL	1.839 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PHL}	11.039	1.921 + 0.182*CL	1.919 + 0.182*CL	1.922 + 0.182*CL
	t_{PLZ}	1.609	1.609 + 0.000*CL	1.609 + 0.000*CL	1.609 + 0.000*CL
EN to PAD	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PHL}	11.212	2.092 + 0.182*CL	2.094 + 0.182*CL	2.094 + 0.182*CL
	t_{PLZ}	1.693	1.693 + 0.000*CL	1.693 + 0.000*CL	1.693 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PHL}	6.366	1.806 + 0.091*CL	1.806 + 0.091*CL	1.807 + 0.091*CL
	t_{PLZ}	1.738	1.738 + 0.000*CL	1.738 + 0.000*CL	1.738 + 0.000*CL
EN to PAD	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PHL}	6.538	1.979 + 0.091*CL	1.979 + 0.091*CL	1.978 + 0.091*CL
	t_{PLZ}	1.821	1.821 + 0.000*CL	1.820 + 0.000*CL	1.821 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POD6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.097	0.260 + 0.117*CL	0.256 + 0.117*CL	0.256 + 0.117*CL
	t_{PHL}	4.856	1.816 + 0.061*CL	1.817 + 0.061*CL	1.816 + 0.061*CL
	t_{PLZ}	1.865	1.865 + 0.000*CL	1.865 + 0.000*CL	1.865 + 0.000*CL
EN to PAD	t_F	6.097	0.260 + 0.117*CL	0.256 + 0.117*CL	0.256 + 0.117*CL
	t_{PHL}	5.029	1.989 + 0.061*CL	1.989 + 0.061*CL	1.989 + 0.061*CL
	t_{PLZ}	1.948	1.948 + 0.000*CL	1.948 + 0.000*CL	1.948 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.591	0.229 + 0.087*CL	0.215 + 0.088*CL	0.210 + 0.088*CL
	t_{PHL}	4.137	1.857 + 0.046*CL	1.857 + 0.046*CL	1.858 + 0.046*CL
	t_{PLZ}	1.992	1.992 + 0.000*CL	1.992 + 0.000*CL	1.992 + 0.000*CL
EN to PAD	t_F	4.591	0.229 + 0.087*CL	0.215 + 0.088*CL	0.210 + 0.088*CL
	t_{PHL}	4.310	2.029 + 0.046*CL	2.030 + 0.046*CL	2.030 + 0.046*CL
	t_{PLZ}	2.075	2.074 + 0.000*CL	2.075 + 0.000*CL	2.075 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	3.668	0.175 + 0.070*CL	0.166 + 0.070*CL	0.163 + 0.070*CL
	t_{PHL}	3.608	1.784 + 0.036*CL	1.784 + 0.036*CL	1.784 + 0.036*CL
	t_{PLZ}	1.849	1.849 + 0.000*CL	1.849 + 0.000*CL	1.849 + 0.000*CL
EN to PAD	t_F	3.668	0.175 + 0.070*CL	0.166 + 0.070*CL	0.163 + 0.070*CL
	t_{PHL}	3.780	1.956 + 0.036*CL	1.957 + 0.036*CL	1.956 + 0.036*CL
	t_{PLZ}	1.932	1.932 + 0.000*CL	1.932 + 0.000*CL	1.932 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POD12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	3.069	0.168 + 0.058*CL	0.154 + 0.058*CL	0.147 + 0.058*CL
	t_{PHL}	3.328	1.807 + 0.030*CL	1.808 + 0.030*CL	1.808 + 0.030*CL
	t_{PLZ}	1.913	1.913 + 0.000*CL	1.913 + 0.000*CL	1.913 + 0.000*CL
EN to PAD	t_F	3.069	0.168 + 0.058*CL	0.154 + 0.058*CL	0.147 + 0.058*CL
	t_{PHL}	3.500	1.980 + 0.030*CL	1.980 + 0.030*CL	1.980 + 0.030*CL
	t_{PLZ}	1.996	1.995 + 0.000*CL	1.996 + 0.000*CL	1.996 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	9.489	1.017 + 0.169*CL	0.900 + 0.172*CL	0.797 + 0.173*CL
	t_{PHL}	8.414	3.778 + 0.093*CL	3.838 + 0.092*CL	3.859 + 0.091*CL
	t_{PLZ}	1.882	1.881 + 0.000*CL	1.881 + 0.000*CL	1.882 + 0.000*CL
EN to PAD	t_F	9.489	1.017 + 0.169*CL	0.900 + 0.172*CL	0.797 + 0.173*CL
	t_{PHL}	8.586	3.950 + 0.093*CL	4.011 + 0.092*CL	4.028 + 0.091*CL
	t_{PLZ}	1.965	1.964 + 0.000*CL	1.964 + 0.000*CL	1.965 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.995	1.478 + 0.110*CL	1.435 + 0.111*CL	1.338 + 0.113*CL
	t_{PHL}	7.726	4.313 + 0.068*CL	4.537 + 0.064*CL	4.673 + 0.062*CL
	t_{PLZ}	2.156	2.156 + 0.000*CL	2.156 + 0.000*CL	2.156 + 0.000*CL
EN to PAD	t_F	6.995	1.478 + 0.110*CL	1.435 + 0.111*CL	1.338 + 0.113*CL
	t_{PHL}	7.898	4.485 + 0.068*CL	4.709 + 0.064*CL	4.844 + 0.062*CL
	t_{PLZ}	2.239	2.239 + 0.000*CL	2.239 + 0.000*CL	2.239 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POD8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	5.742	1.646 + 0.082*CL	1.653 + 0.082*CL	1.585 + 0.083*CL
	t_{PHL}	7.020	4.215 + 0.056*CL	4.496 + 0.050*CL	4.691 + 0.048*CL
	t_{PLZ}	2.765	2.763 + 0.000*CL	2.764 + 0.000*CL	2.764 + 0.000*CL
EN to PAD	t_F	5.742	1.647 + 0.082*CL	1.653 + 0.082*CL	1.585 + 0.083*CL
	t_{PHL}	7.192	4.387 + 0.056*CL	4.668 + 0.050*CL	4.864 + 0.048*CL
	t_{PLZ}	2.848	2.845 + 0.000*CL	2.847 + 0.000*CL	2.847 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.754	1.409 + 0.067*CL	1.455 + 0.066*CL	1.434 + 0.066*CL
	t_{PHL}	6.586	4.260 + 0.047*CL	4.508 + 0.042*CL	4.692 + 0.039*CL
	t_{PLZ}	2.765	2.763 + 0.000*CL	2.764 + 0.000*CL	2.764 + 0.000*CL
EN to PAD	t_F	4.754	1.409 + 0.067*CL	1.455 + 0.066*CL	1.434 + 0.066*CL
	t_{PHL}	6.759	4.433 + 0.047*CL	4.680 + 0.042*CL	4.864 + 0.039*CL
	t_{PLZ}	2.848	2.846 + 0.000*CL	2.847 + 0.000*CL	2.848 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.604	1.684 + 0.058*CL	1.818 + 0.056*CL	1.879 + 0.055*CL
	t_{PHL}	6.762	4.483 + 0.046*CL	4.801 + 0.039*CL	5.062 + 0.036*CL
	t_{PLZ}	3.133	3.131 + 0.000*CL	3.132 + 0.000*CL	3.132 + 0.000*CL
EN to PAD	t_F	4.604	1.683 + 0.058*CL	1.818 + 0.056*CL	1.879 + 0.055*CL
	t_{PHL}	6.934	4.655 + 0.046*CL	4.973 + 0.039*CL	5.235 + 0.036*CL
	t_{PLZ}	3.216	3.214 + 0.000*CL	3.215 + 0.000*CL	3.215 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POD10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.494	2.829 + 0.073*CL	3.072 + 0.068*CL	3.229 + 0.066*CL
	t_{PHL}	9.394	6.161 + 0.065*CL	6.697 + 0.054*CL	7.149 + 0.048*CL
	t_{PLZ}	3.204	3.202 + 0.000*CL	3.203 + 0.000*CL	3.203 + 0.000*CL
EN to PAD	t_F	6.494	2.829 + 0.073*CL	3.072 + 0.068*CL	3.229 + 0.066*CL
	t_{PHL}	9.567	6.333 + 0.065*CL	6.870 + 0.054*CL	7.321 + 0.048*CL
	t_{PLZ}	3.287	3.285 + 0.000*CL	3.286 + 0.000*CL	3.286 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POD12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.638	3.349 + 0.066*CL	3.653 + 0.060*CL	3.877 + 0.057*CL
	t_{PHL}	9.829	6.518 + 0.066*CL	7.156 + 0.053*CL	7.695 + 0.046*CL
	t_{PLZ}	3.572	3.569 + 0.000*CL	3.571 + 0.000*CL	3.571 + 0.000*CL
EN to PAD	t_F	6.638	3.349 + 0.066*CL	3.653 + 0.060*CL	3.877 + 0.057*CL
	t_{PHL}	10.002	6.690 + 0.066*CL	7.330 + 0.053*CL	7.867 + 0.046*CL
	t_{PLZ}	3.655	3.652 + 0.000*CL	3.655 + 0.000*CL	3.653 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PHL}	17.999	2.434 + 0.311*CL	2.435 + 0.311*CL	2.435 + 0.311*CL
	t_{PLZ}	1.763	1.762 + 0.000*CL	1.763 + 0.000*CL	1.763 + 0.000*CL
EN to PAD	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PHL}	18.171	2.609 + 0.311*CL	2.607 + 0.311*CL	2.604 + 0.311*CL
	t_{PLZ}	1.845	1.845 + 0.000*CL	1.845 + 0.000*CL	1.845 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	18.188	0.706 + 0.350*CL	0.702 + 0.350*CL	0.705 + 0.350*CL
	t_{PHL}	10.958	2.062 + 0.178*CL	2.064 + 0.178*CL	2.061 + 0.178*CL
	t_{PLZ}	1.620	1.620 + 0.000*CL	1.620 + 0.000*CL	1.620 + 0.000*CL
EN to PAD	t_F	18.188	0.706 + 0.350*CL	0.702 + 0.350*CL	0.705 + 0.350*CL
	t_{PHL}	11.130	2.235 + 0.178*CL	2.234 + 0.178*CL	2.234 + 0.178*CL
	t_{PLZ}	1.703	1.703 + 0.000*CL	1.703 + 0.000*CL	1.703 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PHL}	6.393	1.945 + 0.089*CL	1.945 + 0.089*CL	1.945 + 0.089*CL
	t_{PLZ}	1.770	1.770 + 0.000*CL	1.770 + 0.000*CL	1.770 + 0.000*CL
EN to PAD	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PHL}	6.566	2.118 + 0.089*CL	2.118 + 0.089*CL	2.119 + 0.089*CL
	t_{PLZ}	1.853	1.853 + 0.000*CL	1.853 + 0.000*CL	1.853 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOD6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.082	0.254 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PHL}	4.851	1.886 + 0.059*CL	1.886 + 0.059*CL	1.886 + 0.059*CL
	t_{PLZ}	1.729	1.729 + 0.000*CL	1.729 + 0.000*CL	1.729 + 0.000*CL
EN to PAD	t_F	6.082	0.254 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PHL}	5.024	2.058 + 0.059*CL	2.059 + 0.059*CL	2.058 + 0.059*CL
	t_{PLZ}	1.812	1.812 + 0.000*CL	1.812 + 0.000*CL	1.812 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.572	0.205 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PHL}	4.115	1.891 + 0.044*CL	1.891 + 0.044*CL	1.891 + 0.044*CL
	t_{PLZ}	1.804	1.804 + 0.000*CL	1.804 + 0.000*CL	1.804 + 0.000*CL
EN to PAD	t_F	4.572	0.205 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PHL}	4.287	2.063 + 0.044*CL	2.063 + 0.044*CL	2.063 + 0.044*CL
	t_{PLZ}	1.887	1.887 + 0.000*CL	1.887 + 0.000*CL	1.887 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	3.669	0.183 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PHL}	3.688	1.908 + 0.036*CL	1.908 + 0.036*CL	1.909 + 0.036*CL
	t_{PLZ}	1.879	1.879 + 0.000*CL	1.879 + 0.000*CL	1.879 + 0.000*CL
EN to PAD	t_F	3.669	0.183 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PHL}	3.860	2.081 + 0.036*CL	2.081 + 0.036*CL	2.081 + 0.036*CL
	t_{PLZ}	1.962	1.962 + 0.000*CL	1.962 + 0.000*CL	1.962 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOD12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	3.071	0.177 + 0.058*CL	0.163 + 0.058*CL	0.156 + 0.058*CL
	t_{PHL}	3.415	1.931 + 0.030*CL	1.932 + 0.030*CL	1.932 + 0.030*CL
	t_{PLZ}	1.953	1.954 + 0.000*CL	1.953 + 0.000*CL	1.953 + 0.000*CL
EN to PAD	t_F	3.071	0.177 + 0.058*CL	0.163 + 0.058*CL	0.156 + 0.058*CL
	t_{PHL}	3.587	2.104 + 0.030*CL	2.104 + 0.030*CL	2.104 + 0.030*CL
	t_{PLZ}	2.036	2.036 + 0.000*CL	2.036 + 0.000*CL	2.036 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	9.439	0.956 + 0.170*CL	0.850 + 0.172*CL	0.752 + 0.173*CL
	t_{PHL}	8.113	3.603 + 0.090*CL	3.652 + 0.089*CL	3.668 + 0.089*CL
	t_{PLZ}	1.869	1.869 + 0.000*CL	1.869 + 0.000*CL	1.869 + 0.000*CL
EN to PAD	t_F	9.439	0.956 + 0.170*CL	0.850 + 0.172*CL	0.752 + 0.173*CL
	t_{PHL}	8.285	3.776 + 0.090*CL	3.825 + 0.089*CL	3.837 + 0.089*CL
	t_{PLZ}	1.952	1.951 + 0.000*CL	1.952 + 0.000*CL	1.952 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.922	1.379 + 0.111*CL	1.347 + 0.112*CL	1.264 + 0.113*CL
	t_{PHL}	7.391	4.076 + 0.066*CL	4.285 + 0.062*CL	4.414 + 0.060*CL
	t_{PLZ}	2.174	2.173 + 0.000*CL	2.173 + 0.000*CL	2.173 + 0.000*CL
EN to PAD	t_F	6.922	1.379 + 0.111*CL	1.347 + 0.112*CL	1.264 + 0.113*CL
	t_{PHL}	7.563	4.248 + 0.066*CL	4.458 + 0.062*CL	4.585 + 0.060*CL
	t_{PLZ}	2.256	2.255 + 0.000*CL	2.256 + 0.000*CL	2.256 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOD8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.080	1.825 + 0.085*CL	1.936 + 0.083*CL	1.952 + 0.083*CL
	t_{PHL}	7.414	4.439 + 0.059*CL	4.789 + 0.052*CL	5.061 + 0.049*CL
	t_{PLZ}	2.477	2.477 + 0.000*CL	2.477 + 0.000*CL	2.477 + 0.000*CL
EN to PAD	t_F	6.080	1.825 + 0.085*CL	1.936 + 0.083*CL	1.952 + 0.083*CL
	t_{PHL}	7.586	4.611 + 0.059*CL	4.961 + 0.052*CL	5.235 + 0.049*CL
	t_{PLZ}	2.560	2.560 + 0.000*CL	2.560 + 0.000*CL	2.559 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	5.308	1.865 + 0.069*CL	2.008 + 0.066*CL	2.054 + 0.065*CL
	t_{PHL}	6.869	4.256 + 0.052*CL	4.626 + 0.045*CL	4.920 + 0.041*CL
	t_{PLZ}	3.225	3.225 + 0.000*CL	3.225 + 0.000*CL	3.225 + 0.000*CL
EN to PAD	t_F	5.308	1.865 + 0.069*CL	2.008 + 0.066*CL	2.054 + 0.065*CL
	t_{PHL}	7.042	4.428 + 0.052*CL	4.798 + 0.045*CL	5.093 + 0.041*CL
	t_{PLZ}	3.308	3.308 + 0.000*CL	3.308 + 0.000*CL	3.308 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	4.504	1.544 + 0.059*CL	1.686 + 0.056*CL	1.759 + 0.055*CL
	t_{PHL}	6.443	4.222 + 0.044*CL	4.526 + 0.038*CL	4.778 + 0.035*CL
	t_{PLZ}	3.225	3.225 + 0.000*CL	3.225 + 0.000*CL	3.225 + 0.000*CL
EN to PAD	t_F	4.504	1.544 + 0.059*CL	1.686 + 0.056*CL	1.759 + 0.055*CL
	t_{PHL}	6.615	4.395 + 0.044*CL	4.698 + 0.038*CL	4.950 + 0.035*CL
	t_{PLZ}	3.308	3.308 + 0.000*CL	3.308 + 0.000*CL	3.308 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOD10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.249	2.489 + 0.075*CL	2.761 + 0.070*CL	2.944 + 0.067*CL
	t_{PHL}	8.667	5.538 + 0.063*CL	6.042 + 0.052*CL	6.474 + 0.047*CL
	t_{PLZ}	3.279	3.279 + 0.000*CL	3.279 + 0.000*CL	3.279 + 0.000*CL
EN to PAD	t_F	6.249	2.489 + 0.075*CL	2.761 + 0.070*CL	2.944 + 0.067*CL
	t_{PHL}	8.839	5.711 + 0.063*CL	6.214 + 0.052*CL	6.645 + 0.047*CL
	t_{PLZ}	3.362	3.362 + 0.000*CL	3.362 + 0.000*CL	3.362 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOD12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	6.277	2.840 + 0.069*CL	3.189 + 0.062*CL	3.455 + 0.058*CL
	t_{PHL}	8.984	5.804 + 0.064*CL	6.388 + 0.052*CL	6.898 + 0.045*CL
	t_{PLZ}	3.684	3.683 + 0.000*CL	3.684 + 0.000*CL	3.684 + 0.000*CL
EN to PAD	t_F	6.277	2.840 + 0.069*CL	3.189 + 0.062*CL	3.455 + 0.058*CL
	t_{PHL}	9.156	5.976 + 0.064*CL	6.561 + 0.052*CL	7.067 + 0.045*CL
	t_{PLZ}	3.767	3.765 + 0.000*CL	3.767 + 0.000*CL	3.767 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvODyz

Open Drain Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PTOD1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	33.498	2.496 + 0.620*CL	2.456 + 0.621*CL	2.426 + 0.621*CL
	t_{PHL}	17.769	2.404 + 0.307*CL	2.405 + 0.307*CL	2.408 + 0.307*CL
	t_{PLZ}	1.592	1.592 + 0.000*CL	1.592 + 0.000*CL	1.592 + 0.000*CL
EN to PAD	t_F	33.498	2.496 + 0.620*CL	2.456 + 0.621*CL	2.426 + 0.621*CL
	t_{PHL}	17.941	2.579 + 0.307*CL	2.575 + 0.307*CL	2.584 + 0.307*CL
	t_{PLZ}	1.675	1.675 + 0.000*CL	1.675 + 0.000*CL	1.675 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PTOD2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	16.748	1.240 + 0.310*CL	1.234 + 0.310*CL	1.222 + 0.310*CL
	t_{PHL}	9.756	2.082 + 0.153*CL	2.085 + 0.153*CL	2.083 + 0.153*CL
	t_{PLZ}	1.714	1.714 + 0.000*CL	1.714 + 0.000*CL	1.714 + 0.000*CL
EN to PAD	t_F	16.748	1.240 + 0.310*CL	1.234 + 0.310*CL	1.222 + 0.310*CL
	t_{PHL}	9.928	2.255 + 0.153*CL	2.257 + 0.153*CL	2.259 + 0.153*CL
	t_{PLZ}	1.798	1.798 + 0.000*CL	1.798 + 0.000*CL	1.798 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PTOD3

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TN to PAD	t_F	11.158	0.810 + 0.207*CL	0.812 + 0.207*CL	0.809 + 0.207*CL
	t_{PHL}	7.122	2.006 + 0.102*CL	2.009 + 0.102*CL	2.009 + 0.102*CL
	t_{PLZ}	1.836	1.836 + 0.000*CL	1.836 + 0.000*CL	1.836 + 0.000*CL
EN to PAD	t_F	11.158	0.810 + 0.207*CL	0.812 + 0.207*CL	0.809 + 0.207*CL
	t_{PHL}	7.294	2.178 + 0.102*CL	2.181 + 0.102*CL	2.183 + 0.102*CL
	t_{PLZ}	1.919	1.919 + 0.000*CL	1.919 + 0.000*CL	1.919 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Cell Availability

2.5V Interface	3.3V Interface	5V Tolerant
POT(1/2/4/6/8/10/12) POT(4/6/8/10/12)SM POT(10/12)SH	PHOT(1/2/4/6/8/10/12) PHOT(4/6/8/10/12)SM PHOT(10/12)SH	PTOT(1/2/3)

Logic Symbol



Truth Table

TN	EN	A	PAD
1	0	0	0
1	0	1	1
x	1	x	Hi-Z
0	x	x	Hi-Z

Standard Load (SL)

Cell Name	TN	EN	A
POT(1/2/4/6/8/10/12)	2.833	2.816	5.147
POT(4/6/8/10/12)SM	2.833	2.816	5.147
POT(10/12)SH	2.833	2.816	5.147
PHOT(1/2/4/6/8/10/12)	2.833	2.816	5.147
PHOT(4/6/8/10/12)SM	2.833	2.816	5.147
PHOT(10/12)SH	2.833	2.816	5.147
PTOT(1/2/3)	2.833	2.816	5.147

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	31.508	1.210 + 0.606*CL	1.212 + 0.606*CL	1.209 + 0.606*CL
	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PLH}	16.405	1.897 + 0.290*CL	1.897 + 0.290*CL	1.900 + 0.290*CL
	t_{PHL}	18.184	2.076 + 0.322*CL	2.074 + 0.322*CL	2.077 + 0.322*CL
TN to PAD	t_R	31.508	1.210 + 0.606*CL	1.212 + 0.606*CL	1.209 + 0.606*CL
	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PLH}	16.690	2.180 + 0.290*CL	2.182 + 0.290*CL	2.182 + 0.290*CL
	t_{PHL}	18.589	2.477 + 0.322*CL	2.481 + 0.322*CL	2.478 + 0.322*CL
	t_{PLZ}	1.841	1.841 + 0.000*CL	1.841 + 0.000*CL	1.841 + 0.000*CL
	t_{PHZ}	1.584	1.584 + 0.000*CL	1.584 + 0.000*CL	1.584 + 0.000*CL
EN to PAD	t_R	31.508	1.210 + 0.606*CL	1.212 + 0.606*CL	1.209 + 0.606*CL
	t_F	33.275	1.275 + 0.640*CL	1.279 + 0.640*CL	1.276 + 0.640*CL
	t_{PLH}	16.870	2.362 + 0.290*CL	2.362 + 0.290*CL	2.365 + 0.290*CL
	t_{PHL}	18.769	2.659 + 0.322*CL	2.661 + 0.322*CL	2.661 + 0.322*CL
	t_{PLZ}	1.923	1.923 + 0.000*CL	1.923 + 0.000*CL	1.923 + 0.000*CL
	t_{PHZ}	1.667	1.667 + 0.000*CL	1.667 + 0.000*CL	1.667 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	15.772	0.624 + 0.303*CL	0.622 + 0.303*CL	0.625 + 0.303*CL
	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PLH}	8.962	1.708 + 0.145*CL	1.709 + 0.145*CL	1.708 + 0.145*CL
	t_{PHL}	10.822	1.703 + 0.182*CL	1.704 + 0.182*CL	1.701 + 0.182*CL
TN to PAD	t_R	15.772	0.624 + 0.303*CL	0.622 + 0.303*CL	0.625 + 0.303*CL
	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PLH}	9.247	1.991 + 0.145*CL	1.992 + 0.145*CL	1.993 + 0.145*CL
	t_{PHL}	11.226	2.105 + 0.182*CL	2.106 + 0.182*CL	2.106 + 0.182*CL
	t_{PLZ}	1.690	1.690 + 0.000*CL	1.690 + 0.000*CL	1.690 + 0.000*CL
	t_{PHZ}	1.690	1.690 + 0.000*CL	1.690 + 0.000*CL	1.690 + 0.000*CL
EN to PAD	t_R	15.772	0.624 + 0.303*CL	0.622 + 0.303*CL	0.625 + 0.303*CL
	t_F	18.210	0.685 + 0.351*CL	0.688 + 0.350*CL	0.685 + 0.350*CL
	t_{PLH}	9.427	2.174 + 0.145*CL	2.173 + 0.145*CL	2.173 + 0.145*CL
	t_{PHL}	11.406	2.288 + 0.182*CL	2.286 + 0.182*CL	2.289 + 0.182*CL
	t_{PLZ}	1.772	1.772 + 0.000*CL	1.772 + 0.000*CL	1.772 + 0.000*CL
	t_{PHZ}	1.773	1.773 + 0.000*CL	1.773 + 0.000*CL	1.773 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.917	0.348 + 0.151*CL	0.342 + 0.151*CL	0.343 + 0.151*CL
	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PLH}	5.396	1.769 + 0.073*CL	1.769 + 0.073*CL	1.770 + 0.073*CL
	t_{PHL}	6.155	1.597 + 0.091*CL	1.596 + 0.091*CL	1.597 + 0.091*CL
TN to PAD	t_R	7.917	0.348 + 0.151*CL	0.342 + 0.151*CL	0.343 + 0.151*CL
	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PLH}	5.681	2.052 + 0.073*CL	2.053 + 0.073*CL	2.054 + 0.073*CL
	t_{PHL}	6.558	1.996 + 0.091*CL	1.998 + 0.091*CL	1.998 + 0.091*CL
	t_{PLZ}	1.822	1.822 + 0.000*CL	1.822 + 0.000*CL	1.822 + 0.000*CL
	t_{PHZ}	1.901	1.901 + 0.000*CL	1.901 + 0.000*CL	1.901 + 0.000*CL
EN to PAD	t_R	7.917	0.348 + 0.151*CL	0.342 + 0.151*CL	0.343 + 0.151*CL
	t_F	9.121	0.359 + 0.175*CL	0.359 + 0.175*CL	0.359 + 0.175*CL
	t_{PLH}	5.861	2.234 + 0.073*CL	2.234 + 0.073*CL	2.235 + 0.073*CL
	t_{PHL}	6.739	2.178 + 0.091*CL	2.179 + 0.091*CL	2.180 + 0.091*CL
	t_{PLZ}	1.905	1.905 + 0.000*CL	1.905 + 0.000*CL	1.905 + 0.000*CL
	t_{PHZ}	1.983	1.983 + 0.000*CL	1.983 + 0.000*CL	1.983 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.317	0.309 + 0.100*CL	0.280 + 0.101*CL	0.265 + 0.101*CL
	t_F	6.097	0.261 + 0.117*CL	0.256 + 0.117*CL	0.256 + 0.117*CL
	t_{PLH}	4.332	1.913 + 0.048*CL	1.914 + 0.048*CL	1.914 + 0.048*CL
	t_{PHL}	4.652	1.616 + 0.061*CL	1.614 + 0.061*CL	1.612 + 0.061*CL
TN to PAD	t_R	5.317	0.309 + 0.100*CL	0.280 + 0.101*CL	0.265 + 0.101*CL
	t_F	6.097	0.260 + 0.117*CL	0.256 + 0.117*CL	0.256 + 0.117*CL
	t_{PLH}	4.617	2.196 + 0.048*CL	2.197 + 0.048*CL	2.198 + 0.048*CL
	t_{PHL}	5.051	2.008 + 0.061*CL	2.009 + 0.061*CL	2.011 + 0.061*CL
	t_{PLZ}	1.950	1.950 + 0.000*CL	1.950 + 0.000*CL	1.950 + 0.000*CL
	t_{PHZ}	2.110	2.110 + 0.000*CL	2.110 + 0.000*CL	2.110 + 0.000*CL
EN to PAD	t_R	5.317	0.309 + 0.100*CL	0.280 + 0.101*CL	0.265 + 0.101*CL
	t_F	6.097	0.260 + 0.117*CL	0.256 + 0.117*CL	0.256 + 0.117*CL
	t_{PLH}	4.797	2.378 + 0.048*CL	2.379 + 0.048*CL	2.379 + 0.048*CL
	t_{PHL}	5.231	2.190 + 0.061*CL	2.191 + 0.061*CL	2.192 + 0.061*CL
	t_{PLZ}	2.033	2.033 + 0.000*CL	2.033 + 0.000*CL	2.033 + 0.000*CL
	t_{PHZ}	2.193	2.193 + 0.000*CL	2.193 + 0.000*CL	2.193 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.049	0.351 + 0.074*CL	0.303 + 0.075*CL	0.269 + 0.075*CL
	t_F	4.592	0.229 + 0.087*CL	0.216 + 0.088*CL	0.210 + 0.088*CL
	t_{PLH}	3.892	2.073 + 0.036*CL	2.078 + 0.036*CL	2.079 + 0.036*CL
	t_{PHL}	3.941	1.672 + 0.045*CL	1.667 + 0.045*CL	1.663 + 0.046*CL
TN to PAD	t_R	4.049	0.351 + 0.074*CL	0.303 + 0.075*CL	0.269 + 0.075*CL
	t_F	4.591	0.227 + 0.087*CL	0.214 + 0.088*CL	0.209 + 0.088*CL
	t_{PLH}	4.177	2.356 + 0.036*CL	2.362 + 0.036*CL	2.363 + 0.036*CL
	t_{PHL}	4.333	2.048 + 0.046*CL	2.051 + 0.046*CL	2.053 + 0.046*CL
	t_{PLZ}	2.078	2.078 + 0.000*CL	2.078 + 0.000*CL	2.078 + 0.000*CL
	t_{PHZ}	2.320	2.320 + 0.000*CL	2.319 + 0.000*CL	2.320 + 0.000*CL
EN to PAD	t_R	4.049	0.351 + 0.074*CL	0.303 + 0.075*CL	0.269 + 0.075*CL
	t_F	4.591	0.227 + 0.087*CL	0.214 + 0.088*CL	0.209 + 0.088*CL
	t_{PLH}	4.357	2.539 + 0.036*CL	2.543 + 0.036*CL	2.544 + 0.036*CL
	t_{PHL}	4.513	2.230 + 0.046*CL	2.232 + 0.046*CL	2.233 + 0.046*CL
	t_{PLZ}	2.160	2.160 + 0.000*CL	2.160 + 0.000*CL	2.160 + 0.000*CL
	t_{PHZ}	2.402	2.402 + 0.000*CL	2.402 + 0.000*CL	2.402 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.218	0.240 + 0.060*CL	0.209 + 0.060*CL	0.191 + 0.060*CL
	t_F	3.669	0.176 + 0.070*CL	0.166 + 0.070*CL	0.164 + 0.070*CL
	t_{PLH}	3.324	1.871 + 0.029*CL	1.873 + 0.029*CL	1.873 + 0.029*CL
	t_{PHL}	3.435	1.613 + 0.036*CL	1.612 + 0.036*CL	1.611 + 0.036*CL
TN to PAD	t_R	3.218	0.240 + 0.060*CL	0.209 + 0.060*CL	0.191 + 0.060*CL
	t_F	3.668	0.174 + 0.070*CL	0.166 + 0.070*CL	0.163 + 0.070*CL
	t_{PLH}	3.610	2.154 + 0.029*CL	2.157 + 0.029*CL	2.158 + 0.029*CL
	t_{PHL}	3.834	2.005 + 0.037*CL	2.008 + 0.037*CL	2.009 + 0.036*CL
	t_{PLZ}	1.978	1.978 + 0.000*CL	1.978 + 0.000*CL	1.978 + 0.000*CL
	t_{PHZ}	2.070	2.070 + 0.000*CL	2.070 + 0.000*CL	2.070 + 0.000*CL
EN to PAD	t_R	3.218	0.240 + 0.060*CL	0.209 + 0.060*CL	0.191 + 0.060*CL
	t_F	3.668	0.174 + 0.070*CL	0.166 + 0.070*CL	0.163 + 0.070*CL
	t_{PLH}	3.790	2.337 + 0.029*CL	2.338 + 0.029*CL	2.339 + 0.029*CL
	t_{PHL}	4.014	2.188 + 0.037*CL	2.189 + 0.037*CL	2.190 + 0.036*CL
	t_{PLZ}	2.061	2.061 + 0.000*CL	2.061 + 0.000*CL	2.061 + 0.000*CL
	t_{PHZ}	2.153	2.153 + 0.000*CL	2.153 + 0.000*CL	2.153 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	2.721	0.269 + 0.049*CL	0.232 + 0.050*CL	0.204 + 0.050*CL
	t_F	3.069	0.169 + 0.058*CL	0.155 + 0.058*CL	0.148 + 0.058*CL
	t_{PLH}	3.168	1.952 + 0.024*CL	1.958 + 0.024*CL	1.959 + 0.024*CL
	t_{PHL}	3.159	1.645 + 0.030*CL	1.642 + 0.030*CL	1.640 + 0.030*CL
TN to PAD	t_R	2.721	0.269 + 0.049*CL	0.232 + 0.050*CL	0.204 + 0.050*CL
	t_F	3.069	0.167 + 0.058*CL	0.154 + 0.058*CL	0.147 + 0.058*CL
	t_{PLH}	3.453	2.236 + 0.024*CL	2.242 + 0.024*CL	2.243 + 0.024*CL
	t_{PHL}	3.555	2.030 + 0.031*CL	2.033 + 0.030*CL	2.034 + 0.030*CL
	t_{PLZ}	2.043	2.043 + 0.000*CL	2.043 + 0.000*CL	2.043 + 0.000*CL
	t_{PHZ}	2.175	2.175 + 0.000*CL	2.175 + 0.000*CL	2.175 + 0.000*CL
EN to PAD	t_R	2.721	0.269 + 0.049*CL	0.232 + 0.050*CL	0.204 + 0.050*CL
	t_F	3.069	0.167 + 0.058*CL	0.154 + 0.058*CL	0.147 + 0.058*CL
	t_{PLH}	3.634	2.418 + 0.024*CL	2.424 + 0.024*CL	2.424 + 0.024*CL
	t_{PHL}	3.736	2.212 + 0.030*CL	2.214 + 0.030*CL	2.215 + 0.030*CL
	t_{PLZ}	2.126	2.126 + 0.000*CL	2.126 + 0.000*CL	2.126 + 0.000*CL
	t_{PHZ}	2.258	2.258 + 0.000*CL	2.258 + 0.000*CL	2.258 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.136	0.756 + 0.148*CL	0.663 + 0.149*CL	0.590 + 0.150*CL
	t_F	9.485	1.005 + 0.170*CL	0.893 + 0.172*CL	0.791 + 0.173*CL
	t_{PLH}	6.615	2.960 + 0.073*CL	2.981 + 0.073*CL	2.986 + 0.073*CL
	t_{PHL}	8.253	3.616 + 0.093*CL	3.678 + 0.092*CL	3.695 + 0.091*CL
TN to PAD	t_R	8.136	0.756 + 0.148*CL	0.663 + 0.149*CL	0.590 + 0.150*CL
	t_F	9.485	1.005 + 0.170*CL	0.893 + 0.172*CL	0.791 + 0.173*CL
	t_{PLH}	6.900	3.243 + 0.073*CL	3.265 + 0.073*CL	3.272 + 0.073*CL
	t_{PHL}	8.656	4.018 + 0.093*CL	4.080 + 0.092*CL	4.095 + 0.091*CL
	t_{PLZ}	2.052	2.052 + 0.000*CL	2.052 + 0.000*CL	2.052 + 0.000*CL
	t_{PHZ}	2.446	2.446 + 0.000*CL	2.446 + 0.000*CL	2.446 + 0.000*CL
EN to PAD	t_R	8.136	0.756 + 0.148*CL	0.663 + 0.149*CL	0.590 + 0.150*CL
	t_F	9.485	1.005 + 0.170*CL	0.893 + 0.172*CL	0.791 + 0.173*CL
	t_{PLH}	7.080	3.425 + 0.073*CL	3.446 + 0.073*CL	3.452 + 0.073*CL
	t_{PHL}	8.836	4.200 + 0.093*CL	4.261 + 0.092*CL	4.278 + 0.091*CL
	t_{PLZ}	2.135	2.135 + 0.000*CL	2.135 + 0.000*CL	2.135 + 0.000*CL
	t_{PHZ}	2.529	2.529 + 0.000*CL	2.529 + 0.000*CL	2.529 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.049	1.312 + 0.095*CL	1.251 + 0.096*CL	1.155 + 0.097*CL
	t_F	6.982	1.450 + 0.111*CL	1.413 + 0.111*CL	1.321 + 0.113*CL
	t_{PLH}	6.260	3.553 + 0.054*CL	3.735 + 0.051*CL	3.836 + 0.049*CL
	t_{PHL}	7.564	4.152 + 0.068*CL	4.374 + 0.064*CL	4.509 + 0.062*CL
TN to PAD	t_R	6.049	1.312 + 0.095*CL	1.252 + 0.096*CL	1.155 + 0.097*CL
	t_F	6.982	1.451 + 0.111*CL	1.414 + 0.111*CL	1.322 + 0.113*CL
	t_{PLH}	6.546	3.837 + 0.054*CL	4.020 + 0.051*CL	4.122 + 0.049*CL
	t_{PHL}	7.966	4.553 + 0.068*CL	4.777 + 0.064*CL	4.912 + 0.062*CL
	t_{PLZ}	2.331	2.331 + 0.000*CL	2.331 + 0.000*CL	2.331 + 0.000*CL
	t_{PHZ}	3.326	3.326 + 0.000*CL	3.326 + 0.000*CL	3.326 + 0.000*CL
EN to PAD	t_R	6.049	1.312 + 0.095*CL	1.252 + 0.096*CL	1.155 + 0.097*CL
	t_F	6.982	1.451 + 0.111*CL	1.414 + 0.111*CL	1.322 + 0.113*CL
	t_{PLH}	6.726	4.020 + 0.054*CL	4.201 + 0.051*CL	4.303 + 0.049*CL
	t_{PHL}	8.147	4.735 + 0.068*CL	4.958 + 0.064*CL	5.094 + 0.062*CL
	t_{PLZ}	2.414	2.414 + 0.000*CL	2.414 + 0.000*CL	2.414 + 0.000*CL
	t_{PHZ}	3.409	3.409 + 0.000*CL	3.409 + 0.000*CL	3.409 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.157	1.657 + 0.070*CL	1.671 + 0.070*CL	1.601 + 0.071*CL
	t_F	5.712	1.575 + 0.083*CL	1.605 + 0.082*CL	1.549 + 0.083*CL
	t_{PLH}	5.906	3.567 + 0.047*CL	3.850 + 0.041*CL	4.043 + 0.039*CL
	t_{PHL}	6.869	4.083 + 0.056*CL	4.352 + 0.050*CL	4.541 + 0.048*CL
TN to PAD	t_R	5.158	1.661 + 0.070*CL	1.673 + 0.070*CL	1.602 + 0.071*CL
	t_F	5.723	1.615 + 0.082*CL	1.625 + 0.082*CL	1.561 + 0.083*CL
	t_{PLH}	6.191	3.850 + 0.047*CL	4.135 + 0.041*CL	4.328 + 0.039*CL
	t_{PHL}	7.260	4.454 + 0.056*CL	4.735 + 0.050*CL	4.930 + 0.048*CL
	t_{PLZ}	2.936	2.936 + 0.000*CL	2.936 + 0.000*CL	2.936 + 0.000*CL
	t_{PHZ}	4.179	4.179 + 0.000*CL	4.179 + 0.000*CL	4.179 + 0.000*CL
EN to PAD	t_R	5.158	1.661 + 0.070*CL	1.673 + 0.070*CL	1.602 + 0.071*CL
	t_F	5.723	1.615 + 0.082*CL	1.625 + 0.082*CL	1.561 + 0.083*CL
	t_{PLH}	6.372	4.033 + 0.047*CL	4.316 + 0.041*CL	4.509 + 0.039*CL
	t_{PHL}	7.440	4.636 + 0.056*CL	4.917 + 0.050*CL	5.111 + 0.048*CL
	t_{PLZ}	3.018	3.018 + 0.000*CL	3.018 + 0.000*CL	3.018 + 0.000*CL
	t_{PHZ}	4.262	4.262 + 0.000*CL	4.262 + 0.000*CL	4.262 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.208	1.327 + 0.058*CL	1.366 + 0.057*CL	1.346 + 0.057*CL
	t_F	4.733	1.366 + 0.067*CL	1.422 + 0.066*CL	1.407 + 0.066*CL
	t_{PLH}	5.547	3.634 + 0.038*CL	3.859 + 0.034*CL	4.027 + 0.032*CL
	t_{PHL}	6.428	4.108 + 0.046*CL	4.352 + 0.042*CL	4.533 + 0.039*CL
TN to PAD	t_R	4.208	1.327 + 0.058*CL	1.366 + 0.057*CL	1.346 + 0.057*CL
	t_F	4.736	1.381 + 0.067*CL	1.430 + 0.066*CL	1.412 + 0.066*CL
	t_{PLH}	5.833	3.920 + 0.038*CL	4.145 + 0.034*CL	4.313 + 0.032*CL
	t_{PHL}	6.826	4.499 + 0.047*CL	4.747 + 0.042*CL	4.931 + 0.039*CL
	t_{PLZ}	2.936	2.936 + 0.000*CL	2.936 + 0.000*CL	2.936 + 0.000*CL
	t_{PHZ}	4.179	4.179 + 0.000*CL	4.179 + 0.000*CL	4.179 + 0.000*CL
EN to PAD	t_R	4.208	1.327 + 0.058*CL	1.366 + 0.057*CL	1.346 + 0.057*CL
	t_F	4.736	1.381 + 0.067*CL	1.430 + 0.066*CL	1.412 + 0.066*CL
	t_{PLH}	6.014	4.102 + 0.038*CL	4.326 + 0.034*CL	4.494 + 0.032*CL
	t_{PHL}	7.007	4.681 + 0.047*CL	4.928 + 0.042*CL	5.112 + 0.039*CL
	t_{PLZ}	3.018	3.018 + 0.000*CL	3.018 + 0.000*CL	3.018 + 0.000*CL
	t_{PHZ}	4.262	4.261 + 0.000*CL	4.262 + 0.000*CL	4.262 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.196	1.636 + 0.051*CL	1.780 + 0.048*CL	1.853 + 0.047*CL
	t_F	4.558	1.568 + 0.060*CL	1.742 + 0.056*CL	1.824 + 0.055*CL
	t_{PLH}	5.781	3.826 + 0.039*CL	4.130 + 0.033*CL	4.385 + 0.030*CL
	t_{PHL}	6.623	4.382 + 0.045*CL	4.677 + 0.039*CL	4.927 + 0.036*CL
TN to PAD	t_R	4.196	1.637 + 0.051*CL	1.782 + 0.048*CL	1.854 + 0.047*CL
	t_F	4.583	1.655 + 0.059*CL	1.790 + 0.056*CL	1.854 + 0.055*CL
	t_{PLH}	6.068	4.111 + 0.039*CL	4.416 + 0.033*CL	4.672 + 0.030*CL
	t_{PHL}	7.004	4.722 + 0.046*CL	5.042 + 0.039*CL	5.304 + 0.036*CL
	t_{PLZ}	3.304	3.304 + 0.000*CL	3.304 + 0.000*CL	3.304 + 0.000*CL
	t_{PHZ}	5.058	5.057 + 0.000*CL	5.057 + 0.000*CL	5.058 + 0.000*CL
EN to PAD	t_R	4.196	1.637 + 0.051*CL	1.782 + 0.048*CL	1.854 + 0.047*CL
	t_F	4.583	1.655 + 0.059*CL	1.790 + 0.056*CL	1.854 + 0.055*CL
	t_{PLH}	6.248	4.294 + 0.039*CL	4.597 + 0.033*CL	4.852 + 0.030*CL
	t_{PHL}	7.184	4.905 + 0.046*CL	5.223 + 0.039*CL	5.485 + 0.036*CL
	t_{PLZ}	3.387	3.387 + 0.000*CL	3.387 + 0.000*CL	3.387 + 0.000*CL
	t_{PHZ}	5.140	5.140 + 0.000*CL	5.140 + 0.000*CL	5.140 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

POT10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.218	2.939 + 0.066*CL	3.224 + 0.060*CL	3.411 + 0.057*CL
	t_F	6.448	2.737 + 0.074*CL	3.005 + 0.069*CL	3.175 + 0.067*CL
	t_{PLH}	8.547	5.619 + 0.059*CL	6.170 + 0.048*CL	6.638 + 0.041*CL
	t_{PHL}	9.261	6.045 + 0.064*CL	6.571 + 0.054*CL	7.015 + 0.048*CL
TN to PAD	t_R	6.220	2.942 + 0.066*CL	3.226 + 0.060*CL	3.414 + 0.057*CL
	t_F	6.460	2.782 + 0.074*CL	3.029 + 0.069*CL	3.189 + 0.066*CL
	t_{PLH}	8.834	5.906 + 0.059*CL	6.457 + 0.048*CL	6.927 + 0.041*CL
	t_{PHL}	9.657	6.424 + 0.065*CL	6.961 + 0.054*CL	7.411 + 0.048*CL
	t_{PLZ}	3.415	3.415 + 0.000*CL	3.415 + 0.000*CL	3.414 + 0.000*CL
	t_{PHZ}	5.160	5.160 + 0.000*CL	5.160 + 0.000*CL	5.160 + 0.000*CL
EN to PAD	t_R	6.220	2.942 + 0.066*CL	3.226 + 0.060*CL	3.414 + 0.057*CL
	t_F	6.460	2.782 + 0.074*CL	3.029 + 0.069*CL	3.189 + 0.066*CL
	t_{PLH}	9.014	6.088 + 0.059*CL	6.639 + 0.048*CL	7.103 + 0.041*CL
	t_{PHL}	9.837	6.607 + 0.065*CL	7.142 + 0.054*CL	7.594 + 0.048*CL
	t_{PLZ}	3.498	3.498 + 0.000*CL	3.498 + 0.000*CL	3.498 + 0.000*CL
	t_{PHZ}	5.243	5.242 + 0.000*CL	5.243 + 0.000*CL	5.243 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	6.593	3.555 + 0.061*CL	3.937 + 0.053*CL	4.210 + 0.049*CL
	t_F	6.548	3.126 + 0.068*CL	3.508 + 0.061*CL	3.773 + 0.057*CL
	t_{PLH}	9.056	5.919 + 0.063*CL	6.599 + 0.049*CL	7.177 + 0.041*CL
	t_{PHL}	9.722	6.468 + 0.065*CL	7.071 + 0.053*CL	7.594 + 0.046*CL
TN to PAD	t_R	6.596	3.560 + 0.061*CL	3.941 + 0.053*CL	4.214 + 0.049*CL
	t_F	6.600	3.299 + 0.066*CL	3.606 + 0.060*CL	3.832 + 0.057*CL
	t_{PLH}	9.344	6.206 + 0.063*CL	6.887 + 0.049*CL	7.465 + 0.041*CL
	t_{PHL}	10.098	6.787 + 0.066*CL	7.426 + 0.053*CL	7.966 + 0.046*CL
	t_{PLZ}	3.783	3.783 + 0.000*CL	3.783 + 0.000*CL	3.783 + 0.000*CL
	t_{PHZ}	6.038	6.037 + 0.000*CL	6.038 + 0.000*CL	6.038 + 0.000*CL
EN to PAD	t_R	6.596	3.560 + 0.061*CL	3.941 + 0.053*CL	4.214 + 0.049*CL
	t_F	6.600	3.299 + 0.066*CL	3.606 + 0.060*CL	3.832 + 0.057*CL
	t_{PLH}	9.525	6.388 + 0.063*CL	7.070 + 0.049*CL	7.641 + 0.041*CL
	t_{PHL}	10.278	6.970 + 0.066*CL	7.608 + 0.053*CL	8.145 + 0.046*CL
	t_{PLZ}	3.866	3.866 + 0.000*CL	3.866 + 0.000*CL	3.866 + 0.000*CL
	t_{PHZ}	6.121	6.120 + 0.000*CL	6.121 + 0.000*CL	6.121 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	42.148	1.623 + 0.811*CL	1.624 + 0.810*CL	1.621 + 0.811*CL
	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PLH}	20.687	1.940 + 0.375*CL	1.939 + 0.375*CL	1.942 + 0.375*CL
	t_{PHL}	17.678	2.113 + 0.311*CL	2.114 + 0.311*CL	2.114 + 0.311*CL
TN to PAD	t_R	42.146	1.623 + 0.810*CL	1.620 + 0.811*CL	1.623 + 0.810*CL
	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PLH}	21.198	2.448 + 0.375*CL	2.448 + 0.375*CL	2.451 + 0.375*CL
	t_{PHL}	18.144	2.577 + 0.311*CL	2.578 + 0.311*CL	2.581 + 0.311*CL
	t_{PLZ}	1.813	1.813 + 0.000*CL	1.813 + 0.000*CL	1.813 + 0.000*CL
	t_{PHZ}	1.525	1.525 + 0.000*CL	1.525 + 0.000*CL	1.525 + 0.000*CL
EN to PAD	t_R	42.146	1.623 + 0.810*CL	1.620 + 0.811*CL	1.623 + 0.810*CL
	t_F	33.014	1.269 + 0.635*CL	1.270 + 0.635*CL	1.267 + 0.635*CL
	t_{PLH}	21.379	2.629 + 0.375*CL	2.633 + 0.375*CL	2.630 + 0.375*CL
	t_{PHL}	18.324	2.761 + 0.311*CL	2.760 + 0.311*CL	2.757 + 0.311*CL
	t_{PLZ}	1.896	1.896 + 0.000*CL	1.896 + 0.000*CL	1.896 + 0.000*CL
	t_{PHZ}	1.608	1.608 + 0.000*CL	1.608 + 0.000*CL	1.608 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	21.098	0.836 + 0.405*CL	0.836 + 0.405*CL	0.833 + 0.405*CL
	t_F	18.188	0.706 + 0.350*CL	0.702 + 0.350*CL	0.705 + 0.350*CL
	t_{PLH}	10.983	1.609 + 0.187*CL	1.609 + 0.187*CL	1.609 + 0.187*CL
	t_{PHL}	10.634	1.738 + 0.178*CL	1.738 + 0.178*CL	1.741 + 0.178*CL
TN to PAD	t_R	21.098	0.836 + 0.405*CL	0.836 + 0.405*CL	0.833 + 0.405*CL
	t_F	18.188	0.706 + 0.350*CL	0.702 + 0.350*CL	0.705 + 0.350*CL
	t_{PLH}	11.494	2.118 + 0.188*CL	2.120 + 0.187*CL	2.120 + 0.187*CL
	t_{PHL}	11.101	2.202 + 0.178*CL	2.205 + 0.178*CL	2.205 + 0.178*CL
	t_{PLZ}	1.669	1.669 + 0.000*CL	1.669 + 0.000*CL	1.669 + 0.000*CL
	t_{PHZ}	1.572	1.572 + 0.000*CL	1.572 + 0.000*CL	1.572 + 0.000*CL
EN to PAD	t_R	21.098	0.836 + 0.405*CL	0.836 + 0.405*CL	0.833 + 0.405*CL
	t_F	18.188	0.706 + 0.350*CL	0.702 + 0.350*CL	0.705 + 0.350*CL
	t_{PLH}	11.674	2.301 + 0.187*CL	2.300 + 0.187*CL	2.300 + 0.187*CL
	t_{PHL}	11.281	2.385 + 0.178*CL	2.385 + 0.178*CL	2.388 + 0.178*CL
	t_{PLZ}	1.752	1.752 + 0.000*CL	1.752 + 0.000*CL	1.752 + 0.000*CL
	t_{PHZ}	1.655	1.655 + 0.000*CL	1.655 + 0.000*CL	1.655 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT4

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.563	0.433 + 0.203*CL	0.431 + 0.203*CL	0.431 + 0.203*CL
	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PLH}	6.206	1.519 + 0.094*CL	1.519 + 0.094*CL	1.519 + 0.094*CL
	t_{PHL}	6.074	1.626 + 0.089*CL	1.626 + 0.089*CL	1.627 + 0.089*CL
TN to PAD	t_R	10.563	0.433 + 0.203*CL	0.431 + 0.203*CL	0.431 + 0.203*CL
	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PLH}	6.717	2.027 + 0.094*CL	2.029 + 0.094*CL	2.031 + 0.094*CL
	t_{PHL}	6.540	2.090 + 0.089*CL	2.091 + 0.089*CL	2.090 + 0.089*CL
	t_{PLZ}	1.821	1.821 + 0.000*CL	1.821 + 0.000*CL	1.821 + 0.000*CL
	t_{PHZ}	1.665	1.665 + 0.000*CL	1.665 + 0.000*CL	1.664 + 0.000*CL
EN to PAD	t_R	10.563	0.433 + 0.203*CL	0.431 + 0.203*CL	0.431 + 0.203*CL
	t_F	9.114	0.371 + 0.175*CL	0.371 + 0.175*CL	0.372 + 0.175*CL
	t_{PLH}	6.897	2.210 + 0.094*CL	2.210 + 0.094*CL	2.210 + 0.094*CL
	t_{PHL}	6.720	2.272 + 0.089*CL	2.272 + 0.089*CL	2.272 + 0.089*CL
	t_{PLZ}	1.903	1.903 + 0.000*CL	1.903 + 0.000*CL	1.903 + 0.000*CL
	t_{PHZ}	1.748	1.748 + 0.000*CL	1.748 + 0.000*CL	1.748 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT6

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.047	0.293 + 0.135*CL	0.294 + 0.135*CL	0.293 + 0.135*CL
	t_F	6.082	0.254 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PLH}	4.603	1.478 + 0.063*CL	1.478 + 0.062*CL	1.479 + 0.062*CL
	t_{PHL}	4.551	1.586 + 0.059*CL	1.586 + 0.059*CL	1.586 + 0.059*CL
TN to PAD	t_R	7.047	0.293 + 0.135*CL	0.294 + 0.135*CL	0.293 + 0.135*CL
	t_F	6.082	0.254 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PLH}	5.114	1.986 + 0.063*CL	1.988 + 0.063*CL	1.988 + 0.063*CL
	t_{PHL}	5.017	2.049 + 0.059*CL	2.050 + 0.059*CL	2.051 + 0.059*CL
	t_{PLZ}	1.811	1.811 + 0.000*CL	1.811 + 0.000*CL	1.811 + 0.000*CL
	t_{PHZ}	1.667	1.667 + 0.000*CL	1.667 + 0.000*CL	1.667 + 0.000*CL
EN to PAD	t_R	7.047	0.293 + 0.135*CL	0.294 + 0.135*CL	0.293 + 0.135*CL
	t_F	6.082	0.254 + 0.117*CL	0.254 + 0.117*CL	0.255 + 0.117*CL
	t_{PLH}	5.294	2.169 + 0.063*CL	2.169 + 0.062*CL	2.169 + 0.062*CL
	t_{PHL}	5.197	2.231 + 0.059*CL	2.232 + 0.059*CL	2.232 + 0.059*CL
	t_{PLZ}	1.893	1.893 + 0.000*CL	1.893 + 0.000*CL	1.893 + 0.000*CL
	t_{PHZ}	1.750	1.750 + 0.000*CL	1.750 + 0.000*CL	1.750 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT8

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.293	0.229 + 0.101*CL	0.228 + 0.101*CL	0.227 + 0.101*CL
	t_F	4.572	0.205 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PLH}	3.835	1.491 + 0.047*CL	1.492 + 0.047*CL	1.492 + 0.047*CL
	t_{PHL}	3.818	1.593 + 0.044*CL	1.594 + 0.044*CL	1.594 + 0.044*CL
TN to PAD	t_R	5.293	0.229 + 0.101*CL	0.228 + 0.101*CL	0.227 + 0.101*CL
	t_F	4.572	0.205 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PLH}	4.346	1.999 + 0.047*CL	2.001 + 0.047*CL	2.002 + 0.047*CL
	t_{PHL}	4.283	2.056 + 0.045*CL	2.058 + 0.045*CL	2.059 + 0.044*CL
	t_{PLZ}	1.887	1.887 + 0.000*CL	1.887 + 0.000*CL	1.887 + 0.000*CL
	t_{PHZ}	1.714	1.714 + 0.000*CL	1.714 + 0.000*CL	1.714 + 0.000*CL
EN to PAD	t_R	5.293	0.229 + 0.101*CL	0.228 + 0.101*CL	0.227 + 0.101*CL
	t_F	4.572	0.205 + 0.087*CL	0.202 + 0.087*CL	0.201 + 0.087*CL
	t_{PLH}	4.526	2.182 + 0.047*CL	2.182 + 0.047*CL	2.183 + 0.047*CL
	t_{PHL}	4.463	2.239 + 0.044*CL	2.239 + 0.044*CL	2.239 + 0.044*CL
	t_{PLZ}	1.969	1.969 + 0.000*CL	1.969 + 0.000*CL	1.969 + 0.000*CL
	t_{PHZ}	1.796	1.796 + 0.000*CL	1.796 + 0.000*CL	1.796 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT10

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.242	0.194 + 0.081*CL	0.191 + 0.081*CL	0.190 + 0.081*CL
	t_F	3.669	0.183 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PLH}	3.391	1.515 + 0.038*CL	1.516 + 0.038*CL	1.516 + 0.037*CL
	t_{PHL}	3.392	1.613 + 0.036*CL	1.613 + 0.036*CL	1.613 + 0.036*CL
TN to PAD	t_R	4.242	0.194 + 0.081*CL	0.191 + 0.081*CL	0.190 + 0.081*CL
	t_F	3.669	0.183 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PLH}	3.901	2.023 + 0.038*CL	2.024 + 0.038*CL	2.025 + 0.038*CL
	t_{PHL}	3.858	2.075 + 0.036*CL	2.077 + 0.036*CL	2.078 + 0.036*CL
	t_{PLZ}	1.961	1.961 + 0.000*CL	1.961 + 0.000*CL	1.961 + 0.000*CL
	t_{PHZ}	1.760	1.760 + 0.000*CL	1.760 + 0.000*CL	1.760 + 0.000*CL
EN to PAD	t_R	4.242	0.194 + 0.081*CL	0.191 + 0.081*CL	0.190 + 0.081*CL
	t_F	3.669	0.183 + 0.070*CL	0.175 + 0.070*CL	0.172 + 0.070*CL
	t_{PLH}	4.081	2.205 + 0.038*CL	2.206 + 0.038*CL	2.206 + 0.038*CL
	t_{PHL}	4.038	2.258 + 0.036*CL	2.258 + 0.036*CL	2.258 + 0.036*CL
	t_{PLZ}	2.045	2.045 + 0.000*CL	2.045 + 0.000*CL	2.045 + 0.000*CL
	t_{PHZ}	1.842	1.842 + 0.000*CL	1.842 + 0.000*CL	1.842 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT12

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.544	0.178 + 0.067*CL	0.169 + 0.067*CL	0.166 + 0.068*CL
	t_F	3.071	0.176 + 0.058*CL	0.163 + 0.058*CL	0.156 + 0.058*CL
	t_{PLH}	3.108	1.545 + 0.031*CL	1.546 + 0.031*CL	1.546 + 0.031*CL
	t_{PHL}	3.121	1.637 + 0.030*CL	1.638 + 0.030*CL	1.638 + 0.030*CL
TN to PAD	t_R	3.544	0.178 + 0.067*CL	0.169 + 0.067*CL	0.166 + 0.068*CL
	t_F	3.071	0.176 + 0.058*CL	0.163 + 0.058*CL	0.156 + 0.058*CL
	t_{PLH}	3.617	2.051 + 0.031*CL	2.053 + 0.031*CL	2.054 + 0.031*CL
	t_{PHL}	3.586	2.100 + 0.030*CL	2.102 + 0.030*CL	2.103 + 0.030*CL
	t_{PLZ}	2.037	2.037 + 0.000*CL	2.037 + 0.000*CL	2.037 + 0.000*CL
	t_{PHZ}	1.806	1.806 + 0.000*CL	1.806 + 0.000*CL	1.806 + 0.000*CL
EN to PAD	t_R	3.544	0.178 + 0.067*CL	0.169 + 0.067*CL	0.166 + 0.068*CL
	t_F	3.071	0.176 + 0.058*CL	0.163 + 0.058*CL	0.156 + 0.058*CL
	t_{PLH}	3.798	2.233 + 0.031*CL	2.235 + 0.031*CL	2.235 + 0.031*CL
	t_{PHL}	3.766	2.282 + 0.030*CL	2.283 + 0.030*CL	2.283 + 0.030*CL
	t_{PLZ}	2.119	2.119 + 0.000*CL	2.119 + 0.000*CL	2.119 + 0.000*CL
	t_{PHZ}	1.889	1.889 + 0.000*CL	1.889 + 0.000*CL	1.889 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT4SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	10.608	0.513 + 0.202*CL	0.486 + 0.202*CL	0.477 + 0.203*CL
	t_F	9.436	0.949 + 0.170*CL	0.845 + 0.172*CL	0.747 + 0.173*CL
	t_{PLH}	6.731	2.042 + 0.094*CL	2.043 + 0.094*CL	2.045 + 0.094*CL
	t_{PHL}	7.832	3.323 + 0.090*CL	3.373 + 0.089*CL	3.384 + 0.089*CL
TN to PAD	t_R	10.608	0.513 + 0.202*CL	0.486 + 0.202*CL	0.477 + 0.203*CL
	t_F	9.436	0.949 + 0.170*CL	0.845 + 0.172*CL	0.747 + 0.173*CL
	t_{PLH}	7.243	2.551 + 0.094*CL	2.554 + 0.094*CL	2.555 + 0.094*CL
	t_{PHL}	8.297	3.786 + 0.090*CL	3.836 + 0.089*CL	3.850 + 0.089*CL
	t_{PLZ}	1.982	1.982 + 0.000*CL	1.982 + 0.000*CL	1.982 + 0.000*CL
	t_{PHZ}	1.929	1.929 + 0.000*CL	1.929 + 0.000*CL	1.929 + 0.000*CL
EN to PAD	t_R	10.608	0.513 + 0.202*CL	0.486 + 0.202*CL	0.477 + 0.203*CL
	t_F	9.436	0.949 + 0.170*CL	0.845 + 0.172*CL	0.747 + 0.173*CL
	t_{PLH}	7.423	2.734 + 0.094*CL	2.735 + 0.094*CL	2.737 + 0.094*CL
	t_{PHL}	8.478	3.969 + 0.090*CL	4.017 + 0.089*CL	4.033 + 0.089*CL
	t_{PLZ}	2.064	2.064 + 0.000*CL	2.064 + 0.000*CL	2.064 + 0.000*CL
	t_{PHZ}	2.011	2.011 + 0.000*CL	2.011 + 0.000*CL	2.011 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT6SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	7.208	0.611 + 0.132*CL	0.535 + 0.133*CL	0.477 + 0.134*CL
	t_F	6.913	1.361 + 0.111*CL	1.334 + 0.112*CL	1.254 + 0.113*CL
	t_{PLH}	5.489	2.346 + 0.063*CL	2.361 + 0.063*CL	2.364 + 0.063*CL
	t_{PHL}	7.110	3.797 + 0.066*CL	4.005 + 0.062*CL	4.132 + 0.060*CL
TN to PAD	t_R	7.208	0.611 + 0.132*CL	0.535 + 0.133*CL	0.477 + 0.134*CL
	t_F	6.914	1.361 + 0.111*CL	1.334 + 0.112*CL	1.251 + 0.113*CL
	t_{PLH}	6.001	2.855 + 0.063*CL	2.871 + 0.063*CL	2.875 + 0.063*CL
	t_{PHL}	7.575	4.261 + 0.066*CL	4.470 + 0.062*CL	4.597 + 0.060*CL
	t_{PLZ}	2.288	2.288 + 0.000*CL	2.288 + 0.000*CL	2.288 + 0.000*CL
	t_{PHZ}	2.316	2.316 + 0.000*CL	2.316 + 0.000*CL	2.316 + 0.000*CL
EN to PAD	t_R	7.208	0.611 + 0.132*CL	0.535 + 0.133*CL	0.477 + 0.134*CL
	t_F	6.914	1.361 + 0.111*CL	1.334 + 0.112*CL	1.251 + 0.113*CL
	t_{PLH}	6.181	3.038 + 0.063*CL	3.053 + 0.063*CL	3.056 + 0.063*CL
	t_{PHL}	7.755	4.443 + 0.066*CL	4.651 + 0.062*CL	4.779 + 0.060*CL
	t_{PLZ}	2.371	2.372 + 0.000*CL	2.371 + 0.000*CL	2.371 + 0.000*CL
	t_{PHZ}	2.399	2.399 + 0.000*CL	2.399 + 0.000*CL	2.399 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT8SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.686	0.878 + 0.096*CL	0.795 + 0.098*CL	0.705 + 0.099*CL
	t_F	6.065	1.797 + 0.085*CL	1.914 + 0.083*CL	1.934 + 0.083*CL
	t_{PLH}	5.127	2.672 + 0.049*CL	2.754 + 0.047*CL	2.786 + 0.047*CL
	t_{PHL}	7.136	4.164 + 0.059*CL	4.513 + 0.052*CL	4.784 + 0.049*CL
TN to PAD	t_R	5.687	0.884 + 0.096*CL	0.796 + 0.098*CL	0.707 + 0.099*CL
	t_F	6.065	1.798 + 0.085*CL	1.914 + 0.083*CL	1.935 + 0.083*CL
	t_{PLH}	5.638	3.178 + 0.049*CL	3.263 + 0.047*CL	3.296 + 0.047*CL
	t_{PHL}	7.601	4.628 + 0.059*CL	4.977 + 0.052*CL	5.248 + 0.049*CL
	t_{PLZ}	2.593	2.593 + 0.000*CL	2.593 + 0.000*CL	2.592 + 0.000*CL
	t_{PHZ}	2.702	2.702 + 0.000*CL	2.702 + 0.000*CL	2.702 + 0.000*CL
EN to PAD	t_R	5.687	0.884 + 0.096*CL	0.796 + 0.098*CL	0.707 + 0.099*CL
	t_F	6.065	1.798 + 0.085*CL	1.914 + 0.083*CL	1.935 + 0.083*CL
	t_{PLH}	5.818	3.361 + 0.049*CL	3.444 + 0.047*CL	3.477 + 0.047*CL
	t_{PHL}	7.782	4.810 + 0.059*CL	5.159 + 0.052*CL	5.430 + 0.049*CL
	t_{PLZ}	2.675	2.676 + 0.000*CL	2.675 + 0.000*CL	2.675 + 0.000*CL
	t_{PHZ}	2.785	2.785 + 0.000*CL	2.785 + 0.000*CL	2.785 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT10SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.500	0.605 + 0.078*CL	0.552 + 0.079*CL	0.500 + 0.080*CL
	t_F	5.289	1.831 + 0.069*CL	1.979 + 0.066*CL	2.030 + 0.066*CL
	t_{PLH}	4.366	2.445 + 0.038*CL	2.484 + 0.038*CL	2.496 + 0.037*CL
	t_{PHL}	6.592	3.984 + 0.052*CL	4.351 + 0.045*CL	4.644 + 0.041*CL
TN to PAD	t_R	4.509	0.633 + 0.078*CL	0.572 + 0.079*CL	0.511 + 0.080*CL
	t_F	5.290	1.834 + 0.069*CL	1.981 + 0.066*CL	2.031 + 0.066*CL
	t_{PLH}	4.854	2.901 + 0.039*CL	2.958 + 0.038*CL	2.980 + 0.038*CL
	t_{PHL}	7.058	4.447 + 0.052*CL	4.816 + 0.045*CL	5.109 + 0.041*CL
	t_{PLZ}	3.338	3.338 + 0.000*CL	3.338 + 0.000*CL	3.338 + 0.000*CL
	t_{PHZ}	2.683	2.683 + 0.000*CL	2.683 + 0.000*CL	2.683 + 0.000*CL
EN to PAD	t_R	4.509	0.633 + 0.078*CL	0.572 + 0.079*CL	0.511 + 0.080*CL
	t_F	5.290	1.834 + 0.069*CL	1.981 + 0.066*CL	2.031 + 0.066*CL
	t_{PLH}	5.035	3.083 + 0.039*CL	3.139 + 0.038*CL	3.161 + 0.038*CL
	t_{PHL}	7.238	4.630 + 0.052*CL	4.997 + 0.045*CL	5.290 + 0.041*CL
	t_{PLZ}	3.421	3.421 + 0.000*CL	3.421 + 0.000*CL	3.420 + 0.000*CL
	t_{PHZ}	2.765	2.766 + 0.000*CL	2.765 + 0.000*CL	2.765 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT12SM

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	3.998	0.788 + 0.064*CL	0.767 + 0.065*CL	0.718 + 0.065*CL
	t_F	4.487	1.515 + 0.059*CL	1.662 + 0.057*CL	1.739 + 0.055*CL
	t_{PLH}	4.328	2.602 + 0.035*CL	2.705 + 0.032*CL	2.764 + 0.032*CL
	t_{PHL}	6.164	3.947 + 0.044*CL	4.249 + 0.038*CL	4.500 + 0.035*CL
TN to PAD	t_R	4.011	0.830 + 0.064*CL	0.793 + 0.064*CL	0.733 + 0.065*CL
	t_F	4.488	1.518 + 0.059*CL	1.663 + 0.056*CL	1.740 + 0.055*CL
	t_{PLH}	4.822	3.068 + 0.035*CL	3.188 + 0.033*CL	3.255 + 0.032*CL
	t_{PHL}	6.629	4.410 + 0.044*CL	4.713 + 0.038*CL	4.964 + 0.035*CL
	t_{PLZ}	3.338	3.338 + 0.000*CL	3.338 + 0.000*CL	3.338 + 0.000*CL
	t_{PHZ}	3.069	3.069 + 0.000*CL	3.069 + 0.000*CL	3.068 + 0.000*CL
EN to PAD	t_R	4.011	0.830 + 0.064*CL	0.793 + 0.064*CL	0.733 + 0.065*CL
	t_F	4.488	1.518 + 0.059*CL	1.663 + 0.056*CL	1.740 + 0.055*CL
	t_{PLH}	5.002	3.251 + 0.035*CL	3.369 + 0.033*CL	3.436 + 0.032*CL
	t_{PHL}	6.809	4.592 + 0.044*CL	4.894 + 0.038*CL	5.145 + 0.035*CL
	t_{PLZ}	3.421	3.421 + 0.000*CL	3.421 + 0.000*CL	3.420 + 0.000*CL
	t_{PHZ}	3.151	3.151 + 0.000*CL	3.151 + 0.000*CL	3.151 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PHOT10SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	5.273	1.448 + 0.077*CL	1.465 + 0.076*CL	1.414 + 0.077*CL
	t_F	6.224	2.449 + 0.075*CL	2.727 + 0.070*CL	2.915 + 0.067*CL
	t_{PLH}	5.937	3.601 + 0.047*CL	3.843 + 0.042*CL	4.013 + 0.040*CL
	t_{PHL}	8.404	5.281 + 0.062*CL	5.782 + 0.052*CL	6.211 + 0.047*CL
TN to PAD	t_R	5.279	1.469 + 0.076*CL	1.475 + 0.076*CL	1.420 + 0.077*CL
	t_F	6.225	2.451 + 0.075*CL	2.728 + 0.070*CL	2.916 + 0.067*CL
	t_{PLH}	6.445	4.100 + 0.047*CL	4.347 + 0.042*CL	4.520 + 0.040*CL
	t_{PHL}	8.870	5.745 + 0.062*CL	6.247 + 0.052*CL	6.677 + 0.047*CL
	t_{PLZ}	3.421	3.422 + 0.000*CL	3.421 + 0.000*CL	3.421 + 0.000*CL
	t_{PHZ}	3.146	3.146 + 0.000*CL	3.146 + 0.000*CL	3.146 + 0.000*CL
EN to PAD	t_R	5.279	1.469 + 0.076*CL	1.475 + 0.076*CL	1.420 + 0.077*CL
	t_F	6.225	2.451 + 0.075*CL	2.728 + 0.070*CL	2.916 + 0.067*CL
	t_{PLH}	6.625	4.282 + 0.047*CL	4.529 + 0.042*CL	4.701 + 0.040*CL
	t_{PHL}	9.050	5.927 + 0.062*CL	6.428 + 0.052*CL	6.860 + 0.047*CL
	t_{PLZ}	3.504	3.504 + 0.000*CL	3.504 + 0.000*CL	3.503 + 0.000*CL
	t_{PHZ}	3.228	3.228 + 0.000*CL	3.228 + 0.000*CL	3.228 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PHOT12SH

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.965	1.691 + 0.065*CL	1.798 + 0.063*CL	1.812 + 0.063*CL
	t_F	6.246	2.790 + 0.069*CL	3.146 + 0.062*CL	3.418 + 0.058*CL
	t_{PLH}	6.084	3.853 + 0.045*CL	4.156 + 0.039*CL	4.395 + 0.035*CL
	t_{PHL}	8.726	5.553 + 0.063*CL	6.134 + 0.052*CL	6.641 + 0.045*CL
TN to PAD	t_R	4.984	1.756 + 0.065*CL	1.834 + 0.063*CL	1.833 + 0.063*CL
	t_F	6.248	2.799 + 0.069*CL	3.151 + 0.062*CL	3.421 + 0.058*CL
	t_{PLH}	6.585	4.330 + 0.045*CL	4.647 + 0.039*CL	4.893 + 0.035*CL
	t_{PHL}	9.191	6.014 + 0.064*CL	6.599 + 0.052*CL	7.103 + 0.045*CL
	t_{PLZ}	3.826	3.827 + 0.000*CL	3.826 + 0.000*CL	3.826 + 0.000*CL
	t_{PHZ}	3.531	3.531 + 0.000*CL	3.531 + 0.000*CL	3.531 + 0.000*CL
EN to PAD	t_R	4.984	1.756 + 0.065*CL	1.834 + 0.063*CL	1.833 + 0.063*CL
	t_F	6.248	2.799 + 0.069*CL	3.151 + 0.062*CL	3.421 + 0.058*CL
	t_{PLH}	6.765	4.512 + 0.045*CL	4.829 + 0.039*CL	5.074 + 0.035*CL
	t_{PHL}	9.371	6.197 + 0.063*CL	6.780 + 0.052*CL	7.283 + 0.045*CL
	t_{PLZ}	3.909	3.910 + 0.000*CL	3.909 + 0.000*CL	3.909 + 0.000*CL
	t_{PHZ}	3.614	3.614 + 0.000*CL	3.614 + 0.000*CL	3.614 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PvOTyz

Tri-State Output Buffers

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PTOT1

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	44.026	2.843 + 0.824*CL	2.992 + 0.821*CL	3.100 + 0.819*CL
	t_F	33.890	2.747 + 0.623*CL	2.704 + 0.624*CL	2.677 + 0.624*CL
	t_{PLH}	21.904	3.047 + 0.377*CL	3.102 + 0.376*CL	3.138 + 0.376*CL
	t_{PHL}	17.900	2.290 + 0.312*CL	2.310 + 0.312*CL	2.325 + 0.312*CL
TN to PAD	t_R	44.026	2.843 + 0.824*CL	2.992 + 0.821*CL	3.100 + 0.819*CL
	t_F	33.854	2.744 + 0.622*CL	2.692 + 0.623*CL	2.662 + 0.624*CL
	t_{PLH}	22.415	3.558 + 0.377*CL	3.611 + 0.376*CL	3.650 + 0.376*CL
	t_{PHL}	18.285	2.735 + 0.311*CL	2.743 + 0.311*CL	2.761 + 0.311*CL
	t_{PLZ}	1.641	1.641 + 0.000*CL	1.641 + 0.000*CL	1.641 + 0.000*CL
	t_{PHZ}	5.196	5.198 + 0.000*CL	5.196 + 0.000*CL	5.196 + 0.000*CL
EN to PAD	t_R	44.026	2.843 + 0.824*CL	2.992 + 0.821*CL	3.100 + 0.819*CL
	t_F	33.854	2.744 + 0.622*CL	2.692 + 0.623*CL	2.662 + 0.624*CL
	t_{PLH}	22.596	3.739 + 0.377*CL	3.794 + 0.376*CL	3.830 + 0.376*CL
	t_{PHL}	18.465	2.918 + 0.311*CL	2.925 + 0.311*CL	2.937 + 0.311*CL
	t_{PLZ}	1.724	1.724 + 0.000*CL	1.724 + 0.000*CL	1.724 + 0.000*CL
	t_{PHZ}	5.279	5.281 + 0.000*CL	5.279 + 0.000*CL	5.278 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

PTOT2

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	22.250	1.485 + 0.415*CL	1.620 + 0.413*CL	1.725 + 0.411*CL
	t_F	17.034	1.379 + 0.313*CL	1.416 + 0.312*CL	1.419 + 0.312*CL
	t_{PLH}	11.738	2.249 + 0.190*CL	2.296 + 0.189*CL	2.338 + 0.188*CL
	t_{PHL}	9.753	1.902 + 0.157*CL	1.928 + 0.157*CL	1.948 + 0.156*CL
TN to PAD	t_R	22.250	1.485 + 0.415*CL	1.620 + 0.413*CL	1.725 + 0.411*CL
	t_F	16.992	1.367 + 0.312*CL	1.396 + 0.312*CL	1.402 + 0.312*CL
	t_{PLH}	12.250	2.758 + 0.190*CL	2.810 + 0.189*CL	2.846 + 0.188*CL
	t_{PHL}	10.142	2.337 + 0.156*CL	2.356 + 0.156*CL	2.377 + 0.155*CL
	t_{PLZ}	1.765	1.765 + 0.000*CL	1.765 + 0.000*CL	1.765 + 0.000*CL
	t_{PHZ}	7.277	7.291 + 0.000*CL	7.277 + 0.000*CL	7.272 + 0.000*CL
EN to PAD	t_R	22.250	1.485 + 0.415*CL	1.620 + 0.413*CL	1.725 + 0.411*CL
	t_F	16.992	1.367 + 0.312*CL	1.396 + 0.312*CL	1.402 + 0.312*CL
	t_{PLH}	12.430	2.941 + 0.190*CL	2.990 + 0.189*CL	3.029 + 0.188*CL
	t_{PHL}	10.322	2.520 + 0.156*CL	2.538 + 0.156*CL	2.556 + 0.155*CL
	t_{PLZ}	1.848	1.848 + 0.000*CL	1.848 + 0.000*CL	1.848 + 0.000*CL
	t_{PHZ}	7.359	7.373 + 0.000*CL	7.359 + 0.000*CL	7.354 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 0.19ns, CL: Capacltive Load[pf])

PTOT3

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	14.950	1.003 + 0.279*CL	1.124 + 0.277*CL	1.223 + 0.275*CL
	t_F	11.398	0.929 + 0.209*CL	0.952 + 0.209*CL	0.976 + 0.209*CL
	t_{PLH}	8.375	2.018 + 0.127*CL	2.056 + 0.126*CL	2.093 + 0.126*CL
	t_{PHL}	7.074	1.817 + 0.105*CL	1.837 + 0.105*CL	1.854 + 0.105*CL
TN to PAD	t_R	14.950	1.005 + 0.279*CL	1.122 + 0.277*CL	1.227 + 0.275*CL
	t_F	11.350	0.906 + 0.209*CL	0.926 + 0.208*CL	0.947 + 0.208*CL
	t_{PLH}	8.886	2.529 + 0.127*CL	2.567 + 0.126*CL	2.605 + 0.126*CL
	t_{PHL}	7.460	2.242 + 0.104*CL	2.255 + 0.104*CL	2.274 + 0.104*CL
	t_{PLZ}	1.887	1.887 + 0.000*CL	1.887 + 0.000*CL	1.887 + 0.000*CL
	t_{PHZ}	9.372	9.409 + 0.000*CL	9.372 + 0.000*CL	9.357 + 0.000*CL
EN to PAD	t_R	14.950	1.005 + 0.279*CL	1.122 + 0.277*CL	1.227 + 0.275*CL
	t_F	11.350	0.906 + 0.209*CL	0.926 + 0.208*CL	0.947 + 0.208*CL
	t_{PLH}	9.067	2.711 + 0.127*CL	2.748 + 0.126*CL	2.785 + 0.126*CL
	t_{PHL}	7.640	2.425 + 0.104*CL	2.438 + 0.104*CL	2.453 + 0.104*CL
	t_{PLZ}	1.970	1.970 + 0.000*CL	1.970 + 0.000*CL	1.970 + 0.000*CL
	t_{PHZ}	9.455	9.492 + 0.000*CL	9.455 + 0.000*CL	9.439 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

BI-DIRECTIONAL BUFFERS

Cell List

Cell Name	Function Description
PBaDyz	2.5V Interface Open-Drain Bi-Directional Buffers
PBaUDyz	2.5 V Interface Open-Drain Bi-Directional Buffers with Pull-Up
PHBaDyz	3.3V Interface Open-Drain Bi-Directional Buffers with Pull-Down
PHBaUDyz	3.3 V Interface Open-Drain Bi-Directional Buffers with Pull-Up
PTBaDyz	5V - Tolerant Open-Drain Bi-Directional Buffers
PTBaUDyz	5V - Tolerant Open-Drain Bi-Directional Buffers with Pull-Up
PBaTyz	2.5V Tri-State Bi-Directional Buffers
PBaDTyz	2.5V Tri-State Bi-Directional Buffers with Pull-Down
PBaUTyz	2.5V Tri-State Bi-Directional Buffers with Pull-Up
PHBaTyz	3.3V Interface Tri-State Bi-Directional Buffers
PHBaDTyz	3.3V Interface Tri-State Bi-Directional Buffers with Pull-Down
PHBaUTyz	3.3V Interface Tri-State Bi-Directional Buffers with Pull-Up
PTBaTyz	5V - Tolerant Tri-State Bi-Directional Buffers
PTBaDTyz	5V - Tolerant Tri-State Bi-Directional Buffers with Pull-Down
PTBaUTyz	5V - Tolerant Tri-State Bi-Directional Buffers with Pull-Up

Open Drain Bi-Directional Buffers

PvBaDyz



PvBaUDyz



Tri-State Bi-Directional Buffers

PvBaTyz



PvBaDTyz



PvBaUTyz



OSCILLATORS

Cell List

Cell Name	Function Description
PHSOSCK1	Oscillator Cell with Enable (~ 100kHz)
PHSOSCK2	Oscillator Cell with Enable (100K ~ 1MHz)
PHSOSCM1	Oscillator Cell with Enable (1M ~ 10MHz)
PHSOSCM2	Oscillator Cell with Enable (10M ~ 40MHz)

NOTE: Use I/O 3.3V and Core 1.8V

Cell Name	Function Description
PH2SOSCK1	Oscillator Cell with Enable (~ 100kHz)
PH2SOSCK2	Oscillator Cell with Enable (100K ~ 1MHz)
PH2SOSCM1	Oscillator Cell with Enable (1M ~ 10MHz)
PH2SOSCM2	Oscillator Cell with Enable (10M ~ 40MHz)

NOTE: Use I/O 2.5V and Core 1.8V

Cell Name	Function Description
PSOSCK1	Oscillator Cell with Enable (~ 100kHz)
PSOSCK2	Oscillator Cell with Enable (100K ~ 1MHz)
PSOSCM1	Oscillator Cell with Enable (1M ~ 10MHz)
PSOSCM2	Oscillator Cell with Enable (10M ~ 40MHz)

NOTE: Use I/O 1.8V and Core 1.8V

Logic Symbol



Truth Table

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Cell Data

Input Load (SL)		I/O Sizes	
PHSOSCK1/K2	*PHSOSCM1/M2*	*PHSOSCK1/K2*	*PHSOSCM1/M2*
E	E		
3.42	3.42	2 I/O Slots	2 I/O Slots

Switching Characteristics

PHSOSCK1

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2030.800	40.630 + 39.802*CL	40.630 + 39.802*CL	40.600 + 39.804*CL
	t_F	1973.660	39.470 + 38.682*CL	39.430 + 38.686*CL	39.460 + 38.684*CL
	t_{PLH}	908.930	18.920 + 17.800*CL	18.900 + 17.802*CL	18.930 + 17.800*CL
	t_{PHL}	957.530	20.040 + 18.750*CL	20.060 + 18.748*CL	20.030 + 18.750*CL
E to PADY	t_R	2030.800	40.630 + 39.802*CL	40.630 + 39.802*CL	40.600 + 39.804*CL
	t_F	1973.720	39.430 + 38.686*CL	39.450 + 38.684*CL	39.420 + 38.686*CL
	t_{PLH}	910.720	20.710 + 17.800*CL	20.690 + 17.802*CL	20.720 + 17.800*CL
	t_{PHL}	957.630	20.140 + 18.750*CL	20.160 + 18.748*CL	20.130 + 18.750*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.155	0.138 + 0.009*SL	0.139 + 0.008*SL	0.139 + 0.008*SL
	t_F	0.144	0.127 + 0.009*SL	0.127 + 0.009*SL	0.126 + 0.009*SL
	t_{PLH}	8.595	8.584 + 0.005*SL	8.588 + 0.004*SL	8.601 + 0.004*SL
	t_{PHL}	11.804	11.791 + 0.006*SL	11.795 + 0.005*SL	11.808 + 0.005*SL
E to YN	t_R	0.155	0.138 + 0.008*SL	0.139 + 0.008*SL	0.138 + 0.008*SL
	t_F	0.145	0.127 + 0.009*SL	0.128 + 0.009*SL	0.126 + 0.009*SL
	t_{PLH}	10.225	10.215 + 0.005*SL	10.217 + 0.004*SL	10.231 + 0.004*SL
	t_{PHL}	11.984	11.972 + 0.006*SL	11.975 + 0.005*SL	11.989 + 0.005*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PHSOSCK2

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	261.584	5.319 + 5.123*CL	5.343 + 5.120*CL	5.244 + 5.127*CL
	t_F	246.418	5.004 + 4.827*CL	4.994 + 4.828*CL	4.988 + 4.829*CL
	t_{PLH}	96.561	2.524 + 1.877*CL	2.470 + 1.883*CL	2.491 + 1.881*CL
	t_{PHL}	97.576	2.509 + 1.901*CL	2.497 + 1.902*CL	2.506 + 1.901*CL
E to PADY	t_R	261.436	5.303 + 5.124*CL	5.299 + 5.124*CL	5.326 + 5.122*CL
	t_F	246.420	4.998 + 4.827*CL	4.982 + 4.828*CL	4.970 + 4.829*CL
	t_{PLH}	98.346	4.216 + 1.883*CL	4.248 + 1.880*CL	4.206 + 1.883*CL
	t_{PHL}	97.764	2.695 + 1.898*CL	2.665 + 1.901*CL	2.644 + 1.902*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.169	0.148 + 0.010*SL	0.147 + 0.011*SL	0.146 + 0.011*SL
	t_F	0.159	0.136 + 0.011*SL	0.136 + 0.011*SL	0.135 + 0.011*SL
	t_{PLH}	3.028	3.015 + 0.007*SL	3.019 + 0.005*SL	3.031 + 0.005*SL
	t_{PHL}	2.897	2.882 + 0.007*SL	2.886 + 0.006*SL	2.898 + 0.006*SL
E to YN	t_R	0.169	0.147 + 0.011*SL	0.147 + 0.011*SL	0.147 + 0.011*SL
	t_F	0.159	0.136 + 0.011*SL	0.136 + 0.011*SL	0.135 + 0.011*SL
	t_{PLH}	4.742	4.729 + 0.007*SL	4.732 + 0.005*SL	4.744 + 0.005*SL
	t_{PHL}	2.946	2.931 + 0.007*SL	2.935 + 0.006*SL	2.947 + 0.006*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PHSOSCM1

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	16.255	0.429 + 0.345*CL	1.025 + 0.285*CL	0.607 + 0.313*CL
	t_F	17.466	0.730 + 0.315*CL	0.736 + 0.315*CL	0.312 + 0.343*CL
	t_{PLH}	8.464	1.015 + 0.149*CL	1.002 + 0.150*CL	1.015 + 0.149*CL
	t_{PHL}	9.530	1.023 + 0.171*CL	1.050 + 0.169*CL	1.029 + 0.170*CL
E to PADY	t_R	16.814	0.667 + 0.300*CL	0.288 + 0.338*CL	0.441 + 0.327*CL
	t_F	16.841	0.414 + 0.334*CL	0.399 + 0.335*CL	0.538 + 0.326*CL
	t_{PLH}	10.333	2.879 + 0.150*CL	2.890 + 0.149*CL	2.889 + 0.149*CL
	t_{PHL}	9.549	1.091 + 0.170*CL	1.095 + 0.170*CL	1.111 + 0.169*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.169	0.147 + 0.011*SL	0.148 + 0.011*SL	0.147 + 0.011*SL
	t_F	0.158	0.136 + 0.011*SL	0.135 + 0.011*SL	0.134 + 0.011*SL
	t_{PLH}	3.200	3.187 + 0.007*SL	3.191 + 0.005*SL	3.203 + 0.005*SL
	t_{PHL}	2.924	2.909 + 0.007*SL	2.912 + 0.006*SL	2.925 + 0.006*SL
E to YN	t_R	0.169	0.148 + 0.010*SL	0.147 + 0.011*SL	0.147 + 0.011*SL
	t_F	0.158	0.136 + 0.011*SL	0.135 + 0.011*SL	0.134 + 0.011*SL
	t_{PLH}	5.161	5.147 + 0.007*SL	5.151 + 0.005*SL	5.163 + 0.005*SL
	t_{PHL}	2.713	2.698 + 0.007*SL	2.702 + 0.006*SL	2.714 + 0.006*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PHSOSCM2

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	5.071	0.780 + 0.084*CL	0.813 + 0.080*CL	0.707 + 0.087*CL
	t_F	5.095	0.944 + 0.092*CL	0.984 + 0.088*CL	1.111 + 0.080*CL
	t_{PLH}	4.259	1.687 + 0.062*CL	1.771 + 0.053*CL	1.846 + 0.048*CL
	t_{PHL}	4.631	1.602 + 0.071*CL	1.677 + 0.063*CL	1.770 + 0.057*CL
E to PADY	t_R	5.149	0.808 + 0.082*CL	0.816 + 0.082*CL	0.709 + 0.089*CL
	t_F	4.426	0.568 + 0.077*CL	0.568 + 0.077*CL	0.574 + 0.077*CL
	t_{PLH}	6.269	3.696 + 0.062*CL	3.779 + 0.053*CL	3.856 + 0.048*CL
	t_{PHL}	4.124	1.679 + 0.057*CL	1.756 + 0.050*CL	1.804 + 0.046*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 3.3V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.169	0.147 + 0.011*SL	0.148 + 0.011*SL	0.147 + 0.011*SL
	t_F	0.158	0.136 + 0.011*SL	0.135 + 0.011*SL	0.134 + 0.011*SL
	t_{PLH}	3.200	3.187 + 0.007*SL	3.191 + 0.005*SL	3.203 + 0.005*SL
	t_{PHL}	2.924	2.909 + 0.007*SL	2.912 + 0.006*SL	2.925 + 0.006*SL
E to YN	t_R	0.169	0.148 + 0.010*SL	0.147 + 0.011*SL	0.147 + 0.011*SL
	t_F	0.158	0.136 + 0.011*SL	0.135 + 0.011*SL	0.134 + 0.011*SL
	t_{PLH}	5.161	5.147 + 0.007*SL	5.151 + 0.005*SL	5.163 + 0.005*SL
	t_{PHL}	2.713	2.698 + 0.007*SL	2.702 + 0.006*SL	2.714 + 0.006*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

PH2SOSCK1/K2/M1/M2

Oscillator Cell with Enable

Logic Symbol



Truth Table

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Cell Data

Input Load (SL)		I/O Sizes	
PH2SOSCK1/K2	*PH2SOSCM1/M2*	*PH2SOSCK1/K2*	*PH2SOSCM1/M2*
E	E		
3.75	3.75	2 I/O Slots	2 I/O Slots

Switching Characteristics

PH2SOSCK1

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	2129.550	82.270 + 40.944*CL	82.250 + 40.946*CL	82.250 + 40.946*CL
	t_F	1941.280	72.580 + 37.374*CL	72.580 + 37.374*CL	72.580 + 37.374*CL
	t_{PLH}	917.000	34.170 + 17.658*CL	34.170 + 17.658*CL	34.200 + 17.656*CL
	t_{PHL}	872.750	36.090 + 16.738*CL	36.150 + 16.732*CL	36.150 + 16.732*CL
E to PADY	t_R	2129.550	82.270 + 40.944*CL	82.250 + 40.946*CL	82.250 + 40.946*CL
	t_F	1941.340	72.430 + 37.378*CL	72.410 + 37.380*CL	72.440 + 37.378*CL
	t_{PLH}	917.290	34.460 + 17.658*CL	34.460 + 17.658*CL	34.490 + 17.656*CL
	t_{PHL}	872.430	35.810 + 16.734*CL	35.830 + 16.732*CL	35.830 + 16.732*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.821	0.792 + 0.015*SL	0.799 + 0.012*SL	0.909 + 0.010*SL
	t_F	1.649	1.602 + 0.024*SL	1.633 + 0.013*SL	1.748 + 0.010*SL
	t_{PLH}	52.693	52.664 + 0.015*SL	52.676 + 0.011*SL	52.793 + 0.008*SL
	t_{PHL}	73.145	73.104 + 0.021*SL	73.121 + 0.015*SL	73.289 + 0.011*SL
E to YN	t_R	0.802	0.766 + 0.018*SL	0.782 + 0.013*SL	0.887 + 0.010*SL
	t_F	1.656	1.627 + 0.014*SL	1.631 + 0.013*SL	1.769 + 0.010*SL
	t_{PLH}	52.669	52.640 + 0.015*SL	52.651 + 0.011*SL	52.773 + 0.007*SL
	t_{PHL}	72.118	72.077 + 0.021*SL	72.093 + 0.015*SL	72.262 + 0.011*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PH2SOSCK2

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	294.178	11.479 + 5.652*CL	11.469 + 5.653*CL	11.448 + 5.655*CL
	t_F	302.784	11.325 + 5.826*CL	11.285 + 5.830*CL	11.294 + 5.830*CL
	t_{PLH}	105.487	4.313 + 2.022*CL	4.303 + 2.023*CL	4.297 + 2.024*CL
	t_{PHL}	126.747	5.674 + 2.421*CL	5.670 + 2.421*CL	5.667 + 2.422*CL
E to PADY	t_R	294.168	11.446 + 5.654*CL	11.444 + 5.654*CL	11.438 + 5.655*CL
	t_F	302.728	11.247 + 5.833*CL	11.277 + 5.830*CL	11.298 + 5.829*CL
	t_{PLH}	105.772	4.596 + 2.023*CL	4.588 + 2.023*CL	4.582 + 2.024*CL
	t_{PHL}	126.716	5.630 + 2.421*CL	5.626 + 2.422*CL	5.626 + 2.422*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.271	0.248 + 0.011*SL	0.255 + 0.009*SL	0.266 + 0.009*SL
	t_F	0.415	0.397 + 0.009*SL	0.402 + 0.007*SL	0.448 + 0.006*SL
	t_{PLH}	6.287	6.271 + 0.008*SL	6.278 + 0.006*SL	6.322 + 0.005*SL
	t_{PHL}	7.058	7.039 + 0.010*SL	7.048 + 0.007*SL	7.127 + 0.005*SL
E to YN	t_R	0.271	0.247 + 0.012*SL	0.256 + 0.009*SL	0.267 + 0.009*SL
	t_F	0.415	0.397 + 0.009*SL	0.402 + 0.007*SL	0.448 + 0.006*SL
	t_{PLH}	6.207	6.191 + 0.008*SL	6.198 + 0.006*SL	6.242 + 0.005*SL
	t_{PHL}	6.903	6.883 + 0.010*SL	6.892 + 0.007*SL	6.972 + 0.005*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PH2SOSCM1

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	18.965	0.653 + 0.380*CL	1.486 + 0.297*CL	0.357 + 0.372*CL
	t_F	14.651	0.912 + 0.253*CL	0.677 + 0.277*CL	0.617 + 0.281*CL
	t_{PLH}	8.562	0.900 + 0.152*CL	0.870 + 0.155*CL	0.890 + 0.153*CL
	t_{PHL}	7.569	0.913 + 0.134*CL	0.914 + 0.134*CL	0.925 + 0.133*CL
E to PADY	t_R	18.205	0.580 + 0.377*CL	1.060 + 0.329*CL	0.765 + 0.349*CL
	t_F	13.750	0.587 + 0.282*CL	0.599 + 0.281*CL	0.979 + 0.255*CL
	t_{PLH}	8.786	1.149 + 0.155*CL	1.153 + 0.155*CL	1.194 + 0.152*CL
	t_{PHL}	7.838	1.115 + 0.135*CL	1.117 + 0.134*CL	1.117 + 0.134*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.165	0.145 + 0.010*SL	0.147 + 0.009*SL	0.152 + 0.009*SL
	t_F	0.199	0.183 + 0.008*SL	0.186 + 0.007*SL	0.197 + 0.007*SL
	t_{PLH}	0.928	0.916 + 0.006*SL	0.919 + 0.005*SL	0.935 + 0.004*SL
	t_{PHL}	1.225	1.212 + 0.006*SL	1.217 + 0.005*SL	1.253 + 0.004*SL
E to YN	t_R	0.161	0.141 + 0.010*SL	0.142 + 0.009*SL	0.148 + 0.009*SL
	t_F	0.197	0.182 + 0.008*SL	0.184 + 0.007*SL	0.195 + 0.007*SL
	t_{PLH}	1.222	1.211 + 0.006*SL	1.214 + 0.005*SL	1.229 + 0.004*SL
	t_{PHL}	1.429	1.417 + 0.006*SL	1.422 + 0.005*SL	1.457 + 0.004*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PH2SOSCM2

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	4.532	0.619 + 0.085*CL	0.565 + 0.091*CL	0.810 + 0.074*CL
	t_F	3.992	0.731 + 0.067*CL	0.709 + 0.069*CL	0.785 + 0.064*CL
	t_{PLH}	3.175	1.053 + 0.048*CL	1.104 + 0.043*CL	1.139 + 0.041*CL
	t_{PHL}	3.065	0.923 + 0.051*CL	0.994 + 0.044*CL	1.049 + 0.040*CL
E to PADY	t_R	4.934	0.538 + 0.087*CL	0.679 + 0.073*CL	0.426 + 0.090*CL
	t_F	4.049	0.597 + 0.067*CL	0.608 + 0.066*CL	0.549 + 0.070*CL
	t_{PLH}	3.561	1.419 + 0.049*CL	1.471 + 0.043*CL	1.503 + 0.041*CL
	t_{PHL}	3.562	1.505 + 0.048*CL	1.562 + 0.042*CL	1.610 + 0.039*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 1.600ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.118	0.107 + 0.006*SL	0.108 + 0.005*SL	0.110 + 0.005*SL
	t_F	0.140	0.131 + 0.005*SL	0.133 + 0.004*SL	0.139 + 0.004*SL
	t_{PLH}	1.240	1.233 + 0.003*SL	1.235 + 0.003*SL	1.246 + 0.003*SL
	t_{PHL}	1.409	1.401 + 0.004*SL	1.404 + 0.003*SL	1.426 + 0.002*SL
E to YN	t_R	0.119	0.109 + 0.005*SL	0.107 + 0.005*SL	0.109 + 0.005*SL
	t_F	0.140	0.131 + 0.005*SL	0.132 + 0.004*SL	0.139 + 0.004*SL
	t_{PLH}	1.559	1.552 + 0.003*SL	1.554 + 0.003*SL	1.564 + 0.003*SL
	t_{PHL}	1.922	1.915 + 0.004*SL	1.917 + 0.003*SL	1.939 + 0.002*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Logic Symbol



Truth Table

E	PADA	PADY	YN	PI	PO
0	0	0	0	0	1
0	0	0	0	1	1
0	1	0	0	0	1
0	1	0	0	1	1
1	0	1	1	0	1
1	0	1	1	1	0
1	1	0	0	0	1
1	1	0	0	1	1

Cell Data

Input Load (SL)		I/O Sizes	
PSOSCK1/K2	*PSOSCM1/M2*	*PSOSCK1/K2*	*PSOSCM1/M2*
E	E		
3.38	3.38	2 I/O Slots	2 I/O Slots

Switching Characteristics

PSOSCK1

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	1570.690	63.890 + 30.136*CL	63.890 + 30.136*CL	63.890 + 30.136*CL
	t_F	1267.650	50.060 + 24.352*CL	50.080 + 24.350*CL	50.050 + 24.352*CL
	t_{PLH}	671.780	26.396 + 12.907*CL	26.410 + 12.906*CL	26.380 + 12.908*CL
	t_{PHL}	589.710	25.374 + 11.289*CL	25.380 + 11.288*CL	25.410 + 11.286*CL
E to PADY	t_R	1570.690	63.890 + 30.136*CL	63.890 + 30.136*CL	63.890 + 30.136*CL
	t_F	1267.650	50.060 + 24.352*CL	50.080 + 24.350*CL	50.050 + 24.352*CL
	t_{PLH}	671.670	26.276 + 12.908*CL	26.300 + 12.906*CL	26.270 + 12.908*CL
	t_{PHL}	589.520	25.186 + 11.288*CL	25.190 + 11.288*CL	25.220 + 11.286*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.156	0.139 + 0.009*SL	0.141 + 0.008*SL	0.147 + 0.008*SL
	t_F	0.189	0.174 + 0.007*SL	0.176 + 0.007*SL	0.182 + 0.007*SL
	t_{PLH}	0.943	0.932 + 0.005*SL	0.935 + 0.004*SL	0.956 + 0.004*SL
	t_{PHL}	0.939	0.927 + 0.006*SL	0.932 + 0.004*SL	0.961 + 0.004*SL
E to YN	t_R	0.153	0.136 + 0.008*SL	0.138 + 0.008*SL	0.144 + 0.008*SL
	t_F	0.184	0.169 + 0.007*SL	0.171 + 0.007*SL	0.178 + 0.007*SL
	t_{PLH}	0.883	0.872 + 0.005*SL	0.875 + 0.004*SL	0.895 + 0.004*SL
	t_{PHL}	0.835	0.823 + 0.006*SL	0.827 + 0.004*SL	0.856 + 0.004*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PSOSCK2

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	225.440	9.316 + 4.319*CL	9.214 + 4.329*CL	9.310 + 4.323*CL
	t_F	200.981	7.937 + 3.861*CL	7.929 + 3.862*CL	7.941 + 3.861*CL
	t_{PLH}	78.039	3.596 + 1.492*CL	3.618 + 1.489*CL	3.639 + 1.488*CL
	t_{PHL}	70.414	3.616 + 1.340*CL	3.654 + 1.337*CL	3.684 + 1.335*CL
E to PADY	t_R	225.561	9.265 + 4.326*CL	9.295 + 4.323*CL	9.241 + 4.326*CL
	t_F	200.984	7.953 + 3.860*CL	7.945 + 3.861*CL	7.954 + 3.861*CL
	t_{PLH}	77.976	3.538 + 1.489*CL	3.532 + 1.490*CL	3.556 + 1.488*CL
	t_{PHL}	70.237	3.463 + 1.335*CL	3.457 + 1.336*CL	3.457 + 1.336*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.155	0.138 + 0.008*SL	0.140 + 0.008*SL	0.147 + 0.008*SL
	t_F	0.188	0.174 + 0.007*SL	0.175 + 0.007*SL	0.181 + 0.007*SL
	t_{PLH}	1.024	1.013 + 0.005*SL	1.017 + 0.004*SL	1.037 + 0.004*SL
	t_{PHL}	1.008	0.996 + 0.006*SL	1.000 + 0.004*SL	1.030 + 0.004*SL
E to YN	t_R	0.153	0.137 + 0.008*SL	0.137 + 0.008*SL	0.145 + 0.008*SL
	t_F	0.184	0.169 + 0.008*SL	0.171 + 0.007*SL	0.178 + 0.007*SL
	t_{PLH}	0.959	0.948 + 0.005*SL	0.952 + 0.004*SL	0.972 + 0.004*SL
	t_{PHL}	0.890	0.879 + 0.006*SL	0.883 + 0.004*SL	0.912 + 0.004*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PSOSCM1

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	13.460	0.744 + 0.254*CL	0.548 + 0.274*CL	0.877 + 0.252*CL
	t_F	13.448	0.660 + 0.255*CL	0.730 + 0.248*CL	0.596 + 0.257*CL
	t_{PLH}	6.813	0.909 + 0.117*CL	0.927 + 0.115*CL	0.877 + 0.119*CL
	t_{PHL}	7.308	1.014 + 0.124*CL	0.995 + 0.126*CL	0.993 + 0.126*CL
E to PADY	t_R	12.710	0.501 + 0.292*CL	0.951 + 0.247*CL	1.215 + 0.230*CL
	t_F	13.700	0.736 + 0.232*CL	0.458 + 0.260*CL	0.359 + 0.267*CL
	t_{PLH}	6.733	0.828 + 0.118*CL	0.844 + 0.116*CL	0.807 + 0.119*CL
	t_{PHL}	7.462	1.136 + 0.127*CL	1.138 + 0.127*CL	1.148 + 0.126*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.154	0.138 + 0.008*SL	0.139 + 0.008*SL	0.148 + 0.008*SL
	t_F	0.188	0.172 + 0.008*SL	0.176 + 0.007*SL	0.182 + 0.007*SL
	t_{PLH}	1.073	1.062 + 0.006*SL	1.066 + 0.004*SL	1.086 + 0.004*SL
	t_{PHL}	1.084	1.072 + 0.006*SL	1.077 + 0.004*SL	1.106 + 0.004*SL
E to YN	t_R	0.153	0.136 + 0.009*SL	0.138 + 0.008*SL	0.145 + 0.008*SL
	t_F	0.186	0.171 + 0.008*SL	0.173 + 0.007*SL	0.179 + 0.007*SL
	t_{PLH}	1.012	1.001 + 0.005*SL	1.005 + 0.004*SL	1.025 + 0.004*SL
	t_{PHL}	1.244	1.232 + 0.006*SL	1.237 + 0.004*SL	1.266 + 0.004*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

Switching Characteristics

PSOSCM2

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, CL: Capacitive Load)

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to PADY	t_R	4.014	0.589 + 0.066*CL	0.646 + 0.061*CL	0.500 + 0.070*CL
	t_F	3.578	0.703 + 0.064*CL	0.781 + 0.056*CL	0.790 + 0.056*CL
	t_{PLH}	2.865	1.083 + 0.042*CL	1.144 + 0.036*CL	1.183 + 0.034*CL
	t_{PHL}	3.158	1.148 + 0.048*CL	1.218 + 0.041*CL	1.272 + 0.038*CL
E to PADY	t_R	4.052	0.491 + 0.070*CL	0.574 + 0.062*CL	0.413 + 0.073*CL
	t_F	3.679	0.709 + 0.060*CL	0.719 + 0.059*CL	0.713 + 0.059*CL
	t_{PLH}	2.881	1.101 + 0.042*CL	1.151 + 0.036*CL	1.191 + 0.034*CL
	t_{PHL}	3.817	1.794 + 0.049*CL	1.865 + 0.042*CL	1.926 + 0.038*CL

*Group1 : CL < 10, *Group2 : 10 ≦ CL ≦ 15, *Group3 : 15 < CL

(Typical process, 25°C, 1.8V, t_R/t_F = 1.60ns, SL: Standard Load)

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PADA to YN	t_R	0.121	0.109 + 0.006*SL	0.110 + 0.005*SL	0.114 + 0.005*SL
	t_F	0.148	0.138 + 0.005*SL	0.139 + 0.005*SL	0.138 + 0.005*SL
	t_{PLH}	1.407	1.400 + 0.004*SL	1.402 + 0.003*SL	1.415 + 0.003*SL
	t_{PHL}	1.470	1.463 + 0.004*SL	1.465 + 0.003*SL	1.483 + 0.002*SL
E to YN	t_R	0.121	0.110 + 0.005*SL	0.110 + 0.005*SL	0.113 + 0.005*SL
	t_F	0.149	0.140 + 0.004*SL	0.140 + 0.005*SL	0.140 + 0.005*SL
	t_{PLH}	1.367	1.359 + 0.004*SL	1.361 + 0.003*SL	1.374 + 0.003*SL
	t_{PHL}	2.094	2.087 + 0.004*SL	2.089 + 0.003*SL	2.107 + 0.002*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 39, *Group3 : 39 < SL

PCI BUFFERS

Overview

PCI buffers are designed for PCI local bus application which is intended for high-performance 32-bit or 64-bit bus architecture.

Samsung supports PCI input, output and bi-directional buffers for 3.3V and 5V signaling environment.

Features

— 0.24µm, low-power, high performance CMOS Technology
— Input, output, and bi-directional PCI buffers
— PCI local bus specification rev2.2 compliant
— Operating at up to 66MHz, including 33MHz
— Electrically compliant interface in 3.3V and 5V bus environments

Description

These PCI buffers are designed for 3.3V and 5V environments. These buffers are compliant with the PCI local bus specification rev2.2. The PCI buffers for 66MHz can be available in 33MHz interface, but require more power pads due to their fast and noisy characteristics. The 5V tolerant PCI buffers can be used for 33MHz, 5V environment. These tolerant PCI buffers require 5V power for bulk of PMOS driver for 5V bus environment or 3.3V power for 3.3V environment. The 5V tolerant PCI drivers support 5V environment while EN5V is low. Although tolerant PCI buffers support 5V environment, they do not drive 5V.

NOTE: If you want to use PCI buffers, please contact SEC.

Cell List

Cell Name	Description	Operating Frequency	Operating Voltage
PTBPCI	bi-direction	Up to 33MHz at 5V signaling(note1) Up to 66MHz at 3.3V signaling	3.3V
PTOPCI	driver	Up to 33MHz at 5V signaling Up to 66MHz at 3.3V signaling	
PTIPCI	receiver	Up to 33MHz at 5V signaling Up to 66MHz at 3.3V signaling	

NOTE1: 3.3V signaling conditions: EN5V=high, VIO=3.3V, 5V tolerant is not supported.
5V signaling conditions: EN5V=low, VIO=5V, and 5V tolerant is supported.

Power Cell Name	Description
VDD1I_PCI	1.8V Power cell for internal core and PCI I/Os
VDD3OP_PCI	3.3V Power cell for PCI I/Os
VDD5O_PCI	VIO(3.3V or 5V) Power cell for PCI I/Os(note2)
VSSI_PCI	Gnd Power cell for internal core; not used for PCI I/Os
VSSOP_PCI	Gnd Power cell for PCI I/Os

NOTE2: In 3.3V signaling, VIO is 3.3V, which is provided through the vdd5o_pci power cell.
In 5V signaling, VIO is 5V, which is provided through the vdd5o_pci power cell.

Option (note3)

Cell Name	Description
vdet_m110pci	3.3V or 5V voltage detector

NOTE3: Voltage detector circuit will automatically set the EN5V pin either high or low according to VIO voltage level.

Electrical Characteristics

DC Characteristics

Symbol	Parameter	3.3V Signaling			5V Signaling			Unit
		Condition	Min	Max	Condition	Min	Max	
V_{CC}	Supply Voltage		3.0	3.6		3.0	3.6	V
VIO	Vdd5o Voltage		V_{CC}			4.75	5.25	V
V_{ih}	Input high voltage		$0.47V_{CC}$	V_{CC}+0.5		1.9	VIO+0.5	V
V_{il}	Input low voltage		– 0.5	$0.33V_{CC}$		– 0.5	0.9	V
I_i	Input leakage current	$0 < V_{IN} < V_{CC}$	–10	10	$0 < V_{IN} < VIO$	–70	70	µA
V_{oh}	Output high voltage	I_{OUT} = –500 µA	$0.9V_{CC}$	–	I_{OUT} = –2mA	2.4	–	V
V_{ol}	Output low voltage	I_{OUT} = 1500 µA	–	$0.1V_{CC}$	I_{OUT} = 6mA	–	0.55	V

AC Characteristics

Symbol	Parameter	3.3V Signaling			5V Signaling			Unit
		Condition	Min	Max	Condition	Min	Max	
$I_{oh\ (AC)}$	Switching current high	$V_{OUT} = 0.3V_{CC}$	$–12V_{CC}$		V_{OUT} = 1.4V	–44		mA
		$V_{OUT} = 0.7V_{CC}$		$–32V_{CC}$	V_{OUT} = 2.4V	– 2.33		
		$V_{OUT} = 0.9V_{CC}$	$–1.71V_{CC}$		V_{OUT} = 3.0V		– 142	
$I_{ol\ (AC)}$	Switching current low	$V_{OUT} = 0.6V_{CC}$	$16V_{CC}$		V_{OUT} = 2.2V	95		mA
		$V_{OUT} = 0.1V_{CC}$	$2.67V_{CC}$		V_{OUT} = 0.55V	23.9		
		$V_{OUT} = 0.18V_{CC}$		$38V_{CC}$	V_{OUT} = 0.71V		206	
I_{cl}	Low clamp current	$– 3 < V_{IN} \leq –1$	$–25 + (V_{IN} + 1) / 0.015$		$– 5 < V_{IN} \leq –1$	$–25 + (V_{IN} + 1) / 0.015$		mA
I_{ch}	High clamp current	$V_{CC}+1 \leq V_{IN} < V_{CC}+4$	$25 + (V_{IN} – V_{CC} – 1) / 0.015$					mA
T_r	Output rise time	$0.3V_{CC}$ to $0.6V_{CC}$	1.0	4.0	0.4V to 2.4V	1.0	5.0	V/ns
T_f	Output fall time	$0.6V_{CC}$ to $0.3V_{CC}$	1.0	4.0	2.4V to 0.4V	1.0	5.0	V/ns

PTIPCI

5V-tolerant PCI Input Buffers

Logic Symbol



Truth Table

Input Truth Table			
PAD	**PI**	**Y**	**PO**
1	1	1	0
0	x	0	1
1	0	1	1

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, SL: Standard Load)

PTIPCI

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	**Group2***	**Group3***
PAD to Y	t_R	0.153	0.140 + 0.006*SL	0.140 + 0.007*SL	0.142 + 0.007*SL
	t_F	0.064	0.059 + 0.002*SL	0.060 + 0.002*SL	0.059 + 0.002*SL
	t_{PLH}	0.711	0.703 + 0.004*SL	0.705 + 0.003*SL	0.712 + 0.003*SL
	t_{PHL}	1.251	1.248 + 0.002*SL	1.249 + 0.001*SL	1.259 + 0.001*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 60, *Group3 : 60 < SL

Logic Symbol



NOTE:
EN5V=Low: Enable the 5V signaling
EN5V=High: Enable the 3.3V signaling

Truth Table

Output Truth Table			
A	**EN**	**TN**	**PAD**
0	0	1	0
1	0	1	1
x	1	x	Hi-Z
x	x	0	HI-Z

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, CL: Capacitive Load)

PTOPCI

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	1.292	0.299 + 0.020*CL	0.254 + 0.021*CL	0.215 + 0.022*CL
	t_F	1.752	0.841 + 0.018*CL	0.822 + 0.019*CL	0.801 + 0.019*CL
	t_{PLH}	3.036	1.768 + 0.025*CL	1.758 + 0.026*CL	1.750 + 0.026*CL
	t_{PHL}	2.895	2.045 + 0.017*CL	2.137 + 0.014*CL	2.201 + 0.013*CL
TN to PAD	t_R	1.313	0.244 + 0.021*CL	0.230 + 0.022*CL	0.209 + 0.022*CL
	t_F	1.895	0.609 + 0.026*CL	0.771 + 0.020*CL	0.814 + 0.019*CL
	t_{PLH}	3.498	2.137 + 0.027*CL	2.162 + 0.026*CL	2.171 + 0.026*CL
	t_{PHL}	3.175	2.018 + 0.023*CL	2.234 + 0.016*CL	2.355 + 0.014*CL
	t_{PLZ}	2.400	2.399 + 0.000*CL	2.400 + 0.000*CL	2.400 + 0.000*CL
	t_{PHZ}	3.361	3.358 + 0.000*CL	3.359 + 0.000*CL	3.360 + 0.000*CL
EN to PAD	t_R	1.313	0.244 + 0.021*CL	0.230 + 0.022*CL	0.209 + 0.022*CL
	t_F	1.895	0.610 + 0.026*CL	0.771 + 0.020*CL	0.814 + 0.019*CL
	t_{PLH}	3.681	2.321 + 0.027*CL	2.346 + 0.026*CL	2.355 + 0.026*CL
	t_{PHL}	3.358	2.201 + 0.023*CL	2.418 + 0.016*CL	2.539 + 0.014*CL
	t_{PLZ}	2.347	2.346 + 0.000*CL	2.346 + 0.000*CL	2.346 + 0.000*CL
	t_{PHZ}	3.308	3.305 + 0.000*CL	3.307 + 0.000*CL	3.307 + 0.000*CL

*Group1 : CL < 30, *Group2 : 30 ≤ CL ≤ 50, *Group3 : 50 < CL

PTBPCI

5V-Tolerant PCI Bidirectional Buffer

Logic Symbol



NOTE:
EN5V=Low: Enable the 5V signaling
EN5V=High: Enable the 3.3V signaling

Truth Table

Input Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Output Truth Table

A	EN	TN	PAD
0	0	1	0
1	0	1	1
x	1	x	Hi-Z
x	x	0	Hi-Z

Option:

Logic Symbol



Truth Table

Input		Output
A	PD	Y
3.3V	⎍	1
5V	⎍	0
X	0	Last Y
X	1	Last Y

Cell Data

Cell Name	Detecting Voltage
vdet_m110pci	3.3V, 5V

USB (Universal Serial Bus) I/O Buffers *(Under Development)*

Overview

USB I/O buffer consists of a differential input receiver, a differential output driver, two single-ended receivers, and two pads. The differential input receiver has the 0.8V ~ 2.5V common mode input voltage range and both of the two single-ended receivers have 0.8V and 2.0V as their low and high input threshold voltages, V_{IL}, V_{IH}, respectively.

For low power consumption in a stand-by mode, the suspend pin (SUSPND) of the receiver and the driver should be in the high state. The differential output drivers have a Low/Full speed control pin (SPEED) to select the operation speed and have Output Enable Negative pin (OEN) to achieve a bi-directional half duplex operation.

Features

— Complies with universal serial bus specification 1.0
— Supports 12Mbps “Full speed” and 1.5Mbps “Low speed” serial data transmission
— Supports both “Full speed” and “Low speed” Design Kits
— Supports both “Full speed only” and “Low speed only” cells to reduce silicon area

Electrical Specifications

DC Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2)	Min	Max	Unit
Supply Current					
Suspend Device	I_{CCS}			10	µA
Leakage Current					
Hi-Z State Input Leakage	I_{LO}	0V < VIN < 3.3V	–10	10	µA
Input Levels					
Differential Input Sensitivity	V_{DI}	I (D+) – (D-) I	0.2		V
Differential Common Mode Range	V_{CM}	Includes V_{DI} range	0.8	2.5	
Single Ended Receiver Threshold	V_{SE}		0.8	2.0	
Output Levels					
Static Output Low	V_{OL}	RL of 1.5KΩ to 3.6V		0.3	V
Static Output High	V_{OH}	RL of 15KΩ to GND	2.8	3.6	
Capacitance					
Transceiver Capacitance	C_{IN}	Pin to GND		20	pF

Full Speed Output Buffer Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2, 3)	Min	Max	Unit
Driver Characteristics					
Transition Time Rise Time Fall Time	 T_R T_F	Notes 5 and Figure 1 CL = 50pF CL = 50pF	 4.0 4.0	 20.0 20.0	ns
Rise/Fall Time Matching	T_{RFM}	(T_R/T_F)	90	110	%
Output Signal Crossover Voltage	V_{CRS}		1.3	2.0	V
Drive Output Resistance	Z_{DRV}	Steady state drive	28	43	Ω

Low Speed Output Buffer Electrical Characteristics

Parameter	Symbol	Condition (Notes 1, 2, 4)	Min	Max	Unit
Driver Characteristics					
Transition Time Rise Time Fall Time	 T_R T_F	Notes 5 and Figure 1 CL = 50pF CL = 350pF CL = 50pF CL = 350pF	 75 75 	 300 300	ns
Rise/Fall Time Matching	T_{RFM}	(T_R/T_F)	80	120	%
Output Signal Crossover Voltage	V_{CRS}		1.3	2.0	V

NOTES:

1. All voltages are measured from the local ground potential, unless otherwise specified.
2. All timings use a capacitive load (CL) to ground of 50pF, unless otherwise specified.
3. Full speed timings have a 1.5KΩ pull-up to 2.8V on the DP data line.
4. Low speed timings have a 1.5KΩ pull-up to 2.8V on the DN data line.
5. Measured from 10% to 90% of the data signal.

FIGURE 1: Data Signal Rise and Fall Time



Full Speed: 4 to 20ns at C_L = 50pF Low Speed: 75ns at C_L = 50pF, 300ns at C_L = 350pF

Cell List

Cell Name	Function Description
PBUSB/PBUSB1	Low/Full speed USB Buffer (1.5 MHz/12 MHz select)
PBUSB_LS	Low speed only USB Buffer (1.5 MHz only, reduced cell size)
PBUSB_FS	Full speed only USB Buffer (12 MHz only, reduced cell size)

PBUSB/PBUSB1

Symbol



Pin Connection

Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

Cell Structure

PBUSB = PISER + PICDR + POTLS + POTFS
PBUSB1 = PISER + PICDR + POTLS + POTFS

There only exists PBUSB not PBUSB1 in the physical DB. The division of cell name (PBUSB/PBUSB1) is caused to notify their different working-mode. PBUSB selects POTLS (SPEED=0) to work on the Low Speed Mode. PBUSB1 selects POTFS (SPEED=1) to work on the Full Speed Mode.In case that the physical area is critical, Low speed only (PBUSB_LS) or Full speed only (PBUSB_FS) USB IO cell would be provided at the request of the customer, i.e.

PBUSB_LS = PISER + PICDR + POTLS
PBUSB_FS = PISER + PICDR + POTFS

PBUSB_LS

Symbol



Pin Connection

Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

PBUSB_FS

Symbol



Pin Connection

Input	Output	Bi-Direction
TXDP	RXDP	DP
TXDN	RXDN	DN
SUSPND	RXD	
OEN		
SPEED		

PISER

Single-Ended Receiver

Symbol



Pin Connection

Input	Output
DP	RXDP
DN	RXDN

Truth Table

DP	DN	RXDP	RXDN
0	0	0	0
0	1	0	1
1	0	1	0
1	1	1	1

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, SL: Standard Load)

PISER

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
DP to RXDP	t_R	0.172	0.141 + 0.015*SL	0.140 + 0.016*SL	0.134 + 0.016*SL
	t_F	0.169	0.143 + 0.013*SL	0.145 + 0.012*SL	0.131 + 0.013*SL
	t_{PLH}	0.633	0.615 + 0.009*SL	0.618 + 0.008*SL	0.624 + 0.008*SL
	t_{PHL}	0.792	0.773 + 0.010*SL	0.782 + 0.007*SL	0.809 + 0.007*SL
DN to RXDN	t_R	0.172	0.141 + 0.015*SL	0.140 + 0.016*SL	0.134 + 0.016*SL
	t_F	0.169	0.143 + 0.013*SL	0.145 + 0.012*SL	0.131 + 0.013*SL
	t_{PLH}	0.633	0.615 + 0.009*SL	0.618 + 0.008*SL	0.624 + 0.008*SL
	t_{PHL}	0.792	0.773 + 0.010*SL	0.782 + 0.007*SL	0.809 + 0.007*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 60, *Group3 : 60 < SL

PICDR

Differential Receiver

Symbol



Pin Connection

Input	Output
DP DN SUSPND	RXD

Truth Table

DP	DN	SUSPND	RXD
0	0	0	0
0	1	0	0
1	0	0	1
1	1	0	x
x	x	1	0

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, SL: Standard Load)

PICDR

R F

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
DP to RXD	t_R	0.218	0.187 + 0.016*SL	0.189 + 0.015*SL	0.166 + 0.016*SL
	t_F	0.181	0.163 + 0.009*SL	0.178 + 0.005*SL	0.248 + 0.004*SL
	t_{PLH}	9.772	9.749 + 0.012*SL	9.761 + 0.009*SL	9.796 + 0.008*SL
	t_{PHL}	9.016	8.997 + 0.009*SL	9.018 + 0.005*SL	9.130 + 0.003*SL
DN to RXD	t_R	0.245	0.212 + 0.016*SL	0.217 + 0.015*SL	0.202 + 0.015*SL
	t_F	0.218	0.199 + 0.010*SL	0.217 + 0.006*SL	0.295 + 0.004*SL
	t_{PLH}	3.777	3.751 + 0.013*SL	3.768 + 0.009*SL	3.825 + 0.008*SL
	t_{PHL}	4.446	4.423 + 0.012*SL	4.450 + 0.006*SL	4.588 + 0.003*SL
SUSPND to RXD	t_R	0.213	0.182 + 0.015*SL	0.183 + 0.015*SL	0.161 + 0.016*SL
	t_F	0.216	0.195 + 0.011*SL	0.215 + 0.006*SL	0.316 + 0.005*SL
	t_{PLH}	2.752	2.730 + 0.011*SL	2.741 + 0.009*SL	2.774 + 0.008*SL
	t_{PHL}	2.069	2.045 + 0.012*SL	2.072 + 0.006*SL	2.215 + 0.003*SL

*Group1 : SL < 4, *Group2 : 4 ≦ SL ≦ 60, *Group3 : 60 < SL

POTLS

Tri-State Output Buffer with Low Speed

Symbol



Pin Connection

Input	Output
TXDP TXDN SPEED SUSPND OEN	DP DN

Truth Table

TXDP	TXDN	SUSPND	OEN	SPEED	DP	DN
0	0	0	0	0	0	0
0	1	0	0	0	0	1
1	0	0	0	0	1	0
1	1	0	0	0	1	1
x	x	1	x	x	Hi-Z	Hi-Z
x	x	x	1	x	Hi-Z	Hi-Z
x	x	x	x	1	Hi-Z	Hi-Z

NOTE: SUSPND is the Suspend Mode control signal for the output driver. SUSPND=1 or OEN=1, both Low speed driver and Full speed driver are suspended. SPEED is the Low/Full speed output mode selecting signal, SPEED=0, SUSPND=0, OEN=0 Low speed mode transmitting.

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, CL: Capacitive Load)

POTLS

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TXDP to DP	t_R	116.340	115.140 + 0.024*CL	120.900 + 0.000*CL	122.040 + 0.000*CL
	t_F	135.000	135.000 + 0.000*CL	122.170 + 0.052*CL	135.790 + 0.000*CL
	t_{PLH}	112.415	112.415 + 0.000*CL	105.700 + 0.077*CL	105.280 + 0.082*CL
	t_{PHL}	113.570	109.045 + 0.091*CL	119.710 + 0.000*CL	110.170 + 0.004*CL
OEN to DP	t_R	114.285	114.285 + 0.000*CL	113.270 + 0.009*CL	113.210 + 0.010*CL
	t_F	129.395	129.395 + 0.000*CL	131.320 + 0.000*CL	127.390 + 0.000*CL
	t_{PLH}	80.167	80.167 + 0.000*CL	78.709 + 0.028*CL	74.371 + 0.086*CL
	t_{PHL}	113.860	109.810 + 0.081*CL	111.820 + 0.041*CL	120.070 + 0.000*CL
	t_{PLZ}	2.882	2.882 + 0.000*CL	2.882 + 0.000*CL	2.882 + 0.000*CL
	t_{PHZ}	3.079	3.078 + 0.000*CL	3.078 + 0.000*CL	3.079 + 0.000*CL
SPEED to DP	t_R	114.300	114.300 + 0.000*CL	113.260 + 0.009*CL	113.170 + 0.010*CL
	t_F	6.166	3.979 + 0.044*CL	4.262 + 0.038*CL	4.527 + 0.035*CL
	t_{PLH}	80.053	80.053 + 0.000*CL	78.593 + 0.028*CL	74.267 + 0.085*CL
	t_{PHL}	12.606	9.994 + 0.052*CL	10.530 + 0.042*CL	11.007 + 0.035*CL
	t_{PLZ}	2.855	2.855 + 0.000*CL	2.855 + 0.000*CL	2.855 + 0.000*CL
	t_{PHZ}	2.126	2.126 + 0.000*CL	2.127 + 0.000*CL	2.126 + 0.000*CL
SUSPND to DP	t_R	114.230	114.230 + 0.000*CL	113.240 + 0.009*CL	113.150 + 0.010*CL
	t_F	129.395	129.395 + 0.000*CL	131.340 + 0.000*CL	127.350 + 0.000*CL
	t_{PLH}	79.712	79.712 + 0.000*CL	78.298 + 0.028*CL	73.945 + 0.086*CL
	t_{PHL}	113.520	109.445 + 0.081*CL	111.500 + 0.040*CL	119.750 + 0.000*CL
	t_{PLZ}	2.674	2.674 + 0.000*CL	2.674 + 0.000*CL	2.674 + 0.000*CL
	t_{PHZ}	2.880	2.879 + 0.000*CL	2.880 + 0.000*CL	2.880 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POTFS

Tri-State Output Buffer with Full Speed

Symbol



Pin Connection

Input	Output
TXDP TXDN SPEED SUSPND OEN	DP DN

Truth Table

TXDP	TXDN	SUSPND	OEN	SPEED	DP	DN
0	0	0	0	1	0	0
0	1	0	0	1	0	1
1	0	0	0	1	1	0
1	1	0	0	1	1	1
x	x	1	x	x	Hi-z	Hi-z
x	x	x	1	x	Hi-z	Hi-z
x	x	x	x	0	Hi-z	Hi-z

NOTE: SUSPND is the Suspend Mode control signal for the output driver. SUSPND=1 or OEN=1, both Low speed driver and Full speed driver are suspended. SPEED is the Low/Full speed output mode selecting signal, SPEED=1, SUSPND=0, OEN=0 Low speed mode transmitting.

Switching Characteristics

(Typical process, 25°C, 1.8V, t_R/t_F = 0.80ns, CL: Capacitive Load)

POTFS

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
TXDP to DP	t_R	5.661	3.572 + 0.042*CL	3.880 + 0.036*CL	4.155 + 0.032*CL
	t_F	5.904	3.666 + 0.045*CL	3.981 + 0.038*CL	4.273 + 0.035*CL
	t_{PLH}	12.411	9.973 + 0.049*CL	10.513 + 0.038*CL	10.990 + 0.032*CL
	t_{PHL}	12.992	10.335 + 0.053*CL	10.896 + 0.042*CL	11.391 + 0.035*CL
OEN to DP	t_R	5.889	3.845 + 0.041*CL	4.118 + 0.035*CL	4.370 + 0.032*CL
	t_F	6.166	3.980 + 0.044*CL	4.262 + 0.038*CL	4.527 + 0.035*CL
	t_{PLH}	13.226	10.829 + 0.048*CL	11.344 + 0.038*CL	11.812 + 0.031*CL
	t_{PHL}	12.972	10.367 + 0.052*CL	10.896 + 0.042*CL	11.376 + 0.035*CL
	t_{PLZ}	1.778	1.778 + 0.000*CL	1.778 + 0.000*CL	1.778 + 0.000*CL
	t_{PHZ}	2.322	2.322 + 0.000*CL	2.322 + 0.000*CL	2.322 + 0.000*CL
SPEED to DP	t_R	5.889	3.844 + 0.041*CL	4.117 + 0.035*CL	4.370 + 0.032*CL
	t_F	6.166	3.977 + 0.044*CL	4.261 + 0.038*CL	4.527 + 0.035*CL
	t_{PLH}	12.625	10.225 + 0.048*CL	10.745 + 0.038*CL	11.210 + 0.031*CL
	t_{PHL}	12.370	9.770 + 0.052*CL	10.292 + 0.042*CL	10.778 + 0.035*CL
	t_{PLZ}	2.165	2.165 + 0.000*CL	2.165 + 0.000*CL	2.165 + 0.000*CL
	t_{PHZ}	2.710	2.710 + 0.000*CL	2.710 + 0.000*CL	2.710 + 0.000*CL
SUSPND to DP	t_R	5.889	3.845 + 0.041*CL	4.118 + 0.035*CL	4.370 + 0.032*CL
	t_F	129.370	129.370 + 0.000*CL	131.320 + 0.000*CL	127.390 + 0.000*CL
	t_{PLH}	12.860	10.460 + 0.048*CL	10.978 + 0.038*CL	11.446 + 0.031*CL
	t_{PHL}	113.730	109.705 + 0.081*CL	111.670 + 0.041*CL	119.980 + 0.000*CL
	t_{PLZ}	1.581	1.581 + 0.000*CL	1.581 + 0.000*CL	1.581 + 0.000*CL
	t_{PHZ}	3.049	3.049 + 0.000*CL	3.049 + 0.000*CL	3.049 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POWER PADS

Cell List

Cell Name		Function Description
VDD Power Pads	**VSS Power Pads**	
VDD2I	VSS2I	2.5V Internal
VDD2P	VSS2P	2.5V Pre-Driver
VDD2O	VSS2O	2.5V Output-Driver
VDD2IP	VSS2IP	2.5V Internal and Pre-Driver
VDD2OP	VSS2OP	2.5V Output-Driver and Pre-Driver
VDD2T	VSS2T	2.5V Total
VDD3P	VSS3P	3.3V Pre-Driver
VDD3O	VSS3O	3.3V Output-Driver
VDD3OP	VSS3OP	3.3V Output-Driver and Pre-Driver

Logic Symbol



Cell Name		Function Description
VDD Power Pads	**VSS Power Pads**	
VDD2I_ABB	VSS2I_ABB	2.5V Internal with Separate Bulk Bias
VDD2OP_ABB	VSS2OP_ABB	2.5V Pre-Driver and Output-Driver with Separate Bulk Bias
VDD2T_ABB	VSS2T_ABB	2.5V Total with Separate Bulk Bias
	VBB_ABB	Bulk Bias Power Pad
	VSSBB_ABB	Bulk Bias and VSS Power Pad

Logic Symbol



Analog Input

Cell Name	Function Description
PIC_ABB	Analog CMOS Level Input Buffer Separate Bulk-Bias
PICC_ABB	Analog CMOS Level Input Buffer Separate Bulk-Bias and without Nand-Tree
PICEN_ABB	Analog CMOS Level Input Buffer with Enable Port and Separate Bulk-Bias

Analog Output

Cell Name	Function Description
POT1_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 1mA Drive
POT2_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 2mA Drive
POT4_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 4mA Drive
POT8_ABB	Analog Tri-State Output Buffer with Separate Bulk Bias, 8mA Drive

PIC_ABB

Analog CMOS Level Input Buffers with Separate Bulk-Bias

Logic Symbol



Truth Table

PAD	PI	Y	PO
1	1	1	0
0	x	0	1
1	0	1	1

Standard Load (SL)

Cell Name	PI
PIC_ABB	3.620

Switching Characteristics

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)

PIC_ABB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.196	0.180 + 0.008*SL	0.179 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.210	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.421	1.410 + 0.005*SL	1.413 + 0.004*SL	1.430 + 0.004*SL
	t_{PHL}	1.826	1.814 + 0.006*SL	1.821 + 0.004*SL	1.896 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

Logic Symbol



Truth Table

PAD	Y
0	0
1	1

Switching Characteristics

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)

PICC_ABB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.175	0.160 + 0.007*SL	0.158 + 0.008*SL	0.128 + 0.008*SL
	t_F	0.189	0.175 + 0.007*SL	0.178 + 0.006*SL	0.143 + 0.006*SL
	t_{PLH}	1.405	1.394 + 0.006*SL	1.398 + 0.004*SL	1.416 + 0.004*SL
	t_{PHL}	1.810	1.798 + 0.006*SL	1.806 + 0.004*SL	1.887 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

PICEN_ABB

Analog CMOS Level Input Buffers with Enable Port and Separate Bulk-Bias

Logic Symbol



Truth Table

PAD	PI	EN	Y	PO
1	1	1	1	0
0	x	1	0	1
1	0	1	1	1
x	x	0	0	1

Standard Load (SL)

Cell Name	PI	EN
PICEN_ABB	2.897	2.897

Switching Characteristics

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 3.00ns, SL: Standard Load)

PICEN_ABB

Path	Parameter	Delay [ns] SL = 2	Delay Equations [ns]		
			Group1*	Group2*	Group3*
PAD to Y	t_R	0.197	0.181 + 0.008*SL	0.180 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.211	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	1.556	1.545 + 0.005*SL	1.549 + 0.004*SL	1.565 + 0.004*SL
	t_{PHL}	2.044	2.032 + 0.006*SL	2.039 + 0.004*SL	2.114 + 0.003*SL
EN to Y	t_R	0.196	0.181 + 0.008*SL	0.179 + 0.008*SL	0.159 + 0.008*SL
	t_F	0.211	0.197 + 0.007*SL	0.199 + 0.006*SL	0.166 + 0.006*SL
	t_{PLH}	0.792	0.781 + 0.005*SL	0.784 + 0.004*SL	0.801 + 0.004*SL
	t_{PHL}	1.091	1.079 + 0.006*SL	1.086 + 0.004*SL	1.161 + 0.003*SL

*Group1 : SL < 3, *Group2 : 3 ≦ SL ≦ 300, *Group3 : 300 < SL

Logic Symbol



Truth Table

TN	EN	A	PAD
1	0	0	0
1	0	1	1
x	1	x	Hi - z
0	x	x	Hi - z

Standard Load (SL)

Cell Name	TN	EN	A
POT1_ABB	2.898	2.916	3.023
POT2_ABB	2.898	2.916	3.023
POT4_ABB	2.898	2.916	3.023
POT8_ABB	2.898	2.916	3.023

Switching Characteristics

(Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacitive Load)

POT1_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	32.056	1.759 + 0.606*CL	1.758 + 0.606*CL	1.761 + 0.606*CL
	t_F	33.870	1.873 + 0.640*CL	1.872 + 0.640*CL	1.872 + 0.640*CL
	t_{PLH}	16.688	2.181 + 0.290*CL	2.180 + 0.290*CL	2.183 + 0.290*CL
	t_{PHL}	18.467	2.357 + 0.322*CL	2.359 + 0.322*CL	2.359 + 0.322*CL
TN to PAD	t_R	32.056	1.759 + 0.606*CL	1.758 + 0.606*CL	1.761 + 0.606*CL
	t_F	33.870	1.873 + 0.640*CL	1.872 + 0.640*CL	1.872 + 0.640*CL
	t_{PLH}	16.973	2.463 + 0.290*CL	2.465 + 0.290*CL	2.465 + 0.290*CL
	t_{PHL}	18.871	2.761 + 0.322*CL	2.761 + 0.322*CL	2.764 + 0.322*CL
	t_{PLZ}	1.841	1.841 + 0.000*CL	1.841 + 0.000*CL	1.841 + 0.000*CL
	t_{PHZ}	1.584	1.584 + 0.000*CL	1.584 + 0.000*CL	1.584 + 0.000*CL
EN to PAD	t_R	32.056	1.759 + 0.606*CL	1.758 + 0.606*CL	1.761 + 0.606*CL
	t_F	33.870	1.873 + 0.640*CL	1.872 + 0.640*CL	1.872 + 0.640*CL
	t_{PLH}	17.153	2.646 + 0.290*CL	2.645 + 0.290*CL	2.648 + 0.290*CL
	t_{PHL}	19.051	2.944 + 0.322*CL	2.941 + 0.322*CL	2.944 + 0.322*CL
	t_{PLZ}	1.923	1.923 + 0.000*CL	1.923 + 0.000*CL	1.923 + 0.000*CL
	t_{PHZ}	1.667	1.667 + 0.000*CL	1.667 + 0.000*CL	1.667 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics (Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacitive Load)

POT2_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	16.047	0.897 + 0.303*CL	0.899 + 0.303*CL	0.899 + 0.303*CL
	t_F	18.535	1.010 + 0.350*CL	1.011 + 0.350*CL	1.011 + 0.350*CL
	t_{PLH}	9.104	1.850 + 0.145*CL	1.851 + 0.145*CL	1.849 + 0.145*CL
	t_{PHL}	10.982	1.862 + 0.182*CL	1.864 + 0.182*CL	1.864 + 0.182*CL
TN to PAD	t_R	16.047	0.897 + 0.303*CL	0.899 + 0.303*CL	0.899 + 0.303*CL
	t_F	18.535	1.010 + 0.350*CL	1.011 + 0.350*CL	1.011 + 0.350*CL
	t_{PLH}	9.388	2.132 + 0.145*CL	2.135 + 0.145*CL	2.131 + 0.145*CL
	t_{PHL}	11.386	2.265 + 0.182*CL	2.266 + 0.182*CL	2.266 + 0.182*CL
	t_{PLZ}	1.690	1.690 + 0.000*CL	1.690 + 0.000*CL	1.690 + 0.000*CL
	t_{PHZ}	1.690	1.690 + 0.000*CL	1.690 + 0.000*CL	1.690 + 0.000*CL
EN to PAD	t_R	16.047	0.897 + 0.303*CL	0.899 + 0.303*CL	0.899 + 0.303*CL
	t_F	18.535	1.010 + 0.350*CL	1.011 + 0.350*CL	1.011 + 0.350*CL
	t_{PLH}	9.569	2.315 + 0.145*CL	2.316 + 0.145*CL	2.314 + 0.145*CL
	t_{PHL}	11.566	2.448 + 0.182*CL	2.446 + 0.182*CL	2.449 + 0.182*CL
	t_{PLZ}	1.772	1.772 + 0.000*CL	1.772 + 0.000*CL	1.772 + 0.000*CL
	t_{PHZ}	1.773	1.773 + 0.000*CL	1.773 + 0.000*CL	1.773 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

POT4_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	8.054	0.484 + 0.151*CL	0.480 + 0.151*CL	0.480 + 0.151*CL
	t_F	9.284	0.522 + 0.175*CL	0.521 + 0.175*CL	0.522 + 0.175*CL
	t_{PLH}	5.467	1.840 + 0.073*CL	1.840 + 0.073*CL	1.840 + 0.073*CL
	t_{PHL}	6.235	1.676 + 0.091*CL	1.676 + 0.091*CL	1.677 + 0.091*CL
TN to PAD	t_R	8.054	0.484 + 0.151*CL	0.480 + 0.151*CL	0.480 + 0.151*CL
	t_F	9.284	0.522 + 0.175*CL	0.521 + 0.175*CL	0.522 + 0.175*CL
	t_{PLH}	5.752	2.122 + 0.073*CL	2.124 + 0.073*CL	2.124 + 0.073*CL
	t_{PHL}	6.638	2.076 + 0.091*CL	2.078 + 0.091*CL	2.078 + 0.091*CL
	t_{PLZ}	1.822	1.822 + 0.000*CL	1.822 + 0.000*CL	1.822 + 0.000*CL
	t_{PHZ}	1.901	1.901 + 0.000*CL	1.901 + 0.000*CL	1.901 + 0.000*CL
EN to PAD	t_R	8.054	0.484 + 0.151*CL	0.480 + 0.151*CL	0.480 + 0.151*CL
	t_F	9.284	0.522 + 0.175*CL	0.521 + 0.175*CL	0.522 + 0.175*CL
	t_{PLH}	5.932	2.305 + 0.073*CL	2.305 + 0.073*CL	2.305 + 0.073*CL
	t_{PHL}	6.819	2.258 + 0.091*CL	2.259 + 0.091*CL	2.260 + 0.091*CL
	t_{PLZ}	1.905	1.905 + 0.000*CL	1.905 + 0.000*CL	1.905 + 0.000*CL
	t_{PHZ}	1.983	1.983 + 0.000*CL	1.983 + 0.000*CL	1.983 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

Switching Characteristics (Typical process, 25°C, 1.8V, 2.5V, t_R/t_F = 0.19ns, CL: Capacitive Load)

POT8_ABB

Path	Parameter	Delay [ns] CL = 50.0pF	Delay Equations [ns]		
			Group1*	Group2*	Group3*
A to PAD	t_R	4.117	0.414 + 0.074*CL	0.368 + 0.075*CL	0.336 + 0.075*CL
	t_F	4.673	0.309 + 0.087*CL	0.297 + 0.088*CL	0.291 + 0.088*CL
	t_{PLH}	3.928	2.109 + 0.036*CL	2.113 + 0.036*CL	2.114 + 0.036*CL
	t_{PHL}	3.981	1.712 + 0.045*CL	1.706 + 0.045*CL	1.703 + 0.046*CL
TN to PAD	t_R	4.117	0.414 + 0.074*CL	0.368 + 0.075*CL	0.336 + 0.075*CL
	t_F	4.672	0.307 + 0.087*CL	0.295 + 0.088*CL	0.290 + 0.088*CL
	t_{PLH}	4.213	2.392 + 0.036*CL	2.397 + 0.036*CL	2.398 + 0.036*CL
	t_{PHL}	4.373	2.088 + 0.046*CL	2.091 + 0.046*CL	2.093 + 0.046*CL
	t_{PLZ}	2.078	2.078 + 0.000*CL	2.078 + 0.000*CL	2.078 + 0.000*CL
	t_{PHZ}	2.320	2.320 + 0.000*CL	2.319 + 0.000*CL	2.320 + 0.000*CL
EN to PAD	t_R	4.117	0.414 + 0.074*CL	0.368 + 0.075*CL	0.336 + 0.075*CL
	t_F	4.672	0.307 + 0.087*CL	0.295 + 0.088*CL	0.290 + 0.088*CL
	t_{PLH}	4.393	2.575 + 0.036*CL	2.579 + 0.036*CL	2.579 + 0.036*CL
	t_{PHL}	4.553	2.271 + 0.046*CL	2.272 + 0.046*CL	2.273 + 0.046*CL
	t_{PLZ}	2.160	2.160 + 0.000*CL	2.160 + 0.000*CL	2.160 + 0.000*CL
	t_{PHZ}	2.402	2.402 + 0.000*CL	2.402 + 0.000*CL	2.402 + 0.000*CL

*Group1 : CL < 50, *Group2 : 50 ≦ CL ≦ 75, *Group3 : 75 < CL

ESD Slot Cells

Cell List

Cell Name	Function Description
EV1I	1.8V Internal ESD Protection
EV2P	2.5V Pre-Driver ESD Protection
EV2O	2.5V Output-Driver ESD Protection
EV2OP	2.5V Output-Driver and Pre-Driver ESD Protection
EV3P	3.3V Pre-Driver ESD Protection
EV3O	3.3V Output-Driver ESD Protection
EV3OP	3.3V Output-Driver and Pre-Driver ESD Protection
EV1I_ABB	1.8V Internal ESD Protection with Separated Bulk-Bias
EV2OP_ABB	2.5V Output-Driver and Pre-Driver ESD Protection with Separated Bulk-Bias

NOTE: All of Slot Cells have no Pad and can be added automatically by using Samsung utility CubicPlan.

Cell List

Cell Name	Function Description
EC0C0	Metal Ring Separator between Different Digital Blocks
EC0C0D(note 1)	Metal Ring Separator between Different Digital Blocks for Noise Critical Design
EC0CA0	Metal Ring Separator between Digital to Analog
EC0CA0D(note 1)	Metal Ring Separator between Digital to Analog for Noise Critical Design
EC0C0_BB	Metal Ring Separator between Different Analog Blocks with VBB Ring Separated
EC0C0D_BB (note 1)	Metal Ring Separator between Different Analog Blocks for Noise Critical Design with VBB Ring Separated
EC0C0_VBB (note 2)	Metal Ring Separator between Different Analog Blocks with VBB Ring Connected
EC0C0D_VBB (note 1, 2)	Metal Ring Separator between Different Analog Blocks for Noise Critical Design with VBB Ring Connected

NOTES:

1. If CDL ring connected with bi-directional diode, ESD protection level can be dropped.
2. If analog blocks have only one VBB power pad, metal connected VBB ring type should be used.
3. All of Slot Cells can be added automatically by using Samsung utility CubicPlan, or by Manual.

Compiled Memory

5

Contents

Overview 5-1
Compiled Memory Naming Convention 5-1
Characteristics for Timing and Power 5-2
Built-In Self Test and Built-In Redundancy-Analysis 5-4
Compiled Memory Selection Guide 5-5

Low-Power Compiled Memory
SPSRAM_LP Low-Power Single-Port Synchronous SRAM 5-6
DPSRAM_LP Low-Power Dual-Port Synchronous SRAM 5-16
SPARAM_LP Low-Power Single-Port Asynchronous SRAM 5-26
DROM Low-Power Synchronous Diffusion Programmable ROM 5-36
MROM Low-Power Synchronous Metal Programmable ROM 5-44

Overview to Compiled Datapath 5-52
Compiled Macrocell Selection Guide 5-53
ADDER Adder/Subtracter 5-54
BS Barrel Shifter 5-65
MPY Modified Booth Multiplier 5-77

OVERVIEW

OVERVIEW TO COMPILED MEMORY

This section contains the overview of STDM110 compiled memory. In STDM110 compiled memory, we provide application-specific memory solution - high-density and low-power application. That is, two different library set of compiled memory are available in STDM110 cell library. One is the high-density compiled memory, called STDM110-HD compiled memory and the other is the low-power compiled memory, called STDM110-LP compiled memory. The high-density compiled memories are suitable for high integration application with high-performance whereas the low-power compiled memories are suitable for portable applications. These are complete memories that are customized to satisfy the requirements of the circuit at hand. Depending on the function to be generated, the final memory will be implemented as a stand-alone, pitch-matched and customized leafcells. In addition, to implement optimized memory, we apply the state-of-the-art design architecture techniques. In STDM110 cell library, the compiled memory is fully generated by a user-configurable compiler, called memory compiler. It allows you to configure a memory through memory-related specification such as word depth, bit per word, column mux type and so on. The compiler allows you to select and customize any of memory to satisfy the specific circuit requirements. When the required specifications have been fully given, you may get any or all of the following items:

- Area-optimized and speed-optimized layout blocks
- Schematic netlist for simulation and verification
- Phantom cell to use in chip-level layout
- Tabular model for timing and power characteristics
- Automatic datasheet for a specific instance

For more detailed information regarding to memory compiler, contact your local representative or headquarters.

COMPILED MEMORY NAMING CONVENTION

The naming convention of compiled memory in this section will be shown as Figure 5-1. The memory name consists of the following convention.

[memory_code]_[appl_code]_[opt_code]_[config_code]

Figure 5-1. Compiled Memory Naming Convention

The first string, ‘memory_code’, means the name of memory type. In STDM110 compiled memory, the available memory types are as follows:

The second string, ‘appl_code’, means the specific application to suitably support the compiled memory and the application code is one of HD (High-Density), LP (Low-Power) and HS (High-Speed). In STDM110 compiled memory, the high-speed compiled memory is not supported as another library set. Instead, the high-density compiled memory can be applied for the high-performance application.
The third string, ‘opt_code’, represents the number of read and write ports for multi-port memory and the option code is composed of the following convention:

opt_code = <n>r<m>w

Currently this field is only used for ARFRAM, where n is the total number of read ports (1~2) and m is the total number of write ports (1~2). The last string, ‘config_code’, represents the configuration of the memory to be specified. This configuration code is composed of the following convention:

<WORD> x <BPW> m <YMUX> b <BANK>

Here, WORD is the word depth, BPW is bit per word, YMUX is the available column mux type and BANK is the number of bank to be used. For example, ‘spsram_hd_1024x32m16b2’ refers to a High-Density single-port synchronous SRAM with 1024 words, 32 bits, 16 column mux and 2 bank. Second, ‘arfram_hd_1r2w_32x32m2’ refers to a High-Density three-port (1 read/2 write) asynchronous register file with 32 word, 32 bits and 2 column mux and ‘spsram_lp_1024x32m16b2’ refers to a Low-Power single-port synchronous SRAM with 1024 words, 32 bits, 16 column mux and 2 bank.

CHARACTERISTICS FOR TIMING AND POWER

STDM110-HD compiled memory is only supported at 2.5V supply voltage whereas STDM110-LP compiled memory is supported at both 2.5V supply voltage and 1.8V supply voltage. Compiled memory in this section has been characterized using typical-case at 25 degree and 2.5V supply. The values of worst-case or best-case can be derived by using derating factors provided in Chapter 1.

For the timing characteristics, 2-dimensional table look-up model has been adopted to yield more accuracy. Based on the combination of input slopes and output loads, the propagation delay is measured from the input crossing 50% VDD to the output crossing 50% VDD. The timing values reported in the tables are also taken from the same voltage level as the switching characteristics with 0.2ns for input slope and 10SL(Standard Load) for output load.

For the power characteristics, the average power consumption is measured on the condition that input slope is 0.2ns and output load is 10SL. Also, the power consumption depends on input switching activity. The power values reported in the tables are also taken from 50% input switching activity. For compiled memory macrocells, average read power consumption, average write power consumption and average standby power consumption are available, except that the standby power consumption is not available in ARFRAM and FIFO. Average standby power consumption is measured on the condition that CSN (Chip Select Negative) is in disable mode and other signals are in normal operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while disabling CSN signal, if possible. In dual-port memory, the average power consumption is measured on the condition that only one port is in active mode and the other port is isolated.

BUILT-IN SELF TEST AND BUILT-IN REDUNDANCY-ANALYSIS

SEC provides engineering design services to support Built-In Self-Test (BIST) for the compiled memory macrocell. BIST circuits are designed to detect a set of fault types, such as stuck-at faults, transition faults, coupling faults and address decoder faults that adversely impact the functionality of the memory block. As shown in Figure 5-2, SEC adopts BIST architecture which is called SOA (Single Ordered Addressing) algorithm.



Figure 5-2. Memory BIST Architecture

From Figure 5-2, although several memory macrocells of the same types or the different types exist together in a circuit, SEC supports it as single BIST architecture. For more detailed information regarding to the BIST for compiled memory macrocells, please contact your local representative or headquarters.

SELECTION GUIDE FOR COMPILED MEMORY

Low-Power Compiled Memory

Application	Memory Type	Description
Low-Power	SPSRAM_LP	- Low-Power Single-port Synchronous Static RAM - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	DPSRAM_LP	- Low-Power Dual-port Synchronous Static RAM - Positive-edge clock operation - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	SPARAM_LP	- Low-Power Single-port Asynchronous Static RAM - Synchronous write operation / Asynchronous read operation - Dual bank available - Flexible aspect ratio (Ymux = 4, 8, 16, 32)
	DROM_LP	- Low-Power Synchronous Diffusion programmable ROM - Diffusion programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)
	MROM_LP	- Low-Power Synchronous Metal programmable ROM - Metal-2 programmable coded - Positive-edge clock operation - Dual bank available - Flexible aspect ratio (Ymux = 8, 16, 32)

Logic Symbol



NOTES:

1. Words(w) is the number of words in SPSRAM_LP.
2. Bpw(b) is the number of bits per word.
3. Ymux(y) is one of the lower address decoder types.
4. Banks(ba) is the number of banks.
5. $m = \lceil \log_2 w \rceil$

Features

- Suitable for low-power application
- Separated data I/O
- Synchronous operation
- Asynchronous tristate output
- Latched inputs and outputs
- Automatic power-down mode available
- Self-controlled circuit available
- Zero standby current
- Low noise output optimization
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPSRAM_LP is a single-port synchronous static RAM which is provided as a compiler. SPSRAM_LP is intended for use in low-power applications. On the rising edge of CK, the write cycle is initiated when WEN is low and CSN is low. The data on DI[] is written into the memory location specified on A[]. During the write cycle, DOUT[] remains stable. On the rising edge of CK, the read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] and DI[] are disabled, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

CK	CSN	WEN	OEN	A	DI	DOUT	COMMENT
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read Cycle

Parameter Description

SPSRAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	1	1	1	1
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If WEN is high on the rising edge of CK, the RAM is in read mode. Upon the falling edge of CK, the RAM is in a precharge state.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are present at DOUT.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other input. When OEN is high, DOUT is disabled and goes to high-impedance state.
A [ ]	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI [ ]	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT [ ]	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.

Pin Capacitance

Unit: [SL]

	CK	CSN	WEN	OEN	A	DI	DOUT
ba = 1	8.15	14.34	7.73	5.75	9.02	3.07	9.44
ba = 2	8.15	14.34	7.73	5.75	9.02	3.07	9.44

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPSRAM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from SPSRAM_LP compiler. Power is only consumed by the bank that is selected by the address and the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing.
   In chip-level layout, over-the-cell routing in SPSRAM_LP is permitted only for Metal-5 layer.

2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.

3. Power stripe should be tapped from both sides of SPSRAM_LP.

4. Power reduction during standby mode.
   The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

Characteristics

Definition for AC Timing (ns)			
Symbol	**Description**	**Symbol**	**Description**
t_{cyc}	Clock cycle time	t_{ckh}	Clock pulse width high
t_{ckl}	Clock pulse width low	t_{as}	Address setup time
t_{ah}	Address hold time	t_{cs}	CSN setup time
t_{ch}	CSN hold time	t_{ds}	Data-In setup time
t_{dh}	Data-In hold time	t_{ws}	WEN setup time
t_{wh}	WEN hold time	t_{acc}	Data access time
t_{da}	De-access time	t_{dz}	DOUT drive to high-Z time
t_{zd}	DOUT high-Z to drive time	t_{od}	OEN to valid output time
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

*** For Ymux=4** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**256**	**512**	**512**	**1024**	**768**	**1536**	**1024**	**2048**
bpw	**32**	**32**	**64**	**64**	**96**	**96**	**128**	**128**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.90	7.95	8.23	9.47	9.61	10.91	11.05	12.28
t_{ckl}	1.96	2.44	2.06	2.69	2.18	2.92	2.32	3.15
t_{ckh}	3.48	3.82	4.21	4.64	4.88	5.41	5.51	6.14
t_{as}	0.72	1.06	0.80	1.16	0.90	1.27	1.02	1.37
t_{ah}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.73
t_{cs}	1.60	2.29	1.74	2.58	1.87	2.85	2.00	3.11
t_{ch}	0.50	0.84	0.50	0.94	0.50	1.04	0.50	1.14
t_{ds}	0.71	0.89	0.71	1.00	0.71	1.12	0.71	1.23
t_{dh}	1.26	1.82	1.39	2.05	1.49	2.25	1.57	2.43
t_{ws}	1.20	1.52	1.27	1.65	1.32	1.76	1.33	1.83
t_{wh}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.73
t_{acc}	4.66	5.09	5.57	6.16	6.42	7.18	7.22	8.16
t_{da}	4.10	4.46	5.00	5.48	5.85	6.45	6.65	7.36
t_{dz}	0.99	0.98	1.13	1.12	1.24	1.23	1.33	1.32
t_{zd}	1.20	1.20	1.35	1.35	1.47	1.47	1.57	1.56
t_{od}	1.33	1.33	1.48	1.48	1.60	1.60	1.70	1.69
Power (µW/MHz)								
Power_read	67.62	77.96	133.94	161.06	206.41	259.57	285.03	373.49
Power_write	84.55	91.75	184.49	200.31	310.51	339.26	462.60	508.60
Power_standby	0.53	2.06	0.58	2.55	0.67	3.10	0.81	3.71
Area (µm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

SPSRAM_LP

Low-Power Single-Port Synchronous Static RAM

Reference Table

*** For Ymux=8** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**512**	**1024**	**1024**	**2048**	**1536**	**3072**	**2048**	**4096**
bpw	**16**	**16**	**32**	**32**	**48**	**48**	**64**	**64**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.90	7.93	8.22	9.43	9.62	10.85	11.08	12.19
t_{ckl}	1.99	2.45	2.07	2.71	2.11	2.95	2.12	3.15
t_{ckh}	3.49	3.82	4.21	4.65	4.88	5.41	5.51	6.13
t_{as}	0.73	1.06	0.76	1.16	0.79	1.27	0.82	1.37
t_{ah}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.74
t_{cs}	1.60	2.26	1.68	2.53	1.74	2.79	1.79	3.04
t_{ch}	0.50	0.84	0.50	0.94	0.50	1.04	0.50	1.13
t_{ds}	0.70	0.89	0.70	1.00	0.70	1.12	0.70	1.23
t_{dh}	1.24	1.80	1.34	2.01	1.43	2.19	1.49	2.35
t_{ws}	1.20	1.52	1.28	1.65	1.32	1.76	1.33	1.83
t_{wh}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.74
t_{acc}	4.71	5.16	5.61	6.23	6.47	7.25	7.27	8.22
t_{da}	4.12	4.49	5.02	5.50	5.87	6.47	6.67	7.38
t_{dz}	0.96	0.95	1.06	1.06	1.15	1.14	1.21	1.21
t_{zd}	1.17	1.17	1.28	1.28	1.37	1.37	1.44	1.44
t_{od}	1.30	1.30	1.41	1.41	1.50	1.50	1.57	1.57
Power (µW/MHz)								
Power_read	47.39	55.61	89.05	107.40	133.83	166.91	181.74	234.14
Power_write	57.85	63.52	118.53	129.12	193.27	210.96	282.08	309.04
Power_standby	0.52	2.05	0.59	2.57	0.67	3.11	0.77	3.66
Area (µm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

Reference Table

*** For Ymux=16** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**1024**	**2048**	**2048**	**4096**	**3072**	**6144**	**4096**	**8192**
bpw	**8**	**8**	**16**	**16**	**24**	**24**	**32**	**32**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.90	7.93	8.23	9.42	9.62	10.82	11.09	12.15
t_{ckl}	1.97	2.44	2.03	2.71	2.08	2.95	2.13	3.15
t_{ckh}	3.50	3.82	4.21	4.65	4.88	5.41	5.50	6.13
t_{as}	0.73	1.06	0.75	1.17	0.76	1.27	0.76	1.36
t_{ah}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.73
t_{cs}	1.60	2.25	1.67	2.51	1.72	2.76	1.75	3.00
t_{ch}	0.50	0.84	0.50	0.94	0.50	1.04	0.50	1.13
t_{ds}	0.70	0.88	0.70	1.00	0.70	1.12	0.70	1.23
t_{dh}	1.23	1.79	1.32	1.99	1.40	2.16	1.45	2.31
t_{ws}	1.20	1.52	1.28	1.65	1.32	1.76	1.33	1.84
t_{wh}	1.12	1.39	1.17	1.53	1.20	1.64	1.21	1.73
t_{acc}	4.78	5.25	5.68	6.32	6.53	7.33	7.34	8.30
t_{da}	4.15	4.53	5.05	5.53	5.89	6.49	6.69	7.40
t_{dz}	0.94	0.93	1.03	1.02	1.10	1.09	1.15	1.15
t_{zd}	1.15	1.15	1.25	1.25	1.32	1.32	1.37	1.37
t_{od}	1.28	1.28	1.38	1.38	1.45	1.45	1.50	1.50
Power (µW/MHz)								
Power_read	36.39	42.92	64.92	77.60	95.03	116.16	126.73	158.60
Power_write	44.55	49.38	85.67	93.63	134.90	147.06	192.24	209.68
Power_standby	0.51	2.05	0.58	2.55	0.66	3.06	0.76	3.57
Area (µm)								
Width	700.90	700.90	1303.55	1303.55	1906.21	1906.21	2508.86	2508.86
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

Reference Table

*** For Ymux=32** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**2048**	**4096**	**4096**	**8192**	**6144**	**12288**	**8192**	**16384**
bpw	**4**	**4**	**8**	**8**	**12**	**12**	**16**	**16**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.97	8.03	8.31	9.51	9.72	10.92	11.20	12.25
t_{ckl}	1.94	2.45	2.02	2.71	2.07	2.95	2.10	3.15
t_{ckh}	3.60	3.93	4.31	4.74	4.97	5.50	5.58	6.21
t_{as}	0.73	1.07	0.74	1.17	0.74	1.27	0.75	1.37
t_{ah}	1.10	1.39	1.16	1.53	1.20	1.64	1.21	1.73
t_{cs}	1.57	2.25	1.64	2.52	1.69	2.77	1.74	3.01
t_{ch}	0.50	0.84	0.50	0.94	0.50	1.04	0.50	1.13
t_{ds}	0.70	0.89	0.70	1.00	0.70	1.12	0.70	1.23
t_{dh}	1.24	1.79	1.34	1.99	1.41	2.17	1.45	2.31
t_{ws}	1.16	1.52	1.25	1.65	1.31	1.76	1.34	1.84
t_{wh}	1.10	1.39	1.16	1.53	1.20	1.64	1.21	1.73
t_{acc}	5.01	5.54	5.93	6.60	6.79	7.62	7.60	8.60
t_{da}	4.32	4.70	5.21	5.71	6.06	6.66	6.86	7.57
t_{dz}	0.94	0.93	1.03	1.03	1.10	1.09	1.14	1.13
t_{zd}	1.15	1.14	1.25	1.22	1.32	1.30	1.35	1.38
t_{od}	1.28	1.28	1.38	1.38	1.45	1.45	1.48	1.49
Power (µW/MHz)								
Power_read	31.30	36.62	54.24	63.82	77.99	93.00	102.56	124.15
Power_write	38.38	42.42	70.70	77.10	108.18	117.47	150.80	163.54
Power_standby	0.51	2.04	0.55	2.54	0.59	3.02	0.63	3.50
Area (µm)								
Width	686.34	686.34	1295.06	1295.06	1903.78	1903.78	2512.50	2512.50
Height	483.42	927.14	807.26	1574.82	1131.10	2222.50	1454.94	2870.18

NOTE: Standby power is measured on condition that CSN is High and the others are in normal operation mode.

Read Cycle



Write Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



NOTES:

1. Words (w) is the number of words in DPSRAM_LP.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. m = $\lceil \log_2 w \rceil$

Features

- Suitable for low-power applications
- Synchronous operation
- Automatic power-down mode available
- Self-controlled circuit available
- Asynchronous tristate output
- Low noise output optimization
- Separated data I/O
- Flexible aspect ratio
- Zero standby current
- Latched inputs and outputs
- Up to128Kbits capacity
- Up to 8K number of words
- Up to 128 number of bit per word

Function Description

DPSRAM_LP is a dual-port synchronous static RAM which is provided as a compiler. DPSRAM_LP is intended for use in low-power applications. Each port is fully independent. On the rising edge of CK1 (CK), the write cycle is initiated when WEN1 (WEN2) is low and CSN1 (CSN2) is low. The data on DI1[] (DI2[]) is written into the memory location specified on A1[](A2[]). During the write cycle, DOUT1[] (DOUT2[]) remains stable. On the rising edge of CK1 (CK2), the read cycle is initiated when WEN1 (WEN2) is high and CSN1(CSN2) is low. The data at DOUT1[] (DOUT2[]) become valid after a delay. While in standby mode that CSN1(CSN2) is high, A1[] (A2[]) and DI1[] (DI2[]) are disabled, data stored in the memory is retained and DOUT1[] (DOUT2[]) remains stable. When OEN1 (OEN2) is high, DOUT1[] (DOUT2[]) is placed in a high-impedance state.

DPSRAM_LP Function Table

CK1 CK2	CSN1 CSN2	WEN1 WEN2	OEN1 OEN2	A1 A2	DI1 DI2	DOUT1 DOUT2	Comment
X	X	X	H	X	X	Z	Unconditional tri-state output
X	H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	L	Valid	Valid	DOUT(t-1)	Write cycle
↑	L	H	L	Valid	X	MEM(A)	Read Cycle

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Parameter Description

DPSRAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and column mux(y).

Parameters		Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	Min	32	64	128	256
	Max	1024	2048	4096	8192
	Step	16	32	64	128
Bpw (b)	Min	1	1	1	1
	Max	128	64	32	16
	Step	1	1	1	1

Pin Descriptions

Name	Type	Description
CK1 CK2	Clock	Clock input. CSN, WEN, A[] and DI[] are latched into the RAM on the rising edge of CK. If CSN and WEN are low on the rising edge of CK, the RAM is in write mode. If WEN is high on the rising edge of CK, the RAM is in read mode. Upon the falling edge of CK, the RAM is in a precharge state.
CSN1 CSN2	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the RAM on the rising edge of CK. When CSN is low, the RAM is enabled for reading or writing, depending on the state of WEN. When CSN is high, the RAM goes to the standby mode and is disabled for reading or writing. DOUT remains previous data output.
WEN1 WEN2	Read/Write Enable	Read or write enable input. The read/write enable is latched into the RAM on the rising edge of CK. When WEN is low, data are written to the addressed location and DOUT remains stable. When WEN is high, data from the addressed word are present at DOUT.
OEN1 OEN2	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of the state of other inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A1 [ ] A2 [ ]	Address	Address input bus. The address is latched into the RAM on the rising edge of CK.
DI1 [ ] DI2 [ ]	Data Input	Data input bus. Data are latched on the rising edge of CK. Data input is written into the addressed location in write mode.
DOUT1 [ ] DOUT2 [ ]	Data Output	Data output bus. Data output is valid after the rising edge of CK while the RAM is in read mode. Data output remains previous data output while the RAM is in write mode.

Pin Capacitance

(Unit = SL)

CK	CSN	WEN	OEN	A	DI	DOUT
5.04	12.00	7.25	4.51	8.02	4.94	9.13

NOTE: Each pin's capacitance is exactly same regardless of available mux types.

Block Diagram



Application Notes

1. Permitting over-the-cell routing
In chip-level layout, over-the-cell routing in DPSRAM_LP is permitted for only Metal-5 layer.

2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.

3. Power stripe should be tapped from both sides of DPSRAM_LP.

4. Contention mode in same address access
In DPSRAM_LP, simultaneous operation by both ports on the same memory address, as write/write, write/read or read/write operation, causes a contention problem. Simultaneous operation is defined as a state in which both ports are enabled, both address buses are equal at the rising edge of CK. DPSRAM_LP has no scheme preventing the contention. Due to simultaneous operation, silicon will behave unpredictably. A write operation cannot end and data appearing at outputs may not be valid. Please refer to the timing diagrams if you want to avoid the contention mode between both ports. In write/write operation, the data stored at the current address will be unpredictable. In write/read or read/write operation, the read port is invalid while the write port is still valid. If you want to avoid the contention mode, you have to give the value greater than tcc (clock-to-clock setup time). However, simultaneous read/read is allowable without any restrictions.Power reduction during standby mode.

5. Power reduction during standby mode
The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Characteristics

Definition for AC Timing (ns)			
Symbol	**Description**	**Symbol**	**Description**
t_{cyc}	Clock cycle time	t_{ckl}	Clock pulse width low
t_{ckh}	Clock pulse width high	t_{cc}	Clock to Clock Setup time
t_{as}	Address setup time	t_{ah}	Address hold time
t_{cs}	CSN setup time	t_{ch}	CSN hold time
t_{ds}	Data-In setup time	t_{dh}	Data-In hold time
t_{ws}	WEN setup time	t_{wh}	WEN hold time
t_{acc}	Data access time	t_{da}	De-access time
t_{dz}	DOUT drive to high-Z time	t_{zd}	DOUT high-Z to drive time
t_{od}	OEN to valid output time		
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

*** For Ymux=4** (Typical process2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	**256**	**512**	**768**	**1024**
bpw	**32**	**64**	**96**	**128**
Timing (ns)				
t_{cyc}	7.15	9.31	11.55	13.84
t_{ckl}	1.92	2.20	2.60	3.10
t_{ckh}	3.44	4.55	5.74	7.02
t_{cc}	3.03	4.14	5.32	6.57
t_{as}	0.77	1.02	1.31	1.62
t_{ah}	0.93	0.97	0.98	0.98
t_{cs}	1.79	2.22	2.74	3.36
t_{ch}	0.45	0.45	0.45	0.44
t_{ds}	0.34	0.34	0.34	0.34
t_{dh}	1.24	1.52	1.81	2.12
t_{ws}	1.20	1.26	1.28	1.27
t_{wh}	0.93	0.97	0.98	0.98
t_{acc}	4.55	5.91	7.36	8.93
t_{da}	4.07	5.42	6.88	8.45
t_{dz}	1.10	1.39	1.69	2.00
t_{zd}	1.30	1.59	1.89	2.20
t_{od}	1.42	1.71	2.01	2.32
Power (µW/MHz)				
Power_read	91.02	179.16	278.26	388.31
Power_write	1.21	1.72	2.81	4.46
Power_standby	111.04	248.10	427.72	649.88
Area (µm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Reference Table

*** For Ymux=8** (Typical process2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	**512**	**1024**	**1536**	**2048**
bpw	**16**	**32**	**48**	**64**
Timing (ns)				
t_{cyc}	7.10	9.27	11.52	13.83
t_{ckl}	1.90	2.17	2.55	3.04
t_{ckh}	3.44	4.55	5.74	7.03
t_{cc}	3.03	4.14	5.32	6.57
t_{as}	0.77	1.04	1.34	1.66
t_{ah}	0.94	0.97	0.99	0.98
t_{cs}	1.72	2.11	2.62	3.26
t_{ch}	0.45	0.45	0.45	0.44
t_{ds}	0.34	0.34	0.34	0.34
t_{dh}	1.20	1.42	1.66	1.90
t_{ws}	1.20	1.26	1.28	1.27
t_{wh}	0.94	0.97	0.99	0.98
t_{acc}	4.63	6.00	7.46	9.02
t_{da}	4.10	5.46	6.92	8.49
t_{dz}	1.04	1.28	1.51	1.76
t_{zd}	1.25	1.49	1.72	1.96
t_{od}	1.37	1.60	1.84	2.08
Power (µW/MHz)				
Power_read	69.02	125.93	188.38	256.35
Power_write	80.79	166.09	274.18	405.07
Power_standby	0.81	1.06	1.55	2.30
Area (µm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=16** (Typical process2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	**1024**	**2048**	**3072**	**4096**
bpw	**8**	**16**	**24**	**32**
Timing (ns)				
t_{cyc}	7.08	9.24	11.51	13.89
t_{ckl}	1.93	2.24	2.56	2.90
t_{ckh}	3.44	4.55	5.74	7.03
t_{cc}	3.03	4.14	5.31	6.57
t_{as}	0.74	0.99	1.28	1.59
t_{ah}	0.93	0.97	0.98	0.98
t_{cs}	1.74	2.16	2.61	3.06
t_{ch}	0.45	0.45	0.45	0.44
t_{ds}	0.34	0.34	0.34	0.34
t_{dh}	1.17	1.37	1.57	1.79
t_{ws}	1.20	1.26	1.28	1.27
t_{wh}	0.93	0.97	0.98	0.98
t_{acc}	4.69	6.07	7.53	9.08
t_{da}	4.12	5.48	6.93	8.50
t_{dz}	1.02	1.22	1.43	1.63
t_{zd}	1.22	1.43	1.64	1.85
t_{od}	1.34	1.55	1.75	1.97
Power (µW/MHz)				
Power_read	65.42	105.59	148.64	194.56
Power_write	74.14	133.68	206.20	291.70
Power_standby	0.78	0.92	1.18	1.55
Area (µm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DPSRAM_LP

Low-Power Dual-Port Synchronous Static RAM

Reference Table

*** For Ymux=32** (Typical process2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters				
words	**2048**	**4096**	**6144**	**8192**
bpw	**4**	**8**	**12**	**16**
Timing (ns)				
t_{cyc}	7.05	9.23	11.51	13.91
t_{ckl}	1.92	2.23	2.54	2.87
t_{ckh}	3.44	4.55	5.74	7.03
t_{cc}	3.04	4.13	5.31	6.57
t_{as}	0.74	0.99	1.28	1.59
t_{ah}	0.94	0.97	0.99	0.98
t_{cs}	1.72	2.14	2.57	3.01
t_{ch}	0.45	0.45	0.45	0.44
t_{ds}	0.34	0.34	0.34	0.34
t_{dh}	1.16	1.35	1.54	1.73
t_{ws}	1.20	1.26	1.28	1.27
t_{wh}	0.94	0.97	0.99	0.98
t_{acc}	4.79	6.19	7.66	9.20
t_{da}	4.16	5.51	6.97	8.54
t_{dz}	1.01	1.20	1.38	1.57
t_{zd}	1.21	1.40	1.59	1.79
t_{od}	1.33	1.52	1.71	1.91
Power (µW/MHz)				
Power_read	58.88	90.94	124.54	159.69
Power_write	65.90	113.17	168.58	232.14
Power_standby	0.76	0.85	0.99	1.18
Area (µm)				
Width	1063.71	2012.43	2961.15	3909.87
Height	524.26	873.70	1223.14	1572.58

NOTES:

1. In power consumption of DPSRAM_LP, only one port is measured and the other port is isolated.
2. Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle



(CSN = low, OEN = low, DI = don't care)

Write Cycle



(CSN= low, OEN = don't care)

Read Cycle with CSN Controlled



(OEN = low, WEN = high, DI = don't care)

OEN Controlled Output Enable



(CK, A, WEN, DI, CSN = don't care)

Contention Mode



(A1 = A2)

NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



NOTES:

1. Words (w) is the number of words in SPARAM_LP.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. Banks(ba) is the number of banks.
5. $m = \lceil \log_2 w \rceil$

Features

- Suitable for low-power applications
- Standby (power down) mode available
- Separated data I/O
- Asynchronous operation
- Asynchronous tri-state output
- Address transition detectors
- Write enable transition detector
- Chip select transition detector
- Bank select transition detector
- Automatic power-down mode
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual bank scheme available
- Up to 256Kbits capacity
- Up to 16K number of words
- Up to 128 number of bit per word

Function Description

SPARAM_LP is a single-port asynchronous static RAM which is provided as a compiler. SPARAM_LP is intended for use in low-power applications. At the falling edge of WEN, the write cycle is initiated. At the rising edge of WEN, the write cycle is ended. During the write cycle, the data on DI[] is written into the memory location specified on A[]. The read cycle is initiated when WEN is high and CSN is low. The data at DOUT[] become valid after a delay whenever A[] transition is detected. While in standby mode that CSN is high, A[] and DI[] are disabled, data stored in the memory is retained and DOUT[] remains stable. When OEN is high, DOUT[] is placed in a high-impedance state.

SPARAM_LP Function Table

CSN	WEN	OEN	A	DI	DOUT	Comment
X	X	H	X	X	Z	Unconditional tri-state output
H	X	L	X	X	DOUT(t-1)	De-selected (standby mode)
L	↓	L	Valid	Valid	DOUT(t-1)	Write cycle starts
L	↑	L	Valid	Valid	MEM(A)	Write cycle ends and read cycle starts
L	L	L	Stable	Valid	DOUT(t-1)	Write cycle
L	H	L	Toggle	X	MEM(A)	Read cycle

SPARAM_LP

Low-Power Single-Port Asynchronous Static RAM

Parameter Description

SPARAM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bit per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 4	Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	32	64	128	256
		Max	1024	2048	4096	8192
		Step	16	32	64	128
	ba = 2	Min	64	128	256	512
		Max	2048	4096	8192	16384
		Step	32	64	128	256
Bpw (b)		Min	1	1	1	1
		Max	128	64	32	16
		Step	1	1	1	1

Pin Descriptions

Name	I/O	Description
CSN	Chip Enable	Chip select input. The chip select signal acts as the memory enable signal for selections of multiple blocks. When CSN is high, the memory goes to stand-by (power down) mode and no access to the memory can occur. Conversely, if low, a read or write access can occur. When CSN falls, an access is initiated.
WEN	Read/Write Enable	Write enable input. The write enable signal selects the type of memory access. The high state for a read access and the low state for a write access. Upon the rising edge of WEN, a write access completed and a read access initiated.
OEN	Data Output Enable	Output enable input. The output enable signal controls the output drivers from driven to tri-state condition unconditionally.
A [ ]	Address	Address input bus. A[] should be stable when WEN is low. The address selects the location to be accessed. When the address changes, the transition is detected and the internal clock pulse is generated.
DI [ ]	Data Input	Data input bus. The data input is written to the accessed location when WEN is low.
DOUT [ ]	Data Output	Data output bus. The data output is data stored in the accessed location during a read access. Data output driver has tri-state logic. When OEN is low, the driver drives a certain value. Otherwise, data output keeps Hi-Z state. During a write access, data on DOUT is predictable.

Pin Capacitance

Unit: [SL]

	CSN	WEN	OEN	A	DI	DOUT
ba = 1	1.87	1.87	1.87	3.91	1.87	7.12
ba = 2	1.87	1.87	1.87	3.91	1.87/	7.12

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

SPARAM_LP has 2 different physical architectures due to the word depth. Optionally, one of these architectures is generated from SPARAM_LP compiler. In dual-bank, the bank selected by the address is only activated while the other bank is in idle mode.



Application Notes

1. Permitting over-the-cell routing
   In chip-level layout, over-the-cell routing in SPARAM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of SPARAM_LP.
4. Avoiding short transition on the address bus
   In SPARAM_LP, rather than the write operation which is synchronously performed by WEN signal, the read operation is asynchronously performed whenever the address transition is occurred. In this case, if the short transition on the address, called a skew, is happened, since SPARAM_LP recognizes the short address transition as the stable address transition and do perform a read operation. At that time, while in the read operation, the data stored in the memory may be corrupted due to the short transition. To prevent such fail, the stable address cycle time (tcyc) is required. The essential requirement to recognize valid address transition is that at least minimum address period should be equal or greater than tacc (access time).
5. Power reduction during standby mode.
   The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

Characteristics

Definition for AC Timing (ns)			
Symbol	**Description**	**Symbol**	**Description**
t_{cyc}	Address cycle time	t_{as}	Address setup time
t_{cas}	Address setup time for CSN rise	t_{ah}	Address hold time
t_{wh}	WEN hold time	t_{cs}	CSN setup time
t_{ch}	CSN hold time	t_{ds}	Data-In setup time
t_{dh}	Data-In hold time	t_{wen}	WEN pulse width low
t_{acc}	Data access time for read cycle	t_{wacc}	Data access time for WEN rise
t_{da}	De-access time	t_{wda}	De-access time for WEN rise
t_{zd}	DOUT high-Z to drive time	t_{dz}	DOUT drive to high-Z time
t_{od}	OEN to valid output time		
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_write	The dynamic average power consumption while in a write cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

*** For Ymux=4** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**256**	**512**	**512**	**1024**	**768**	**1536**	**1024**	**2048**
bpw	**32**	**32**	**64**	**64**	**96**	**96**	**128**	**128**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	5.84	5.98	6.39	6.60	6.95	7.23	7.50	7.85
t_{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{cas}	6.14	6.28	6.69	6.90	7.24	7.52	7.80	8.15
t_{ah}	2.36	2.38	2.89	2.92	3.42	3.45	3.95	3.98
t_{wh}	6.14	6.28	6.69	6.90	7.24	7.52	7.80	8.15
t_{ds}	0.10	0.29	0.15	0.41	0.15	0.45	0.09	0.42
t_{dh}	0.89	0.84	1.02	0.92	1.15	1.00	1.27	1.08
t_{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{ch}	1.95	2.13	2.06	2.31	2.17	2.49	2.28	2.68
t_{wen}	4.11	4.32	4.59	4.91	5.07	5.50	5.56	6.09
t_{acc}	5.84	5.98	6.39	6.60	6.95	7.23	7.50	7.85
t_{da}	1.40	1.40	1.40	1.40	1.40	1.40	1.40	1.40
t_{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{wacc}	1.66	1.83	1.76	2.01	1.87	2.19	1.98	2.38
t_{dz}	0.43	0.43	0.53	0.53	0.63	0.63	0.72	0.72
t_{zd}	0.41	0.41	0.51	0.51	0.61	0.61	0.70	0.69
t_{od}	0.57	0.57	0.67	0.67	0.76	0.77	0.86	0.86
Power (µW/MHz)								
Power_read	63.27	76.91	113.57	145.13	161.88	218.96	208.20	298.42
Power_write	100.89	112.83	222.37	257.95	388.11	460.72	598.11	721.14
Power_standby	7.90	12.97	13.94	24.37	20.01	38.01	26.12	53.88
Area (µm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=8** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**512**	**1024**	**1024**	**2048**	**1536**	**3072**	**2048**	**4096**
bpw	**16**	**16**	**32**	**32**	**48**	**48**	**64**	**64**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	5.87	6.02	6.42	6.65	6.98	7.27	7.53	7.89
t_{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{cas}	6.17	6.32	6.72	6.94	7.24	7.57	7.83	8.19
t_{ah}	2.37	2.38	2.90	2.92	3.42	3.45	3.95	3.98
t_{wh}	6.17	6.32	6.72	6.94	7.27	7.57	7.83	8.19
t_{ds}	0.18	0.31	0.24	0.45	0.25	0.51	0.18	0.49
t_{dh}	0.85	0.77	0.99	0.85	1.12	0.93	1.24	1.01
t_{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{ch}	1.98	2.17	2.09	2.36	2.20	2.54	2.31	2.72
t_{wen}	4.15	4.40	4.63	4.99	5.12	5.58	5.60	6.17
t_{acc}	5.87	6.02	6.42	6.65	6.98	7.27	7.53	7.89
t_{da}	1.40	1.40	1.40	1.40	1.40	1.40	1.40	1.40
t_{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{wacc}	1.69	1.87	1.79	2.06	1.90	2.24	2.01	2.42
t_{dz}	0.39	0.39	0.46	0.47	0.53	0.53	0.60	0.59
t_{zd}	0.38	0.38	0.45	0.45	0.52	0.52	0.58	0.58
t_{od}	0.54	0.54	0.61	0.60	0.67	0.67	0.74	0.73
Power (µW/MHz)								
Power_read	44.19	55.30	74.14	96.59	103.00	140.58	130.78	187.28
Power_write	65.56	73.87	130.03	151.84	216.72	258.82	325.63	394.81
Power_standby	6.27	10.79	10.49	18.67	14.73	27.69	18.98	37.84
Area (µm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=16** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**1024**	**2048**	**2048**	**4096**	**3072**	**6144**	**4096**	**8192**
bpw	**8**	**8**	**16**	**16**	**24**	**24**	**32**	**32**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	5.93	6.12	6.48	6.73	7.03	7.35	7.58	7.97
t_{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{cas}	6.22	6.42	6.77	7.04	7.32	7.65	7.87	8.27
t_{ah}	2.37	2.38	2.90	2.92	3.42	3.45	3.95	3.99
t_{wh}	6.22	6.42	6.77	7.04	7.32	7.65	7.87	8.27
t_{ds}	0.21	0.35	0.30	0.52	0.31	0.61	0.25	0.63
t_{dh}	0.79	0.64	0.91	0.72	1.04	0.79	1.17	0.86
t_{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{ch}	2.04	2.26	2.14	2.44	2.25	2.62	2.36	2.80
t_{wen}	4.23	4.55	4.71	5.14	5.19	5.72	5.68	6.31
t_{acc}	5.93	6.12	6.48	6.73	7.03	7.35	7.58	7.97
t_{da}	1.40	1.40	1.40	1.40	1.40	1.40	1.40	1.40
t_{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{wacc}	1.74	1.96	1.85	2.14	1.95	2.32	2.06	2.50
t_{dz}	0.38	0.38	0.43	0.43	0.48	0.48	0.53	0.53
t_{zd}	0.36	0.36	0.41	0.41	0.46	0.46	0.52	0.52
t_{od}	0.52	0.52	0.57	0.57	0.62	0.62	0.67	0.67
Power (µW/MHz)								
Power_read	34.31	44.16	54.36	72.28	73.53	101.34	91.81	131.35
Power_write	47.88	54.83	83.70	99.21	130.96	158.44	189.65	232.52
Power_standby	5.43	9.90	8.70	16.10	12.14	22.88	15.51	30.24
Area (µm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=32** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**2048**	**4096**	**4096**	**8192**	**6144**	**12288**	**8192**	**16384**
bpw	**4**	**4**	**8**	**8**	**12**	**12**	**16**	**16**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.05	6.31	6.59	6.91	7.12	7.52	7.66	8.12
t_{as}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{cas}	6.35	6.62	6.89	7.22	7.42	7.82	7.96	8.42
t_{ah}	2.35	2.37	2.89	2.92	3.42	3.46	3.95	3.99
t_{wh}	6.35	6.62	6.89	7.22	7.42	7.82	7.96	8.42
t_{ds}	0.13	0.45	0.24	0.62	0.28	0.75	0.24	0.85
t_{dh}	0.65	0.39	0.78	0.46	0.91	0.52	1.04	0.58
t_{cs}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{ch}	2.13	2.43	2.24	2.44	2.34	2.78	2.45	2.96
t_{wen}	4.40	4.84	4.87	5.42	5.35	6.00	5.82	6.58
t_{acc}	6.05	6.31	6.59	6.91	7.12	7.52	7.66	8.12
t_{da}	1.40	1.40	1.40	1.40	1.40	1.40	1.40	1.40
t_{wda}	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
t_{wacc}	1.83	2.12	1.94	2.30	2.04	2.48	2.15	2.65
t_{dz}	0.35	0.35	0.42	0.42	0.47	0.47	0.50	0.50
t_{zd}	0.33	0.33	0.41	0.41	0.46	0.46	0.49	0.49
t_{od}	0.49	0.49	0.56	0.56	0.62	0.62	0.65	0.65
Power (µW/MHz)								
Power_read	28.17	37.11	43.53	58.99	58.48	81.37	73.04	104.24
Power_write	38.20	46.23	60.54	74.81	88.54	110.81	122.22	154.21
Power_standby	5.20	10.38	8.16	15.92	11.13	21.75	14.10	27.87
Area (µm)								
Width	831.84	831.84	1437.28	1437.28	2042.72	2042.72	2648.17	2648.17
Height	529.32	1017.68	853.16	1665.36	1177.00	2313.04	1500.84	2960.72

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle



(WEN = high, CSN = low, OEN = low, DI = don't care)

Read Cycle with CSN-Controlled



(OEN = low, WEN = high, DI = don't care)

Basic Write Cycle



(CSN = low, OEN = don't care)

Write Cycle with CSN Controlled



Read-Modified-Write Cycle



NOTES:

1. When the wen hold time after the last address bit transition is satisfied, D+ will toggle in response to a successful read of the initial contents of address A1. When the wen hold time after the last address bit transition is not satisfied, D+ will go to unknown state.
2. Address bits are not allowed to change while WEN is low. If they do change, then the data for one or more addresses in the memory array may be corrupted.

OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



NOTES:
1. Words (w) is the number of words in DROM_LP.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. Banks (ba) is the number of banks.
5. m = $\lceil \log_2 w \rceil$

Features

- Suitable for low-power applications
- Diffusion-programmable code available
- Synchronous operation
- Asynchronous tri-state output
- Latched inputs and outputs
- Automatic power-down mode available
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

DROM_LP is a synchronous diffusion programmable ROM which is provided as a compiler. DROM_LP is intended for use in low-power applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] is disabled and DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

DROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

Parameter Description

DROM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b) and Column mux(y) and Number of banks(ba).

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A [ ]	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT [ ]	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance

(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	4.581	5.336	3.799	5.623	8.015
ba = 2	4.392	4.322	3.050	4.512	8.189

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

DROM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from DROM_LP compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
   In chip-level layout, over-the-cell routing in DROM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of DROM_LP.
4. Power reduction during standby mode.
   The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Characteristics

Definition for AC Timing (ns)			
Symbol	**Description**	**Symbol**	**Description**
t_{cyc}	Clock cycle time	t_{ch}	CSN hold time from CK rise
t_{ckl}	Clock pulse width low	t_{acc}	Data access time
t_{ckh}	Clock pulse width high	t_{da}	De-access time
t_{as}	Address setup time	t_{dz}	DOUT drive to high-Z time
t_{ah}	Address hold time	t_{zd}	DOUT high-Z to drive time
t_{cs}	CSN setup time	t_{od}	OEN to Valid Output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

*** For Ymux=8** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**512**	**1024**	**1024**	**2048**	**1536**	**3072**	**2048**	**4096**
bpw	**32**	**32**	**64**	**64**	**96**	**96**	**128**	**128**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.61	6.88	8.33	8.64	10.38	10.73	12.75	13.15
t_{ckl}	2.77	2.77	3.29	3.29	3.79	3.79	4.26	4.26
t_{ckh}	3.06	3.34	3.74	4.05	4.46	4.81	5.22	5.62
t_{as}	0.10	1.81	0.10	1.86	0.10	1.90	0.10	1.95
t_{ah}	0.94	1.21	0.94	1.25	0.94	1.29	0.94	1.33
t_{cs}	1.19	1.71	1.19	1.76	1.19	1.80	1.19	1.85
t_{ch}	0.84	1.11	0.84	1.15	0.84	1.19	0.84	1.23
t_{acc}	4.88	5.26	5.43	5.86	6.18	6.67	7.13	7.68
t_{da}	4.08	4.37	4.87	5.21	5.72	6.10	6.62	7.04
t_{dz}	0.90	0.89	1.02	1.02	1.14	1.13	1.26	1.24
t_{zd}	1.08	1.06	1.19	1.17	1.29	1.27	1.39	1.37
t_{od}	1.20	1.18	1.31	1.29	1.42	1.40	1.52	1.50
Power (µW/MHz)								
Power_read	83.64	87.72	188.40	198.14	322.93	340.02	487.24	513.36
Power_standby	0.43	2.31	0.48	2.71	0.53	3.10	0.57	3.49
Area (µm)								
Width	511.53	511.53	883.93	883.93	1256.06	1256.06	1627.93	1627.93
Height	214.62	405.22	295.26	566.50	375.90	727.78	456.54	889.06

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

DROM_LP

Low-Power Synchronous Diffusion Programmable ROM

Reference Table

*** For Ymux=16** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**1024**	**2048**	**2048**	**4096**	**3072**	**6144**	**4096**	**8192**
bpw	**16**	**16**	**32**	**32**	**48**	**48**	**64**	**64**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.61	6.89	8.33	8.64	10.37	10.73	12.75	13.15
t_{ckl}	2.77	2.77	3.29	3.29	3.79	3.79	4.26	4.26
t_{ckh}	3.06	3.34	3.74	4.05	4.46	4.81	5.22	5.62
t_{as}	0.10	1.81	0.10	1.86	0.10	1.90	0.10	1.95
t_{ah}	0.94	1.21	0.94	1.25	0.94	1.29	0.94	1.33
t_{cs}	1.19	1.71	1.19	1.76	1.19	1.80	1.19	1.85
t_{ch}	0.84	1.11	0.84	1.15	0.84	1.19	0.84	1.23
t_{acc}	4.95	5.37	5.49	5.97	6.23	6.77	7.19	7.78
t_{da}	4.09	4.38	4.88	5.22	5.73	6.12	6.63	7.06
t_{dz}	0.86	0.85	0.95	0.94	1.03	1.02	1.12	1.10
t_{zd}	1.04	1.02	1.12	1.10	1.19	1.18	1.27	1.25
t_{od}	1.17	1.15	1.24	1.23	1.32	1.31	1.40	1.38
Power (µW/MHz)								
Power_read	59.28	63.60	125.92	134.31	207.91	221.25	305.28	324.42
Power_standby	0.43	2.30	0.47	2.69	0.51	3.08	0.54	3.47
Area (µm)								
Width	511.24	511.24	883.86	883.86	1256.06	1256.06	1627.86	1627.86
Height	214.62	405.22	295.26	566.50	375.90	727.78	456.54	889.06

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=32** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**2048**	**4096**	**4096**	**8192**	**6144**	**12288**	**8192**	**16384**
bpw	**8**	**8**	**16**	**16**	**24**	**24**	**32**	**32**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	6.63	6.90	8.32	8.64	10.37	10.73	12.75	13.15
t_{ckl}	2.77	2.77	3.29	3.29	3.79	3.78	4.26	4.25
t_{ckh}	3.07	3.34	3.74	4.06	4.46	4.82	5.22	5.62
t_{as}	0.10	1.81	0.10	1.86	0.10	1.90	0.10	1.95
t_{ah}	0.94	1.21	0.94	1.25	0.94	1.29	0.93	1.33
t_{cs}	1.19	1.71	1.19	1.76	1.19	1.80	1.19	1.85
t_{ch}	0.84	1.11	0.84	1.15	0.84	1.19	0.84	1.23
t_{acc}	5.07	5.56	5.59	6.14	6.33	6.94	7.29	7.96
t_{da}	4.11	4.42	4.90	5.25	5.75	6.14	6.65	7.08
t_{dz}	0.84	0.83	0.91	0.90	0.98	0.96	1.04	1.03
t_{zd}	1.02	1.00	1.08	1.07	1.14	1.13	1.20	1.19
t_{od}	1.15	1.13	1.21	1.19	1.27	1.25	1.33	1.31
Power (µW/MHz)								
Power_read	47.53	51.47	95.27	102.51	151.15	162.15	215.17	230.40
Power_standby	0.42	2.32	0.46	2.74	0.50	3.18	0.53	3.63
Area (µm)								
Width	510.65	510.65	883.69	883.69	1256.06	1256.06	1627.76	1627.76
Height	214.62	405.22	295.26	566.50	375.90	727.78	456.54	889.06

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode.

Logic Symbol



NOTES:

1. Words (w) is the number of words in MROM_LP.
2. Bpw (b) is the number of bits per word.
3. Ymux (y) is one of the column mux types.
4. Banks (ba) is the number of banks.
5. m = $\lceil \log_2 w \rceil$

Features

- Suitable for low-power applications
- Metal-2 programmable code available
- Synchronous operation
- Asynchronous tri-state output
- Latched inputs and outputs
- Automatic power-down mode
- Low noise output optimization
- Zero standby current
- Flexible aspect ratio
- Dual-bank scheme available
- Up to 512Kbits capacity
- Up to 16K number of words
- Up to 128 number of bits per word

Function Description

MROM_LP is a synchronous diffusion programmable ROM which is provided as a compiler. MROM_LP is intended for use in low-power applications. The read cycle is initiated at the rising edge of CK. The data at DOUT[] become valid after a delay. While in standby mode that CSN is high, A[] is disabled and DOUT[] remains stable. When OEN is high, DOUT is placed in a high-impedance state.

MROM Function Table

CK	CSN	OEN	A	DOUT	Comment
X	X	H	X	Z	Unconditional tri-state output
X	H	L	X	DOUT(t-1)	De-selected (standby mode)
↑	L	L	Valid	MEM(A)	Read cycle

MROM_LP

Low-Power Synchronous Metal Programmable ROM

Parameter Description

MROM_LP is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters; Number of words(w), Number of bits per word(b), Column mux(y) and Number of banks(ba).

Parameters			Ymux = 8	Ymux = 16	Ymux = 32
Words (w)	ba = 1	Min	64	128	256
		Max	2048	4096	8192
		Step	32	64	128
	ba = 2	Min	128	256	512
		Max	4096	8192	16384
		Step	64	128	256
Bpw (b)		Min	2	2	2
		Max	128	64	32
		Step	1	1	1

Pin Descriptions

Name	I/O	Description
CK	Clock	Clock input. CSN and A[] are latched into the ROM on the rising edge of CK. If CSN is low on the rising edge of CK, the ROM is in read mode.
CSN	Chip Enable	Chip enable input. The chip enable is active-low and is latched into the ROM on the rising edge of CK. When CSN is low, the ROM is enabled for reading. When CSN is high, the ROM goes to the standby mode and is disabled for reading. DOUT remains previous data output.
OEN	Data Output Enable	Data output enable input. The data output enable is asynchronously operated regardless of any inputs. When OEN is high, DOUT is disabled and goes to high-impedance state.
A [ ]	Address	Address input bus. The address is latched into the ROM on the rising edge of CK.
DOUT [ ]	Data Output	Data output bus. Data output is valid after the rising edge of CK while the ROM is in read mode.

Pin Capacitance

(Unit = SL)

	CK	CSN	OEN	A	DOUT
ba = 1	4.346	4.741	3.257	7.865	8.308
ba = 2	5.190	5.288	3.405	4.614	8.463

NOTE: Each pin's capacitance is exactly same regardless of available mux types for same bank.

Block Diagrams

MROM_LP has 2 different physical architectures due to the word depth. For a specific configuration, only one of these architectures is generated from MROM_LP compiler. Power is consumed by the bank that is selected by the address whereas the other bank will be in idle mode.



Application Notes

1. Permitting over-the-cell routing
   In chip-level layout, over-the-cell routing in MROM_LP is permitted for only Metal-5 layer.
2. Incoming power bus should be adjusted to guarantee NOT more than 10% voltage drop at typical-case current levels.
3. Power stripe should be tapped from both sides of MROM_LP.
4. Power reduction during standby mode.
   The standby power is measured on the condition that only CSN is in disable mode and other signals are in operation mode. If any of signals are activated while in standby mode, the power will be consumed because the input switching activities are occurred by the signal transition. Therefore, to reduce unnecessary power consumption, you should keep stable for all signals while standby mode.

Characteristics

Definition for AC Timing (ns)			
Symbol	**Description**	**Symbol**	**Description**
t_{cyc}	Clock cycle time	t_{ch}	CSN hold time from CK rise
t_{ckl}	Clock pulse width low	t_{acc}	Data access time
t_{ckh}	Clock pulse width high	t_{da}	De-access time
t_{as}	Address setup time	t_{dz}	DOUT drive to high-Z time
t_{ah}	Address hold time	t_{zd}	DOUT high-Z to drive time
t_{cs}	CSN setup time	t_{od}	OEN to valid output
Definition for Power Consumption (μW/MHz)			
Power_read	The dynamic average power consumption while in a read cycle		
Power_standby	The standby power consumption while CSN is high		
Definition for Area (μm)			
Width	The physical width in X-direction		
Height	The physical height in Y-direction		

Reference Table

*** For Ymux=8** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**512**	**1024**	**1024**	**2048**	**1536**	**3072**	**2048**	**4096**
bpw	**32**	**32**	**64**	**64**	**96**	**96**	**128**	**128**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	7.73	8.05	11.16	11.55	14.87	15.33	18.85	19.39
t_{ckl}	2.92	2.92	3.60	3.60	4.22	4.22	4.77	4.77
t_{ckh}	3.32	3.64	4.26	4.65	5.27	5.73	6.35	6.89
t_{as}	0.10	1.83	0.10	1.93	0.10	2.02	0.10	2.12
t_{ah}	0.88	1.19	0.88	1.27	0.89	1.35	0.89	1.42
t_{cs}	1.16	1.73	1.16	1.83	1.16	1.92	1.16	2.02
t_{ch}	0.79	1.11	0.79	1.18	0.79	1.26	0.79	1.33
t_{acc}	5.04	5.46	5.95	6.46	7.07	7.68	8.41	9.11
t_{da}	4.38	4.71	5.49	5.91	6.69	7.19	7.97	8.55
t_{dz}	0.86	0.87	0.99	0.99	1.10	1.11	1.21	1.22
t_{zd}	1.03	1.04	1.15	1.15	1.25	1.26	1.35	1.36
t_{od}	1.16	1.17	1.27	1.28	1.38	1.39	1.49	1.49
Power (µW/MHz)								
Power_read	100.05	105.37	242.79	254.13	438.00	457.13	685.69	714.37
Power_standby	0.43	2.61	0.49	3.32	0.53	4.04	0.58	4.75
Area (µm)								
Width	484.49	484.49	876.09	876.09	1267.42	1267.42	1658.49	1658.49
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

MROM_LP

Low-Power Synchronous Metal Programmable ROM

Reference Table

*** For Ymux=16** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**1024**	**2048**	**2048**	**4096**	**3072**	**6144**	**4096**	**8192**
bpw	**16**	**16**	**32**	**32**	**48**	**48**	**64**	**64**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	7.74	8.05	11.16	11.55	14.86	15.33	18.85	19.39
t_{ckl}	2.93	2.93	3.60	3.60	4.22	4.22	4.77	4.77
t_{ckh}	3.32	3.64	4.26	4.65	5.27	5.73	6.36	6.89
t_{as}	0.10	1.83	0.10	1.93	0.10	2.02	0.10	2.12
t_{ah}	0.88	1.19	0.89	1.27	0.89	1.35	0.89	1.42
t_{cs}	1.16	1.73	1.16	1.83	1.16	1.92	1.16	2.02
t_{ch}	0.79	1.11	0.80	1.18	0.80	1.26	0.80	1.33
t_{acc}	5.11	5.57	6.00	6.56	7.13	7.77	8.47	9.21
t_{da}	4.39	4.73	5.51	5.93	6.71	7.21	7.99	8.57
t_{dz}	0.82	0.83	0.90	0.91	0.99	0.99	1.07	1.07
t_{zd}	0.99	1.01	1.07	1.08	1.15	1.16	1.22	1.22
t_{od}	1.12	1.13	1.20	1.21	1.28	1.28	1.35	1.35
Power (µW/MHz)								
Power_read	67.22	71.75	153.86	162.74	267.43	281.59	407.93	428.30
Power_standby	0.43	2.60	0.47	3.31	0.51	4.02	0.55	4.73
Area (µm)								
Width	484.20	484.20	876.02	876.02	1267.42	1267.42	1658.42	1658.42
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Reference Table

*** For Ymux=32** (Typical process, 2.5V, 25°C, Output load = 10SL, Input slope = 0.2 ns, SA=0.5)

Parameters								
words	**2048**	**4096**	**4096**	**8192**	**6144**	**12288**	**8192**	**16384**
bpw	**8**	**8**	**16**	**16**	**24**	**24**	**32**	**32**
ba	**1**	**2**	**1**	**2**	**1**	**2**	**1**	**2**
Timing (ns)								
t_{cyc}	7.75	8.07	11.16	11.55	14.86	15.32	18.86	19.39
t_{ckl}	2.93	2.93	3.60	3.60	4.22	4.22	4.78	4.78
t_{ckh}	3.33	3.64	4.26	4.65	5.27	5.73	6.36	6.89
t_{as}	0.10	1.83	0.10	1.93	0.10	2.02	0.10	2.12
t_{ah}	0.88	1.19	0.88	1.27	0.89	1.35	0.89	1.42
t_{cs}	1.16	1.73	1.16	1.83	1.16	1.92	1.16	2.02
t_{ch}	0.79	1.11	0.79	1.18	0.79	1.26	0.79	1.33
t_{acc}	5.22	5.76	6.11	6.74	7.23	7.96	8.57	9.40
t_{da}	4.41	4.76	5.53	5.95	6.73	7.22	8.01	8.58
t_{dz}	0.80	0.80	0.86	0.87	0.93	0.93	0.99	1.00
t_{zd}	0.98	0.98	1.04	1.04	1.10	1.10	1.15	1.16
t_{od}	1.10	1.11	1.17	1.17	1.23	1.23	1.28	1.29
Power (µW/MHz)								
Power_read	52.22	56.38	110.96	118.68	183.81	195.56	270.79	287.03
Power_standby	0.42	2.62	0.46	3.37	0.50	4.13	0.53	4.91
Area (µm)								
Width	483.61	483.61	875.85	875.85	1267.42	1267.42	1658.32	1658.32
Height	275.80	529.46	419.16	816.18	562.52	1102.90	705.88	1389.62

NOTE: Standby power is measured on the condition that other signals are in normal operation while CSN is in disable mode.

Timing Diagrams

Read Cycle



Read Cycle with CSN Controlled



OEN Controlled Output Enable



NOTE: "don't care" means the condition that these pins are in normal operation mode

COMPILED DATAPATH MACROCELLS

Datapath macro cell is a set of n-bit data operators that enables more efficient datapath module design and implementation. Compiled datapath macro cell creates area-, speed- and power-optimized adders, subtracters, barrel shifters, and multipliers based on the user specified parameters. It creates a function model, a timing information for simulation, and a verified hard macro layout.
The followings are the summary of main features of compiled datapath macro cells:

ADVANCED DESIGN TECHNIQUE

All of STDM110 compiled datapath macro cells adopt very advanced design techniques to get optimized performances on the given parameters. Some of those design techniques are as follows:

- Hierarchical double carry select scheme to reduce carry-chain delay
- Transmission gate multiplexing for data shifting
- Allowing pipeline insertion in multiplication
- Primitive standard cell compatible leaf cell layout
- Allowing over-the-cell routing
- Dense datapath module layout generation with topological regularity.

FLEXIBLE DATAPATH MACROCELL DESIGN FLOW

The implementation of datapath module is one of the most critical and important elements in the design of high performance systems; DSPs, multimedia, graphics, microprocessors and so on. In these systems, the datapath modules are used much more than other designs and at the same time, datapath module affects the overall design performances.
The macrocell generation flow is tightly integrated into Apollo, Avant! which is used as a main tool at a full chip layout step. By supporting an easy-to-use ASIC environment, achieving full custom-like density, performance, ASIC designers can expect improving productivity. In the design of datapath macro cell, the optimal module placement of leafcell is a key point to take advantage of inherent regularity in datapaths. An optimal datapath module placement can maximize density, minimize speed, bus line skew, power consumption and turn-around time in ASIC design.

The design environment has been developed to support datapath macro cells as shown in below. This flow is tightly integrated from Verilog, Cadence, to Apollo, Avant!. With the pre-defined leafcell information and given parameters, the schematic generator gives a Verilog structural netlist of datapath cell and the placement information of used leafcell instances. It enables the mapping of regularity from a logic design into a standard cell place-and-rout tool. You can get area- and performance-optimized layouts of datapath macro cells.



Figure 5-3 Datapath Instance Generatin Flow

COMPILED MACROCELL SELECTION GUIDE

Type	Macrocell	Description
Datapath	ADDER	Low-power/high-speed 4-to-64 bits addition/subtraction - Double-carry select algorithm - 2's complement overflow
	BS	Low-power/high-speed 4-to-64 bits barrel shifter - Bi-directional shift and rotation - Logical or arithmetic shift - External filler data is available
	MPY	Low-power/high-speed 6-to-64 bits modified Booth Multiplier - 2's complement multiplication - 1-stage pipeline insertion is available

Logic Symbol



Features

- Asynchronous operation
- 4 to 64 bit Adder/Subtracter
- High-speed / low-power operation
- 2’s complement or unsigned-magnitude operation
- 2’s complement overflow flag available
- Sophisticated carry-select and group-bypass scheme
- Two output drive-strengths available

Function Description

The ADDER is an *n*-bit carry-select adder and subtracter which is provided as a compiler. The ADDER is intended for use in high-speed and low power applications. It essentially adopts the double carry-select scheme which has hierarchically doubled carry-select groups of bits to allow the high-speed of addition/subtraction operation. And in addition, the inside of each group is designed by a partial group-bypass scheme so as to acquire more high-speed. It performs a 2’s complement addition/subtraction or unsigned-magnitude addition. The overflow flag shows the occurrence of overflow while adding two positive or two negative numbers and it should be ignored while doing unsigned-magnitude operations.

Function Table

output	Function
SOUT	AIN + BIN + CIN (addition)
	AIN + ~BIN + CIN (subtraction)
OVF	(~SOUT [bits–1]) • (AIN [bits–1] • BIN [bits–1]) + (SOUT [bits–1]) • (~AIN [bits–1]) •(~ BIN [bits–1])

Parameter Description

ADDER is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	Description	Range
bits	Number of bits for the input data bus	4 to 64
sub	0: addition only; 1: addition/subtraction	0/1
ovf	Overflow flag for signed operation	0/1
drv	output drive strength	1/2

ADDER

Adder/Subtracter

Pin Description

Name	Type	Description
AIN [ ]	Input	Augend in addition, Minuend in subtraction
BIN [ ]		Addend in addition, Subtrahend in subtraction
CIN		Carry-in in addition/subtraction It must be kept with the 'HIGH' state in 2's complement subtraction.
SUB		Addition/subtraction flag (optional when the parameter sub = 1)
SOUT[ ]	output	The result of addition/subtraction
COUT		Carry-out in addition/subtraction
OVF		The overflow/underflow of addition/subtraction (optional when the parameter ovf = 1)

Pin Capacitance [Unit: pF]

Name	Case	Value
AIN[ ]	all	0.0127
BIN[ ]	sub=0 sub=1	0.0137 0.0088
CIN	all	0.0176
SUB	sub=1	0.0107

Block Diagram



Timing Diagram



Timing Type Definition

Timing Type	Definition
tPHLas/tPLHas	Propagation delay from AIN[ ] to SOUT[ ]
tPHLbs/tPLHbs	Propagation delay from BIN[ ] to SOUT[ ]
ttPHLcs/tPLHcs	Propagation delay from CIN to SOUT [ ]
tPHLss/tPLHss	Propagation delay from SUB to SOUT [ ]
tPHLac/tPLHac	Propagation delay from AIN[ ] to COUT
tPHLbc/tPLHbc	Propagation delay from BIN[ ] to COUT
tPHLcc/tPLHcc	Propagation delay from CIN to COUT
tPHLsc/tPLHsc	Propagation delay from SUB to COUT
tPHLao/tPLHao	Propagation delay from AIN[ ] to OVF
tPHLbo/tPLHbo	Propagation delay from BIN[ ] to OVF
tPHLco/tPLHco	Propagation delay from CIN to OVF
tPHLso/tPLHso	Propagation delay from SUB to OVF
tPDAas	De-access time from AIN[ ] to SOUT[ ]
tPDAbs	De-access time from BIN[ ] to SOUT[ ]
tPDAcs	De-access time from CIN to SOUT[ ]
tPDAss	De-access time from SUB to SOUT[ ]

ADDER

Adder/Subtracter

Characteristic Reference Table

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of Bits	-	S	Input Slope	ns
V_{DD}	Power Supply Voltage	V	SL	Standard Load	-
C_L	Output Load	SL	SA	Input Switching Activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	8		24		36		48		64	
Case: sub=0, ovf=1, drv=1										
tPHLac/tPLHac	0.94	1.00	1.29	1.42	1.51	1.63	1.68	1.75	1.84	1.79
tPHLbc/tPLHbc	0.92	0.99	1.27	1.39	1.48	1.60	1.65	1.73	1.82	1.77
tPHLcc/tPLHcc	0.36	0.36	0.59	0.54	0.76	0.68	0.94	0.82	1.17	1.01
tPHLao/tPLHao	1.13	1.08	1.55	1.53	1.77	1.74	1.90	1.86	1.94	1.86
tPHLbo/tPLHbo	1.11	1.06	1.53	1.50	1.75	1.72	1.87	1.84	1.92	1.84
tPHLco/tPLHco	0.46	0.51	0.70	0.83	0.85	1.00	0.98	1.12	1.12	1.19
tPHLas/tPLHas	1.18	1.07	1.61	1.50	1.82	1.71	1.95	1.82	1.98	1.82
tPHLbs/tPLHbs	1.17	1.05	1.58	1.48	1.79	1.69	1.92	1.80	1.96	1.79
tPHLcs/tPLHcs	0.51	0.47	0.75	0.80	0.90	0.97	1.03	1.09	1.16	1.15
tPDAas	0.41		0.41		0.41		0.41		0.41	
tPDAbs	0.39		0.39		0.39		0.39		0.39	
tPDAcs	0.28		0.28		0.28		0.28		0.28	
Case: sub=1, ovf=1, drv=1										
tPHLac/tPLHac	0.98	0.94	1.23	1.38	1.41	1.60	1.59	1.72	1.84	1.75
tPHLbc/tPLHbc	1.14	1.06	1.48	1.51	1.70	1.73	1.87	1.85	2.03	1.87
tPHLcc/tPLHcc	0.36	0.36	0.59	0.54	0.76	0.68	0.94	0.82	1.17	1.00
tPHLsc/tPLHsc	0.87	1.09	0.87	1.52	0.86	1.74	0.86	1.86	0.86	1.89
tPHLao/tPLHao	1.06	1.08	1.51	1.48	1.74	1.68	1.87	1.80	1.89	1.81
tPHLbo/tPLHbo	1.19	1.28	1.65	1.72	1.87	1.93	2.00	2.05	2.02	2.05
tPHLco/tPLHco	0.46	0.51	0.70	0.83	0.85	1.01	0.98	1.12	1.12	1.19
tPHLso/tPLHso	0.95	1.24	0.97	1.69	0.98	1.92	1.00	2.06	1.02	2.09
tPHLas/tPLHas	1.12	1.07	1.57	1.46	1.79	1.65	1.92	1.76	1.94	1.77
tPHLbs/tPLHbs	1.25	1.27	1.70	1.69	1.92	1.90	2.05	2.01	2.06	2.00
tPHLcs/tPLHcs	0.51	0.48	0.75	0.80	0.90	0.97	1.03	1.09	1.16	1.15
tPHLss/tPLHss	1.26	1.21	1.74	1.66	1.98	1.89	2.12	2.03	2.14	2.08
tPDAas	0.37		0.37		0.37		0.37		0.37	
tPDAbs	0.51		0.51		0.51		0.51		0.51	
tPDAcs	0.28		0.28		0.28		0.28		0.28	
tPDAss	0.62		0.62		0.61		0.61		0.61	

2) Power Characteristics [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Case			8	24	36	48	64
sub=0	ovf=0	drv=1	6.83	20.40	30.58	40.76	54.33
		drv=2	7.18	22.27	33.59	44.91	60.00
	ovf=1	drv=1	6.99	20.56	30.73	40.91	54.48
		drv=2	7.35	22.46	33.79	45.12	60.23
sub=1	ovf=0	drv=1	9.10	26.55	39.64	52.73	70.18
		drv=2	10.61	29.59	43.83	58.07	77.05
	ovf=1	drv=1	9.24	26.68	39.76	52.83	70.27
		drv=2	10.80	29.78	44.02	58.26	77.24

3) Size Characteristics [Unit: μm]

Type	Case	8	24	36	48	64
Width	sub=0 ovf=0	45.92	49.75	51.04	50.96	48.76
	sub=0 ovf=1	47.26	49.85	50.73	50.68	49.20
	sub=1 ovf=0	52.92	56.75	58.04	57.96	55.76
	sub=1 ovf=1	54.26	56.85	57.73	57.68	56.20
Height	all	88.00	264.00	396.00	528.00	704.00

ADDER

Adder/Subtracter

Characteristic Equation Table

1) Timing Equations [Unit: ns]

Case=ovf0sub0 (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLac	all	(2.18e-01*S+9.63e-01*SL*5.37e-03+2.71e-02*B+6.26e-01+(-1.54e-04)*B*B)
tPHLbc	drv=1	(2.00e-01*S+9.64e-01*SL*5.37e-03+2.67e-02*B+6.13e-01+(-1.50e-04)*B*B)
	drv=2	(2.00e-01*S+9.66e-01*SL*5.37e-03+2.67e-02*B+6.12e-01+(-1.49e-04)*B*B)
tPHLcc	drv=1	(1.59e-01*S+9.63e-01*SL*5.37e-03+1.44e-02*B+1.47e-01+3.76e-04*S*B)
	drv=2	(1.59e-01*S+9.62e-01*SL*5.37e-03+1.44e-02*B+1.45e-01+3.79e-04*S*B)
tPHLas	drv=1	((-1.34e-01)*S+2.00*SL*5.37e-03+3.68e-02*B+7.86e-01+(-3.14e-04)*B*B)
	drv=2	((-1.35e-01)*S+1.04*SL*5.37e-03+3.65e-02*B+8.10e-01+(-3.10e-04)*B*B)
tPHLbs	drv=1	((-1.21e-01)*S+2.00*SL*5.37e-03+3.56e-02*B+7.79e-01+(-3.00e-04)*B*B)
	drv=2	((-1.20e-01)*S+1.03*SL*5.37e-03+3.56e-02*B+7.99e-01+(-2.99e-04)*B*B)
tPHLcs	drv=1	(1.51e-02*S+2.00*SL*5.37e-03+1.79e-02*B+2.16e-01+(-8.76e-05)*B*B)
	drv=2	(1.43e-02*S+1.04*SL*5.37e-03+1.21e-02*B+3.06e-01+(-1.94e-04)*SL*5.37e-03*B)
tPLHac	all	((-1.34e-01)*S+1.24*SL*5.37e-03+3.65e-02*B+6.81e-01+(-3.17e-04)*B*B)
tPLHbc	drv=1	((-1.21e-01)*S+1.24*SL*5.37e-03+3.53e-02*B+6.75e-01+(-3.03e-04)*B*B)
	drv=2	((-1.20e-01)*S+1.23*SL*5.37e-03+3.53e-02*B+6.73e-01+(-3.03e-04)*B*B)
tPLHcc	all	(1.47e-02*S+1.24*SL*5.37e-03+1.91e-02*B+9.55e-02+(-1.11e-04)*B*B)
tPLHas	drv=1	(2.18e-01*S+1.96*SL*5.37e-03+3.82e-02*B+5.95e-01+(-3.41e-04)*B*B)
	drv=2	(2.18e-01*S+9.63e-01*SL*5.37e-03+3.80e-02*B+6.16e-01+(-3.37e-04)*B*B)
tPLHbs	drv=1	(2.00e-01*S+1.96*SL*5.37e-03+3.78e-02*B+5.83e-01+(-3.37e-04)*B*B)
	drv=2	(1.99e-01*S+9.65e-01*SL*5.37e-03+3.75e-02*B+6.03e-01+(-3.31e-04)*B*B)
tPLHcs	drv=1	(1.70e-01*S+1.96*SL*5.37e-03+2.64e-02*B+1.05e-01+(-1.97e-04)*B*B)
	drv=2	(1.70e-01*S+9.63e-01*SL*5.37e-03+2.59e-02*B+1.26e-01+(-1.90e-04)*B*B)
tPDAas	all	((-1.44e-01)*S+2.00*SL*5.37e-03+2.08e-06*B+3.35e-01)
tPDAbs	all	((-1.31e-01)*S+2.00*SL*5.37e-03+(-1.21e-05)*B+3.11e-01)
tPDAcs	drv=1	((-1.17e-02)*S+2.03*SL*5.37e-03+(-1.09e-04)*B+1.73e-01+1.14e-06*B*B)
	drv=2	((-8.15e-03)*S+1.04*SL*5.37e-03+(-1.56e-04)*B+2.10e-01+1.70e-06*B*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=ovf0sub1 (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLac	all	(2.53e-01*S+9.09e-01*SL*5.37e-03+1.51e-02*B+7.53e-01+1.65e-03*SL*5.37e-03*B)
tPHLbc	drv=1	(2.36e-01*S+9.64e-01*SL*5.37e-03+2.66e-02*B+8.24e-01+(-1.50e-04)*B*B)
	drv=2	(2.37e-01*S+9.65e-01*SL*5.37e-03+2.66e-02*B+8.21e-01+(-1.50e-04)*B*B)
tPHLcc	drv=1	(1.60e-01*S+9.61e-01*SL*5.37e-03+1.44e-02*B+1.47e-01+3.50e-04*S*B)
	drv=2	(1.60e-01*S+9.62e-01*SL*5.37e-03+1.44e-02*B+1.45e-01+3.64e-04*S*B)
tPHLsc	drv=1	(1.02e-01*S+9.01e-01*SL*5.37e-03+(-4.40e-04)*B+7.95e-01+(-2.56e-03)*S*SL*5.37e-03+5.39e-06*S*B+2.02e-03*SL*5.37e-03*B)
	drv=2	(1.01e-01*S+9.02e-01*SL*5.37e-03+(-4.43e-04)*B+8.03e-01+1.98e-03*SL*5.37e-03*B)
tPHLas	drv=1	((-4.02e-02)*S+2.00*SL*5.37e-03+3.95e-02*B+6.80e-01+(-3.46e-04)*B*B)
	drv=2	((-4.09e-02)*S+1.04*SL*5.37e-03+3.93e-02*B+7.04e-01+(-3.42e-04)*B*B)
tPHLbs	drv=1	((-8.91e-02)*S+2.00*SL*5.37e-03+3.93e-02*B+8.23e-01+(-3.45e-04)*B*B)
	drv=2	((-8.98e-02)*S+1.04*SL*5.37e-03+3.91e-02*B+8.47e-01+(-3.42e-04)*B*B)
tPHLcs	drv=1	(1.52e-02*S+2.00*SL*5.37e-03+1.79e-02*B+2.16e-01+(-8.77e-05)*B*B)
	drv=2	(1.05e-02*S+1.04*SL*5.37e-03+1.19e-02*B+3.09e-01+7.45e-04*S*SL*5.37e-03+1.12e-04*S*B+(-1.75e-04)*SL*5.37e-03*B)
tPHLss	drv=1	((-4.80e-02)*S+1.88*SL*5.37e-03+4.14e-02*B+8.17e-01+(-3.57e-04)*B*B)
	drv=2	((-1.85e-02)*S+9.89e-01*SL*5.37e-03+4.25e-02*B+7.96e-01+(-3.71e-04)*B*B)
tPLHac	all	((-4.00e-02)*S+1.24*SL*5.37e-03+3.91e-02*B+5.79e-01+(-3.49e-04)*B*B)
tPLHbc	all	((-8.89e-02)*S+1.24*SL*5.37e-03+3.91e-02*B+7.17e-01+(-3.48e-04)*B*B)
tPLHcc	all	(1.48e-02*S+1.23*SL*5.37e-03+1.90e-02*B+9.72e-02+(-1.11e-04)*B*B)
tPLHsc	all	((-4.30e-03)*S+1.24*SL*5.37e-03+3.83e-02*B+7.26e-01+(-3.39e-04)*B*B)
tPLHas	drv=1	(2.53e-01*S+1.96*SL*5.37e-03+3.41e-02*B+6.16e-01+(-2.97e-04)*B*B)
	drv=2	(2.52e-01*S+9.63e-01*SL*5.37e-03+3.39e-02*B+6.38e-01+(-2.92e-04)*B*B)
tPLHbs	drv=1	(2.36e-01*S+1.96*SL*5.37e-03+3.77e-02*B+7.93e-01+(-3.36e-04)*B*B)
	drv=2	(2.37e-01*S+9.65e-01*SL*5.37e-03+3.74e-02*B+8.13e-01+(-3.31e-04)*B*B)
tPLHcs	drv=1	(1.70e-01*S+1.96*SL*5.37e-03+2.63e-02*B+1.06e-01+(-1.97e-04)*B*B)
	drv=2	(1.70e-01*S+9.63e-01*SL*5.37e-03+2.60e-02*B+1.26e-01+(-1.91e-04)*B*B)
tPLHss	drv=1	((-3.63e-03)*S+1.97*SL*5.37e-03+3.88e-02*B+7.67e-01+(-3.24e-04)*B*B)
	drv=2	((-3.73e-03)*S+9.68e-01*SL*5.37e-03+3.89e-02*B+7.85e-01+(-3.25e-04)*B*B)
tPDAas	all	((-7.05e-02)*S+2.00*SL*5.37e-03+(-5.14e-06)*B+2.73e-01)
tPDAbs	all	((-8.79e-02)*S+2.00*SL*5.37e-03+(-1.62e-05)*B+4.19e-01)
tPDAcs	drv=1	((-1.26e-02)*S+2.03*SL*5.37e-03+(-1.48e-04)*B+1.74e-01+1.57e-06*B*B)
	drv=2	((-8.08e-03)*S+1.04*SL*5.37e-03+(-1.58e-04)*B+2.10e-01+1.73e-06*B*B)
tPDAss	drv=1	((-3.97e-02)*S+1.23*SL*5.37e-03+(-2.86e-03)*B+5.94e-01+(-2.29e-01)*S*SL*5.37e-03+4.06e-03*S*B+1.96e-02*SL*5.37e-03*B)
	drv=2	(1.28e-02*S+7.38e-01*SL*5.37e-03+(-1.16e-03)*B+5.63e-01+(-7.78e-02)*S*SL*5.37e-03+2.44e-03*S*B+8.05e-03*SL*5.37e-03*B)

1) Timing Equations [Unit: ns] (Cont.)

Case=ovf1sub0 (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLac	drv=1	(2.18e-01*S+9.54e-01*SL*5.37e-03+2.67e-02*B+6.41e-01+(-1.48e-04)*B*B)
	drv=2	(2.18e-01*S+9.52e-01*SL*5.37e-03+2.68e-02*B+6.41e-01+(-1.47e-04)*B*B)
tPHLbc	all	(2.00e-01*S+9.54e-01*SL*5.37e-03+2.63e-02*B+6.28e-01+(-1.43e-04)*B*B)
tPHLcc	all	(1.59e-01*S+9.55e-01*SL*5.37e-03+1.45e-02*B+1.55e-01+3.82e-04*S*B)
tPHLao	drv=1	((-1.34e-01)*S+1.85*SL*5.37e-03+3.67e-02*B+7.80e-01+(-3.09e-04)*B*B)
	drv=2	((-1.34e-01)*S+9.37e-01*SL*5.37e-03+3.65e-02*B+8.03e-01+(-3.05e-04)*B*B)
tPHLbo	drv=1	((-1.21e-01)*S+1.84*SL*5.37e-03+3.55e-02*B+7.74e-01+(-2.94e-04)*B*B)
	drv=2	((-1.20e-01)*S+9.37e-01*SL*5.37e-03+3.54e-02*B+7.95e-01+(-2.92e-04)*B*B)
tPHLco	drv=1	(1.52e-02*S+1.84*SL*5.37e-03+1.76e-02*B+2.19e-01+(-8.06e-05)*B*B)
	drv=2	(1.36e-02*S+9.35e-01*SL*5.37e-03+1.73e-02*B+2.43e-01+(-7.63e-05)*B*B)
tPHLas	drv=1	((-1.34e-01)*S+2.01*SL*5.37e-03+3.62e-02*B+8.34e-01+(-3.05e-04)*B*B)
	drv=2	((-1.35e-01)*S+1.05*SL*5.37e-03+3.60e-02*B+8.57e-01+(-3.03e-04)*B*B)
tPHLbs	drv=1	((-1.21e-01)*S+2.01*SL*5.37e-03+3.50e-02*B+8.26e-01+(-2.91e-04)*B*B)
	drv=2	((-1.20e-01)*S+1.05*SL*5.37e-03+3.51e-02*B+8.46e-01+(-2.92e-04)*B*B)
tPHLcs	drv=1	(1.50e-02*S+2.01*SL*5.37e-03+1.75e-02*B+2.61e-01+(-8.13e-05)*B*B)
	drv=2	(1.44e-02*S+1.04*SL*5.37e-03+1.73e-02*B+2.85e-01+(-7.81e-05)*B*B)
tPLHac	drv=1	((-1.34e-01)*S+1.22*SL*5.37e-03+3.54e-02*B+6.97e-01+(-2.96e-04)*B*B)
	drv=2	((-1.35e-01)*S+1.21*SL*5.37e-03+3.53e-02*B+6.97e-01+(-2.94e-04)*B*B)
tPLHbc	drv=1	((-1.21e-01)*S+1.22*SL*5.37e-03+3.43e-02*B+6.90e-01+(-2.81e-04)*B*B)
	drv=2	((-1.20e-01)*S+1.21*SL*5.37e-03+3.43e-02*B+6.87e-01+(-2.82e-04)*B*B)
tPLHcc	all	(1.47e-02*S+1.18*SL*5.37e-03+1.16e-02*B+1.96e-01+1.06e-03*SL*5.37e-03*B)
tPLHao	drv=1	(2.20e-01*S+2.54*SL*5.37e-03+3.88e-02*B+6.13e-01+(-3.46e-04)*B*B)
	drv=2	(2.19e-01*S+1.23*SL*5.37e-03+3.87e-02*B+6.34e-01+(-3.43e-04)*B*B)
tPLHbo	drv=1	(2.00e-01*S+2.54*SL*5.37e-03+3.84e-02*B+6.02e-01+(-3.42e-04)*B*B)
	drv=2	(2.00e-01*S+1.23*SL*5.37e-03+3.83e-02*B+6.23e-01+(-3.39e-04)*B*B)
tPLHco	drv=1	(1.70e-01*S+2.54*SL*5.37e-03+2.66e-02*B+1.35e-01+(-2.00e-04)*B*B)
	drv=2	(1.70e-01*S+1.23*SL*5.37e-03+2.65e-02*B+1.55e-01+(-1.97e-04)*B*B)
tPLHas	drv=1	(2.18e-01*S+1.98*SL*5.37e-03+3.80e-02*B+6.36e-01+(-3.42e-04)*B*B)
	drv=2	(2.18e-01*S+9.80e-01*SL*5.37e-03+3.77e-02*B+6.60e-01+(-3.36e-04)*B*B)
tPLHbs	drv=1	(2.00e-01*S+1.98*SL*5.37e-03+3.77e-02*B+6.23e-01+(-3.38e-04)*B*B)
	drv=2	(2.00e-01*S+9.83e-01*SL*5.37e-03+3.72e-02*B+6.47e-01+(-3.30e-04)*B*B)
tPLHcs	drv=1	(1.70e-01*S+1.98*SL*5.37e-03+2.68e-02*B+1.32e-01+(-2.06e-04)*B*B)
	drv=2	(1.69e-01*S+9.83e-01*SL*5.37e-03+2.66e-02*B+1.54e-01+(-2.01e-04)*B*B)
tPDAas	all	((-1.44e-01)*S+2.00*SL*5.37e-03+(-2.34e-06)*B+3.35e-01+(-8.99e-04)*S*SL*5.37e-03)
tPDAbs	all	((-1.31e-01)*S+2.00*SL*5.37e-03+(-1.38e-05)*B+3.11e-01)
tPDAcs	drv=1	((-1.19e-02)*S+2.03*SL*5.37e-03+(-3.11e-05)*B+1.72e-01)
	drv=2	((-8.20e-03)*S+1.04*SL*5.37e-03+(-1.49e-04)*B+2.10e-01+1.66e-06*B*B)

1) Timing Equations [Unit: ns] (Cont.)

Case=ovf1sub1 (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLac	all	(2.52e-01*S+8.99e-01*SL*5.37e-03+1.51e-02*B+7.64e-01+1.62e-03*SL*5.37e-03*B)
tPHLbc	drv=1	(2.36e-01*S+9.54e-01*SL*5.37e-03+2.63e-02*B+8.38e-01+(-1.45e-04)*B*B)
	drv=2	(2.37e-01*S+9.54e-01*SL*5.37e-03+2.63e-02*B+8.36e-01+(-1.44e-04)*B*B)
tPHLcc	drv=1	(1.59e-01*S+9.52e-01*SL*5.37e-03+1.45e-02*B+1.56e-01+3.59e-04*S*B)
	drv=2	(1.60e-01*S+9.53e-01*SL*5.37e-03+1.46e-02*B+1.54e-01+3.69e-04*S*B)
tPHLsc	drv=1	(1.01e-01*S+8.91e-01*SL*5.37e-03+(-3.35e-04)*B+8.05e-01+1.99e-03*SL*5.37e-03*B)
	drv=2	(1.00e-01*S+8.93e-01*SL*5.37e-03+(-2.98e-04)*B+8.12e-01+(-3.61e-04)*S*SL*5.37e-03+3.38e-05*S*B+1.88e-03*SL*5.37e-03*B)
tPHLao	drv=1	((-4.06e-02)*S+1.85*SL*5.37e-03+3.94e-02*B+6.74e-01+(-3.41e-04)*B*B)
	drv=2	((-4.02e-02)*S+9.38e-01*SL*5.37e-03+3.91e-02*B+6.97e-01+(-3.36e-04)*B*B)
tPHLbo	drv=1	((-8.93e-02)*S+1.85*SL*5.37e-03+3.92e-02*B+8.19e-01+(-3.40e-04)*B*B)
	drv=2	((-8.88e-02)*S+9.39e-01*SL*5.37e-03+3.91e-02*B+8.40e-01+(-3.37e-04)*B*B)
tPHLco	drv=1	(1.45e-02*S+1.84*SL*5.37e-03+1.76e-02*B+2.18e-01+(-8.06e-05)*B*B)
	drv=2	(1.41e-02*S+9.35e-01*SL*5.37e-03+1.74e-02*B+2.40e-01+(-7.71e-05)*B*B)
tPHLso	drv=1	(9.75e-02*S+1.80*SL*5.37e-03+1.14e-03*B+8.19e-01+(-2.42e-03)*S*SL*5.37e-03+2.62e-05*S*B+2.74e-03*SL*5.37e-03*B)
	drv=2	(9.85e-02*S+8.96e-01*SL*5.37e-03+8.59e-04*B+8.65e-01+(-4.56e-03)*S*SL*5.37e-03+7.22e-05*S*B+3.00e-03*SL*5.37e-03*B)
tPHLas	drv=1	((-4.05e-02)*S+2.01*SL*5.37e-03+3.89e-02*B+7.28e-01+(-3.37e-04)*B*B)
	drv=2	((-4.14e-02)*S+1.05*SL*5.37e-03+3.87e-02*B+7.51e-01+(-3.34e-04)*B*B)
tPHLbs	drv=1	((-8.90e-02)*S+2.01*SL*5.37e-03+3.88e-02*B+8.70e-01+(-3.37e-04)*B*B)
	drv=2	((-8.95e-02)*S+1.05*SL*5.37e-03+3.87e-02*B+8.93e-01+(-3.35e-04)*B*B)
tPHLcs	drv=1	(1.51e-02*S+2.01*SL*5.37e-03+1.76e-02*B+2.59e-01+(-8.18e-05)*B*B)
	drv=2	(1.46e-02*S+1.04*SL*5.37e-03+1.74e-02*B+2.82e-01+(-7.93e-05)*B*B)
tPHLss	drv=1	((-4.68e-02)*S+1.89*SL*5.37e-03+4.14e-02*B+8.54e-01+(-3.55e-04)*B*B)
	drv=2	((-1.76e-02)*S+1.00*SL*5.37e-03+4.23e-02*B+8.37e-01+(-3.67e-04)*B*B)
tPLHac	drv=1	((-4.03e-02)*S+1.22*SL*5.37e-03+3.81e-02*B+5.94e-01+(-3.28e-04)*B*B)
	drv=2	((-4.12e-02)*S+1.21*SL*5.37e-03+3.80e-02*B+5.94e-01+(-3.25e-04)*B*B)
tPLHbc	all	((-8.90e-02)*S+1.22*SL*5.37e-03+3.81e-02*B+7.33e-01+(-3.28e-04)*B*B)
tPLHcc	all	(1.47e-02*S+1.18*SL*5.37e-03+1.15e-02*B+1.96e-01+9.35e-04*SL*5.37e-03*B)
tPLHsc	drv=1	((-4.00e-03)*S+1.22*SL*5.37e-03+3.72e-02*B+7.45e-01+(-3.17e-04)*B*B)
	drv=2	((-3.94e-03)*S+1.22*SL*5.37e-03+3.71e-02*B+7.45e-01+(-3.15e-04)*B*B)
tPLHao	drv=1	(2.52e-01*S+2.54*SL*5.37e-03+3.48e-02*B+6.36e-01+(-3.04e-04)*B*B)
	drv=2	(2.52e-01*S+1.23*SL*5.37e-03+3.47e-02*B+6.57e-01+(-3.00e-04)*B*B)
tPLHbo	drv=1	(2.34e-01*S+2.54*SL*5.37e-03+3.83e-02*B+8.12e-01+(-3.42e-04)*B*B)
	drv=2	(2.36e-01*S+1.23*SL*5.37e-03+3.83e-02*B+8.28e-01+(-3.41e-04)*B*B)
tPLHco	drv=1	(1.69e-01*S+2.54*SL*5.37e-03+2.67e-02*B+1.34e-01+(-2.02e-04)*B*B)
	drv=2	(1.70e-01*S+1.23*SL*5.37e-03+2.65e-02*B+1.55e-01+(-1.97e-04)*B*B)
tPLHso	drv=1	((-4.79e-03)*S+2.55*SL*5.37e-03+3.89e-02*B+8.10e-01+(-3.28e-04)*B*B)
	drv=2	((-4.52e-03)*S+1.23*SL*5.37e-03+3.86e-02*B+8.32e-01+(-3.23e-04)*B*B)

1) Timing Equations [Unit: ns] (Cont.)

Case=ovf1sub1(Cont.) (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPLHas	drv=1	(2.52e-01*S+1.98*SL*5.37e-03+3.40e-02*B+6.57e-01+(-2.99e-04)*B*B)
	drv=2	(2.52e-01*S+9.82e-01*SL*5.37e-03+3.36e-02*B+6.80e-01+(-2.91e-04)*B*B)
tPLHbs	drv=1	(2.36e-01*S+1.98*SL*5.37e-03+3.76e-02*B+8.33e-01+(-3.39e-04)*B*B)
	drv=2	(2.37e-01*S+9.82e-01*SL*5.37e-03+3.72e-02*B+8.55e-01+(-3.32e-04)*B*B)
tPLHcs	drv=1	(1.70e-01*S+1.98*SL*5.37e-03+2.68e-02*B+1.34e-01+(-2.06e-04)*B*B)
	drv=2	(1.70e-01*S+9.83e-01*SL*5.37e-03+2.65e-02*B+1.56e-01+(-1.99e-04)*B*B)
tPLHss	drv=1	((-3.45e-03)*S+1.97*SL*5.37e-03+3.80e-02*B+8.18e-01+(-3.11e-04)*B*B)
	drv=2	((-3.56e-03)*S+9.68e-01*SL*5.37e-03+3.78e-02*B+8.41e-01+(-3.08e-04)*B*B)
tPDAas	all	((-6.96e-02)*S+2.00*SL*5.37e-03+(-1.02e-05)*B+2.73e-01)
tPDAbs	all	((-8.79e-02)*S+2.00*SL*5.37e-03+(-9.95e-06)*B+4.19e-01)
tPDAcs	drv=1	((-1.25e-02)*S+2.03*SL*5.37e-03+(-3.48e-05)*B+1.73e-01)
	drv=2	((-8.11e-03)*S+1.04*SL*5.37e-03+(-1.50e-04)*B+2.09e-01+1.66e-06*B*B)
tPDAss	drv=1	((-2.63e-03)*S+1.31*SL*5.37e-03+(-1.78e-03)*B+5.57e-01+(-1.15e-01)*S*SL*5.37e-03+2.89e-03*S*B+1.67e-02*SL*5.37e-03*B)
	drv=2	(8.32e-02*S+9.72e-01*SL*5.37e-03+1.59e-02*B+2.78e-01+(-1.91e-04)*B*B)

Characteristic Equation Tables (Cont.)

2) Power Equations [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Case	Case	Equation
ovf0sub0	drv=1	(2.74e-01*S+3.48*SL*5.37e-03+7.60e-01*B+(-1.81e-01)+(-1.73)*S*SL*5.37e-03 +(-3.41e-02)*S*B+1.78*SL*5.37e-03*B)
	drv=2	(8.17e-01*S+4.97*SL*5.37e-03+8.33e-01*B+(-7.59e-01)+(-3.59)*S*SL*5.37e-03 +(-2.16e-02)*S*B+2.14*SL*5.37e-03*B)
ovf0sub1	drv=1	((-6.90e-01)*S+(-3.05)*SL*5.37e-03+9.89e-01*B+6.46e-01+2.64*S*SL*5.37e-03 +2.60e-02*S*B+1.81*SL*5.37e-03*B)
	drv=2	((-1.84)*S+(-6.39)*SL*5.37e-03+1.06*B+1.77+5.81*S*SL*5.37e-03+4.92e-02*S* B+2.12*SL*5.37e-03*B)
ovf1sub0	drv=1	(5.03e-01*S+5.35*SL*5.37e-03+7.60e-01*B+(-1.67e-01)+(-1.90)*S*SL*5.37e-03 +(-3.61e-02)*S*B+1.78*SL*5.37e-03*B)
	drv=2	(1.10*S+7.43*SL*5.37e-03+8.34e-01*B+(-7.83e-01)+(-3.76)*S*SL*5.37e-03+(-2. 49e-02)*S*B+2.14*SL*5.37e-03*B)
ovf1sub1	drv=1	((-5.35e-01)*S+(-1.44)*SL*5.37e-03+9.88e-01*B+6.76e-01+2.54*S*SL*5.37e-03 +2.55e-02*S*B+1.81*SL*5.37e-03*B)
	drv=2	((-1.63)*S+(-4.47)*SL*5.37e-03+1.06*B+1.81+5.80*S*SL*5.37e-03+4.68e-02*S* B+2.13*SL*5.37e-03*B)

3) Size Equations [Unit: μm]

Type	Case	Equation
Width	ovf0sub0	((-4.72e-03)*B*B+3.90e-01*B+43.10)
	ovf0sub1	((-4.72e-03)*B*B+3.90e-01*B+50.10)
	ovf1sub0	((-3.18e-03)*B*B+2.64e-01*B+45.35)
	ovf1sub1	((-3.18e-03)*B*B+2.64e-01*B+52.35)
Height	all	(11.00*B+1.75e-15)

BS

Barrel Shifter

Logic Symbol



Features

- Asynchronous operation
- 4 to 64 bit Barrel Shifter
- High speed, low power operation
- Transmission gate mutiplexing scheme
- Bi-directional shift or rotation
- Fill with zero, MSB, or filler data
- Refresh flag
- Two output drive-strengths available

Function Description

The BS is an n-bit barrel shifter which is provided as a compiler. The BS is intended for use in high-speed and low-power applications. It performs a shifting or circular rotation operation and allows both arithmetic and logical shift operations. Also, it can shift and rotate input data in either direction and the direction of the shift can be chosen between MSB (LEFT) and LSB (RIGHT) of the bit string. Logical shifts fill vacant bits with zeros, and arithmetic shifts fill spaces with duplicates of the original MSB. The vacant bits also can be filled with filler data input (FIN). During a right shift, the FIN data fills the vacant bits with data from the LSB of the shift data bus. During a left shift, the shift data bus fills the vacant bits with data from the MSB of the shift data bus (essentially a circular shift).

Function Table

MSH	DIR	C1	C2	DOUT
0	0	0	0	Shift right and fill with zeros
0	0	0	1	Shift right and fill with MSB of DIN[ ]
0	0	1	0	Shift right and fill with FIN[ ] data
0	0	1	1	Rotate right
0	1	0	0	Shift left and fill with zeros
0	1	0	1	Shift left and fill with MSB
0	1	1	0	Shift left and fill with FIN[ ] data
0	1	1	1	Rotate left
1	X	0	0	All the bits are set to zero
1	X	0	1	All the bits are set to the MSB of DIN[ ]
1	X	1	0	FIN[ ]
1	X	1	1	DIN[ ]

Parameter Description

BS is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	Description	Range
bits	Number of bits for the input data bus	4 to 64
type	Direction of shift	BOTH/LEFT/RIGHT
drv	Drive strength	1/2

Pin Description

Name	TYPE	Description
DIN[ ]	Input	Data input bus
FIN[ ]		Filler data input
DIR		Specify the direction of the shift or rotation (Left/Right) (optional when the parameter type = BOTH)
C1, C2		Specify the filler at the vacant bit (zero/MSB/FIN[ ])
SH[ ]		Shift amount (unsigned-magnitude binary)
MSH		Maximum shift flag. It refreshes all the bits of output data with filler according to C1 and C2.
DOUT[ ]	Output	Data output bus

Pin Capacitance [Unit: pF]

Name	Case	Value
C1	all	0.0078
C2	all	0.0111
FIN[ ]	all	0.0014
MSH	type=BOTH	0.0114
	type=LEFT/RIGHT	0.0174
DIN[ ]	type=BOTH	0.0095
	type=LEFT/RIGHT	0.0081
SH[ ]	type=BOTH	-0.000009*bits*bits+0.00048*bits+0.021
	type=LEFT/RIGHT	-0.000005*bits*bits+0.00029*bits+0.010
DIR	type=BOTH	0.0055

Block Diagram



Timing Diagram



* tPXX means tPHL or tPLH.

Timing Type Definition

Timing Type	Definition
tPHLdid/tPLHdid	Propagation delay from DIN[ ] to DOUT[ ]
tPHLfid/tPLHfid	Propagation delay from FIN[ ] to DOUT[ ]
tPHLshd/tPLHshd	Propagation delay from SH[ ] to DOUT[ ]
tPHLdrd/tPLHdrd	Propagation delay from DIR to DOUT[ ]
tPHLc1d/tPLHc1d	Propagation delay from C1 to DOUT[ ]
tPHLc2d/tPLHc2d	Propagation delay from C2 to DOUT[ ]
tPHLmsd/tPLHmsd	Propagation delay from MSH to DOUT[ ]
tPDAdid	De-access time from DIN[ ] to DOUT[ ]
tPDAfid	De-access time from FIN[ ] to DOUT[ ]
tPDAshd	De-access time from SH[ ] to DOUT[ ]
tPDAdrd	De-access time from DIR to DOUT[ ]
tPDAc1d	De-access time from C1 to DOUT[ ]
tPDAc2d	De-access time from C2 to DOUT[ ]
tPDAmsd	De-access time from MSH to DOUT[ ]

Characteristic Reference Tables

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of Bits	-	S	Input Slope	ns
V_{DD}	Power Supply Voltage	V	SL	Standard Load	-
C_L	Output Load	SL	SA	Input Switching Activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	8		24		36		48		64	
Case: type=BOTH, drv=1										
tPHLc1d/tPLHc1d	1.14	1.11	1.37	1.30	1.47	1.40	1.53	1.44	1.52	1.44
tPHLc2d/tPLHc2d	1.10	1.07	1.32	1.28	1.42	1.38	1.47	1.43	1.45	1.42
tPHLdid/tPLHdid	1.15	1.07	1.38	1.27	1.49	1.36	1.54	1.41	1.53	1.39
tPHLmsd/tPLHmsd	0.54	0.53	0.57	0.58	0.60	0.61	0.63	0.64	0.67	0.69
tPHLshd/tPLHshd	0.74	0.69	0.76	0.75	0.78	0.80	0.80	0.84	0.82	0.91
tPHLfid/tPLHfid	0.93	0.86	1.11	1.04	1.19	1.12	1.21	1.15	1.18	1.11
tPHLdrd/tPLHdrd	0.50	0.47	0.53	0.49	0.55	0.51	0.57	0.52	0.59	0.55
tPDAc1d	0.59		0.77		0.84		0.86		0.80	
tPDAc2d	0.57		0.75		0.83		0.85		0.81	
tPDAdid	0.56		0.65		0.69		0.69		0.64	
tPDAmsd	0.25		0.27		0.28		0.29		0.31	
tPDAshd	0.36		0.38		0.40		0.42		0.45	
tPDAfid	0.50		0.57		0.63		0.68		0.75	
tPDAdrd	0.25		0.27		0.28		0.29		0.31	
Case: type=LEFT, drv=1										
tPHLc1d/tPLHc1d	1.12	1.09	1.35	1.29	1.45	1.38	1.51	1.42	1.50	1.42
tPHLc2d/tPLHc2d	1.08	1.05	1.29	1.26	1.39	1.36	1.44	1.41	1.42	1.40
tPHLdid/tPLHdid	1.12	1.05	1.35	1.25	1.46	1.34	1.51	1.39	1.50	1.37
tPHLmsd/tPLHmsd	0.38	0.37	0.41	0.42	0.44	0.45	0.46	0.48	0.50	0.53
tPHLshd/tPLHshd	0.72	0.66	0.77	0.73	0.80	0.78	0.83	0.83	0.87	0.90
tPHLfid/tPLHfid	0.90	0.84	1.09	1.02	1.16	1.10	1.19	1.13	1.15	1.09
tPDAc1d	0.58		0.74		0.82		0.85		0.83	
tPDAc2d	0.56		0.73		0.81		0.83		0.79	
tPDAdid	0.54		0.66		0.70		0.70		0.62	
tPDAmsd	0.21		0.22		0.24		0.25		0.26	
tPDAshd	0.34		0.37		0.40		0.42		0.46	
tPDAfid	0.48		0.55		0.61		0.66		0.73	

Characteristic Reference Table (Cont.)

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	8		24		36		48		64	
Case: type=RIGHT, drv=1										
tPHLc1d/tPLHc1d	1.12	1.09	1.35	1.28	1.45	1.38	1.51	1.42	1.50	1.42
tPHLc2d/tPLHc2d	1.08	1.05	1.29	1.26	1.39	1.36	1.44	1.41	1.43	1.40
tPHLdid/tPLHdid	1.13	1.05	1.35	1.25	1.46	1.34	1.52	1.39	1.51	1.38
tPHLmsd/tPLHmsd	0.38	0.37	0.41	0.42	0.44	0.45	0.46	0.48	0.50	0.53
tPHLshd/tPLHshd	0.72	0.67	0.75	0.73	0.76	0.78	0.78	0.82	0.80	0.88
tPHLfid/tPLHfid	0.90	0.84	1.09	1.02	1.16	1.10	1.19	1.13	1.15	1.09
tPDAc1d	0.57		0.75		0.82		0.85		0.80	
tPDAc2d	0.56		0.73		0.81		0.83		0.79	
tPDAdid	0.54		0.68		0.72		0.71		0.62	
tPDAmsd	0.21		0.22		0.23		0.25		0.26	
tPDAshd	0.34		0.37		0.39		0.41		0.43	
tPDAfid	0.48		0.55		0.61		0.66		0.73	

2) Power Characteristics [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5, drv = 1)

Case	8	24	36	48	64
type=BOTH	5.12	32.09	52.32	72.54	99.51
type=LEFT	4.51	19.05	29.96	40.86	55.41
type=RIGHT	2.91	18.36	29.96	41.55	57.00

3) Size Characteristics [Unit: μm]

Type	Case	8	24	36	48	64
Width	type=BOTH	73.45	132.42	168.28	196.97	224.07
	type=LEFT	45.41	72.41	90.79	107.57	127.44
	type=RIGHT	45.41	72.41	90.79	107.57	127.44
Height	all	110.00	286.00	418.00	550.00	726.00

Characteristic Equation Table

1) Timing Equations [Unit: ns]

Case=BOTH (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLc1d	drv=1	(1.22e-01*S+2.06*SL*5.37e-03+1.97e-02*B+8.63e-01+(-1.81e-04)*B*B)
	drv=2	(1.21e-01*S+1.07*SL*5.37e-03+1.97e-02*B+9.05e-01+(-1.81e-04)*B*B)
tPHLc2d	drv=1	(1.20e-01*S+2.07*SL*5.37e-03+1.89e-02*B+8.30e-01+(-1.77e-04)*B*B)
	drv=2	(1.20e-01*S+1.08*SL*5.37e-03+1.90e-02*B+8.70e-01+(-1.78e-04)*B*B)
tPHLdid	drv=1	(1.14e-01*S+2.06*SL*5.37e-03+2.00e-02*B+8.68e-01+(-1.82e-04)*B*B)
	drv=2	(1.15e-01*S+1.08*SL*5.37e-03+2.01e-02*B+9.06e-01+(-1.84e-04)*B*B)
tPHLmsd	drv=1	(8.81e-02*S+1.98*SL*5.37e-03+2.35e-03*B+3.92e-01+1.41e-01*S*SL*5.37e-03+(-3.14e-05)*S*B+(-1.47e-04)*SL*5.37e-03*B)
	drv=2	(8.80e-02*S+9.92e-01*SL*5.37e-03+2.36e-03*B+4.32e-01+1.42e-01*S*SL*5.37e-03+(-4.24e-05)*S*B+(-1.23e-04)*SL*5.37e-03*B)
tPHLshd	drv=1	(9.23e-02*S+1.98*SL*5.37e-03+1.52e-03*B+6.01e-01+1.50e-01*S*SL*5.37e-03+(-8.55e-05)*S*B+(-9.17e-05)*SL*5.37e-03*B)
	drv=2	(9.29e-02*S+9.98e-01*SL*5.37e-03+1.54e-03*B+6.39e-01+1.48e-01*S*SL*5.37e-03+(-8.40e-05)*S*B+(-6.75e-05)*SL*5.37e-03*B)
tPHLfid	drv=1	(2.42e-01*S+2.14*SL*5.37e-03+1.69e-02*B+6.38e-01+(-1.73e-04)*B*B)
	drv=2	(2.41e-01*S+1.15*SL*5.37e-03+1.70e-02*B+6.78e-01+(-1.73e-04)*B*B)
tPHLdrd	drv=1	(8.39e-02*S+1.98*SL*5.37e-03+1.58e-03*B+3.68e-01+1.31e-01*S*SL*5.37e-03+(-5.96e-05)*S*B+(-2.79e-05)*SL*5.37e-03*B
	drv=2	(8.32e-02*S+9.97e-01*SL*5.37e-03+1.60e-03*B+4.09e-01+1.32e-01*S*SL*5.37e-03+(-2.91e-05)*S*B+(-1.37e-05)*SL*5.37e-03*B
tPLHc1d	drv=1	(2.65e-02*S+1.99*SL*5.37e-03+1.69e-02*B+8.74e-01+(-1.55e-04)*B*B)
	drv=2	(2.64e-02*S+1.01*SL*5.37e-03+1.71e-02*B+9.10e-01+(-1.57e-04)*B*B)
tPLHc2d	drv=1	(3.28e-03*S+1.97+SL*5.37e-03+1.81e-02*B+8.32e-01+(-1.64e-04)*B*B)
	drv=2	(4.72e-03*S+9.93e-01+SL*5.37e-03+1.82e-02*B+8.68e-01+(-1.66e-04)*B*B)
tPLHdid	drv=1	(6.40e-03*S+1.97*SL*5.37e-03+1.75e-02*B+8.32e-01+(-1.63e-04)*B*B)
	drv=2	(6.70e-03*S+9.79e-01*SL*5.37e-03+1.76e-02*B+8.69e-01+(-1.63e-04)*B*B)
tPLHmsd	drv=1	(8.61e-02*S+1.95*SL*5.37e-03+2.77e-03*B+3.87e-01+1.40e-01*S*SL*5.37e-03)
	drv=2	(8.64e-02*S+9.64e-01*SL*5.37e-03+2.79e-03*B+4.23e-01+1.42e-01*S*SL*5.37e-03)
tPLHshd	drv=1	(1.22e-01*S+2.06*SL*5.37e-03+3.97e-03*B+5.20e-01+(-2.97e-04)*SL*5.37e-03*B)
	drv=2	(1.22e-01*S+1.08*SL*5.37e-03+3.98e-03*B+5.56e-01+(-3.31e-04)*SL*5.37e-03*B)
tPLHfid	drv=1	((-3.07e-02)*S+1.95*SL*5.37e-03+1.65e-02*B+6.42e-01+(-1.67e-04)*B*B)
	drv=2	((-3.05e-02)*S+9.66e-01*SL*5.37e-03+1.65e-02*B+6.79e-01+(-1.67e-04)*B*B
tPLHdrd	drv=1	((-3.47e-04)*S+1.96*SL*5.37e-03+1.38e-03*B+3.54e-01+(-1.61e-02)*S*SL*5.37e-03+(-7.16e-05)*S*B+(-1.24e-04)*SL*5.37e-03*B)
	drv=2	((-3.30e-03)*S+9.58e-01*SL*5.37e-03+1.40e-03*B+3.93e-01+(-7.35e-05)*S*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=BOTH (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPDAc1d	drv=1	(1.22e-02*S+9.51e-01*SL*5.37e-03+1.72e-02*B+4.13e-01+(-1.87e-04)*B*B)
	drv=2	(2.22e-02*S+4.11e-01*SL*5.37e-03+3.43e-03*B+5.81e-01)
tPDAc2d	drv=1	(1.75e-02*S+9.43e-01*SL*5.37e-03+1.70e-02*B+3.94e-01+(-1.77e-04)*B*B)
	drv=2	(2.44e-02*S+3.93e-01*SL*5.37e-03+2.04e-02*B+3.83e-01+(-2.50e-04)*B*B)
tPDAdid	drv=1	(3.46e-02*S+1.15*SL*5.37e-03+9.78e-03*B+4.18e-01+(-1.15e-04)*B*B)
	drv=2	(5.32e-02*S+6.00e-01*SL*5.37e-03+6.14e-03*B+4.53e-01+(-6.56e-05)*B*B)
tPDAmsd	drv=1	((5.00e-02)*S+1.21*SL*5.37e-03+9.81e-04*B+1.72e-01+(-8.82e-02)*S*SL*5.37e-03+) 7.78e-05*S*B+(-2.47e-04)*SL*5.37e-03*B)
	drv=2	((5.32e-02)*S+6.17e-01*SL*5.37e-03+9.72e-04*B+1.96e-01+(-9.12e-02)*S*SL*5.37e-03+ 6.18e-05*S*B+(-2.26e-04)*SL*5.37e-03*B)
tPDAshd	drv=1	(6.07e-02*S+1.20*SL*5.37e-03+1.64e-03*B+2.65e-01+(-1.35e-01)*S*SL*5.37e-03
	drv=2	(7.00e-02*S+6.12e-01*SL*5.37e-03+1.69e-03*B+2.88e-01+(-1.39e-01)*S*SL*5.37e-03
tPDAfid	drv=1	((-4.52e-02)*S+1.01*SL*5.37e-03+4.55e-03*B+4.20e-01+2.09e-01*S*SL*5.37e-03+6.36e-04*S*B+(-5.43e-03)*SL*5.37e-03*B)
	drv=2	((-2.19e-02)*S+4.75e-01*SL*5.37e-03+5.58e-03*B+4.05e-01+1.91e-01*S*SL*5.37e-03+1.79e-04*S*B+(-6.64e-03)*SL*5.37e-03*B)
tPDAdrd	drv=1	((-3.91e-03)*S+1.19*SL*5.37e-03+9.42e-04*B+1.83e-01+(-1.70e-02)*S*SL* 5.37e-03+(-7.17e-05)*S*B+(-6.07e-05)*SL*5.37e-03*B)
	drv=2	((-3.81e-03)*S+6.01e-01*SL*5.37e-03+9.51e-04*B+2.08e-01+(-1.67e-02)*S*SL* 5.37e-03+(-7.43e-05)*S*B+(-2.91e-05)*SL*5.37e-03*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=LEFT (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLc1d	drv=1	(1.22e-01*S+2.06*SL*5.37e-03+1.99e-02*B+8.40e-01+(-1.83e-04)*B*B)
	drv=2	(1.23e-01*S+1.08*SL*5.37e-03+1.99e-02*B+8.83e-01+(-1.82e-04)*B*B)
tPHLc2d	drv=1	(1.20e-01*S+2.07*SL*5.37e-03+1.89e-02*B+8.08e-01+(-1.79e-04)*B*B)
	drv=2	(1.20e-01*S+1.09*SL*5.37e-03+1.90e-02*B+8.51e-01+(-1.79e-04)*B*B)
tPHLdid	drv=1	(1.17e-01*S+2.06*SL*5.37e-03+2.00e-02*B+8.42e-01+(-1.84e-04)*B*B)
	drv=2	(1.16e-01*S+1.09*SL*5.37e-03+2.00e-02*B+8.86e-01+(-1.84e-04)*B*B)
tPHLmsd	drv=1	(6.09e-02*S+1.95*SL*5.37e-03+1.97e-03*B+2.41e-01+1.50e-01*S*SL*5.37e-03+ 8.54e-04*S*B+5.76e-04*SL*5.37e-03*B)
	drv=2	(1.21e-01*S+1.07*SL*5.37e-03+2.59e-03*B+2.49e-01+6.07e-04*SL*5.37e-03*B)
tPHLshd	drv=1	(9.05e-02*S+1.99*SL*5.37e-03+2.60e-03*B+5.77e-01+1.50e-01*S*SL*5.37e-03)
	drv=2	(9.19e-02*S+1.00*SL*5.37e-03+2.67e-03*B+6.21e-01+1.51e-01*S*SL*5.37e-03+ (-5.25e-05)*S*B+4.87e-05*SL*5.37e-03*B)
tPHLfid	drv=1	(2.40e-01*S+2.14*SL*5.37e-03+1.70e-02*B+6.15e-01+(-1.74e-04)*B*B)
	drv=2	(2.41e-01*S+1.16*SL*5.37e-03+1.71e-02*B+6.58e-01+(-1.76e-04)*B*B)
tPLHc1d	drv=1	(2.58e-02*S+2.00*SL*5.37e-03+1.71e-02*B+8.55e-01+(-1.57e-04)*B*B)
	drv=2	(2.66e-02*S+1.01*SL*5.37e-03+1.69e-02*B+8.96e-01+(-1.55e-04)*B*B)
tPLHc2d	drv=1	(3.35e-03*S+1.98+SL*5.37e-03+1.81e-02*B+8.14e-01+(-1.65e-04)*B*B)
	drv=2	(3.72e-03*S+9.90e-01+SL*5.37e-03+1.80e-02*B+8.54e-01+(-1.64e-04)*B*B)
tPLHdid	drv=1	(6.59e-03*S+1.97*SL*5.37e-03+1.75e-02*B+8.14e-01+(-1.62e-04)*B*B)
	drv=2	(5.84e-03*S+9.81e-01*SL*5.37e-03+1.75e-02*B+8.53e-01+(-1.63e-04)*B*B)
tPLHmsd	drv=1	(8.44e-02*S+1.94*SL*5.37e-03+2.62e-03*B+2.29e-01+1.67e-01*S*SL*5.37e-03+ 5.64e-04*S*B+3.35e-04*SL*5.37e-03B)
	drv=2	(8.63e-02*S+9.53e-01*SL*5.37e-03+2.88e-03*B+2.68e-01+1.70e-01*S*SL*5.37e-03+ 5.43e-04*S*B+3.63e-04*SL*5.37e-03B)
tPLHshd	drv=1	(9.01e-02*S+1.96*SL*5.37e-03+4.19e-03*B+5.05e-01+1.48e-01*S*SL*5.37e-03)
	drv=2	(9.00e-02*S+9.74e-01*SL*5.37e-03+4.19e-03*B+5.46e-01+1.50e-01*S*SL*5.37e-03)
tPLHfid	drv=1	((-3.10e-02)*S+1.95*SL*5.37e-03+1.68e-02*B+6.22e-01+(-1.72e-04)*B*B)
	drv=2	((-3.06e-02)*S+9.63e-01*SL*5.37e-03+1.67e-02*B+6.64e-01+(-1.71e-04)*B*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=LEFT (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPDAc1d	drv=1	(2.07e-02*S+9.56e-01*SL*5.37e-03+1.55e-02*B+4.06e-01+(-1.52e-04)*B*B)
	drv=2	((-1.51e-02)*S+3.31e-01*SL*5.37e-03+3.26e-03*B+5.79e-01+1.99e-01*S*SL*5.37e-03)
tPDAc2d	drv=1	(2.08e-02*S+9.68e-01*SL*5.37e-03+1.66e-02*B+3.79e-01+(-1.73e-04)*B*B)
	drv=2	((-4.20e-03)*S+3.37e-01*SL*5.37e-03+3.57e-03*B+5.57e-01+1.67e-01*S*SL*5.37e-03)
tPDAdid	drv=1	(4.19e-02*S+1.13*SL*5.37e-03+1.24e-02*B+3.85e-01+(-1.53e-04)*B*B)
	drv=2	(5.22e-02*S+6.00e-01*SL*5.37e-03+6.98e-03*B+4.36e-01+(-7.68e-05)*B*B)
tPDAfid	drv=1	((-4.12e-02)*S+1.02*SL*5.37e-03+4.51e-03*B+4.01e-01+2.03e-01*S*SL*5.37e-03+ 5.54e-04*S*B+(-5.23e-03)*SL*5.37e-03*B)
	drv=2	((-4.52e-02)*S+4.27e-01*SL*5.37e-03+4.70e-03*B+4.34e-01+2.03e-01*S*SL*5.37e-03+ 5.40e-04*S*B+(-5.53e-03)*SL*5.37e-03*B)
tPDAmsd	drv=1	(3.69e-02*S+1.19*SL*5.37e-03+8.91e-04*B+1.30e-01+(-7.60e-02)*S*SL*5.37e-03+ 3.84e-04*S*B+4.63e-05*SL*5.37e-03*B)
	drv=2	(3.85e-02*S+5.96e-01*SL*5.37e-03+1.03e-03*B+1.54e-01+(-8.14e-02)*S*SL*5.37e-03+ 3.66e-04*S*B+1.24e-04*SL*5.37e-03*B)
tPDAshd	drv=1	(6.04e-02*S+1.21*SL*5.37e-03+1.97e-03*B+2.50e-01+(-1.30e-01)*S*SL* 5.37e-03+4.69e-04*S*B+(-4.96e-04)*SL*5.37e-03*B)
	drv=2	(6.30e-02*S+6.25e-01*S*5.37e-03+1.96e-03*B+2.77e-01+(-1.35e-01)*S*SL* 5.37e-03+4.81e-04*S*B+(-6.12e-04)*SL*5.37e-03*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=RIGHT (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPHLc1d	drv=1	(1.23e-01*S+2.06*SL*5.37e-03+1.97e-02*B+8.42e-01+(-1.80e-04)*B*B)
	drv=2	(1.22e-01*S+1.08*SL*5.37e-03+1.99e-02*B+8.85e-01+(-1.83e-04)*B*B)
tPHLc2d	drv=1	(1.20e-01*S+2.06*SL*5.37e-03+1.88e-02*B+8.09e-01+(-1.76e-04)*B*B)
	drv=2	(1.20e-01*S+1.08*SL*5.37e-03+1.88e-02*B+8.55e-01+(-1.76e-04)*B*B)
tPHLdid	drv=1	(1.14e-01*S+2.06*SL*5.37e-03+1.99e-02*B+8.48e-01+(-1.82e-04)*B*B)
	drv=2	(1.13e-01*S+1.08*SL*5.37e-03+2.00e-02*B+8.91e-01+(-1.82e-04)*B*B)
tPHLmsd	drv=1	(6.12e-02*S+1.95*SL*5.37e-03+1.99e-03*B+2.39e-01+1.49e-01*S*SL*5.37e-03+ 8.32e-04*S*B+5.67e-04*SL*5.37e-03*B)
	drv=2	(1.21e-01*S+1.06*SL*5.37e-03+2.59e-03*B+2.46e-01+6.43e-04*SL*5.37e-03*B)
tPHLshd	drv=1	(9.26e-02*S+1.99*SL*5.37e-03+1.48e-03*B+5.84e-01+1.49e-01*S*SL*5.37e-03+ (-6.52e-05)*S*B+(-7.77e-05)*SL*5.37e-03*B)
	drv=2	(9.28e-02*S+1.01*SL*5.37e-03+1.53e-03*B+6.27e-01+1.50e-01*S*SL*5.37e-03+ (-8.42e-05)*S*B+(-7.61e-05)*SL*5.37e-03*B)
tPHLfid	drv=1	(2.41e-01*S+2.14*SL*5.37e-03+1.70e-02*B+6.14e-01+(-1.75e-04)*B*B)
	drv=2	(2.41e-01*S+1.16*SL*5.37e-03+1.70e-02*B+6.59e-01+(-1.73e-04)*B*B)
tPLHc1d	drv=1	(2.58e-02*S+2.00*SL*5.37e-03+1.70e-02*B+8.53e-01+(-1.56e-04)*B*B)
	drv=2	(2.55e-02*S+1.01*SL*5.37e-03+1.70e-02*B+8.94e-01+(-1.55e-04)*B*B)
tPLHc2d	drv=1	(3.27e-03*S+1.98*SL*5.37e-03+1.80e-02*B+8.13e-01+(-1.63e-04)*B*B)
	drv=2	(3.47e-03*S+9.91e-01*SL*5.37e-03+1.81e-02*B+8.53e-01+(-1.64e-04)*B*B)
tPLHdid	drv=1	(6.89e-03*S+1.97*SL*5.37e-03+1.74e-02*B+8.13e-01+(-1.61e-04)*B*B)
	drv=2	(6.06e-03*S+9.80e-01*SL*5.37e-03+1.74e-02*B+8.54e-01+(-1.61e-04)*B*B)
tPLHmsd	drv=1	(8.45e-02*S+1.94*SL*5.37e-03+2.66e-03*B+2.27e-01+1.68e-01*S*SL*5.37e-03+ 5.53e-04*S*B+3.27e-04*SL*5.37e-03B)
	drv=2	(8.52e-02*S+9.52e-01*SL*5.37e-03+2.85e-03*B+2.67e-01+1.70e-01*S*SL*5.37e-03+ 5.90e-04*S*B+3.03e-04*SL*5.37e-03B)
tPLHshd	drv=1	(1.22e-01*S+2.06*SL*5.37e-03+3.85e-03*B+5.03e-01+(-2.56e-04)*SL*5.37e-03)
	drv=2	(1.21e-01*S+1.08*SL*5.37e-03+3.90e-03*B+5.43e-01+(-3.79e-04)*SL*5.37e-03)
tPLHfid	drv=1	((-3.22e-02)*S+1.95*SL*5.37e-03+1.66e-02*B+6.22e-01+(-1.69e-04)*B*B)
	drv=2	((-3.24e-02)*S+9.64e-01*SL*5.37e-03+1.65e-02*B+6.63e-01+(-1.68e-04)*B*B)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns]

Case=RIGHT (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	Case	Equation
tPDAc1d	drv=1	(2.39e-02*S+9.67e-01*SL*5.37e-03+1.66e-02*B+3.92e-01+(-1.74e-04)*B*B)
	drv=2	((-1.48e-02)*S+3.31e-01*SL*5.37e-03+3.29e-03*B+5.77e-01+1.98e-01*S*SL*5.37e-03)
tPDAc2d	drv=1	(2.10e-02*S+9.68e-01*SL*5.37e-03+1.67e-02*B+3.77e-01+(-1.73e-04)*B*B)
	drv=2	(2.25e-02*S+4.16e-01*SL*5.37e-03+1.98e-02*B+3.72e-01+(-2.38e-04)*B*B)
tPDAdid	drv=1	(4.52e-02*S+1.11*SL*5.37e-03+1.45e-02*B+3.69e-01+(-1.81e-04)*B*B)
	drv=2	(4.83e-02*S+5.89e-01*SL*5.37e-03+7.97e-03*B+4.31e-01+(-9.01e-05)*B*B)
tPDAfid	drv=1	((-4.15e-02)*S+1.02*SL*5.37e-03+4.51e-03*B+4.00e-01+2.02e-01*S*SL*5.37e-03+ 5.59e-04*S*B+(-5.23e-03)*SL*5.37e-03*B)
	drv=2	((-4.50e-02)*S+4.28e-01*SL*5.37e-03+4.72e-03*B+4.31e-01+2.02e-01*S*SL*5.37e-03+ 5.26e-04*S*B+(-5.52e-03)*SL*5.37e-03*B)
tPDAmsd	drv=1	(3.61e-02*S+1.19*SL*5.37e-03+8.74e-04*B+1.30e-01+(-7.56e-02)*S*SL*5.37e-03+ 4.01e-04*S*B+6.44e-05*SL*5.37e-03*B)
	drv=2	(3.75e-02*S+6.00e-01*SL*5.37e-03+9.92e-04*B+1.54e-01+(-8.04e-02)*S*SL*5.37e-03+ 3.87e-04*S*B+7.87e-05*SL*5.37e-03*B)
tPDAshd	drv=1	(6.45e-02*S+1.20*SL*5.37e-03+1.60e-03*B+2.54e-01+(-1.29e-01)*S*SL*5.37e-03)
	drv=2	(6.77e-02*S+6.15e-01*SL*5.37e-03+1.66e-03*B+2.78e-01+(-1.35e-01)*S*SL*5.37e-03)

2) Power Equations [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Parameter		Equation
type=BOTH	drv=1	(3.46*S+1.28*SL*5.37e-03+1.66*B+(-9.12)+(-1.82e-01)*S*SL*5.37e-03+(-2.16e-01)*S*B+1.34*SL*5.37e-03*B)
	drv=2	(6.58*S+6.82*SL*5.37e-03+1.74*B+(-12.09)+(-4.53)*S*SL*5.37e-03+(-2.60e-01)*S*B+1.13*SL*5.37e-03*B)
type=LEFT	drv=1	(4.07e-01*S+(-1.53e-01)*SL*5.37e-03+8.22e-01*B+(-2.85)+1.22*S*SL*5.37e-03+6.64e-02*S*B+1.37*SL*5.37e-03*B)
	drv=2	(2.23*S+5.21*SL*5.37e-03+8.72e-01*B+(-5.04)+(-2.71)*S*SL*5.37e-03+1.24e-01*S*B+1.14*SL*5.37e-03*B)
type=RIGHT	drv=1	(3.26*S+9.09e-01*SL*5.37e-03+8.93e-01*B+(-5.52)+1.37*SL*5.37e-03*B)
	drv=2	(1.93*S+5.14*SL*5.37e-03+8.75e-01*B+(-5.12)+(-2.71)*S*SL*5.37e-03+1.41e-01*S*B+1.15*SL*5.37e-03*B)

3) Size Equations [Unit: μm]

Type	Case	Equation
Width	type=BOTH	((-2.49e-02)*B*B+4.48*B+39.19)
	type=LEFT	((-5.57e-03)*B*B+1.87*B+30.84)
	type=RIGHT	((-5.57e-03)*B*B+1.87*B+30.84)
Height	all	(11.00*B+22.00)

MPY

Modified Booth Multiplier

Logic Symbol



Features

- Asynchronous/Synchronous operation
- 6 to 64 bit multiplication
- High speed/low power operation
- 2's complement signed multiplication
- Modified Booth Algorithm
- 1-stage pipeline insertion available
- Two drive-strengths available.

Function Description

The MPY is an NxM multiplier which is provided as a compiler. The MPY is intended for use in high-speed and low-power applications. It adopts the modified booth's multiplication scheme to encode the multiplier bits by partitioning the bits into three bit groups, with one bit shared between groups and performs a signed multiplication operation between two integers. It allows from 6-bit to 64-bit with a configurable size of output buffer and 1-stage pipeline scheme is available to improve the frequency of design.

The partial products are summed up with two adders; the MSB adder and the LSB adder. The MSB adder is a fast group bypass adder. The LSB adder is programmable to insert 1-stage pipeline scheme and is, therefore, the ripple carry adder. The clock to the pipeline controls the internal data change, so that the data is always stable throughout the clock period and there is no hold problem.

Parameter Description

MPY is the compiler that automatically generates symbol, netlist, timing model, power model and layout according to the following parameters.

Parameter Name	**Description**	**Range**
xbits	Multiplicand (XIN) bits	6 to 64 (even)
ybits	Multiplier (YIN) bits	6 to 64 (even)
pipes	Pipeline stage	0/1
drv	Output drive strength	1/2

Note: The xbits should be greater than or equal to the ybits ($x \geq y$).

Pin Description

Pin Name	TYPE	Description
XIN [ ]	Input	Data input bus – Multiplicand
YIN [ ]		Data input bus – Multiplier
MCKN		Clock input to the pipeline register. (optional when the parameter pipes = 1)
RSTN		Reset negative input to the pipeline register. (optional when the parameter pipes = 1).
POUT[ ]	output	Data output bus – Product result

Pin Capacitance [Unit: pF]

Name	Case	Value
XIN[ ]	all	0.0082
YIN[ ]	all	0.0180
MCKN	pipe=1	0.000069*x_width+0.0012*y_width+0.00661-0.000004*x_width*y_width
RSTN	pipe=1	0.000153*x_width+0.0027*y_width+0.00096-0.000009*x_width*y_width

Block Diagram

<pipes=0>



<pipes=1>



MPY

Modified Booth Multiplier

Timing Diagram

<pipes=0>



Timing Type Definition

Timing Type	Definition
tPHLxp/tPLHxp	Propagation delay from XIN[ ] to POUT[ ]
tPHLyp/tPLHyp	Propagation delay from YIN[ ] to POUT[ ]
tPDAxp	De-access time from XIN[ ] to POUT[ ]
tPDAyp	De-access time from YIN[ ] to POUT[ ]

Timing Diagram (Cont.)

<pipes=1>



*NOTE: Synchronous reset: RSTN goes to 'LOW' state, when MCKN is at 'HIGH' state.
Asynchronous reset: RSTN goes to 'LOW' state, when MCKN is at 'LOW' state.

Timing Type Definition

Timing Type	Definition
SETUPxck	Setup time for XIN[ ] to MCKN
SETUPyck	Setup time for YIN[ ] to MCKN
SETUPrck	Setup time for RSTN to MCKN
HOLDxck	Hold time for XIN[ ] to MCKN
HOLDyck	Hold time for YIN[ ] to MCKN
HOLDrck	Hold time for RSTN to MCKN
MINHpck	Minimum Clock Pulse width HIGH
MINLpck	MInimum Clock Pulse width LOW
MINLprn	MInimum Clock Pulse width RSTN
tPHLckp/tPLHckp	Propagation delay from MCKN to POUT[ ]
tPHLrnp/tPLHrnp	Propagation delay from RSTN to POUT[ ]
tPDAckp	De-access time from MCKN to POUT[ ]
tPDArnp	De-access time from RSTN to POUT[ ]

MPY

Modified Booth Multiplier

Characteristic Reference Table

Symbol	Description	Unit	Symbol	Description	Unit
B	Number of XIN[ ] bits	-	W	Number of YIN[ ] bits	-
V_{DD}	Power Supply Voltage	V	S	Input Slope	ns
C_L	Output Load	SL	SA	Input Switching Activity	-

1) Timing Characteristics [Unit: ns]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

Type	8x8	24x24	36x36	48x48	64x64
Case: pipes=0,drv=1					
tPHLxp/tPLHxp	1.62/1.55	3.70/3.70	5.21/5.25	6.69/6.74	8.59/8.63
tPHLyp/tPLHyp	1.84/1.72	3.51/3.46	4.76/4.76	6.01/6.06	7.68/7.80
tPDAxp	0.62	0.65	0.67	0.70	0.73
tPDAyp	0.99	1.05	1.10	1.14	1.21
Case: pipes=1,drv=1					
HOLDrck	0.00	0.00	0.00	0.00	0.00
HOLDxck	0.00	0.00	0.00	0.00	0.00
HOLDyck	0.00	0.00	0.00	0.00	0.00
MINHpck	0.12	0.20	0.25	0.31	0.39
MINLpck	0.14	0.19	0.23	0.26	0.31
MINLprn	0.26	0.49	0.67	0.85	1.09
SETUPrck	0.25	0.49	0.67	0.85	1.09
SETUPxck	0.81	1.81	2.61	3.46	4.67
SETUPyck	1.01	1.74	2.32	2.93	3.80
tPHLckp	1.33	2.37	3.08	3.73	4.51
tPHLrnp	1.52	1.77	1.94	2.09	2.26
tPLHckp	1.25	2.39	3.16	3.86	4.68
tPLHrnp	0.00	0.00	0.00	0.00	0.00
tPDAckp	0.36	0.39	0.41	0.44	0.47
tPDArnp	0.41	0.46	0.50	0.54	0.59

Characteristic Reference Table (Cont.)

2) Power Characteristics [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Case	8x8	24x24	36x36	48x48	64x64
pipes=0, drv=1	64.28	394.93	1088.07	2162.76	4189.22
pipes=1, drv=1	76.78	436.88	1036.20	1917.74	3532.13

3) Size Characteristics [Unit: μm]

Type	Case	8x8	24x24	36x36	48x48	64x64
Width	pipes=0, drv=1	191.65	448.41	640.57	832.39	1087.62
	pipes=1, drv=1	244.65	501.41	693.57	885.39	1140.62
Height	pipes=0, drv=1	110.00	286.00	418.00	550.00	726.00
	pipes=1, drv=1	121.00	297.00	429.00	561.00	737.00

Characteristic Equation Table

1) Timing Equations [Unit: ns] (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

<pipes=0>

Type	Case	Equation
tPHLxp	drv=1	(1.37e-01*S+2.00*SL*5.37e-03+2.07e-02*B+1.14e-01*W+4.23e-01+(-1.35e-04)*B*B)
	drv=2	(1.33e-01*S+1.04*SL*5.37e-03+9.81e-03*B+1.16e-01*W+6.21e-01+2.33e-04*S*W)
tPHLyp	drv=1	(1.26e-01*S+2.01*SL*5.37e-03+5.15e-03*B+9.92e-02*W+8.71e-01)
	drv=2	(1.14e-01*S+1.02*SL*5.37e-03+4.77e-03*B+9.83e-02*W+9.24e-01+1.36e-02*S*SL*5.37e-03+1.54e-04*S*B+5.30e-04*SL*5.37e-03*B+1.40e-04*S*W+2.72e-04*SL*5.37e-03*W+1.49e-05*B*W)
tPLHxp	drv=1	(6.43e-03*S+1.95*SL*5.37e-03+2.57e-02*B+1.15e-01*W+3.30e-01+(-2.05e-04)*B*B)
	drv=2	(8.28e-03*S+9.55e-01*SL*5.37e-03+2.53e-02*B+1.18e-01*W+3.41e-01+(-1.98e-04)*B*B)
tPLHyp	drv=1	(2.26e-02*S+1.96*SL*5.37e-03+3.66e-03*B+1.05e-01*W+7.43e-01)
	drv=2	(1.30e-02*S+9.36e-01*SL*5.37e-03+3.37e-03*B+1.04e-01*W+7.83e-01+1.24e-02*S*SL*5.37e-03+1.16e-04*S*B+2.94e-04*SL*5.37e-03*B+1.70e-04*S*W+5.86e-04*SL*5.37e-03*W+1.60e-05*B*W)
tPDAxp	drv=1	(6.32e-03*S+1.95*SL*5.37e-03+(-6.99e-06)*B+2.03e-03*W+4.95e-01)
	drv=2	((-6.13e-03)*S+9.21e-01*SL*5.37e-03+(-2.96e-04)*B+1.24e-03*W+5.35e-01+1.17e-02*S*SL*5.37e-03+1.22e-04*S*B+3.26e-04*SL*5.37e-03*B+2.50e-04*S*W+5.06e-04*SL*5.37e-03*W+1.02e-05*B*W)
tPDAyp	drv=1	(2.29e-02*S+1.95*SL*5.37e-03+3.91e-03*B+(-7.74e-05)*W+8.51e-01)
	drv=2	(1.32e-02*S+9.23e-01*SL*5.37e-03+3.67e-03*B+(-7.42e-04)*W+8.86e-01+1.10e-02*S*SL*5.37e-03+1.27e-04*S*B+2.23e-04*SL*5.37e-03*B+1.43e-04*S*W+5.78e-04*SL*5.37e-03*W+9.10e-06*B*W)

Characteristic Equation Table (Cont.)

1) Timing Equations [Unit: ns] (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

<pipes=1>

Type	Case	Equation
HOLDrck	drv=1	((-3.43e-03)*S+(-1.19e-02)*B+(-2.18e-05)*W+(-1.66e-02)+6.64 e-05*S*B+(-1.59e-04)*S*W+6.62e-07*B*W)
	drv=2	((-4.84e-03)*S+(-1.19e-02)*B+6.05e-05*W+(-1.77e-02)+8.40 e-05*S*B+(-1.47e-04)*S*W+(-9.19e-07)*B*W)
HOLDxck	drv=1	(1.17e-01*S+3.08e-03*B+(-5.79e-02)*W+(-6.46e-02)+ (-1.69e-04)*W*W)
	drv=2	(1.17e-01*S+3.08e-03*B+(-5.91e-02)*W+(-7.12e-02)+ (-1.73e-04)*W*W)
HOLDyck	drv=1	(1.01e-01*S+(-8.36e-04)*B+(-3.66e-02)*W+(-4.49e-01)+(-1.17e-04) *W*W)
	drv=2	(1.01e-01*S+(-8.56e-04)*B+(-3.66e-02)*W+(-4.66e-01)+(-1.18e-04) *W*W)
MINHpck	all	(2.51e-02*S+(-9.90e-05)*SL*5.37e-03+4.42e-03*B+(-9.56e-05)*W+ 8.44e-02+5.40e-06*B*B)
MINLpck	all	(1.19e-01*S+9.61e-05*SL*5.37e-03+3.04e-03*B+1.20e-04*W+9.19 e-02+(-1.84e-05)*S*SL*5.37e-03+8.94e-05*S*B+(-6.96e-06)*SL*5. 37e-03*B+(-3.05e-05)*S*W+6.74e-06*SL*5.37e-03*W+(-2.84e-06)* B*W)
MINLprn	all	(1.23e-01*S+(-5.58e-04)*SL*5.37e-03+1.49e-02*B+(-4.76e-05)*W+ 1.12e-01+1.39e-04*S*W)
SETUPrck	drv=1	(1.23e-01*S+1.49e-02*B+(-5.81e-05)*W+1.11e+1.40e-04*S*W)
	drv=2	(1.27e-01*S+1.49e-02*B+5.48-05*W+1.09e-01)
SETUPxck	drv=1	(1.36e-01*S+(-4.10e-05)*B+5.70e-02*W+3.19e-01+1.65e-04*W*W)
	drv=2	(1.36e-01*S+(-4.47e-05)*B+5.84e-02*W+3.28e-01+1.68e-04*W*W)

1) Timing Equations [Unit: ns] (Cont.) (Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2)

<pipes=1>

Type	Case	Equation
SETUPyck	drv=1	(1.24e-01*S+5.16e-03*B+3.65e-02*W+6.49e-01+1.12e-04*W*W)
	drv=2	(1.25e-01*S+5.15e-03*B+3.63e-02*W+6.60e-01+1.15e-04*W*W)
tPHLckp	drv=1	(1.27e-01*S+1.99*SL*5.37e-03+9.96e-03*B+6.18e-02*W+6.38e-01+(-2.09e-04)*W*W)
	drv=2	(1.27e-01*S+1.02*SL*5.37e-03+9.97e-03*B+6.31e-02*W+6.63e-01+(-2.13e-04)*W*W)
tPHLrnp	drv=1	(1.57e-01*S+2.00*SL*5.37e-03+1.72e-02*B+1.59e-04*W+1.25+(-5.70e-05)*B*B)
	drv=2	(1.57e-01*S+1.04*SL*5.37e-03+1.72e-02*B+2.04e-04*W+1.28+(-5.77e-05)*B*B)
tPLHckp	drv=1	(1.29e-01*S+1.96*SL*5.37e-03+2.92e-02*B+4.96e-02*W+5.09e-01+(-2.46e-04)*B*W)
	drv=2	(1.29e-01*S+9.59e-01*SL*5.37e-03+2.94e-02*B+5.05e-02*W+5.27e-01+(-2.47e-04)*B*W)
tPLHrnp	all	(1.25e-11*S+7.61e-11*SL*5.37e-03+(-4.36e-12)*B+2.05e-12*W+1.01e-10+4.97e-13*S*B
tPDAckp	all	(1.22e-01*S+1.22*SL*5.37e-03+(-2.46e-05)*B+1.92e-03*W+2.51e-01+3.12e-03*S*SL*5.37e-03+7.17e-06*S*B+(-6.00e-05)*SL*5.37e-03*B+1.19e-04*S*W+2.32e-04*SL*5.37e-03*W+6.38e-07*B*W)
tPDArnp	drv=1	(1.24e-01*S+1.13*SL*5.37e-03+2.66e-05*B+3.21e-03*W+2.98e-01+3.07e-04*S*W)
	drv=2	(1.25e-01*S+1.13*SL*5.37e-03+1.25e-05*B+3.22e-03*W+2.98e-01+3.07e-04*S*W)

Characteristic Equation Table (Cont.)

2) Power Equations [Unit: μW/MHz]

(Typical process, 25°C, V_{DD}=2.5V, C_L=10, S=0.2, SA=0.5)

Case	Equation
pipes=0, drv=1	((-7.20)*B+(-14.53)*W+153.33+1.32*B*W)
pipes=0, drv=2	((-7.15)*B+(-14.38)*W+152.61+1.33*B*W)
pipes=1, drv=1	((-3.08)*B+(-5.77)*W+84.87+9.80e-01*B*W)
pipes=1, drv=2	((-3.04)*B+(-5.80)*W+87.52+9.86e-01*B*W)

3) Size Equations [Unit: μm]

Type	Case	Equation
Width	pipes=0, drv=1	(2.03e-02*B+16.06*W+63.05+(-1.19e-03)*B*W)
	pipes=0, drv=2	(2.03e-02*B+16.06*W+64.05+(-1.19e-03)*B*W)
	pipes=1, drv=1	(2.03e-02*B+16.06*W+116.05+(-1.19e-03)*B*W)
	pipes=1, drv=2	(2.03e-02*B+16.06*W+117.05+(-1.19e-03)*B*W)
Height	pipes=0	(11.00*B+(-1.25e-09)*W+22.00+1.86e-11*B*W)
	pipes=1	(11.00*B+(-1.08e-09)*W+33.00+1.55e-11*B*W)

PLL

6

Contents

PLL2013X 6-1

General Description

The PLL2013X is a Phase-Locked Loop (PLL) Frequency Synthesizer constructed in CMOS on single monolithic structure. The PLL macrofunctions provide frequency multiplication capabilities. The output clock frequency Fout is related to the reference input clock frequency Fin (XTALIN) by the following equation:

$$Fout = (m \times Fin) / (p \times 2^S)$$

Where, Fout is the output clock frequency. Fin is the reference input clock frequency. m, p and s are the values for programmable dividers. PLL2013X consists of a Phase/Frequency Detector (PFD), a Charge Pump, an External Loop Filter, a Voltage Controlled Oscillator (VCO), a 6-bit Pre-divider, an 8-bit Main divider and a 2-bit Post Scaler as shown in Figure 6-1

Features

- 0.25μm CMOS device technology
- 2.5V single power supply
- Output frequency range: 20-170MHz
- Jitter: ±150 ps at 170MHz
- Duty ratio: 45% to 55% (All tuned range)
- Frequency changed by programmable dividers
- Provision for 14.318MHz crystal oscillator buffer (option)
- Lock detector (option)
- Power down mode

Block Diagram

Figure 6-1 Phase Locked Loop Block Diagram



NOTE: X-tal oscillator and Lock detector are optional block. If customer concerns about this block - xtal buffer or lock detector, refer to next chapter.

Pin Description

NAME	I/O TYPE	I/O PAD	PIN DESCRIPTION
VDDD	Digital Power	vddd	Digital power supply
VSSD	Digital Ground	vssd	Digital ground
VDDA	Analog Power	vdda	Analog power supply
VSSA	Analog Ground	vssa	Analog ground
VBB	Analog sub bias /Digital sub bias	vbba	Analog / Digital sub bias
FIN	Digital Input	pic_bb	Reference Frequency Input
FILTER	Analog Output	poa_bb	Pump out is connected to Filter. A capacitor is connected between the pin and analog ground.
FOUT	Digital Output	pot8_bb	20MHz~170MHz clock output
PWRDN	Digital Input	pic_bb	FSPLL clock power down. - When PWRDN is High, PLL do not operate. - If PWRDN is not used, it should be tied to VSS.
P[5:0]	Digital Input	pic_bb	The values for 6bit programmable pre-divider.
M[7:0]	Digital Input	pic_bb	The values for 8bit programmable main divider.
S[1:0]	Digital Input	pic_bb	The values for 2bit programmable post scaler.

Figure 6-2 Core Configuration



Absolute Maximum Ratings (Ta=25°C)

Characteristics	Symbol	Value	Unit	Applicable Pin
Supply voltage	VDDD, VDDA	3.3	V	VDDD,VDDA,VSSD, VSSA,VBB
Voltage on any digital pin	Vin	VSSD-0.25 to VDDD+0.25	V	P[5:0],M[7:0],S[1:0] PWRDN
Operating temperature	Topr	0 to 70	°C	-
Storage temperature	Tstg	-45 to 125	°C	-

NOTES*:*

1. Absolute maximum rating specifies the values beyond which the device may be damaged permanently. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Each condition value is applied with the other values kept within the following operating conditions and function operation under any of these conditions is not implied.
2. All voltages are measured with respect to VSS unless otherwise specified.
3. 100pF capacitor is discharged through a 1.5kΩ resistor (human body model)

Recommended Operating Conditions

Characteristics	Symbol	Min	Typ	Max	Unit
Supply voltage	VDDD - VDDA	-0.1		+0.1	V
Oscillator frequency	Fosc		14.318		MHz
External loop filter capacitance	LF		820		pF
Operating temperature	Topr	0		70	°C

NOTE: It is strongly recommended that all the supply pins (VDDA, VDDD) be powered from the same operating supply voltage to avoid power latch-up.

DC Electrical Characteristics

Characteristics	Symbol	Min	Typ	Max	Unit
Operating voltage	VDDD/VDDA	2.375	2.5	2.625	V
Digital input voltage high	V_{IH}	2.0			V
Digital input voltage low	V_{IL}			0.8	V
Dynamic current	Idd			3	mA
Power down current	Ipd			50	µA

AC Electrical Characteristics

Characteristics	Symbol	Min	Typ	Max	Unit
Crystal frequency	F_{XTAL}		14.318		MHz
Input Frequency	F_{IN}	5		40	MHz
Output clock frequency	F_{OUT}	20		170	Mhz
Input clock duty cycle	T_{ID}	40		60	%
Output clock duty cycle (at 170MHz)	T_{OD}	45		55	%
Input glitch pulse width	T_{IGP}	1			ns
Locking time	T_{LT}			150	µs
Jitter, cycle to cycle	T_{JCC}	-150		+150	ps

NOTE: It is strongly recommended that input signal is not generated glitch, but if customer cannot help generating glitch, customer must carefully considerate the specification.

Functional Description

A PLL is the circuit synchronizing an output signal (generated by an VCO) with a reference or input signal in frequency as well as in phase.

In this application, it includes the following basic blocks.

— The voltage-controlled oscillator to generate the output frequency

— The divider P divides the reference frequency by p

— The divider M divides the VCO output frequency by m

— The divider S divides the VCO output frequency by s

— The phase frequency detector detects the phase difference between the reference frequency and the output frequency (after division) and controls the charge pump voltage.

— The loop filter removes the high frequency components in charge pump voltage and gives smooth and clean control to VCO

The m, p, s values can be programmed by 16bit digital data from the external source. So the PLL can be locked in the desired frequency.

$Fout = (m \times Fin) / (p \times s)$

where

$Fin = 14.318\ MHz,\ \ m = M + 8,\ \ p = P + 2,\ \ s = 2^S$

Table 6-1 Digital Data Format

Main Divider	Pre Divider	Post Scaler
M7, M6, M5, M4, M3, M2, M1, M0	P5, P4, P3, P2, P1, P0	S1, S0

NOTES:

1. S[1]-S[0]: Output frequency scaler
2. M[7]-M[0]: VCO frequency divider
3. P[5]-P[0]: Reference frequency input divider

OUTPUT FREQUENCY EQUATION & TABLE

Frequency equation: $F_{OUT} = \frac{(M+8)}{(P+2)\times 2^{S}} \times F_{IN}$

Table 6-2 Example of Divider Ratio

M7	M6	M5	M4	M3	M2	M1	M0	M	m(M+8)	S1	S0	2^S
0	1	0	1	0	1	0	1	85	93	0	0	1
P6	P5	P4	P3	P2	P1	P0	P	p(P+2)				
0	1	0	1	0	1	0	42	44				

CORE EVALUATION GUIDE

For the embedded PLL, we must consider the test circuits for the embedded PLL core in multiple applications. Hence the following requirements should be satisfied.

— The FILTER and FOUT pins must be bypassed for external test.
— For PLL test (below 2 examples), it is needed to control the dividers - M[7:0], P[5:0] and S[1:0] - that generate multiple clocks.

#1. Registers can be used for easy control of divider values.
#2. N sample bits of 16-bit divider pins can be bypassed for test using MUX.

Figure 6-3 PLL Functional Block Diagram



Figure 6-4 The example of PLL block with dedicated 14.318 MHz XTAL-OSC



XTAL Buffer Cell

Figure 6-5 XTAL PAD Symbol



- A XTAL Buffer cell for PLL is supported MDL111 databook of SEC
- The XTAL must be located between PADA and PADB.
  Enable pin (E) must be HIGH in normal operation.
- PI pin must be connected to VDDD and the PO pin floated.

Lock Detector

Figure 6-6 Lock Detector Block



The built-in lock detector circuit will only work, when it is used in conjunction with PFD block output up/down

signal. (refer to Figure 6-6)
We represent the output of lock detector in the timing diagram. (refer to Figure 6-7)

Figure 6-7 Lock Detector Timing Diagram



PACKAGE CONFIGURATION



PACKAGE PIN DESCRIPTION

NAME	PIN No.	I/O TYPE	PIN DESCRIPTION
VDDD	35,36	DP	Digital power supply
VSSD	33,34	DG	Digital ground
VBB	19,20	AB/DB	Analog / digital sub bias
PWRDN	18	DI	FSPLL clock power down. - When PWRDN is High, PLL do not operate. - If PWRDN is not used, it should be tied to VSS.
P[0]~P[5]	45~48,1,2	DI	Pre-divider input
VDDA	13,14	AP	Analog power supply
VSSA	11,12	AG	Analog ground
XTALIN	15	AI	Crystal external clock input
XTALOUT	16	AO	Xtal buffer output clock
FOUT	23	DO	20MHZ~170MHz clock output
LDOUT	10	DO	Lock detector output
FILTER	17	AO	Pump out is connected to the Filter. A 900pF Capacitor is connected between the pin and analog pin
S[0]~S[1]	32,31	DI	Post scaler input
M[0]~M[7]	37~44	DI	8-bit main divider input
VDDO	28	PP	I/O pad power
VSSO	27	PG	I/O pad power

NOTES:

1. I/O TYPE PP and PG denote PAD power and PAD ground respectively.

2. XTALIN, XTALOUT, LDOUT is test pin for PLL in Samsung.

PLL Components

Figure 6-8 is the block diagram of the components of a PLL: the phase detector, charge pump, voltage controlled oscillator, and loop filter.

In Samsung technology, the loop filter is implemented as external components close to the chip.

Figure 6-8 PLL Functional Block Diagram



■Phase detector:

The phase detector monitors the phase difference between the Fref and Fvco, and generates a control signal when it detects difference between the two.

If the Fref frequency is higher then the Fvco frequency, its falling edge occurs before (lead) the falling edge of the Fvco output. When this occurs the phase detector signals the VCO to increase the frequency of the on-chip clock. If the falling edge of the Fref occurs after (lag) the falling edge of the Fvco output, the detector signals the VCO to decrease on-chip clock frequency. Figure 6-9 illustrates the lead and lag conditions.

If the frequencies of the Fref and Fvco are the same, the detect or does not generate a control signal, so the frequencies remain the same.

Figure 6-9 Lead and Lag Clocking Relationship



■Charge Pump:

The charge pump converts the phase detector control signal to a charge in voltage across the external filter that drives the VCO. As the Voltage Controlled Oscillator decreases, or increases, If the voltage remains constant, the frequency of the oscillator remains constant.

■Loop Filter:

The control signal that the phase detector generates for the charge pump may generate large excursions (ripples) each time the VCO output is compared to the system clock. To avoid overloading the VCO, a low pass filter samples and filters the high-frequency components out of the control signal. The filter is typically a single-pole RC filter consisting of a resistor and capacitor.

■ Voltage Controlled Oscillator (VCO):

The output voltage from the loop filter drives the VCO, causing its oscillation frequency to increase or decrease as a function of variations in voltage. When the VCO output matches the system clock in frequency and phase, the phase detector stops sending a control signal to the charge pump, which in turn stabilizes the input voltage to the loop filter. The VCO frequency then remains constant, and the PLL remains locked onto the system clock.

Frequency Synthesis

Frequency synthesis uses the system clock as a base frequency to generate higher/lower frequency clocks for internal logic.

For high speed applications in high-end designs, transmission line effects cause problems because of parasitic and impedance mismatch among various on-board components. These problems can be eliminated by moving the high frequency to the chip level. On-chip clocks that are faster than the external system clock can be synthesized by inserting a divider in the feedback path. The divider is placed after voltage controlled oscillator, as illustrated in Figure 6-11. The signal is running at M times the system clock frequency, so the PLL matches the divider signal output to the system clock. This configuration reduces the problem of interfacing to the system clock on the board, and it reduces the noise generated by the system clock oscillator and driver for all the components in the system.

Design Considerations

The following design considerations apply:

- Phase tolerance and jitter are independent of the PLL frequency.
- Jitter is affected by the noise frequency in the power (VDDD/VSSD, VDDA/VSSA). It increases when the noise level increases.
- A CMOS-level input reference clock is recommend for signal compatibility with the PLL circuit. Other levels such as TTL may degrade the tolerances.
- The used of two, or more PLLs requires special design considerations. Please consult your application engineer for more information.
- The following apply to the noise level, which can be minimized by using good analog power and ground isolation techniques in the system:
  - Use wide PCB traces for POWER (VDDD/VSSD, VDDA/VSSA, VBB) connections to the PLL core.
  - Separate the traces from the chip's VDDD/VSSD, VDDA/VSSA supplies.
  - Use proper VDDD/VSSD, VDDA/VSSA de-coupling.
  - Use good power and ground sources on the board.
  - Use power VBB for minimize substrate noise.
- The PLL core should be placed as close as possible to the dedicated loop filter and analog power and ground pins.
- It is inadvisable to locate noise-generating signals, such as data buses and high-current outputs, near the PLL I/O cells.
- Other related I/O signals should be placed near the PLL I/O but do not have any pre-defined placement restriction.

PLL Specification

We appreciate your interest in our products. If you have further questions, please specify in the attached form. Thank you very much.

Parameter	Min	Typ	Max	Unit	Remarks
Supply voltage					
Output frequency range					
Input frequency range					
Cycle-to-cycle jitter					
Lock up time					
Dynamic current					
Standby current					
Output clock duty ratio					
Long term jitter					
Output slew rate					

- Do you need XTAL driver buffer in PLL core?
  If you need it, what is the crystal frequency range?
  If not, What is the input frequency range?
- Do you need the lock detector?
- Do you need the I/O cell of Samsung?
- Do you need the external pin for PLL test?
- What is the main frequency and frequency range?
- How many FSPLLs do you use in your system?
- What is output loading?
- Could you internal/external pin configurations as required?
- Specially requested function list: