

SANYO

No.3098

2SC4492

NPN Triple Diffused Planar Silicon Transistor

High-Voltage Amp,
High-Voltage Switching Applications**Features**


- High breakdown voltage
- Small c_{ob}
- High reliability (adoption of HVP process)
- Intended for high-density mounting (Suitable for sets whose height is restricted)









Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$


			unit
Collector to Base Voltage	V_{CBO}	600	V
Collector to Emitter Voltage	V_{CEO}	600	V
Emitter to Base Voltage	V_{EBO}	7	V
Collector Current	I_C	20	mA
Peak Collector Current	i_{cp}	60	mA
Collector Dissipation	P_C	1.65	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics at $T_a = 25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = 600\text{V}, I_E = 0$			1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5\text{V}, I_C = 0$			1	μA
DC Current Gain	$h_{FE}(1)$	$V_{CE} = 5\text{V}, I_C = 2\text{mA}$	20		50	
	$h_{FE}(2)$	$V_{CE} = 5\text{V}, I_C = 10\text{mA}$	10			
Gain-Bandwidth Product	f_T	$V_{CE} = 10\text{V}, I_C = 2\text{mA}$		40		MHz
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = 10\text{mA}, I_B = 2\text{mA}$			1	V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = 10\text{mA}, I_B = 2\text{mA}$			1.5	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}, I_E = 0$	600			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, R_{BE} = \infty$	600			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	7			V
Output Capacitance	c_{ob}	$V_{CB} = 100\text{V}, f = 1\text{MHz}$		1.6		pF

Package Dimensions 2049B
(unit: mm)





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.