

**STK401-080**

## AF Power Amplifier (Split Power Supply) (45W+45W min, THD = 0.4%)

### Overview

The STK401-080 is a thick-film audio power amplifier IC belonging to a series in which all devices are pin compatible. This allows a single PCB design to be used to construct amplifiers of various output capacity simply by changing hybrid ICs. Also, this series is part of a new, larger series that comprises mutually similar devices with the same pin compatibility. This makes possible the development of a 2-channel amplifier from a 3-channel amplifier using the same PCB. In addition, this new series features  $6/3\Omega$  drive in order to support the low impedance of modern speakers.


### Features

- Pin compatible  
STK400-000 series (3-channel/single package)  
↓  
STK401-000 series (2-channel/single package)
- Output load impedance  $R_L = 6/3\Omega$  supported
- New pin configuration  
Pin configuration has been grouped into individual blocks of inputs, outputs and supply lines, minimizing the adverse effects of pattern layout on operating characteristics.
- Few external components  
In comparison with existing series, external bootstrap resistors and capacitors can be eliminated.

### Package Dimensions

unit: mm

4134



## Specifications

### Maximum Ratings at $T_a = 25^{\circ}\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Maximum supply voltage	$V_{CC\text{ max}}$		$\pm 45$	V
Thermal resistance	$\theta_{j-c}$	Per power transistor	1.7	$^{\circ}\text{C/W}$
Junction temperature	$T_J$		150	$^{\circ}\text{C}$
Operating substrate temperature	$T_c$		125	$^{\circ}\text{C}$
Storage temperature	$T_{stg}$		$-30$ to $+125$	$^{\circ}\text{C}$
Available time for load short-circuit	$t_s$	$V_{CC} = \pm 31\text{V}$ , $R_L = 6\Omega$ , $f = 50\text{Hz}$ , $P_O = 45\text{W}$	1	s

### Operating Characteristics at $T_a = 25^{\circ}\text{C}$ , $R_L = 6\Omega$ (noninductive load), $R_g = 600\Omega$ , $V_G = 40\text{dB}$

Parameter	Symbol	Conditions	min	typ	max	Unit
Quiescent current	$I_{CCO}$	$V_{CC} = \pm 37\text{V}$	20	60	100	mA
Output power	$P_{O(1)}$	$V_{CC} = \pm 31\text{V}$ , $f = 20\text{Hz}$ to $20\text{kHz}$ , $\text{THD} = 0.4\%$	45	50	–	W
	$P_{O(2)}$	$V_{CC} = \pm 25\text{V}$ , $f = 1\text{kHz}$ , $\text{THD} = 1.0\%$ , $R_L = 3\Omega$	45	50	–	W
Total harmonic distortion	$\text{THD}(1)$	$V_{CC} = \pm 31\text{V}$ , $f = 20\text{Hz}$ to $20\text{kHz}$ , $P_O = 1.0\text{W}$	–	–	0.4	%
	$\text{THD}(2)$	$V_{CC} = \pm 31\text{V}$ , $f = 1\text{kHz}$ , $P_O = 5.0\text{W}$	–	0.01	–	%
Frequency response	$f_L, f_H$	$V_{CC} = \pm 31\text{V}$ , $P_O = 1.0\text{W}$ , $_{-3}^{+0}\text{dB}$	–	20 to 50k	–	Hz
Input impedance	$r_i$	$V_{CC} = \pm 31\text{V}$ , $f = 1\text{kHz}$ , $P_O = 1.0\text{W}$	–	55	–	$\text{k}\Omega$
Output noise voltage	$V_{NO}$	$V_{CC} = \pm 37\text{V}$ , $R_g = 10\text{k}\Omega$	–	–	1.2	mVrms
Neutral voltage	$V_N$	$V_{CC} = \pm 37\text{V}$	$-70$	0	$+70$	mV


#### Notes.

All tests are measured using a constant-voltage supply unless otherwise specified.


Available time for load short-circuit and output noise voltage are measured using the transformer supply specified below.

The output noise voltage is the peak value of an average-reading meter with an rms value scale (VTVM). A regulated AC supply (50Hz) should be used to eliminate the effects of AC primary line flicker noise.


### Specified Transformer Supply (MG-200 or Equivalent)



## Equivalent Circuit



## Sample PCB Layout for 2-Channel or 3-Channel Amplifiers



Copper (Cu) foil surface  
Pin 6 of STK400-000 series devices corresponds to pin 1 of STK401-000 series devices.




# Series Configuration


3-channel amplifier type Nos.	Rated output	2-channel amplifier type Nos.	Rated output	THD [%] f = 20Hz to 20kHz	Supply voltage [V] <sup>1</sup>			
					V <sub>CC</sub> max1	V <sub>CC</sub> max2	V <sub>CC</sub> 1	V <sub>CC</sub> 2
STK400-010	10W × 3	STK401-010	10W × 2	0.4	—	±26	±17	±14
STK400-020	15W × 3	STK401-020	15W × 2		—	±29	±20	±16
STK400-030	20W × 3	STK401-030	20W × 2		—	±34	±23	±19
STK400-040	25W × 3	STK401-040	25W × 2		—	±36	±25	±21
STK400-050	30W × 3	STK401-050	30W × 2		—	±39	±26	±22
STK400-060	35W × 3	STK401-060	35W × 2		—	±41	±28	±23
STK400-070	40W × 3	STK401-070	40W × 2		—	±44	±30	±24
STK400-080	45W × 3	STK401-080	45W × 2		—	±45	±31	±25
STK400-090	50W × 3	STK401-090	50W × 2		—	±47	±32	±26
STK400-100	60W × 3	STK401-100	60W × 2		—	±51	±35	±27
STK400-110	70W × 3	STK401-110	70W × 2		±56.0	—	±38	—
—	—	STK401-120	80W × 2		±61.0	—	±42	—
—	—	STK401-130	100W × 2		±65.0	—	±45	—
—	—	STK401-140	120W × 2		±74.0	—	±51	—

1. V<sub>CC</sub> max1 (R<sub>L</sub> = 6Ω), V<sub>CC</sub> max2 (R<sub>L</sub> = 3 to 6Ω), V<sub>CC</sub>1 (R<sub>L</sub> = 6Ω), V<sub>CC</sub>2 (R<sub>L</sub> = 3Ω)

## Sample Designs using a Common PCB



## External Circuit Diagram



## Heatsink Design Considerations

The heatsink thermal resistance,  $\theta_{c-a}$ , required to dissipate the STK401-080 device total power dissipation,  $P_d$ , is determined as follows:

Condition 1: IC substrate temperature not to exceed 125°C.

$$P_d \times \theta_{c-a} + T_a < 125^\circ\text{C} \quad (1)$$

where  $T_a$  is the guaranteed maximum ambient temperature.

Condition 2: Power transistor junction temperature,  $T_j$ , not to exceed 150°C.

$$P_d \times \theta_{c-a} + P_d/N \times \theta_{j-c} + T_a < 150^\circ\text{C} \quad (2)$$

where  $N$  is the number of power transistors and  $\theta_{j-c}$  is the power transistor thermal resistance per transistor. Note that the power dissipated per transistor is the total,  $P_d$ , divided evenly among the  $N$  power transistors.

Expressions (1) and (2) can be rewritten making  $\theta_{c-a}$  the subject.

$$\theta_{c-a} < (125 - T_a)/P_d \quad (1)'$$

$$\theta_{c-a} < (150 - T_a)/P_d - \theta_{j-c}/N \quad (2)'$$

The heatsink required must have a thermal resistance that simultaneously satisfies both expressions.

The heatsink thermal resistance can be determined from (1)' and (2)' once the following parameters have been defined.

- Supply voltage
- Load resistance
- Guaranteed maximum ambient temperature

The total device power dissipation when STK401-080  $V_{CC} = \pm 31\text{V}$  and  $R_L = 6\Omega$ , for a continuous sine wave signal, is a maximum of 65.5W, as shown in Figure 1.

When estimating the power dissipation for an actual audio signal input, the rule of thumb is to select  $P_d$  corresponding to 1/10  $P_{O \text{ max}}$  (within safe limits) for a continuous sine wave input. For example, from Figure 1,

$$P_d = 40.5\text{W} \text{ (for } 1/10 P_{O \text{ max}} = 4.5\text{W)}$$

The STK401-080 has 4 power transistors, and the thermal resistance per transistor,  $\theta_{j-c}$ , is 1.7°C/W. If the guaranteed maximum ambient temperature,  $T_a$ , is 50°C, then the required heatsink thermal resistance,  $\theta_{c-a}$ , is:

$$\text{From expression (1)': } \theta_{c-a} < (125 - 50)/40.5 < 1.85$$

$$\text{From expression (2)': } \theta_{c-a} < (150 - 50)/40.5 - 1.7/4 < 2.04$$

Therefore, to satisfy both expressions, the required heatsink must have a thermal resistance less than 1.85°C/W.

Similarly, when STK401-080  $V_{CC} = \pm 25V$  and  $R_L = 3\Omega$ , from Figure 2:

$$P_d = 47W \text{ (for } 1/10 P_{O \text{ max}} = 4.5W)$$

$$\text{From expression (1)'}: \theta_{c-a} < (125 - 50)/47 < 1.59$$

$$\text{From expression (2)'}: \theta_{c-a} < (150 - 50)/47 - 1.7/4 < 1.70$$

Therefore, to satisfy both expressions, the required heat-sink must have a thermal resistance less than  $1.59^\circ C/W$ .

This heatsink design example is based on a constant-voltage supply, and should be verified within your specific set environment.

Figure 1.  $P_d - P_O$







Figure 2.  $P_d - P_O$




THD —  $P_O$




THD —  $P_O$








$P_O - V_{in}$



$P_O - f$







- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees, jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of June, 1997. Specifications and information herein are subject to change without notice.