



## 0.5 AMP NEGATIVE VOLTAGE REGULATOR




Pin 1 – Ground  
Pin 2 –  $V_{OUT}$   
Case –  $V_{IN}$

**H Package – TO-39**



Pin 1 – Ground  
Pin 2 –  $V_{IN}$   
Case –  $V_{OUT}$

**SMD Package - SMD1  
CERAMIC SURFACE MOUNT**



**8 Pin J Package**

### FEATURES

- **OUTPUT CURRENT UP TO 0.5A**
- **OUTPUT VOLTAGES OF -5, -12, -15V**
- **0.01% / V LINE REGULATION**
- **0.3% / A LOAD REGULATION**
- **THERMAL OVERLOAD PROTECTION**
- **SHORT CIRCUIT PROTECTION**
- **OUTPUT TRANSISTOR SOA PROTECTION**
- **1% VOLTAGE TOLERANCE (–A VERSIONS)**

### Order Information

Part Number	H-Pack (TO-39)	J-Pack CERPDP	SMD-Pack SMD1	Temp. Range
IP79MxxAzz	✓	✓	✓	-55 to +150°C
IP79Mxxzz	✓	✓	✓	"
IP120MAzz-xx	✓		✓	"
IP120Mzz-xx	✓		✓	"

#### Note:

xx = Voltage Code (05, 12, 15)  
eg. IP79M05J  
zz = Package Code (H, J)  
IP120MAH-12

### DESCRIPTION

The IP120MA and IP79M00A series of voltage regulators are fixed output regulators intended for local, on-card voltage regulation. These devices are available in -5, -12, and -15 volt options and are capable of delivering in excess of 500mA over temperature.

The A suffix devices are fully specified at 0.5A, provide 0.01% / V line regulation, 0.3% / A load regulation, and  $\pm 1\%$  output voltage tolerance at room temperature. Protection features include safe operating area, current limiting and thermal shutdown.

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ unless otherwise stated)

$V_I$	DC Input Voltage (for $V_O = -5, -12, -15\text{V}$ )	-35V
$P_D$	Power Dissipation	Internally limited
$R_{\theta JC}$	Thermal Resistance Junction to Case	– H Package 20°C / W – SMD Package TBA°C / W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	– H Package 120°C / W – J Package 119°C / W
$T_J$	Operating Junction Temperature Range	–55 to 150°C
$T_{stg}$	Storage Temperature	–65 to 150°C

Note 1. Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation  $P_{MAX}$  of 2W for the H-Package, 1.05W for the J-Package and 15W for the SG-Package.

## ELECTRICAL CHARACTERISTICS

Parameter		Test Conditions		IP79M05A IP120MA-05			IP79M05 IP120M-05			Units												
				Min.	Typ.	Max.	Min.	Typ.	Max.													
V <sub>O</sub>	Output Voltage	I <sub>O</sub> = 100mA      V <sub>IN</sub> = -10V		-4.95	-5	-5.05	-4.8	-5	-5.2	V												
		I <sub>O</sub> = 5mA to 350mA P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = -7V to -25V      T <sub>J</sub> = -55 to 150°C		-4.85			-5.15				-4.75			-5.25								
ΔV <sub>O</sub>	Line Regulation	I <sub>O</sub> = 350mA	V <sub>IN</sub> = -7V to -25V	3			10			50			mV									
			V <sub>IN</sub> = -8V to -18V T <sub>J</sub> = -55 to 150°C	3			10			30												
ΔV <sub>O</sub>	Load Regulation	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -10V      T <sub>J</sub> = -55 to 150°C		5			50			100			mV									
I <sub>Q</sub>	Quiescent Current	V <sub>IN</sub> = -10V      I <sub>O</sub> = 350mA T <sub>J</sub> = -55 to 150°C		1			2			1			2			mA						
ΔI <sub>Q</sub>	Quiescent Current Change	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -10V      T <sub>J</sub> = -55 to 150°C		0.1			0.4			0.4			mA									
		I <sub>O</sub> = 200mA      V <sub>IN</sub> = -8V to -25V T <sub>J</sub> = -55 to 150°C		0.1			0.4			0.4												
V <sub>N</sub>	Output Noise Voltage	f = 10Hz to 100kHz		40			400			400			μV									
$\frac{\Delta V_{IN}}{\Delta V_O}$	Ripple Rejection	f = 120Hz	I <sub>O</sub> = 300mA	65	80		54			dB												
		V <sub>IN</sub> = -8V to -18V	I <sub>O</sub> = 100mA T <sub>J</sub> = -55 to 150°C	65	80		54															
Dropout Voltage		I <sub>O</sub> = 350mA		1.1			2.3			2.3			V									
I <sub>sc</sub>	Short Circuit Current	V <sub>IN</sub> = -35V		300			600			300			600			mA						
I <sub>pk</sub>	Peak Output Current	V <sub>IN</sub> = -10V		0.5			1.0			1.4			0.5			1.0			1.6			A
Average Temperature Coefficient of V <sub>O</sub>		I <sub>O</sub> = 5mA		0.5			2.0			0.5						mV /°C						

- 1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.
- 2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SMD1 Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter		Test Conditions		IP79M12A IP120MA-12			IP79M12 IP120M-12			Units
				Min.	Typ.	Max.	Min.	Typ.	Max.	
V <sub>O</sub>	Output Voltage	I <sub>O</sub> = 100mA      V <sub>IN</sub> = -19V		-11.88	-12	-12.12	-11.5	-12	-12.5	V
		I <sub>O</sub> = 5mA to 350mA P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = -14.5V to -30V T <sub>J</sub> = -55 to 150°C		-11.64		-12.36		-11.4	-12.6	
ΔV <sub>O</sub>	Line Regulation	I <sub>O</sub> = 350mA	V <sub>IN</sub> = -14.5V to -30V	4		18	80			mV
			V <sub>IN</sub> = -15V to -25V T <sub>J</sub> = -55 to 150°C	4		18	50			
ΔV <sub>O</sub>	Load Regulation	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -19V      T <sub>J</sub> = -55 to 150°C		10		60	240			mV
I <sub>Q</sub>	Quiescent Current	V <sub>IN</sub> = -19V      I <sub>O</sub> = 350mA T <sub>J</sub> = -55 to 150°C		1.5		3	1.5		3	mA
ΔI <sub>Q</sub>	Quiescent Current Change	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -19V      T <sub>J</sub> = -55 to 150°C		0.1		0.4	0.4			mA
		I <sub>O</sub> = 200mA      V <sub>IN</sub> = -14.5V to -30V T <sub>J</sub> = -55 to 150°C		0.1		0.4	0.4			
V <sub>N</sub>	Output Noise Voltage	f = 10Hz to 100kHz		96		960	960			μV
$\frac{\Delta V_{IN}}{\Delta V_O}$	Ripple Rejection	f = 120Hz	I <sub>O</sub> = 300mA	58	72		54			dB
		V <sub>IN</sub> = -15V to -25V	I <sub>O</sub> = 100mA	58	72		54			
			T <sub>J</sub> = -55 to 150°C							
	Dropout Voltage	I <sub>O</sub> = 350mA		1.1		2.3	2.3			V
I <sub>sc</sub>	Short Circuit Current	V <sub>IN</sub> = -35V		300		600	300		600	mA
I <sub>pk</sub>	Peak Output Current	V <sub>IN</sub> = -19V		0.5	1.0	1.4	0.5	1.0	1.6	A
Average Temperature Coefficient of V <sub>O</sub>		I <sub>O</sub> = 5mA		1.2		4.8	1.2			mV/°C

- 1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.
- 2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SMD Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter		Test Conditions		IP79M15A IP120MA-15			IP79M15 IP120M-15			Units
				Min.	Typ.	Max.	Min.	Typ.	Max.	
V <sub>O</sub>	Output Voltage	I <sub>O</sub> = 100mA      V <sub>IN</sub> = -23V		-14.85	-15	-15.15	-14.4	-15	-15.6	V
		I <sub>O</sub> = 5mA to 350mA P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = -17.5V to -30V T <sub>J</sub> = -55 to 150°C		-14.55		-15.45		-14.25	-15.75	
ΔV <sub>O</sub>	Line Regulation	I <sub>O</sub> = 350mA	V <sub>IN</sub> = -17.5V to -30V	4		22	80			mV
			V <sub>IN</sub> = -18V to -28V T <sub>J</sub> = -55 to 150°C	4		22	50			
ΔV <sub>O</sub>	Load Regulation	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -23V      T <sub>J</sub> = -55 to 150°C		12		75	240			mV
I <sub>Q</sub>	Quiescent Current	V <sub>IN</sub> = -23V      I <sub>O</sub> = 350mA T <sub>J</sub> = -55 to 150°C		1.5		3	1.5		3	mA
ΔI <sub>Q</sub>	Quiescent Current Change	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -23V      T <sub>J</sub> = -55 to 150°C		0.1		0.4	0.4			mA
		I <sub>O</sub> = 200mA      V <sub>IN</sub> = -17.5V to -30V T <sub>J</sub> = -55 to 150°C		0.1		0.4	0.4			
V <sub>N</sub>	Output Noise Voltage	f = 10Hz to 100kHz		120		1200	1200			μV
$\frac{\Delta V_{IN}}{\Delta V_O}$	Ripple Rejection	f = 120Hz	I <sub>O</sub> = 300mA	57	70		54			dB
		V <sub>IN</sub> = -18.5V to -28.5V	I <sub>O</sub> = 100mA	57	70	54				
			T <sub>J</sub> = -55 to 150°C							
Dropout Voltage		I <sub>O</sub> = 350mA		1.1		2.3	2.3			V
I <sub>sc</sub>	Short Circuit Current	V <sub>IN</sub> = -35V		300		600	300		600	mA
I <sub>pk</sub>	Peak Output Current	V <sub>IN</sub> = -23V		0.5	1.0	1.4	0.5	1.0	1.6	A
Average Temperature Coefficient of V <sub>O</sub>		I <sub>O</sub> = 5mA		1.5		6.0	1.5			mV /°C

- 1) All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF.  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.
- 2) Test Conditions unless otherwise stated: T<sub>J</sub> = 25°C  
 P<sub>MAX</sub> = 2W for H Package (TO-39)  
 P<sub>MAX</sub> = 1.05W for J Package (CERDIP)  
 P<sub>MAX</sub> = 15W for SMD Package (SMD1)