


0.5 AMP NEGATIVE ADJUSTABLE VOLTAGE REGULATOR



Pin 1 – ADJ.
Pin 2 – V_{OUT}
Pin 3 – V_{IN}

H Package – TO-39

FEATURES

- –1.2V TO 47V OUTPUT VOLTAGE RANGE
- 0.5A OUTPUT CURRENT
- 1% OUTPUT VOLTAGE TOLERANCE
- 0.5% / A LOAD REGULATION
- 0.01% / V LINE REGULATION
- 0.02% / W THERMAL REGULATION
- INTERNAL PROTECTION

Internal current and power limiting coupled with true thermal limiting prevents device damage due to overloads or shorts, even if the regulator is not fastened to a heat sink.

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}\text{C}$ unless otherwise stated)

V_{I-O}	Input - Output Differential Voltage	– Standard – HV Series	40V 50V
I_O	Output Current		Internally limited
P_D	Power Dissipation		Internally limited
T_J	Operating Junction Temperature Range		–55 to +150°C
T_{STG}	Storage Temperature		–65 to 150°C
T_J	Lead temperature		300°C

Parameter	Test Conditions	IP137MAHV IP137MA			IP137MHV , IP137M LM137HV , LM137			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V_{REF} Reference Voltage	$I_{OUT} = 10mA$	-1.238	-1.25	-1.262	-1.225	-1.25	-1.275	V
	$I_{OUT} = 10mA$ to I_{MAX} $V_{IN} - V_{OUT} = 3V$ to V_{MAX} $P \leq P_{MAX}$ $T_J = -55$ to $150^{\circ}C$	-1.220	-1.25	-1.280	-1.200	-1.25	-1.300	V
$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$ Line Regulation 1	$V_{IN} - V_{OUT} = 3V$ to V_{MAX} $T_J = -55$ to $150^{\circ}C$	0.005	0.010		0.010	0.020		%/V
		0.010	0.030		0.020	0.050		
$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ Load Regulation 1	$I_{OUT} = 10mA$ to I_{MAX} $T_J = -55$ to $150^{\circ}C$	$V_{OUT} \leq 5V$		5	25	15	25	mV
		$V_{OUT} \geq 5V$		0.1	0.5	0.3	0.5	%
	$I_{OUT} = 10mA$ to I_{MAX} $T_J = -55$ to $150^{\circ}C$	$V_{OUT} \leq 5V$		10	50	20	50	mV
		$V_{OUT} \geq 5V$		0.2	1	0.3	1	%
Thermal Regulation	$t_p = 10ms$ $T_A = 25^{\circ}C$	0.002	0.020		0.002	0.02		%/W
Ripple Rejection	$V_{OUT} = -10V$ $f = 120Hz$ $T_J = -55$ to $150^{\circ}C$	$C_{ADJ} = 0$		60	66	60		dB
		$C_{ADJ} = 10\mu F$		70	80	66	77	dB
I_{ADJ} Adjust Pin Current	$T_J = -55$ to $150^{\circ}C$	65	100		65	100		μA
ΔI_{ADJ} Adjust Pin Current Change	$T_J = -55$ to $+150^{\circ}C$	$I_{OUT} = 10mA$ to I_{MAX}		0.2	2	0.5	5	μA
		$V_{IN} - V_{OUT} = 3V$ to $40V$		1.0	5	2	5	
		$V_{IN} - V_{OUT} = 3V$ to $50V$ (HV SERIES)		2.0	6	3	6	
I_{MIN} Minimum Load Current	$T_J = -55$ to $150^{\circ}C$	$V_{IN} - V_{OUT} \leq 40V$		2.5	5	2.5	5	mA
		$V_{IN} - V_{OUT} \leq 10V$		1.2	3	1.2	3	
I_{CL} Current Limit	$T_J = -55$ to $150^{\circ}C$	$V_{IN} - V_{OUT} \leq 15V$		0.50	0.80	1.5	0.50	A
		$V_{IN} - V_{OUT} = 40V$		0.15	0.17		0.15	
		$V_{IN} - V_{OUT} = 50V$ (HV SERIES)		0.10	0.17	0.5	0.10	
$\frac{\Delta V_{OUT}}{\Delta TEMP}$ Temperature Stability	$T_J = -55$ to $150^{\circ}C$	0.6	1.5		0.6			%
$\frac{\Delta V_{OUT}}{\Delta TIME}$ Long Term Stability	$T_A = +125^{\circ}C$ $t = 1000$ Hrs	0.3	1		0.3	1		%
e_n RMS Output Noise (% of V_{OUT})	$f = 10$ Hz to 10 kHz $T_A = 25^{\circ}C$	0.003			0.003			%
$R_{\theta JC}$ Thermal Resistance Junction to Case	H Package	12	15		12	15		$^{\circ}C/W$

1) Regulation is measured at constant junction temperature, using pulse testing at a low duty cycle. Changes in output voltage due to heating effects are covered under thermal regulation specifications. Load regulation is measured at a point $1/8$ " from the bottom of the package for the TO-3 and TO-66 packages, at the junction of the wide and narrow portion of the output lead for the SMD1package, and $1/8$ " below the base of the package on the output pin of the TO-257 package.

2) Test Conditions unless otherwise stated: $V_{IN} - V_{OUT} = 5V$, $I_{OUT} = 0.1A$, $P_{MAX} = 2W$, $I_{MAX} = 0.5A$
 $V_{MAX} = 40V$ for standard series, $50V$ for HV series.