


Chip Type 2C2857
Geometry 0011
Polarity NPN

Generic Packaged Part:
2N2857


[Request Quotation](#)

Chip type **2C2857** by Semicoa Semiconductors provides performance similar to these devices.

Part Numbers:

[2N2857](#), [2N2857UB](#), SD2857, SD2857F, SQ2857, SQ2857F

Product Summary:

APPLICATIONS: Designed for use in high-gain, low noise amplifier, oscillator, mixer and UHF converters.

Features: $f_t = 1.2 \text{ GHz (typ)}$ at 5 mA/6V

Mechanical Specifications

Metallization	Top	Al - 15 kÅ min.
	Backside	Au - 6.5 kÅ nom.
Bonding Pad Size	Emitter	2.3 mils x 2.3 mils
	Base	2.3 mils x 2.3 mils
Die Thickness	8 mils nominal	
Chip Area	16 mils x 16 mils	
Top Surface	Silox Passivated	

Electrical Characteristics

 $T_A = 25^\circ\text{C}$

Parameter	Test conditions	Min	Max	Unit
BV_{CEO}	$I_C = 3.0 \text{ mA}$	15	---	V dc
BV_{CBO}	$I_C = 1.0 \mu\text{A}$	30	---	V dc
BV_{EBO}	$I_E = 10 \mu\text{A}$	2.5	---	V dc
I_{CBO}	$V_{CB} = 15 \text{ V}$	---	0.01	$\mu\text{A dc}$
h_{FE}	$I_C = 3.0 \text{ mA dc}, V_{CE} = 1.0 \text{ V}$	30	150	---

Due to limitations of probe testing, only dc parameters are tested. This must be done with pulse width of less than 300 μs , duty cycle less than 2%.