

# SHARP

## LQ058T5GG01

Color TFT-LCD Module  
(Car Navigation)

### Features

- 15 cm [5.8"] display size
- Wide temperature range  
(Topr: -30°C to +85°C Tstg: -30°C to +85°C)
- Wide screen (16 : 9)
- Wide viewing angle  
(Horizontal: 130° Vertical: 105°)
- Compact structure by ACF-COG technology

### Specifications


Parameter		Unit
Display size	15 [5.8]	cm ["]
No. of pixels	93 600	pixel
Dot format (H x V)	400 x RGB x 234	dot
Dot pitch (H x V)	0.106 x 0.307	mm
Active area (H x V)	127.2 x 71.8	mm
Input signal system	NTSC/PAL *1	-
Input video signal	TFT Specific Analog RGB	-
Viewing direction	6:00	-

Parameter		Unit
Backlight type	1CCFT	-
Brightness	400	cd/m <sup>2</sup>
Power consumption	6.3	W
Outline dimensions (W x H x D)	145.0 x 89.2 x 7.7	mm
Weight	140	g
Operating temperature	-30 to +85	°C
Storage temperature	-30 to +85	°C

\*1...MBK-PAL system is adopted as PAL. LCD panel has 234 scanning lines, and displays a picture of 273 virtual scanning lines.  
(Video-signals are deleted for certain intervals.)

### Outline Dimensions

unit : mm



In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device. Specifications are subject to change without notice for improvement.