


KT10L07

OUTLINE DIMENSIONS




RATINGS


Absolute Maximum Ratings				
Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-40 ~ 125	
Junction Temperature	Tj		125	
Maximum Off-State Voltage	V _{DRM}		58	V
Surge On-State Current	I _{TSM}	10/1000 μs, Non-repetitive	100	A
		10/200 μs, Non-repetitive	150	
		8/20 μs, Non-repetitive	250	

Electrical Characteristics (Tl=25)				
Item	Symbol	Conditions	Ratings	Unit
Breakover Voltage	V _{BO}	Pulse measurement (Peak hold)	Min 65	V
Off-State Current	I _{DRM}	V _D = V _{DRM}	Max 10	μ A
Holding Current	I _H	Pulse measurement	Min 100	mA
On-State Voltage	V _T	I _T = 2A	TYP 1.15	V
Junction Capacitance	C _j	f = 1kHz OSC = 1V, V _D = 50V	Max 180	pF
Clamping Voltage	V _{CL}	dv/dt = 100V/ μ s	Max 80	V


KT10L07 On-State Voltage - On-State Current




KT10L07 Breakover Voltage - Junction Temperature



KT10L07 Holding Current - Junction Temperature



KT10L07 Junction Capacitance



KT10L07 Junction Capacitance

