

## VCO Product Specification

**Model:** VCO-108 **Rev:** C **Date:** 8/19/2002  
**Customer:** VARI-L COMPANY  
**Operating Temperature Range:** ( 0 ° to 70 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	800		1600	MHz	X	
Tuning Voltage:						
800 MHz	0	1.2		Vdc	X	
1600 MHz		17.6	20	Vdc	X	
Tuning Sensitivity:						
800 MHz	46.5	62	77.5	MHz/V	X	
1000 MHz	41	55	69	MHz/V	X	
1200 MHz	58	77	96	MHz/V	X	
1400 MHz	37.5	50	62.5	MHz/V	X	
1600 MHz	14	21	28	MHz/V	X	
Output Power -	10	13	16	dBm	X	
Output Phase Noise:						
10 kHz		-92	-81	dBc/Hz	X	
100 kHz		-115	-104	dBc/Hz	X	
1000 kHz		-135	-124	dBc/Hz	X	
Power Supply -	14.75	15	15.25	Volts	X	
Supply Current -		15	18	mA	X	
Harmonic Suppression:						
2nd Harmonic		-12	-10	dBc	X	
3rd Harmonic		-12	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.75-15.25 V		4	20	MHz p-p		
Frequency Pulling - 20 dB RL		20	27	MHz p-p		
Output Impedance -		50		$\Omega$		
Modulation:						
Bandwidth	12000	15000		kHz		
Input Impedance		0.05		k $\Omega$		

### Package Information

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	P

### Comments

X Indicates parameter to be tested 100% in production

Page 1 of 1