



DUAL CHANNEL ADSL LINE DRIVER

DATA BRIEF

1 MAIN FEATURES

- Low Noise: 3.5nV/Hz
- Class AB architecture
- High Peak Output Current: 600 mA
- Low Single Tone Distortion: -60dBc
- Thermal And Overload Protection
- BCD-SOI technology
- HTSSOP28 Package
- -40 TO +85°C Operating Rang

2 DESCRIPTION

The STLC60243 is a dual channel ADSL Line Driver featuring a high slew rate and a large bandwidth optimized for XDSL applications (ADSL and ADSL+). The device is available in a HTSSOP 28 pin package (4x9 mm) with an exposed lead

Figure 1. Package



Table 1. Order Codes

Part Number	Package
STLC60243	HTSSOP28

frame. The STLC60243 is designed optimizing bandwidth, distortion performances and power consumption. It can be used in Copperwing12 chipset ADSL application.

Table 2. Revision History

Date	Revision	Description of Changes
September 2004	1	First Issue

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com