



STPS0540Z / STPS0560Z

SCHOTTKY RECTIFIER

PRELIMINARY DATASHEET

MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	0.5 A
V_{RRM}	40 / 60 V
$V_F (max)$	0.40 / 0.50 V


FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- EXTREMELY FAST SWITCHING

DESCRIPTION

Single Schottky rectifier suited for switch mode power supplies and high frequency DC to DC converters.

Packades in SOD-123, these device are intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications. Due to the small size of the package these devices fit GSM and PCMCIA requirements.



SOD-123

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value		Unit
				STPS		
				0540Z	0560Z	
V _{RRM}	Repetitive peak reverse voltage			40	60	V
I _{F(RMS)}	RMS forward current			2		A
I _{F(AV)}	Average forward current δ=0.5	STPS0540Z STPS0560Z	Ta = 60°C Ta = 40°C	0.5		A
I _{FSM}	Surge non repetitive forward current		tp=10ms sinusoidal	5.5		A
dV/dt	Critical rate of rise of reverse voltage			10000		V/μs
T _{stg}	Storage temperature range			- 65 to + 150		°C
T _j	Maximum operating junction temperature *			150		°C
TL	Maximum temperature for soldering during 10s			260		°C

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink

STPS0540Z / STPS0560Z

THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to ambient (*)	340	°C/W

(*) Mounted on epoxy board with recommended Pad Layout.

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Value				Unit
				STPS0540Z		STPS0560Z		
				typ.	max.	typ.	max.	
I _R *	Reverse leakage current	T _j =25°C	V _R = V _{RRM}		40		50	μA
		T =100°C		1.5	5	1	4	mA
V _F **	Forward voltage drop	T _j =25°C	I _F = 0.5 A		0.50		0.53	V
		T _j =100°C		0.35	0.40	0.44	0.50	
		T _j =25°C	I _F = 1 A		0.55		0.66	
		T _j =100°C		0.45	0.51	0.58	0.65	

Pulse test : * $t_p = 5\text{ ms}$, $\delta < 2\%$

** $t_p = 380\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation :

$$\text{STPS0540Z: } P = 0.29 \times I_{F(AV)} + 0.22 \times I_F^2 (RMS)$$

$$\text{STPS0560Z: } P = 0.35 \times I_{F(AV)} + 0.3 \times I_F^2 (RMS)$$

PACKAGE MECHANICAL DATA
SOD-123

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A		1.45		0.057
A1	0	0.1	0	0.004
A2	0.85	1.35	0.033	0.053
b	0.55 Typ.		0.022 Typ.	
c	0.15 Typ.		0.039 Typ.	
D	2.55	2.85	0.1	0.112
E	1.4	1.7	0.055	0.067
G	0.25		0.01	
H	3.55	3.95	0.14	0.156

MARKING

Type	Marking	Package	Weight	Base qty	Delivery mode
STPS0540Z	Z54	SOD-123	0.01g.	3000	Tape & reel
STPS0560Z	Z56	SOD-123	0.01g.	3000	Tape & Reel

Epoxy meets UL94, V0.
 Band indicates cathode.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
 Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>

