

**STRF0000****CONTACTLESS READER CHIP SET**

DATA BRIEFING**FUNCTION: ANALOG FRONT END FOR CONTACTLESS SMARTCARD READER****■ GENERAL DESCRIPTION**

- This is an analog front end dedicated to contactless Smartcards.
- This interface complies with ISO 14443-2 Type B: powering, data transfer from reader to card with amplitude modulation, data transfer from card to reader.

■ MAIN FEATURES

- Supply voltage: from 5 V to 15 V
- Modulation: 10% ASK
- Data transfer to card: up to 424 KBit/second
- Data transfer to reader: up to 424 KBit/second
- DC subcarrier output level
- Quartz oscillator 13.56 MHz \pm 100 ppm

FUNCTION: DECODER AND FRAME FORMATING FOR CONTACTLESS SMARTCARD READERS**■ GENERAL DESCRIPTION**

- This is an FPGA dedicated to contactless Smartcard. This interface complies with ISO 14443-3 Type B

■ MAIN FEATURES

- Supply voltage: 3.3 V
- Programmable data transfer from reader to card
- 106 KBit/second, 212 KBit/second and 424 KBit/second
- Programmable data transfer from card to reader
- 106 KBit/second, 212 KBit/second and 424 KBit/second
- 8 bit parallel interface for MCU
- Programmable SCI interface from 4800 to 115 KBit/second

Figure 1 Contactless Reader Architecture

