

# LM339x2 OCTAL DIFFERENTIAL COMPARATOR


SLCS122A – APRIL 1996 – REVISED SEPTEMBER 1996

- Single Supply or Dual Supplies
- Wide Range of Supply Voltage  
2 V to 36 V
- Low Supply-Current Drain Independent of Supply Voltage . . . 1.6 mA Typ
- Low Input Bias Current . . . 25 nA Typ
- Low Input Offset Current . . . 5 nA Typ
- Low Input Offset Voltage . . . 2 mV Typ
- Common-Mode Input Voltage Range Includes Ground
- Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage . . .  $\pm 36$  V
- Low Output Saturation Voltage
- Output Compatible With TTL, MOS, and CMOS

## description


The LM339x2 consists of eight independent voltage comparators that are designed to operate from a single power supply over a wide range of voltages. Operation from dual supplies is also possible when the difference between the two supplies is 2 V to 36 V and  $V_{CC}$  is at least 1.5 V more positive than the input common-mode voltage. Current drain is independent of the supply voltage. The outputs can be connected to other open-collector outputs to achieve wire-AND relationships.

DB PACKAGE  
(TOP VIEW)



NC – No internal connection

## symbol (each comparator)



AVAILABLE OPTION

$T_A$	$V_{IOmax}$ AT 25°C	PACKAGE
		SMALL OUTLINE (DB)†
0°C to 70°C	5 mV	LM339x2DBLE

† The DB package is only available left-end taped and reeled.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**


POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1996, Texas Instruments Incorporated

LM339x2  
OCTAL DIFFERENTIAL COMPARATOR

SLCS122A – APRIL 1996 – REVISED SEPTEMBER 1996

schematic (each comparator)



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

Supply voltage, $V_{CC}$ (see Note 1)	36 V
Differential input voltage, $V_{ID}$ (see Note 2)	$\pm 36$ V
Input voltage range, $V_I$ (any input)	$-0.3$ V to 36 V
Output voltage, $V_O$	36 V
Output current, $I_O$	20 mA
Duration of output short circuit to ground (see Note 3)	unlimited
Continuous total dissipation	See Dissipation Rating Table
Operating free-air temperature range, $T_A$	$0^{\circ}\text{C}$ to $70^{\circ}\text{C}$
Storage temperature range	$-60^{\circ}\text{C}$ to $150^{\circ}\text{C}$

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these conditions beyond those indicated is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. All voltage values, except differential voltages, are with respect to network GND.  
2. Differential voltages are at IN+ with respect to IN-.  
3. Short circuits from outputs to  $V_{CC}$  can cause excessive heating and eventual destruction.

DISSIPATION RATING TABLE

PACKAGE	$T_A \leq 25^{\circ}\text{C}$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25^{\circ}\text{C}$	$T_A = 70^{\circ}\text{C}$ POWER RATING
DB	1024 mW	8.2 mW/ $^{\circ}\text{C}$	655 mW

electrical characteristics at specified free-air temperature,  $V_{CC} = 5$  V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	$T_A^{\dagger}$	MIN	TYP <sup>‡</sup>	MAX	UNIT
$V_{IO}$ Input offset voltage	$V_{CC} = 5$ V to 30 V, $V_{IC} = V_{ICRmin}$ , $V_O = 1.4$ V	$25^{\circ}\text{C}$		2	5	mV
		Full range			9	
$I_{IO}$ Input offset current	$V_O = 1.4$ V	$25^{\circ}\text{C}$		5	50	nA
		Full range			150	

# LM339x2 OCTAL DIFFERENTIAL COMPARATOR

SLCS122A – APRIL 1996 – REVISED SEPTEMBER 1996

$I_{IB}$ Input bias current	$V_O = 1.4\text{ V}$	25°C	–25 –250	nA
		Full range	–400	
$V_{ICR}$ Common-mode input voltage range		25°C	0 to $V_{CC}-1.5$	V
		Full range	0 to $V_{CC}-2$	
$A_{VD}$ Large-signal differential voltage amplification	$V_{CC} = 15\text{ V}$ , $V_O = 1.4\text{ V to } 11.4\text{ V}$ , $R_L \geq 15\text{ k}\Omega\text{ to } V_{CC}$	25°C	50 200	V/mV
$V_{OL}$ Low-level output voltage	$V_{ID} = -1\text{ V}$ , $I_{OL} = 4\text{ mA}$	25°C	150 400	mV
		Full range	700	
$I_{OH}$ High-level output current	$V_{ID} = 1\text{ V}$	$V_{OH} = 5\text{ V}$	25°C 0.1 50	nA
		$V_{OH} = 30\text{ V}$	Full range 1	$\mu\text{A}$
$I_{OL}$ Low-level output current	$V_{ID} = -1\text{ V}$ , $V_{OL} = 1.5\text{ V}$	25°C	6 16	mA
$I_{CC}$ Supply current (eight comparators)	$V_O = 2.5\text{ V}$ , No load	25°C	1.6 4	mA
	$V_{CC} = 30\text{ V}$ , No load	25°C	2 5	mA

† Full range for LM339 is 0°C to 70°C. All characteristics are measured with zero common-mode input voltage unless otherwise specified.

‡ All typical values are measured at  $T_A = 25^\circ\text{C}$ .

## switching characteristics, $V_{CC} = 5\text{ V}$ , $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Response time	$R_L$ connected to 5 V through 5.1 k $\Omega$ , $C_L = 15\text{ pF}$ §, See Note 4	100-mV input step with 5-mV overdrive		1.3		ns
		TTL 1-level input step		0.3		

§  $C_L$  includes probe and jig capacitance.

NOTE 4: The response time specified is the interval between the input step function and the instant when the output crosses 1.4 V.



## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.