

UTC U584/57 LINEAR INTEGRATED CIRCUIT


8A,5A,3A LOW DROPOUT POSITIVE REGULATORS ADJUSTABLE AND FIXED

DESCRIPTION

The UTC U584/585/587 voltage regulators are monolithic integrated circuits, designed for use in applications requiring a well regulated positive output voltage with +5V input. The output voltage can be adjustable from 3.8 V down to 1.3V.


FEATURES

- *Low dropout performance.
- *Adjustable output down to 1.3V.
- *Line regulation typically below 0.1%.
- *Load regulation typically below 0.1%.
- *Output current can be up to 8 A for UTC U584.
- *Three-terminal adjustable or fixed 3.3V.



1: ADJ/GND 2: OUTPUT 3: INPUT

BLOCK DIAGRAM



UTC U584/5/7 LINEAR INTEGRATED CIRCUIT

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNIT
Input Voltage	V _{IN}	7	V
Power Dissipation	P _D	Internally Limited	W
Operating Junction Temperature Range	T _J	0 to 125	°C
Storage Temperature	T _{STG}	-65 to 150	°C
Lead Temperature (Soldering 10 Sec.)	T _{LEAD}	300	°C

ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reference Voltage U584 U585 U587	1.3V ≤ (V _{IN} -V _{OUT}) ≤ 3V, 10mA ≤ I _{OUT} ≤ 8A 1.3V ≤ (V _{IN} -V _{OUT}) ≤ 3V, 10mA ≤ I _{OUT} ≤ 5A , 1.3V ≤ (V _{IN} -V _{OUT}) ≤ 3V, 10mA ≤ I _{OUT} ≤ 3A	* 1.225	1.25	1.275	V
Output Voltage U584-3.3 U585-3.3 U587-3.3	4.75V ≤ V _{IN} ≤ 6.5V, 10mA ≤ I _{OUT} ≤ 8A 4.75V ≤ V _{IN} ≤ 7V, 10mA ≤ I _{OUT} ≤ 5A 4.75V ≤ V _{IN} ≤ 7V, 10mA ≤ I _{OUT} ≤ 3A	3.234	3.300	3.366	V
Line Regulation (Note 1.2) U584/5/7 U584/5/7-3.3	2.75V ≤ V _{IN} ≤ 7V, I _{OUT} = 10mA 4.75V ≤ V _{IN} ≤ 7V, I _{OUT} = 0mA		0.1	0.2	%
Load Regulation (Note 1, 2, 3) U584/5/7 U584/5/7-3.3	V _{IN} -V _{OUT} = 2.5V, T _J = 25°C, 10mA ≤ I _{OUT} ≤ I _{FULLLOAD} V _{IN} = 5V, T _J = 25°C, 0mA ≤ I _{OUT} ≤ I _{FULLLOAD}	*	0.2	1.0	%
Dropout Voltage	ΔV _{REF} = 1%, I _{OUT} = I _{FULLLOAD} T _J ≥ 25°C T _J ≤ 25°C		1.2 1.2	1.3 1.35	V V
Current Limit (Note 3) U584 U585 U587	V _{IN} -V _{OUT} = 3 V V _{IN} -V _{OUT} = 3 V V _{IN} -V _{OUT} = 3 V	* 8.0 5.0 3.0	8.5 5.5 3.6		A
Adjust Pin Current			55	120	μA
Adjust Pin Current Change (Note 3)	1.5V ≤ (V _{IN} -V _{OUT}) ≤ 3 V, 10mA ≤ I _{OUT} ≤ I _{FULLLOAD}		0.2	5	mA
Minimum Load Current	1.5V ≤ (V _{IN} -V _{OUT}) ≤ 3V	*	2	10	mA
Quiescent Circuit Current	V _{IN} ≤ 5V	*	8	13	mA
Ripple Rejection	f = 120Hz, C _{OUT} = 25μA Tant, V _{IN} -V _{OUT} = 2.5V, I _{OUT} = I _{FULLLOAD}	60	72		dB
Temperature Stability			0.5		%
Long-Term Stability	T _A = 25°C, 1000Hrs		0.03	1.0	%
RMS Output Noise (% of V _{OUT})	T _A = 125°C, 10Hz ≤ f ≤ 10kHz		0.03		%
Thermal Resistance Junction to Case U584 U587				1.6 3.0	°C /W
Thermal Resistance Junction to A _{MBIENT} , θ _{JA} U585				60	°C /W
Thermal Resistance Junction to T _{AB} , θ _{JT} U585				2.7	°C /W

UTC U584/5/7 LINEAR INTEGRATED CIRCUIT


The * denotes specifications which apply over the specified operating temperature range.

Note 1: Load and line regulation are measured at a constant junction temperature by low duty cycle pulse testing.

Note 2: Line and load regulation are guaranteed up to the maximum power dissipation (15W for the UTC U584, 10W for the UTC U585). Power dissipation is determined by input / output differential and the output current. Guaranteed maximum output power will not be available over the full input-output voltage range.

Note 3: IFULLLOAD is defined as the maximum value of output load current as a function of input-to-output voltage. Output current can be different for different input-to-output voltage.


APPLICATION CIRCUIT (ADJUSTABLE)



REQUIRED FOR STABILITY










$$V_{OUT} = V_{REF} \cdot (1 + R_2/R_1) + I_{ADJ} \cdot R_2$$

APPLICATION CIRCUIT (3.3V)




UTC U584/57 LINEAR INTEGRATED CIRCUIT

TYPICAL PERFORMANCE CHARACTERISTICS




UTC U584/5/7 LINEAR INTEGRATED CIRCUIT


Minimum Operating Current



Temperature Stability




Adjust Pin Current




U584

Ripple Rejection




U584

Ripple Rejection vs Current




U584

Maximum Power Dissipation*




U585

Ripple Rejection




U585

Ripple Rejection vs Current



U585


Maximum Power Dissipation



UTC U584/5/7 LINEAR INTEGRATED CIRCUIT


U587

Ripple Rejection




U587

Ripple Rejection vs Current




U587

Maximum Power Dissipation




U584

Load Transient Response




U585

Load Transient Response




U587

Load Transient Response




U584

Line Transient Response



U585

Line Transient Response



U587

Line Transient Response

