

## VXB2 Microprocessor Crystals

<b>Package Options</b>	<b>B2</b> = 4.4 mm tall surface mount
<b>Frequency Range</b>	3.5 MHz to 75.00 MHz
<b>Standard Frequencies</b>	See <a href="#">Standard Frequency Table</a>
<b>Mode</b>	<b>1</b> = Fundamental (3.5 to 30 MHz) <b>3</b> = 3 <sup>rd</sup> Overtone (24.1 to 75 MHz)
<b>Stability Options</b>	<b>A</b> = $\pm 100$ PPM -20°C to +70°C <b>B</b> = $\pm 50$ PPM -20°C to +70°C <b>C</b> = $\pm 100$ PPM -40°C to +85°C <b>D</b> = $\pm 50$ PPM -40°C to +85°C <b>F</b> = $\pm 30$ PPM -20°C to +70°C
<b>Load Capacitance</b>	<b>0</b> = Series Resonant <b>1</b> = 16 pF <b>2</b> = 20 pF <b>3</b> = 32 pF <b>4</b> = 18 pF <b>5</b> = 10 pF <b>6</b> = 30 pF
<b>STD Calibration Tolerance</b>	$\pm 25$ PPM at +25°C Tolerances to $\pm 10$ PPM are available
<b>Equivalent Series Resistance</b>	See <a href="#">ESR Table II</a>
<b>Shunt Capacitance</b>	7 pf Maximum
<b>Drive Level</b>	10 to 2,000 uW
<b>Crystal Aging</b>	<5 ppm/1 <sup>st</sup> year
<b>Standard Packaging</b>	Tape & Reel (500 pc minimum)
<b>Typical P/N</b>	<b>VXB2-3A2-56M448</b>



**B2** = 5.0 mm tall package  
**3** = 3<sup>rd</sup> Overtone  
**A** =  $\pm 100$  PPM -20°C to +70°C  
**2** = 20 pF load

[Generate your own part number!](#)

We welcome your custom requests and will issue a custom part number for items that are not listed.

