VICOR CONFIDENTIAL
THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED, USED, OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT PERMISSION OF VICOR CORP.

REV.	DESCRIPTION		DATE	APPROVED
#1	RELEASED FOR DEVELOPMENT	DPK	11/19/97	SWN
#2	ADDED ±.010 TOL TO DIM	DPK	12/8/97	SWN
#3	.49 WAS .490: REMOVED P/N STAMPING	DPK	8/24/98	SWN
#4	1.47 WAS 1.470	DPK	9/2/98	SWN
#5	.40 WAS .400: ADDED "O" TO .100 & .190	DPK	9/11/98	SWN
#6	ADDED NOTE 4, CRITICAL CHA."O"	AK	10/5/99	SWN





NOTES
1. MAKE FROM VICOR EXTRUSION P/N 16296.
2. REMOVE ALL BURRS AND SHARP EDGES.
3. FINISH. CLEAR CHROMATE.
4. "O" DENOTES CRITICAL CHARACTERISTICS FOR LOT INSPECTION.

DRAWN BY	DATE
D.P. KELLY	11/97

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES-TOLERANCES ARE:
FRACTIONS ±1/64 DECIMALS .XX= ±.01 .XXX= ±.005 ANGLES ±1°

THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING

VICOR

HTSNK, "C" X-FLOW, .4H
LOW FLOW, THRU HOLE

SIZE	FSCM NO.	DWG NO	REV
C	67131	18074	#6

SCALE 2=1 SHEET 1 OF 1