


Metal Film Resistors, Industrial, Flameproof



FEATURES

- Small physical size.
- Low cost.
- FP resistors have the ability to withstand overloads up to 100 times rated power without any trace of flame.
- Exceptional frequency characteristics.
- Especially suited for circuitry where functions, environments and duty cycles demand power resistors.
- Electroplated tin-lead or Lead (Pb)-free solder finish leads.
- Tighter tolerances available on request
- Lead (Pb)-Free version is RoHS Compliant



RoHS*
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	HISTORICAL MODEL	POWER RATING			VOLTAGE RATING	RESISTANCE RANGE Ω	STANDARD TOLERANCE %	TEMPERATURE COEFFICIENT ppm/°C
		P _{25°C} W	P _{40°C} W	P _{70°C} W				
FP01/2	FP1/2	—	—	0.5	350	10R - 1M	1, 2, 5, 10	150
FP0001	FP1	—	—	1	500	10R - 1M	1, 2, 5, 10	150
FP0032	FP32	—	—	1	500	10R - 1M	1, 2, 5, 10	150
FP0002	FP2	3.5	3	2	500	9R - 1M5	1, 2, 5, 10	150
FP0042	FP42	—	—	2	500	10R - 1M5	1, 2, 5, 10	150
FP0003	FP3	4	4	3	500	9R - 1M	1, 2, 5, 10	150
FP0004	FP4	5.5	5	4	500	6R - 1M	1, 2, 5, 10	150
FP0005	FP5	6.5	6	5	600	7R - 1M	1, 2, 5, 10	150
FP0007	FP7	7.5	—	7	700	8R - 1M	1, 2, 5, 10	150
FP0010	FP10	—	10	—	700	8R - 1M	1, 2, 5, 10	150
FP0067	FP67	5	—	—	500	5R - 19K	1, 2, 5, 10	150
FP0069	FP69	3	—	2	500	2R6 - 1M5	1, 2, 5, 10	150

GLOBAL PART NUMBER INFORMATION


New Global Part Numbering: FP000251K1F9251B8 (preferred part numbering format)



Note: Some packaging codes are model specific

* Pb containing terminations are not RoHS compliant, exemptions may apply





DIMENSIONS



GLOBAL MODEL	DIMENSIONS in inches [millimeters]		
	A	B	D
FP01/2	0.360 ± 0.020 [9.14 ± 0.51]*	0.138 + 0.012 - 0.023 [3.51 + 0.31 - 0.58]	0.032 ± 0.002 [0.81 ± 0.05]
FP0001	0.560 ± 0.031 [14.22 ± 0.79]	0.190 + 0.007 - 0.015 [4.83 + 0.18 - 0.38]	0.032 ± 0.002 [0.81 ± 0.05]
FP0032	0.560 ± 0.031 [14.22 ± 0.79]	0.190 + 0.007 - 0.015 [4.83 + 0.18 - 0.38]	0.040 ± 0.002 [1.02 ± 0.05]
FP0002	0.687 ± 0.031 [17.45 ± 0.79]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0042	0.687 ± 0.031 [17.45 ± 0.79]	0.300 ± 0.020 [7.62 ± 0.51]	0.045 ± 0.002 [1.14 ± 0.05]
FP0003	0.900 ± 0.031 [22.86 ± 0.79]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0004	1.530 ± 0.035 [38.86 ± 0.89]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0005	1.710 ± 0.035 [43.43 ± 0.89]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0007	2.040 ± 0.035 [51.82 ± 0.89]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0010	2.040 ± 0.035 [51.82 ± 0.89]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0067	0.900 ± 0.031 [22.86 ± 0.79]	0.300 ± 0.020 [7.62 ± 0.51]	0.032 ± 0.002 [0.81 ± 0.05]
FP0069	0.516 ± 0.021 [13.11 ± 0.53]	0.225 ± 0.012 [5.72 ± 0.31]	0.032 ± 0.002 [0.81 ± 0.05]

*Clean lead to clean lead dimensions on FP1/2 are .437" [11.10mm] maximum.

DERATING



SPEC CODES

GLOBAL MODEL	SPEC	RESISTOR TOLERANCE	DESCRIPTION
FP01/2	5605	1, 2, 5, 10	Color banded, 4 or 5 bands depending on tolerance
	5610	1, 2, 5, 10	Alphanumeric marking
FP0001	6200	2, 5, 10	Color banded, 4 bands
	6201	1	Color banded, 5 bands
FP0032	6601	1	Color banded, 5 bands
	6602	2, 5, 10	Color banded, 4 bands
FP0002	9251	1, 2, 5, 10	Alphanumeric marking
FP0042	9201	1	Color banded, 5 bands
	9202	2, 5, 10	Color banded, 4 bands
FP0003	9300	1, 2, 5, 10	Alphanumeric marking
	9320	2, 5, 10	Color banded, 4 bands
	9330	1	Color banded, 5 bands
FP0004	9400	1, 2, 5, 10	Alphanumeric marking
FP0005	9500	1, 2, 5, 10	Alphanumeric marking
FP0007	9700	1, 2, 5, 10	Alphanumeric marking
FP0010	9800	1, 2, 5, 10	Alphanumeric marking
FP0067	9550	1, 2, 5, 10	Alphanumeric marking
FP0069	7500	1, 2, 5, 10	Alphanumeric marking
	7536	2, 5, 10	Color banded, 4 bands
	7538	1	Color banded, 5 bands

MARKING


— DALE

— Value


— Tolerance

— Model and case size
(Date and source code included on some styles.)

± 1% tolerance parts are marked with 5 color bands.
5 band, EIA Standard RS196.



± 2%, ± 5% and ± 10% tolerance parts are marked with 4 color bands. 4 band commercial, EIA Standard.





PERFORMANCE												
TEST	MAXIMUM $\Delta R \pm \%$											
	FP01/2	FP0001	FP0032	FP0002	FP0042	FP0003	FP0004	FP0005	FP0007	FP0010	FP0067	FP0069
Short Time Overload	0.5	1.0	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Low Temperature Operation	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.25	0.25
Moisture Resistance	1.0	1.5	1.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Shock	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Vibration	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Temperature Cycle	1.0	1.0	1.0	0.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.5
Load Life (1000 Hours Rated Cond.)	1.0	2.0	2.0	5.0	2.0	5.0	5.0	5.0	5.0	5.0	5.0	3.0
Terminal Strength	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Dielectric Withstanding Voltage	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.25	0.25
Effect Solder Heat	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.25	0.25



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.