


# 200 V - 1,000 V Single Phase Bridge

3.0 A Forward Current

70 ns - 3000 ns Recovery Time

**1202D - 1210D**  
**1202FD - 1210FD**  
**1202UFD - 1210UFD**




## ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage	Average Rectified Current @TC (Io)		Reverse Current @ Vrwm (Ir)		Forward Voltage (Vf)		1 Cycle Surge Current tp=8.3ms (Ifsm)	Repetitive Surge Current (Ifrm)	Reverse Recovery Time (1) (Trr)	Thermal Impd. $\theta_{J-C}$
	(Vrwm)	55°C	100°C	25°C	100°C	25°C		25°C	25°C	25°C	
	Volts	Amps	Amps	µA	µA	Volts	Amps	Amps	Amps	ns	°C/W
1202D	200	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1206D	600	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1210D	1000	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1202FD	200	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1206FD	600	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1210FD	1000	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1202UFD	200	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21
1206UFD	600	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21
1210UFD	1000	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21

(1)Trr Testing: If=0.5A, Ir=1.0A, Irr=0.25A \*Op. Temp.= -55°C to +150°C Stg. Temp.= -55°C to +150°C

10



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



**VOLTAGE MULTIPLIERS INC.**  
 8711 W. Roosevelt Ave.  
 Visalia, CA 93291

TEL 559-651-1402  
 FAX 559-651-0740  
[www.voltagemultipliers.com](http://www.voltagemultipliers.com)

# 1202D - 1210D • 1202FD - 1210FD • 1202UFD - 1210UFD

