

### High Speed 5 Volt Byte Alterable Nonvolatile Memory Array

#### FEATURES

- High Speed, High Density Memory Module
  - 150ns, 120ns, 90ns and 70ns Access Times Available
  - 1 Megabit Memory in 1 square inch.
- Flexible Multiplane Architecture
  - Four Separate Chip Selects
  - 32 Separate I/Os
    - User Configurable I/Os—x8, x16, or x32
    - User Configurable Page Size—64 Double-words, 128 Words, or 256 Bytes
  - Concurrent Read/Write Operations
    - Able to Continue Reading During a Nonvolatile Write Cycle.
- 5 Volt Byte or Page Alterable
  - No Erase Before Write
- Software Data Protection
- Early End of Write Polling
  - DATA Polling
  - Toggle Bit Polling

#### High Reliability


- Endurance: 100,000 Cycles
- Data Retention: 100 Years

#### DESCRIPTION

The XM28C010P is a high speed, high density CMOS byte alterable nonvolatile memory array constructed on a co-fired ceramic substrate using Xicor's High Speed 32K x 8 components in 32-pad leadless chip carriers. The Substrate is a 66-pin ceramic pin grid array.

The module is configured with four separate chip enable and write enable inputs and 32 separate I/Os. This, along with the small footprint, provides the end user with a large degree of flexibility in board layout and memory configuration. In addition, with the large number of pins and the growth path being implemented, the module will be able to grow to 16 megabits.


#### FUNCTIONAL DIAGRAM




6491 ILL F01

# XM28C010P


## PIN CONFIGURATION



## PACKAGE INFORMATION



## ORDERING INFORMATION



Devices sold by Xicor, Inc. are covered by the warranty and patent indemnification provisions appearing in its Terms of Sale only. Xicor, Inc. makes no warranty, express, statutory, implied, or by description regarding the information set forth herein or regarding the freedom of the described devices from patent infringement. Xicor, Inc. makes no warranty of merchantability or fitness for any purpose. Xicor, Inc. reserves the right to discontinue production and change specifications and prices at any time and without notice.

## U.S. PATENTS

Xicor products are covered by one or more of the following U.S. Patents: 4,263,664; 4,274,012; 4,300,212; 4,314,265; 4,326,134; 4,393,481; 4,404,475; 4,450,402; 4,486,769; 4,488,060; 4,520,461; 4,533,846; 4,599,706; 4,617,652; 4,668,932; 4,752,912; 4,829,482; 4,874,967; 4,883,976. Foreign patents and additional patents pending.

In situations where semiconductor component failure may endanger life, system designers using this product should design the system with appropriate error detection and correction, redundancy and back-up features to prevent such an occurrence.

Xicor's products are not authorized for use in critical components in life support devices or systems

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.