

Features

- ☐ Dynamic random access memory 262144 x 1 bit manufactured using a CMOS technology
- ☐ RAS access times 70 ns, 80 ns
- ☐ TTL-compatible
- ☐ Three-state output
- ☐ 256 refresh cycles
4 ms refresh cycle time
- ☐ FAST PAGE MODE
- ☐ Operating modes: Read, Write, Read - Write, $\overline{\text{RAS}}$ only Refresh, Hidden Refresh with address transfer
- ☐ Power Supply Voltage 5 V
- ☐ Packages PDIP16 (300 mil) SOJ20/26 (300 mil)
- ☐ Operating temperature range 0 to 70 °C
- ☐ Quality assessment according to CECC 90000, CECC 90100 and CECC 90112

Description

Addressing

The UD61256 is a dynamic Write-Read-memory with random access. FPM facilitates faster data operation with predefined row address. Via 9 address inputs the 18 address bits are transmitted into the internal address memories in a time-multiplex operation. The falling $\overline{\text{RAS}}$ -edge takes over the row address. During $\overline{\text{RAS}}$ Low, the column address together with the $\overline{\text{CAS}}$ signal are taken over. The selection of one or more memory circuits can be made by activation of the $\overline{\text{RAS}}$ input.

Read-Write-Control

The choice between Read or Write cycle is made at the $\overline{\text{W}}$ input. HIGH at the $\overline{\text{W}}$ input causes a Read cycle, meanwhile LOW leads to a Write cycle.

Both $\overline{\text{CAS}}$ -controlled and $\overline{\text{W}}$ -controlled Write cycles are possible with activated $\overline{\text{RAS}}$ signal.

Data Output Control

The usual state of the data output is the High-Z state. Whenever $\overline{\text{CAS}}$ is inactive (HIGH), Q will float (High-Z). Thus, $\overline{\text{CAS}}$ functions as data output control.



After access time, in case of a Read cycle, the output is activated, and it contains the logic „0“ or „1“.

Q is then valid until $\overline{\text{CAS}}$ returns into to inactive state (HIGH).

The memory cycle being a Read, Read-Write or a Write cycle ($\overline{\text{W}}$ -controlled), Q changes from High-Z state to the active state („0“ or „1“). After the access time the contents of the selected cell is available, except for the Write cycle.

The output remains active until $\overline{\text{CAS}}$ becomes inactive, irrespective of $\overline{\text{RAS}}$ becoming inactive or not. The memory cycle being a Write cycle ($\overline{\text{CAS}}$ -controlled), the data output keeps its High-Z state throughout the whole cycle. This configuration makes Q fully controllable by the user merely through the timing of $\overline{\text{W}}$. The output storing the data, they remain valid from the end of access time until the start of another cycle.

Pin Configuration



Pin Description

Signal Name	Signal Description
A0 - A8	Address Inputs
D	Data Input
$\overline{\text{W}}$	Read, Write Control
$\overline{\text{RAS}}$	Row Address Strobe
UCC	Power Supply Voltage
USS	Ground
$\overline{\text{CAS}}$	Column Address Strobe
Q	Data Output
n.c.	no connected

Characteristics

All voltages are referenced to $V_{SS} = 0$ V (ground).

All characteristics are valid in the power supply voltage range and operating temperature range indicated below.

Absolute Maximum Ratings	Symbol	Min.	Max.	Unit
Power Supply Voltage	V_{CC}	-0.5	7.0	V
Input Voltage ¹⁾	V_I	-1.0	7.0	V
Output Voltage ¹⁾	V_O	-1.0	7.0	V
Output Current	I_O	-50	50	mA
Power Dissipation	P_D		1	W
Operating Temperature	T_a	0	70	°C
Storage Temperature	T_{stg}	-55	125	°C

Remarks: see page 7

Recommended Operating Conditions	Symbol	Min.	Max.	Unit
Power Supply Voltage	V_{CC}	4.5	5.5	V
Input Low Voltage ¹⁾	V_{IL}	-1.0	0.8	V
Input High Voltage	V_{IH}	2.4	5.5	V

Remark: see page 7

Capacitances	Conditions	Symbol	Min.	Max.	Unit
Input Capacitance A0 to A8, D	$V_{CC} = 5.0$ V $V_I = V_{SS}$ $f = 1$ MHz $T_a = 25$ °C	C_{I1}		6	pF
Input Capacitance RAS, CAS, W		C_{I2}		7	pF
Output Capacitance		C_O		7	pF

All pins not under test must be connected with ground by capacitors.

Static Characteristics	Conditions	Symbol	Min.		Max.		Unit
			07	08	07	08	
Power Supply Current (average value of $\overline{\text{RAS}}\text{-}\overline{\text{CAS}}$ cycles) ²⁾	$t_{cW} = t_{cWmin}$ $t_{cR} = t_{cRmin}$	I_{CC1}			70	60	mA
Refresh Current ²⁾ (average value of $\overline{\text{RAS}}$ cycles)	$t_{cW} = t_{cWmin}$ $t_{cR} = t_{cRmin}$ $\overline{\text{CAS}} = V_{IH}$	I_{CC2}			70	60	mA
FPM Current ²⁾ (average value of FPM cycles)	$t_{cPG} = t_{cPGmin}$ $\overline{\text{RAS}} = V_{IL}$	I_{CC3}			50	40	mA
Stand-by Current (TTL Level)	$\overline{\text{RAS}} = \overline{\text{CAS}}$ $= V_{IH}$	I_{CC4}			2	2	mA
Stand-by Current (CMOS Level)	$\overline{\text{RAS}} = \overline{\text{CAS}}$ $= V_{CC} - 0.2 \text{ V}$	I_{CC5}			1	1	mA
Output High Voltage	$I_{OH} = -5 \text{ mA}$	V_{OH}	2.4	2.4			V
Output Low Voltage	$I_{OL} = 4.2 \text{ mA}$	V_{OL}			0.4	0.4	V
Input Leakage Current at any input, all other pins = 0 V	$V_I = 0 \text{ V to } 5.5 \text{ V}$	I_I	-10	-10	10	10	μA
Output Leakage Current Q = High-Z	$V_O = 0 \text{ V to } 5.5 \text{ V}$ $\overline{\text{RAS}} = \overline{\text{CAS}}$ $= V_{IH}$	I_O	-10	-10	10	10	μA

Remarks: see page 7

Dynamic Characteristics ³⁾	Symbol		Min.		Max.		Unit
	Alt.	IEC	07	08	07	08	
<input type="checkbox"/> ALL CYCLES							
Transition Time (Rise and Fall) ⁴⁾	t _T	t _t	3	3	50	50	ns
RAS Precharge Time	t _{RP}	t _w (RASH)	50	60			ns
CAS Precharge Time	t _{CP}	t _w (CASH)	10	10			ns
Row Address Set-up Time	t _{ASR}	t _{su} (RA-RAS)	0	0			ns
Column Address Set-up Time	t _{ASC}	t _{su} (CA-CAS)	0	0			ns
Row Address Hold Time	t _{RAH}	t _h (RAS-RA)	10	10			ns
Column Address Hold Time	t _{CAH}	t _h (CAS-CA)	15	15			ns
Column Address Hold Time ref. to $\overline{\text{RAS}}$	t _{AR}	t _h (RAS-CA)	55	60			ns
Output Buffer Turn-off Delay ⁵⁾	t _{OFF}	t _v (CAS)	0	0	20	20	ns
$\overline{\text{CAS}}$ to $\overline{\text{RAS}}$ Precharge Time	t _{CRP}	t _{CASH-RASL}	5	5			ns
RAS to Column Address $\overline{\text{Delay}}$ Time ⁶⁾	t _{RAD}	t _{RAS-CA}	15	15	35	40	ns
Column Address to $\overline{\text{RAS}}$ Lead Time	t _{RAL}	t _{CA-RASH}	35	40			ns
$\overline{\text{CAS}}$ to Output in Low-Z	t _{CLZ}	t _{CASL-QX}	0	0			ns
Refresh Period	t _{REF}	t _{rf}			4	4	ms
<input type="checkbox"/> READ							
Random Read Cycle Time ¹²⁾	t _{RC}	t _{cR}	130	150			ns
Access Time from $\overline{\text{RAS}}$ ^{7), 8)}	t _{RAC}	t _a (RAS)			70	80	ns
Access Time from Column Address ^{7), 8)}	t _{AA}	t _a (CA)			35	40	ns
Access Time from $\overline{\text{CAS}}$ ^{7), 8)}	t _{CAC}	t _a (CAS)			20	20	ns
$\overline{\text{RAS}}$ Pulse Width	t _{RAS}	t _w (RASL)	70	80	10000	10000	ns
CAS Pulse Width	t _{CAS}	t _w (CASL)	20	20	10000	10000	ns
Read Command Set-up Time	t _{RCS}	t _{su} (R-CAS)	0	0			ns
Read Command Hold Time ref. to $\overline{\text{RAS}}$ ⁹⁾	t _{RRH}	t _h (RAS-R)	0	0			ns
Read Command Hold Time ⁹⁾	t _{RCH}	t _h (CAS-R)	0	0			ns
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ Delay Time ⁶⁾	t _{RCD}	t _{RASL-CASL}	20	20	50	60	ns
CAS Hold Time	t _{CSH}	t _{RASL-CASH}	70	80			ns
RAS Hold Time	t _{RSH}	t _{CASL-RASH}	20	20			ns
<input type="checkbox"/> WRITE							
Random Write Cycle Time ¹²⁾	t _{RC}	t _{cW}	130	150			ns
$\overline{\text{RAS}}$ Pulse Width	t _{RAS}	t _w (RASL)	70	80	10000	10000	ns
$\overline{\text{CAS}}$ Pulse Width	t _{CAS}	t _w (CASL)	20	20	10000	10000	ns
Write Command Pulse Width	t _{WP}	t _w (W)	15	15			ns

Remarks: see page 7


Dynamic Characteristics ³⁾	Symbol		Min.		Max.		Unit
	Alt.	IEC	07	08	07	08	
<input type="checkbox"/> WRITE (continuation)							
Write Command Set-up Time ¹⁰⁾	t_{WCS}	$t_{su(W-CAS)}$	0	0			ns
Data Set-up Time ref. to \overline{CAS} ¹¹⁾	t_{DS}	$t_{su(D-CAS)}$	0	0			ns
Data Set-up Time ref. to \overline{W} ¹¹⁾	t_{DS}	$t_{su(D-W)}$	0	0			ns
Write Command Hold Time	t_{WCH}	$t_h(CAS-W)$	15	15			ns
Write Command to RAS Lead Time	t_{RWL}	$t_h(W-RAS)$	20	20			ns
Write Command to CAS Lead Time	t_{CWL}	$t_h(W-CAS)$	20	20			ns
Data Hold Time ref. to RAS	t_{DHR}	$t_h(RAS-D)$	55	60			ns
Data Hold Time ref. to CAS	t_{DH}	$t_h(CAS-D)$	15	15			ns
Data Hold Time ref. to \overline{W}	t_{DH}	$t_h(W-D)$	15	15			ns
\overline{RAS} to \overline{CAS} Delay Time ⁶⁾	t_{RCD}	$t_{RASL-CASL}$	20	20	50	60	ns
\overline{CAS} Hold Time	t_{CSH}	$t_{RASL-CASH}$	70	80			ns
\overline{RAS} Hold Time	t_{RSH}	$t_{CASL-RASH}$	20	20			ns
<input type="checkbox"/> READ-WRITE							
Read-Write Cycle Time ¹²⁾	t_{RWC}	t_{cRW}	155	175			ns
\overline{RAS} Pulse Width	t_{RAS}	$t_{w(RASL)RW}$	95	105	10000	10000	ns
\overline{CAS} Pulse Width	t_{CAS}	$t_{w(CASL)RW}$	45	45	10000	10000	ns
\overline{CAS} Hold Time	t_{CSH}	$t_{(RASL-CASH)RW}$	95	105			ns
\overline{RAS} to \overline{WRITE} Delay Time ¹⁰⁾	t_{RWD}	t_{RAS-W}	70	80			ns
\overline{CAS} to \overline{WRITE} Delay Time ¹⁰⁾	t_{CWD}	t_{CAS-W}	20	20			ns
Column to \overline{WRITE} Delay Time ¹⁰⁾	t_{AWD}	$t_{(CA-W)RW}$	35	40			ns
<input type="checkbox"/> FPM							
Fast Page Mode Cycle Time ¹²⁾	t_{PC}	t_{cPG}	50	50			ns
RAS Pulse Width	t_{RASP}	$t_{w(RASL)}$	70	80	100000	100000	ns
Access Time from \overline{CAS} Precharge	t_{CPA}	$t_a(CASH)$	35	40			ns
<input type="checkbox"/> HIDDEN-REFRESH							
\overline{CAS} Hold Time (\overline{CAS} before \overline{RAS} Cycle)	t_{CHR}	$t_{RASL-CASH}$	15	15			ns

Remarks: see page 7


Remarks:

- 1) The Input Low Voltage must not drop below -0.3 V for more than 40 ns.
- 2) The current is inversely proportional to the cycle time; the max. current is measured in the shortest cycle time.
- 3) For test conditions see test configuration for functional test and timing diagrams.
- 4) V_{IHmin} and V_{ILmax} are reference levels for time measurement of the input signals; transition times are measured between V_{IH} and V_{IL} .
- 5) $t_{V(CAS)}$ and $t_{V(RAS)}$ define the time at which the data output goes to High-Z; this time is not related to any level.
- 6) $t_{RASL-CASLmax}$ and t_{RAS-CA} are given as reference points only; they do not represent restrictive conditions.
- 7) The access time is determined by the three times $t_{a(RAS)}$, $t_{a(CAS)}$ and $t_{a(CA)}$:
 - if $t_{RASL-CASL} < t_{RASL-CASLmax}$ and $t_{RAS-CA} < t_{RAS-CAmax}$ $t_{a(RAS)}$ is valid,
 - if $t_{RASL-CASL} > t_{RASL-CASLmax}$ and $t_{su(CA-CAS)} < (t_{a(CA)max} - t_{a(CAS)max})$ $t_{a(CA)}$ is valid,
 - if $t_{RASL-CASL} > t_{RASL-CASLmax}$ and $t_{su(CA-CAS)} > (t_{a(CA)max} - t_{a(CAS)max})$ $t_{a(CAS)}$ is valid.
- 8) Measured with a load equivalent to 2 TTL loads.
- 9) In a READ cycle either $t_{h(RAS-R)}$ or $t_{h(CAS-R)}$ must be kept.
- 10) $t_{su(W-CAS)}$, t_{RAS-W} , t_{CAS-W} and $t_{su(A)}$ do not represent restrictive parameters:
 - if $t_{su(W-CAS)} \geq t_{su(W-CAS)min}$, the cycle is a WRITE cycle (CAS-controlled) and the data output remains in High-Z throughout the whole \overline{CAS} cycle,
 - if $t_{CAS-W} > t_{CAS-Wmin}$, $t_{RAS-W} > t_{RAS-Wmin}$ and $t_{su(CA-W)RW} > t_{su(CA-W)RWmin}$, the cycle is a READ-WRITE cycle and the content of the cell is available at the data output,
 - if none of these conditions is satisfied, the condition of the data output (at access time) is indeterminate, since a WRITE cycle (\overline{W} -controlled) is carried out.
- 11) These parameters refer to \overline{CAS} in the WRITE cycle (\overline{CAS} -controlled) and to \overline{W} during WRITE (\overline{W} -controlled) or to \overline{W} in the READ-WRITE cycle, resp.
- 12) The values of t_{cmin} are used for indication of the particular cycle time in which full function is guaranteed in the temperature range from 0 to 70 °C. Values below the one shown above may cause permanent damage to the component.

Test Configuration for Functional Check





IC Code Numbers




The date of manufacture is given by the 4 last digits of the mark, the 2 first digits indicating the year, and the last 2 digits the calendar week.


Read

Write ($\overline{\text{CAS}}$ -controlled)


Read-Write



FPM Read



HIDDEN-Refresh with address transfer





Zentrum Mikroelektronik Dresden

Memory Products 1998

256K x 1 DRAM UD61256

LIFE SUPPORT POLICY

ZMD products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the ZMD product could create a situation where personal injury or death may occur.

Components used in life-support devices or systems must be expressly authorized by ZMD for such purpose.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

Zentrum Mikroelektronik Dresden GmbH

Grenzstraße 28 • D-01109 Dresden • P. O. B. 80 01 34 • D-01101 Dresden • Germany

Phone: +49 351 88 22-3 06 • Fax: +49 351 88 22-3 37 • Email: sales@zmd.de

Internet Web Site: <http://www.zmd.de>